

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE EAST BOUNDARY (GUIDE MERIDIAN),

A PORTION OF THE SUBDIVISIONAL LINES,

AND THE

SURVEY OF THE SUBDIVISION OF SECTIONS 13, 14, 23 AND 24,

IN

TOWNSHIP 17 SOUTH, RANGE 6 WEST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

John F. Carroll
Cadastral Surveyor

Under Special Instructions dated *August 23, 1999*, approved *August 23, 1999*, which provided for the surveys included under Group Number *907*, and assignment instructions dated *May 22, 2000*.

Survey commenced *August 15, 2000*

Survey completed *November 8, 2000*

INDEX DIAGRAM

Township 17 South, Range 6 West

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15 10	14 6	13 2
19	20	21	22 8	23 4	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 13.....Page 11
 Subdivision of Section 14.....Page 12
 Subdivision of Section 23.....Page 14
 Subdivision of Section 24.....Page 16

TOWNSHIP 17 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The following field notes describe the dependent resurvey of a portion of the east boundary (Guide Meridian), a portion of the subdivisional lines, and the survey of the subdivision of sections 13, 14, 23 and 24, in Township 17 South, Range 6 West, Salt Lake Meridian, Utah.

History of Earlier Surveys

Surveyed by			Ret. or Resurveyed by	
SOUTH BOUNDARY				
All	J. Bausman	1871		
All			E. Bird, etal	1941-45
EAST BOUNDARY (GUIDE MERIDIAN)				
All	J. Bausman	1869		
All			J.C. Thoma	1920
WEST BOUNDARY				
All	J. Bausman	1871		
NORTH BOUNDARY				
All	J. Bausman	1871		
All			J. Gorlinski	1874
Portion			G.L. Kratz	1982-83
SUBDIVISION				
All	J. Bausman	1869		

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instruction, 1973, and the Special Instructions for Group No. 907, Utah, dated August 23, 1999.

Preliminary to the resurvey and survey, a diligent search was made for any evidence of the original field note record. Coordinates by the use of Global Positioning System (GPS) were determined for each found and proportioned corner in this survey. Geodetic bearings and distances were calculated by inverting between these points. Cadastral Measurement Management (CMM) was utilized throughout the survey.

The geographic position of the 1/4 section corner of sections 24 and 25, was determined by a tie to National Geodetic Survey triangulation station "DELTA NORTHWEST BASE", by use of GPS, using relative positioning techniques, is as follows:

TOWNSHIP 17 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Latitude: 39° 19' 00.978" N. Longitude: 112° 28' 24.480" W.
 N.A.D. 1983(1994) Elev. 4679 ft.

This corner will also function as a B.L.M. Control Station.

The geographic position of National Geodetic Survey triangulation station "DELTA NORTHWEST BASE" is as follows:

Latitude 39° 18' 14.55589" N. Longitude 112° 28' 77995 W.
 N.A.D. 1983 (1994) Elev. 4663 ft.

The mean magnetic declination as projected from the U.S. Geological Survey Magnetic Declination Map of 1990, is 14 1/2° E.

Dependent Resurvey of a Portion of the East Boundary, (Guide Meridian)
 T. 17 S., R. 6 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by J. Bausman in 1869,
 and the Resurvey Executed by J.C. Thoma in 1920

Beginning at the corner of sections 13 and 24 only, on the east boundary of the township, monumented with an iron post, 2 inches diameter, firmly set, projecting 13 inches above ground, with brass cap marked as described in the field notes of the 1920 resurvey record, with a steel fence post alongside.

From this corner, an iron pipe, 2 inches diameter, firmly set, projecting 10 inches above ground, bears N. 8° E., 0.046 chains distance, set utilizing incorrect procedures and is not utilized during the course of this resurvey.

Corner is located on a flat in grass and rabbit brush.

N. 0°28.9' E., on the east boundary of section 13.

6.465

The corner of sections 18 and 19 only, T. 17 S., R. 5 W., monumented with an iron post, 2 inches diameter, firmly set, projecting 13 inches above ground, with brass cap marked as described in the field notes of the 1920 resurvey record, at the intersection of fences bearing N and E.

Corner is located on a flat in grass and rabbit brush.

40.135

Point for the 1/4 section corner of section 13 only, T. 17 S., R. 6 W., at proportionate distance.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 17 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 inches diameter, 25 inches in the ground, with magnet at base, with aluminum cap marked:

T 17 S
R 6 W | R 5 W
1/4 |
S 13 |
2000

Note: The 1920 iron post was disturbed during a chaining operation and was recovered in the immediate area. The 1920 iron post is buried alongside the aluminum post.

Corner is located on a flat in rabbit brush and at the intersection of fences bearing N and W.

46.938

Point for the 1/4 section corner of section 18 only, T. 17 S., R. 5 W., at proportionate distance, there is no remaining evidence of the 1920 iron post.

Set an aluminum post, 30 inches long, 2 inches diameter, 25 inches in the ground, with magnet at base, with aluminum cap marked:

T 17 S
R 6 W | R 5 W
1/4 |
S 18 |
2000

Corner is located on a flat, 30 ft. E of an abandoned canal, bears N and S.

80.270

The corner of sections 12 and 13 only, on the east boundary of the township, monumented with an iron post, 2 inches diameter, firmly set, projecting 4 inches above ground, with brass cap marked as described in the field notes of the 1920 resurvey record, with a steel fence post along the south side of the iron post.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 17 S., R. 6 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by J. Bausman in 1871

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 24 and 25, monumented with an unrecorded concrete pier block, 4X6X1 inches above ground, with brass cap mkd: REESTABLISHED BY T17S R6W S24 _____ 1/4 S25 1982 MILLARD COUNTY SURVEY MARKER, utilized by Sunrise Engineering during an unrecorded survey in section 24, and is accepted as the best available evidence of the original corner position.

Corner is located on a flat in grass and rabbit brush.

S. 89°24.1' W., between sections 24 and 25.

20.043

The W 1/16 section corner of sections 24 and 25, monumented with an unrecorded iron post, 1 1/2 inches diameter, in poor condition, loosely set, projecting 6 inches above ground, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, with aluminum cap marked:

W 1/16	S 24

	S 25
	2000

Bury iron post inside aluminum post.

Corner is located on a flat in rabbit brush.

S. 89°24.1' W., beginning new measurement.

20.043

The corner of sections 23, 24, 25 and 26, monumented with an unrecorded concrete pier block, 5X5X1 in. below ground, firmly set, with brass cap marked REESTABLISHED BY T17S R6W S23 S24 S26 S25 1982 MILLARD COUNTY SURVEY MARKER, and is accepted as the best available evidence of the original corner position. Not remonumented.

From this corner, an unrecorded rebar, 3/4 in. diameter, firmly set, projecting 3 inches above ground, bears S. 85°05.3' E., 0.048 chains distance, set using incorrect procedures, and is not utilized during the course of this resurvey.

Corner is located at the intersection of fences bearing. N and W.

N. 0°51.9' E., between sections 23 and 24.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

<i>CHAINS</i>	
40.350	<p>The 1/4 section corner of sections 23 and 24, monumented with an unrecorded concrete pier block, 5X5X2 inches above ground, firmly set, with a brass cap marked REESTABLISHED BY T17S R6W S23 S24 1/4 1982 MILLARD COUNTY SURVEY MARKER, and a steel fence post on the south side of the concrete pier block, and is accepted as the best available evidence of the original corner position. Not remonumented.</p> <p>Corner is located on a flat in rabbit brush.</p> <hr/> <p>N. 0°52.0' E., beginning new measurement.</p>
20.175	<p>The N 1/16 section corner of sections 23 and 24, monumented with an unrecorded iron pipe, 2 inches diameter, firmly set, projecting 4 inches above ground and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 inches long, 2 1/2 inches diam. 24 inches in the ground with magnet at base, with aluminum cap marked:</p> <div style="text-align: center;"> <p>N 1/16 S 23 S 24 2000</p> </div> <p>Bury iron pipe along west side of aluminum post.</p> <p>Corner is located at intersection of fences bearing N and E.</p> <hr/> <p>N. 0°51.3' E., beginning new measurement.</p>
20.185	<p>The corner of sections 13, 14, 23 and 24, monumented with an unrecorded concrete pier block, 5X5X1 in. above ground, firmly set, with brass cap marked REESTABLISHED BY T17SR6W S14 S13 S23 S24 1982 MILLARD COUNTY SURVEY MARKER, with an unrecorded iron pipe, 2 inches diameter, laying loose on the south side of the concrete pier block. The concrete pier block is accepted as the best available evidence of the original corner position. Not remonumented.</p> <p>Corner is located on a flat in scattered grass, and at the intersection of fences bearing E, S and W.</p> <hr/> <p>From the 1/4 section corner of sections 13 and 24, monumented with an unrecorded concrete pier block, 5X5X2 inches above ground, with brass cap marked REESTABLISHED BY T17S R6W S13 S24 1982 MILLARD COUNTY SURVEY MARKER, and is accepted as the best available evidence of the original corner position. Not remonumented.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

<i>CHAINS</i>	
	<p>Corner is located at intersection of fences bearing S and W.</p> <p>S. 89°43.7' W., between sections 13 and 24.</p>
20.061	Point for the W 1/16 section corner of sections 13 and 24. Not monumented.
40.122	The corner of sections 13, 14, 23 and 24.
	<hr/> <p>N. 0°37.8' E., between sections 13 and 14.</p>
40.301	<p>The 1/4 section corner of sections 13 and 14, monumented with an unrecorded aluminum post, 2 inches diameter, firmly set, projecting 8 inches above ground, with aluminum cap marked MILLARD COUNTY 1984 R6W 14 1/4 13 T17S RLS1623 SURVEY, with an unrecorded iron pipe, 2 inches diameter, firmly set, projecting 5 inches above ground on the north side of the aluminum post. The aluminum post is accepted as the best available evidence of the original corner position. Not remonumented.</p> <p>Corner is located on a flat in grass and rabbit brush, and at intersection of fences bearing N and E.</p> <hr/> <p>N. 0°37.3' E., beginning new measurement.</p>
40.236	<p>The corner of sections 11, 12, 13 and 14, monumented with an unrecorded aluminum post, 2 inches diameter, firmly set, projecting 11 inches above ground, with an aluminum cap marked MILLARD COUNTY 1984 R6W 11 12 13 14 T17S SLM PLS 1623, with an unrecorded iron post, 2 inches diameter, laying near the aluminum post. The aluminum post is accepted as the best available evidence of the original corner position. Not remonumented.</p> <p>Corner is located in sand dunes and grass, and in a fence, bears N. 1° E. and S. 1° W.</p> <hr/> <p>From the corner of sections 12 and 13 only, on the east boundary of the township, hereinbefore described.</p> <p>S. 89°58.7' W., between sections 12 and 13.</p>
40.003	<p>The 1/4 section corner of sections 12 and 13, monumented with a unrecorded iron pipe, badly rusted, firmly set, 12 inches below ground, and is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, with aluminum cap marked:</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
	<p style="text-align: center;">T 17 S R 6 W S 12 1/4 ————— S 13 2000</p> <p>Bury badly rusted iron pipe on south side of aluminum post.</p> <p>Drive a steel fence post alongside aluminum post.</p> <p>Corner is located in sand dunes, grass and scattered rabbit brush.</p> <hr/> <p>S. 89°54.5' W., beginning new measurement.</p>
39.992	<p>The corner of sections 11, 12, 13 and 14.</p> <hr/>
	<p>From the corner of sections 23, 24, 25 and 26.</p> <p>N. 89°54.5' W., between sections 23 and 26.</p>
19.966	<p>Point for the E 1/16 section corner of sections 23 and 26.</p> <p>Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 23 inches in the ground, with magnet at base, with aluminum cap marked:</p> <p style="text-align: center;">E 1/16 S 23 S 26 2000</p> <p>Drive a steel fence post on the west side of the aluminum post.</p> <p>Corner is located on a flat in rabbit brush, and 1.55 chs. N. 12° E. of the west end of a fence, bears N. 87° E.</p>
39.932	<p>Point for the 1/4 section corner of sections 23 and 26, at proportionate distance, there is no remaining evidence of the original corner</p> <p>Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with magnet at base, with aluminum cap marked:</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T 17 S R 6 W
S 23
1/4 —————
S 26
2000

Corner is located on a flat in scattered rabbit brush.

79.864

The corner of sections 22, 23, 26 and 27, monumented with an unrecorded railroad spike, 14 inches long, badly rusted and in poor condition, firmly set, projecting 2 inches above ground, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diam. 19 inches in the ground, with magnet at base, with aluminum cap marked:

T17S R6W
S 22 | S 23

S 27 | S 26
2000

Bury railroad spike inside aluminum post.

Drive a steel fence post along west side of aluminum post.

Corner is located on a flat in grass and 1.70 chs. north of a fence, bears E and W.

N. 1°00.2' E., between sections 22 and 23.

39.228

Point for the 1/4 section corner of sections 22 and 23, at proportionate distance, there is no remaining evidence of the original corner

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with magnet at base, with aluminum cap marked:

T 17 S R 6 W
1/4
S 22 | S 23
2000

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
	<p>Drive a steel fence post alongside the aluminum post.</p>
	<p>Corner is located on a flat and 1.90 chs. North of a fence, bears E and W.</p>
58.842	<p>Point for the N 1/16 section corner of sections 22 and 23.</p>
	<p>Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with magnet at base, with aluminum cap marked:</p>
	<p style="text-align: center;"> N 1/16 S 22 S 23 2000 </p>
	<p>Drive a steel fence post on the east side of the aluminum post.</p>
	<p>Corner is located on a flat in scattered desert brush.</p>
78.456	<p>The corner of sections 14, 15, 22 and 23, monumented with an unrecorded aluminum post, 2 1/2 inches diameter, firmly set, projecting 12 inches above ground, with an aluminum cap marked</p>
	<p>MILLARD COUNTY 1984 SLM 15 14 22 23 R6W T17S RLS1623 SURVEY, and is accepted as the best available evidence of the original corner position. Not remonumented.</p>
	<p>Corner is located on a flat in rabbit brush.</p>
	<hr/> <p>From the corner of sections 13, 14, 23 and 24.</p>
	<p>S. 88°28.4' W., between sections 14 and 23.</p>
39.849	<p>The 1/4 section corner of sections 14 and 23, monumented with an unrecorded concrete pier block,</p>
	<p>5X7X4 inches above ground, firmly set, with a brass cap marked REESTABLISHED BY T17SR6W S14 1/4 S23 1983 SURVEY MARKER MILLARD COUNTY, with an iron pipe, 2 inches diameter, on the south side of concrete pier block, with a steel fence post alongside. The concrete pier block is accepted as the best available evidence of the original corner position. Not remonumented.</p>
	<p>Corner is located on a flat in rabbit brush.</p>
	<hr/> <p>S. 88°28.1' W., beginning new measurement.</p>
19.933	<p>Point for the W 1/16 section corner of sections 14 and 23. Not monumented.</p>
39.866	<p>The corner of sections 14, 15, 22 and 23.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
	N. 0°13.8' E., between sections 14 and 15.
20.939	Point for the S 1/16 section corner of sections 14 and 15. Not monumented.
41.878	The 1/4 section corner of sections 14 and 15, monumented with an unrecorded iron pipe, 2 inches diameter, in poor condition, 6 inches below ground, and is accepted as the best available evidence of the original corner position.
	At the corner point
	Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, with aluminum cap marked:
	<p>T 17 S R 6 W 1/4 S 15 S 14 2000</p>
	Bury iron pipe remains west of aluminum post.
	Corner is located on a flat in rabbit brush.
40.402	N. 0°58.2' E., beginning new measurement.
	The corner of sections 10, 11, 14 and 15, monumented with an unrecorded concrete pier block, 5X5X2 inches above ground, firmly set, with brass cap marked REESTABLISHED BY T17S R6W S10 S11 S15 S14 1982 MILLARD COUNTY SURVEY MARKER, with an iron pipe, 2 inches diameter, firmly set on the northwest corner of the concrete pier block. The concrete pier block is accepted as the best available evidence of the original corner position. Not remonumented.
	Corner is located on a flat in rabbit brush.
	From the 1/4 section corner of sections 11 and 14, monumented with an unrecorded aluminum post, 2 1/4 inches diameter, firmly set, projecting 15 inches above ground, with aluminum cap marked MILLARD COUNTY 1984 R6W 1/4 11 T17S RLS1623 SURVEY, with an unrecorded iron pipe, 2 inches diameter, laying near the concrete pier block. The concrete pier block is accepted as the best available evidence of the original corner position. Not remonumented.
	Corner is located on a flat in rabbit brush.
	S. 89°43.1' W., between sections 11 and 14.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

19.931

The W 1/16 section corner of sections 11 and 14, monumented with an unrecorded galvanized iron pipe, firmly set, projecting 11 inches above ground, and is accepted as a careful and faithful determination of the position of the corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, with aluminum cap marked:

S 11
 W 1/16 —————
 S 14
 2000

Bury galvanized iron pipe inside aluminum post.

Corner is located on a slight gradual slope on the west bank of a ditch channel, and 40 lks. W of the bottom of the channel, drains S. 30° W.

—————
S. 89°43.1' W., beginning new measurement.

19.931

The corner of sections 10, 11, 14 and 15.

Survey of the Subdivision of Section 13
 T. 17 S., R. 6 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 13 and 24.

N. 0°32.4' E., on the N-S center line of section 13.

40.200

The center 1/4 section corner of section 13, monumented with an unrecorded iron pipe, 2 inches diameter, in poor condition, projecting 3 inches above ground, and is accepted as a careful and faithful determination of the position of the corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with magnet at base, with aluminum cap marked:

T 17 S R 6 W
 C 1/4 S 13
 2000

SURVEY OF THE SUBDIVISION OF SECTION 13,
T. 17 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

<i>CHAINS</i>	
	<p>Bury iron pipe on south side of aluminum post.</p> <p>Corner is located in sand dunes and 1 lk. south of a fence, bears E and W.</p> <hr/> <p>N. 0°32.4' E., beginning new measurement.</p>
40.210	<p>The 1/4 section corner of sections 12 and 13.</p> <hr/> <p>From the 1/4 section corner of section 13 only, on the east boundary of the township, hereinbefore described.</p> <p>S. 89°52.5' W., on the E-W center line of section 13.</p>
40.050	<p>The center 1/4 section corner of section 13.</p> <hr/> <p>S. 89°52.5' W., beginning new measurement.</p>
40.053	<p>The 1/4 section corner of sections 13 and 14.</p> <hr/> <p style="text-align: center;">Survey of the Subdivision of Section 14 T. 17 S., R. 6 W., Salt Lake Meridian, Utah</p> <hr/>
20.544	<p>From the 1/4 section corner of sections 14 and 23.</p> <p>N. 0°36.7' E., on the N-S center line of section 14.</p> <p>Point for the center S 1/16 section corner of section 14.</p> <p>Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, with aluminum cap marked:</p> <div style="text-align: center;"> <p>C</p> <p>S 1/16 S 14</p> <p>C</p> <p>2000</p> </div> <p>From this point, an unrecorded iron pipe, 1 1/2 inches diameter, firmly set, projecting 11 inches above ground, bears N. 39°58.1' W., 0.211 chains distance, set using incorrect procedures, and is not utilized during the course of this resurvey.</p>

SURVEY OF THE SUBDIVISION OF SECTION 14,
T. 17 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

<i>CHAINS</i>	
41.088	<p>Corner is located on a flat in rabbit brush.</p> <p>The center 1/4 section corner of section 14, at intersection with the E-W center line of section 14.</p> <p>Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, with aluminum cap marked:</p> <p style="text-align: center;">T 17 S R 6 W C 1/4 S 14 2000</p> <p>From this point, an unrecorded iron pipe, badly rusted and in poor condition, 2 1/2 inches diameter, loosely set, 2 inches below ground, bears S. 45°44.1' W., 0.163 chains distance, set using incorrect procedures and is not utilized during the course of this resurvey.</p> <p>Corner is located on a flat in rabbit brush, and 1.40 chs. W of a fence, bears S. 20° E. and N. 20° W.</p>
81.406	<p>The 1/4 section corner of sections 11 and 14.</p> <hr/> <p>From the 1/4 section corner of sections 13 and 14.</p> <p>S. 89°36.4' W., on the E-W center line of section 14.</p>
39.837	<p>The center 1/4 section corner of section 14.</p>
59.896	<p>Point for the center W 1/16 section corner of section 14.</p> <p>Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with magnet at base, with aluminum cap marked:</p> <p style="text-align: center;">W 1/16 C ——— C S 14 2000</p> <p>From this point, an unrecorded iron pipe, in poor condition, diam. indeterminate, bears S. 58°02.0' W., 0.115 chains distance, set using incorrect procedures, and is not utilized during the course of this resurvey.</p> <p>Corner is located on a flat in rabbit brush.</p>
79.955	<p>The 1/4 section corner of sections 14 and 15.</p> <hr/>

SURVEY OF THE SUBDIVISION OF SECTION 14,
T. 17 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

<i>CHAINS</i>	
20.741	<p>From the point for the W 1/16 section corner of sections 14 and 23.</p> <p>N. 0°25.1' E., on the N-S center line of the SW 1/4 of section 14.</p> <p>Point for the SW 1/16 section corner of section 14, at intersection with the E-W center line of the SW 1/4 of section 14.</p> <p>Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, with aluminum cap marked:</p> <p style="text-align: center;">SW 1/16 S 14 2000</p> <p>Corner is located on a flat in rabbit brush.</p>
41.482	<p>The center W 1/16 section corner of section 14.</p> <hr/> <p>From the center S 1/16 section corner of section 14.</p> <p>S. 89°02.4' W., on the E-W centerline of the SW 1/4 of section 14.</p>
19.995	<p>The SW 1/16 section corner of section 14.</p>
39.990	<p>Point for the S 1/16 section corner of sections 14 and 15.</p> <hr/> <p>From the center W 1/16 section corner of section 14.</p> <p>N. 0°47.4' E., on the N-S center line of the NW 1/4 of section 14.</p>
40.361	<p>The W 1/16 section corner of sections 11 and 14.</p> <hr/> <p style="text-align: center;">Survey of the Subdivision of Section 23 T. 17 S., R. 6 W., Salt Lake Meridian, Utah</p> <hr/> <p>From the 1/4 section corner of sections 23 and 26.</p> <p>N. 0°56.3' E., on the N-S center line of section 23.</p>
39.789	<p>Point for the center 1/4 section corner of section 23, at intersection with the E-W center line of section 23.</p>

SURVEY OF THE SUBDIVISION OF SECTION 23,
T. 17 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

<i>CHAINS</i>	
	<p>Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, with aluminum cap marked:</p> <p style="text-align: center;">T 17 S R 6 W C 1/4 S 23 2000</p> <p>Corner is located on a flat in rabbit brush, and 1.10 chs. North of a fence, bears E and W.</p>
59.686	<p>Point for the center N 1/16 section corner of section 23.</p> <p>Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, with aluminum cap marked:</p> <p style="text-align: center;"> C N 1/16 S 23 C 2000</p> <p>Drive a steel fence post on the east side of the aluminum post.</p> <p>Corner is located on a flat in rabbit brush, 1.50 chs. N of a dry canal channel, bears E and W, and 2.70 chs. E of same dry canal channel, bears N and S.</p>
79.583	<p>The 1/4 section corner of sections 14 and 23.</p> <hr/> <p>From the 1/4 section corner of sections 23 and 24.</p> <p>S. 89°17.2' W., on the E-W center line of section 23.</p>
19.943	<p>Point for the center E 1/16 section corner of section 23.</p> <p>Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, with aluminum cap marked:</p> <p style="text-align: center;"> E 1/16 C C S 23 2000</p> <p>Drive a steel fence post on the southwest side of the aluminum post.</p> <p>Corner is located on a flat in rabbit brush, 1.10 chs. N of a fence, bears E and W.</p>
39.886	<p>The center 1/4 section corner of section 23.</p>

SURVEY OF THE SUBDIVISION OF SECTION 23,
T. 17 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

<i>CHAINS</i>	
79.781	The 1/4 section corner of sections 22 and 23.
	From the E 1/16 section corner of sections 23 and 26.
	N. 0°54.1' E., on the N-S center line of the SE 1/4 of section 23.
40.072	The center E 1/16 section corner of section 23.
	From the center N 1/16 section corner of section 23.
	S. 88°52.5' W., on the E-W center line of the NW 1/4 of section 23.
39.879	The N 1/16 section corner of sections 22 and 23.
	Survey of the Subdivision of Section 24 T. 17 S., R. 6 W., Salt Lake Meridian, Utah
	From the 1/4 section corner of sections 24 and 25.
	N. 0°54.7' E., on the N-S center line of section 24.
20.125	The center S 1/16 section corner of section 24, monumented with an unrecorded concrete cylinder, 10 inches diameter, with a rebar, 1/2 in. diameter, projecting 1 in. above concrete, with a steel fence post alongside, and is accepted as a careful and faithful determination of the position of the corner . Not remonumented.
	Corner is located 50 lks. South of a curve on a paved road, 18 ft. wide, concave to the northwest.
	N. 0°53.5' E., beginning new measurement.
20.125	The center 1/4 section corner of section 24, monumented with an unrecorded iron pipe, 2 inches diameter, firmly set in concrete, projecting 6 inches above concrete and is accepted as a careful and faithful determination of the position of the corner Not remonumented.
	Corner is located at intersection of fences bearing N, S, and E, and W.
	N. 0°54.5' E., beginning new measurement.

SURVEY OF THE SUBDIVISION OF SECTION 24,
T. 17 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

<i>CHAINS</i>	
20.091	<p>The center N 1/16 section corner of section 24, monumented with an unrecorded iron pipe, 1 1/2 inches diameter, firmly set, leaning northwesterly, projecting 11 inches above ground, and is accepted as a careful and faithful determination of the position of the corner Note: The measurement was taken to the southwest side of the iron pipe.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with magnet at base, with aluminum cap marked:</p> <div style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16 \mid S\ 24 \\ C \\ 2000 \end{array}$ </div> <p>Bury iron pipe inside aluminum post.</p> <p>Corner is located in a fence, bears N and S.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0°53.3' E., beginning new measurement.</p>
20.140	<p>The 1/4 section corner of section 13 and 24.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the 1/4 section corner of section 24 only, on the east boundary of the township, monumented with an iron post, 1 inch diameter, firmly set in concrete, projecting 12 inches above concrete, with brass cap marked as described in the field notes of the 1920 resurvey record.</p> <p>From this corner, an unrecorded iron pipe, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, bears N. 12° E., 0.046 chains distance, set using incorrect procedures, and is not utilized during the course of this resurvey.</p> <p>Corner is located on a flat in grass and scattered rabbit brush.</p> <p>S. 89°36.3' W., on the E-W center line of section 24.</p>
40.380	<p>The center 1/4 section corner of section 24.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 89°35.3' W., beginning new measurement.</p>
20.056	<p>The center W 1/16 section corner of section 24, monumented with an unrecorded iron pipe, 1 1/2 inches diameter, firmly set, projecting 4 inches above ground and is accepted as a careful and faithful determination of the position of the corner.</p>

SURVEY OF THE SUBDIVISION OF SECTION 24,
T. 17 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with magnet at base, with aluminum cap marked:

$$\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{ --- } \text{C} \\ \text{S } 24 \\ 2000 \end{array}$$

Bury iron pipe inside aluminum post.

Corner is located at intersection of fences bearing N and E.

S. 89°30.0' W., beginning new measurement.

20.048

The 1/4 section corner of section 23 and 24.

From the center W 1/16 section corner of section 24.

N. 0°53.8' E., on the N-S center line of the NW 1/4 of section 24.

20.120

The NW 1/16 section corner of section 24, monumented with a steel fence post, firmly set, projecting 48 inches above ground, at intersection of fences bearing S and W and is accepted as a careful and faithful determination of the position of the corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, with aluminum cap marked:

$$\begin{array}{c} \text{NW } 1/16 \text{ S } 24 \\ 2000 \end{array}$$

Note: The aluminum post is alongside the southwest side of the steel fence post.

N. 0°52.5' E., beginning new measurement.

20.155

Point for the W 1/16 section corner of sections 13 and 24.

TOWNSHIP 17 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

<i>CHAINS</i>	
	From the center N 1/16 section corner of section 24.
	S. 89°40.4' W., on the E-W center line of the NW 1/4 of section 24.
20.058	The NW 1/16 section corner of sections 23 and 24. <hr/>
	S. 89°39.7' W., beginning new measurement.
20.056	The N 1/16 section corner of sections 23 and 24. <hr/>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Brandon Sanchez	Survey Technician
Daniel W. Webb	Chief Cadastral Surveyor for Utah

CERTIFICATE OF SURVEY

I, John F. Carroll, Cadastral Surveyor, **HEREBY CERTIFY** upon honor that, in pursuance of Special Instructions bearing the date of the 23rd day of August, 1999, I have *dependently resurveyed a portion of the east boundary (Guide Meridian), a portion of the subdivisional lines and the survey of the subdivision of sections 13, 14, 23 and 24, in Township 17 South, Range 6 West,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instruction, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

3/19/01

Date

John F. Carroll

Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the east boundary (Guide Meridian), a portion of the subdivisional lines and the survey of the subdivision of sections 13, 14, 23 and 24, in Township 17 South, Range 6 West, Salt Lake Meridian, Utah,*

executed by *John F. Carroll, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

April 20, 2001

Date

Daniel W. Webb

Chief Cadastral Surveyor for Utah