

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

# FIELD NOTES

OF  
THE DEPENDENT RESURVEY OF

A PORTION OF THE NORTH BOUNDARY,  
A PORTION OF THE SUBDIVISIONAL LINES,

AND THE

SURVEY OF THE SUBDIVISION OF SECTIONS 4, 5, 8, AND 9,

IN

TOWNSHIP 14 SOUTH, RANGE 4 WEST

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*John F. Carroll*  
*Cadastral Surveyor*

Under special instructions dated *October 22, 1999*, approved *October 22, 1999*, which provided for the surveys included under Group Number *909*, and assignment instructions dated *October 22, 1999*.

Survey commenced *November 1, 1999*

Survey completed *May 25, 2000*

# INDEX DIAGRAM

Township 14 South , Range 4 West

6 9	3 7 5 8	2 4 4 6	3	2	1
7 8	8 7 6	9 4 6	10	11	12
18	17 5	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

The Subdivision of Section 4 .....Page 10

The Subdivision of Section 5 .....Page 11

The Subdivision of Section 8 .....Page 12

The Subdivision of Section 9 .....Page 13

## TOWNSHIP 14 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The following field notes describe the dependent resurvey of a portion of the north boundary, a portion of the subdivisional lines, and the survey of the subdivision of secs. 4, 5, 8 and 9, in Township 14 South, Range 4 West, Salt Lake Meridian, Utah.

## History of Earlier Surveys

Surveyed by		Ret. or Resurveyed by	
<b>SOUTH BOUNDARY</b>			
Portion	J. Gorlinski 1873		
All	Stewart and Clark 1913	Stewart and Clark	1913
<b>EAST BOUNDARY</b>			
All	S.M. Richardson 1884		
All		Stewart and Clark	1913
<b>WEST BOUNDARY</b>			
Portion	J. Gorlinski 1873		
All	Stewart and Clark 1913	Stewart and Clark	1913
<b>NORTH BOUNDARY</b>			
Portion	J. Gorlinski 1873		
Portion	J.W. Dougall 1911	J.W. Dougall	1911
Portion	Stewart and Clark 1913	Stewart and Clark	1913
Portion		B.S. Owens	1960
Portion		J.F. Carroll	1999
<b>SUBDIVISION</b>			
Portion	J. Gorlinski 1873		
All	Stewart and Clark 1913	Stewart and Clark	1913

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 909, Utah, dated October 22 1999.

The direction of the lines were determined by geodetic inverse bet. cors. Global Positioning System utilizing Real-time kinematic (RTK) was used throughout the survey. Cadastral Measurement Management (CMM) was utilized during the course of the survey.

## TOWNSHIP 14 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the cor. of secs. 9, 10, 15 and 16, T. 14 S., R. 4 W., as determined by a tie to the U.S. Coast and Geodetic Survey triangulation station "DYER", utilizing GPS, using RTK techniques, is as follows:

Latitude: 39°36' 41.903" N.      Longitude: 112°17'23.851" W.  
N.A.D. 1983(1994)

This cor. will now function as a BLM Control Station.

The geographic position of tri-station "DYER" is as follows:

Latitude: 39° 40' 21.25464" N.      Longitude: 112° 15' 40.12772" W.  
N.A.D. 1983(1994) Elevation 5112 FT.

The mean magnetic declination as projected from the U.S. Geological Survey Declination Map of 1990, is 13 1/2° E.

---

Dependent Resurvey of a Portion of the North Boundary,  
T. 14 S., R. 4 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by J. Gorlinski in 1873,  
and the Resurveys Executed by J.W. Dougall in 1911 and  
Stewart and Clark in 1913

---

Beginning at the 1/4 sec. cor. of secs. 4 and 33, Tps. 13 and 14 S., R. 4 W., monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the field notes of the 1911 resurvey record.

Drive a steel fence post alongside of the iron post.

N. 89° 49.1' W., bet. secs. 4 and 33.

39.708

The witness cor. to secs. 4, 5, 32 and 33, Tps. 13 and 14 S., R. 4 W., monumented with an iron post, 3 ins. diam., firmly set, projecting 17 ins. above ground, with brass cap mkd. as described in the field notes of the 1911 survey record. Note: No remaining evidence of the 1911 bearing tree was recovered.

Drive a steel fence post on the south side of the iron post.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 14 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
40.478	<p>Cor. is located in a fence, bearing N. 18° E. and S. 18° W.</p> <p>True point for the cor. of secs. 4, 5, 32 and 33, Tps. 13 and 14 S., R. 4 W., falls within the railroad right-of-way.</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by J. Gorlinski in 1873 and the Resurvey Executed by J.W. Dougall in 1911</p> <hr/> <p>N. 89°58.4' W., bet. secs. 5 and 32.</p>
2.050	<p>Point for the record position for the witness cor. for the cor. of secs. 4, 5, 32 and 33, Tps. 13 and 14 S., R. 4 W. Note: No remaining evidence of the witness cor. was recovered. Not monumented.</p>
39.692	<p>The 1/4 sec. cor. of secs. 5 and 32, Tps. 13 and 14 S., R. 4 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, 24 ins. below ground, with brass cap mkd. as described in the field notes of the 1911 resurvey record, from which the 1911 bearing trees:</p> <p style="padding-left: 40px;">A cedar, 14 ins. diam., bears N. 6° E., 107 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A cedar, 14 ins. diam., bears S. 54° W., 61 lks. dist., with the marks S5BT visible on partially healed blaze.</p>
39.975	<p>Cor. is located on the west side of a steel fence post and in a fence, bears E and W.</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by J.W. Dougall in 1911</p> <hr/> <p>N. 89°54.8' W., beginning new measurement.</p> <p>The cor. of secs. 5, 6, 31 and 32, Tps. 13 and 14 S., R. 4 W., monumented with an iron post, 3 ins. diam., firmly set, 2 ins. below ground, with brass cap mkd. as described in the field notes of the 1911 survey record, from which the remains of the 1911 bearing tree:</p> <p style="padding-left: 40px;">A cedar, 15 ins. diam., bears N. 61°08' E., 689 lks. dist., with the marks XX and illegible scribe marks visible on partially healed blaze.</p> <p>Drive a steel fence post on east side of iron post.</p> <p>Cor. is located in sand dunes and scattered incense cedar.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the Subdivisional Lines

Reestablishment of the Survey Executed by Stewart and Clark in 1913

From the cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd. and witnessed as described in the field notes of the 1913 survey record. No remaining evidence of the bearing trees was recovered.

N. 0°02.0' E., bet. secs. 9 and 10.

20.027

Point for the S 1/16 sec. cor. of secs. 9 and 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:

T 14 S R 4 W  
S 1/16  
S 9 | S 10  
1999

40.054

The 1/4 sec. cor. of secs. 9 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 17 ins. above ground, in a mound of stone, with brass cap mkd. as described in the field notes of the 1913 survey record. (Record: mound of earth to the west)

Cor. is located in grass.

N. 0°00.7' E., beginning new measurement.

40.057

The cor. of secs. 3, 4, 9 and 10, monumented with an iron post, 2 ins. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, 4 ft. base, with brass cap mkd. as described in the field notes of the 1913 survey record.

Cor. is located in grass on a spur ridge.

N. 0°17.1' E., bet. secs. 3 and 4..

39.602

Point for the 1/4 sec. cor. of sec. 4 only, at proportionate dist. Note: This cor. was not set during the 1913 Stewart and Clark survey record.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, with aluminum cap mkd.:

T 14 S    R 4 W  
  1/4 |  
  S 4 |  
      1999

Drive a steel fence post alongside the aluminum post.

**40.088**

The 1/4 sec. cor. of secs. 3 only, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. as described in the field notes of the 1913 survey record.

Note: This cor. functions as the 1/4 sec. cor. of sec. 3 only.

Remove the marks pertaining to sec. 4 from the brass cap.

Add the marks 1999 to the brass cap.

Cor. is located 50 ft. South of a draw, drains west.

---

N. 0°16.3' E., beginning new measurement.

**39.116**

The cor. of secs. 3, 4, 33 and 34, Tps. 13 and 14 S., R. 4 W., monumented with an iron post, 3 ins. diam., firmly set, projecting 24 ins. above ground, with brass cap mkd. as described in the field notes of the 1913 resurvey record, with a steel fence post alongside.

Cor. is located on a flat.

---

Reestablishment of the Survey Executed by J. Gorlinski in 1873  
and the Resurvey Executed by Stewart and Clark in 1913

---

From the 1/4 sec. cor. of secs. 16 and 17, monumented with an iron post, 1 in. diam., firmly set, 1 in. below ground, with brass cap mkd. as described in the field notes of the 1913 resurvey record.

Cor. is located in an old fence, bearing N and S.

N. 0°00.5' W., bet. secs. 16 and 17.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 4 W., SALT LAKE MERIDIAN, UTAH


CHAINS

40.047

The cor. of secs. 8, 9, 16 and 17, at the intersection of old fences bearing N, S and W, and is accepted as the best available evidence of the 1913 resurvey record.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam. 23 ins. in the ground with magnet at base, with aluminum cap mkd.:



From this cor., the 1/4 sec. cor. of secs. 8 and 9, hereinafter described, bears N. 0°03.3' E., 40.042 chs. dist. for a tie line.

From this same cor., the 1/4 sec. cor. of secs. 8 and 17, hereinafter described, bears N. 89°58.8' W., 40.013 chs. dist., for a tie line.

From the 1/4 sec. cor. of secs. 9 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd. and witnessed as described in the field notes of the 1913 survey record.

Cor. is located on the edge of a plateau.

N. 89°58.6' W., bet. secs. 9 and 16.

40.094

The cor. of secs. 8, 9, 16 and 17.

Reestablishment of the Survey Executed by Stewart and Clark in 1913

From the cor. of secs. 3, 4, 9 and 10.

N. 89°58.8' W., bet. secs. 4 and 9.

39.696

The 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. as described in the field notes of the 1913 survey record, with a steel fence post alongside the iron post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on a flat in grass.

---

Reestablishment of the Survey Executed by J. Gorlinski in 1873  
and the Resurvey Executed by Stewart and Clark in 1913

---

From the 1/4 sec. cor. of secs. 4 and 5, monumented with an iron pipe, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. as described in the field notes of the 1913 resurvey record, with a steel fence post alongside the iron post.

Cor. is located on a grassy flat.

N. 1°07.9' W., bet. secs. 4 and 5.

39.536

True point for the cor. of secs. 4, 5, 32 and 33, Tps. 13 and 14 S., R. 4 W., hereinbefore described.

---

From the 1/4 sec. cor. of secs. 8 and 17, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. as described in the field notes of the 1913 survey record, with a steel fence post along side the iron post.

Cor. is located on a flat in grass.

S. 89°59.8' W., bet. secs. 8 and 17.

20.004

Point for the W 1/16 sec. cor. of secs. 8 and 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, with aluminum cap mkd.:

	T 14 S R 4 W	
	S 8	
W 1/16	_____	
	S 17	
	1999	

Drive a steel fence post alongside the aluminum post.

Cor. is located in an old fence line, bears E and W.

40.008

The cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2 ins. diam., firmly set, 6 ins. below ground, with brass cap mkd. as described in the field notes of the 1913 survey record, with a wooden fence post, flush with the ground on the north side of the iron post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

*CHAINS*

---

N. 0°07.1' E., bet. secs. 7 and 8.

**39.941**

The 1/4 sec. cor. of secs. 7 and 8, monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. as described in the field notes of the 1913 survey record.

Cor. is located in a fence, bears E and W.

---

N. 0°05.5' E., beginning new measurement.

**40.133**

The cor. of secs. 5, 6, 7 and 8, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. as described in the field notes of the 1913 survey record, with a steel fence post alongside the iron post.

---

From the cor. of secs. 4, 5, 8 and 9, monumented with an iron post, 2 ins. diam., 20 ins. above ground, with brass cap mkd. as described in the field notes of the 1913 survey record.

Corner is located in a flat grass field.

S. 89°58.9' W., bet. secs. 5 and 8.

**20.020**

Point for the E 1/16 sec. cor. of secs. 5 and 8.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, with aluminum cap mkd.:

T 14 S R 4 W  
S 5  
E 1/16 —————  
S 8  
1999

Drive a steel fence post alongside the aluminum post.

**40.040**

The 1/4 sec. cor. of secs. 5 and 8, determined at record bearing and dist. from the 1913 bearing trees:

An incense cedar, 10 ins. diam., bears N. 35° E., 35 lks. dist., with no marks visible on healed blaze.

An incense cedar, 12 ins. diam., bears S. 25° E., 62 lks. dist., with the marks 1/4S8BT visible on partially healed blaze.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam. 30 ins. in the ground with magnet at base, with aluminum cap mkd.:

T 14 S    R 4 W  
          S 5  
1/4 —————  
          S 8  
          1999

Cor. falls at intersection of motorcycle trails, and 8 ft. North of a steel fence post.

---

N. 89°58.1' W., beginning new measurement.

**39.885**

The cor. of secs. 5, 6, 7 and 8.

---

Reestablishment of the Survey Executed by Stewart and Clark in 1913

---

N. 0°25.3' W., bet. secs. 5 and 6.

**39.818**

Point for the 1/4 sec. cor. of sec. 5 only, at proportionate dist. Note: This cor. was not set during the 1913 survey record.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam. 24 ins. in the ground with magnet at base, with aluminum cap mkd.:

T 14 S    R 4 W  
          | 1/4  
          | S 5  
          1999

Drive a steel fence post alongside the aluminum post.

Cor. is located in sand dunes.

**39.936**

The 1/4 sec. cor. of sec. 6 only, determined at record bearing and dist. from the original bearing trees:

A cedar, 17 ins. diam., bears S. 49° E., 336 lks. dist., with no marks visible on healed blaze.

SURVEY OF THE SUBDIVISION OF SECTION 4,  
T. 14 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

*CHAINS*

A cedar, 6 ins. diam., bears N. 21° W., 290 lks. dist., with the marks 1/4S6BT visible on partially healed blaze.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam. 24 ins. in the ground with magnet at base, aluminum cap mkd.:

T 14 S R 4 W  
1/4 |  
S 6 |  
1999

Drive a steel fence post alongside the aluminum post.

Cor. is located in sand dunes.

---

N. 0°19.3' W., beginning new measurement.

39.700

The cor. of secs. 5, 6, 31 and 32, Tps. 13 and 14 S., R. 4 W., hereinbefore described.

---

Survey of the Subdivision of Section 4,  
T. 14 S., R. 4 W., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 4 and 9.

N. 0°13.1' W., on the N-S center line of sec. 4.

39.811

Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E-W center line of sec. 4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam. 24 ins. in the ground with magnet at base, with aluminum cap mkd.:

T 14 S R 4 W  
C 1/4 S 4  
1999

Drive a steel fence post alongside the aluminum post.

79.433

The 1/4 sec. cor. of secs. 4 and 33, Tps. 13 and 14 S., R. 4 W., hereinbefore described.

---

SURVEY OF THE SUBDIVISION OF SECTION 5,  
T. 14 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

*CHAINS*

From the 1/4 sec. cor. of sec. 4 only.

N. 89°41.0' W., on the E-W center line of sec. 4..

40.042

The center 1/4 sec. cor. of sec. 4.

79.891

The 1/4 sec. cor. of secs. 4 and 5.

Survey of the Subdivision of Section 5,  
T. 14 S., R. 4 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 5 and 8.

N. 0°18.1' W., on the N-S center line of sec. 5.

39.946

The center 1/4 sec. cor. of sec. 5, at intersection with the E-W center line of sec. 5.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam. 24 ins. in the ground with magnet at base, with aluminum cap mkd.:

T 14 S    R 4 W  
C 1/4 S 5  
1999

Drive a steel fence post alongside the aluminum post.

79.596

The 1/4 sec. cor. of secs. 5 and 32, Tps. 13 and 14 S., R. 4 W., hereinbefore described.

From the 1/4 sec. cor. of secs. 4 and 5.

S. 89°51.0' W., on the E-W center line of sec. 5.

20.134

Point for the center E 1/16 sec. cor. of sec. 5.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam. 24 ins. in the ground with magnet at base, with aluminum cap mkd.:

T 14 S R 4 W  
E 1/16  
C ——— C  
S 5  
1999

SURVEY OF THE SUBDIVISION OF SECTION 8,  
T. 14 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Drive a steel fence post alongside the aluminum post.

**40.268**

The center 1/4 sec. cor. of sec. 5.

**80.232**

The 1/4 sec. cor. of sec. 5 only.

---

From the E 1/16 sec. cor. of secs. 5 and 8.

N. 0°08.0' W., on the N-S center line of the SE 1/4 of sec. 5.

**39.990**

The center E 1/16 sec. cor. of sec. 5.

---

Survey of the Subdivision of Section 8,  
T. 14 S., R. 4 W., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 8 and 17.

N. 0°01.3' E., on the N-S center line of sec. 8.

**39.983**

Point for the center 1/4 sec. cor. of sec. 8, at intersection with the E-W center line of sec. 8.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam. 24 ins. in the ground with magnet at base, with aluminum cap mkd.:

T 14 S    R 4 W  
C 1/4 S 8  
1999

Drive a steel fence post alongside the aluminum post.

Cor. is located 10 ft. West of a dirt road, and East and adjacent to railroad tracks.

**80.050**

The 1/4 sec. cor. of secs. 5 and 8.

---

From the 1/4 sec. cor. of secs. 8 and 9, monumented with an iron post, 1 in. diam., firmly set, flush with ground, with brass cap mkd. as described in the field notes of the 1913 survey record.

Cor. is located 2 ft. S. 45° W. of the cor. of fences bearing S and W.

S. 89°56.2' W., on the E-W center line of sec. 8.

SURVEY OF THE SUBDIVISION OF SECTION 9,  
T. 14 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

<i>CHAINS</i>	
<b>40.032</b>	The center 1/4 sec. cor. of sec. 8.
<b>79.970</b>	The 1/4 sec. cor. of secs. 7 and 8.
<hr/> Survey of the Subdivision of Section 9, T. 14 S., R. 4 W., Salt Lake Meridian, Utah	
<b>40.042</b>	From the 1/4 sec. cor. of secs. 9 and 16.  N. 0°00.5' E., on the N-S center line of sec. 9.  Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E-W center line of sec. 9.  Set an aluminum post, 30 ins. long, 2 1/2 ins. diam. 24 ins. in the ground with magnet at base, with aluminum cap mkd.:
T 14 S    R 4 W C 1/4 S 9 1999	
<b>80.097</b>	Drive a steel fence post alongside the aluminum post.  The 1/4 sec. cor. of secs. 4 and 9.
<b>39.699</b>	From the 1/4 sec. cor. of secs. 9 and 10.  N. 89°58.7' W., on the E-W center line of sec. 9.  The center 1/4 sec. cor. of sec. 9.
<b>79.752</b>	The 1/4 sec. cor. of secs. 8 and 9.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Jerry Thomas Von Del Newby	Cadastral Surveyor Survey Aid

## CERTIFICATE OF SURVEY

I, *John F. Carroll, Cadastral Surveyor*, **HEREBY CERTIFY** upon honor that, in pursuance of Special Instructions bearing the date of the 22nd day of October, 1999, I have *dependently resurveyed a portion of the north boundary, a portion of the subdivisional lines and the survey of the subdivision of sections 4, 5, 8 and 9, in Township 14 South, Range 4 West,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instruction, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

JULY 31, 2000

Date

John F. Carroll

Cadastral Surveyor

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the north boundary, a portion of the subdivisional lines and the survey of the subdivision of sections 4, 5, 8 and 9, in Township 14 South, Range 4 West, Salt Lake Meridian, Utah,*

executed by *John F. Carroll, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

August 23, 2000

Date

Daniel W. Webb

Chief Cadastral Surveyor for Utah