

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

TRACT 'F'

AND

A PORTION OF THE SUBDIVISIONAL LINES,

AND THE

SURVEY OF TRACTS 37, 38, AND 39,

IN

TOWNSHIP 1 NORTH, RANGE 1 EAST

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*M. Ross Workman*  
*Supervisory Cadastral Surveyor*

Under special instructions dated *October 25, 1999*, approved *October 25, 1999*, which provided for the surveys included under Group Number *910*, and assignment instructions dated *October 25, 1999*.

Survey commenced *December 2, 1999*

Survey completed *June 9, 2000*

# INDEX DIAGRAM

Township 1 North, Range 1 East

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27 6	26	25
31	32	33	34	35	36

Resurvey of Tract "F" .....Page 3

Survey of Tract 37 .....Page 6

Survey of Tract 38 .....Page 10

Survey of Tract 39 .....Page 21

## TOWNSHIP 1 NORTH, RANGE 1 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The following field notes describe the dependent resurvey of Tract "F", and a portion of the subdivisional lines, and the survey of Tracts 37, 38, and 39, in Township 1 North, Range 1 East, Salt Lake Meridian, Utah.

**History of Surveys**

	Surveyed by		Rear. or Resurveyed by	
<b>SOUTH BOUNDARY (Salt lake Base Line)</b>				
Portion	J. Troskolawski	1855		
Portion	J. Bausman	1869	J. Bausman	1869
Portion			F. Dickert	1881
Portion			E.W. Koeber	1884-85
Portion			G.B. Hatch	1967
<b>EAST BOUNDARY</b>				
Portion	A. Jessen	1878		
Portion	F. Dickert	1881	F. Dickert	1881
Portion	E.W. Koeber	1884	E.W. Koeber	1884
Portion			O.E. Saloman	1886
<b>WEST BOUNDARY (Salt Lake Meridian)</b>				
Portion	J. Troskolawski	1855		
Portion	J. Bausman	1869	J. Bausman	1869
Portion	J. Gorlinski	1872	J. Gorlinski	1872
Portion	A.D. Ferron	1878	A.D. Ferron	1878
Portion			R.C. Yundt	1952
<b>NORTH BOUNDARY</b>				
Portion	J. Troskolawski	1855		
Portion	J. Gorlinski	1872	J. Gorlinski	1872
Portion	E.W. Koeber	1883-85	E.W. Koeber	1883-85
Portion	O.E. Saloman	1886		
Portion			R.C. Yundt	1952
Portion			Murphy and Harkin	1966-67
<b>SUBDIVISION</b>				
Portion	U.S. Military	1862		
Portion	J. Bausman	1869	J. Bausman (FDMRB)	1869
Portion	J. Gorlinski	1872		
Portion	R.H. Browne	1874		
Portion	A. Jessen	1878	A. Jessen	1878
Portion	E.W. Koeber	1883-85	E.W. Koeber	1883-85

## TOWNSHIP 1 NORTH, RANGE 1 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS****SUBDIVISION (continued)**

Portion	J. Gorkinski	1894	J. Gorkinski	1894
Portion	Q.M. Fort Douglas	1940-41	Q.M. Fort Douglas	1940-41
Portion	G.B. Hatch	1967	G.B. Hatch	1967

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 910, dated October 25, 1999.

The directions and distances of the lines were determined by the use of Global Positioning System (G.P.S.) using relative positioning techniques.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the monuments and calls of the original field note record. Identified corners were monumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of AP 1 of Tract "F", on the Salt Lake Base Line, T. 1 N., R. 1 E., which will also function as a B.L.M. Control Station, was determined by G.P.S. methods from National Geodetic Survey triangulation stations "FOURTH 13" and "PIERCE", is as follows:

Latitude 40°46'10.268" N. Longitude 111°48' 51.626" W.  
N.A.D. 1983 (1994)

The geographic position of the National Geodetic Survey triangulation station "FOURTH 13", is as follows:

Latitude 40°45'38.39284" N. Longitude 111°51'13.99192" W.  
N.A.D. 1983 (1994) Elevation 4581.06 FT.

The geographic position of the National Geodetic Survey triangulation station "PIERCE", is as follows:

Latitude 40°43'18.73752" N. Longitude 111°51' 09.38765" W.  
N.A.D. 1983 (1994) Elevation 4442.

The mean magnetic declination as determined from the U.S. Geological Survey Magnetic Declination Map of 1990 is 13 1/2° E.

---

Dependent Resurvey of Tract "F",  
T. 1 N., R. 1 E., Salt Lake Meridian, Utah

---

DEPENDENT RESURVEY OF TRACT "F"  
T. 1 N., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Reestablishment of the Survey Executed by the U.S. Military in 1862,  
The Dependent Resurveys by J.Bausman in 1869, and G.B. Hatch in 1967

Beginning at Angle Point 1 of Tract "F", identical with Angle Point 5 of Tract "E" and the closing corner on the Salt Lake Base Line with the Fort Douglas Military Reservation East Boundary, monumented with an iron post, 2 1/2 ins. diameter, 18 ins. above ground, in a mound of stone, with a brass cap marked as described in the official record of the 1967 resurvey.

N. 0°02.9' E., on line 1-2 of Tract "F".

20.573  
(1357.80') Intersect line 1-2 of Tract 37; not monumented.

33.482  
(2209.82') Intersect line 23-24 of Tract 38; not monumented.

45.765  
(3020.49') Intersect line 12-13 of Tract 38; not monumented.

55.497  
(3662.79') Angle Point 2 of Tract "F", monumented with an iron post, 2 1/2 ins. diameter, 3 ins. above ground, with brass cap marked as described in the official record the 1967 resurvey.

This corner will also function as Angle Point 8 of Tract 37; remark cap.

T1N	/	
R1E		TR37
TRF		AP8
AP2		S35
2000		
1967		

Old fences bears S and W.

A Forest Service boundary post bears N, 1 ft.

N. 89°56.9' W., on line 2-3 of Tract "F".

3.262  
(215.30') Point for the closing corner of sections 34 and 35, at an intersection point SOUTH from the corner of sections 26, 27, 34, and 35, hereinafter described; there is no remaining evidence of the original closing corner.

Set a drive rod, 30 ins. long, 1 1/4 ins. diameter, 24 ins. in the ground, and in a collar of stone, with a standard Forest Service aluminum cap marked:

DEPENDENT RESURVEY OF TRACT "F"  
T. 1 N., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T1N	R1E
S34	S35
C	C
TRF	
2000	

Corner is located on a steep SW slope in an old E and W fence line with barbed wires lying on the ground.

23.067  
(1522.44')

The 1/16 section corner for the separation of lots 1 and 2 of section 34, monumented with an iron post, 2 ins. diam., 12 ins. above ground, with brass cap marked by the Q.M. of Fort Douglas in 1940-41.

USA		
RB		
13	43	1/16
13	43	

---

Reestablishment of the Survey Executed by the U.S. Military in 1862,  
the Dependent Resurvey by J. Bausman in 1869,  
Q.M. Fort Douglas in 1940-41 and G.B. Hatch in 1967

Continue measurement.

70.292  
(4639.28')

Angle Point 3 of Tract "F", monumented with an iron post, 1 in. diam., 8 ins. above ground, with a 3 1/2 in. Forest Service brass cap marked as described in; the official record of the 1967 resurvey.

---

Reestablishment of the Survey Executed by  
Q.M. of Fort Douglas in 1940-41 and the Resurvey by G.B. Hatch in 1967

S. 0° 00.5' W., on line 3-4 of Tract "F".

55.583  
(3668.45')

Angle Point 4 of Tract "F", identical with Angle Point 7 of Tract "D", on the Salt Lake Base line, monumented with a P.K. nail in driveway between parking lots at the University of Utah. This point was reestablished and referenced by Sandy Lewis of the Forest Service from the original monument in 1988, which was marked and described in the official record of the 1967 resurvey.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 36 ins. in the ground, in concrete with ring and cover with aluminum cap marked:

DEPENDENT RESURVEY OF TRACT "F"  
T. 1 N., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

TRF
AP 4
TRD
AP 7
2000

---

Reestablishment of the Survey Executed by J. Troskolawski in 1855,  
the Dependent Resurvey by J. Bausman in 1869,  
F. Dickert in 1881, Q.M. of Fort Douglas in 1940-41, and the  
Resurvey by G.B. Hatch in 1967

---

N. 89° 59.4' E., on line 4-1 of Tract "F", and on the Salt Lake Base Line.

**31.535** Point for Angle Point 6 of Tract 39, hereinafter described.  
**(2081.31')**

**34.035** Point for Angle Point 7 of Tract 39, hereinafter described.  
**(2246.34')**

**47.202** Angle Point 6 of Tract "D", identical with Angle Point 4 of Tract "E", on the Salt Lake Base  
**(3115.36')** Line, monumented with an iron post, 2 1/2 ins. diam., 6 ins. above ground, with brass cap marked  
as described in the official record of the 1967 resurvey.

Corner is located on steep N slope.

---

Reestablishment of the Survey Executed by J. Bausman in 1869,  
the Dependent Resurvey by F. Dickert in 1881,  
Q.M. of Fort Douglas in 1940-41, and G.B. Hatch in 1967

---

N. 89° 57.8' E., beginning new measurement.

**23.061** Angle Point 1 of Tract "F", and point of beginning.  
**(1522.00')**

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 1 N., R. 1 E., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by J. Bausman in 1869

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 1 N., R. 1 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the corner of sections 26, 27, 34, and 35, monumented with an iron post, 2 ins. diameter, projecting 20 ins. above ground, and in a mound of stone, with brass cap marked:

USA	
R	B
27	26
34	35

SOUTH, between sections 34 and 35.

**24.400**  
**(1610.40')**

The closing corner of sections 34 and 35, hereinbefore described.

---

Survey of Tract 37,  
T. 1 N., R. 1 E., Salt Lake Meridian, Utah

---

Beginning at the point for Angle Point 1 of Tract 37.

Set a rebar, 18 ins. long, 3/4 in. diam., 12 ins. in the ground, with a 2 in. Forest Service site survey aluminum cap marked:

AP1  
TR37

Set a Forest Service boundary post alongside rebar.

Corner is located on top of rock outcrop.

S. 58° 38.7' E., on line 1-2 of Tract 37.

**1.331**  
**(87.86')**

Intersect line 1-2 of Tract "F".

**25.075**  
**(1654.98')**

Point for Angle Point 2 of Tract 37.

Set a rebar, 18 ins. long, 3/4 ins. diam., 12 ins. in the ground, with a 2 in. Forest Service site survey aluminum cap marked:

AP2  
TR37

Set a Forest Service boundary post alongside the rebar.

SURVEY OF TRACT 37,  
T. 1 N., R. 1 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Corner is located near top of rock outcrop.

---

N. 39° 27.2' E., on line 2-3 of Tract 37.

**15.659**  
**(1033.50')**

Point for Angle Point 3 of Tract 37.

Set a rebar, 18 ins. long, 3/4 in. diam., 12 ins. in the ground, with a 2 in. Forest Service site survey aluminum cap marked:

AP3  
TR 37

Set a Forest Service boundary post alongside the rebar.

Corner is located on top of ridge.

---

N. 45° 27.6' E., on line 3-4 of Tract 37.

**11.812**  
**(779.59')**

Point for Angle Point 4 of Tract 37.

Set a rebar, 18 ins. long, 3/4 in. diam., 14 ins. in the ground, with a 2 in. Forest Service site survey aluminum cap marked:

TR 37  
AP4

Set a Forest Service boundary post, 2 ft. SE of rebar.

Corner is located on top of ridge.

---

N. 50° 39.9' E., on line 4-5 of Tract 37.

**11.143**  
**(735.42')**

Point for Angle Point 5 of Tract 37.

Set a rebar, 18 ins. long, 3/4 in. diam., 12 ins. in the ground, with a 2 in. Forest Service site survey aluminum cap marked:

TR 37  
AP5

Set a Forest Service boundary post, NE of rebar.

SURVEY OF TRACT 37,  
T. 1 N., R. 1 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Corner is located on top of ridge.

---

N. 32° 11.2' E., on line 5-6 of Tract 37.

**38.061**  
**(2512.02')**

Point for Angle Point 6 of Tract 37.

Set a rebar, 18 ins. long, 3/4 in. diam., 12 ins. in the ground, with a 2 in. Forest Service site survey aluminum cap marked:

TR 37  
AP6

Set a Forest Service boundary post, alongside the rebar.

Corner is located on top of ridge.

---

N. 81° 30.0' W., on line 6-7 of Tract 37.

**40.218**  
**(2654.40')**

Point for Angle Point 7 of Tract 37.

Set a rebar, 18 ins. long, 3/4 in. diam., 12 ins. in the ground, with a 2 in. Forest Service site survey aluminum cap marked:

TR 37  
AP7

Set a Forest Service boundary post, alongside the rebar.

Corner is located on a SE slope.

---

S. 56° 33.1' W., on line 7-8 of Tract 37.

**33.227**  
**(2193.02')**

Angle Point 8 of Tract 37, identical with Angle Point 2 of Tract "F", hereinbefore described.

---

S. 36° 57.6' W., on line 8-9 of Tract 37.


**30.684**  
**(2025.13')**

Point for Angle Point 9 of Tract 37.

SURVEY OF TRACT 37,  
T. 1 N., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:



Set a Forest Service boundary post, 1 ft. NE of rebar.




S. 38° 44.8' E., on line 9-10 of Tract 37.

**3.169**  
**(209.15')**

Point for Angle Point 18 of Tract 38, identical with Angle Point 2 of Tract 39.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 25 ins. in the ground, with a standard Forest Service aluminum cap marked:




Set a Forest Service boundary post, 1 ft. N of drive rod.

Corner is located 20 ft. W of a power line and 100 ft. S of an E and W fence line.

**5.512**  
**(363.80')**

Point for Angle Point 1 of Tract 39.


Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 32 ins. in the ground, with a 1 1/2 in. aluminum cap marked:



**10.656**  
**(703.31')**

Point for Angle Point 19 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:



SURVEY OF TRACT 37,  
T. 1 N., R. 1 E., SALT LAKE MERIDIAN, UTAH


**CHAINS**

Set a Forest Service boundary post, 1 ft. NE of drive rod.

**15.148**  
**(999.76')**

Point for Angle Point 10 of Tract 37.

Set a B.L.M. aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:



Set a Forest Service boundary post, 6 ins. NE of aluminum post.

Corner is located on a steep W slope.

N. 74° 55.7' E., on line 10-1 of Tract 37.

**8.081**  
**(533.36')**

Angle Point 1 of Tract 37 and point of beginning.


---

Survey of Tract 38,  
T. 1 N., R. 1 E., Salt Lake Meridian, Utah

---

Beginning at the point for Angle Point 01 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:



Set a Forest Service boundary post alongside the drive rod.

Corner is located at base of hill.

N. 38° 17.1' W., on line 1-2 of Tract 38.

**4.564**  
**(301.22')**

Point for Angle Point 02 of Tract 38.

SURVEY OF TRACT 38,  
T. 1 N., R. 1 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:



Set a Forest Service boundary post, 1 ft. west of drive rod.

---

S. 51° 56.5' W., on line 2-3 of Tract 38.

**2.450**  
**(161.67')** Point for Angle Point 03 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 16 ins. in the ground, with a standard Forest Service aluminum cap marked:



Set a Forest Service boundary post, 1 1/2 ft. east of drive rod.

---

S. 87° 56.8' W., on line 3-4 of Tract 38.

**4.973**  
**(328.25')** Point for Angle Point 04 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 20 ins. in the ground, with a standard Forest Service aluminum cap marked:



Set a Forest Service boundary post, 2 ft. west of drive rod.

---

S. 82° 16.1' W., on line 4-5 of Tract 38.

**5.096**  
**(336.33')** Point for Angle Point 05 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 18 ins. in the ground, with a standard Forest Service aluminum cap marked:

SURVEY OF TRACT 38,  
T. 1 N., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS




Set a Forest Service boundary post, 1 ft. north of drive rod.

N. 82° 46.4' W., on line 5-6 of Tract 38.

**4.418**  
**(291.58')** Point for Angle Point 06 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:




Set a Forest Service boundary post, 1 ft. north of drive rod.

S. 39° 14.1' W., on line 6-7 of Tract 38.

**5.579**  
**(368.20')** Point for Angle Point 07 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 20 ins. in the ground, with a standard Forest Service aluminum cap marked:



Set a Forest Service boundary post, 1 ft. north of drive rod.

N. 60° 31.7' W., on line 7-8 of Tract 38.

**5.493**  
**(362.52')** Point for Angle Point 08 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 12 ins. in the ground, with a standard Forest Service aluminum cap marked:



SURVEY OF TRACT 38,  
T. 1 N., R. 1 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set a Forest Service boundary post, alongside the drive rod.


---

S. 2° 30.8' W., on line 8-9 of Tract 38.

**6.082**  
**(401.43')**

Point for Angle Point 09 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:



Set a Forest Service boundary post, 1 ft. north of drive rod.


---

S. 29° 10.7' W., on line 9-10 of Tract 38.

**3.607**  
**(238.08')**

Point for Angle Point 10 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 18 ins. in the ground, with a standard Forest Service aluminum cap marked:



Set a Forest Service boundary post, 1 ft. east of drive rod.


---

S. 57° 24.1' W., on line 10 -11 of Tract 38.

**2.145**  
**(141.55')**

Point for Angle Point 11 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 12 ins. in the ground, with a standard Forest Service aluminum cap marked:



SURVEY OF TRACT 38,  
T. 1 N., R. 1 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

S. 88° 04.1' W., on line 11-12 of Tract 38.

**5.320**  
**(351.12')**

Point for Angle Point 12 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:



Set a Forest Service boundary post alongside the drive rod.

---

S. 39° 50.7' W., on line 12-13 of Tract 38.

**0.142**  
**(9.39')**

Intersect line 1-2 of Tract "F"; not monumented.

**3.718**  
**(245.40')**

Point for Angle Point 13 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 10 ins. to solid rock, in a mound of stone, 5 ft. base to top of a standard Forest Service aluminum cap marked:




S. 79° 32.9' W., on line 13-14 of Tract 38.

**3.703**  
**(244.38')**

Point for Angle Point 14 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 12 ins. in the ground, with a standard Forest Service aluminum cap marked:



Set a Forest Service boundary post, alongside the drive rod.

Corner is located on a steep S slope.

---

SURVEY OF TRACT 38,  
T. 1 N., R. 1 E., SALT LAKE MERIDIAN, UTAH


**CHAINS**

S. 41° 48.3' W., on line 14-15 of Tract 38.

**3.579**  
**(236.21')**

Point for Angle Point 15 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 18 ins. in the ground to solid rock, with a standard Forest Service aluminum cap marked:



AP15  
TR38  
2000

Set a Forest Service boundary post, 1 ft. north of drive rod.


---

S. 13° 41.2' W., on line 15-16 of Tract 38.

**3.530**  
**(232.96')**

Point for Angle Point 16 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:



TR38  
AP16  
2000

Set a Forest Service boundary post, 4 ins. west of drive rod.


---

S. 35° 20.8' W., on line 16-17 of Tract 38.

**7.093**  
**(468.13')**

Point for Angle Point 17 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 18 ins. in the ground, with a standard Forest Service aluminum cap marked:



TR38  
AP17  
2000

Set a Forest Service boundary post, north of drive rod.

---

S. 58° 33.1' W., on line 17-18 of Tract 38.

SURVEY OF TRACT 38,  
T. 1 N., R. 1 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**3.751**  
**(247.56')**

Angle point 18 of Tract 38, identical with Angle Point 2 of Tract 39, and on line 9-10 of Tract 37, hereinbefore described.

---

S. 38° 44.8' E., on line 18-19 of Tract 38, identical with a portion of line 9-10 of Tract 37.

**7.487**  
**(494.16')**

Angle Point 19 of Tract 38, on line 9-10 of Tract, 37, hereinbefore described.

---

N. 61° 07.1' E., on line 19-20 of Tract 38.

**5.211**  
**(343.92')**

Point for Angle Point 20 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:

TR38  
AP20  
2000

Set a Forest Service boundary post, 1 ft. south of drive rod.

---

N. 36° 41.3' E., on line 20-21 of Tract 38.

**3.538**  
**(233.48')**

Point for Angle Point 21 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:

TR38  
AP21  
2000

Set a Forest Service boundary post, 1 ft. south of drive rod.

---

N. 51° 37.5' E., on line 21-22 of Tract 38.

**2.862**  
**(188.92')**

Point for Angle Point 22 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 20 ins. in the ground, with a standard Forest Service aluminum cap marked:

SURVEY OF TRACT 38,  
T. 1 N., R. 1 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

TR38  
AP22  
2000



Set a Forest Service boundary post, 1 ft. south of drive rod.


---

N. 25° 17.7' E., on line 22-23 of Tract 38.

**4.156**  
**(274.29')** Point for Angle Point 23 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 20 ins. in the ground, with a standard Forest Service aluminum cap marked:

TR38  
AP23  
2000



Set a Forest Service boundary post, 1 ft. north of drive rod.

---

S. 86° 02.2' E., on line 23-24 of Tract 38.

**1.068**  
**(70.47')** Intersect line 1-2 of Tract "F"; not monumented.

**3.100**  
**(204.59')** Point for Angle Point 24 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:

TR38  
AP24  
2000



Set a Forest Service boundary post, 3 ins. southwest of drive rod.

---

N. 61° 17.9' E., on line 24-25 of Tract 38.

**2.732**  
**(180.31')** Point for Angle Point 25 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:

SURVEY OF TRACT 38,  
T. 1 N., R. 1 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

TR38  
AP25  
2000

Set a Forest Service boundary post, 3 ft. northeast of drive rod.

---

N. 68° 11.1' E., on line 25-26 of Tract 38.

**4.725**  
**(311.83')** Point for Angle Point 26 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:

TR38  
AP26  
2000

Set a Forest Service boundary post, 1 ft. northeast of drive rod.

---

N. 82° 08.2' E., on line 26-27 of Tract 38.

**2.236**  
**(147.58')** Point for Angle Point 27 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:

TR38  
AP27  
2000

Set a Forest Service boundary post, 3 ins. west of drive rod.

---

N. 55° 56.8' E., on line 27-28 of Tract 38.

**5.762**  
**(380.30')** Point for Angle Point 28 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:

SURVEY OF TRACT 38,  
T. 1 N., R. 1 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

TR38  
AP28  
2000



Set a Forest Service boundary post, 6 ins. southeast of drive rod.


---

N. 16° 29.5' E., on line 28-29 of Tract 38.

**3.649**  
**(240.82')** Point for Angle Point 29 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:

TR38  
AP29  
2000



Set a Forest Service boundary post, 3 ins. north of drive rod.


---

N. 56° 55.7' E., on line 29-30 of Tract 38.

**4.292**  
**(283.26')** Point for Angle Point 30 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:

TR38  
AP30  
2000



Set a Forest Service boundary post, 3 ins. north of drive rod.

---

N. 79° 38.0' E., on line 30-31 of Tract 38.


**5.224**  
**(344.78')** Point for Angle Point 31 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:

SURVEY OF TRACT 38,  
T. 1 N., R. 1 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

TR38  
AP31  
2000



Set a Forest Service boundary post, 4 ins. north of drive rod.

---

N. 42° 47.5' E., on line 31-32 of Tract 38.

**9.806**  
**(647.20')**

Point for Angle Point 32 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:

TR38  
AP32  
2000



Set a Forest Service boundary post, alongside the drive rod.

Corner is located at base of a hill.

---


N. 83° 11.8' E., on line 32-33 of Tract 38.

**1.949**  
**(128.61')**

Point for Angle Point 33 of Tract 38.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:

TR38  
AP33  
2000



Set a Forest Service boundary post, alongside the drive rod.

Corner is located at base of a hill.

---

N. 50° 03.2' E., on line 33-1 of Tract 38.

**3.332**  
**(219.94')**

Angle Point 01 of Tract 38 and point of beginning.

---

SURVEY OF TRACT 39,  
T. 1 N., R. 1 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Survey of Tract 39,  
T. 1 N., R. 1 E., Salt Lake Meridian, Utah

---

Beginning at Angle Point 01 of Tract 39, on line 9-10 of Tract 37, hereinbefore described.

N. 38° 44.8' W., on line 1-2 of Tract 39, identical with line 9-10 of Tract 37.

**2.343**  
**(154.65')**

Angle Point 02 of Tract 39, identical with angle Point 18 of tract 38 and on line 9-10 of Tract 37, hereinbefore described.


---

S. 66° 18.5' W., on line 2-3 of Tract 39.

**4.791**  
**(316.19')**

Point for Angle Point 03 of Tract 39.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:

  
 AP03  
 TR39  
 2000

Set a Forest Service boundary post, 1 ft. northeast of drive rod.

Corner is located 20 ft. west of a power line.


---

S. 37° 09.1' W., on line 3-4 of Tract 39.

**1.880**  
**(124.10')**

Point for Angle Point 04 of Tract 39.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:

  
 AP04  
 TR39  
 2000

Set a Forest Service boundary post, 1 ft. southeast of drive rod.

Corner is located 20 ft. west of a power line.

---

SURVEY OF TRACT 39,  
T. 1 N., R. 1 E., SALT LAKE MERIDIAN, UTAH


**CHAINS**

S. 31° 19.0' W., on line 4-5 of Tract 39.

**23.147**  
**(1527.69')**

Point for Angle Point 05 of Tract 39.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:

  
 AP05  
 TR39  
 2000

Set a Forest Service boundary post, alongside of drive rod.


Corner is located 20 ft. west of a power line.

S. 41° 46.3' W., on line 5-6 of Tract 39.

**7.135**  
**(470.91')**

Point for Angle Point 06 of Tract 39, on line 4-1 of Tract "F", and on the Salt Lake Base Line.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:

  
 TR39  
 TRF / AP06  
 2000


Set a Forest Service boundary post, 2 ft. northeast of drive rod.

N. 89° 59.4' E., on line 6-7 of Tract 39, identical with a portion of line 4-1 of Tract "F" and on the Salt Lake Base Line.

**2.500**  
**(165.03')**

Point for Angle Point 07 of Tract 39, on line 4-1 of Tract "F", and on the Salt Lake Base Line.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:

  
 TR39  
 AP07 / TRF  
 2000

Corner is located 2 ft. west of fence

SURVEY OF TRACT 39,  
T. 1 N., R. 1 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 44° 38.9'E., on line 7-8 of Tract 39.

**6.501**  
**(429.07')**

Point for Angle Point 08 of Tract 39.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 24 ins. in the ground, with a standard Forest Service aluminum cap marked:

TR39  
AP08  
2000

---

N. 27° 49.4'E., on line 8-9 of Tract 39.

**1.199**  
**(79.15')**

Point for Angle Point 09 of Tract 39.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 27 ins. in the ground, with a standard Forest Service aluminum cap marked:

TR39  
AP09  
2000

---

N. 16° 33.3'E., on line 9-10 of Tract 39.

**3.340**  
**(220.46')**

Point for Angle Point 10 of Tract 39.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 18 ins. in the ground, with a standard Forest Service aluminum cap marked:

TR39  
AP10  
2000

---

N. 30° 23.3'E., on line 10-11 of Tract 39.

**6.945**  
**(458.39')**

Point for Angle Point 11 of Tract 39.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 18 ins. in the ground, with a standard Forest Service aluminum cap marked:

SURVEY OF TRACT 39,  
T. 1 N., R. 1 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

TR39  
AP11  
2000

N. 31° 25.5' E., on line 11-12 of Tract 39.

**7.457**  
**(492.13')** Point for Angle Point 12 of Tract 39.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 18 ins. in the ground, with a standard Forest Service aluminum cap marked:

TR39  
AP12  
2000

N. 40° 08.0' E., on line 12-13 of Tract 39.

**1.990**  
**(131.32')** Point for Angle Point 13 of Tract 39.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 18 ins. in the ground, with a standard Forest Service aluminum cap marked:

TR39  
AP13  
2000

N. 57° 11.0' E., on line 13-14 of Tract 39.

**3.020**  
**(199.32')** Point for Angle Point 14 of Tract 39.

Set a drive rod, 30 ins. long, 1 1/4 ins. diam., 18 ins. in the ground, with a standard Forest Service aluminum cap marked:

TR39  
AP14  
2000

N. 59° 59.2' E., on line 14-1 of Tract 39.

SURVEY OF TRACT 39,  
T. 1 N., R. 1 E., SALT LAKE MERIDIAN, UTAH

*CHAINS*

**4.587**  
**(302.75')**

Angle Point 01 of Tract 39, and point of beginning.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Ronald K. Baugh	Cadastral Surveyor
Henry J. Peterson	Survey Technician
Jared Black	Survey Technician
Steve J. Oatman	Survey Aid
Mathew J. Leonard	Survey Aid
Paula Coleman	Survey Aid

## CERTIFICATE OF SURVEY

I, *M. Ross Workman*, *Supervisory Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *25th day of October, 1999*, I have *dependently resurveyed Tract "F"*, and a *portion of the subdivisional lines, and surveyed Tracts 37, 38, and 39, in Township 1 North, Range 1 East,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

8-10-00

Date

M. Ross Workman

(Supervisory Cadastral Surveyor)

\_\_\_\_\_  
Date

\_\_\_\_\_  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of Tract "F"*, and a *portion of the subdivisional lines, and the survey of Tracts 37, 38, and 39, in Township 1 North, Range 1 East, Salt Lake Meridian, Utah,*

executed by *M. Ross Workman, Supervisory Cadastral Surveyor*

having been critically examined and found correct, are hereby approved

February 4, 2003

Date

Daniel W. Webb

(Chief Cadastral Surveyor for Utah)