

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY

OF

A PORTION OF THE EAST BOUNDRY (ASHLEY GUIDE MERIDIAN) ,

AND

A PORTION OF THE SUBDIVISIONAL LINES

AND

THE SUBDIVISION OF SECTIONS 13, 14 AND 23

IN

TOWNSHIP 3 SOUTH, RANGE 22 EAST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Merrill D. Cazier
Cadastral Surveyor

Under special instructions dated **May 26, 2000**, approved **May 26, 2000**,
which provided for the surveys included under Group Number **914**, and
assignment instructions dated **July 31, 2002**.

Survey commenced **August 5, 2002**
Survey completed **August 15, 2002**

INDEX DIAGRAM

Township 3 South, Range 22 East

6	5	4	3	2	1	
7	8	9	10	11	12	
				8	6	
18	17	16	15	8 14	4 13	2
				7	4	
19	20	21	22	12 23	3 24	
				6	3	
30	29	28	27	26	2 25	
31	32	33	34	35	36	

The Subdivision of Section 13.....Page 9
 The Subdivision of Section 14.....Page 10
 The Subdivision of Section 23.....Page 13

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of a portion of the east boundary (Ashley Guide Meridian), and a portion of the subdivisional lines, and the subdivision of sections 13, 14 and 23, in T. 3 S., R. 22 E., Salt Lake Meridian, Utah.

History of Surveys

Surveyed by	Retr. or Resurveyed by
SOUTH BOUNDARY	
All Jesson and Harmston 1900	
Portion	H.W. Miller 1911
All	J.L. Thomas 1985-1986
EAST BOUNDARY (Ashley Guide Meridian)	
All A.D. Ferron 1878	
All	Jesson and Harmston 1900
All	R.A. Zaninovich 1984
WEST BOUNDARY	
All Jesson and Harmston 1900	
Portion	R. Gentry 1920
Portion	J.L. Thomas 1973
Portion	J.L. Thomas 1985-1986
Portion	J.L. Thomas 1991
NORTH BOUNDARY	
All Jesson and Harmston 1906	
Portion	H.W. Miller 1911
All	J.C. Clark 1935
Portion	G.W. Hockstrasser 1965
SUBDIVISION	
Portion Jesson and Harmston 1906	
Portion H.W. Miller 1911	H.W. Miller 1911
Portion	G.W. Hockstrasser 1965
Portion	J.L. Thomas 1985

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 914, dated May 26, 2000.

This survey was executed with a Trimble 5700, Global Positioning System (GPS), using relative positioning techniques to establish a geographic position for each corner. The true geodetic mean bearing and the true horizontal ground distances were determined by inverting between the established positions.

Preliminary to the resurvey, the lines of prior surveys were retraced and a diligent search was made for all corners and other calls of record. Lost corners were reestablished and

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH

remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS) utilizing Continuously Operating Reference Stations (CORS) Midvale, Myton 1 and Carbon County Cou. The geographic position of the 1/4 section corner of sections 14 and 23, T. 3 S., R. 22 E., as determined, utilizing GPS, using RTK techniques, is as follows:

Latitude: 40°33'05.890" N. Longitude: 109°24'49.628" W.
Elevation 5500 feet, N.A.D. 1983 (1994)

Dependent Resurvey of a portion of the East Boundry
(Ashley Guide Meridian)

Reestablishment of the survey executed by A.D. Ferron in 1878, the dependent resurveys by Jensen and Harmston in 1900, and R.A. Zaninovich in 1984.

Chains

From the 1/4 section corner of section 13 and 18 on the east boundary of the township, monumented with an aluminum post, 2 1/2 inch diameter, firmly set, projecting 4 inches above ground, with aluminum cap marked as described in the official record of the 1984 resurvey.

Raised a mound of stone 3 foot base, 2 feet high, west of corner.

N. 0°00.7' W., between sections 13 and 18.

40.516 The corner of sections 7, 12, 13 and 18, on the east boundary, of the township, monumented with an aluminum post, 2 1/2 inch diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1984 resurvey.

Raised a mound of stone, 5 foot base, 2 1/2 foot high, west of corner.

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 3 South, Range 22 East, Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by Jesson and Harmston in 1906 and the Resurvey by J.L. Thomas in 1985.

From the 1/4 section corner of sections 25 and 26, monumented with an aluminum post, 2 1/2 inch diameter, firmly set, projecting 3 inches above ground, with aluminum cap marked as described in the official record of the 1985 resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH

Chains

N. 0°08.5' W., between sections 25 and 26.

- 40.080** Point selected for the witness corner of sections 23, 24, 25 and 26.

NOTE: The 1985 aluminum post was found laying in the wash, with aluminum cap marked as described in the official record of the 1985 resurvey.

Set the 1985 aluminum post, 24 inches in the ground, with a magnet at base, add the marks "2002, WC and an arrow" to the aluminum cap.

Set a steel fence post alongside.

- 40.280** True point for the corner of sections 23, 24, 25 and 26, at proportionate distance, falls on the edge of a wash which is an unsafe place for a monument.

From the W 1/16 section corner of sections 24 and 25, monumented with an aluminum post, 2 1/2 inch diameter, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1985 resurvey.

N. 89°54.4' W., between sections 24 and 25.

- 20.165** True point for the corner of sections 23, 24, 25 and 26.

N. 0°15.0'E., between sections 23 and 24.

- 20.010** The S 1/16 section corner of sections 23 and 24, monumented with an aluminum post, 2 1/2 inch diameter, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1985 resurvey.

N. 0°10.1'E beginning new measurement

- 20.010** The 1/4 section corner of sections 23 and 24 monumented with an aluminum post, 2 1/2 inch diameter, firmly set, projecting 2 inches above the ground, with aluminum cap marked as described in the official record of the 1985 resurvey.

N 0°02.8' W., beginning new measurement

- 20.132** The N 1/16 section corner of sections 23 and 24, monumented with an aluminum post, 2 1/2 inch diameter, firmly set, projecting 3 inches above ground, with aluminum cap, marked as described in the official record of the 1985 resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH

Chains

Raised a mound of stone 3 foot base, 1 1/2 feet high, west of corner.

N. 0°02.8'W., beginning new measurement

- 10.066** The N-N 1/64 section corner of sections 23 and 24, monumented with a 2 1/2 inch diameter aluminum post, firmly set, projecting 4 inches above ground, with aluminum cap, marked as described in the official record of the 1985 resurvey.

Corner falls in a hay field

Set a steel fence post alongside.

N. 0°02.8'W., beginning new measurement.

- 10.066** Point for the corner of sections 13, 14, 23 and 24, at proportionate distant; there is no remaining evidence of original corner, not monumented.

Corner falls in a cultivated field.

From the 1/4 section corner of sections 13 and 24, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with aluminum cap marked as described in the official record of the 1985 resurvey.

Raise a mound of stone, 3 foot base, 2 feet high, north of corner.

N. 89°18.5' W., between sections 13 and 24.

- 20.125** The W 1/16 section corner of sections 13 and 24, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 5 inches above ground, with aluminum cap marked as described in the official record of the 1985 resurvey.

A 5 inch diameter cedar post projecting 6 feet above ground, is 1 foot west of corner.

Raised a mound of stone, 3 foot base, 1 1/2 feet high north of corner.

N. 89°18.5'W., beginning new measurement.

- 20.125** The point for the corner of sections 13, 14, 23 and 24.
-

Reestablishment of the Survey Executed by
Jessen and Harmstom in 1906.

N. 0°10.7' E., between sections 13 and 14.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH

Chains

20.132 Point for the S 1/16 section corner of sections 13 and 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

```

T3S R22E
  S1/16
S14 | S13
    |
    2002

```

40.264 The 1/4 section corner of sections 13 and 14, monumented with an aluminum post, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1985 resurvey.

Raised a mound of stone, 3 foot base, 1 1/2 feet high, west of corner.

A sheep fence runs north and south, 1 foot west of corner.

N. 0°00.6' W. beginning new measurement

20.088 Point for the N 1/16 section corner of sections 13 and 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, in a mound of stone 3 foot base to top of aluminum cap, marked:

```

T3S R22E
  N1/16
S14 | S13
    |
    2002

```

40.176 The corner of sections 11, 12, 13 and 14, monumented with a sandstone 19X10X6 inches, firmly set, plainly marked with 4 grooves on south and 1 groove on the east faces.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

```

T3S R22E
S11 | S12
---+---
S14 | S13
    |
    2002

```

Bury the marked stone alongside.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH

Chains

Raised a mound of stone 3 foot base, 1 1/2 feet high, west of corner.

From the corner of sections 7, 12, 13 and 18, on the east boundary of the township, hereinbefore described.

N. 86°36.3' W., between sections 12 and 13.

- 40.135** The 1/4 section corner of sections 12 and 13, monumented with a sandstone 14X8X3 inches, dimly marked 1/4, lying loose on the ground, with mound of stone to north, 2 foot base, 1 foot high.

At the corner point

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 22 inches in the ground with magnet at base, with aluminum cap marked:

T3S R22E
S12
1/4 ———
S13
2002

Bury the marked stone alongside,

Raised a mound of stone 3 foot base, 1 1/2 feet, north of the corner.

S. 87°17.1' W., beginning new measurement.

- 40.253** The corner of sections 11, 12, 13 and 14.
-

From the true point for the corner of sections 23, 24, 25 and 26.

N. 89°52.7' W., between sections 23 and 26.

- 40.090** The 1/4 section corner of sections 23 and 26, monumented with a sandstone 14X10X3 inches dimly marked 1/4, loosely set with remnants of a mound of stone to north.

At corner point

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T3S R22E
S23
1/4 ———
S26
2002

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH

Chains

Raised a mound of stone 2 foot base, 1 foot high north of corner.

Bury marked stone alongside.

From the point for the corner of sections 13, 14, 23 and 24.

S. 89°42.5' W., between sections 14 and 23.

5.0105 Point for the E-E-E 1/256 section corner of sections 14 and 23.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T3S R22E
S14
E-E-E 1/256
S23
2002

10.021 Point for the E-E 1/64 section corner of sections 14 and 23, not monumented.

20.042 Point for the E 1/64 section corner of sections 14 and 23.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with a magnet at base, with aluminum cap marked:

T3S R22E
S 14
E1/16 ———
S 23
2002

Raised a mound of stone, 3 foot base, 1 foot high, north of corner.

40.084 The 1/4 section corner of sections 14 and 23, monumented with a 2 1/2 inch diameter aluminum post, firmly set, projecting 3 inches above ground, with aluminum cap, marked as described in the official record of the 1985 resurvey.

Raised a mound of stone 3 foot base, 1 foot high, north of corner.

Note: a 5/8 inch rebar with a 1 1/2 inch brass cap, falls northeasterly 0.3 feet, with the brass cap marked:

RLS UINTAH COUNTY SUR.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH

Chains

From the 1/4 section corner of sections 14 and 15, monumented with a sandstone 16X12X5 inches, dimly marked 1/4 on west face firmly set in the ground.

At corner point

Set an aluminum post 30 inches long, 2 1/2 inch diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T3S	R22E
	1/4
S15	S14
	2002

Bury marked stone alongside

Raised a mound of stone, 3 foot base, 1 foot high, west of corner.

N.0°53.6' W., between sections 14 and 15.

39.260

The corner of sections 10, 11, 14 and 15 monumented with a sandstone 18X8X6 inches, loosely set in ground, marked 4 grooves and 2 grooves.

At corner point

Set an aluminum post 30 inches long, 2 1/2 inch diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T3S	R22E
S10	S11
S15	S14
	2002

Bury marked stone alongside

Set a steel fence post alongside.

From the corner of sections 11, 12, 13 and 14.

S. 89°03.6' W., between sections 11 and 14.

20.177

True point for the E 1/16 section corner of sections 11 and 14, point falls in N and S dirt road.

From which

An aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, for a reference monument, near a north gate post, bears

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH

Chains

N. 74°41.1' W., 27.0 links distance, with aluminum cap marked: T3S R22E E1/16 S11 RM 17.8 FT 2002 and an arrow pointing to the corner.

An aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in ground, with a magnet at base, for a reference monument near a south gate post, bears S. 38° 54.0' W., 33.3 links distance, with aluminum cap marked: T3S R22E E1/16 S14 RM 21.9 FT 2002 and an arrow pointing to the corner.

40.354 True point for the 1/4 section corner of sections 11 and 14, at proportionate distance; falls in cultivated alfalfa field. There is no remaining evidence of the original corner.

Point selected for an off line witness corner to the 1/4 section corner, bears N. 69°30.7' W., 1.285 chains distance.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

WC
T3S R22E
S11
→
1/4
S14
2002

Set a steel fence post alongside.

80.708 The corner of sections 10, 11, 14 and 15.

The Subdivision of Section 13,
Township 3 South, Range 22 East, Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 13 and 24.

N. 0°03.7' E., on the North-South center line of section 13.

20.172 Point for the center S 1/16 section corner of section 13, not monumented.

40.344 Point for the center 1/4 section corner of section 13 at intersection with the East-West center line.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, and in a mound of stone, 4 foot base to top of aluminum cap, marked:

THE SUBDIVISION OF SECTION 13,
TOWNSHIP 3 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH

Chains

T3S R22E
S13
C1/4
2002

82.832 The 1/4 section corner of sections 12 and 13.

From the 1/4 section corner of sections 13 and 18 on the east boundary of the township, hereinbefore described.

N. 89°25.4' W., on the East-West center line of section 13.

40.125 The center 1/4 section corner of section 13.

60.206 Point for the center W 1/16 section corner of section 13, not monumented.

80.287 The 1/4 section corner of sections 13 and 14.

From the W 1/16 section corner of sections 13 and 24.

N. 0°07.2' E., on the North-South center line of the SW 1/4 of section 13.

20.152 Point for the SW 1/16 section corner of section 13, at intersection with the East-West center line of the SW 1/4.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, to solid rock, with a magnet at base in a mound of stone, 3 foot base to top of aluminum cap, marked:

T3S R22E
S13
SW 1/16
2002

40.304 The point for the center W 1/16 section corner of section 13.

From the point for the center S 1/16 section corner of section 13.

N. 89°21.9' W., on the East-West center line of the SW 1/4 of section 13.

20.103 The SW 1/16 section corner of section 13.

40.206 The S 1/16 section corner of sections 13 and 14.

The Subdivision of Section 14,
Township 3 South, Range 22 East, Salt Lake Meridian, Utah.

THE SUBDIVISION OF SECTION 14,
TOWNSHIP 3 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH

Chains

From the 1/4 section corner of sections 14 and 23.

N. 0°06.7' W., on the North-South center line of section 14.

20.132 Point of the center S 1/16 section corner of section 14.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T3S R22E
S14
C-S 1/16
2002

40.264 Point of the center 1/4 section corner of section 14, at intersection with the East-West center line.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T3S R22E
S14
C 1/4
2002

Raised a mound of stone 2 foot base, 1 foot high west of corner.

A 4-strain barbed wire fence runs North and South, 4 feet east of corner.

60.122 Point for the center N 1/16 section corner of section 14, not monumented.

79.980 The true point for the 1/4 section corner of sections 11 and 14.

From the 1/4 section corner of sections 13 and 14.

S 89°42.8' W., on the East-West center line of section 14.

20.141 Point for the center E 1/16 section corner of section 14, not monumented.

40.282 The center 1/4 section corner of section 14.

80.099 The 1/4 section corner of sections 14 and 15.

From the point of the center E 1/16 section corner of section 14.

N. 0°03.6' W., on the North-South center line of the NE 1/4 of section 14.

THE SUBDIVISION OF SECTION 14,
TOWNSHIP 3 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH

*Chains***19.973**

Point for the NE 1/16 section corner of section 14, at intersection with the E-W center line of the NE 1/4.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T3S R22E
NE 1/16
S14
2002

Raised a mound of stone 3 foot base, 1 foot high, west of the corner.

39.946

The E 1/16 section corner of sections 11 and 14.

From the N 1/16 section corner of sections 13 and 14.

S. 89°23.1' W., on the East-West center line of the NE 1/4 of section 14.

20.158

The NE 1/16 section corner of section 14.

40.316

The point for the center N 1/16 section corner of section 14.

From the E 1/16 section corner of sections 14 and 23.

N. 0°02.1' E., on the North-South center line of the SE 1/4 of section 14.

20.132

Point for the SE 1/16 section corner of section 14, at intersection of the East-West center line of the SE 1/4.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T3S R22E
S14
SE 1/16
2002

Raised a mound of stone 3 foot base, 1 foot high, west of the corner.

40.264

The point for the center E 1/16 section corner of section 14.

From the S 1/16 section corner of sections 13 and 14.

S. 89°42.6' W., on the East-West center line of the SE 1/4 of section 14.

THE SUBDIVISION OF SECTION 14,
TOWNSHIP 3 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH

Chains

- 20.091** The SE 1/16 section corner of section 14.
40.182 The center S 1/16 section corner of section 14.

The Subdivision of Section 23,
Township 3 South, Range 22 East, Salt Lake Meridian, Utah.

- From the 1/4 section corner of sections 23 and 26.
N. 0° 04.8' E., on the North-South center line of section 23.
- 39.951** Point for the center 1/4 section corner of section 23, at intersection with the East-West center line.
Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, in a mound of stone, 3 foot base to top of aluminum cap, marked:

T3S R22E
C 1/4
S23
2002

- 60.057** Point for the center N 1/16 section corner of section 23, not monumented.
80.163 The 1/4 section corner of sections 14 and 23.

- From the 1/4 section corner of sections 23 and 24.
S. 89°46.9 W., on the East-West center line of section 23.
- 20.088** Point for the center E 1/16 section corner of section 23, not monumented.
40.176 The center 1/4 section corner of section 23.
80.291 The 1/4 section corner of sections 22 and 23, monumented with a limestone 13X12X3 inches, dimly marked, 1/4 on east face, firmly set in the ground, with mound of stone to west, 2-foot base, 1 foot high.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T3S R22E
1/4
S22 | S23
2002

Bury marked stone alongside

THE SUBDIVISION OF SECTION 23,
TOWNSHIP 3 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH

Chains

Raised a mound of stone 3 foot base, 1½ feet high west of corner.

From the point of the center E 1/16 section corner of section 23.

N. 0°01.0' E., on the North-South center line of the NE 1/4 of section 23.

- 20.119** Point of the NE 1/16 section corner of section 23, at intersection with the East-West center line of the NE 1/4.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T3S R22E
NE 1/16
S23
2002

Raised a mound of stone 2 foot base, 1 foot high, west of the corner

- 30.178** Point for the C-N-NE 1/64 section corner of section 23, not monumented.

- 40.237** The E 1/16 section corner of sections 14 and 23.

From the N 1/16 section corner of sections 23 and 24.

S. 89°44.7' W., on the East-West center line of the northeast 1/4 of section 23.

- 10.032** Point for the C-E-NE 1/64 section corner of section 23, not monumented.

- 20.064** The NE 1/16 section corner of section 23.

- 40.129** The point of the center N 1/16 section corner of section 23.

From the point of the C-E-NE 1/64 section corner of sections 23.

N. 0°00.9' W., on the North-South center line of the NE 1/4 of the NE 1/4 of section 23.

- 10.062** Point for the NE-NE 1/64 section corner of section 23, at the intersection with the East-West center line of the NE 1/4 of the NE 1/4, not monumented.

- 20.124** The point for the E-E 1/64 section corner of sections 14 and 23.

THE SUBDIVISION OF SECTION 23,
TOWNSHIP 3 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the N-N 1/64 section corner of sections 23 and 24.

S. 89°43.6' W., on the East-West center line of the NE 1/4 of the NE 1/4 of section 23.

5.013 Point for the C-E-NE-NE 1/256 section corner of section 23.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T3S R22E
S23
C-E-NE-NE 1/256
2002

10.026 The point for the NE-NE 1/64 section corner of section 23.

20.053 The point for the C-N-NE 1/64 section corner of section 23.

From the C-E-NE-NE 1/256 section corner of section 23.

N. 0° 01.9' W., on the North-South center line of the NE 1/4 of the NE 1/4 of the NE 1/4 of section 23.

10.064 The E-E-E 1/256 section corner of sections 14 and 23.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Brandon S. Sanchez	Survey Tech.
Tyler G. Trujillo	Survey Aid

CERTIFICATE OF SURVEY

I, **Merrill D. Cazier, Cadastral Surveyor**, hereby certify upon honor that, in pursuance of special instructions bearing the date of the **26th day of May, 2000**, I have, **dependently resurveyed a portion of the east boundary (Ashley Guide Meridian), and a portion of the subdivisional lines, and the subdivision of sections 13, 14, and 23 in Township 3 South, Range 22 East**, of the **Salt Lake Meridian**, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

1-28-04

Date

Merrill D. Cazier

(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the **dependent resurvey of a portion of the East boundary (Ashley Guide Meridian), and a portion of the subdivisional lines, and the subdivision of section 13, 14 and 23, in Township 3 South, Range 22 East, Salt Lake Meridian, Utah, under group number 914.**

executed by **Merrill D. Cazier, Cadastral Surveyor**

having been critically examined and found correct, are hereby approved.

February 2, 2004

Date

Daniel W. Welch

(Chief Cadastral Surveyor for Utah)