

United States
Department of the Interior
Bureau of Land Management

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,

AND

A PORTION OF THE SUBDIVISIONAL LINES

IN

TOWNSHIP 12 SOUTH, RANGE 1 WEST

OF THE SALT LAKE MERIDIAN

IN THE STATE OF UTAH

EXECUTED BY

John F. Carroll
Cadastral Surveyor

Under special instructions dated and approved **June 1, 2001** and supplemental special instructions dated and approved **December 19, 2001**, which provided for the survey included under Group No. **933**, and assignment instructions dated **June 6, 2001**.

Survey commenced **December 19, 2001**

Survey completed **December 19, 2001**

INDEX DIAGRAM

Township 12 South, Range 1 West

	3	4			
6	5 7	4	3	2	1
7	8 5	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

TOWNSHIP 12 SOUTH, RANGE 1 WEST, SALT LAKE MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of a portion of the north boundary, and a portion of the subdivisional lines in T. 12 S., R. 1 W., Salt Lake Meridian, Utah. This resurvey was requested by B.L.M. - Fillmore District because of discrepancies discovered by field investigation with the 1920-21 resurvey record.

History of Surveys

	Surveyed by		Retr. or Resurveyed by	
SOUTH BOUNDARY				
Portion	C.L. Craig	1856		
Portion	A.J. Stewart, Jr.	1878	A.J. Stewart Jr.	1878
Portion			E.W. Koeber	1884
Portion			J.C. Thoma and	1920-21
			H.W. Miller	
Portion			R.A. Zaninovich	1991-92
Portion			F.D. Reynolds	1996
EAST BOUNDARY				
All	C.L. Craig	1856		
WEST BOUNDARY				
All	A.J. Stewart, Jr.	1878		
Portion (concurrently)			J.F. Carroll	2001
NORTH BOUNDARY				
Portion	C.L. Craig	1856		
Portion	A.J. Stewart	1878	A.J. Stewart, Jr.	1878
Portion	J.C. Thoma	1920-21	J.C. Thoma and	1920-21
			H.W. Miller	
Portion			F.D. Reynolds	1994-95
Portion			J.L. Thomas	1987
SUBDIVISION				
Portion	C.L. Craig	1856		
Portion	A.J. Stewart, Jr.	1878		
Portion	J.C. Thoma	1920-21	J.C. Thoma	1920-21
	H.W. Miller		H.W. Miller	
Portion			F.D. Reynolds	1995

TOWNSHIP 12 SOUTH, RANGE 1 WEST, SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 933, dated June 1, 2001 and Supplemental Special Instructions dated December 19, 2001.

The direction of the lines were determined by mean geodetic inverse bet. cors. Global Positioning System (GPS) utilizing Real-time kinematic (RTK) was used throughout the survey. Cadastral Measurement Management (CMM) was utilized during the course of the survey.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the cor. of T. 12 S., Rs. 1 and 2 W., as determined by a tie to the National Geodetic Survey Control Station "CAPPS", utilizing GPS, using RTK techniques, is as follows:

Latitude: 39°48'11.718" N. Longitude: 111°59'21.303" W.

The geographic position of National Geodetic Survey Control Station "CAPPS" is as follows:

Latitude: 39°39'43.87548" N. Longitude: 112°02'47.39982" W.
N.A.D. 1983 (1994)

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 12 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the North Boundary,
T. 12 S., R. 1 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by A.J. Stewart, Jr.
in 1878 and the Resurvey Executed by J.C. Thoma in 1920-21

Beginning at the cor. of T. 12 S., Rs. 1 and 2 W., monumented with a stainless steel post, 2 ½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the field notes of the 1987 resurvey record, with a steel fence post alongside the stainless steel post.

Cor. is located on a steep east slope.

N. 88°01.5' E., on the south bdy. of sec. 31, T. 11 S., R. 1 W.

34.610 The 1/4 sec. cor. of sec. 31 only, T. 11 S., R. 1 W., monumented with an iron post, 1 in. diam., firmly set, bent flush with the ground, with brass cap mkd. as described in the field notes of the 1920-21 resurvey record.

At the corner point, remove the damaged iron post and in place

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T 11 S R 1 W
1/4 S 31

T 12 S
2001

Note: The damaged iron post was not buried alongside the aluminum post.

Cor. is located on a flat in a burned area.

N. 88°03.5' E., beginning new measurement.

4.740 The 1/4 sec. cor. of sec. 6 only, T. 12 S., R. 1 W., monumented with an iron post, 1 in. diam., firmly set, flush with the ground, with brass cap mkd. as described in the field notes of the 1920-21 resurvey record.

Cor. is located on a flat in a burned area.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 12 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 88°44.5' E., beginning new measurement.

- 35.248** The cor. of secs. 31 and 32, T. 11 S., R. 1 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, 4 ft. diam., with brass cap mkd. as described in the field notes of the 1920-21 resurvey record, with a steel fence post alongside the mound of stone.

Cor. is located on a SW slope in a burned area.

N. 89°00.2' E., on the south bdy. of sec. 32, T. 11 S., R. 1 W.

- 4.330** The cor. of secs. 5 and 6, T. 12 S., R. 1 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, 4 ft. diam., with a brass cap mkd. as described in the field notes of the 1920-21 resurvey record, with a steel fence post alongside the mound of stone.

Cor. is located on a SW slope in a burned area.

N. 88°31.1' E., beginning new measurement.

- 35.431** The 1/4 sec. cor. of sec. 32 only, T. 11 S., R. 1 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, 4 ft. diam., with brass cap mkd. as described in the field notes of the 1920-21 resurvey record, with a steel fence post alongside the mound of stone.

Cor. is located on a SW slope in a burned area.

N. 88°11.7' E., beginning new measurement.

- 4.012** The 1/4 sec. cor. of sec. 5 only, T. 12 S., R. 1 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the field notes of the 1920-21 resurvey record, with a steel fence post alongside the iron post.

Cor. is located on a SE slope in a burned area.

N. 88°23.7' E., beginning new measurement.

- 36.042** The cor. of secs. 32 and 33, T. 11 S., R. 1 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 24 ins.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 12 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

above ground, in a mound of stone, 4 ft. diam., with brass cap mkd. as described in the field notes of the 1920-21 resurvey record, with a steel fence post alongside the mound of stone.

Cor. is located on a SW slope in a burned area.

N. 88°27.5' E., on the south bdy. of sec. 33.

- 3.864** The cor. of secs. 4 and 5, T. 12 S., R. 1 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, with brass cap mkd. as described in the field notes of the 1920-21 resurvey record.

Cor. is located on a SW slope in a burned area.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 12 S., R. 1 W., Salt Lake Meridian, Utah

Dependent Resurvey of the Survey Executed by
A.J. Stewart, Jr. in 1878 and the Resurvey
Executed by J.C. Thoma in 1920-21

From the cor. of secs. 8 and 17, monumented with a trachyte stone, 14X8X6 ins., firmly set, dimly mkd. with 4 notches on the east and south edges, in a mound of stone, 3 ft. diam., at the intersection of fences bearing E, W, and N.

Note: No remains of the 1920 iron post was recovered.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

```

T 12 S R 1 W
  |
  | S 8
  |
  |-----| S 16
  |
  | S 17
  |
  | 2001

```

Bury the mkd. stone on the north side of the aluminum post.

Rebuild reference mound of stone around the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on a southerly slope.

N. 1'09.7' W., on the east bdy. of sec. 8.

- 8.612** The cor. of secs. 9 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, 4 ft. diam., with brass cap mkd. as described in the field notes of the 1920-21 resurvey record, with a steel fence post alongside the mound of stone.

Cor. is located on a SE slope.

N. 1'47.0' W., beginning new measurement.

- 31.261** The 1/4 sec. cor. of sec. 8 only, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, 4 ft. diam., with brass cap mkd. as described in the field notes of the 1920-21 resurvey record, with a steel fence post alongside the mound of stone.

Cor. is located on top of a ridge, bears NE and SW.

N. 2'02.2' W., beginning new measurement.

- 8.629** The 1/4 sec. cor. of sec. 9 only, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. as described in the field notes of the 1920-21 resurvey record, with a steel fence post alongside the iron post.

Cor. is located on a NW slope.

N. 1'44.5' W., beginning new measurement.

- 31.377** The cor. of secs. 5 and 8, monumented with a trachyte stone, 14X8X6 ins., firmly set, clearly mkd. with 5 notches on the south and 4 notches on the east edges, with a steel fence post along the east side, with a reference mound of stone to the west. Note: In the center of the reference mound of stone is an unrecorded iron pipe, 3 ins. diam., firmly set, projecting 6 ins. above ground.


Note: No remains of the 1920 iron post was recovered.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 21 ins. in the ground with magnet at base, and in a mound of stone, 2 ft. diam., with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS



Bury the mkd. stone on the south side of the aluminum post.

Bury the iron pipe on the west side of the aluminum post.

Rebuild reference mound of stone around the aluminum post.

Cor. is located on a SW slope in sagebrush and thick cedar to the N.

N. 1°31.7' W., on the east bdy. of sec. 5.

- 8.688** The cor. of secs. 4 and 9, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with a steel fence post alongside, with a brass cap mkd. as described in the field notes of the 1920-21 resurvey record.


Cor. is located on a SW slope in cedar.

N. 1°09.3' W., beginning new measurement.

- 31.531** The 1/4 sec. cor. of sec. 5 only, monumented with a trachyte stone, 24X18X20 ins., clearly mkd. 1/4 on west face, with a steel fence post alongside, with a reference mound of stone to the west.

Note: No remains of the 1920 iron post was recovered.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, and in a mound of stone, 4 ft. diam., to top, with aluminum cap mkd.



Bury mkd. stone, marks down, alongside aluminum post.

Rebuild reference mound of stone around aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on a westerly slope in burned cedar.

N. 0°51.7' W., beginning new measurement.

- 8.534** The 1/4 sec. cor. of sec. 4 only, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, 3 ft. diam., with brass cap mkd. as described in the field notes of the 1920-21 resurvey record, with a steel fence post alongside the mound of stone.

Cor. is located on a westerly slope in burned cedar.

N. 0°46.0' W., beginning new measurement.

- 31.821** The cor. of secs. 4 and 5, T. 12 S., R. 1 W., hereinbefore described.
-

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Jeremy Davis	Survey Aid

CERTIFICATE OF SURVEY

I, **John F. Carroll, Cadastral Surveyor**, hereby certify upon honor that, in pursuance of special instructions bearing the date of the 1st day of June, 2001 and supplemental special instructions bearing the date of the **19th of December, 2001**, I have **dependently resurveyed a portion of the north boundary and a portion of the subdivisional lines, in Township 12 South, Range 1 West,**

of the **Salt Lake** Meridian, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

02/25/04

Date

John F. Carroll
(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the **dependent resurvey of a portion of the north boundary, and a portion of the subdivisional lines, in Township 12 South, Range 1 West, Salt Lake Meridian, Utah,**

executed by **John F. Carroll, Cadastral Surveyor**

having been critically examined and found correct, are hereby approved.

September 20, 2004

Date

Daniel W. Webb

(Chief Cadastral Surveyor for Utah)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,

AND

A PORTION OF THE SUBDIVISIONAL LINES

AND THE SUBDIVISION OF SECTIONS 10, 13, 14, AND 15,

IN

TOWNSHIP 12 SOUTH, RANGE 2 WEST

OF THE SALT LAKE MERIDIAN

IN THE STATE OF UTAH

EXECUTED BY

John F. Carroll
Cadastral Surveyor

Under special instructions dated and approved **June 1, 2001** and approved **June 1, 2001**, which provided for the survey included under Group No. **933**, and assignment instructions dated **June 6, 2001**.

Survey commenced **June 20, 2001**
Survey completed **September 17, 2001**

INDEX DIAGRAM

Township 12 South, Range 2 West

6	5	4	3 19	2 11 15	1 6 10
7	8	9 18 19	10 14 17	11 10 13	12 5 9
18	17	16 16	15 11 15	14 8	13 3 7
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

The Subdivision of Section 10.....Page 20
 The Subdivision of Section 13.....Page 21
 The Subdivision of Section 14.....Page 22
 The Subdivision of Section 15.....Page 24

TOWNSHIP 12 SOUTH, RANGE 2 WEST, SALT LAKE MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of a portion of the east boundary, and a portion of the subdivisional lines, and the subdivision of sections 10, 13, 14 and 15, of T. 12 S., R. 2 W., Salt Lake Meridian, Utah.

History of Earlier Surveys

	Surveyed by		Retr. or Resurveyed by	
SOUTH BOUNDARY				
Portion	A.J. Stewart, Jr.	1878		
Portion	Stewart and Stewart	1898		
Portion			E. Bird and A. Nelson	1944
Portion			R.A. Zaninovich	1991-92
EAST BOUNDARY				
All	A.J. Stewart, Jr.	1878		
WEST BOUNDARY				
Portion	J. Gorlinski	1873		
All	E. Bird and A. Nelson	1944	E. Bird and A. Nelson	1944
NORTH BOUNDARY				
Portion	J. Gorlinski	1873		
All	A.J. Stewart, Jr.	1878	A.J. Stewart, Jr.	1878
Portion			H.D. Heist	1903
Portion			J.C. Thoma and	
			H.W. Miller	1921
Portion			E. Bird and A. Nelson	1944
Portion			J.L. Thomas	1987
SUBDIVISION				
Portion	A.J. Stewart	1878		
Portion	E. Bird and A. Nelson	1944	E. Bird and A. Nelson	1944
Portion			M.R. Workman and	1996
			R.K. Baugh	

TOWNSHIP 12 SOUTH, RANGE 2 WEST, SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 933, dated June 1, 2001.

The direction of the lines were determined by mean geodetic inverse bet. cors. Global Positioning System (GPS) utilizing Real-time kinematic (RTK) was used throughout the survey. Cadastral Measurement Management (CMM) was utilized during the course of the survey.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the cor. of secs. 15, 16, 21 and 22, T. 12 S., R. 2 W., as determined by a tie to the National Geodetic Survey Control Station "CAPPS", utilizing GPS, using RTK techniques, is as follows:

Latitude: 39°45'32.386" N. Longitude: 112°02'39.824" W.
N.A.D. 1983 (1994)

The geographic position of National Geodetic Survey Control Station "CAPPS" is as follows:

Latitude: 39°39'43.87548" N. Longitude: 112°02'47.39982" W.
N.A.D. 1983 (1994)

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the East Boundary,
T. 12 S., R. 2 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
A.J. Stewart, Jr. in 1878

Beginning at the cor. of secs. 13, 18, 19 and 24, T. 12 S., Rs. 1 and 2 W., monumented with an aluminum post, 2 3/4 ins. diam., firmly set, projecting 8 ins. above ground, with aluminum cap mkd. T 12 S S13 S18 R2W R1W S24 S19 1985, in a mound of stone, 3 ft. diam., with a trachyte stone, 16X10X5 ins., clearly mkd. with 3 notches on one side and 3 notches on the opposite side, on the westside of the aluminum post and in the mound of stone, and is accepted as a careful and faithful perpetuation of the original cor. Not remonumented.

from which the local reference objects

A cedar fence post, 7 ins. diam., bears North, 17 lks. dist., to a double head nail on the east side of the cedar fence post.

A cedar fence post, 7 ins. diam., bears N. 60° E., 28 1/2 lks. dist., to a double head nail on the south side of the cedar fence post.

A cedar fence post, 5 ins. diam., bears South, 12 1/2 lks. dist. to a double head nail.

A cedar fence post, 5 ins. diam., bears South, 28 1/2 lks. dist., to a double head nail.

A cedar fence post, 4 ins. diam., bears N. 30° W., 2 1/2 lks. dist., to a double head nail,

Cor. is located at the intersection of fences bearing N, N. 60° E., South and West.

N. 1°01.5' W., bet. secs. 13 and 18.


- 20.035** The S 1/16 sec. cor. of secs. 13 and 18, monumented with an unrecorded rebar, 3/8 in. diam., firmly set, projecting 3 ins. above ground, and is accepted as a faithful and careful establishment of the cor.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, and in a collar of stone, to top, with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS



Bury rebar inside aluminum post.

Drive a steel fence post along the southwest side of the aluminum post.


Cor. is located 60 ft., S. 60' E., of fences bearing N, S and W.

N. 1'01.5' W., beginning new measurement.

- 20.035** The 1/4 sec. cor. of secs. 13 and 18, monumented with an unrecorded rebar, 3/8 in. diam., firmly set, projecting 3 ins. above ground, with a trachyte stone, 14X12X8 ins., mkd. 1/4 on one side, on the west side of the rebar, in a collar of stone, and the rebar is accepted as a careful and faithful perpetuation of the original cor.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, and in a collar of stone, 1 ft. diam., with aluminum cap mkd.:



Bury rebar inside aluminum post.

Bury mkd. stone on west side of aluminum post.

Drive a steel fence post alongside the aluminum post.

Cor. is located 120 ft. East of a fence, bears N and S.

N. 1'12.1' W., beginning new measurement.

- 40.065** Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist.; there is no remaining evidence of the original cor.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with aluminum cap mkd.:

T 12 S	
R 2 W	R 1 W
S 12	S 7

S 13	S 18
2001	

Drive a steel fence post alongside the aluminum post.

Cor. is located on a flat, 20 ft. South of a fence, bears E and W, and 25 ft. South of a dirt road, 7 ft. wide, bears E and W.

N. 1'12.1' W., bet. secs. 7 and 12.

- 40.065** Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with aluminum cap mkd.:

T 12 S	
R 2 W	R 1 W
1/4	
S 12	S 7
2001	

Drive a steel fence post along the southeast side of the aluminum post.

Cor. is located on a flat in grass and scattered sagebrush, 120 ft. East of a fence, bears N and S.

- 80.130** The cor. of secs. 1, 6, 7 and 12, monumented with an unrecorded rebar, 3/8 in. diam., firmly set, projecting 3 ins. above ground, with a trachyte stone, 16X10X6 ins., with 5 notches on one side and 1 notch on the opposite side, on the north side of the rebar, in a mound of stone, 3 ft. diam., and the rebar is accepted as a faithful and careful perpetuation of the original cor.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground with magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T 12 S	
R 2 W	R 1 W
S 1	S 6
S 12	S 7
2001	

Bury rebar inside aluminum post.

Bury mkd. stone on north side of aluminum post.

Drive a steel fence post on the southwest side of the aluminum post.

Cor. is located on a rocky northeast slope, and 4 ft. East of an electric fence, bears N and S.

N. 1'16.7' W., bet. secs. 1 and 6.

- 39.818** Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, and in a mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:

T 12 S	
R 2 W	R 1 W
1/4	
S 1	S 6
2001	

Drive a steel fence post alongside the aluminum post.

Cor. is located on a southwest slope in an old fence line.

- 79.636** The cor. of T. 12 S., Rs. 1 and 2 W., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the field notes of the 1987 resurvey record, with a steel fence post alongside the stainless steel post.

Cor. is located a steep east slope.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 12 S., R. 2 W., Salt Lake Meridian, Utah

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Reestablishment of the Survey Executed by
A.J. Stewart, Jr. in 1878

From the cor. of secs. 13, 18, 19 and 24, on the east bdy. of
the tp., hereinbefore described.

S. 87°37.2' W., bet. secs. 13 and 24.

- 39.872** Point for the 1/4 sec. cor. of secs. 13 and 24, at
proportionate dist.; there is no remaining evidence of the
original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins.
in the ground with magnet at base, with aluminum cap mkd.:

T 12 S R 2 W
S 13
1/4 —————
S 24
2001

Drive a steel fence post on the south side of the aluminum
post.

- 79.744** The cor. of secs. 13, 14, 23 and 24, monumented with a trachyte
stone, 16X10X8 ins., clearly mkd. with 3 notches on the south
and 1 notch on the east edges, in a mound of stone, 4 ft.
diam., from which the original bearing trees

A cedar, 10 ins. diam., bears N. 60° E., 14 lks. dist.,
with illegible scribe mks. visible on a partially healed
blaze. (Record; N. 38° E., 11 lks. dist.)

A cedar, 9 ins. diam., bears N. 50° W., 18 lks. dist.,
with illegible scribe marks visible on a partially healed
blaze. (Record; N. 52° W., 15 lks. dist.)


A cedar branch, 6 ins. diam., bears S. 3° W., 30 1/2 lks.
dist., with illegible scribe marks and scribe mks. BT
visible on a partially healed blaze. (Record; S. 10° W.,
20 lks. dist.) Note: The 6 ins. diam. cedar branch is on
a 16 ins. diam. cedar tree.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins.
in the ground to solid rock with magnet at base, and in a
supporting mound of stone, 4 ft. diam., to top, with aluminum
cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS



Bury mkd. stone alongside the aluminum post.


Drive a steel fence post on the northeast side of the aluminum post.

Cor. is located on a northerly slope in dense cedar.

N. 2°27.1' W., bet. secs. 13 and 14.

20.171 Point for the S 1/16 sec. cor. of secs. 13 and 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to solid rock with magnet at base, and in a supporting mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:




Drive a steel fence post on the south side of the aluminum post.

Cor. is located on a northeast slope, 60 ft. South of a draw, drains S. 40° E. and approximately 160 ft. South of a fence bears E and W.

40.342 Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:



Drive a steel fence post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on a SE slope in burned cedar.

- 80.684** Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T 12 S R 2 W	
S 11	S 12
S 14	S 13
2001	

Drive a steel fence post along the SW side of the aluminum post.

Cor. is located on a slight southerly slope in dense cedar.

From the cor. of secs. 7, 12, 13 and 18, on the east bdy. of the tp., hereinbefore described.

S. 88°03.9' W., bet. secs. 12 and 13.

- 41.555** The 1/4 sec. cor. of secs. 12 and 13, monumented with a trachyte stone, 14X9X6 ins., loosely set, clearly mkd. 1/4 on north face, in an embedded mound of stone.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground with magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T 12 S R 2 W	
S 12	
1/4	
S 13	
2001	

Bury mkd. stone, marks down, on the north side of the aluminum post.

Drive a steel fence post on the west side of the aluminum post.

Cor. is located on a NE slope in scattered cedar.

S. 87°58.2' W., beginning new measurement.

- 40.043** The cor. of secs. 11, 12, 13 and 14.


DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0°18.2' W., bet. secs. 11 and 12.

- 40.306** Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with 60 D penny nail at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:




Drive a steel fence post on the south side of the aluminum post.

Cor. is located on a W slope in dense cedar.

- 80.612** Point for the cor. of secs. 1, 2, 11 and 12, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, and in a mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:



Cor. is located on a SE slope, 12 ft. East of a fence, bears N and S, and 130 ft. South of a draw, drains S. 20° E.

From the cor. of secs. 1, 6, 7 and 12, on the east bdy. of the tp., hereinbefore described.

S. 88°20.6' W., bet. secs. 1 and 12.

- 40.156** Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, with a reference mound of stone, 4 ft. diam., to the north, with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T 12 S R 2 W
S 1
1/4 —————
S 12
2001

Drive a steel fence post along the southeast side of the aluminum post.

Cor. is located on a gentle east slope in cedar in a railed area.

80.312 The cor. of secs. 1, 2, 11 and 12.

N. 0°54.3' W., bet. secs. 1 and 2.

40.310 Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, and in a mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:

T 12 S R 2 W
1/4
S 2 | S 1
2001

Drive a steel fence post alongside the aluminum post.

Cor. is located on a steep and rocky northeasterly slope in burned cedar.

81.627 The cor. of secs. 1 and 2, on the north bdy. of the tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the field notes of the 1987 resurvey record, with a steel fence post alongside.

Cor. is located on a northerly slope in cedar.

From the cor. of secs. 14, 15, 22 and 23, monumented with an unrecorded rebar, 3/8 in. diam., firmly set, projecting 3 ins. above ground, with a trachyte stone, 15X9X7 ins., mkd. with 3 notches on the south and 2 notches on the east edges, north of the rebar, in an embedded mound of stone, and the rebar is accepted as a faithful and careful perpetuation of the original cor.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 23 ins. in the ground with magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T 12 S	R 2 W
S 15	S 14
S 22	S 23
2001	

Bury the rebar inside the aluminum post.

Bury the mkd. stone alongside the aluminum post.

Drive a steel fence post alongside the aluminum post.

Cor. is located on a gradual E slope in cedar.

N. 0°55.7' W., bet. secs. 14 and 15.

19.957 Point for the S 1/16 sec. cor. of secs. 14 and 15.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, with aluminum cap mkd.:

S 1/16	
S 15	S 14
2001	

Drive a steel fence post alongside the aluminum post.

Cor. is located on a steep SE slope, 20 ft. north of a fence, bears E and W.

39.914 The 1/4 sec. cor. of secs. 14 and 15, monumented with a granite stone, 21X12X7 ins., loosely set, in a mound of stone, 2 ft. diam., dimly mkd. 1/4 on west face. (Record; 18X12X7 ins.)

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T 12 S	R 2 W
1/4	
S 15	S 14
2001	

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Bury mkd. stone on west side of aluminum post.

Drive a steel fence post on the southeast side of the aluminum post.

Cor. is located on a gradual easterly slope in scattered cedar.

N. 2°16.9' W., beginning new measurement.

- 40.712** The cor. of secs. 10, 11, 14 and 15, monumented with a granite stone, 16X12X4 ins., loosely set, clearly mkd. with 3 notches on the south edge. (Record; 4 notches on the south and 3 notches on the east edges)

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, and in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:

T 12 S R 2 W	
S 10	S 11
S 15	S 14
2001	

Bury mkd. stone on S side of aluminum post.

Drive a steel fence post on the SE side of aluminum post.

Cor. is located on an easterly slope in dense cedar.

From the cor. of secs. 11, 12, 13 and 14.

N. 89°11.8' W., bet. secs. 11 and 14.

- 39.674** Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T 12 S R 2 W	
S 11	
1/4	_____
S 14	
2001	

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Bury mkd. stone alongside aluminum post.

Cor. is located in a burned area.

From the cor. of secs. 1, 2, 11 and 12.

S. 89°01.4' W., bet. secs. 2 and 11.

- 39.959** The 1/4 sec. cor. of secs. 2 and 11, monumented with a trachyte stone, 15X12X6 ins., firmly set, clearly mkd. 1/4 on north face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with a reference mound of stone, 3 ft. diam., to the north, with aluminum cap mkd.:

T 12 S R 2 W
S 2
1/4 —————
S 11
2001

Bury the mkd. stone alongside the aluminum post.

Cor. is located in a burned area.

N. 88°05.6' W., beginning new measurement.

- 39.676** The cor. of secs. 2, 3, 10 and 11.

From the cor. of secs. 14, 15, 22 and 23.

S. 88°20.2' W., bet. secs. 15 and 22.

- 19.950** Point for the E 1/16 sec. cor. of secs. 15 and 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 23 ins. in the ground with magnet at base, with aluminum cap mkd.:

S 15
E 1/16 —————
S 22
2001

Drive a steel fence post on the west side of the aluminum post.

Cor. is located on a steep west slope in scattered cedar.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- 39.900** Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 5 ins. in the ground to solid rock with magnet at base, and in a supporting mound of stone, 5 ft. diam., to top, with aluminum cap mkd.:

T 12 S R 2 W
S 15
1/4 —————
S 22
2001

Drive a steel fence post to the northeast of the aluminum post.

Cor. is located on an east slope in cedar.

- 79.800** The cor. of secs. 15, 16, 21 and 22, monumented with a sandstone, 19X8X3 ins., firmly set, clearly mkd. with 3 notches on the south and 3 notches on the east edges, in a mound of stone, from which the remains of the original bearing tree

A cedar, 16 ins. diam., bears N. 85° W., 51 lks. dist., with illegible scribe marks visible on a partially healed blaze. (Record; 30 lks. dist.)

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock with magnet at base, and in a supporting mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:

T 12 S R 2 W
S 16 S 15
—————
S 21 S 22
2001

Bury the mkd. stone alongside the aluminum post.

Drive a steel fence post alongside the aluminum post.

N. 2°13.7' W., bet. secs. 15 and 16.

- 40.003** Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T 12 S R 2 W	
1/4	
S 16	S 15
2001	

Drive a steel fence post on the west side of the aluminum post.

Cor. is located on a steep easterly slope in dense cedar.

- 80.006** Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to solid rock with magnet at base, and in a supporting mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:

T 12 S R 2 W	
S 9	S 10

S 16	S 15
2001	

Cor. is located on an easterly slope in dense cedar, 35 ft. West of a draw, drains N. 40° E.

From the cor. of secs. 10, 11, 14 and 15.

S. 88°13.1' W., bet. secs. 10 and 15.

- 40.538** The 1/4 sec. cor. of secs. 10 and 15, monumented with a trachyte stone, 16X9X8 ins., firmly set, clearly mkd. 1/4 on north face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock with magnet at base, and in a supporting mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T 12 S R 2 W	
S 10	
1/4	-----
S 15	
2001	

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Bury the mkd. stone alongside the aluminum post.

Drive a steel fence post alongside the aluminum post.

Cor. is located on a flat in grass.

S. 87°34.3' W., beginning new measurement.

40.111 The cor. of secs. 9, 10, 15 and 16.

N. 1°37.3' E., bet. secs. 9 and 10.

39.990 The 1/4 sec. cor. of secs. 9 and 10, monumented with a trachyte stone, 18X11X9 ins., firmly set, clearly mkd. 1/4 on west face, in a mound of stone, with a steel fence post alongside. No remains of the bearing tree was recovered.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock with magnet at base, and in a supporting mound of stone, 4 ft. diam., to top, with aluminum cap mkd.

T 12 S R 2 W
1/4
S 9 | S 10
2001

Bury the mkd. stone alongside the aluminum post.

Cor. is located on an east slope in cedar.

N. 0°01.8' E., beginning new measurement.

39.755 The cor. of secs. 3, 4, 9 and 10, monumented with a trachyte stone, 17X13X7 ins., firmly set, in a mound of stone, clearly mkd. with 4 notches on the south and 3 notches on the east edges, from which the original bearing tree

A cedar, 12 ins. diam., bears N. 30° E., 99 1/2 lks. dist., with illegible scribe marks visible on partially healed blaze. (Record; N. 35° E., 87 lks. dist.)

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to solid rock with magnet at base, and in a

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH
CHAINS

supporting mound of stone, 6 ft. diam., to top, with aluminum cap mkd.:

T 12 S R 2 W	
S 4	S 3
S 9	S 10
2001	

Bury the mkd. stone alongside the aluminum post.

From the cor. of secs. 2, 3, 10 and 11.

S. 87°52.3' W., bet. secs. 3 and 10.

- 39.860** The 1/4 sec. cor. of secs. 3 and 10, monumented with a trachyte stone, 17X15X7 ins., firmly set, dimly mkd. 1/4 on north face, in a mound of stone, at intersection of fences bearing S and W.

At the corner point

T 12 S R 2 W	
S 3	
1/4	
S 10	
2001	

Bury the mkd. stone alongside the aluminum post.

S. 87°13.0' W., beginning new measurement.

- 38.929** The cor. of secs. 3, 4, 9 and 10.
-

From the cor. of secs. 9, 10, 15 and 16.

S. 88°39.6' W., bet. secs. 9 and 16.

- 39.421** Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 5 ins. in the ground to solid rock with magnet at base, and in a mound of stone, 5 ft. diam., to top, with aluminum cap mkd.:

T 12 S R 2 W	
S 9	
1/4	
S 16	
2001	

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH
CHAINS

Drive a steel fence post along the north side of the aluminum post.

Cor. is located 46 ft. West of draw, drains southerly.

- 78.842** The cor. of secs. 8, 9, 16 and 17, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 26 ins. above ground, in a mound of stone, with aluminum cap mkd. as described in the field notes of the 1996 resurvey record.

Cor. is located on a westerly slope.

Survey of the Subdivision of Section 10,
T. 12 S., R. 2 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 10 and 15.

N. 0°01.4' W., on the N-S center line of sec. 10.

- 39.816** Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 32 ins. in the ground with magnet at base, with aluminum cap mkd.:

T 12 S R 2 W
C 1/4 S 10
2001

Drive a steel fence post 4 ft. North of the aluminum post.

Cor. is located on the north edge of a dirt road, 7 ft. wide, bears E and W, and 7 ft. South of a fence, bears E and W.

- 79.920** The 1/4 sec. cor. of secs. 3 and 10.

From the 1/4 sec. cor. of secs. 10 and 11.

S. 87°43.9' W., on the E-W center line of sec. 10.

- 39.322** The center 1/4 sec. cor. of sec. 10.

- 78.276** The 1/4 sec. cor. of secs. 9 and 10.

Survey of the Subdivision of Section 13,
T. 12 S., R. 2 W., Salt Lake Meridian, Utah

SURVEY OF THE SUBDIVISION OF SECTION 13,
T. 12 S, R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 sec. cor. of secs. 13 and 24.

N. 2°19.4' W., on the N-S center line of sec. 13.

20.100 Point for the center S 1/16 sec. cor. of sec. 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, with aluminum cap mkd.:

C
|
S 1/16 S 13
|
C
2001

Drive a steel fence post on the southwest side of the aluminum post.

Cor. is located on a flat in juniper, and 80 ft. South of a fence, bears E and W.

40.200 Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T 12 S R 2 W
C 1/4 S 13
2001

Drive a steel fence post on the southwest side of the aluminum post.

Cor. is located in juniper on a gentle east slope.

80.440 The 1/4 sec. cor. of secs. 12 and 13.

From the 1/4 sec. cor. of secs. 13 and 18 on the east bdy. of the tp., hereinbefore described

S. 87°49.3' W., on the E-W center line of sec. 13.

40.775 The center 1/4 sec. cor. of sec. 13.

80.730 The 1/4 sec. cor. of secs. 13 and 14.

SURVEY OF THE SUBDIVISION OF SECTION 13,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the S 1/16 sec. cor. of secs. 13 and 18 on the east bdy. of the tp., hereinbefore described.

S. 87°43.2' W., on the E-W center line of the SE 1/4 of sec. 13.

40.322 The center S 1/16 sec. cor. of sec. 13.

From the center S 1/16 sec. cor. of sec. 13.

S. 87°42.9' W., on the E-W center line of the SW 1/4 of sec. 13.

39.912 The S 1/16 sec. cor. of secs. 13 and 14.

Survey of the Subdivision of Section 14,
T. 12 S., R. 2 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 14 and 23, monumented with an unrecorded rebar, 3/8 in. diam., firmly set, projecting 5 ins. above ground, with a trachyte stone, 17X10X7 ins., clearly mkd. 1/4 on one side, loosely set, alongside the rebar, in a mound of stone, and the rebar is accepted as a careful and faithful perpetuation of the original cor., from which the original bearing tree

A cedar, 8 ins. diam., bears N. 30° W., 13 1/2 lks. dist., with the marks 1/4 BT visible on a partially healed blaze. (Record; N. 8° W., 200 lks. dist.)

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground to solid rock with magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T 12 S R 2 W
S 14
1/4 —————
S 23
2001

Bury the rebar inside the aluminum post.

Bury the mkd. stone alongside the aluminum post.

Drive a steel fence post alongside the aluminum post.

Cor. is located in cedar.

SURVEY OF THE SUBDIVISION OF SECTION 14,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 2'00.1' W., on the N-S center line of sec. 14.

20.357 Point for the center S 1/16 sec. cor. of sec. 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, and in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:

C
S 1/16 | S 14
C
2001

Drive a steel fence post alongside the aluminum post.

40.714 Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to solid rock with magnet at base, and in a supporting mound of stone, 5 ft. diam., to top, with aluminum cap mkd.:

T 12 S R 2 W
C 1/4 S 14
2001

Drive a steel fence post alongside the aluminum post.

81.228 The cor. of secs. 11 and 14.

From the 1/4 sec. cor. of secs. 13 and 14.

N. 89'28.0' W., on the E-W center line of sec. 14.

39.987 The center 1/4 sec. cor. of sec. 14.

79.457 The 1/4 sec. cor. of secs. 14 and 15.

From the S 1/16 sec. cor. of secs. 13 and 14.

N. 89'44.3' W., on the E-W center line of the SE 1/4 of sec. 14.

40.139 The center S 1/16 sec. cor. of sec. 14.

From the center S 1/16 sec. cor. of sec. 14.

SURVEY OF THE SUBDIVISION OF SECTION 14,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 88°54.7' W., on the E-W center line of the SW 1/4 of sec. 14.

39.864 The S 1/16 sec. cor. of secs. 14 and 15.

Survey of the Subdivision of Section 15,
T. 12 S., R. 2 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 15 and 22.

N. 2°04.2' W., on the N-S center line of sec. 15.

19.977 Point for the center S 1/16 sec. cor. of sec. 15, not monumented.

39.954 Point for the center 1/4 sec. cor. of sec. 15, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to solid rock with magnet at base, and in a supporting mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T 12 S R 2 W
C 1/4 S 15
2001

Drive a steel fence post along the west side of the aluminum post.

Cor. is located on a gradual NW slope in dense cedar.

80.535 The 1/4 sec. cor. of secs. 10 and 15.

From the 1/4 sec. cor. of secs. 14 and 15.

S. 88°24.0' W., on the E-W center line of sec. 15.

20.346 Point for the center E 1/16 sec. cor. of sec. 15, not monumented.

40.692 The center 1/4 sec. cor. of sec. 15.

80.696 The 1/4 sec. cor. of secs. 15 and 16.

From the E 1/16 sec. cor. of secs. 15 and 22.

N. 1°29.9' W., on the N-S center line of the SE 1/4 of sec. 15.

SURVEY OF THE SUBDIVISION OF SECTION 15,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- 19.966** Point for the SE 1/16 sec. cor. of sec. 15, at intersection with the E-W center line of the SE 1/4 of sec. 15.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 23 ins. in the ground to solid rock with magnet at base, and in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:

SE 1/16 S 15
2001

Drive a steel fence post on the NW side of the aluminum post.

Cor. is located on a NE slope, 9 ft. South of a fence, bears East and S. 70° W.

- 39.931** The point for the center E 1/16 sec. cor. of sec. 15.
-

From the S 1/16 sec. cor. of secs. 14 and 15.

S. 88°22.0' W., on the E-W center line of the SE 1/4 of sec. 15.

- 20.147** The SE 1/16 sec. cor. of sec. 15.

- 40.295** The point for the center S 1/16 sec. cor. of sec. 15.
-

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Jeremy Davis	Survey Aid
Jason Davis	Survey Aid
Scott Bishop	Survey Aid
Matthew Peck	Survey Aid
Ronald K. Baugh	Supervisory Cadastral Surveyor
M. Ross Workman	Supervisory Cadastral Surveyor

CERTIFICATE OF SURVEY

I, **John F. Carroll, Cadastral Surveyor**, hereby certify upon honor that, in pursuance of special instructions bearing the date of the **1st day of June, 2001**, I have, **dependently resurveyed a portion of the east boundary and a portion of the subdivisional lines, and the subdivision of sections 10, 13, 14 and 15 in Township 12 South, Range 2 West,**

of the **Salt Lake Meridian**, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

02/25/04

Date

John F. Carroll

(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the **dependent resurvey of a portion of the east boundary and a portion of the subdivisional lines, and the subdivision of sections 10, 13, 14 and 15, in Township 12 South, Range 2 West, Salt Lake Meridian, Utah,**

executed by **John F. Carroll, Cadastral Surveyor**

having been critically examined and found correct, are hereby approved.

September 20, 2004

Date

Daniel W. Webb

(Chief Cadastral Surveyor for Utah)