

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF A PORTION OF THE
SOUTH BOUNDARY OF TOWNSHIP 13 SOUTH, RANGE 3 WEST,

AND

THE DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 5, 6, 29 AND 30,

IN

TOWNSHIP 14 SOUTH, RANGE 3 WEST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

John F. Carroll
Cadastral Surveyor

Under special instructions dated **August 8, 2001**, approved **August 8, 2001**,
which provided for the surveys included under Group Number **938**, and
assignment instructions dated **August 20, 2001**

Survey commenced **September 21, 2001**
Survey completed **November 9, 2004**

INDEX DIAGRAM

Township 14 South, Range 3 West

9		7									
5	6	18	5	11	4	3	2	1			
		18			17						
7		8		9		10		11		12	
18		17		16		15		14		13	
19		20		21		22		23		24	
		16			16						
3	30	14	29	28		27		26		25	
		14			13						
31		12	32	33		34		35		36	

The Subdivision of Section 5.....Page 19
 The Subdivision of Section 6.....Page 20
 The Subdivision of Section 29.....Page 22
 The Subdivision of Section 30.....Page 23

The following field notes are those of the dependent resurvey of a portion of the south boundary of T. 13 S., R. 3 W. and a portion of the west boundary, a portion of the subdivisional lines and the subdivision of sections 5, 6, 29 and 30, in T. 14 S., R. 3 W., Salt Lake Meridian, Utah.

History of Surveys

Surveyed by		Retr. or Resurveyed by	
SOUTH BOUNDARY			
All	S.M. Richardson	1884	
Portion			Stewart and Heist 1912
Portion			J.C. Thoma, C.J. Terry 1920 and H.W. Miller
Portion			D.H. Meyers 1988 (Mineral Surveyor)
Portion			R.L. Houston 1997
Portion			R.K. Baugh 1996- 2000
EAST BOUNDARY			
All	S.M. Richardson	1884	
All			Stewart and Heist 1912
All			R.K. Baugh 1996- 2000
WEST BOUNDARY			
All	S.M. Richardson	1884	
All			Stewart and Clark 1913
NORTH BOUNDARY			
Portion	J. Gorlinski	1872	
All	S.M. Richardson	1884	S.M. Richardson 1884
Portion			Stewart and Clark 1913
Portion			B.S. Owens 1960
Portion			R.K. Baugh 1996- 2000
SUBDIVISION			
All	S.M. Richardson	1884	
Portion			D.H. Meyers 1988 (Mineral Surveyor)
Portion			R.K. Baugh 1996- 2000

T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 938, dated August 8, 2001.

The direction of the lines were determined by mean geodetic inverse between corners. Global Positioning System (GPS) utilizing Real-time kinematic (RTK) was used throughout the survey. Cadastral Measurement Management (CMM) was utilized during the course of the survey.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the closing corner of sections 31 and 32, T. 13 S., R. 3 W., as determined by a tie to the National Geodetic Survey Control Station "DYER", utilizing GPS, using RTK techniques, is as follows:

Latitude: 39°38'26.868" N. Longitude: 112°12'48.369" W.
N.A.D. 1983 (1994)

The geographic position of National Geodetic Survey Control Station "DYER" is as follows:

Latitude: 39°40'21.25464" N. Longitude: 112°15'40.12772" W.
N.A.D. 1983 (1994) N.A.V.D. 1988 Elevation 5112 feet.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 13 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the West Boundary,
T. 14 S., R. 3 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
S.M. Richardson in 1884 and the Resurvey
Executed by Stewart and Clark in 1913

Beginning at the cor. of secs. 30 and 31, T. 14 S., R. 3 W.,
monumented with an iron post, 3 ins. diam., firmly set,
projecting 13 ins. above ground, with brass cap mkd. and
witnessed as described in the field notes of the 1913 resurvey
record.

Bury mkd. stone on east side of iron post.

Rebuild reference mound of stone to 3 ft. diam. around iron
post.

Cor. is located on a gradual SE slope in cedar.

From this point, the closing cor. of secs. 25 and 36,
T. 14 S., R. 4 W., monumented with an iron post, 2 ins. diam.,
firmly set, projecting 14 ins. above ground, with brass cap
mkd. and witnessed as described in the field notes of the 1913
resurvey record, bears S. 0°03.5' E., 2.601 chs. dist.

Drive a steel fence post along west side of the iron post.

N. 0°02.8' E., on the west bdy. of sec. 30.

20.040 Point for the S 1/16 sec. cor. of sec. 30 only.

Set an aluminum post, 30 ins. diam., 2 1/2 ins. diam., 20 ins.
in the ground with a magnet at base, and in a mound of stone,
3 ft. diam., to top, with aluminum cap mkd.:

S1/16
S30

2001

Drive a steel fence post along SE side of the aluminum post.

Cor. is located on a gradual SE slope in chamise and cedar, 10
ft. North of a shallow draw, drains SE.

37.204 Point for the 1/4 sec. cor. of sec. 25 only, T. 14 S.,
R. 4 W., at midpoint bet. closing cors.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T14S
R4W R3W
1/4
S25
2001

Drive a steel fence post along west side of the aluminum post.

Cor. is located on a northeasterly slope in cedar and 10 ft. South of a draw, drains SE.

- 40.080** The 1/4 sec. cor. of sec. 30, monumented with an iron post, 1 in. diam., loosely set, laying southerly, with brass cap mkd. as described in the field notes of the 1913 resurvey record. Stand iron post in an upright position.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to solid rock with a magnet at base, and in a supporting mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:

T14S
R4W R3W
1/4
S30
2001

Remove iron post.

Drive a steel fence post along NE side of the aluminum post.

from which

The marks BXO, 6 ins. above base and on the SW face of a limestone rock, bears N. 24°12.8' E., 7.7 lks. dist.

Cor. is located on a steep southerly slope in cedar.

N. 0°02.5' W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- 36.929** The closing cor. of secs. 24 and 25, T. 14 S., R. 4 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. as described in the field notes of the 1913 resurvey record, bears East, 0.180 chs. dist.

from which the 1913 bearing trees not of record

A cedar branch, 7 ins. diam., bears S. 80° W., 17 1/2 lks. dist., with scribe marks T14SR4WS25BT visible on partially healed blaze.

A cedar, 8 ins. diam., bears N. 60° W., 51 1/2 lks. dist., with scribe marks T14SR4WS24BT visible on open blaze.

Cor. is located on a steep NE slope in pinyon and cedar.

- 40.113** The cor. of secs. 19 and 30, monumented with an iron post, 3 ins. diam., firmly set, in mound of stone, with brass cap mkd. as described in the field notes of the 1913 resurvey record.

from which the 1913 bearing trees

A cedar, 11 ins. diam., bears N. 40° E., 31 1/2 lks. dist., with scribe marks T14SR3WS19BT visible on partially healed blaze. (Record; pine, N. 33° E., 67 lks.)

A dead and standing cedar, 14 ins. diam., bears S. 50° E., 38 lks. slope dist., with scribe marks T14SR3WS30BT visible on partially healed blaze. (Record; pine, S. 48° E., 32 lks. dist.)

Cor. is located on a steep NE slope in pine and cedar.

From the cor. of secs. 6 and 7, T. 14 S., R. 3 W., monumented with an iron post, 3 ins. diam., firmly set, with brass cap mkd. and witnessed as described in the field notes of the 1913 resurvey record.

from which the 1913 bearing trees

A charred pinyon pine, 18 ins. diam., bears S. 70° E., 12 lks. dist., with illegible scribe marks visible on partially healed blaze. (Record; S. 80° E., 10 lks. dist.)

Rebuild reference mound of stone to 3 ft. diam., around iron post.

Cor. is located on a steep SE slope in burned pinyon and cedar.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From this point, the closing cor. of secs. 1 and 12, T. 14 S., R. 4 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, with brass cap mkd. as described in the field notes of the 1913 resurvey record, bears S. 0°10.2' W., 1.789 chs. dist.

from which the 1913 bearing trees

A charred pine, 8 ins. diam., bears S. 40° W., 47 lks. dist., with illegible scribe marks visible on charred blaze.

A charred pine, 11 ins. diam., bears N. 48° W., 173 lks. dist., with illegible scribe marks visible on charred blaze.

Cor. is located on a steep SE slope in burned cedar.

N. 0°06.9' E., on the west bdy. of sec. 6.

38.117 Point for the 1/4 sec. cor. of sec. 1, T. 14 S., R. 4 W., at proportionate dist.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T14S
R4W R3W
1/4 |
S1 |
2001

Drive a steel fence post on the east side of the aluminum post.

Cor. is located on a very steep northwesterly slope in chamise and scattered cedar.

39.914 The 1/4 sec. cor. of sec. 6, T. 14 S., R. 3 W., monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. and witnessed as described in the field notes of the 1913 resurvey record.

Cor. is located on a steep NW slope in scattered scrub oak and scattered cedar.

N. 0°07.2' E., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 13 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- 36.900** The closing cor. of Ts. 13 and 14 S., R. 4 W., monumented with an iron post, 3 ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd. and witnessed as described in the field notes of the 1913 resurvey record.

Cor. is located on a NE slope in burned cedar and grass.

- 38.331** The closing cor. of T. 14 S., Rs. 3 and 4 W., monumented with an iron post, 3 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. and witnessed as described in the field notes of the 1913 resurvey record.

Cor. is located on a NE slope in burned cedar and grass.

Dependent Resurvey of a Portion of the South Boundary,
T. 13 S., R. 3 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
S.M. Richardson in 1884 and the Resurvey
Executed by B.S. Owens in 1960

From the cor. of secs. 32 and 33, T. 13 S., R. 3 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. as described in the field notes of the 1960 resurvey record.

from which the 1960 bearing trees

A juniper, 9 ins. diam., bears N. 34°06' E., 68 lks. dist., with scribe marks T13SR3WS33BT visible on partially healed blaze (record; 0.68 lks. dist.)

A juniper, 7 ins. diam., bears N. 9°42' W., 43 lks. dist., with scribe marks T13SR3WS32BT visible on partially healed blaze (record; 0.43 lks. dist.)

Cor. is located on a northerly slope in cedar.

From this point, the 1/4 sec. cor. of sec. 35 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. and witnessed as described in the field notes of the 1960 resurvey record, with a steel fence post to the SW., bears S. 89°32.0' E., 200.021 chs. dist.

N. 89°30.5' W., on the south bdy. of sec. 32.

- 13.750** Point for the closing cor. of secs. 4 and 5, T. 14 S., R. 3 W., at proportionate dist.,; there is no remaining evidence of the original cor.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 13 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, with aluminum cap mkd.

T13S R3W	
S32	

C	C
S5	S4
T14S	R3W
2001	

Drive a steel fence post on the SW side of the aluminum post.

Cor. is located on a gradual NW slope in grass and cedar to the NE, SE and SW.

33.298 Point for the E 1/16 sec. cor. of sec. 5.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with a magnet at base, and in a collar of stone, 1 1/2 ft. diam., to top, with aluminum cap mkd.:

E 1/16 S5	
2001	

Cor. is located on a gradual NW slope in grass and scattered cedar, and in a fence, bears E and W.

40.000 The angle point for sec. 32, formerly the 1/4 sec. cor. of sec. 32, T. 13 S., R. 4 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. and witnessed as described in the field notes of the 1960 resurvey record.

Cor. is located on a gradual W slope grass and in a fence, bears E and W.

N. 89°40.6' W., beginning new measurement.

0.263 The 1/4 sec. cor. of sec. 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. and witnessed as described in the field notes of the 1960 resurvey record.

Cor. is located on a gradual W slope in grass and in a fence, bears E and W.

12.846 Point for the 1/4 sec. cor. of sec. 5, at midpoint bet. closing cors.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with a magnet at base, and in a collar of stone, 1 1/2 ft. diam., to top, with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 13 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T13S R3W

1/4 S5
T14S R3W
2001

Cor. is located on a gradual NW slope in grass and in a fence, bears E and W.

- 36.850** The angle point on the south bdy. of sec. 32, formerly the cor. of secs. 31 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. and witnessed as described in the field notes of the 1960 resurvey record. No remains of the fence post was recovered.

Cor. is located on a gradual NE slope in grass and in a fence, bears E and W.

S. 89°32.7' W., beginning new measurement.

- 3.448** The closing cor. of secs. 31 and 32, T. 13 S., R. 3 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. as described in the field notes of the 1960 resurvey record, with a steel fence post to the NW.

Cor. is located on a gradual N slope in grass and in a fence, bears E and W.

From this point, National Geodetic Survey Control Station "DYER", bears N. 49°14'13" W. (forward) and S. 49°16'03" E. (reverse) bearing, 268.736 chs. dist., monumented with a standard N.G.S. brass cap encased in concrete.

- 15.092** Point for the closing cor. of secs. 5 and 6, T. 14 S., R. 3 W., at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with a magnet at base, and in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:

T13S R3W
S32

C | C
S6 | S5
T14S
2001

Drive a steel fence post along east side of the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 13 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on a gradual easterly slope in grass and 1 ft. South of a fence, bears E and W.

- 58.148** Point for the 1/4 sec. cor. of sec. 6, T. 14 S., R. 3 W., at proportionate dist. bet. closing cors.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with a magnet at base, and in a collar of stone, 1 ft. diam., to top, with aluminum cap mkd.:

T13S R3W

1/4 S6
T14S
2001

Cor. is located on a NE slope in grass and 100 ft. West of a valley, bears NE and SW.

- 87.355** The cor. of T. 13 S., Rs. 3 and 4 W., monumented with an iron post, 2 1/2 ins. diam., loosely set, projecting 17 ins. above ground, with brass cap mkd. and witnessed as described in the field notes of the 1960 resurvey record.

Cor. is located on a steep easterly slope in burned cedar and grass.

Dependent Resurvey of a Portion of the South Boundary,
T. 13 S., R. 4 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
Stewart and Clark in 1913 and the Resurvey
Executed by B.S. Owens in 1960

With continuous measurement.

- 88.347** The angle point for sec. 36, T. 13 S., R. 4 W., formerly the cor. of Ts. 13 and 14 S., Rs. 3 and 4 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. and witnessed as described in the field notes of the 1960 resurvey record.

Drive a steel fence post 1 ft. West of the iron post.

Cor. is located on a steep easterly slope in burned cedar and grass.

S. 89°32.7' W., beginning new measurement.

- 11.490** The closing cor. of T. 14 S., Rs. 3 and 4 W., hereinbefore described.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH
CHAINS

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 14 S., R. 3 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
S.M. Richardson in 1884

From the point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground with magnet at base, in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T14S R3W	
S5	S4
S8	S9
2004	

Drive a steel fence post along south side of the aluminum post.

Cor. is located on a NW slope in burned juniper and grass.

From this point the cor. of secs. 2, 3, 10 and 11, bears N. 89°59.7' E., 157.461 chs. dist., mkd. with a rebar, 3/4 in. diam., firmly set, projecting 15 ins. above ground, with an aluminum cap mkd. SURVEY MONUMENT LOYAL D. OLSON III T14S S3 S2 S10 S11 R3W RLS 4954 DO NOT DISTURB, with a limestone, 15X11X9 ins., dimly mkd. with 2 notches on one side, and 5 notches on another side, laying on the east side of the rebar, in a mound of stone, as recorded in the Juab County Records office, Land Corner Records, and is accepted as a faithful and careful perpetuation of the original cor. Intervening corners were searched for and not found.

N. 4°41.9' E., bet. secs. 4 and 5.

41.340 Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 25 ins. in the ground with magnet at base, in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T14S R3W	
1/4	S4
S5	S4
2004	

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH
CHAINS

Drive a steel fence post along east side of aluminum post.

Cor. is located on a SW slope in juniper and burned juniper to the SW.

62.010 Point for the N 1/16 sec. cor. of secs. 4 and 5. Not monumented.

70.898 The closing cor. of secs. 4 and 5, on the north bdy. of the tp., hereinbefore described.

From the 1/4 sec. cor. of secs. 31 and 32, monumented with a granite, 18X10X6 ins., loosely set, dimly mkd. 1/4 on west face, in a collar of stone.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, in a collar of stone, to top, with aluminum cap mkd.:

T14S R3W
1/4
S31 | S32
2001

Bury mkd. stone on SW side of aluminum post.

Cor. is located on a flat at the intersection of fences bearing SE and SW.

N. 0°07.9' W., bet. secs. 31 and 32.

40.797 The cor. of secs. 29, 30, 31 and 32, monumented with a broken limestone, 14X9X7 ins., loosely set, clearly mkd. with 5 notches on the east and 1 notch on the south edges.

from which the original bearing tree

A cedar, 9 ins. diam., bears N. 70° E., 13 lks. dist., with the marks 14 R3 T visible on partially healed blaze. (Record; N. 85° E., 15 lks. dist.)

Bury broken limestone along east side of aluminum post.

Cor. is located on a SE slope, in cedar and 5 ft. North of a draw, drains SE.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the cor. of secs. 28, 29, 32 and 33, monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. T14S S29S28 S32 S33 R3W 1980, as recorded in the Juab County Recorders office, Land Corner Records, and is accepted as a faithful and careful perpetuation of the original cor.

from which the local reference objects

A wooden fence post, 4 ins. diam., bears N. 60° W., 5.2 lks. dist. to a double headed nail on south side of fence post. (Local Record; 4.4 lks. dist.)

A wooden fence post, 4 ins. diam., bears West, 55 1/2 lks. dist. to a double headed nail on south side of wooden post.

A wooden fence post, 4 ins. diam., bears West, 83 lks. dist. to a double headed nail on south side of wooden post.

A wooden fence post, 4 ins. diam., loosely set in fence, bears East, 13 lks. dist. to a double headed nail on south side of wooden post. (Local Record; 16 lks. dist.)

A wooden fence post, 4 ins. diam., bears East, 78 lks. dist. to a double headed nail on south side of wooden post.

A wooden fence post, 4X8 ins., bears East, 118 1/2 lks. dist. No remains of the double headed nail was recovered.

A concrete fence post, 6 ins. diam., bears S. 20° E., 124 lks. dist. to the west side of concrete fence post.

A power pole, 8 ins. diam., with aluminum tag 15F, bears S. 80° E., 137 lks. dist. to a double headed nail on the south side of power pole.

Cor. is located 1 ft. West of west end of fence, bears E.

N. 89°17.9' W., bet. secs. 29 and 32.

38.386 Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 23 ins. in the ground with magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T14S R3W
S29
1/4 —
S32
2001

Drive a steel fence post alongside the aluminum post.

Cor. is located on a gradual southerly slope in sagebrush and scattered cedar.

76.772 The cor. of secs. 29, 30, 31 and 32.

N. 89°35.1 W., bet. secs. 30 and 31.

20.548 Point for the E 1/16 sec. cor. of secs. 30 and 31. Not monumented.

41.096 The 1/4 sec. cor. of secs. 30 and 31, monumented with a limestone, 17X10X7 ins., firmly set, clearly mkd. 1/4 on north face, with a reference mound of stone to the north.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T14S R3W
S30
1/4 —
S31
2001

Bury mkd. stone on south side of aluminum post.

Rebuild reference mound of stone around aluminum post.

Cor. is located on a gradual SE slope in grass and burned cedar.

S. 88°59.9' W., beginning new measurement.

40.675 The cor. of secs. 30 and 31, on the west bdy. of the township, hereinbefore described.

From the cor. of secs. 29, 30, 31 and 32.

N. 2°28.8' W., bet. secs. 29 and 30.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- 20.486** Point for the S 1/16 sec. cor. of secs. 29 and 30. Not monumented.
- 40.972** Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, in a collar of stone, 1 ft. diam., with aluminum cap mkd.:

T14S R3W
1/4
S30 | S29
2004

Cor. is located on a SE slope in burned juniper.

- 61.458** Point for the N 1/16 sec. cor. of secs. 29 and 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to solid rock with magnet at base, in a supporting mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:

N 1/16
S30 | S29
2004

Drive a steel fence post alongside aluminum post.

Cor. is located on a SW slope in burned juniper and grass, approximately 90 ft. North of draw, drains SE.

- 81.944** Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T14S R3W
S19 | S20

S30 | S29
2004

Cor. is located on SE slope in burned juniper, grass and 40 ft. South of a draw, drains S. 50° E.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the cor. of secs. 20, 21, 28 and 29, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, with aluminum cap mkd. as described in the field notes of the 1996-2000 resurvey record.

Cor. is located in a fence, bears N and S, and on a southwesterly slope in cedar.

From this point, the cor. of secs. 4, 5, 8 and 9, bears N. 0°04.1'E., 247.205 chs. dist., hereinbefore described. Intervening corners were searched for and not found.

N. 88°27.6' W., bet. secs. 20 and 29.

19.630 Point for the E 1/16 sec. cor. of secs. 20 and 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to solid rock with magnet at base, in a supporting mound of stone, 4 1/2 ft. diam., to top, with aluminum cap mkd.:

S20
E 1/16 ———
S29
2004

Cor. is located on a NW slope, 20 ft. South of bottom of drainage.

39.260 Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock with a magnet at base, in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T14S R3W
S20
1/4 ———
S29
2004

Cor. is located on a top of ridge, bears S. 80° E. and N. 80° W., in scattered and burned juniper.

78.520 The cor. of secs. 19, 20, 29 and 30.

S. 88°28.1' W., bet. secs. 19 and 30.

19.606 Point for the E 1/16 sec. cor. of secs 19 and 30. Not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH
CHAINS

- 39.212** Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the original cor.

Set a rebar, 12 ins. long, 5/8 in. diam., flush with ground, with an aluminum cap, 2 ins. diam., mkd.:

S19
1/4 —
S30
2004

Build a reference mound of stone to the south.

Cor. is located on a steep E slope, approximately 2 chs. from bottom of drainage.

- 78.228** The cor. of secs. 19 and 30, on the west bdy. of the tp, hereinbefore described.

From the cor. of secs. 4, 5, 8 and 9.

N. 89°37.6' W., bet. secs. 5 and 8.

- 39.263** Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, with aluminum cap mkd.:

T14S R3W
S5
1/4 —
S8
2004

Drive a steel fence post along west side of aluminum post.

Cor. is located on a NE slope in grass.

- 78.536** Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to solid rock with a magnet at base, in a supporting mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T14S R3W	
S6	S5
S7	S8
2004	

Drive a steel fence post along SE side of aluminum post.

Cor. is located on a NW slope in burned juniper and grass.

From this point, the cor. of secs. 19, 20, 29 and 30, bears
S. 0°02.8' W., 245.606 chs. dist., hereinbefore described.
Intervening corners were searched for and not found.

S. 83°52.9' W., bet. secs. 6 and 7.

19.782 Point for the E 1/16 sec. cor. of secs. 6 and 7.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with aluminum cap mkd.:

	S6
E 1/16	—
	S7
	2004

Cor. is located on a NE slope in burned juniper and grass.

39.564 Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate
dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 23 ins.
in the ground with a magnet at base, in a mound of stone, 3 ft.
diam., to top, with aluminum cap mkd.:

T14S R3W	
	S6
1/4	—
	S7
	2004

Drive a steel fence post on SE side of aluminum post.

Cor. is located on a steep N slope in sagebrush and pinyon pine
to the NE and SW.

79.228 The cor. of secs. 6 and 7, on the west bdy. of the tp.,
hereinbefore described.

From the cor. of secs. 5, 6, 7 and 8.

N. 4°58.8' E., bet. secs. 5 and 6.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- 20.545** Point for the S 1/16 sec. cor. of secs. 5 and 6. Not monumented.
- 41.090** Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with a magnet at base, with aluminum cap mkd.:

T14S R3W
1/4
S6 | S5
2004

- 70.726** The closing cor. of secs. 5 and 6, on the north bdy. of the tp., hereinbefore described.

Survey of the Subdivision of Section 5,
T. 14 S., R. 3 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 5 and 8.

N. 4°49.6' E., on the N-S center line of sec. 5.

- 41.216** Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E-W center line of sec. 5.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at the base, with aluminum cap mkd.:

T14S R3W
C1/4 • S5
2004

Cor. is located on a gradual easterly slope in grass and 120 ft. West of a fence, bears N and S.

- 61.917** Point for the center N 1/16 sec. cor. of sec. 5.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with a magnet at base, with aluminum cap mkd.:

C
N 1/16 | S 5
C
2004

Drive a steel fence post along west side of aluminum post.

Cor. is located on a slight NE slope in grass and scattered cedar.

SURVEY OF THE SUBDIVISION OF SECTION 5,
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- 70.953** The 1/4 sec. cor. of sec. 5 only, on the north bdy. of the tp., hereinbefore described.

From the 1/4 sec. cor. of secs. 4 and 5.

N. 89°49.2' W., on the E-W center line of sec. 5.

- 19.589** Point for the center E 1/16 sec. cor. of sec. 5. Not monumented.

- 39.178** The center 1/4 sec. cor. of sec. 5.

- 78.346** The 1/4 sec. cor. of secs. 5 and 6.

From the point for the center E 1/16 sec. cor. of sec. 5.

N. 4°45.6' E., on the N-S center line of the NE 1/4 of sec. 5.

- 20.686** Point for the NE 1/16 sec. cor. of sec. 5, at intersection with the E-W center line of the NE 1/4 of sec. 5.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with a magnet at base, with aluminum cap mkd.:

NE 1/16 S5
2004

Drive a steel fence post along west side of aluminum post.

Cor. is located on gentle E slope, 6 ft. North of fence, bears E and W.

- 29.666** The E 1/16 sec. cor. of sec. 5 only, on the north bdy. of the tp., hereinbefore described.

From the point for the N 1/16 sec. cor. of secs. 4 and 5.

N. 89°46.6' W., on the E-W center line of the NE 1/4 of sec. 5.

- 19.565** The NE 1/16 sec. cor. of sec. 5.

- 39.127** The center N 1/16 sec. cor. of sec. 5.

Survey of the Subdivision of Section 6,
T. 14 S. R. 3 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 6 and 7.

N. 1°51.7' E., on the N-S center line of sec. 6.

SURVEY OF THE SUBDIVISION OF SECTION 5,
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

20.193 Point for the center S 1/16 sec. cor. of sec. 6.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with a magnet at base, with aluminum cap mkd.:

C
S 1/16 | S 6
C
2004

Drive a steel fence post on north side of aluminum post.

Cor. is located on NW slope in juniper and sagebrush.

40.386 Point for the center 1/4 sec. cor. of sec. 6, at intersection with the E-W center line of sec. 6.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with a magnet at base, in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T14S R3W
C1/4 X S6
2004

Drive a steel fence post along north side of aluminum post.

Cor. is located on a SE slope in burned juniper and grass, 57 ft. South of a fence, bears S. 60° E. and N. 70° W.

74.378 The 1/4 sec. cor. of sec. 6 only on the north bdy. of the tp., hereinbefore described.

From the 1/4 sec. cor. of secs. 5 and 6.

S. 83°26.0' W., on the E-W center line of sec. 6.

20.932 Point for the center E 1/16 sec. cor. of sec. 6. Not monumented.

41.864 The center 1/4 sec. cor. of sec. 6.

82.802 The 1/4 sec. cor. of sec. 6, on the west bdy. of the township, hereinbefore described.

From the E 1/16 sec. cor. of secs. 6 and 7.

N. 3°26.1" E., on the N-S center line of the SE 1/4 of sec. 6.

20.362 Point for the SE 1/16 sec. cor. of sec. 6, at intersection with the E-W center line of the SE 1/4 of sec. 6.

SURVEY OF THE SUBDIVISION OF SECTION 6,
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground with a magnet at base, in a supporting mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:

SE 1/16 X S6
2004

Drive a steel fence post alongside aluminum post.

Cor. is located on NE slope in burned juniper.

40.724 The point for the center E 1/16 sec. cor. of sec. 6.

From the point for the S 1/16 sec. cor. of secs. 5 and 6.

S. 83°39.1' W., on the E-W center line of the SE 1/4 of sec. 6.

20.357 The SE 1/16 sec. cor. of sec. 6.

40.714 The center S 1/16 sec. cor. of sec. 6.

Survey of the Subdivision of Section 29.
T. 14 S., R. 3 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 29 and 32.

N. 1°53.1' W., on the N-S center line of sec. 29.

40.662 Point for the center 1/4 sec. cor. of sec. 29, at intersection with the E-W center line of sec. 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, in a collar of stone, 1 ft. diam., with aluminum cap mkd.:

T14S R3W
C1/4 • S29
2004

Cor. is located on a steep SE slope in burned juniper and grass.

81.328 The 1/4 sec. cor. of secs. 20 and 29.

From the 1/4 sec. cor. of secs. 28 and 29, monumented with an aluminum post, firmly set, projecting 15 ins. above ground, with aluminum cap mkd. and witnessed as described in the field notes of the 1996-2000 resurvey record.

SURVEY OF THE SUBDIVISION OF SECTION 29,
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on a S slope in cedar, 2 ft. South of the intersection of fences, bearing E and N.

N. 88°52.3' W., on the E-W center line of sec. 29.

19.412 Point for the center E 1/16 sec. cor. of sec. 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 21 ins. in the ground with a magnet at base, with aluminum cap mkd.:

E 1/16
C — C
S30
2004

Drive a steel fence post along north side of aluminum post.

Cor. is located on a SE slope in burned juniper and grass.

38.824 The center 1/4 sec. cor. of sec. 29.

77.646 The 1/4 sec. cor. of secs. 29 and 30.

From the center E 1/16 sec. cor. of sec. 29.

N. 1°35.1' W., on the N-S center line of the NE 1/4 of sec. 29.

40.514 The E 1/16 sec. cor. of secs. 20 and 29.

Survey of the Subdivision of Section 30,
T. 14 S. R. 3 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 30 and 31.

N. 1°10.7' W., on the N-S center line of sec. 30.

20.004 Point for the center S 1/16 sec. cor. of sec. 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground with a magnet at base, in a collar of stone, 1 ft. diam., with aluminum cap mkd.:

C
S 1/16 | S 30
C
2004

Drive a steel fence post along east side of the aluminum post.

Cor. is located on a SE slope in scattered juniper and sagebrush.

SURVEY OF THE SUBDIVISION OF SECTION 30,
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.008** Point for the center 1/4 sec. cor. of sec. 30, at intersection with the E-W center line of sec. 30. Not monumented.
- 60.274** Point for the center N 1/16 sec. cor. of sec. 30. Not monumented.
- 80.540** The 1/4 sec. cor. of secs. 19 and 30.

From the 1/4 sec. cor. of secs. 29 and 30.

S. 89°05.5' W., on the E-W center line of sec. 30.

- 20.073** Point for the center E 1/16 sec. cor. of sec. 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with a magnet at base, in a collar of stone, 1 ft. diam., with aluminum cap mkd.:

E 1/16
C ——— C
S30
2004

Drive a steel fence post along west side of aluminum post.

Cor. is located on a westerly slope in juniper.

- 40.146** The point for the center 1/4 sec. cor. of sec. 30.
- 79.961** The 1/4 sec. cor. of sec. 30 only, on the west bdy. of the tp., hereinbefore described.

From the center E 1/16 sec. cor. of sec. 30.

N. 1°50.0' W., on the N-S center line of the NE 1/4 of sec. 30.

- 20.375** Point for the NE 1/16 sec. cor. of sec. 30, at intersection with the E-W center line of the NE 1/4 of sec. 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with a magnet at base, in a collar of stone, 1 ft. diam., with aluminum cap mkd.:

NE 1/16 S30
2004

Cor. is located on S slope in thick juniper and near the bottom of a saddle on top of a ridge.

- 40.750** The point for the E 1/16 sec. cor. of secs. 19 and 30.

From the N 1/16 sec. cor. of secs. 29 and 30.

SURVEY OF THE SUBDIVISION OF SECTION 30,
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 88°47.0' W., on the E-W center line of the NE 1/4 sec. cor. of sec. 30.

19.839 The NE 1/16 sec. cor. of sec. 30.

39.678 The point for the center N 1/16 sec. cor.

From the point for the E 1/16 sec. cor. of secs. 30 and 31.

N. 1°50.2' W., on the N-S center line of the SE 1/4 of sec. 30.

20.244 Point for the SE 1/16 sec. cor. of sec. 30, at intersection with the E-W center line of the SE 1/4 of sec. 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock with a magnet at base, in a supporting mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:

SE 1/16 X S30
2004

Drive a steel fence post alongside aluminum post.

Cor. is located on a SE slope on a rock outcrop in juniper.

40.488 The center E 1/16 sec. cor. of sec. 30.

From the point for the S 1/16 sec. cor. of secs. 29 and 30.

S. 89°45.7' W., on the E-W center line of the SE 1/4 of sec. 30.

20.309 The SE 1/16 sec. cor. of sec. 30.

40.618 The center S 1/16 sec. cor. of sec. 30.

From the center S 1/16 sec. cor. of sec. 30.

S. 89°02.7' W., on the E-W center line of the SW 1/4 of sec. 30.

40.245 The S 1/16 sec. cor. of sec. 30 only, on the west bdy. of the tp., hereinbefore described.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Jerry L. Thomas	Cadastral Surveyor
Jeremy D. Davis	Survey Technician
Matthew M. Peck	Survey Technician
Sterling L. Profaizer	Survey Aid

CERTIFICATE OF SURVEY

I, **John F. Carroll, Cadastral Surveyor**, hereby certify upon honor that, in pursuance of special instructions bearing the date of the **8th day of August, 2001**, I have **executed a dependent resurvey of a portion of the south boundary of Township 13 South, Range 3 West, and a dependent resurvey of a portion of the west boundary, a portion of the subdivisional lines and the subdivision of sections 5, 6, 29 and 30, in Township 14 South, Range 3 West,**

of the **Salt Lake Meridian**, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

04/22/05

Date

John F. Carroll

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the dependent resurvey of a portion of the south boundary of Township 13 South, Range 3 West, and a dependent resurvey of a portion of the west boundary, a portion of the subdivisional lines and the subdivision of sections 5, 6, 29 and 30, in Township 14 South, Range 3 West, Salt Lake Meridian, Utah,

executed by *John F. Carroll, Cadastral Surveyor*,

having been critically examined and found correct, are hereby approved.

April 28, 2005

Date

Daniel W. Webb

Chief Cadastral Surveyor for Utah