

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL  
FIELD NOTES

OF

THE DEPENDENT RESURVEY OF A PORTION OF THE

SOUTH BOUNDARY,  
(FIRST STANDARD PARALLEL SOUTH)

A PORTION OF THE WEST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND THE SUBDIVISION OF SECTIONS

14, 15, 21, 22, 28, 29, 31, AND 32

IN

**TOWNSHIP 4 SOUTH, RANGE 5 WEST**

OF THE UNITAH SPECIAL MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

**Merrill D. Cazier**  
**Cadastral Surveyor**

Under special instructions dated **June 24, 2002**, approved **June 24, 2002**,  
which provided for the surveys included under Group Number **948**, and  
assignment instructions dated **June 24, 2002**.

Survey commenced **June 25, 2002**  
Survey completed **August 15, 2002**

## INDEX DIAGRAM

Township 4 South, Range 5 West

6	5	4	3	2	1
					8
7	8	9	10	12 11	7 12
18	17	16	17 16 15 10	12 14	6 13
19	20	22 21	16 14 22	10 9 23	24
	27	21	14		
30	26 29	19 28	13 27	26	25
25	25	19			
5 31	23 32	17 33	34	35	36
4	2				

The Subdivision of Section 14.....Page 27  
 The Subdivision of Section 15.....Page 29  
 The Subdivision of Section 21.....Page 29  
 The Subdivision of Section 22.....Page 32  
 The Subdivision of Section 28.....Page 33  
 The Subdivision of Section 29.....Page 34  
 The Subdivision of Section 31.....Page 37  
 The Subdivision of Section 32.....Page 39

## T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of a portion of the south boundary (First Standard Parallel South), a portion of the west boundary, and a portion of the subdivisional lines, and the subdivisions of sections 14, 15, 21, 22, 28, 29, 31, and 32 in T. 4 S., R. 5 W, Uintah Special Meridian, Utah.

**History of Surveys**

<b>Surveyed by</b>	<b>Retr. or Resurveyed by</b>
<b>SOUTH BOUNDARY</b> (First Standard Parallel South)	
All A.J. Stewart Jr. & A.L. Booth	1903
<b>EAST BOUNDARY</b> (First Guide Meridian West)	
All D.G. Major	1882
All	A.J. Stewart Jr. & A.L. Booth
Portion	A.D. Kidder, Et Al. 1905
<b>WEST BOUNDARY</b>	
All D.G. Major	1882
All	A.J. Stewart Jr. & A.L. Booth
Portion	J.L. Thomas 1993
<b>NORTH BOUNDARY</b>	
All A.J. Stewart Jr. & A.L. Booth	1903
Portion	A.D. Kidder, Et Al. 1905
Portion	J.L. Thomas 1993
<b>SUBDIVISION</b>	
All A.J. Stewart Jr. & A.L. Booth	1903
Portion	A.D. Kidder, Et Al. 1905
Portion	J.L. Thomas 1993

## T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 948, dated June 24, 2002.

The true meridian direction and length of all lines were determined by Global Positioning System (GPS) utilizing Real-Time Kinematics (RTK) observations using the Trimble 5700 model receiver.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and their calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations, post processed by National Geodetic Survey, Online Positioning User Service, (OPUS), Utilizing Continuously Operating Reference Stations; (CORS) RED BUTTE, CARBON COUNTY, and MYTON 1. The NAD 83 (CORS96) geographic position of the standard corner of sections 32 and 33 is as follows:

Latitude: 40°04'57.048" N.      Longitude: 110°27'52.521" W.  
N.A.D. 83

Elevation: 6821.3 ft.

---

Dependent Resurvey of a Portion of the First Standard Parallel  
South, Uintah Special Meridian, Utah.

---

Reestablishment of the Survey established by  
A.J. Stewart Jr., & A.L. Booth in 1903

---

Beginning at the standard corner of sections 32 and 33, monumented with a sandstone, 19 X 12 X 3 inches, clearly marked with 4 grooves on the east, 2 grooves on the west faces.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 26 inches in the ground, in a collar of stone, with aluminum cap marked:

SC  
T 4 S R 5 W  
S 32 | S 33  
-----  
S 5  
2002

DEPENDENT RESURVEY OF A PORTION OF THE FIRST STANDARD PARALLEL  
SOUTH, UINTAH SPECIAL MERIDIAN, UTAH.

## CHAINS

Deposit marked stone alongside.

From which

A pinion, 7 inches diameter bears N 45° E, 68.9 links  
distance, dimly marked, T 4 S R 5 W S 32 BT.  
(Record, N 45° W, 55 links.)

A pinion, 10 inches diameter bears S 65° W, 41.4 links  
distance, plainly marked, T 5 S R 5 W S 5 BT.  
(Record, N 80° E, 80 links.)

N. 89° 56.7' W., on the south boundary of section 32.

**39.736** Point for the standard 1/4 section corner of section 32, set  
at proportionate distance; there is no remaining evidence of  
the original stone.

Set an aluminum post, 30 inches long, 2½ inches diameter, over  
a magnet, 28 inches in the ground, in a collar of stone, with  
aluminum cap marked:

SC  
T 4 S R 5 W  
1/4 S 32

2002

From which a bearing tree not of record:

A pinion, 7 inches diameter bears S 20° W 37.9 links,  
distance, marked 1/4 S 5 BT.

**69.460** The closing corner of sections 5 and 6, T. 5 S., R. 5 W.,  
bears South 0.105 chains distance, monumented with a sandstone  
34 X 10 X 2 inches, laying on top of the ground, marked 5  
grooves on the west face.

From which the original bearing tree:

A pinion, 15 inches diameter bears S 18° E, 66 links.

Not remonumented.

**79.472** The standard corner of sections 31 and 32, monumented with a  
sandstone, 19 X 13 X 5 inches, clearly marked with 5 grooves  
on the east, 1 groove on the west, and SC on the north faces.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over  
a magnet, 12 inches in the ground, in a mound of stone, 3 ft.  
base, to top, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE FIRST STANDARD PARALLEL  
SOUTH, UINTAH SPECIAL MERIDIAN, UTAH.

## CHAINS

SC  
T 4 S R 5 W  
S 31 | S 32  
S 6  
2002

Deposit marked stone alongside.

From which the original bearing trees:

A pinion, 8½ inches diameter bears N 21° E, 117 links distance, dimly marked, T 4 S R 5 W S 32 BT.  
(Record N 25° E, 116 links).

A pinion, 12½ inches diameter bears N 44° W, 121 links distance, clearly marked, T 4 S R 5 W S 31 BT.  
(Record N 45° W, 120 links).

S. 89° 49.3' W., on the south boundary of section 31.

**19.913** Point for the East 1/16 section corner of section 31.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 22 inches in the ground, in a collar of stone, with aluminum cap marked:

T 4 S R 5 W  
E 1/16 S 31  
                      
2002

**39.826** The standard 1/4 section corner of section 31, monumented with a 2½ inch aluminum post, 12 inches exposed, in a mound of stone, 3 ft. base, 1 1/2 ft. high, with aluminum cap marked:

Duchesne County Survey  
1/4 S 31  
                      
T 4 S R 5 W  
2002

From which the original bearing tree:

A pinion, 14 inches diameter bears N 5° E, 55.8 links distance, dimly marked, 1/4 S 31 BT.

This is accepted as the best available evidence of the original corner position.

N. 89° 45.2' W., beginning new measurement.

**20.004** Point for the West 1/16 section corner of section 31.

DEPENDENT RESURVEY OF A PORTION OF THE FIRST STANDARD PARALLEL  
SOUTH, UINTAH SPECIAL MERIDIAN, UTAH.

## CHAINS

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 26 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
W 1/16 S 31

2002

**27.167** The closing corner of sections 1 and 6, T. 5 S., R. 5 W., bears South 0.113 chains distance, monumented with a 3/4 inch rebar, with the original limestone, a 34 X 18 X 6 inches, alongside.

Not remonumented.

**40.808** The standard corner of Township 4 South, Ranges 5 and 6 West, monumented with a sandstone, 24 X 10 X 4 inches, clearly marked with 6 grooves on the north, south, and west faces.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

SC  
T 4 S  
R 6 W | R 5 W  
S 36 | S 31  
S 1  
2002

From which the original bearing trees:

A pinion, 8 inches diameter bears N 60° E, 30 links distance, marked, T 4 S R 5 W S 31 BT.  
(Record N 57° E, 27 links).

A pinion, 10 inches diameter bears N 21 1/2° W, 19 links distance, clearly marked, T 4 S R 6 W S 36 BT.  
(Record, 98 links).

Deposit marked stone alongside.

Raise a mound of stone 5 ft. base, 2 ft. high to the north.

Corner is located on a steep north slope.

---

Dependent Resurvey of a Portion of the West Boundary,  
Township 4 South, Range 5 West,  
Uintah Special Meridian, Utah.

---

Reestablishment of the Survey established by  
A.J. Stewart Jr., & A.L. Booth in 1903

---

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH.

## CHAINS

From the standard corner of Township 4 South, Ranges 5 and 6 West, hereinbefore described.

N. 0° 07.5' E., between sections 31 and 36.

39.120

The 1/4 section corner of sections 31 and 36, monumented with a broken limestone, no marks visible.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 12 inches in the ground, to solid rock, in a mound of stone, 3 ft. base to top, with aluminum cap marked:

	T 4 S	
R 6 W		R 5 W
		1/4
S 36		S 31
		2002

Deposit broken stone alongside.

From which the original bearing trees:

A pinion, 12 inches diameter bears East, 44.5 links distance, marked, 1/4 S 31 BT. (Record, 40 links).

A pinion, 8 inches diameter bears West, 4.7 links distance, marked, 1/4 S 36 BT. (Record W, 4 links).

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 5 W., Uintah Special Meridian, Utah.

Reestablishment of the Survey established by  
A.J. Stewart Jr., & A.L. Booth in 1903

From the 1/4 section corner of sections 13 and 14, monumented with a sandstone, 14 X 14 X 4 inches, loosely set, in a mound of stone, clearly marked with 1/4 on west face.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 20 inches in the ground, in a mound of stone, 4 ft. base, to top, with aluminum cap marked:

	T 4 S R 5 W	
	1/4	
S 14		S 13
		2002

Deposit marked stone alongside.

From which the original bearing tree:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH.

## CHAINS

A pinion, 18 inches diameter bears N 46° E, 64.1 links distance, marked, 1/4 S 13 BT. (Record N 58° E, 71 links).

Remaining bearing tree, a pinion, dead and knocked over.

N. 0° 06.7' W., between sections 13 and 14.

## 40.141

The corner of sections 11, 12, 13, and 14, monumented with, a 2½ inch aluminum post, 6 inches exposed, in a collar of stone, with aluminum cap marked:

## Duchesne County Survey

T 4 S R 5 W

S 11 | S 12

S 14 | S 13

1995

From which the original bearing trees:

A pinion, 11 inches diameter bears N 28° E, 100 links distance, marked, T 4 R 5 W S 12 BT.

A pinion, 15 inches diameter bears S 41° E, 95.5 links distance, marked, T 4 R 5 W S 13 BT.  
(Record S 40° E, 94 links).

A pinion, 10 inches diameter bears S 72° W, 24.2 links distance, marked, T 4 R 5 W S 14 BT.  
(Record N 73° E, 27 links).

A pinion, 6 inches diameter bears N 46° W, 80.7 links distance, marked, T 4 R 5 W S 11 BT.  
(Record N 43° E 78 links).

This is accepted as the best available evidence of the original corner position.

N. 0° 04.9' W., between sections 11 and 12.

## 39.825

The 1/4 section corner of sections 11 and 12, monumented with a sandstone, 26 X 13 X 3 inches, firmly set and clearly marked with 1/4 on west face.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 18 inches in the ground, to solid rock, in a collar of stone, with aluminum cap marked:

T 4 S R 5 W

1/4

S 11 | S 12

2002

Deposit marked stone alongside.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH.

## CHAINS

From which the original bearing trees:

A pinion, 12 inches diameter bears S 52° E, 40.9 links  
distance, marked, 1/4 S 12 BT. (Record S 50° E, 45 links).

A pinion, 12 inches diameter bears S 88° W, 68.2 links  
distance, marked, 1/4 S 11 BT. (Record S 87° W, 73 links).

N. 0° 55.3' E., beginning new measurement.

**39.052** The corner of sections 1, 2, 11, and 12, monumented with, a 2½  
inch aluminum post, 10 inches exposed, with aluminum cap  
marked:

Duchesne County Survey  
T 4 S R 5 W  
S 2 | S 1  
S 11 | S 12  
1982

Steel fence post alongside.

This is accepted as the best available evidence of the  
original corner position.

From the corner of sections 1, 6, 7, and 12, on the east  
boundary, monumented with, a 2½ inch aluminum post, 10 inches  
exposed, in a collar of stone, with aluminum cap marked:

Duchesne County Survey  
T 4 S  
S 1 | S 6  
S 12 | S 7  
R 5 W | R 4 W  
1982

Steel fence post to the north.

From which the original bearing tree:

A pinion, 8 inches diameter bears S 64° W, 87.6 links  
distance, marked, T 4 S R 5 W S 12 BT.  
(Record S 40° W, 85 links).

This is accepted as the best available evidence of the  
original corner position.

S. 89° 28.3' W., between sections 1 and 12.

**39.753** The 1/4 section corner of sections 1 and 12, monumented with,  
a 2½ inch aluminum post, 20 inches exposed, in a collar of  
stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

Duchesne County Survey

T 4 S R 5 W

S 1

1/4 ———

S 12

1989

This is accepted as the best available evidence of the original corner position.

S. 87° 50.7' W., beginning new measurement.

**39.308** The corner of sections 1, 2, 11, and 12.

From the 1/4 section corner of section 22 and 23, monumented with a mound of stone, accepted as the best available evidence of the original corner.

At the corner point, in center of mound,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T 4 S R 5 W

1/4

S 22 | S 23

2002

Raise a mound of stone west.

From which the original bearing trees:

A pinion, 10 inches diameter bears S 80° E, 68.2 links distance, marked, 1/4 S 23 BT. (Record S 80° E, 35 links).

A pinion, 10 inches diameter bears S 75° W, 34.8 links distance, marked, 1/4 S 22 BT. (Record S 75° W, 75 links).

Corner is located on north slope in scattered sage brush.

N. 0° 45.0' E., between section 22 and 23.

**39.604** The corner of sections 14, 15, 22, and 23, monumented with a mound of stone, accepted as the best available evidence of the original corner.

At the corner point, in center of mound,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 20 inches in the ground, in a mound of stone 3 ft. base, to top, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

T 4 S		R 5 W
S 15		S 14
S 22		S 23
2002		

From which the original bearing tree:

A pinion, 10 inches diameter bears S 62° W, 107 links distance, marked, T 4 S R 5 W S 22 BT.  
(Record, 113 links).

Corner is located on south end of spur bearing N 80° W.

---

From the 1/4 section corner of sections 14 and 23, monumented with a sandstone 26 X 17 X 5 inches, set on top of a nail, 8 inches in the ground, stone marked with 1/4 on one face.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 25 inches in the ground, in a mound of stone, 4 ft. base, to top, with aluminum cap marked:

T 4 S		R 5 W
S 14		
1/4		
S 23		
2002		

Deposit marked stone alongside.

From which the original bearing tree:

A pinion, 13 inches diameter bears S 40° W, 90 links distance, marked, 1/4 S 23 BT. (Record S 30° W, 105 links).

S. 89° 46.0' W., between sections 14 and 23.

**19.940** Point for the West 1/16 section corner, of sections 14 and 23.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 12 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap marked:

T 4 S		R 5 W
S 14		
W 1/16		
S 23		
2002		

Corner is located on gentle north slope.

**39.880** The corner of sections 14, 15, 22, and 23.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

N. 0° 00.8' E., between sections 14 and 15.

**19.958** Point for the South 1/16 section corner of sections 14 and 15.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 22 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
S 1/16  
S 15 | S 14  
2002

Corner is located in bottom of dry wash, bearing east and west.

**39.916** The 1/4 section corner of sections 14 and 15, monumented with a 5/8 inch rebar 2 ft. long with 1 1/4 inch aluminum cap marked:

1/4  
15 | 14

This is accepted as the best available evidence of the original corner position.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 26 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
1/4  
S 15 | S 14  
2002

Invert rebar and cap and bury inside of aluminum post.

Raise a mound of stone west.

---

N. 0° 02.0' E., beginning new measurement.

**39.765** The corner of sections 10, 11, 14, and 15, monumented with a mound of stone, accepted as the best available evidence of the original corner.

At the corner point, in center of mound,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 10 inches in the ground, to solid rock, in a mound of stone 3 ft. base, to top, with aluminum cap marked:

T 4 S R 5 W  
S 10 | S 11  
S 15 | S 14  
2002

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH.

## CHAINS

Corner is located on top of spur bearing N 80° E.

---

From the corner of sections 11, 12, 13, and 14.

S. 89° 36.2' W., between sections 11 and 14.

39.661

The 1/4 section corner of sections 11 and 14, monumented with a sandstone 12 X 9 X 5 inches, plainly marked with 1/4 on north face.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T 4 S R 5 W
S 11
1/4 <hr style="display: inline-block; width: 50px; border: 0.5px solid black; vertical-align: middle;"/>
S 14
2002

Deposit marked stone alongside.

Raise a mound of stone north.

There is no remaining evidence of the original bearing trees.

Corner is located 15 links distance north of ridge top.

---

S. 89° 45.2' W., beginning new measurement.

39.854

The corner of sections 10, 11, 14, and 15.

---

N. 0° 03.9' E., between sections 10 and 11.

39.859

The 1/4 section corner of sections 10 and 11, monumented with a sandstone 24 X 15 X 2 inches, firmly set, marked with 1/4 on west face.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 26 inches in the ground, with aluminum cap marked:

T 4 S R 5 W
1/4
S 10   S 11
2002

Deposit marked stone alongside.

Raise a mound of stone west.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH.

## CHAINS

There is no remaining evidence of the original bearing trees.

---

N. 0° 00.6' W., beginning new measurement.

## 40.147

The corner of sections 2, 3, 10, and 11, monumented with an aluminum post, 2½ inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap as described in the official record of the 1993 resurvey.

---

From the 1/4 section corner of sections 27 and 28, monumented with a sandstone 20 X 14 X 4 inches, marked with 1/4 on north face.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 26 inches in the ground, in a collar of stone, with aluminum cap marked:

T 4 S	R 5 W
1/4	
S 28	S 27
2002	

Deposit marked stone alongside.

From which the original bearing tree:

A pinion, 8 inches diameter bears S 37° E, 20.6 links distance, marked, 1/4 S 27 BT. (Record, 22 links).

N. 0° 03.8' E., between sections 27 and 28.

## 39.710

The corner of sections 21, 22, 27, and 28, monumented with a sandstone 21 X 11 X 6 inches, loosely set, plainly marked with 2 grooves on the south, and 3 grooves on the east edges.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 23 inches in the ground, in a collar of stone, with aluminum cap marked:

T 4 S	R 5 W
S 21	S 22
S 28	S 27
2002	

Deposit marked stone along side.

From which the original bearing trees:

A pinion, 12 inches diameter bears N 44° E, 13.3 links distance, marked, T 4 S R 5 W S 22 BT.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH.

## CHAINS

(Record N 73° E, 13 links).

A pinion, 9 inches diameter bears S 10° E, 50.2 links  
distance, marked, T 4 S R 5 W S 27 BT.  
(Record S 11° E, 50 links).

A pinion, 12 inches diameter bears S 49° W, 33 links  
distance, marked, T 4 S R 5 W S 28 BT.  
(Record S 38° W, 36 links).

A pinion, 7 inches diameter bears N 74° W, 40.3 links  
distance, marked, T 4 S R 5 W S 21 BT.  
(Record N 82° W, 38 links).

From the 1/4 section corner of sections 22 and 27, monumented  
with a broken and deteriorating sandstone, marks obliterated.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over  
a magnet, 18 inches in the ground, to solid rock, in a collar  
of stone, with aluminum cap marked:

T 4 S R 5 W  
S 22  
1/4 —————  
S 27  
2002

Deposit remains of stone alongside.

From which the original bearing trees:

A pinion, 13 inches diameter bears N 55° E, 160 links  
distance, marked, 1/4 S 22 BT.

A pinion, 9 inches diameter bears S 22° E, 42 links  
distance, marked, 1/4 S 27 BT.

Corner is located on top edge of spur.

S. 89° 33.1' W., between sections 22 and 27.

**39.999** The corner of sections 21, 22, 27, and 28

N. 0° 00.3' W., between sections 21 and 22.

**19.885** Point for the South 1/16 section corner of sections 21 and 22.

Set an aluminum post, 30 inches long, 2½ inches diameter, over  
a magnet, 20 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH.

CHAINS

T 4 S R 5 W  
S 1/16  
S 21 | S 22  
2002

Corner is located on east slope below top of ridge.

**39.770** The 1/4 section corner of sections 21 and 22, monumented with a sandstone, 17 X 16 X 4 inches, 12 inches in the ground, plainly marked with 1/4 on the west face.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 26 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
1/4  
S 21 | S 22  
2002

Deposit marked stone alongside.

From which the original bearing tree:

A pinion, 10 inches diameter bears S 29° E, 187.9 links distance, marked, 1/4 S 22 BT.  
(Record S 31° E, 200 links).

There is no remaining evidence of the remaining bearing tree.

---

N. 0° 01.9' E., beginning new measurement.

**20.039** True point for the North 1/16 section corner of sections 21 and 22, falls in bottom of wash, drains N. 30° W. From which an off line witness corner bears S. 0° 42.1' E., 0.309 chains distance, monumented with a ½ inch rebar, firmly set, with a 1½ inch aluminum cap marked:

U I T  
W C  
S21 S22 N1/16  
20 ↑  
83

**40.078** The corner of sections 15, 16, 21, and 22, monumented with a limestone 16 X 15 X 5 inches, in a mound of stone, plainly marked with 3 notches on the east, and 3 notches on the south edges.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 25 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH.

CHAINS

T 4 S		R 5 W
S 16		S 15
S 21		S 22
2002		

Deposit marked stone along side.

From which the original bearing trees:

A pinion, 8 inches diameter bears N 50° E, 19.8 links distance, marked, T 4 S R 5 W S 15 BT.  
(Record N 80° E, 53 links).

A pinion, 12 inches diameter bears S 52° E, 22.9 links distance, marked, T 4 S R 5 W S 22 BT.  
(Record S 46° E, 23 links).

A pinion, 10 inches diameter bears N 7° W, 19.1 links distance, marked, T 4 S R 5 W S 16 BT.  
(Record N 17° W, 18 links).

From the corner of sections 14, 15, 22, and 23.

S. 89° 45.5' W., between sections 15 and 22.

**39.813**

The 1/4 section corner of sections 15 and 22, monumented with a sandstone 16 X 9 X 4 inches, plainly marked with 1/4 on north face, steel fence post alongside.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 26 inches in the ground, with aluminum cap marked:

T 4 S		R 5 W
		S 15
1/4		S 22
2002		

Deposit marked stone alongside.

Raise a mound of stone north.

There is no remaining evidence of the original bearing trees.

S. 89° 45.4' W., beginning new measurement.

**40.228**

The corner of sections 15, 16, 21, and 22.

N. 0° 05.6' W., between sections 15 and 16.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH.

CHAINS  
40.056

The 1/4 section corner of sections 15 and 16, monumented with a limestone, 17 X 6 X 5 inches, firmly set, 10 inches in the ground, plainly marked with 1/4 on the west face.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
1/4  
S 16 | S 15  
2002

Deposit marked stone alongside.

Raise a mound of stone 2 ft. base, to the west.

From which the original bearing trees:

A pinion, 17 inches diameter bears S 89° E, 50.6 links distance, faintly marked, 1/4 S 15 BT.  
(Record S 87° E, 40 links).

A pinion, 20 inches diameter bears N 15° W, 28.8 links distance, faintly marked, 1/4 S 16 BT.  
(Record N 30° W, 38 links).

From the corner of sections 10, 11, 14, and 15.

S. 89° 58.8' W., between sections 10 and 15.

39.918

The 1/4 section corner of sections 10 and 15, monumented with a sandstone 19 X 7 X 6 inches, firmly set, dimly marked with 1/4 on north face.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 2 inches in the ground, to solid rock, in a mound of stone, 2 ft. base, to top, with aluminum cap marked:

T 4 S R 5 W  
S 10  
1/4 ———  
S 15  
2002

Deposit marked stone alongside.

Raise a mound of stone north.

From which the original bearing trees:

A pinion, 7 inches diameter bears S 56° E, 11.2 links distance, faintly marked, 1/4 S 15 BT.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

(Record S 58° E, 10 links).

A pinion, 7 inches diameter bears N 6° W, 82.2 links  
distance, faintly marked, 1/4 S 10 BT.

(Record N 6° E, 80 links).

From the standard corner of section 32 and 33, on the South  
boundary, hereinbefore described.

N. 0° 00.8' W., between sections 32 and 33.

40.057

The 1/4 section corner of sections 32 and 33, monumented with  
a sandstone, 15 X 13 X 3 inches, loosely set, marked with 1/4  
on west face.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over  
a magnet, 26 inches in the ground, with aluminum cap marked:

T 4 S	R 5 W
1/4	
S 32	S 33
2002	

Deposit marked stone alongside.

From which the original bearing trees:

A pinion, 9 inches diameter bears East, 8.3 links  
distance, dimly marked, 1/4 S 33 BT.  
(Record, 11 links).

A juniper, 8 inches diameter bears West, 6.2 links  
distance, dimly marked, 1/4 S 32 BT.  
(Record, 12 links).

N. 0° 00.6' E., beginning new measurement.

39.877

The corner of sections 28, 29, 32, and 33, monumented with a  
sandstone, 18 X 15 X 5 inches, marked with 1 groove on the  
south, and 5 grooves on the east edges.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over  
a magnet, 20 inches in the ground, with aluminum cap marked:

T 4 S	R 5 W
S 29	S 28
S 32	S 33
2002	

Deposit marked stone along side.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH.

## CHAINS

From which the original bearing trees:

A pinion, 12 inches diameter bears N 58° E, 19.4 links  
distance, dimly marked, T 4 S R 5 W S 28 BT.  
(Record N 52° E, 20 links).

A pinion, 6 inches diameter bears S 34° E, 57.6 links  
distance, plainly marked, T 4 S R 5 W S 33 BT.  
(Record S 8° E, 67 links).

A pinion, 8 inches diameter bears S 74° W, 18.9 links  
distance, plainly marked, T 4 S R 5 W S 32 BT.  
(Record S 82° W, 20 links).

A pinion, 10 inches diameter bears N 54° W, 77 links  
distance, plainly marked, T 4 S R 5 W S 29 BT.  
(Record N 57° W).

From the 1/4 section corner of sections 28 and 33, monumented  
with a sandstone 18 X 9 X 4 inches, marked 1/4 on north face.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over  
a magnet, 26 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
S 28  
1/4 ———  
S 33  
2002

Deposit marked stone alongside.

From which the original bearing trees:

A pinion, 8 inches diameter bears S 60° E, 53.8 links  
distance, marked, 1/4 S 33 BT. (Record S 40° E, 55 links).

A dead pinion, 12 inches diameter bears N 45° W, 4 links  
distance, marked, 1/4 S 28 BT. (Record N, 5 links).

N. 89° 58.1' W., between sections 28 and 32.

**39.865** The corner of sections 28, 29, 32, and 33.

N. 0° 07.8' E., between section 28 and 29.

**19.862** Point for the South 1/16 section corner of sections 28 and 29.

Set an aluminum post, 30 inches long, 2½ inches diameter, over  
a magnet, 18 inches in the ground, in a mound of stone, 3 ft.  
base, to top, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

T 4 S R 5 W  
S 1/16  
S 29 | S 28  
2002

Corner is located on steep south slope.

39.724

The 1/4 section corner of sections 28 and 29, monumented with a limestone, 19 X 10 X 3 inches, dimly marked with 1/4 on the west face.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 28 inches in the ground, in a collar of stone, with aluminum cap marked:

T 4 S R 5 W  
1/4  
S 29 | S 28  
2002

Deposit marked stone alongside.

From which the original bearing trees:

A pinion, 7 inches diameter bears N 55° E, 25.8 links distance, marked, 1/4 S 28 BT. (Record, 35 links).

A pinion, 6 inches diameter bears N 31° W, 19 links distance, marked, 1/4 S 29 BT. (Record N 27° W.).

---

N. 0° 00.9' E., beginning new measurement.

19.751

The North 1/16 section corner of sections 28 and 29, monumented with a ½ inch rebar, in a collar of stone, steel fence post alongside, with a 1½ inch aluminum cap marked:

U I T  
S 29 | S 28  
N 1/16  
83

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 22 inches in the ground, in a collar of stone, with aluminum cap marked:

T 4 S R 5 W  
N 1/16  
S 29 | S 28  
2002

Invert rebar and cap and bury inside of aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH.

## CHAINS

Corner is located 9 links east of an old ditch bearing  
N 80° W.

39.502

The corner of sections 20, 21, 28, and 29, monumented with a  
sandstone 15 X 12 X 4 inches, plainly marked with 2 grooves on  
the south, and 4 grooves on the east edges.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over  
a magnet, 6 inches in the ground, to solid rock, in a mound of  
stone, 4 ft. base, to top, with aluminum cap marked:

T 4 S	R 5 W
S 20	S 21
S 29	S 28
2002	

Deposit marked stone along side.

From which the original bearing trees:

A pinion, 5 inches diameter bears N 18° E, 123 links  
distance, marked, T 4 S R 5 W S 21 BT.  
(Record, 123 links).

A pinion, 4 inches diameter bears S 14° E, 50 links  
distance, marked, T 4 S R 5 W S 28 BT.

A pinion, 9 inches diameter bears S 51° W, 40 links  
distance, marked, T 4 S R 5 W S 29 BT.

A pinion, 5 inches diameter bears N 45° W, 32 links  
distance, marked, T 4 S R 5 W S 20 BT.

From the corner of sections 21, 22, 27, and 28.

S. 89° 45.0' W., between sections 21 and 28.

19.841

Point for the East 1/16 section corner, of sections 21 and 28.

Set an aluminum post, 30 inches long, 2½ inches diameter, over  
a magnet, 24 inches in the ground, with aluminum cap marked:

T 4 S	R 5 W
S 21	
E 1/16	_____
S 28	
2002	

Raise a mound of stone, 4 ft. base, 2 ft. high, to the east.

Corner is located on steep east slope.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS  
39.682

The 1/4 section corner of sections 21 and 28, monumented with a sandstone 20 X 6 X 5 inches, 12 inches in the ground, plainly marked with 1/4 on north face.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 28 inches in the ground, in a collar of stone, with aluminum cap marked:

T 4 S R 5 W  
S 21  
1/4 ———  
S 28  
2002

Deposit marked stone alongside.

From which the original bearing trees:

A pinion, 10 inches diameter bears N 75° E, 357 links distance, marked, 1/4 S 21 BT.  
(Record N 76° E, 322 links).

A pinion, 5 inches diameter bears S 50° E, 221 links distance, marked, 1/4 S 28 BT.  
(Record S 52° E, 154 links).

---

S. 89° 47.4' W., beginning new measurement.

19.915 Point for the West 1/16 section corner, of sections 21 and 28.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 26 inches in the ground, in a collar of stone, with aluminum cap marked:

T 4 S R 5 W  
S 21  
W 1/16 ———  
S 28  
2002

39.830 The corner of sections 20, 21, 28, and 29.

---

N. 0° 14.5' E., between sections 20 and 21.

39.703 The 1/4 section corner of sections 20 and 21, monumented with a mound of stone, original sandstone obliterated.

At the corner point, in the center of the mound of stone,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 14 inches in the ground, to solid rock, in a mound of stone, 5 ft. base, to top, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

T 4 S R 5 W  
1/4  
S 20 | S 21  
2002

From which the original bearing trees:

A pine, 10 inches diameter bears N 47° E, 159 links  
distance, marked 1/4 S 21 BT. (Record, 155 links).

A pine, 14 inches diameter bears S 38° W, 184.8 links  
distance, marked 1/4 S 20 BT. (Record N 38° W, 182 links).

---

From the corner of sections 15, 16, 21, and 22.

S. 89° 27.6' W., between sections 16 and 21.

**19.967** Point for the East 1/16 section corner, of sections 16 and 21.

Set an aluminum post, 30 inches long, 2½ inches diameter, over  
a magnet, 10 inches in the ground, to solid rock, in a mound  
of stone, 3 ft. base, to top, with aluminum cap marked:

T 4 S R 5 W  
S 16  
E 1/16 ———  
S 21  
2002

Corner is located at base of 10 inch diameter pinion.

**39.934** The 1/4 section corner of sections 16 and 21, monumented with  
a limestone 24 X 12 X 3 inches, firmly set, marked 1/4 on  
north face.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over  
a magnet, 10 inches in the ground, to solid rock, in a mound  
of stone, 5 ft. base, to top, with aluminum cap marked:

T 4 S R 5 W  
S 16  
1/4 ———  
S 21  
2002

Deposit marked stone alongside.

From which the original bearing trees:

A pinion, 38 inches diameter bears N 80° E, 51 links  
distance, marked, 1/4 S 16 BT. (Record N 65° E, 62 links).

A pinion, 12 inches diameter bears S 14° W, 51 links  
distance, marked, 1/4 S 21 BT. (Record S 10° W, 50 links).

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH.

## CHAINS

From the standard corner of section 31 and 32, on the South boundary, hereinbefore described.

N. 0° 40.1' E., between sections 31 and 32.

**19.772** Point for the South 1/16 section corner of sections 31 and 32.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
S 1/16  
S 31 | S 32  
2002

**39.544** The 1/4 section corner of sections 31 and 32, determined from an original bearing tree:

A pinion, 9 inches diameter bears S 80° W, 65 links distance, marked, 1/4 S 31 BT.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 14 inches in the ground, to solid rock, in a mound of stone, 4 ft. base, to top, with aluminum cap marked:

T 4 S R 5 W  
1/4  
S 31 | S 32  
2002

---

N. 1° 24.1' W., beginning new measurement.

**19.768** Point for the North 1/16 section corner of sections 31 and 32.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 26 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
N 1/16  
S 31 | S 32  
2002

**39.536** Point for the corner of sections 29, 30, 31, and 32, at proportionate distance; there is no remaining evidence of the original stone,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
S 30 | S 29  
S 31 | S 32  
2002

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

Raise a mound of stone, 4 ft. base, to the west.

Right of way fence for state route 33, bears west, 63.6 links distance.

---

From the corner of sections 28, 29, 32, and 33.

S. 88° 41.7' W., between sections 29 and 32.

**40.312** The 1/4 section corner of sections 29 and 32, determined from an original bearing tree:

A pinion, 9 inches diameter bears S 35° E, 82 links distance, marked, 1/4 S 32 BT.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 4 inches in the ground, to solid rock, in a mound of stone, 5 ft. base, to top, with aluminum cap marked:

T 4 S R 5 W  
S 29  
1/4 ———  
S 32  
2002

---

N. 89° 49.0' W., beginning new measurement.

**19.828** Point for the West 1/16 section corner, of sections 29 and 32.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 26 inches in the ground, in a collar of stone, with aluminum cap marked:

T 4 S R 5 W  
S 29  
W 1/16 ———  
S 32  
2002

**39.656** The corner of sections 29, 30, 31, and 32.

---

S. 89° 20.0' W., between sections 30 and 31.

**19.854** Point for the East 1/16 section corner, of sections 30 and 31.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

T 4 S R 5 W  
S 30  
E 1/16 —————  
S 31  
2002

- 39.708** The 1/4 section corner of sections 30 and 31, monumented with a sandstone 18 X 10 X 6 inches, loosely set, dimly marked 1/4 on north face.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 22 inches in the ground, in a collar of stone, with aluminum cap marked:

T 4 S R 5 W  
S 30  
1/4 —————  
S 31  
2002

Deposit marked stone alongside.

There is no remaining evidence of the original bearing trees.

Corner is located on steep north slope in pinion and juniper.

---

From the corner of sections 29, 30, 31, and 32.

N. 0° 49.3' E., between sections 29 and 30.

- 19.765** Point for the South 1/16 section corner of sections 29 and 30.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 10 inches in the ground, to solid rock, in mound of stone, 3 ft. base, to top, with aluminum cap marked:

T 4 S R 5 W  
S 1/16  
S 30 | S 29  
2002

Corner is located on steep south slope, in loose shale.

- 39.530** The 1/4 section corner of sections 29 and 30, monumented with a sandstone, 18 X 12 X 3 inches, buried below the ground, broken and marks obliterated.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 20 inches in the ground, to solid rock, in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 5 W., Uintah Special Meridian, Utah.

CHAINS

T 4 S R 5 W  
1/4  
S 30 | S 29  
2002

Deposit marked stone alongside.

From which the original bearing trees:

A pine, 7 inches diameter bears S 40° E, 60 links  
distance, plainly marked, 1/4 S 29 BT.

A pine, 9 inches diameter bears S 65° W, 71 links  
distance, plainly marked, 1/4 S 30 BT.

From the corner of sections 20, 21, 28, and 29.

S. 88° 46.0' W., between sections 20 and 29.

**39.560**

The 1/4 section corner of sections 20 and 29, determined from  
an original bearing tree:

A pine, 10 inches diameter bears North, 55 links  
distance, marked, 1/4 S 20 BT.

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over  
a magnet, 6 inches in the ground, to solid rock, in a mound of  
stone, 5 ft. base, to top, with aluminum cap marked:

T 4 S R 5 W  
S 20  
1/4 ———  
S 29  
2002

The Subdivision of Section 14,  
T. 4 S., R. 5 W., Uintah Special Meridian, Utah.

From the 1/4 section corner of sections 14 and 23.

N. 0° 00.6' E., on the N - S centerline of section 14.

**19.894**

Point for the Center South 1/16 section corner of section 14.

Set an aluminum post, 30 inches long, 2½ inches diameter, over  
a magnet, 26 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
C  
S 1/16 | S 14  
C  
2002

THE SUBDIVISION OF SECTION 14,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS  
39.788

Point for the Center 1/4 section corner of section 14, at intersection of the E - W centerline of section 14.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 22 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
C 1/4  
S 14  
2002

Raise a mound of stone south.

Corner is located on steep north slope, 68 links distance from the top of ridge, in loose shale rock.

79.689

The 1/4 section corner of sections 11 and 14.

---

From the 1/4 section corner of sections 13 and 14.

S. 89° 57.0' W., on the E - W centerline of section 14.

39.749

The center 1/4 section corner of section 14.

59.686

Point for the Center West 1/16 section corner of section 14, not monumented.

79.623

The 1/4 section corner of section 14 and 15.

---

From the West 1/16 section corner of sections 14 and 23.

N. 0° 00.7' E., on the N - S centerline of the Southwest 1/4 of section 14.

19.926

Point for the South West 1/16 section corner of section 14, at intersection of the E - W centerline of the Southwest 1/4 of section 14.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 22 inches in the ground, in a collar of stone, with aluminum cap marked:

T 4 S R 5 W  
SW 1/16  
S 14  
2002

39.852

The point for the Center West 1/16 section corner of section 14.

---

From the Center South 1/16 section corner of section 14.

S. 89° 51.4' W., on the E - W centerline of the Southwest 1/4 of section 14.

THE SUBDIVISION OF SECTION 14,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS  
19.939

The South West 1/16 section corner of section 14.

The South 1/16 section corner of sections 14 and 15.

---

The Subdivision of Section 15,  
T. 4 S., R. 5 W., Uintah Special Meridian, Utah.

---

From the 1/4 section corner of sections 15 and 22.

N. 0° 03.5' W., on the N - S centerline of section 15.

39.984

Point for the Center 1/4 section corner of section 15, at intersection of the E - W centerline of section 15.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 26 inches in the ground, in a collar of stone, with aluminum cap marked:

T 4 S R 5 W  
C 1/4  
S 15  
2002

Corner is located on east slope, in open brush.

79.835

The 1/4 section corner of sections 10 and 15.

---

From the 1/4 section corner of sections 14 and 15.

S. 89° 51.5' W., on the E - W centerline of section 15.

39.858

The center 1/4 section corner of section 15.

80.106

The 1/4 section corner of sections 15 and 16.

---

The Subdivision of Section 21,  
T. 4 S., R. 5 W., Uintah Special Meridian, Utah.

---

From the 1/4 section corner of sections 21 and 28.

N. 0° 10.4' W., on the N - S centerline of section 21.

19.875

Point for the Center South 1/16 section corner of section 21.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
C  
S 1/16 | S 21  
C  
2002

THE SUBDIVISION OF SECTION 21,  
T. 4 S., R. 5 W., UTAH SPECIAL MERIDIAN, UTAH

## CHAINS

Raise a mound of stone, 3 ft. base, to the west.

Corner is located at base of hill.

- 39.750** Point for the Center 1/4 section corner of section 21, at intersection of the E - W centerline of section 21.

Set a 5/8 inch rebar, 6 inches in solid sandstone, 2 inches exposed, with aluminum cap marked:

T 4 S R 5 W  
C 1/4  
S 21  
2002

- 59.698** Point for the Center North 1/16 section corner of section 21.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 16 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap marked:

T 4 S R 5 W  
C  
N 1/16 | S 21  
C  
2002

Corner is located on steep north slope.

- 79.646** The 1/4 section corner of section 16 and 21.

---

From the 1/4 section corner of sections 21 and 22.

S. 89° 43.3' W., on the E - W centerline of section 21.

- 19.897** Point for the Center East 1/16 section corner of section 21.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 26 inches in the ground, in a collar of stone, with aluminum cap marked:

T 4 S R 5 W  
S 21  
CE 1/16  
2002

- 39.794** The center 1/4 section corner of section 21.

- 79.334** The 1/4 section corner of sections 20 and 21.

---

From the Center East 1/16 section corner of section 21.

N. 0° 04.2' W., on the N - S centerline of the Northeast 1/4 of section 21.

THE SUBDIVISION OF SECTION 21,  
T. 4 S., R. 5 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS  
19.993

Point for the North East 1/16 section corner of section 21, at intersection of the E - W centerline of the Northeast 1/4 of section 21.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 18 inches in the ground, to solid rock, in a collar of stone, 2 ft. base, with aluminum cap marked:

T 4 S R 5 W  
NE 1/16  
S 21  
2002

39.986 The East 1/16 section corner of sections 16 and 21.

---

From the true point for the North 1/16 section corner of sections 21 and 22.

S. 89° 35.4' W., on the E - W centerline of the Northeast 1/4 of section 21.

19.932 The North East 1/16 section corner of section 21.

39.864 The Center North 1/16 section corner of section 21.

---

From the East 1/16 section corner of sections 21 and 28.

N. 0° 05.4' W., on the N - S centerline of the Southeast 1/4 of section 21.

19.880 Point for the South East 1/16 section corner of section 21, at intersection of the E - W centerline of the Southeast 1/4 of section 21.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
SE 1/16  
S 21  
2002

Raise a mound of stone, 3 ft. base, to the west.

Corner is located at base of hill, 50 ft. southeast of dirt road.

39.760 The Center East 1/16 section corner of section 21.

---

From the South 1/16 section corner of sections 21 and 22.

S. 89° 44.1' W., on the E - W centerline of the Southeast 1/4 of section 21.

19.869 The South East 1/16 section corner of section 21.

THE SUBDIVISION OF SECTION 21,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS  
39.738

The Center South 1/16 section corner of section 21.

---

The Subdivision of Section 22,  
T. 4 S., R. 5 W., Uintah Special Meridian, Utah.

---

From the 1/4 section corner of sections 22 and 27.

N. 0° 11.1' E., on the N - S centerline of section 22.

39.869

Point for the Center 1/4 section corner of section 22, at intersection of the E - W centerline of section 22.

Set a 5/8 inch rebar, 4 inches in solid sandstone, 4 inches exposed, with aluminum cap marked:

T 4 S R 5 W  
C 1/4  
S 22  
2002

59.787

Point for the Center North 1/16 section corner of section 22.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 20 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
C  
N 1/16 | S 22  
C  
2002

Corner is located on north slope in pinion.

79.705

The 1/4 section corner of sections 15 and 22, hereinbefore described.

---

From the 1/4 section corner of sections 22 and 23.

S. 89° 24.7' W., on the E - W centerline of section 22.

39.429

The center 1/4 section corner of section 22.

79.557

The 1/4 section corner of sections 21 and 22.

---

From the Center North 1/16 section corner of section 22.

S. 89° 35.1' W., on the E - W centerline of the Northwest 1/4 of section 22.

40.178

The true point for the North 1/16 section corner of sections 21 and 22.

THE SUBDIVISION OF SECTION 28,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

---

The Subdivision of Section 28,  
T. 4 S., R. 5 W., Uintah Special Meridian, Utah.

---

From the 1/4 section corner of sections 28 and 33.

N. 0° 03.3' E., on the N - S centerline of section 28.

**39.802** Point for the Center 1/4 section corner of section 28, at intersection of the E - W centerline of section 28,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 20 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
C 1/4  
S 28  
2002

Corner is located on west slope, in open brush.

**59.598** Point for the Center North 1/16 section corner of section 28.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
C  
N 1/16 | S 28  
C  
2002

Corner is located on steep west slope, 1.5 chains from bottom.

**79.394** The 1/4 section corner of sections 21 and 28.

---

From the 1/4 section corner of sections 27 and 28.

S. 89° 55.2' W., on the E - W centerline of section 28.

**39.680** The Center 1/4 section corner of section 28.

**59.584** Point for the Center West 1/16 section corner of section 28.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 18 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap marked:

T 4 S R 5 W  
W 1/16  
C ——— C  
S 28  
2002

THE SUBDIVISION OF SECTION 28,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

Corner is located on steep southwest slope.

**79.488** The 1/4 section corner of sections 28 and 29.

---

From the Center West 1/16 section corner of section 28.

N. 0° 02.1' E., on the N - S centerline of the Northwest 1/4 of section 28.

**19.773** The North West 1/16 section corner of section 28, monumented with, a 3/8 inch rebar, with 1 1/4 inch aluminum cap marked:

U I T  
NW 1/16 S 28  
83

At the corner point,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 20 inches in the ground, in a collar of stone, 2 ft. base, to top, with aluminum cap marked:

T 4 S R 5 W  
NW 1/16  
S 28  
2002

Invert rebar and cap and bury inside aluminum post.

Corner is located on steep north slope, 20 ft. from dirt road bearing northeast and southwest.

**39.546** The West 1/16 section corner of sections 21 and 28.

---

From the Center North 1/16 section corner of section 28.

S. 89° 51.3' W., on the E - W centerline of the Northwest 1/4 of section 28.

**19.910** The North West 1/16 section corner of section 28.

**39.820** The North 1/16 section corner of sections 28 and 29.

---

The Subdivision of Section 29,  
T. 4 S., R. 5 W., Uintah Special Meridian, Utah.

---

From the 1/4 section corner of sections 29 and 32.

N. 0° 36.5 E., on the N - S centerline of section 29.

**20.073** Point for the Center South 1/16 section corner of section 29.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 12 inches in the ground, to solid rock, in a collar of stone, 4 ft. base, with aluminum cap marked:

THE SUBDIVISION OF SECTION 31,  
T. 4 S., R. 5 W., UTAH SPECIAL MERIDIAN, UTAH

## CHAINS

T 4 S R 5 W  
C  
S 1/16 | S 29  
C  
2002

Corner is located at base of hill.

- 40.146** True point for the Center 1/4 section corner of section 29, at intersection of the E - W centerline of section 29, falls on inaccessible ledge.

From which a point selected for an offline witness corner to the Center 1/4 section corner of section 29 bears, N. 6°27.9' E., 0.021 links distance.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 20 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
W C  
C 1/4  
S 29  
2002

Corner is located at top of very steep southeast slope, at base of cliff.

- 59.721** Point for the Center North 1/16 section corner of section 29.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 15 inches in the ground, to solid rock, in a mound of stone, 2 ft. base, to top, with aluminum cap marked:

T 4 S R 5 W  
C  
N 1/16 | S 29  
C  
2002

Corner is located on north slope, in scattered pinion.

- 79.296** The 1/4 section corner of section 20 and 29.

---

From the 1/4 section corner of sections 28 and 29.

S. 89° 17.1' W., on the E - W centerline of section 29.

- 39.963** True point for the center 1/4 section corner of section 29.

- 59.720** Point for the Center West 1/16 section corner of section 29.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 29,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

T 4 S R 5 W  
W 1/16  
C ——— C  
S 29  
2002

Corner is located on steep northeast slope, in scattered pinion.

**79.477** The 1/4 section corner of section 29 and 30.

---

From the North 1/16 section corner of sections 28 and 29.  
S. 89° 01.6' W., on the E - W centerline of the Northeast 1/4  
of section 29.

**39.761** The Center North 1/16 section corner of section 29.

---

From the South 1/16 section corner of sections 28 and 29.

S. 88° 59.3' W., on the E - W centerline of the Southeast 1/4  
of section 29.

**40.137** The Center South 1/16 section corner of section 29.

---

From the West 1/16 section corner of sections 29 and 32.

N. 0° 42.9' E., on the N - S centerline of the Southwest 1/4 of  
section 29.

**19.919** Point for the South West 1/16 section corner of section 29, at  
intersection of the E - W centerline of the Southwest 1/4 of  
section 29.

Set an aluminum post, 30 inches long, 2½ inches diameter, over  
a magnet, 26 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
SW 1/16  
S 29  
2002

**39.838** The Center West 1/16 section corner of section 29.

---

From the Center South 1/16 section corner of section 29.

S. 89° 44.1' W., on the E - W centerline of the Southwest 1/4  
of section 29.

**19.791** The South West 1/16 section corner of section 29.

**39.582** The South 1/16 section corner of sections 29 and 30.

THE SUBDIVISION OF SECTION 31,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

---

The Subdivision of Section 31,  
T. 4 S., R. 5 W., Uintah Special Meridian, Utah.

---

From the 1/4 section corner of section 31, on the South boundary, hereinbefore described.

N. 0° 17.2' W., on the N - S centerline of section 31.

**19.740** Point for the Center South 1/16 section corner of section 31.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
CS 1/16  
S 31  
2002

**39.480** Point for the Center 1/4 section corner of section 31, at intersection of the E - W centerline of section 31,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 26 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
C 1/4  
S 31  
2002

Right-of-way fence for state route 191 bears North, 11.2 links distance.

**59.105** Point for the Center North 1/16 section corner of section 31.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 26 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
C N 1/16  
S 31  
2002

**78.730** The 1/4 section corner of sections 30 and 31.

---

From the 1/4 section corner of sections 31 and 32.

S. 89° 44.3' W., on the E - W centerline of section 31.

**20.240** Point for the Center East 1/16 section corner of section 31.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 26 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 31,  
T. 4 S., R. 5 W., UTAH SPECIAL MERIDIAN, UTAH

## CHAINS

T 4 S R 5 W  
CE 1/16  
S 31  
2002

Corner is located on steep north slope.

**40.480** The center 1/4 section corner of section 31.

**60.416** Point for the Center West 1/16 section corner of section 31,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 24 inches in the ground, in a collar of stone, 3 ft. base, to top, with aluminum cap marked:

T 4 S R 5 W  
CW 1/16  
S 31  
2002

**81.002** The 1/4 section corner of sections 31 and 36, on the West boundary, hereinbefore described.

---

From the Center East 1/16 section corner of section 31.

N. 0° 50.8' W., on the N - S centerline of the Northeast 1/4 of section 31.

**19.695** Point for the North East 1/16 section corner of section 31, at intersection of the E - W centerline of the Northeast 1/4 of section 31.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 12 inches in the ground, to solid rock, in a mound of stone, 4 ft. base, with aluminum cap marked:

T 4 S R 5 W  
NE 1/16  
S 31  
2002

**39.390** The East 1/16 section corner of sections 30 and 31.

---

From the North 1/16 section corner of sections 31 and 32.

S. 89° 32.3' W., on the E - W centerline of the Northeast 1/4 of section 31.

**20.047** The North East 1/16 section corner of section 31.

**40.094** The Center North 1/16 section corner of section 31.

---

From the East 1/16 section corner of section 31, on the South boundary, hereinbefore described.

THE SUBDIVISION OF SECTION 31,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

N. 0° 11.5' E., on the N - S centerline of the Southeast 1/4 of section 31.

- 19.755** Point for the South East 1/16 section corner of section 31, at intersection of the E - W centerline of the Southeast 1/4 of section 31.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
SE 1/16  
S 31  
2002

- 39.510** The Center East 1/16 section corner of section 31.

---

From the South 1/16 section corner of sections 31 and 32.

S. 89° 46.8' W., on the E - W centerline of the Southeast 1/4 of section 31.

- 20.076** The South East 1/16 section corner of section 31.

- 40.152** The Center South 1/16 section corner of section 31.

---

From the West 1/16 section corner of section 31, on the South boundary, hereinbefore described.

N. 0° 11.6' W., on the N - S centerline of the Southwest 1/4 of section 31.

- 39.302** The Center West 1/16 section corner of section 31.

---

The Subdivision of Section 32,  
T. 4 S., R. 5 W., Uintah Special Meridian, Utah.

---

From the 1/4 section corner of section 32, on the South boundary, hereinbefore described.

N. 0° 25.1' W., on the N - S centerline of section 32.

- 39.795** Point for the Center 1/4 section corner of section 32, at intersection of the E - W centerline of section 32,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 24 inches in the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap marked:

T 4 S R 5 W  
C1/4  
S 32  
2002

THE SUBDIVISION OF SECTION 32,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

59.386

Point for the Center North 1/16 section corner of section 32,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 26 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
CN 1/16  
S 32  
2002

78.977

The 1/4 section corner of sections 29 and 32.

---

From the 1/4 section corner of sections 32 and 33.

S. 89° 40.8' W., on the E - W centerline of section 32.

40.013

The center 1/4 section corner of section 32.

59.503

Point for the Center West 1/16 section corner of section 32,

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
CW 1/16  
S 32  
2002

78.993

The 1/4 section corner of sections 31 and 32.

---

From the Center West 1/16 section corner of section 32.

N. 0° 54.7' W., on the N - S centerline of the Northwest 1/4 of section 32.

19.679

Point for the North West 1/16 section corner of section 32, at intersection of E -W centerline of the Northwest 1/4 of section 32.

Set an aluminum post, 30 inches long, 2½ inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T 4 S R 5 W  
NW 1/16  
S 32  
2002

39.358

The West 1/16 section corner of sections 29 and 32.

---

From the Center North 1/16 section corner of section 32.

S. 89° 56.0' W., on the E - W centerline of the Northwest 1/4 of section 32.

19.658

The North West 1/16 section corner of section 32.

THE SUBDIVISION OF SECTION 32,  
T. 4 S., R. 5 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

**39.316** The North 1/16 section corner of sections 31 and 32.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Merrill Cazier	Cadastral Surveyor
M. Ross Workman	Supervisory Cadastral Surveyor
Ronald K. Baugh	Supervisory Cadastral Surveyor
Scott Bishop	Survey Technician
Tyler Trujillo	Survey Technician
Brandon Sanchez	Survey Technician
Nick George	Survey Aid

## CERTIFICATE OF SURVEY

I **Merrill D. Cazier, Cadastral Surveyor**, hereby certify upon honor, that in pursuance of special instructions bearing the date of the **24 day of June, 2002**, I have **executed the Dependent Resurvey of a portion of the south boundary (First Standard Parallel South), a portion of the west boundary, and a portion of the subdivisional lines, and the subdivision of sections 14, 15, 21, 22, 28, 29, 31 and 32 on Township 4 South, Range 5 West,**

of the **Uintah Special Meridian**, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special and supplemental special instructions, the Manual of Instructions of the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

4-13-04

Date

Merrill D. Cazier

Cadastral Surveyor

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The following field notes of the **Dependent Resurvey of a portion of the south boundary (First Standard Parallel South), a portion of the west boundary, and a portion of the subdivisional lines, and the subdivision of sections 14, 15, 21, 22, 28, 29, 31 and 32 on Township 4 South, Range 5 West, Uintah Special Meridian, Utah,**

executed by **Merrill D. Cazier, Cadastral Surveyor** having been critically examined and found correct, are hereby approved.

May 3, 2004

Date

Daniel W. Welch

(Chief Cadastral Surveyor)