

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 22, 23, 26, 27 AND 34,

IN

TOWNSHIP 14 SOUTH, RANGE 3 EAST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

John F. Carroll
Cadastral Surveyor

Under special instructions dated **July 19, 2002**, approved **July 19, 2002**,
which provided for the surveys included under Group Number **951** and
assignment instructions dated **July 19, 2002**

Survey commenced **July 29, 2002**
Survey completed **December 1, 2004**

INDEX DIAGRAM

Township 14 South, Range 3 East

6	5	4	3	2	1
7	8	9	10	11 8 7	12
18	17	16	15	14 7 15 7	13 4 3
19	20	21 20 18	22 13 19 12	23 7 13 6	24 3
30	29	28 18 16	27 11 17 9	26 5 10 4	25 4
31	32	33 16 15	34 9 8	35	36

The Subdivision of Section 22.....Page 21
 The Subdivision of Section 23.....Page 25
 The Subdivision of Section 26.....Page 26
 The Subdivision of Section 27.....Page 28
 The Subdivision of Section 34.....Page 30

T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of a portion of the east boundary, a portion of the subdivisional lines and the subdivision of sections 22, 23, 26, 27 and 34 in T. 14 S., R. 3 E., Salt Lake Meridian, Utah.

History of Surveys

Surveyed by		Retr. or Resurveyed by		
SOUTH BOUNDARY				
Portion	C. Mogo	1856		
All	E.W. Koeber	1894	E.W. Kober	1894
All			Stewart & Stewart	1897
EAST BOUNDARY (First Guide Meridian East)				
Portion	C. Mogo	1856		
All	A.D. Ferron	1872	A.D. Ferron	1872
All			E.W. Koeber	1894
WEST BOUNDARY				
All	C. Mogo	1856		
All			A.D. Ferron	1874
All			E.W. Koeber	1894
Portion			H.D. Page & J.M. Litz	1903
NORTH BOUNDARY				
Portion	C. Mogo	1856		
All	E.W. Koeber	1894	E.W. Koeber	1894
Portion			G.E. Reynolds	1984-85
SUBDIVISION				
Portion	C. Mogo	1856		
Portion	E.W. Koeber	1894	E.W. Koeber	1894

T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 951, dated July 19, 2002.

The direction of the lines were determined by mean geodetic inverse between corners. Global Positioning System (GPS) utilizing Real-time kinematic (RTK) was used throughout the survey. Cadastral Measurement Management (CMM) was utilized during the course of the survey.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the corner of sections 2, 3, 34 and 35, Ts. 14 and 15 S., R. 3 E., as determined by a tie to the National Geodetic Survey Control Station "MORONI", utilizing GPS, using RTK techniques, is as follows:

Latitude: 39°32'57.362" N. Longitude: 111°33'53.404" W.
N.A.D. 1983 (1994), N.A.V.D. 1988 5798 feet

The geographic position of National Geodetic Survey Control Station "MORONI" is as follows:

Latitude: 39°33'06.08165" N. Longitude: 111°34'02.68785" W.
N.A.D. 1983 (1994), N.A.V.D. 1988 5865 feet.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the East Boundary,
T. 14 S., R. 3 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
A.D. Ferron in 1872 and the Resurvey
Executed by E.W. Koeber in 1894

Beginning at the cor. of secs. 19 and 30, T. 14 S., R. 4 E.,
monumented with a limestone, 8X8X8 ins. above ground, loosely
set, clearly mkd. with 4 notches on the north and 2 notches on
the south edges, with a reference mound of stone to the east.
Not remonumented.

Cor. is located on a SE slope in juniper trees and at
intersection of fences bearing E and S.

N. 0°28.7' W., on the west boundary of sec. 19, T. 14 S., R. 4 E.

40.272 Point for the 1/4 sec. cor. of sec. 19, T. 14 S., R. 4 E., at
proportionate dist.; there is no remaining evidence of the
original cor. Not monumented.

78.172 Point for the closing cor. of secs. 13 and 24, at proportionate
dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins.
in the ground with magnet at base, in a mound of stone, 4 1/2
ft. diam., to top, with aluminum cap mkd.;

		T14S	
		R3E R4E	
C S13			S19
C S24			
		2004	

Drive a steel fence post alongside aluminum post.

Cor. is located on a southerly slope in juniper.

80.544 The cor. of secs. 18 and 19, T. 14 S., R. 4 E., monumented with
a sandstone, 12X5X5 ins., firmly set, clearly mkd. with 3
notches on the north and south sides, with a reference mound of
stone to the north.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins.
in the ground with magnet at base, in a mound of stone, 4 ft.
diam., to top, with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T14S
R3E R4E
S13 | S18
| S19
2004

Bury mkd. stone alongside aluminum post.

Drive a steel fence post alongside aluminum post.

Cor. is located on a SE slope in juniper, 2 ft. South of a
fence, bears E and W.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 14 S., R. 3 E., Salt Lake Meridian, Utah

Reestablishment of the Survey
Executed by E.W. Koeber in 1894.

From the 1/4 sec. cor. of secs. 25 and 36, monumented with a
limestone, 8X10X6 ins. above ground, firmly set, clearly mkd.
1/4 on north face, with an unrecorded rebar, 1/2 in. diam.,
firmly set, projecting 4 ins. above ground, along west side of
mkd. stone, with a reference mound of stone to the west.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins.
in the ground with a magnet at base, and in a mound of stone, 3
ft. diam., to top, with aluminum cap mkd.:

T14S R3E
S25
1/4 ———
S36
2002

Bury mkd. stone on west side of aluminum post.

Bury rebar inside aluminum post.

Drive a steel fence post along east side of aluminum post.

Cor. is located on a W slope in cedar and grass, 1 ft. South of
a fence, bears E and W.

S. 88°31.4' W., bet. secs. 25 and 36.

40.268 Point for the cor. of secs. 25, 26, 35 and 36, at proportionate
dist.; there is no remaining evidence of the original cor.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, in a mound of stone, 2 ft. diam. to top, with aluminum cap mkd.:

T14S	R3E
S26	S25
S35	S36
2002	

Drive a steel fence post alongside aluminum post.

Cor. is located on an easterly slope in juniper.

From this point, the cor. of secs. 1, 2, 35 and 36, Ts. 14 and 15 S., R. 3 W., bears S. 1°01.8' E., 79.672 chs. dist., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with aluminum cap mkd. T14S R3E 35 36 12 T15S 2000, with evidence of original cor. alongside aluminum post, as recorded in Sanpete County Section Corner Ties, Sanpete County Recorders office, and is accepted as a faithful and careful perpetuation of the original cor.

from which the local reference objects

A cedar fence post, 4 ins. diam., bears North, 85 1/2 lks. dist., to a double headed nail.

A cedar fence post, 4 ins. diam., bears N. 30° E., 98 1/2 lks. dist., to a double headed nail.

A cedar fence post, 3 ins. diam., bears N. 83° E., 44 lks. dist., to a double headed nail.

A cedar fence post, 3 ins. diam., bears S. 1° W., 23 1/2 lks. dist., to a double headed nail.

A cedar fence post, 4 ins. diam., bears West, 84 lks. dist., to a double headed nail.

Cor. is located on a flat in juniper and sagebrush.

The control line was fully retraced, and no evidence of the intervening cor. was found.

N. 0°42.3' W., bet. secs. 25 and 26.

39.830 Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, and in a mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:

T14S R3E
1/4
S26 | S25
2002

Drive a cedar fence post, 48 ins. long, 2 ins. diam., alongside aluminum post.

Cor. is located on a gradual SW slope in scattered cedar to the East.

- 79.660 The cor. of secs. 23, 24, 25 and 26, monumented with an unrecorded rebar, 1/2 in. diam., firmly set, projecting 4 ins. above ground, with plastic cap mkd. LUDLOW ENG LS152774 in an embedded mound of stone, 2 ft. diam., with a sandstone, 14X9X5 ins., clearly mkd. with 2 notches on one side, laying near the rebar and plastic cap. (Record; 18X9X5 ins., 2 notches on the south and 1 notch on the east sides). The rebar and cap are accepted as a faithful and careful perpetuation of the original cor. Note: Sanpete County Section Corner Ties indicate a 3 1/2 in. aluminum cap was set at this sec. cor. No remains of the aluminum cap were recovered.

At the corner point

Set an aluminum post, 30 ins. long, 26 ins. in the ground, with magnet at base, and in a mound of stone, 3 ft. diam. to top, with aluminum cap mkd.

T14S R3E
S23 | S24

S26 | S25
2002

from which the local reference object

A fence post brace, bears South, 42 1/2 lks. dist., to a double headed nail.

No remains of the other reference objects were recovered.

Bury mkd. stone on east side of aluminum post.

Bury rebar and plastic cap inside aluminum post.

Drive a steel fence post along NW side of aluminum post.

Cor. is located on a W slope in cedar and in a fence, bears N and S.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0°20.4' W., bet. secs. 23 and 24.

- 40.062** Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor., falls within a turkey coop.

Set a rebar, 18 ins. long, 5/8 in. diam., 18 ins. in the ground, with 2 ins. diam. aluminum cap mkd.:

	1/4	
S23		S24
2004		

Cor. is located on a SE slope in scattered juniper, 25 ft. East of a fence, bears N. 10° E. and S. 10° W., and 10 ft. S. 60° E. of a juniper, 10 ins. diam., not marked.

- 80.124** Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist.; there is not remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to solid rock with magnet at base, in a supporting mound of stone, 4 feet diam., to top, with aluminum cap mkd.:

T14S	R3E	
S14		S13

S23		S24
2004		

Drive a steel fence post along south side of aluminum post.

Cor. is located on a SE slope in grass, scattered sagebrush and thick juniper.

From this point, the closing cor. of secs. 13 and 24, bears N. 87°46.8' E., 79.190 chs. dist., on the east bdy. of the Township, hereinbefore described.

The control line was fully retraced, and no evidence of the intervening cor. was found.

N. 1°41.6' W., bet. secs. 13 and 14.

- 40.077** Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor. Not monumented.

- 80.154** The cor. of secs. 11, 12, 13 and 14, monumented with a sandstone, 20X14X10 ins., loosely set, clearly mkd. with 4 notches on the south and 1 notch on the east edges, in a mound of stone

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock, in a supporting mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:

T14S	R3E
S11	S12
S14	S13
2004	

Deposit mkd. stone alongside aluminum post.

Cor. is located on open flat in thick sagebrush.

N. 0°46.1' W., bet. secs. 11 and 12.

- 39.982** The 1/4 sec. cor. of secs. 11 and 12, monumented with a sandstone, 16X10X8 ins., loosely set, clearly mkd. 1/4 on west face, in a mound of stone. Note: This 1/4 sec. cor. is adjacent to B.L.M. administered lands and was recovered and remonumented prior to the recovery of the cor. of secs. 11, 12, 13 and 14.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground with magnet at base, in a supporting mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:

T14S	R3E
1/4	
S11	S12
2004	

Bury mkd. stone along west side of aluminum post.

Drive a wooden fence post, 48 ins. long, 4 ins. diam., 18 ins. in the ground along north side of aluminum post.

Cor. is located on a SE slope on rock outcrop.

From the cor. of secs. 2, 3, 34 and 35, Ts. 14 and 15 S., R. 3 E., monumented with a sandstone, 12X10X5 ins., loosely set, clearly mkd. with 4 notches on the west and 2 notches on the east edges. (Record; limestone, 6X10X5 ins. above ground)

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with a magnet at base, in a collar of stone, 2 ft. diam., to top, with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T14S	R3E
S34	S35
S3	S2
T15S	
2002	

Bury mkd. stone on east side of aluminum post.

Drive a PVC pipe, 60 ins. long, 1 1/2 ins. diam., 20 ins. in the ground, along NW side of aluminum post.

Cor. is located on an easterly slope in sagebrush.

N. 0°58.7' W., bet. secs. 34 and 35.

- 40.504** The 1/4 sec. cor. of secs. 34 and 35, monumented with a limestone, 15X10X6 ins., loosely set, dimly mkd. 1/4 on west face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with a magnet at base, and in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:

T14S	R3E
1/4	
S34	S35
2002	

Bury mkd. stone alongside aluminum post.

Cor. is located on a gradual NW slope in sagebrush and scattered cedar, 67 ft. South of gulch, drains SW.

N. 2°09.6' W., beginning new measurement.

- 40.387** The cor. of secs. 26, 27, 34 and 35, monumented with a limestone, 16X12X10 ins., firmly set, clearly mkd. with 1 notch notch on the south and 2 notches on the east edges, with an aluminum post, 2 1/2 ins. diam. alongside, with aluminum cap mkd. T14S R3E 27 26 34 35 2000, as recorded in Sanpete County Section Corner Ties, Sanpete County Recorders office.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with aluminum cap mkd.:

T14S	R3E
S27	S26
S34	S35
2002	

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Bury mkd. stone on south side of aluminum post.

Bury San Pete County aluminum post on east side of aluminum post.

from which the local reference objects

A cedar tree, 8 ins. diam., bears S. 50° E., 25 1/2 lks. dist. to double headed nail. (Local record; 26 lks. dist.)

A multi trunked cedar, with 3 ins. diam. branch, bears S. 10° W., 76 1/2 lks. dist. to a double headed nail.

A multi trunked cedar, with 3 ins. diam. branch, bears N. 80° W., 42 1/2 lks. dist. to a double headed nail. (Local record; 43 lks. dist.)

A multi trunked cedar, with 5 ins. diam., branch, bears N. 10° W., 23 lks. dist. to double headed nail.

Cor. is located on a SE slope in scattered cedar.

From the cor. of secs. 25, 26, 35 and 36.

S. 89°20.5' W., bet. secs. 26 and 35.

- 40.246** Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T14S R3E
S26
1/4 ———
S35
2002

Cor. is located on a field in scattered sagebrush and cedar.

- 80.492** The cor. of secs. 26, 27, 34 and 35.

N. 0°40.6' W., bet. secs. 26 and 27.

- 19.841** The S 1/16 sec. cor. of secs. 26 and 27, monumented with an unrecorded rebar, 1/2 in. diam., firmly set, with plastic cap mkd. LUDLOW ENG LS152774, and is accepted as a careful and faithful establishment of the cor.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
 T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH
 CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 27 ins. in the ground with magnet at base, in a mound of stone, 3 1/3 ft. diam., with aluminum cap mkd.:

S1/16
 S27 | S26
 2002

Bury rebar and plastic cap at base of aluminum post.

Drive a steel fence post on the north side of the aluminum post.

Cor. is located on a flat with scattering cedar and turkey coops, 90 ft. South of road, bears S. 85° W., and 102 ft. West of turkey coop fence, bears N and S.

N. 0°40.6' W., beginning new measurement.

- 19.841** The 1/4 sec. cor. of secs. 26 and 27, monumented with a limestone, 11X6X4 ins., loosely set, dimly mkd. 1/4 on west face (scratched), with an aluminum post, 2 1/2 ins. diam., firmly set, with aluminum cap mkd. T14S 1/4 R4E 27 26 2000 along west side of mkd. stone, as recorded in Sanpete County Section Corner Ties, Sanpete County Recorders office.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T14S R3E
 1/4
 S27 | S26
 2002

Bury mkd. stone along south side of aluminum post.

Bury aluminum post along south side of aluminum post.

from which the local reference objects

A multi forked cedar, with 4 ins. diam. branch bears N. 20° E., 30 1/2 lks. dist. to double headed nail.

A multi forked cedar, with 8 ins. diam. branch, bears N. 62° E., 56 lks. dist. to double headed nail.

A multi forked cedar, with 6 ins. diam. branch, bears S. 75° E., 54 lks. dist. to double headed nail.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

A multi forked cedar, with 6 ins. diam. branch, bears
S. 35° W., 41 1/2 lks. dist. to double headed nail.

Cor. is located on a NE slope in cedar and 15 ft. West of a
draw, drains S. 20° E.

N. 0°10.7' E., beginning new measurement.

20.016 Point for the N 1/16 sec. cor. of secs. 26 and 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground with magnet at base, in a collar of stone, 2 ft.
diam. to top, with aluminum cap mkd.:

N1/16
S27 | S26
2004

Cor. is located on SW slope in scattered juniper, 50 ft. North
of a draw, drains SW.

40.032 The cor. of secs. 22, 23, 26 and 27, monumented with a boulder,
16X10X6 ins., firmly set, dimly mkd. with 2 notches on the
south and 2 notches on the east edges, with an unrecorded
rebar, 1/2 in. diam., along south side of mkd. boulder, with a
reference mound of stone to the west.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins.
in the ground with magnet at base, in a mound of stone, 3 ft.
diam., to top, with aluminum cap mkd.:

T14S R3E
S22 | S23

S27 | S26
2002

Bury mkd. boulder on east side of aluminum post.

Bury rebar inside aluminum post.

Rebuild reference mound of stone to 3 ft. diam. around aluminum
post.

Cor. is located on a W slope in cedar, 40 ft. South of top of
spur ridge, bears N. 80° E. and S. 80° W.

From the cor. of secs. 23, 24, 25 and 26.

S. 89°22.5' W., bet. secs. 23 and 26.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- 39.920** Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, with aluminum cap mkd.:

T14S R3E
S23
1/4 ———
S26
2004

Cor. is located on top of low spur, gently sloping S, 130 ft. North of high tension power lines, bearing SE and NW.

- 59.880** Point for the W 1/16 sec. cor. of secs. 23 and 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, with aluminum cap mkd.:

S23
W1/16 ———
S26
2004

Cor. is located on SE edge of small grassy clearing, approximately 100 ft. South of trail road.

- 79.840** The cor. of secs. 22, 23, 26 and 27.

N. 0°13.2' E., bet. secs. 22 and 23.

- 20.338** Point for the S 1/16 sec. cor. of secs. 22 and 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with magnet at base, in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

S1/16
S22 | S23
2004

Drive a steel fence post along SW side of aluminum post.

Cor. is located in a west slope in juniper.

- 40.676** Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH
CHAINS

T14S R3E
1/4
S22 | S23
2004

Drive a steel fence post along east side of aluminum post.

Cor. is located on a south slope in juniper and 10 ft. North of a draw, drains West.

61.014 Point for the N 1/16 sec. cor. of secs. 22 and 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

N1/16
S22 | S23
2004

Drive a steel fence post along south side of aluminum post.

Cor. is located on NW slope in juniper, approximately 50 ft. South of draw, drains SW.

81.352 Point for the cor. of secs. 14, 15, 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to solid rock with a magnet at base, in a supporting mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:

T14S R3E
S15 | S14

S22 | S23
2004

Drive a steel fence post on east side of aluminum post.

Cor. is located on a south slope in scattered juniper.

From this point, the cor. of secs. 2, 3, 10 and 11, bears N. 0°14.4' E., 162.708 chs. dist., monumented with a limestone boulder, 18X18X8 ins., no marks visible, with a reference mound of stone to the west. This cor. was recovered by Barry Andreason, LS 166572 as part of a property survey in sec. 2 that is not recorded. The boulder is accepted as the best available evidence of the original cor. Not remonumented.

The control line was fully retraced, and no evidence of the intervening cors. was found.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the cor. of secs. 13, 14, 23 and 24.

N. 89°44.4' W., bet. secs. 14 and 23.

- 39.516** Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:

T14S R3E
S14
1/4 ———
S23
2004

Drive a steel fence post along west side of aluminum post.

Cor. is located on a SW slope in grass and juniper.

- 79.032** The cor. of secs. 14, 15, 22 and 23.

From the cor. of secs. 3, 4, 33 and 34, Ts. 14 and 15 S., R. 3 E., monumented with an aluminum post, 3 ins. diam., firmly set, projecting 14 ins. above ground, with aluminum cap mkd. T14SR3E 33 34 4 3 T15S 1999, with a sandstone, 16X12X5 ins., clearly mkd. with 3 notches on one side and 3 grooves on the opposite side, along east side of aluminum post, in a mound of stone, at intersection of fences, bearing S and W, as recorded in Sanpete County Section Corner Ties, Sanpete County Recorders office. During the local remonumentation of this cor., it appears that the mkd. stone had been moved and the aluminum post now occupies the point for the original cor. The aluminum post is accepted as a careful and faithful perpetuation of the original cor.

from which the local reference monuments (Local record; witness cors.)

A rebar, 3/4 in. diam., firmly set, projecting 2 ins. above ground, bears N. 24°37.3' E., 38.0 lks. dist., with aluminum cap mkd. WC. (Local record; 38.8 lks. dist.)

A rebar, 3/4 in. diam., firmly set, flush with ground, bears S. 70°59.6' E., 27.0 lks. dist., with aluminum cap mkd. WC. (Local record; 28.3 lks. dist.)

A rebar, 3/4 in. diam., firmly set, projecting 3 ins. above ground, bears S. 3°40.0' W., 29.9 lks. dist., with aluminum cap mkd. WC.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

A rebar, 3/4 in. diam., firmly set, projecting 4 ins. above ground, bears N. 89°01.0' W., 27.5 lks. dist., with aluminum cap mkd. WC. (Local record; 26.9 lks. dist.)

Cor. is located on a NE slope in sagebrush, 85 ft. West of a dirt road, 7 ft. wide, bears N and S.

N. 1°00.0' W., bet. secs. 33 and 34.

- 42.850** Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor., falls in gravel road, bears E and W, where it is unsafe to monument with an aluminum post.

Set a rebar, 18 ins. long, 5/8 in. diam., 22 ins. in the ground.

from which

An aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, bears S. 20°36.9' E., 32.0 lks. dist., for a reference monument, with aluminum cap mkd. T14SR3E 1/4 S34 RM 2004 and an arrow pointing to the cor., falls in a fence, bears E and W. Drive a steel fence post alongside aluminum post.

An aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, bears S. 73°51.7' W., 32.4 lks. dist., for a reference monument, with aluminum cap mkd. T14SR3E 1/4 S33 RM 2004 and an arrow pointing to the cor., falls in a fence, bears E and W.

Reestablishment of the Survey Executed by C. Mogo in 1856
and the Resurvey Executed by E.W. Koeber in 1894

- 64.275** Point for the N 1/16 sec. cor. of secs. 33 and 34. Not monumented.
- 85.700** The cor. of secs. 27, 28, 33 and 34, monumented with a sandstone, 20X14X8 ins., loosely set, dimly mkd. with 3 notches on the east and 1 notch on the south edge, with a reference mound of stone to the west, at intersection of fences bearing N and S, and W.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to solid rock with magnet at base, in a supporting mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH
CHAINS

T14S R3E	
S28	S27
S33	S34
2002	

Bury mkd. stone on north side of aluminum post.

Cor. is located on an easterly slope in sagebrush.

From the cor. of secs. 26, 27, 34 and 35.

N. 87°47.4' W., bet. secs. 27 and 34.

19.344 Point for the E 1/16 sec. cor. of secs. 27 and 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, with aluminum cap mkd.:

	S27
E1/16	———
	S34
	2004

Cor. is located on gentle NE slope of low rise.

38.688 Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, with aluminum cap mkd.:

T14S R3E	
	S27
1/4	———
	S34
	2004

Cor. is located on SE slope, 66 ft. East of ridge top, and in alignment with an old power line (no wires).

58.032 Point for the W 1/16 sec. cor. of secs. 27 and 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with aluminum cap mkd.:

	S27
W1/16	———
	S34
	2004

Cor. is located on top of low ridge, S of stock pond.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

77.376 The cor. of secs. 27, 28, 33 and 34.

N. 0°20.2' W., bet. secs. 27 and 28.

20.456 Point for the S 1/16 sec. cor. of secs. 27 and 28, at proportionate dist. latitudinally and longitudinally in a fence, bears N and S.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, in a collar of stone, 1 ft. diam., to top, with aluminum cap mkd.:

S/16
S28 | S27
2002

Drive a steel fence post north of aluminum post.

Cor. is located W. of a dirt road, 7 ft. wide, bears N and S.

N. 0°47.4' W., beginning new measurement.

20.458 Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate dist. latitudinally and longitudinally in a fence, bears N and S.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T14S R3E
1/4
S28 | S27
2002

Drive a steel fence post north of aluminum post.

N. 0°46.0' W., beginning new measurement.

40.915 Point for the cor. of secs. 21, 22, 27 and 28 at proportionate dist. latitudinally and longitudinally in a fence, bears N and S.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 23 ins. in the ground with magnet at base, in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T14S R3E
S21 | S22

S28 | S27
2002

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Drive a steel fence post along north side of aluminum post.

From the cor. of secs. 22, 23, 26 and 27.

N. 86°15.4' W., bet. secs. 22 and 27.

19.519 Point for the E 1/16 sec. cor. of secs. 22 and 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 27 ins. in the ground with magnet at base, in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:

S22
E1/16 ———
S27
2002

Drive a steel fence post along north side of aluminum post.

Cor. is located on a SE slope with scattered cedar, 63 ft. East of ridge, bears S. 5° E. and N. 5° W., and 102 ft. South of top of ridge, bears E and W.

39.038 Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the original cor., falls in a construction area for a well. Note: the 1894 mkd. stone, clearly mkd. 1/4 on one side, was recovered in the vicinity of the proportioned cor., but was found to have been disturbed and was not utilized during the course of this resurvey.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:

T14S R3E
S22
1/4 ———
S27
2002

Bury mkd. stone at base of aluminum post.

Drive a steel fence post north of aluminum post.

Cor. is located in a flat in sagebrush. 60 ft. N. 30° E. of a well, 12 ins. diam.

58.557 Point for the W 1/16 sec. cor. of secs. 22 and 27. Not monumented.

78.076 The cor. of secs. 21, 22, 27 and 28.

N. 0°44.5' W., bet. secs. 21 and 22.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- 20.457** Point for the S 1/16 sec. cor. of secs. 21 and 22, at proportionate dist. latitudinally and longitudinally in a fence, bears N and S.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 23 ins. in the ground with magnet at base, with aluminum cap mkd.:

S/16
S21 | S22
2002

Drive a steel fence post north of aluminum post.

Cor. is located in cheat grass.

N. 0°48.4' W., beginning new measurement.

- 20.458** Point for the 1/4 sec. cor. of secs. 21 and 22, at the cor. of ancient fences bearing N, S and W, is in agreement with identified original cors. recovered in the ancient fence line, and is accepted as the best available evidence of the original cor. position.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:

T14S R3E
1/4
S21 | S22
2002

Cor. is located under east line of overhead powerline, bears N and S, 60 ft. North of a dry wash, drains S. 40° W.

N. 0°29.4' W., beginning new measurement.

- 38.749** The cor. of secs. 15, 16, 21 and 22, monumented with an unrecorded rebar, 3/4 in. diam., firmly set, projecting 2 ins. above ground, with aluminum cap mkd.: T14SR3E 15 16 21 22, in an embedded mound of stone, at intersection of fences, bearing N and S, and W, with a sandstone, 18X16X10 ins., with no marks visible, laying nearby. The rebar and aluminum cap are accepted as a faithful and careful perpetuation of the original cor.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T14S R3E	
S16	S15
S21	S22
2002	

Bury unmarked sandstone alongside aluminum post.

Bury rebar and aluminum cap inside aluminum post.

From the cor. of secs. 14, 15, 22 and 23.

N. 87°32.1' W., bet. secs. 15 and 22.

19.791 Point for the E 1/16 sec. cor. of secs. 15 and 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 27 ins. in the ground with magnet at base, in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:

	S15
E1/16	———
	S22
	2002

Drive a steel fence post along SW side of aluminum post.

Cor. is located on NW slope with juniper, 70 ft. South of draw, drains NW.

39.582 Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the original cor., falls in a road, 8 ft. wide, bears N and S.

Set a rebar, 18 ins. long, 5/8 in. diam., 20 ins. in the ground with 2 ins. diam. aluminum cap mkd.:

	S15
1/4	———
	S22
	2004

Drive a steel fence post, N. 80°25' W., 8.2 lks. dist. of rebar and aluminum cap.

79.164 The cor. of secs. 15, 16, 21 and 22.

Survey of the Subdivision of Section 22,
T. 14 S., R. 3 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 22 and 27.

N. 0°12.2' W., on the N-S centerline of sec. 22.

SURVEY OF THE SUBDIVISION OF SECTION 22,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

20.394 Point for the center S 1/16 sec. cor. of sec. 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, in a collar of stone, 1 ft. diam., with aluminum cap mkd.:

C
S1/16 | S22
C
2004

Drive a steel fence post along side aluminum post.

Cor. is located on NW slope in grass, sagebrush and juniper.

40.788 Point for the center 1/4 sec. cor. of sec. 22, at intersection with the E-W centerline of sec. 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T14S R3E
C 1/4 X S22
2004

Drive a steel fence post along north side of aluminum post.

Cor. is located on a slight NE slope in juniper.

60.646 Point for the center N 1/16 sec. cor. of sec. 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with aluminum cap mkd.:

C
N1/16 | S22
C
2004

Drive a steel fence post along east side of aluminum post.

Cor. is located on a south slope in juniper, 2 ft. North of small drainage, drains West.

80.504 The 1/4 sec. cor. of secs. 15 and 22.

From the 1/4 sec. cor. of secs. 22 and 23.

N. 86°07.2' W., on the E-W centerline of sec. 22.

19.671 Point for the center E 1/16 sec. cor. of sec. 22.

SURVEY OF THE SUBDIVISION OF SECTION 22,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, with aluminum cap mkd.:

E1/16
C———C
S22
2004

Drive a steel fence post along east side of aluminum post.

Cor. is located on a NW slope in juniper.

39.342 The center 1/4 sec. cor. of sec. 22.

59.067 Point for the center W 1/16 sec. cor. of sec. 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, with aluminum cap mkd.:

W1/16
C———C
S22
2004

Drive a steel fence post along SW side of aluminum post.

Cor. is located on a slight SE slope in grass and sagebrush, 55 ft. West of a dirt road, 8 ft. wide, bears N. 50° E. and S. 50° W., and 70 ft. North of same dirt road, bears N. 50° E. and S. 50° W.

78.792 The 1/4 sec. cor. of secs. 21 and 22.

From the center E 1/16 sec. cor. of sec. 22.

N. 0°00.6' E., on the N-S centerline of the NE 1/4 of sec. 22.

20.098 Point for the NE 1/16 sec. cor. of sec. 22, at intersection with the E-W centerline of the NE 1/4 of sec. 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, with aluminum cap mkd.:

NE 1/16
X
S22
2004

Drive a steel fence post along south side of aluminum post.

Cor. is located on a steep ridge, bears E and W.

40.196 The E 1/16 sec. cor. of secs. 15 and 22.

SURVEY OF THE SUBDIVISION OF SECTION 22,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the N 1/16 sec. cor. of secs. 22 and 23.

N. 86°49.8' W., on the E-W centerline of the NE 1/4 of sec. 22.

19.730 The NE 1/16 sec. cor. of sec. 22.

39.460 The center N 1/16 sec. cor. of sec. 22.

From the E 1/16 sec. cor. of secs. 22 and 27.

N. 0°00.5' E., on the N-S centerline of the SE 1/4 of sec. 22.

20.366 Point for the SE 1/16 sec. cor. of sec. 22, at intersection with the E-W centerline of the SE 1/4 of sec. 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:

SE 1/16 X S22
2004

Drive a steel fence post along north side of aluminum post.

Cor. is located on SE slope in grass and juniper.

40.732 The center E 1/16 sec. cor. of sec. 22.

From the S 1/16 sec. cor. of secs. 22 and 23.

N. 86°11.2' W., on the E-W centerline of the SE 1/4 of sec. 22.

19.595 The SE 1/16 sec. cor. of sec. 22.

39.190 The center S 1/16 sec. cor. of sec. 22.

From the point for the W 1/16 sec. cor. of secs. 22 and 27.

N. 0°29.3' W., on the N-S centerline of the SW 1/4 of sec. 22.

20.426 Point for the SW 1/16 sec. cor. of sec. 22, at intersection with the E-W centerline of the SW 1/4 of sec. 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with aluminum cap mkd.:

SW 1/16 X S22
2004

Drive a steel fence post along south side of aluminum post.

Cor. is located on a SW slope in grass and sagebrush, 70 ft. North of a dirt road, 8 ft. wide, bears S. 50° E. and N. 50° W.

SURVEY OF THE SUBDIVISION OF SECTION 22,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.851 The center W 1/16 sec. cor. of sec. 22.

From the center S 1/16 sec. cor. of sec. 22.

N. 86°11.3' W., on the E-W centerline of the SW 1/4 of sec. 22.

19.622 The SW 1/16 sec. cor. of sec. 22.

39.232 The S 1/16 sec. cor. of secs. 21 and 22.

Survey of the Subdivision of Section 23,
T. 14 S., R. 3 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 23 and 26.

N. 0°03.5' W., on the N-S centerline of sec. 23.

20.185 Point for the center S 1/16 sec. cor. of sec. 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with aluminum cap mkd.:

$$\begin{array}{c} \text{C} \\ \text{S1/16} \mid \text{S23} \\ \text{C} \\ 2004 \end{array}$$

Drive a steel fence post along west side of aluminum post.

Cor. is located on NE slope in grass, sagebrush and juniper, 50 ft. North of a dirt road, 8 ft. wide, bears N. 30° E. and S. 30° W., and 48 ft. West of same dirt road, bears N. 40° E. and S. 30° W.

40.370 Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E-W centerline of sec. 23. Not monumented.

80.735 The 1/4 sec. cor. of secs. 14 and 23.

From the 1/4 sec. cor. of secs. 23 and 24.

S. 89°48.8' W., on the E-W centerline of sec. 23.

39.717 The point for the center 1/4 sec. cor. of sec. 23.

79.434 The 1/4 sec. cor. of secs. 22 and 23.

From the center S 1/16 sec. cor. of sec. 23.

S. 89°35.3' W., on the E-W centerline of the SW 1/4 of sec. 23.

SURVEY OF THE SUBDIVISION OF SECTION 23,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

39.818 The S 1/16 sec. cor. of secs. 22 and 23.

Survey of the Subdivision of Section 26,
T. 14 S. R. 3 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 26 and 35.

N. 0°28.6' W., on the N-S centerline of sec. 26.

39.759 The center 1/4 cor. of sec. 26, at intersection with the E-W centerline of sec. 26, monumented with an unrecorded rebar, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with aluminum cap mkd. LUDLOW ENG and an illegible LS number, and is accepted as a careful and faithful establishment of the cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with aluminum cap mkd.:

T14S R3E
C1/4
S26
2004

Bury rebar and aluminum cap inside aluminum post.

Cor. is located 20 ft. West of wash, 8 ft. deep, drains S.

N. 0°28.6' W., beginning new measurement.

19.965 Point for the center N 1/16 sec. cor. of sec. 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at base, with aluminum cap mkd.:

C
N 1/16 | S26
C
2004

39.930 The 1/4 sec. cor. of secs. 23 and 26.

From the 1/4 sec. cor. of secs. 25 and 26.

S. 89°14.1' W., on the E-W centerline of sec. 26.

40.083 The center 1/4 sec. cor. of sec. 26.

S. 89°14.1' W., beginning new measurement.

SURVEY OF THE SUBDIVISION OF SECTION 26,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

20.191 Point for the center W 1/16 sec. cor. of sec. 26, falls on dirt road.

Set a rebar, 12 ins. long, 5/8 in. diam., flush with surface of road, with aluminum cap, 2 ins. diam., mkd.:

W1/16
C ——— C
S26
2004

from which the reference object

A steel fence post, 6 ins. diam., in alignment with
fence projecting W, bears West, 24.1 lks. dist.

40.382 The 1/4 sec. cor. of secs. 26 and 27.

From the center W 1/16 sec. cor. of sec. 26.

N. 0°08.9' W., on the N-S centerline of the NW 1/4 of sec. 26.

8.60 Point of intersect with fence, bears N. 73°43' W., and
S. 73°43' E.

10.141 From this point, the southwesterly fence cor. of a turkey pen
designated as cor. 1, bears East, 1.364 chs.

From which

Fence cor. 2, of turkey pen, bears S. 70°12' E., 4.72 chs.
dist., thence N. 21°23' E., 4.84 chs. dist. to fence cor.
3, thence N. 73°20' W., 2.16 chs., dist. to fence cor. 4,
thence N. 67°19' W., 2.38 chs., dist., to fence cor. 5,
thence S. 70°19' W., 0.19 chs., dist., to fence cor. 6,
thence S. 21°47' W., 4.72 chs., dist., to beginning fence
cor. 1.

13.85 Point of intersect with fence, bears N. 23°59' E., and
S. 23°59' W.

19.991 Point for the NW 1/16 sec. cor. of sec. 26, at intersection
with the E-W centerline of the NW 1/4 of sec. 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 28 ins.
in the ground with magnet at base, with aluminum cap mkd.:

NW 1/16
•
S26
2004

Cor. is located on S slope in thick juniper.

39.982 The W 1/16 sec. cor. of secs. 23 and 26.

SURVEY OF THE SUBDIVISION OF SECTION 26,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the center N 1/16 sec. cor. of sec. 26.

S. 89°18.1' W., on the E-W centerline of the NW 1/4 of sec. 26.

20.076 The NW 1/16 sec. cor. of sec. 26.

40.151 The N 1/16 sec. cor. of secs. 26 and 27.

Survey of the Subdivision of Section 27,
T. 14 S., R. 3 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 27 and 34.

N. 0°27.5' W., on the N-S centerline of sec. 27.

20.144 Point for the center S 1/16 sec. cor. of sec. 27. Not monumented.

40.288 Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E-W centerline of sec. 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, with aluminum cap mkd.:

T14SR3E
C 1/4
S27
2004

Drive a steel fence alongside aluminum post.

Cor. is located on flat ground in thick sagebrush.

80.769 The 1/4 sec. cor. of secs. 22 and 27.

From the 1/4 sec. cor. of secs. 26 and 27.

N. 86°52.5' W., on the E-W centerline of sec. 27.

19.284 Point for the center E 1/16 sec. cor. of sec. 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, with aluminum cap mkd.:

E1/16
C ——— C
S27
2004

Drive a steel fence post alongside aluminum post.

SURVEY OF THE SUBDIVISION OF SECTION 27,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on W slope in bottom of small ravine, in thick juniper.

38.568 The center 1/4 sec. cor. of sec. 27.

57.965 Point for the center W 1/16 sec. cor. of sec. 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, with aluminum cap mkd.:

W1/16
C ——— C
S27
2004

Drive a steel fence post alongside aluminum post.

Cor. is located on S slope near top of low ridge.

77.362 The 1/4 sec. cor. of secs. 27 and 28.

From the E 1/16 sec. cor. of secs. 27 and 34.

N. 0°34.0' W., on the N-S centerline of the SE 1/4 of sec. 27.

19.992 Point for the SE 1/16 sec. cor. of sec. 27, at intersection with the E-W centerline of the SE 1/4 of sec. 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, with aluminum cap mkd.:

SE 1/16
S27
2004

Cor. is located on SW slope in grass and scattered juniper.

39.984 The center E 1/16 sec. cor. of sec. 27.

From the S 1/16 sec. cor. of secs. 26 and 27.

N. 87°19.9' W., on the E-W centerline of the SE 1/4 of sec. 27.

19.314 The SE 1/16 sec. cor. of sec. 27.

38.627 The point for the center S 1/16 sec. cor. of sec. 27.

From the W 1/16 sec. cor. of secs. 27 and 34.

N. 0°30.6' W., on the N-S centerline of the SW 1/4 of sec. 27.

20.301 Point for the SW 1/16 sec. cor. of sec. 27, at intersection with the E-W centerline of the SW 1/4 of sec. 27.

SURVEY OF THE SUBDIVISION OF SECTION 27,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with aluminum cap mkd.:

SW 1/16
S27
2004

Cor. is located on gradual N slope in scattered sagebrush.

40.600 The center W 1/16 sec. cor. of sec. 27.

From the point for the center S 1/16 sec. cor. of sec. 27.

N. 87°19.7' W., on the E-W centerline of the SW 1/4 of sec. 27.

19.371 The SW 1/16 sec. cor. of sec. 27.

38.660 The S 1/16 sec. cor. of secs. 27 and 28.

Survey of the Subdivision of Section 34,
T. 14 S., R. 3 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 3 and 34, Ts. 14 and 15 S., R. 3 E., monumented with a sandstone, 8X4X3 ins., loosely set, dimly mkd. 1/4 on north face. (Record; 14X10X8 ins.)

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to solid rock with a magnet at base, and in a supporting mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:

T14S R3E
S34
1/4 ———
S3
T15S
2002

Bury mkd. stone on north side of aluminum post.

Drive a steel fence post SE 1 ft. dist. of aluminum post.

Cor. is located on a S slope in grass and 60 ft. North of dirt road, 7 ft. wide, bears N. 80° E. and S. 80° W.

N. 2°06.3' W., on the N-S centerline of sec. 34.

41.386 Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E-W centerline of sec. 34. Not monumented.

SURVEY OF THE SUBDIVISION OF SECTION 34,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

62.209 Point for the center N 1/16 sec. cor. of sec. 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with aluminum cap mkd.:

C
N1/16 | S34
C
2004

Cor. is located on gentle S slope, approximately 160 ft. E of trail road.

83.032 The 1/4 sec. cor. of secs. 27 and 34.

From the 1/4 sec. cor. of secs. 34 and 35.

N. 89°38.1' W., on the E-W centerline of sec. 34.

38.659 The point for the center 1/4 sec. cor. of sec. 34.

58.383 Point for the center W 1/16 sec. cor. of sec. 34. Not monumented.

78.107 The 1/4 sec. cor. of secs. 33 and 34.

From the point for the center W 1/16 sec. cor. of sec. 34.

N. 1°32.7' W., on the N-S centerline of the NW 1/4 of sec. 34.

21.122 Point for the NW 1/16 sec. cor. of sec. 34, at intersection with the E-W centerline of the NW 1/4 of sec. 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock with magnet at base, in a supporting mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:

NW 1/16
S34
2004

Cor. is located on S slope of spur, approximately 200 ft. South of the top of ridge, in sparsely scattered sagebrush.

42.244 The W 1/16 sec. cor. of secs. 27 and 34.

From the center N 1/16 sec. cor. of sec. 34.

N. 88°42.5' W., on the E-W centerline of the NW 1/4 of sec. 34.

19.532 The NW 1/16 sec. cor. of sec. 34.

SURVEY OF THE SUBDIVISION OF SECTION 34,
T. 14 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

39.063 The point for the N 1/16 sec. cor. of secs. 33 and 34.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Jerry L. Thomas	Cadastral Surveyor
Jeremy D. Davis	Survey Technician
Nick George	Survey Aide
Matthew M. Peck	Survey Aide
Sterling D. Profaizer	Survey Aide

CERTIFICATE OF SURVEY

I, *John F. Carroll, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *19th day of July, 2004*, I have *executed a dependent resurvey of a portion of the east boundary, a portion of the subdivisional lines, and the subdivision of sections 22, 23, 26, 27 and 34 in Township 14 South, Range 3 East,*

of the *Salt Lake* Meridian, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

9/21/2006

Date

John F. Carroll
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the dependent resurvey of a portion of the east boundary, a portion of the subdivisional lines, and the subdivision of sections 22, 23, 26, 27 and 34, in Township 14 South, Range 3 East, Salt Lake Meridian, Utah,

executed by *John F. Carroll, Cadastral Surveyor*,

having been critically examined and found correct, are hereby approved.

September 29, 2006

Date

Daniel W. Webb
Chief Cadastral Surveyor for Utah