

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL  
FIELD NOTES

OF

THE DEPENDENT RESURVEY OF  
A PORTION OF THE SOUTH BOUNDARY,  
(FIRST STANDARD PARALLEL SOUTH)  
A PORTION OF THE EAST BOUNDARY,  
A PORTION OF THE SUBDIVISIONAL LINES,  
AND THE SUBDIVISION OF SECTIONS

13, 14, 23 AND 24  
IN

**TOWNSHIP 4 SOUTH, RANGE 11 WEST**

OF THE UNITAH SPECIAL MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

**Merrill D. Cazier**  
**Cadastral Surveyor**

Under special instructions dated **August 19, 2002**, approved **August 19, 2002**, which provided for the surveys included under Group Number **953**, and assignment instructions dated **August 19, 2002**.

Survey commenced **October 15, 2002**  
Survey completed **October 1, 2003**

## INDEX DIAGRAM

Township 4 South, Range 11 West

6	5	4	3	2	1
7	8	9	10	11 16	12 10
18	17	16	15 15	14 9 14	13 4 8
19	20	21	22 13	23 7 13	24 3 6
30	29	28	27 12 17	26 5 12	25
31	32	33 16	34 11 2	35 2	36

The Subdivision of Section 13.....Page 18  
 The Subdivision of Section 14.....Page 30  
 The Subdivision of Section 23.....Page 40  
 The Subdivision of Section 24.....Page 53

## TOWNSHIP 4 SOUTH, RANGE 11 WEST, UINTAH SPECIAL MERIDIAN

The following field notes describe the dependent resurvey of a portion of the south boundary, (First Standard Parallel South), a portion of the east boundary, and a portion of the subdivisional lines, and the subdivision of sections 13, 14, 23 and 24, in Township 4 South, Range 11 West, Uintah Special Meridian, Utah.

**HISTORY OF EARLIER SURVEYS**

<b>Surveyed by</b>	<b>Retraced or Resurveyed by</b>
<b>SOUTH BOUNDARY (First Standard Parallel South)</b>	
All H.D. Page & B.S. Kershaw 1904	
Closing Lines	S.P. Stewart & C.S. Jarvis 1904
Remonumentation by	G.W. Hochstrasser 1966
<b>EAST BOUNDARY</b>	
All H.D. Page & B.S. Kershaw 1904	
Remonumentation by	F.D. Reynolds 1971
<b>WEST BOUNDARY</b>	
All H.D. Page & B.S. Kershaw 1904	
Remonumentation by	G.W. Hochstrasser 1966
<b>NORTH BOUNDARY</b>	
All H.D. Page & B.S. Kershaw 1904	
Remonumentation by	F.D. Reynolds 1971
<b>SUBDIVISION</b>	
All H.D. Page & B.S. Kershaw 1904	
Remonumentation by	G.W. Hochstrasser 1966
Remonumentation by	F.D. Reynolds 1971

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instruction, 1973 and the Special Instructions for Group No. 953, dated August 19, 2002.

The true meridian direction and length of all lines were determined by Global Positioning System (GPS) utilizing Real-Time Kinematics (RTK) observation using the Trimble 5700 model receiver.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and their calls of record. Identified corners were remonumented in their original positions. Lost corners were restored and monumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations, post processed by National Geodetic Survey, Online Positioning User Service, (OPUS), Utilizing Continuously Operating Reference Stations; MIDVALE CORS ARP, CARBON COUNTY COU, and MYTON 2 CORS ARP. The N.A.D. 1983 (CORS96) geographic position of the 1/4 section corner of section 19 and 24, east boundary of township, is as follows:

Latitude: 40° 07' 05.578" N.                      Longitude: 111° 03' 58.392" W.  
Elevation: 8451 ft.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY  
T. 4 S., R. 11 W., (FIRST STANDARD PARALLEL SOUTH)  
UINTAH SPECIAL MERIDIAN

CHAINS

---

Dependent Resurvey of a Portion of the South Boundary of  
T. 4 S., R 11 W. (First Standard Parallel South),  
Uintah Special Meridian, Utah

---

Reestablishment of the Survey executed by  
H.D. Page & B.S. Kershaw in 1904

---

Beginning at the standard 1/4 section corner of section 35, on  
the south boundary of the township, monumented with a sandstone,  
14x12x2 inches, plainly marked 1/4 SC and firmly set.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,  
over a magnet, 24 inches in the ground, with aluminum cap  
marked:

SC  
T4S R11W  
1/4 S35  

---

T5S R11W  
2003

Deposit the marked stone alongside monument.

Set a 6 ft. aluminum sign post alongside monument.

S. 89° 58.2' W., on the south boundary of section 35,

**39.867**

Point for the standard corner of sections 34 and 35 at  
proportionate distance, there is no remaining evidence of the  
original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,  
over a magnet, 24 inches in the ground, with aluminum cap  
marked:

SC  
T4S R11W  
S34 | S35  

---

T5S R11W  
2003

Set a steel fence post alongside the monument.

---

S. 89° 58.2' W., on the south boundary of section 34.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY  
T. 4 S., R. 11 W., (FIRST STANDARD PARALLEL SOUTH)  
UINTAH SPECIAL MERIDIAN

CHAINS  
39.867

Point for the standard 1/4 section corner of section 34 at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 22 inches in the ground, with aluminum cap marked:

SC  
T4S R11W  
1/4 S34

T5S R11W  
2003

Set a steel fence post alongside the monument.

79.734

The standard corner of sections 33 and 34, monumented with a sandstone, 14x9x6 inches, firmly set, with a scattered mound of stone to the south.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

SC  
T4S R11W  
S33 | S34

T5S R11W  
2003

Deposit the marked stone alongside the monument.

Raise a mound of stone, 3 ft. base, 1 ft. high, south of the monument.

Set a 6 ft. aluminum sign post alongside the monument.

---

Dependent Resurvey of a Portion of the East Boundary  
T. 4 S., R 11 W. Uintah Special Meridian, Utah

---

Reestablishment of the Survey executed by  
H.D. Page & B.S. Kershaw in 1904

---

From the corner of sections of 19, 24, 25 and 30, on the east boundary, of the township, monumented with an iron post, 2 1/2

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

inches diameter, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1971 remonumentation.

From which

An aspen, 8 inches in diameter, bears S. 59° E., 79 links distance, marked: T4S R10W S30 BT.

An aspen, 7 inches in diameter, bears S. 38° W., 29 links distance, marked: T4S R11W S25 BT.

An aspen, 6 inches in diameter, bears N. 38° W., 52 links distance, marked: T4S R10W S24 BT.

The corner of a net wire fence bears N. 49° E., 10 links distance, bears N and W.

N. 0° 01.0' E., between sections 19 and 24.

- 39.891** The 1/4 section corner of sections 19 and 24, monumented with an iron post, 2 1/2 inches diameter, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1971 remonumentation.

Monument is still located in a N and S net wire fence.

---

N. 0° 05.9' W., beginning new measurement.

- 39.907** The corner of sections 13, 18, 19 and 24, monumented with an iron post, 2 1/2 inches diameter, projecting 3 inches above ground, with brass cap marked as described in the official record of the 1971 remonumentation.

Monument is 13 links W from a N and S net wire fence.

---

N. 0° 01.5' W., between sections 13 and 18,

- 9.920** Point for the S-S 1/64 section corner of sections 13 and 18, not monumented.

- 14.880** Point for the N-S-S 1/256 section corner of sections 13 and 18, monumented with an 1 inch diameter aluminum post, with a 3 inch Forest Service aluminum cap marked:

AP30  
S13 | S18

1991

This monument is accepted as a careful and faithful determination of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

CHAINS

A sign post is located W of the monument.

- 19.840** Point for the S 1/16 section corner of sections 13 and 18, not monumented.
- 39.680** Point for the 1/4 section corner of sections 13 and 18, at proportionate distance, falls in Strawberry Reservoir, not monumented.
- 49.600** Point for the S-N 1/64 section corner of sections 13 and 18, monumented with a 1 inch diameter aluminum post, in a mound of stone, 3 ft. base by 1 ft. high, with a 3 inch Forest Service aluminum cap marked:

S13 | S18  
S-N  
1/64  
1991

This monument is accepted as a careful and faithful determination of the corner.

- 59.520** Point for the N 1/16 section corner of sections 13 and 18, not monumented.
- 79.360** The corner of sections 7, 12, 13 and 18, east boundary of the township, monumented with an iron post, 2 1/2 inches diameter, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1971 remonumentation.

Monument is located at the corner of fences bearing N, S, E and W.

---

Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 4 S., R 11 W., Uintah Special Meridian, Utah

---

Reestablishment of the Survey executed by  
H.D. Page & B.S. Kershaw in 1904

---

From the corner of sections 25, 26, 35 and 36, monumented with a sandstone, 20x10x2 inches, lying on the ground, with 1 notch on S and E edges.

From which original bearing trees

An aspen, 10 inches diameter, bears N. 29° 25.4' E., 40.4 links distance, (Record N. 31° 1/2 E., 7 links) marked:  
T4S R11W S25 BT.

An aspen, 12 inches diameter, bears S. 45° 35.0' E., 45.1 links distance, (Record S. 55° E., 36 links) marked:  
T4S R11W S36 BT.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

CHAINS

An aspen, 12 inches diameter, bears S. 26° 36.9' W., 30.6 links distance, (Record N. 43° E., 35 links) marked: T4S R11W S35 BT.

An aspen, 10 inches diameter, bears N. 57° 34.3' W., 41.4 links distance, (Record N. 57° W., 31 links) marked: T4S R11W S26 BT.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, in a collar of stone, with aluminum cap marked:

T4S R11W	
S26	S25
S35	S36
2003	

Deposit marked stone alongside the monument.

N. 2° 05.2' W., between sections 25 and 26.

**39.929**

The 1/4 section corner of sections 25 and 26, monumented with a sandstone, 16x8x3 inches, firmly set and plainly marked 1/4 on W face, with a mound of stone on W side.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 16 inches in the ground, to bedrock and in a mound of stone, 3 ft. base to top of aluminum cap marked:

T4S R11W	
1/4	
S26	S25
2003	

Deposit marked stone alongside the corner.

---

N. 1° 12.2' E., beginning new measurement,

**39.482**

The corner of sections 23, 24, 25 and 26, monumented with an iron post, 2 1/2 inches diameter, firmly set in mound of stone, 3 ft. base to top of brass cap marked as described in the official record of the 1971 remonumentation.

---

From the corner of sections 19, 24, 25 and 30, on the east boundary of the township, hereinbefore described.

S. 89° 59.7' W., between sections 24 and 25.

**40.276**

Point for the 1/4 section corner of sections 24 and 25 at

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

CHAINS

proportionate distance, found sandstone, 15x10x5 inches, lying loosely on the ground, plainly marked 1/4. No evidence of original bearing trees were found.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 16 inches in the ground to bedrock and in a mound of stone, 4 ft. base to top of aluminum cap marked:

T4S R11W  
S24  
1/4           
S25  
2003

Deposit marked stone alongside the monument.

Monument is located on a steep aspen covered easterly slope.

**80.552** The corner of sections 23, 24, 25 and 26.

---

N. 0° 22.5' E., between sections 23 and 24.

**39.953** The 1/4 section corner of sections 23 and 24, monumented with an iron post, 2 1/2 inches diameter, projecting 6 inches above ground, with a mound of stone, 2 1/2 ft. base, 1 ft. high to the W, with brass cap marked as described in the official record of the 1971 remonumentation.

From which the remains of the original bearing trees

An aspen, 6 inches diameter, bears S. 12° E. 8.5 links distance, (same as 1971 tie) marked: 1/4 S24 BT.

An aspen, 8 inches diameter, bears S. 38° W. 20 links distance, (same as 1971 tie) marked: 1/4 S23 BT.

---

N. 0° 12.9' W., beginning new measurement.

**9.935** Point for the S-N 1/64 section corner of sections 23 and 24.

Set a rebar, 18 inches long, 5/8 inch diameter, 15 inches in the ground, with 3 inch aluminum cap marked:

T4S R11W  
S-N  
1/64  
S23 | S24  
2003

Set an aluminum sign, post 2 ft. E of the monument.

**19.870** Point for the N 1/16 section corner of sections 23 and 24, not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

- 29.805** Point for the N-N 1/64 section corner of sections 23 and 24, not monumented.
- 39.740** The corner of sections 13, 14, 23 and 24, monumented with an aluminum post, 2 1/2 inches in diameter, in a mound of stone, 4 ft. base to top of the Forest Service 3 inch aluminum cap marked:

T4S R11W	
S14	S13
S23	S24
1991	

Added BLM 2002 to the 3 inch aluminum cap.

This monument is accepted as a careful and faithful perpetuation of the original corner position.

From which

An aspen stump, 5 inches diameter, bears N. 65° E., 20 links distance, (Record N. 83° E., 22 links) marked with a tag and blaze.

An aspen, 6 inches diameter, bears S. 27° E., 19 links distance, (Record S. 50° E., 35 links) marked: S24, and with a tag.

An aspen, 7 inches diameter, down and dead, bears S. 37° W. 11 links distance, (Record S. 50° W., 32 links) marked: S23, and with a tag.

An aspen, 5 inches diameter, dead and standing, bears N. 62° W. 25 links distance, (Record N. 43° W., 21 links) marked: S14, and with a tag.

---

From the corner of sections 13, 18, 19, and 24, on the east boundary of the township, hereinbefore described.

N. 89° 53.8' W., between sections 13 and 24.

- 10.006** Point for the E-E 1/64 section corner of sections 13 and 24, not monumented.
- 20.012** Point for the E 1/16 section corner of sections 13 and 24, not monumented.
- 30.018** Point for the W-E 1/64 section corner of sections 13 and 24, not monumented.
- 40.024** The 1/4 section corner of sections 13 and 24, monumented with a sandstone, 15x10x6 inches, loosely set, south of a scattered mound of stone, plainly marked 1/4 on N face.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 10 inches in the ground to solid rock, in a mound of stone, 4 ft. base to top of aluminum cap marked:

T4S R11W  
S13  
1/4           
S24  
2003

Set an aluminum sign post alongside the monument.

Monument is located on a S facing slope in bitter brush and sage brush.

---

S. 89° 44.3' W., beginning new measurement.

**5.043** Point for the E-E-W 1/256 section corner of sections 13 and 24.

Set a rebar 16 inches long, 3/4 inch diameter, over a magnet, 14 inches in the ground, in a collar of stone, with 3 inch aluminum cap marked:

E-E-W  
S13  
1/256           
S24  
2003

Set an aluminum sign post S of the monument.

Monument is located S, 50 links distance from a trail that bears N. 35° W. and S.35° E.

**10.086** Point for the E-W 1/64 section corner of sections 13 and 24, not monumented.

**20.172** Point for the W 1/16 section corner of sections 13 and 24, falls in Strawberry Reservoir, not monumented.

**30.258** Point for the W-W 1/64 section corner of sections 13 and 24, falls in Strawberry Reservoir, not monumented.

**40.344** The corner of sections 13, 14, 23 and 24.

---

N. 0° 06.4' W., between sections 13 and 14.

**19.824** Point for the S 1/16 section corner of sections 13 and 14, falls in Strawberry Reservoir, not monumented.

**29.736** Point for the N-S 1/64 section corner of sections 13 and 14, falls in Strawberry Reservoir, not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 4 S., R. 11 W., UTAH SPECIAL MERIDIAN

## CHAINS

34.692

Point for the N-N-S 1/256 section corner of sections 13 and 14, falls in Strawberry Reservoir, not monumented.

39.648

The 1/4 section corner of sections 13 and 14, monumented with 1 inch pipe, firmly set at base of 15 ft. high sandstone outcropping. Pipe is set in a mound of stone, 4 ft. base to top of the Forest Service 3 inch aluminum cap marked:

T4S R11W  
1/4  
S14 | S13  
1991

Added BLM 2002 to 3 inch aluminum cap.

This monument is accepted as a careful and faithful perpetuation of the original corner position.

---

N. 0° 06.6' W., beginning new measurement.

4.956

Point for the S-S-N 1/256 section corner of sections 13 and 14, monumented with a 1 inch diameter aluminum post, in a mound of stone, 3 ft. base to top of 3 inch Forest Service aluminum cap marked:

S-S-N  
S14 | S13  
1/256  
1991

This monument is accepted as a careful and faithful determination of the corner.

9.912

Point for the S-N 1/64 section corner of sections 13 and 14, not monumented.

19.824

Point for the N 1/16 section corner of sections 13 and 14, not monumented.

39.648

The corner of sections 11, 12, 13 and 14, monumented with an iron post, 2 1/2 inches diameter, projecting 4 inches above ground, in a collar of stone, with a mound of stone, 3 ft. base, 1 ft. high to the W, with brass cap marked as described in the official record of the 1971 remonumentation.

Corner is located in an E and W fence line.

---

From the corner of sections 7, 12, 13, and 18, on the east boundary of the township, hereinbefore described.

S. 89° 47.3' W., between sections 12 and 13.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 4 S., R. 11 W., UTAH SPECIAL MERIDIAN

## CHAINS

20.190

Point for the E 1/16 section corner of sections 12 and 13, not monumented.

40.380

The 1/4 section corner of sections 12 and 13, monumented with an iron post, 2 1/2 inches diameter, projecting 4 inches above ground, and a Forest Service survey corner sign No. 54.4, 3 ft to the SW, with brass cap marked as described in the official record of the 1971 remonumentation.

Monument is located in an E and W fence line.

---

S. 89° 57.5' W., beginning new measurement.

20.041

Point for the W 1/16 section corner of sections 12 and 13, not monumented.

40.082

The corner of sections 11, 12, 13 and 14.

---

From the standard corner of sections 34 and 35, on the south boundary of the township, hereinbefore described.

N. 0° 09.5' E., between sections 34 and 35.

39.776

Point for the 1/4 section corner of sections 34 and 35, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 22 inches in the ground, with aluminum cap marked:

T4S R11W  
1/4  
S34 | S35  
2003

Set an aluminum sign post W of the monument.

79.552

Point for the corner of sections 26, 27, 34 and 35 at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground to solid rock, in a mound of stone, 4 ft. base to top of aluminum cap marked:

T4S R11W  
S27 | S26  
-----  
S34 | S35  
2003

Set an aluminum sign post E of the monument.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

CHAINS

---

From the corner of section 25, 26, 35 and 36.

S. 89° 49.5' W., between section 26 and 35.

**39.685**

The 1/4 section corner of sections 26 and 35, monumented with a sandstone, 12x8x5 inches, loosely set and plainly marked with 1/4 on face and a mound of stone, 3 ft. base, 1 ft. high, to the N.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, in a collar of stone, with aluminum cap marked:

T4S R11W	
	S26
1/4	<u>        </u>
	S35
2002	

Deposit marked stone alongside the monument.

Rebuild mound of stone to the N with a 3 ft. base, 1 1/2 ft. high.

Monument is located in E and W fence line on a steep westerly slope.

---

S. 89° 58.7' W., beginning new measurement.

**39.874**

The corner of sections 26, 27, 34 and 35.

---

N. 0° 17.2' W., between sections 26 and 27.

**39.777**

Point for the 1/4 section corner of sections 26 and 27 at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 4 inches in the ground to solid rock, in a mound of stone, 7 ft. base to top of aluminum cap marked:

T4S R11W	
	1/4
S27	S26
2003	

Set a steel sign post W of the monument.

Monument is located on a steep easterly slope.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

CHAINS  
79.554

The corner of section 22, 23, 26, 27, monumented with a sandstone, 18x9x3 inches, dimly marked and loosely set.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 20 inches in the ground to bed rock, with aluminum cap marked:

T4S	R11W
S22	S23
S27	S26
2003	

Deposit marked stone alongside of the monument.

Set a steel fence post alongside of the monument.

---

From the corner of sections 23, 24, 25, 26.

S. 89° 56.8' W., between sections 23 and 26.

38.973

The 1/4 section corner of sections 23 and 26, monumented with a sandstone, 16x9x3 inches, loosely set, with 1/4 plainly marked on face. There are remnants of a mound of stone to the N.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, and in a mound of stone, 3 ft. base to top of aluminum cap marked:

T4S	R11W
1/4	S23
	S26
2002	

Deposit marked stone alongside the monument.

Corner is located on steep westerly slope.

---

N. 89° 53.6' W., beginning new measurement.

20.170

Point for the W 1/16 section corner of sections 23 and 26, not monumented.

40.340

The corner of sections 22, 23, 26 and 27.

---

N. 0° 03.7' W., between sections 22 and 23.

19.928

Point for the S 1/16 section corner of sections 22 and 23, not

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

monumented.

39.856

Point for the 1/4 section corner of sections 22 and 23, at proportionate distance, there is remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 22 inches in the ground, with aluminum cap marked:

T4S R11W  
1/4  
S22 | S23  
2003

Set a steel fence post alongside the monument.

Monument is located on a steep easterly slope.

59.784

Point for the N 1/16 section corner of sections 22 and 23, not monumented.

64.766

Point for the S-N-N 1/256 section corner of sections 22 and 23.

Set a rebar 18 inches long, 5/8 inch diameter, 14 inches in the ground, with 3 inch aluminum cap marked:

S-N-N  
S22 | S23  
1/256  
2003

Set a steel fence post alongside of the monument.

69.748

Point for the N-N 1/64 section corner of sections 22 and 23, not monumented.

79.712

Point for the corner of sections 14, 15, 22 and 23, falls within the Strawberry Reservoir. This position was determined by the Bureau of Reclamation in 1966 when they found the original sandstone in place and assigned it a coordinate based on the Utah Sate Coordinate System, Central Zone. This position is harmoniously related to identified original corners, and is accepted as the best available evidence of the original corner position.

---

From the corner of sections 13, 14, 23 and 24.

N. 89° 57.7' W., between section 14 and 23.

9.937

Point for the E-E 1/64 section corner of sections 14 and 23, falls in Strawberry Reservoir, not monumented.

19.874

Point for the E 1/16 section corner of sections 14 and 23, falls in Strawberry Reservoir, not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

- 29.811** Point for the W-E 1/64 section corner of sections 14 and 23, falls in Strawberry Reservoir, not monumented.
- 39.748** Point for the 1/4 section corner of sections 14 and 23, at proportionate distance, falls in Strawberry Reservoir, there is no remaining evidence of the original corner, not monumented.
- 49.685** Point for the E-W 1/64 section corner of sections 14 and 23, falls in Strawberry Reservoir, not monumented.
- 59.622** Point for the W 1/16 section corner of sections 14 and 23, not monumented.
- 69.559** Point for the W-W 1/64 section corner of sections 14 and 23, falls in Strawberry Reservoir, not monumented.
- 79.496** The point for the corner of sections 14, 15, 22 and 23.

N. 0° 29.1' E., between sections 14 and 15.

- 19.822** Point for the S 1/16 section corner of sections 14 and 15, not monumented.
- 39.644** Point for the 1/4 section corner of sections 14 and 15, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 22 inches in the ground, with aluminum cap marked:

T4S R11W  
1/4  
S15 | S14  
2003

Set a steel fence post E of the monument.

Monument is located on steep easterly slope.

- 59.466** Point for the N 1/16 section corner of sections 14 and 15, falls in Strawberry Reservoir, not monumented.
- 79.288** The corner of sections 10, 11, 14 and 15, monumented with remnants of a scattered mound of stone, marked by a guy-wired 2x2 inch post with flagging. This monument is accepted as the best available evidence of the original corner.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 18 inches in the ground, to bedrock and in a mound of stone, 4 ft. base to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

	T4S R11W	
S10		S11
S15		S14
2003		

Set aluminum sign post alongside of the monument.

Monument is located on a steep SE facing slope.

---

From the corner of sections 11, 12, 13, and 14.

N. 89° 59.9' W., between sections 11 and 14.

- 39.912** The 1/4 section corner of sections 11 and 14, monumented with an iron post, 2 1/2 inches diameter, projecting 4 inches above ground, and a Forest Service survey marker post 3 ft. to the SW, with brass cap marked as described in the official record of the 1971 remonumentation.

Monument is located in an E and W fence line.

---

N. 89° 56.6' W., beginning new measurement.

- 4.843** Point for the E-E-W 1/256 section corner of sections 11 and 14.

Set a rebar, 18 inches long, 5/8 inch diameter, 15 inches in the ground, with aluminum cap marked:

S11
<u>E-E-W 1/256</u>
S14
2003

Raise a mound of stone on N side of the monument.

Set steel fence post W of the monument.

Monument is located on a N slope and in a 3 strand barbed wire E and W fence line.

- 9.686** Point for the E-W 1/64 section corner of sections 11 and 14, not monumented.
- 19.372** Point for the W 1/16 section corner of sections 11 and 14, falls in Strawberry Reservoir, not monumented.
- 38.744** The corner of sections 10, 11, 14 and 15.

---

From the standard corner of sections 33 and 34, on the south boundary of the township, hereinbefore described.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

N. 0° 00.6' E., between sections 33 and 34.

**40.020**

The 1/4 section corner of sections 33 and 34, monumented with a sandstone, 18x12x6 inches, firmly set and plainly marked with a 1/4 on W face, and with a steel sign post to the W.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T4S R11W	
1/4	
S33	S34
2003	

Deposit the marked stone alongside of the monument.

---

N. 0° 07.9' E., beginning new measurement.

**40.148**

The corner of sections 27, 28, 33 and 34, monumented with a sandstone, 12x6x6 inches, firmly set, 3 holes on E and 1 hole on S faces, with a mound of stone, to the W. There are no original bearing trees remaining.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 20 inches in the ground, in a collar of stone, with aluminum cap marked:

T4S R11W	
S28	S27
2003	
S33	S34

Deposit the marked stone alongside of the monument.

Set a sign post to E of the monument.

---

From the corner of sections 26, 27, 34 and 35.

N. 89° 35.3' W., between sections 27 and 34.

**39.920**

Point for the 1/4 section corner of sections 27 and 34, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 22 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

T4S R11W  
S27  
1/4           
S34  
2003

Set a steel sign post E of the monument.

**79.840** The corner of sections 27, 28, 33, and 34.

---

The Subdivision of Section 13  
T. 4 S., R. 11 W., Uintah Special Meridian, Utah

---

From the 1/4 section corner of sections 13 and 24.

N. 0° 17.5' W., on the N-S center line of section 13.

**4.942** Point for the center S-S-S 1/256 section corner of section 13, not monumented.

**9.884** Point for the center S-S 1/64 section corner of section 13, not monumented.

**19.768** Point for the center S 1/16 section corner of section 13, falls in Strawberry Reservoir, not monumented.

**39.536** Point for the center 1/4 section corner of section 13 at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 8 inches in the ground, to solid rock, and in a mound of stone, 6 ft. base to top of aluminum cap marked:

T4S R11W  
C1/4  
S13  
2003

Set a steel fence post W of the monument.

**44.487** Point for the center S-S-N 1/256 section corner of section 13, monumented with an aluminum post, 1 inch diameter, in a mound of stone, 6 ft. base to top of Forest Service 3 inch aluminum cap marked:

S13  
C-S-S-N  
1/256  
1991

This monument is accepted as a careful and faithful determination of the corner.

THE SUBDIVISION OF SECTION 13  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

CHAINS

An aluminum sign bears 3 links SE, and a sign on a juniper also bears SE.

- 49.438** Point for the center S-N 1/64 section corner of section 13, not monumented.
- 54.389** Point for the center N-S-N 1/256 section corner of section 13, monumented with an aluminum post, 1 inch diameter, in a mound of stone, 6 ft. base to top of Forest Service 3 inch aluminum cap marked:

S13  
C-N-S-N  
1/256  
1991

This monument is accepted as a careful and faithful determination of the corner.

An aluminum sign bears 4 1/2 links S.

- 59.340** Point for the center N 1/16 section corner of section 13, not monumented.
- 79.144** The 1/4 section corner of sections 12 and 13.

From the point for the 1/4 section corner of section 13 and 18, on the east boundary of the township, hereinbefore described.

S. 89° 53.7' W., on the E-W center line of section 13.

- 10.050** Point for the center E-E 1/64 section corner of section 13, not monumented.
- 15.075** Point for the center W-E-E 1/256 section corner of section 13, not monumented.
- 20.100** Point for the center E 1/16 section corner of section 13, not monumented.
- 30.150** Point for the center W-E 1/64 section corner of section 13, not monumented.
- 40.200** The center 1/4 section corner of section 13.
- 50.253** Point for the center E-W 1/64 section corner of section 13, falls in Strawberry Reservoir, not monumented.
- 60.306** Point for the center W 1/16 section corner of section 13, falls in Strawberry Reservoir, not monumented.
- 70.359** Point for the center W-W 1/64 section corner of section 13, not monumented.

THE SUBDIVISION OF SECTION 13  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

**80.412**

The 1/4 section corner of sections 13 and 14.

---

From the point for the center E 1/16 section corner of section 13.

N. 0° 09.5' W., on the N-S center line of the NE 1/4 of section 13.

**4.956**

Point for the center S-S-NE 1/256 section corner of section 13, not monumented.

**9.912**

Point for the center S-NE 1/64 section corner of section 13, not monumented.

**19.824**

Point for the NE 1/16 section corner of section 13, at intersection with the E-W center line of the NE 1/4, not monumented.

**39.646**

The point for the E 1/16 section corner of sections 12 and 13.

---

From the point for the N 1/16 section corner of sections 13 and 18, on the east boundary of the township, hereinbefore described.

S. 89° 50.5' W., on the E-W center line of the NE 1/4 of section 13.

**10.073**

Point for the center E-NE 1/64 section corner of section 13, not monumented.

**20.146**

The point for the NE 1/16 section corner of section 13.

**30.219**

Point for the center W-NE 1/64 section corner of section 13, not monumented.

**40.292**

The point for the center N 1/16 section corner of section 13.

---

From the point for the center E-E 1/64 section corner of section 13.

N. 0° 05.5' W., on the N-S center line of the SE 1/4 of the NE 1/4 of section 13.

**4.958**

Point for the center S-SE-NE 1/256 section corner of section 13, not monumented.

**9.916**

Point for the SE-NE 1/64 section corner of section 13, at intersection with the E-W center line of the SE 1/4 of the NE 1/4, not monumented.

**19.832**

The point for the center E-NE 1/64 section corner of section 13.

THE SUBDIVISION OF SECTION 13  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

CHAINS

---

From the S-N 1/64 section corner of section 13 and 18, on the east boundary of the township, hereinbefore described.

S. 89° 52.1' W., on the E-W center line of the SE 1/4 of the NE 1/4 of section 13.

**10.062** The point for the SE-NE 1/64 section corner of section 13.

**15.093** Point for the center W-SE-NE 1/256 section corner of section 13, monumented with an aluminum post, 1 inch diameter, in a mound of stone, 3 ft. base to top of Forest Service 3 inch aluminum cap, with a mound of stone, 3 ft. base, 1 1/2 ft. high, 4 ft. N., and a sign post 2 ft. E, with cap marked.

S13  
C-W-SE-NE  
1/256  
1991

This monument is accepted as a careful and faithful determination of the corner.

**20.124** The point for the center S-NE 1/64 section corner of section 13.

---

From the point for the center W-E-E 1/256 section corner of section 13.

N. 0° 07.5' W., on the N-S center line of the SW 1/4 of the SE 1/4 of the NE 1/4 of section 13.

**4.957** Point for the SW-SE-NE 1/256 section corner of section 13, at intersection with the E-W center line of the SW 1/4 of the SE 1/4 of the NE 1/4, monumented with an aluminum post, 1 inch diameter, in a mound of stone, 5 ft. base to top of Forest Service 3 inch aluminum cap, with a sign 1 1/2 ft. S. and a mound of stone 3 ft. base, 1 1/2 ft. high, 3 ft. W, with cap marked:

S13  
SW-SE-NE  
1/256  
1991

This monument is accepted as a careful and faithful determination of the corner.

**9.914** The center W-SE-NE 1/256 section corner of section 13.

---

From the point for the center S-SE-NE 1/256 section corner of section 13.

THE SUBDIVISION OF SECTION 13  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

S. 89° 52.9' W., on the E-W center line of the SW 1/4 of the SE 1/4 of the NE 1/4 of section 13.

- 5.028** The SW-SE-NE 1/256 section corner of section 13.
- 10.056** The point for the center S-S-NE 1/256 section corner of section 13.

From the point for the center W-E 1/64 section corner of section 13.

N. 0° 13.5' W., on the N-S center line of the SW 1/4 of the NE 1/4 of section 13.

- 4.953** Point for the center S-SW-NE 1/256 section corner of section 13, not monumented.
- 9.906** Point for the SW-NE 1/64 section corner of section 13, at intersection with the E-W center line of the SW 1/4 of the NE 1/4, not monumented.
- 19.812** The point for the center W-NE 1/64 section corner of section 13.

From the point for the center S-NE 1/64 section corner of section 13.

S. 89° 52.1' W., on the E-W center line of the SW 1/4 of the NE 1/4 of section 13.

- 10.062** The point for the SW-NE 1/64 section corner of section 13.
- 20.124** The point for the center S-N 1/64 section corner of section 13.

From the point for the center S-S-NE 1/256 section corner of section 13.

S. 89° 52.9' W., on the E-W center line of the SE 1/4 of the SW 1/4 of the NE 1/4 of section 13.

- 10.056** The point for the center S-SW-NE 1/256 section corner of section 13.

From the point for the center S-SW-NE 1/256 section corner of section 13.

S. 89° 52.9' W., on the E-W center line of the SW 1/4 of the SW 1/4 of the NE 1/4 of section 13.

- 10.056** The center S-S-N 1/256 section corner of section 13.

THE SUBDIVISION OF SECTION 13  
T. 4 S., R. 11 W., UTAH SPECIAL MERIDIAN

## CHAINS

From the point for the E 1/16 section corner of sections 13 and 24.

N. 0° 09.5' W., on the N-S center line of the SE 1/4 of section 13.

**4.951** Point for the center S-S-SE 1/256 section corner of section 13.

Set a rebar, 18 inches long, 3/4 inch diameter, 18 inches in the ground, with aluminum cap marked:

C-S-S-SE  
1/256 S13  
2003

Set a steel fence post N of the monument.

Monument is located on a gentle N slope near the top of a ridge in aspen and fir.

**9.902** Point for the center S-SE 1/64 section corner of section 13.

Set a rebar, 18 inches long, 3/4 inch diameter, 18 inches in the ground, with aluminum cap marked:

C-S-SE  
1/64 S13  
2003

Monument is located on steep N facing slope in spruce and fir.

**19.804** Point for the SE 1/16 section corner of section 13, at intersection with the E-W center line of the SE 1/4, falls in Strawberry Reservoir, not monumented.

**39.608** The point for the center E 1/16 section corner of section 13.

From the point for the S 1/16 section corner of sections 13 and 18, on the east boundary of the township, hereinbefore described.

S. 89° 59.9' W., on the E-W center line of the SE 1/4 of section 13.

**10.028** Point for the center E-SE 1/64 section corner of section 13, not monumented.

**20.056** The point for the SE 1/16 section corner of section 13.

**30.084** Point for the center W-SE 1/64 section corner of section 13, falls in Strawberry Reservoir, not monumented.

**40.112** The point for the center S 1/16 section corner of section 13.

THE SUBDIVISION OF SECTION 13  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

---

From the point for the E-E 1/64 section corner of sections 13 and 24.

N. 0° 05.5' W., on the N-S center line of the SE 1/4 of the SE 1/4 of section 13.

**9.912**

Point for the SE-SE 1/64 section corner of section 13, at intersection with the E-W center line of the SE 1/4 of the SE 1/4.

Set a rebar, 18 inches long, 5/8 inch diameter, 14 inches in the ground, with 3 inch aluminum cap marked:

S13  
SE-SE  
1/64  
2003

Set an aluminum sign post W of the monument.

**14.868**

Point for the center N-SE-SE 1/256 section corner of section 13.

Set a rebar, 18 inches long, 5/8 inch diameter, 15 inches in the ground, with 3 inch aluminum cap marked:

S13  
C-N-SE-SE  
1/256  
2003

Set an aluminum sign post W of the monument.

**19.824**

The point for the center E-SE 1/64 section corner of section 13.

---

From the point for the S-S 1/64 section corner of sections 13 and 18, on the east boundary of the township, hereinbefore described.

N. 89° 57.0' W., on the E-W center line of the SE 1/4 of the SE 1/4 of section 13.

**10.017**

The SE-SE 1/64 section corner of section 13.

**20.034**

The center S-SE 1/64 section corner of section 13.

---

From the N-S-S 1/256 section corner of sections 13 and 18, on the east boundary of the township, hereinbefore described.

N. 89° 58.5' W., on the E-W center line of the NE 1/4 of the SE 1/4 of the SE 1/4 of section 13.

THE SUBDIVISION OF SECTION 13  
T. 4 S., R. 11 W., UTAH SPECIAL MERIDIAN

CHAINS  
10.022

The center N-SE-SE 1/256 section corner of section 13.

---

From the point for the W-E 1/64 section corner of sections 13 and 24.

N. 0° 13.5' W., on the N-S center line of the SW 1/4 of the SE 1/4 of section 13.

4.947 Point for the center S-SW-SE 1/256 section corner of section 13, not monumented.

9.894 Point for the SW-SE 1/64 section corner of section 13, at intersection with the E-W center line of the SW 1/4 of the SE 1/4, not monumented.

19.787 The point for the center W-SE 1/64 section corner of section 13.

---

From the center S-SE 1/64 section corner of section 13.

N. 89° 57.0' W., on the E-W center line of the SW 1/4 of the SE 1/4 of section 13.

10.017 The point for the SW-SE 1/64 section corner of section 13.

20.034 The point for the center S-S 1/64 section corner of section 13.

---

From the center S-S-SE 1/256 section corner of section 13.

N. 89° 55.4' W., on the E-W center line of the SE 1/4 of the SW 1/4 of the SE 1/4 of section 13.

10.011 The point for the center S-SW-SE 1/256 section corner of section 13.

---

From the point for the center S-SW-SE 1/256 section corner of section 13.

N. 89° 55.4' W., on the E-W center line of the SW 1/4 of the SW 1/4 of the SE 1/4 of section 13.

10.011 The point for the center S-S-S 1/256 section corner of section 13.

---

From the point for the W 1/16 section corner of sections 13 and 24.

N. 0° 11.9' W., on the N-S center line of the SW 1/4 of section 13.

THE SUBDIVISION OF SECTION 13  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

- 9.898** Point for the center S-SW 1/64 section corner of section 13, not monumented.
- 19.796** Point for the SW 1/16 section corner of section 13, at intersection with the E-W center line of the SW 1/4, not monumented.
- 39.592** The point for the center W 1/16 section corner of section 13.
- 
- From the point for the center S 1/16 section corner of section 13.
- S. 89° 49.0' W., on the E-W center line of the SW 1/4 of section 13.
- 10.070** Point for the center E-SW 1/64 section corner of section 13, not monumented.
- 20.140** The point for the SW 1/16 section corner of section 13.
- 40.280** The point for the S 1/16 section corner of sections 13 and 14.
- 
- From the point for the E-W 1/64 section corner of sections 13 and 24.
- N. 0° 14.7' W., on the N-S center line of the SE 1/4 of the SW 1/4 of section 13.
- 4.946** Point for the center S-SE-SW 1/256 section corner of section 13, not monumented.
- 9.892** Point for the SE-SW 1/64 section corner of section 13, at intersection with the E-W center line of the SE 1/4 of the SW 1/4, not monumented.
- 19.784** The point for the center E-SW 1/64 section corner of section 13.
- 
- From the point for the center S-S 1/64 section corner of section 13.
- S. 89° 46.7' W., on the E-W center line of the SE 1/4 of the SW 1/4 of section 13.
- 5.039** Point for the center E-SE-SW 1/256 section corner of section 13, not monumented.
- 10.078** The point for the SE-SW 1/64 section corner of section 13.
- 20.156** The point for the center S-SW 1/64 section corner of section 13.
- 
- From the E-E-W 1/256 section corner of sections 13 and 24.

THE SUBDIVISION OF SECTION 13  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

N. 0° 16.1' W., on the N-S center line of the SE 1/4 of the SE 1/4 of the SW 1/4 of section 13.

4.944

Point for the SE-SE-SW 1/256 section corner of section 13, at intersection with the E-W center line of the SE 1/4 of the SE 1/4 of the SW 1/4.

Set a rebar, 18 inches long, 3/4 inch diameter, 8 inches in the ground, in a collar of stone, 3 ft. base to top of 3 inch aluminum cap marked:

SE-SE-SW  
1/256 S13  
2003

Set steel fence post E of the monument.

Monument is located on a gentle southerly slope in sagebrush and large boulders.

9.888

The point for the center E-SE-SW 1/256 section corner of section 13.

---

From the center S-S-S 1/256 section corner of section 13.

S. 89° 45.5' W., on the E-W center line of the SE 1/4 of the SE 1/4 of the SW 1/4 of section 13.

5.041

The SE-SE-SW 1/256 section corner of section 13.

10.082

The point for the center S-SE-SW 1/256 section corner of section 13.

---

From the point for the center W 1/16 section corner of section 13.

N. 0° 12.0' W., on the N-S center line of the NW 1/4 of section 13.

9.908

Point for the center S-NW 1/64 section corner of section 13, monumented with an 1 inch diameter aluminum post and an aluminum sign post alongside, in a mound of stone, 3 ft. base to top of 3 inch Forest Service aluminum cap marked:

S13  
C-S-NW  
1/64  
1991

This monument is accepted as a careful and faithful determination of the corner.

THE SUBDIVISION OF SECTION 13  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

CHAINS  
14.862

Point for the center N-S-NW 1/256 section corner of section 13, monumented with an 1 inch diameter aluminum post and an aluminum sign post alongside in a mound of stone, 4 ft. base to top of 3 inch Forest Service aluminum cap marked:

S13  
C-N-S-NW  
1/256  
1991

This monument is accepted as a careful and faithful determination of the corner.

- 19.816 Point for the NW 1/16 section corner of section 13, at intersection with the E-W center line of the NW 1/4, not monumented.
- 39.630 Point for the W 1/16 section corner of sections 12 and 13.

From the point for the center N 1/16 section corner of section 13.

S. 89° 55.6' W., on the E-W center line of the NW 1/4 of section 13.

- 10.037 Point for the center E-NW 1/64 section corner of section 13, not monumented.
- 20.074 The point for the NW 1/16 section corner of section 13.
- 30.111 Point for the center W-NW 1/64 section corner of section 13, not monumented.
- 40.148 The point for the N 1/16 section corner of sections 13 and 14.

From the center E-W 1/64 section corner of section 13.

N. 0° 14.7' W., on the N-S center line of the SE 1/4 of the NW 1/4 of section 13.

- 9.905 Point for the SE-NW 1/64 section corner of section 13, at intersection with the E-W center line of the SE 1/4 of the NW 1/4, not monumented.
- 14.857 Point for the center N-SE-NW 1/256 section corner of section 13, not monumented.
- 19.809 The point for the center E-NW 1/64 section corner of section 13.

From the point for the center S-N 1/64 section corner of section 13.

THE SUBDIVISION OF SECTION 13  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

S. 89° 54.6' W., on the E-W center line of the SE 1/4 of the NW 1/4 of section 13.

**10.045** The point for the SE-NW 1/64 section corner of section 13.

**20.090** The center S-NW 1/64 section corner of section 13.

---

From the center N-S-N 1/256 section corner of section 13.

S. 89° 55.1' W., on the E-W center line of the NE 1/4 of the SE 1/4 of the NW 1/4 of section 13.

**10.041** The point for the center N-SE-NW 1/256 section corner of section 13.

---

From the point for the center N-SE-NW 1/256 section corner of section 13.

S. 89° 55.1' W., on the E-W center line of the NW 1/4 of the SE 1/4 of the NW 1/4 of section 13.

**10.041** The center N-S-NW 1/256 section corner of section 13.

---

From the point for the center W-W 1/64 section corner of section 13.

N. 0° 09.3' W., on the N-S center line of the SW 1/4 of the NW 1/4 of section 13.

**4.955** Point for the center S-SW-NW 1/256 section corner of section 13, monumented with an 1 inch diameter aluminum post, with an aluminum sign alongside, in a mound of stone, 4 ft. base to top of 3 inch Forest Service aluminum cap marked:

S13  
C-S-SW-NW  
1/256  
1991

This monument is accepted as a careful and faithful determination of the corner.

**9.910** Point for the SW-NW 1/64 section corner of section 13, at the intersection with the E-W center line of the SW 1/4 of the NW 1/4, monumented with an 1 inch diameter aluminum post, with an aluminum sign alongside, in a mound of stone, 3 ft. base to top of 3 inch Forest Service aluminum cap marked:

THE SUBDIVISION OF SECTION 13  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

S13  
SW-NW  
1/64  
1991

This monument is accepted as a careful and faithful determination of the corner.

**19.820** The point for the center W-NW 1/64 section corner of section 13.

---

From the center S-NW 1/64 section corner of section 13.

S. 89° 54.6' W., on the E-W center line of the SW 1/4 of the NW 1/4 of section 13.

**10.045** The SW-NW 1/64 section corner of section 13.

**20.090** The point for the S-N 1/64 section corner of sections 13 and 14.

---

From the center S-SW-NW 1/256 section corner of section 13.

S. 89° 54.2' W., on the E-W center line of the SW 1/4 of the SW 1/4 of the NW 1/4 of section 13.

**10.049** The S-S-N 1/256 section corner of sections 13 and 14.

---

The Subdivision of Section 14  
T. 4 S., R. 11 W., Uintah Special Meridian, Utah

---

From the point for the 1/4 section corner of sections 14 and 23.

N. 0° 14.0' W., on the N-S center line of section 14.

**19.824** Point for the center S 1/16 section corner of section 14.

Set a rebar, 18 inches long, 5/8 inch diameter, 15 inches in the ground, with 3 inch aluminum cap marked:

S14  
C-S  
1/16  
2003

Set a steel fence post N of the monument.

**24.780** Point for the center S-N-S 1/256 section corner of section 14.

Set a rebar, 18 inches long, 5/8 inch diameter, 12 inches in the ground, with 3 inch aluminum cap marked:

THE SUBDIVISION OF SECTION 14  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

S14  
C-S-N-S 1/256  
2003

Set a steel fence post 4 ft. E of the monument.

Monument is located on a sandstone outcropping on a westerly slope.

**29.736** Point for the center N-S 1/64 section corner of section 14, not monumented.

**39.648** Point for the center 1/4 section corner of section 14, at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 22 inches in the ground, with aluminum cap marked:

T4S R11W  
S14  
C 1/4  
2003

Set a steel fence post alongside the monument.

**49.554** Point for the center S-N 1/64 section corner of section 14, not monumented.

**59.460** Point for the center N 1/16 section corner of section 14, not monumented.

**69.366** Point for the center N-N 1/64 section corner of section 14, not monumented.

**74.319** Point for the center N-N-N 1/256 section corner of section 14, not monumented.

**79.272** The 1/4 section corner of sections 11 and 14.

From the 1/4 section corner of sections 13 and 14.

N. 89° 57.9' W., on the E-W center line of section 14.

**4.979** Point for the center E-E-E 1/256 section corner of section 14.

Set a rebar, 18 inches long, 5/8 inch diameter, 9 inches in the ground, to solid rock, in a mound of stone, 3 ft. base to top of 3 inch aluminum cap marked:

S14  
C-E-E-E  
1/256  
2003

THE SUBDIVISION OF SECTION 14  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

Set steel fence post S of the monument.

Monument is located on a steep south slope.

- 9.958** Point for the center E-E 1/64 section corner of section 14, not monumented.
- 19.916** Point for the center E 1/16 section corner of section 14, not monumented.
- 39.832** The center 1/4 section corner of section 14.
- 49.644** Point for the center E-W 1/64 section corner of section 14, not monumented.
- 59.456** Point for the center W 1/16 section corner of section 14, falls in Strawberry Reservoir, not monumented.
- 79.080** The 1/4 section corner of sections 14 and 15.

From the point for the E 1/16 section corner of sections 14 and 23.

N. 0° 10.2' W., on the N-S center line of the SE 1/4 of section 14.

- 19.824** Point for the SE 1/16 section corner of section 14 at intersection with the E-W center line of the SE 1/4, not monumented.
- 29.736** Point for the center N-SE 1/64 section corner of section 14, not monumented.
- 39.648** The point for the center E 1/16 section corner of section 14.

From the point for the S 1/16 section corner of sections 13 and 14.

N. 89° 57.8' W., on the E-W center line of the SE 1/4 of section 14.

- 9.947** Point for the center E-SE 1/64 section corner of section 14.

Set a rebar, 18 inches long, 5/8 inch diameter, 12 inches in the ground, in a collar of stone, 3 ft. base to top of 3 inch aluminum cap marked:

S14  
C-E-SE  
1/64  
2003

Set steel fence post W of the monument.

THE SUBDIVISION OF SECTION 14  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

Monument is located on a steep easterly slope.

**19.894** The point for the SE 1/16 section corner of section 14.

**39.788** The center S 1/16 section corner of section 14.

---

From the center E-SE 1/64 section corner of section 14.

N. 0° 08.3' W., on the N-S center line of the NE 1/4 of the SE 1/4 of section 14.

**9.912** Point for the NE-SE 1/64 section corner of section 14, at intersection with the E-W center line of the NE 1/4 of the SE 1/4, not monumented.

**14.868** Point for the center N-NE-SE 1/256 section corner of section 14.

Set a rebar, 18 inches long, 5/8 inch diameter, 15 inches in the ground, in a collar of stone, with a 3 inch aluminum cap marked:

S14  
C-N-NE-SE  
1/256  
2003

Set steel fence post W of the monument.

**19.824** The point for the center E-E 1/64 section corner of section 14.

---

From the point for the N-S 1/64 section corner of sections 13 and 14.

N. 89° 57.9' W., on the E-W center line of the NE 1/4 of the SE 1/4 of section 14.

**4.976** Point for the center E-NE-SE 1/256 section corner of section 14, not monumented.

**9.952** The point for the NE-SE 1/64 section corner of section 14.

**19.904** The point for the center N-SE 1/64 section corner of section 14.

---

From the point for the center E-NE-SE 1/256 section corner of section 14.

N. 0° 07.4' W., on the N-S center line of the NE 1/4 of the NE 1/4 of the SE 1/4 of section 14.

THE SUBDIVISION OF SECTION 14  
T. 4 S., R. 11 W., UINTEAH SPECIAL MERIDIAN

## CHAINS

4.956

Point for the NE-NE-SE 1/256 section corner of section 14, at intersection with the E-W center line of the NE 1/4 of the NE 1/4 of the SE 1/4.

Set a rebar, 18 inches long, 5/8 inch diameter, 4 inches in the ground, to bedrock and in a mound of stone, 3 ft. base to top of 3 inch aluminum cap marked:

S14  
NE-NE-SE  
1/256  
2003

Set steel fence post E of the monument.

9.912

The center E-E-E 1/256 section corner of section 14.

---

From the point for the N-N-S 1/256 section corner of sections 13 and 14.

N. 89° 57.9' W., on the E-W center line of the NE 1/4 of the NE 1/4 of the SE 1/4 of section 14.

4.978

The NE-NE-SE 1/256 section corner of section 14.

9.956

The center N-NE-SE 1/256 section corner of section 14.

---

From the point for the W 1/16 section corner of sections 14 and 23.

N. 0° 07.6' E., on the N-S center line of the SW 1/4 of section 14.

19.823

Point for the SW 1/16 section corner of section 14, at intersection with the E-W center line of the SW 1/4, not monumented.

29.734

Point for the center N-SW 1/64 section corner of section 14, falls in Strawberry Reservoir, not monumented.

39.645

The point for the center W 1/16 section corner of section 14.

---

From the center S 1/16 section corner of section 14.

N. 89° 57.8' W., on the E-W center line of the SW 1/4 of section 14.

THE SUBDIVISION OF SECTION 14  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

- 9.874** Point for the center E-SW 1/64 section corner of section 14, not monumented.
- 19.748** The point for the SW 1/16 section corner of section 14.
- 39.497** The point for the S 1/16 section corner of section 14 and 15.
- 

From the point for the center E-SW 1/64 section corner of section 14.

N. 0° 03.2' W., on the N-S center line of the NE 1/4 of the SW 1/4 of section 14.

- 4.956** Point for the center S-NE-SW 1/256 section corner of section 14.

Set a rebar, 18 inches long, 5/8 inch diameter, 16 inches in the ground, with a 3 inch aluminum cap marked:

S14  
C-S-NE-SW  
1/256  
2003

Set aluminum sign post N of the monument.

Monument is located on a 4X4 trail.

- 9.912** Point for the NE-SW 1/64 section corner of section 14, at intersection with the E-W center line of the NE 1/4 of the SW 1/4, not monumented.
- 19.824** The point for the center E-W 1/64 section corner of section 14.
- 

From the point for the center N-S 1/64 section corner of section 14.

N. 89° 57.9' W., on the E-W center line of the NE 1/4 of the SW 1/4 of section 14.

- 9.843** The point for the NE-SW 1/64 section corner of section 14.
- 19.686** The point for the center N-SW 1/64 section corner of section 14.
- 

From the center S-N-S 1/256 section corner of section 14.

N. 89° 57.8' W., on the E-W center line of the SE 1/4 of the NE 1/4 of the SW 1/4 of section 14.

- 9.859** The center S-NE-SW 1/256 section corner of section 14.
-

THE SUBDIVISION OF SECTION 14  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

From the point for the center W 1/16 section corner of section 14.

N. 0° 07.6' E., on the N-S center line of the NW 1/4 of section 14.

- 9.909** Point for the center S-NW 1/64 section corner of section 14, not monumented.
- 19.818** Point for the NW 1/16 section corner of section 14, at intersection in with the E-W center line of the NW 1/4, not monumented.
- 24.772** Point for the center S-N-NW 1/256 section corner of section 14, not monumented.
- 29.726** Point for the center N-NW 1/64 section corner of section 14, not monumented.
- 39.634** The point for the W 1/16 section corner of section 11 and 14.

From the point for the center N 1/16 section corner of section 14.

N. 89° 57.2' W., on the E-W center line of the NW 1/4 of section 14.

- 9.748** Point for the center E-NW 1/64 section corner of section 14, not monumented.
- 14.622** Point for the center W-E-NW 1/256 section corner of section 14, not monumented.
- 19.496** The point for the NW 1/16 section corner of section 14.
- 38.994** The point for the N 1/16 section corner of section 14 and 15.

From the point for the center E-NW 1/64 section corner of section 14.

N. 0° 03.2' W., on the N-S center line of the NE 1/4 of the NW 1/4 of section 14.

- 4.954** Point for the center S-NE-NW 1/256 section corner of section 14.
- Set a rebar, 18 inches long, 5/8 inch diameter, 15 inches in the ground, with a 3 inch aluminum cap marked:

S14  
C-S-NE-NW  
1/256  
2003

THE SUBDIVISION OF SECTION 14  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

Set steel fence post N of the monument.

- 9.908** Point for the NE-NW 1/64 section corner of section 14, at intersection with the E-W center line of the NE 1/4 of the NW 1/4, not monumented.
- 14.862** Point for the center N-NE-NW 1/256 section corner of section 14.  
Set a rebar, 18 inches long, 5/8 inch diameter, 15 inches in the ground, with a 3 inch aluminum cap marked:
- S14  
C-N-NE-NW  
1/256  
2003
- Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N of the monument.
- Set steel fence post S of the monument.
- 19.816** The point for the E-W 1/64 section corner of sections 11 and 14.
- 
- From the point for the center N-N 1/64 section corner of section 14.  
N. 89° 56.9' W., on the E-W center line of the NE 1/4 of the NW 1/4 of section 14.
- 4.859** Point for the center E-NE-NW 1/256 section corner of section 14, not monumented.
- 9.718** The point for the NE-NW 1/64 section corner of section 14.
- 14.577** Point for the center W-NE-NW 1/256 section corner of section 14, not monumented.
- 19.436** The point for the center N-NW 1/64 section corner of section 14.
- 
- From the point for the center E-NE-NW 1/256 section corner of section 14.  
N. 0° 08.6' W., on the N-S center line of the NE 1/4 of the NE 1/4 of the NW 1/4 of section 14.
- 4.954** Point for the NE-NE-NW 1/256 section corner of section 14, at intersection with the E-W center line of the NE 1/4 of the NE 1/4 of the NW 1/4.  
Set a rebar, 18 inches long, 5/8 inch diameter, 15 inches in the ground, with a 3 inch aluminum cap marked:

THE SUBDIVISION OF SECTION 14  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

S14  
NE-NE-NW  
1/256  
2003

Set steel fence post N of the monument.

Monument is located on top of NE facing knoll.

**9.908** The E-E-W 1/256 section corner of section 11 and 14.

---

From the point for the center N-N-N 1/256 section corner of section 14.

N. 89° 56.7' W., on the E-W center line of the NE 1/4 of the NE 1/4 of the NW 1/4 of section 14.

**4.851** The NE-NE-NW 1/256 section corner of section 14.

**9.702** The center N-NE-NW 1/256 section corner of section 14.

---

From the point for the center W-E-NW 1/256 section corner of section 14.

N. 0° 02.2' E., on the N-S center line of the SW 1/4 of the NE 1/4 of the NW 1/4 of section 14.

**4.954** Point for the SW-NE-NW 1/256 section corner of section 14, at intersection with the E-W center line of the SW 1/4 of the NE 1/4 of the NW 1/4.

Set a rebar, 18 inches long, 5/8 inch diameter, 15 inches in the ground, with a 3 inch aluminum cap marked:

S14  
SW-NE-NW  
1/256  
2003

Raise a mound of stone, 3ft. base, 1 1/2 ft. high, N of the monument.

Set steel fence post S of the monument.

**9.908** The point for the center W-NE-NW 1/256 section corner of section 14.

---

From the center S-NE-NW 1/256 section corner of section 14.

N. 89° 57.1' W., on the E-W center line of the SW 1/4 of the NE 1/4 of the NW 1/4 of section 14.

THE SUBDIVISION OF SECTION 14  
T. 4 S., R. 11 W., UTAH SPECIAL MERIDIAN

## CHAINS

4.867

The SW-NE-NW 1/256 section corner of section 14.

9.734

The point for the center S-N-NW 1/256 section corner of section 14.

---

From the point for the center E-W 1/64 section corner of section 14.

N. 0° 03.2' W., on the N-S center line of the SE 1/4 of the NW 1/4 of section 14.

9.908

Point for the SE-NW 1/64 section corner of section 14, at intersection with the E-W center line of the SE 1/4 of the NW 1/4.

Set a rebar, 18 inches long, 5/8 inch diameter, 15 inches in the ground, with a 3 inch aluminum cap marked:

S14  
SE-NW  
1/64  
2003

Set steel fence post alongside of the monument.

19.816

The point for the center E-NW 1/64 section corner of section 14.

---

From the point for the center S-N 1/64 section corner of section 14.

N. 89° 57.6' W., on the E-W center line of the SE 1/4 of the NW 1/4 of section 14.

9.780

The SE-NW 1/64 section corner of section 14.

14.670

Point for the center W-SE-NW 1/256 section corner of section 14.

Set a rebar, 18 inches long, 5/8 inch diameter, 15 inches in the ground, with a 3 inch aluminum cap marked:

S14  
C-W-SE-NW  
1/256  
2003

Raise a mound of stone, 4 ft. base, 2 ft. high, W of the monument.

Set steel fence post N of the monument.

Monument is located on a steep westerly slope.

THE SUBDIVISION OF SECTION 14  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

CHAINS  
19.560

The point for the center S-NW 1/64 section corner of section 14.

---

From the center W-SE-NW 1/256 section corner of section 14.

N. 0° 02.2' E., on the N-S center line of the NW 1/4 of the SE 1/4 of the NW 1/4 of section 14.

9.908

The point for the center W-E-NW 1/256 section corner of section 14.

---

The Subdivision of Section 23  
T. 4 S. R. 11 W., Uintah Special Meridian, Utah

---

From the 1/4 section corner of sections 23 and 26.

N. 0° 28.9' W., on the N-S center line of section 23.

19.980

Point for the center S 1/16 section corner of section 23, not monumented.

29.970

Point for the center N-S 1/64 section corner of section 23, not monumented.

34.965

Point for the center N-N-S 1/256 section corner of section 23.

Set a rebar, 18 inches long, 5/8 inch diameter, 15 inches in the ground, with a 3 inch aluminum cap marked:

S23  
C-N-N-S  
1/256  
2003

Set an aluminum sign post W of the monument.

39.960

The point for the center 1/4 section corner of section 23, at intersection with the E-W center line, not monumented.

44.935

Point for the center S-S-N 1/256 section corner of section 23.

Set a rebar, 18 inches long, 5/8 inch diameter, 14 inches in the ground, with a 3 inch aluminum cap marked:

S23  
C-S-S-N  
1/256  
2003

Set an aluminum sign post W of the monument.

THE SUBDIVISION OF SECTION 23  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

- 49.910** Point for the center S-N 1/64 section corner of section 23, not monumented.
- 59.860** Point for the center N 1/16 section corner of section 23, not monumented.
- 69.810** Point for the center N-N 1/64 section corner of section 23, not monumented.
- 79.760** The point for the 1/4 section corner of sections 14 and 23.
- 
- From the 1/4 section corner of sections 23 and 24.
- S.89° 57.4' W., on the E-W center line of section 23.
- 9.892** Point for the center E-E 1/64 section corner of section 23, not monumented.
- 19.784** Point for the center E 1/16 section corner of section 23, not monumented.
- 29.676** Point for the center W-E 1/64 section corner of section 23, not monumented.
- 34.622** Point for the center W-W-E 1/256 section corner of section 23, not monumented.
- 39.568** The point for the center 1/4 section corner of section 23.
- 49.578** Point for the center E-W 1/64 section corner of section 23, not monumented.
- 54.583** Point for the center W-E-W 1/256 section corner of section 23, not monumented.
- 59.588** Point for the center W 1/16 section corner of section 23, not monumented.
- 79.608** The 1/4 section corner of sections 22 and 23.
- 
- From the point for the center E 1/16 section corner of section 23.
- N. 0° 20.9' W., on the N-S center line of the NE 1/4 of section 23.
- 9.942** Point for the center S-NE 1/64 section corner of section 23, not monumented.
- 19.884** Point for the NE 1/16 section corner of section 23, at intersection with the E-W center line of the NE 1/4, not monumented.

THE SUBDIVISION OF SECTION 23  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

- 24.855** Point for the center S-N-NE 1/256 section corner of section 23, not monumented.
- 29.826** Point for the center N-NE 1/64 section corner of section 23, not monumented.
- 39.768** The point for the E 1/16 section corner of sections 14 and 23.
- 

From the point for the N 1/16 section corner of sections 23 and 24.

S.89° 59.8' W., on the E-W center line of the NE 1/4 of section 23.

- 9.914** Point for the center E-NE 1/64 section corner of section 23.

Set a rebar, 18 inches long, 5/8 inch diameter, 15 inches in the ground, with a 3 inch aluminum cap marked:

S23  
C-E-NE  
1/64  
2003

Set an aluminum sign post W of the monument.

- 14.871** Point for the center W-E-NE 1/256 section corner of section 23.

Set a rebar, 18 inches long, 5/8 inch diameter, 15 inches in the ground, with a 3 inch aluminum cap marked:

S23  
C-W-E-NE  
1/256  
2003

Set steel fence post W of the monument.

- 19.828** The point for the NE 1/16 section corner of section 23.

- 29.742** Point for the W-NE 1/64 section corner of section 23.

Set a rebar, 18 inches long, 5/8 inch diameter, 14 inches in the ground, with a 3 inch aluminum cap marked:

S23  
C-W-NE  
1/64  
2003

Set an aluminum sign post W of the monument.

THE SUBDIVISION OF SECTION 23  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

**34.699**

Point for the center W-W-NE 1/256 section corner of section 23.

Set a rebar, 18 inches long, 5/8 inch diameter, 14 inches in the ground, with a 3 inch aluminum cap marked:

S23  
C-W-W-NE  
1/256  
2003

Set an aluminum sign post W of the monument.

**39.656**

The point for the center N 1/16 section corner of section 23.

---

From the center E-NE 1/64 section corner of sections 23.

N. 0° 16.9' W., on the N-S center line of the NE 1/4 of the NE 1/4 of section 23.

**4.969**

Point for the center S-NE-NE 1/256 section corner of section 23, not monumented.

**9.938**

Point for the NE-NE 1/64 section corner of section 23, at intersection with the E-W center line of the NE 1/4 of the NE 1/4, not monumented.

**19.876**

Point for the E-E 1/64 section corner of sections 14 and 23.

---

From the point for the N-N 1/64 section corner of sections 23 and 24.

S.89° 58.9' W., on the E-W center line of the NE 1/4 of the NE 1/4 of section 23.

**9.926**

The point for the NE-NE 1/64 section corner of section 23.

**14.889**

Point for the center W-NE-NE 1/256 section corner of section 23, not monumented.

**19.852**

The point for the center N-NE 1/64 section corner of section 23.

---

From the center W-E-NE 1/256 section corner of section 23.

N. 0° 18.9' W., on the N-S center line of the SW 1/4 of the NE 1/4 of the NE 1/4 of section 23.

**4.970**

Point for the SW-NE-NE 1/256 section corner of section 23, at intersection with the E-W center line of the SW 1/4 of the NE 1/4 of the NE 1/4.

Set a rebar, 18 inches long, 5/8 inch diameter, 14 inches in the ground, with a 3 inch aluminum cap marked:

THE SUBDIVISION OF SECTION 23  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

CHAINS

S23  
SW-NE-NE  
1/256  
2003

Set an aluminum sign post W of the monument.

- 9.940** The point for the center W-NE-NE 1/256 section corner of section 23.
- 

From the point for the center S-NE-NE 1/256 section corner of section 23.

N. 89° 59.6' W., on the E-W center line of the SW 1/4 of the NE 1/4 of the NE 1/4 of section 23.

- 4.960** The point for the SW-NE-NE 1/256 section corner of section 23.

- 9.920** The point for the center S-N-NE 1/256 section corner of section 23.
- 

From the point for the center E-E 1/64 section corner of section 23.

N. 0° 16.9' W., on the N-S center line of the SE 1/4 of the NE 1/4 of section 23.

- 9.938** Point for the SE-NE 1/64 section corner of section 23, at intersection with the E-W center line of the SE 1/4 of the NE 1/4.

Set a rebar, 18 inches long, 5/8 inch diameter, 15 inches in the ground, with a 3 inch aluminum cap marked:

S23  
SE-NE  
1/64  
2003

Set an aluminum sign post W of the monument.

- 19.876** The center E-NE 1/64 section corner of section 23.
- 

From the S-N 1/64 section corner of section 23 and 24.

S. 89° 58.6' W., on the E-W center line of the SE 1/4 of the NE 1/4 of section 23.

- 9.903** The SE-NE 1/64 section corner of section 23.

- 19.806** The point for the center S-NE 1/64 section corner of section 23.
-

THE SUBDIVISION OF SECTION 23  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

From the point for the center W-E 1/64 section corner of section 23.

N. 0° 24.9' W., on the N-S center line of the SW 1/4 of the NE 1/4 of section 23.

**4.973** Point for the center S-SW-NE 1/256 section corner of section 23, not monumented.

**9.946** Point for the SW-NE 1/64 section corner of section 23, at intersection with the E-W center line of the SW 1/4 of the NE 1/4, not monumented.

**19.892** The center W-NE 1/64 section corner of section 23.

---

From the point for the center S-NE 1/64 section corner of section 23.

S. 89° 58.6' W., on the E-W center line of the SW 1/4 of the NE 1/4 of section 23.

**9.903** The point for the SW-NE 1/64 section corner of section 23.

**14.855** Point for the center W-SW-NE 1/256 section corner of section 23, not monumented.

**19.807** The point for the center S-N 1/64 section corner of section 23.

---

From the point for the center W-W-E 1/256 section corner of section 23.

N. 0° 26.9' W., on the N-S center line of the SW 1/4 of the SW 1/4 of the NE 1/4 of section 23.

**4.974** Point for the SW-SW-NE 1/256 section corner of section 23, at intersection with the E-W center line of the SW 1/4 of the SW 1/4 of the NE 1/4 of section 23.

Set a rebar, 18 inches long, 5/8 inch diameter, 14 inches in the ground, with a 3 inch aluminum cap marked:

S23  
SW-SW-NE  
1/256  
2003

Set an aluminum sign post W of the monument.

THE SUBDIVISION OF SECTION 23  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

9.948

The point for the center W-SW-NE 1/256 section corner of section 23.

---

From the point for the center S-SW-NE 1/256 section corner of section 23.

S. 89° 58.0' W., on the E-W center line of the SW 1/4 of the SW 1/4 of the NE 1/4 of section 23.

4.949

The SW-SW-NE 1/256 section corner of section 23.

9.898

The center S-S-N 1/256 section corner of section 23.

---

From the point for the center W-SW-NE 1/256 section corner of section 23.

N. 0° 26.9' W., on the N-S center line of the NW 1/4 of the SW 1/4 of the NE 1/4 of section 23.

9.948

The center W-W-NE 1/256 section corner of section 23.

---

From the center W-NE 1/64 section corner of section 23.

N. 0° 24.9' W., on the N-S center line of the NW 1/4 of the NE 1/4 of section 23.

4.973

Point for the center S-NW-NE 1/256 section corner of section 23.

Set a rebar, 18 inches long, 5/8 inch diameter, 14 inches in the ground, with a 3 inch aluminum cap marked:

S23  
C-S-NW-NE  
1/256  
2003

Set an aluminum sign post W of the monument.

9.946

Point for the NW-NE 1/64 section corner of section 23, at intersection with the E-W center line of the NW 1/4 of the NE 1/4, not monumented.

19.892

The point for the W-E 1/64 section corner of sections 14 and 23.

---

From the point for the center N-NE 1/64 section corner of section 23.

N. 89° 58.9' W., on the E-W center line of the NW 1/4 of the NE 1/4 of section 23.

THE SUBDIVISION OF SECTION 23  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

- 9.926** The point for the NW-NE 1/64 section corner of section 23.
- 19.852** The point for the center N-N 1/64 section corner of section 23.
- 
- From the point for the center S-N-NE 1/256 section corner of section 23.
- N. 89° 59.6' W., on the E-W center line of the SE 1/4 of the NW 1/4 of the NE 1/4 of section 23.
- 9.920** The center S-NW-NE 1/256 section corner of section 23.
- 
- From the point for the W 1/6 section corner of sections 23 and 26.
- N. 0° 16.3' W., on the N-S center line of the SW 1/4 of section 23.
- 19.954** Point for the SW 1/16 section corner of section 23, at intersection with the E-W center line of the SW 1/4, not monumented.
- 29.930** The point for the center N SW 1/64 section corner of section 23, not monumented.
- 34.918** Point for the center N-N-SW 1/256 section corner of section 23, not monumented.
- 39.906** The point for the center W 1/16 section corner of section 23.
- 
- From the point for the center S 1/16 section corner of section 23.
- N. 89° 58.1' W., on the E-W center line of the SW 1/4 of section 23.
- 10.048** Point for the center E-SW 1/64 section corner of section 23, not monumented.
- 20.096** The point for the SW 1/16 section corner of section 23.
- 40.191** The point for the S 1/16 section corner of sections 22 and 23.
- 
- From the point for the center E-SW 1/64 section corner of section 23.
- N. 0° 22.6' W., on the N-S center line of the NE 1/4 of the SW 1/4 of section 23.

THE SUBDIVISION OF SECTION 23  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

- 9.983** Point for the NE-SW 1/64 section corner of section 23, at intersection with the E-W center line of the NE 1/4 of the SW 1/4 of section 23, not monumented.
- 14.975** Point for the center N-NE-SW 1/256 section corner of section 23, not monumented.
- 19.967** The point for the center E-W 1/64 section corner of section 23.
- 
- From the point for the center N-S 1/64 section corner of section 23.
- S. 89° 59.7' W., on the E-W center line of the NE 1/4 of the SW 1/4 of section 23.
- 10.030** The point for the NE-SW 1/64 section corner of section 23.
- 15.045** Point for the center W-NE-SW 1/256 section corner of section 23, not monumented.
- 20.060** The point for the center N-SW 1/64 section corner of section 23.
- 
- From the center N-N-S 1/256 section corner of section 23.
- S. 89° 58.5' W., on the E-W center line of the NE 1/4 of the NE 1/4 of the SW 1/4 of section 23.
- 10.020** The point for the center N-NE-SW 1/256 section corner of section 23.
- 
- From the point for the center W-NE-SW 1/256 section corner of section 23.
- N. 0° 19.4' W., on the N-S center line of the NW 1/4 of the NE 1/4 of the SW 1/4 of section 23.
- 4.990** Point for the NW-NE-SW 1/256 section corner of section 23, at intersection with the E-W center line of the NW 1/4 of the NE 1/4 of the SW 1/4.
- Set a rebar, 18 inches long, 5/8 inch diameter, 15 inches in the ground, with a 3 inch aluminum cap marked:

S23  
NW-NE-SW  
1/256  
2003

Set an aluminum sign post W of the monument.

THE SUBDIVISION OF SECTION 23  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

9.980

The point for the center W-E-W 1/256 section corner of section 23.

---

From the point for the center N-NE-SW 1/256 section corner of section 23.

S. 89° 58.5' W., on the E-W center line of the NW 1/4 of the NE 1/4 of the SW 1/4 of section 23.

5.010

The NW-NE-SW 1/256 section corner of section 23.

10.020

The point for the center N-N-SW 1/256 section corner of section 23.

---

From the point for the center W 1/16 section corner of section 23.

N. 0° 16.3' W., on the N-S center line of the NW 1/4 of section 23.

9.957

Point for the center S-NW 1/64 section corner of section 23, not monumented.

19.914

Point for the NW 1/16 section corner of section 23, at intersection with the E-W center line of the NW 1/4, not monumented.

29.871

Point for the center N-NW 1/64 section corner of section 23, not monumented.

39.828

The point for the W 1/16 section corner of sections 14 and 23.

---

From the point for the center N 1/16 section corner of section 23.

S. 89° 59.8' W., on the E-W center line of the NW 1/4 of section 23.

9.974

Point for the center E-NW 1/64 section corner of section 23, not monumented.

14.961

Point for the center W-E-NW 1/256 section corner of section 23, not monumented.

19.948

The point for the NW 1/16 section corner of section 23.

29.922

Point for the center W-NW 1/64 section corner of section 23, not monumented.

THE SUBDIVISION OF SECTION 23  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

**34.909**

Point for the center W-W-NW 1/256 section corner of section 23, not monumented.

**39.896**

The point for the N 1/16 section corner of sections 22 and 23.

---

From the point for the center E-NW 1/64 section corner of section 23.

N. 0° 22.6' W., on the N-S center line of the NE 1/4 of the NW 1/4 of section 23.

**9.953**

Point for the NE-NW 1/64 section corner of section 23, at intersection with the E-W center line of the NE 1/4 of the NW 1/4, not monumented.

**19.906**

The point for the E-W 1/64 section corner of sections 14 and 23.

---

From the point for the center N-N 1/64 section corner of section 23.

N. 89° 58.9' W., on the E-W center line of the NE 1/4 of the NW 1/4 of section 23.

**9.956**

The point for the NE-NW 1/64 section corner of section 23, not monumented.

**14.934**

Point for the center W-NE-NW 1/256 section corner of section 23.

Set a rebar, 18 inches long, 5/8 inch diameter, 18 inches in the ground, with a 3 inch aluminum cap marked:

C-W-NE-NW  
1/256 S23  
2003

Set a steel fence post S of the monument.

Monument is located on a gentle NE facing slope in quaking aspen and fir.

**19.912**

The point for the center N-NW 1/64 section corner of section 23.

---

From the point for the center W-E-NW 1/256 section corner of section 23.

N. 0° 19.4' W., on the N-S center line of the SW 1/4 of the NE 1/4 of the NW 1/4 of section 23.

THE SUBDIVISION OF SECTION 23  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

**9.955**

The center W-NE-NW 1/256 section corner of section 23.

---

From the point for the center E-W 1/64 section corner of section 23.

N. 0° 22.6' W., on the N-S center line of the SE 1/4 of the NW 1/4 of section 23.

**9.953**

Point for the SE-NW 1/64 section corner of section 23, at intersection with the E-W center line of the SE 1/4 of the NW 1/4, not monumented.

**19.906**

The point for the center E-NW 1/64 section corner of section 23.

---

From the point for the center S-N 1/64 section corner of section 23.

S. 89° 58.6' W., on the E-W center line of the SE 1/4 of the NW 1/4 of section 23.

**9.992**

The point for the SE-NW 1/64 section corner of section 23.

**14.988**

Point for the center W-SE-NW 1/256 section corner of section 23, not monumented.

**19.984**

The point for the center S-NW 1/64 section corner of section 23.

---

From the point for the center W-E-W 1/256 section corner of section 23.

N. 0° 19.4' W., on the N-S center line of the SW 1/4 of the SE 1/4 of the NW 1/4 of section 23.

**9.955**

The point for the center W-SE-NW 1/256 section corner of section 23.

---

From the point for the center W-SE-NW 1/256 section corner of section 23.

N. 0° 19.4' W., on the N-S center line of the NW 1/4 of the SE 1/4 of the NW 1/4 of section 23.

**9.955**

The point for the center W-E-NW 1/256 section corner of section 23.

---

From the point for the center W-NW 1/64 section corner of section 23.

N. 0° 10.0' W., on the N-S center line of the NW 1/4 of the NW 1/4 of section 23.

THE SUBDIVISION OF SECTION 23  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

- 4.980** Point for the center S-NW-NW 1/256 section corner of section 23, not monumented.
- 9.960** Point for the NW-NW 1/64 section corner of section 23, at intersection with the E-W center line of the NW 1/4 of the NW 1/4, not monumented.
- 19.920** The point for the W-W 1/64 section corner of sections 14 and 23.

From the point for the center N-NW 1/64 section corner of section 23.

N. 89° 58.9' W., on the E-W center line of the NW 1/4 of the NW 1/4 of section 23.

- 9.956** The point for the NW-NW 1/64 section corner of section 23.
- 14.934** Point for the center W-NW-NW 1/256 section corner of section 23.

Set a rebar, 18 inches long, 5/8 inch diameter, 16 inches in the ground, with a 3 inch aluminum cap marked:

C-W-NW-NW  
1/256 S23  
2003

Set a steel fence post S of the monument.

Monument is located on a steep N facing slope in fir and quaking aspen.

- 19.912** The point for the N-N 1/64 section corner of sections 22 and 23.

From the point for the center W-W-NW 1/256 section corner of section 23.

N. 0° 06.8' W., on the N-S center line of the SW 1/4 of the NW 1/4 of the NW 1/4 of section 23.

- 4.981** Point for the SW-NW-NW 1/256 section corner of section 23, at intersection with the E-W center line of the SW 1/4 of the NW 1/4 of the NW 1/4.

Set a rebar, 18 inches long, 5/8 inch diameter, 18 inches in the ground, with a 3 inch aluminum cap marked:

SW-NW-NW  
1/256 S23  
2003

Set a steel fence post W of the monument.

THE SUBDIVISION OF SECTION 23  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

Monument is located on a N facing slope in quaking aspen.

**9.962**

The center W-NW-NW 1/256 section corner of section 23.

---

From the point for the center S-NW-NW 1/256 section corner of section 23.

N. 89° 59.6' W., on the E-W center line of the SW 1/4 of the NW 1/4 of the NW 1/4 of section 23.

**4.982**

The SW-NW-NW 1/256 section corner of section 23.

**9.964**

The S-N-N 1/256 section corner of sections 22 and 23.

---

The Subdivision of Section 24  
T. 4 S., R. 11 W., Uintah Special Meridian, Utah

---

From the 1/4 section corner of sections 24 and 25.

N. 0° 08.1' E., on the N-S center line of section 24.

**39.920**

Point for the center 1/4 section corner of section 24, at intersection with the E-W center line, not monumented.

**59.896**

Point for the center N 1/16 section corner of section 24, not monumented.

**69.884**

Point for the center N-N 1/64 section corner of section 24, not monumented.

**74.878**

Point for the center N-N-N 1/256 section corner of section 24, not monumented.

**79.872**

The 1/4 section corner of sections 13 and 24.

---

From the 1/4 section corner of section 19 and 24, on the east boundary of the township, hereinbefore described.

N. 89° 57.7' W., on the E-W center line of section 24.

**40.190**

The point for the center 1/4 section corner of section 24.

**60.242**

Point for the center W 1/16 section corner of section 24, not monumented.

**70.268**

Point for the center W-W 1/64 section corner of section 24, not monumented.

**80.294**

The 1/4 section corner of sections 23 and 24.

---

From the point for the center W 1/16 section corner of section 24.

THE SUBDIVISION OF SECTION 24  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

N. 0° 02.4' W., on the N-S center line of the NW 1/4 of section 24.

- 9.962** Point for the center S-NW 1/64 section corner of section 24, not monumented.
- 19.924** Point for the NW 1/16 section corner of section 24, at intersection with the E-W center line of the NW 1/4, not monumented.
- 24.905** Point for the center S-N-NW 1/256 section corner of section 24.  
Set a rebar, 18 inches long, 3/4 inch diameter, 18 inches in the ground, with a 3 inch aluminum cap marked:
- C-S-N-NW  
1/256 S24  
2003
- Set a steel fence post W of the monument.  
Monument is located on a gentle westerly slope in fir and aspen.
- 29.886** Point for the center N-NW 1/64 section corner of section 24, not monumented.
- 34.867** Point for the center N-N-NW 1/256 section corner of section 24.  
Set a rebar, 18 inches long, 3/4 inch diameter, 16 inches in the ground, with a 3 inch aluminum cap marked:
- C-N-N-NW  
1/256 S24  
2003
- Set a steel fence post S of the monument.  
Monument is located on a gentle northwesterly facing slope in sagebrush and fir.
- 39.848** The point for the W 1/16 section corner of sections 13 and 24.  

---
- From the point for the center N 1/16 section corner of section 24.  
S. 89° 53.3' W., on the E-W center line of the NW 1/4 of section 24.
- 10.056** Point for the center E-NW 1/64 section corner of section 24, not monumented.
- 20.112** The point for the NW 1/16 section corner of section 24.

THE SUBDIVISION OF SECTION 24  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

**25.140**

Point for the center E-W-NW 1/256 section corner of section 24.

Set a rebar, 18 inches long, 3/4 inch diameter, 18 inches in the ground, with a 3 inch aluminum cap marked:

C-E-W-NW  
1/256 S24  
2003

Set a steel fence post S of the monument.

Monument is located on a bench with a slight northwesterly slope in sagebrush and aspen.

**30.168**

Point for the center W-NW 1/64 section corner of section 24.

Set a rebar, 18 inches long, 3/4 inch diameter, 14 inches in the ground, with a 3 inch aluminum cap marked:

C-W-NW  
1/64 S24  
2003

Set a steel fence post S of the monument.

Monument is located on a bench with a slight northwesterly slope in sagebrush and aspen.

**40.224**

The point for the N 1/16 section corner of sections 23 and 24.

---

From the point for the center E-NW 1/64 section corner of section 24.

N. 0° 02.9' E., on the N-S center line of the NE 1/4 of the NW 1/4 of section 24.

**9.974**

Point for the NE-NW 1/64 section corner of section 24, at intersection with the E-W center line of the NE 1/4 of the NW 1/4, not monumented.

**14.961**

Point for the center N-NE-NW 1/256 section corner of section 24, not monumented.

**19.948**

The point for the E-W 1/64 section corner of sections 13 and 24.

---

From the point for the center N-N 1/64 section corner of section 24.

S. 89° 48.8' W., on the E-W center line of the NE 1/4 of the NW 1/4 of section 24.

THE SUBDIVISION OF SECTION 24  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

- 5.036** Point for the center E-NE-NW 1/256 section corner of section 24, not monumented.
- 10.072** The point for the NE-NW 1/64 section corner of section 24.
- 20.144** The point for the center N-NW 1/64 section corner of section 24.

From the point for the center E-NE-NW 1/256 section corner of section 24.

N. 0° 05.5' E., on the N-S center line of the NE 1/4 of the NE 1/4 of the NW 1/4 of section 24.

- 4.991** Point for the NE-NE-NW 1/256 section corner of section 24, at intersection with the E-W center line of the NE 1/4 of the NE 1/4 of the NW 1/4 of section 24.

Set a rebar, 18 inches long, 5/8 inch diameter, 14 inches in the ground, with a 3 inch aluminum cap marked:

S24  
NE-NE-NW  
1/256  
2003

Set a steel fence post W of the monument.

- 9.982** The E-E-W 1/256 section corner of sections 13 and 24.

From the point for the center N-N-N 1/256 section corner of section 24.

S. 89° 46.6' W., on the E-W center line of the NE 1/4 of the NE 1/4 of the NW 1/4 of section 24.

- 5.039** The NE-NE-NW 1/256 section corner of section 24.
- 10.078** The point for the center N-NE-NW 1/256 section corner of section 24.

From the point for the center N-NE-NW 1/256 section corner of section 24.

S. 89° 46.6' W., on the E-W center line of the NW 1/4 of the NE 1/4 of the NW 1/4 of section 24.

- 10.078** The center N-N-NW 1/256 section corner of section 24.

From the point for the center W-W 1/64 section corner of section 24.

N. 0° 07.6' W., on the N-S center line of the SW 1/4 of the NW 1/4 of section 24.

THE SUBDIVISION OF SECTION 24  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

CHAINS  
9.948

Point for the SW-NW 1/64 section corner of section 24, at intersection with the E-W center line of the SW 1/4 of the NW 1/4.

Set a rebar, 18 inches long, 5/8 inch diameter, 14 inches in the ground, with a 3 inch aluminum cap marked:

S24  
SW-NW  
1/64  
2003

Set 2x2 inch wood post N of the monument.

19.896

The center W-NW 1/64 section corner of section 24.

---

From the center S-NW 1/64 section corner of section 24.

S. 89° 57.8' W., on the E-W center line of the SW 1/4 of the NW 1/4 of section 24.

10.041

The SW-NW 1/64 section corner of section 24.

20.082

The S-N 1/64 section corner of sections 23 and 24.

---

From the center W-NW 1/64 section corner of section 24.

N. 0° 07.6' W., on the N-S center line of the NW 1/4 of the NW 1/4 of section 24.

4.974

Point for the center S-NW-NW 1/256 section corner of section 24, not monumented.

9.948

Point for the NW-NW 1/64 section corner of section 24, at intersection with the E-W center line of the NW 1/4, of the NW 1/4, not monumented.

19.896

The point for the W-W 1/64 section corner of sections 13 and 24.

---

From the point for the center N-NW 1/64 section corner of section 24.

S. 89° 48.8' W., on the E-W center line of the NW 1/4 of the NW 1/4 of section 24.

5.036

Point for the center E-NW-NW 1/256 section corner of section 24, not monumented.

10.072

The point for the NW-NW 1/64 section corner of section 24.

20.143

The point for the N-N 1/64 section corner of sections 23 and 24.

---

THE SUBDIVISION OF SECTION 24  
T. 4 S., R. 11 W., UINTAH SPECIAL MERIDIAN

## CHAINS

From the center E-W-NW 1/256 section corner of section 24.

N. 0° 05.0' W., on the N-S center line of the SE 1/4 of the NW 1/4 of the NW 1/4 of section 24.

**4.977**

Point for the SE-NW-NW 1/256 section corner of section 24, at intersection with the E-W center line of the SE 1/4 of the NW 1/4 of the NW 1/4.

Set a rebar, 18 inches long, 3/4 inch diameter, 18 inches in the ground, with a 3 inch aluminum cap marked:

SE-NW-NW  
1/256 S24  
2003

Set a steel fence post S of the monument.

Monument is located on a steep northwesterly facing slope in spruce.

**9.954**

The point for the center E-NW-NW 1/256 section corner of section 24.

From the center S-N-NW 1/256 section corner of section 24.

S. 89° 51.0' W., on the E-W center line of the SE 1/4 of the NW 1/4 of the NW 1/4 of section 24.

**5.032**

The SE-NW-NW 1/256 section corner of section 24.

**10.064**

The point for the center S-NW-NW 1/256 section corner of section 24.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

<b>Name</b>	<b>Capacity</b>
Daniel Webb	Chief Cadastral Surveyor
M. Ross Workman	Supervisory Cadastral Surveyor
Michael Thompson	Cadastral Surveyor
John Larsen	Cartographic Technician
Deborah Laughlin	Survey Technician
Tyler Trujillo	Survey Technician
Tyler Staggs	Survey Aide
Andy Lund	Survey Aide

## CERTIFICATE OF SURVEY

I **Merrill D. Cazier, Cadastral Surveyor**, hereby certify upon honor, that in pursuance of special instructions bearing the date of the **19th day of August, 2002**, I have **dependently resurveyed a portion of the south boundary (First Standard Parallel South), a portion of the east boundary, a portion of the subdivisional lines, and the subdivision of sections 13, 14, 23 and 24, in Township 4 South, Range 11 West,**

of the **Uintah Special Meridian**, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special and supplemental special instructions, the Manual of Instructions of the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

9-8-04

Date

Merrill D. Cazier

Cadastral Surveyor

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The following field notes of the **dependent resurvey of a portion of the south boundary (First Standard Parallel South), a portion of the east boundary, a portion of the subdivisional lines, and the subdivision of sections 13, 14, 23 and 24, in Township 4 South, Range 11 West, Uintah Special Meridian, Utah,**

executed by **Merrill D. Cazier, Cadastral Surveyor** having been critically examined and found correct, are hereby approved.

September 10, 2004

Date

Daniel W. Webb

(Chief Cadastral Surveyor)