

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF
A PORTION OF THE OLD WEST BOUNDARY OF THE
NAVAJO INDIAN RESEVATION,
THE SOUTH, (EIGHTH STANDARD PARALLEL SOUTH),
EAST, WEST, AND NORTH BOUNDARIES,
THE SUBDIVISIONAL LINES,
AND THE SUBDIVISION OF SECTIONS
2, 3, 8, 10, 17, 20, 30, AND 32

IN

TOWNSHIP 40 SOUTH, RANGE 24 EAST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Merrill D. Cazier
Cadastral Surveyor

Under special instructions dated and approved **April 3, 2003**, which provided for the surveys included under Group Number **957**, and assignment instructions dated **April 3, 2003**.

Survey commenced **April 7, 2003**
Survey completed **August 1, 2003**

INDEX DIAGRAM

Township 40 South, Range 24 East

28		26		25		24		23		22	
21	6	66	5	55	4	48	3	41	2	35	1 17
65		65		54		47		41		34	
20	7	64	8	54	9	46	10	40	11	34	12 16
64		63		53		46		39		33	
20	18	62	17	52	16	45	15	39	14	32	13 15
61		60		52		45		38		32	
19	19	60	20	51	21	44	22	37	23	31	24 15
59		59		50		44		37		31	
19	30	57	29	50	28	43	27	36	26	30	25 14
57		56		49		42		36		30	
18	31	56	32	48	33	42	34	35	35	29	36 13
12		11		10		9		9		7	

Old Navajo Indian Reservation Boundary.....	Page 2
The Subdivision of Section 2.....	Page 66
The Subdivision of Section 3.....	Page 67
The Subdivision of Section 8.....	Page 68
The Subdivision of Section 10.....	Page 68
The Subdivision of Section 17.....	Page 69
The Subdivision of Section 20.....	Page 70
The Subdivision of Section 30.....	Page 71
The Subdivision of Section 32.....	Page 73

TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of a portion of the old west boundary of the Navajo Indian Reservation, the south, (Eighth Standard Parallel South), east, west, and north boundaries, the subdivisional lines, and the subdivision of sections 2, 3, 8, 10, 17, 20, 30, and 32, in T. 40 S., R. 24 E., Salt Lake Meridian, Utah.

History of Surveys

SURVEYED BY	RETR. OR RESURVEYED BY
INDIAN RESERVATION BOUNDARY	
Portion R. Yundt	1942-1944
SOUTH BOUNDARY (EIGHTH STANDARD PARALLEL SOUTH)	
All A.D. Ferron	1884
Portion	Page & Lentz 1899
Portion	R.C. Yundt & A. Nelson 1953
EAST BOUNDARY	
All A.D. Ferron	1884
All	Page & Lentz 1899
WEST BOUNDARY	
All A.D. Ferron	1884
Portion	Page & Lentz 1899
Portion	R.C. Yundt & A. Nelson 1953
Portion	Donald A. Buhler 1980
NORTH BOUNDARY	
All A.D. Ferron	1884
All	Page & Lentz 1899
Portion	D.B. Miller & J.C. Thoma 1912
MEANDERS (NORTH BANK OF THE SAN JUAN RIVER)	
All Page & Lentz	1899
SUBDIVISION	
Portion Page & Lentz	1899

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 957, dated April 3, 2003.

TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS The true meridian direction and length of all lines were determined by Global Positioning System (GPS) utilizing Real-Time Kinematics (RTK) observations using the Trimble 5700 model receiver.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and their calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations, post processed by National Geodetic Survey, Online Positioning User Service, (OPUS), Utilizing Continuously Operating Reference Stations; (CORS) FREDONIA, CARBON COUNTY, and AZTEC. The NAD 83 (CORS96) geographic position of the corner of Townships 39 and 40 South, Ranges 24 and 25 East is as follows:

Latitude: 37° 20' 43.704" N. Longitude: 109° 13' 21.277" W.

Elevation: 5044 ft. NAD 1983

CHAINS

Dependent Resurvey of a Portion of the Old West Boundary
of the Navajo Indian Reservation
Township 40 South, R. 24 E., Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by
Robert C. Yundt in 1942-1944

Beginning at the intersection on the north boundary of Township 40 South, Range 24 East between the 1/4 section corner of section 3 only and the corner of sections 3 and 4 only with the old west boundary of the Navajo Indian Reservation between Angle Points 7 and 8, not monumented.

From which Angle Point 7 bears N. 34° 29.5' E., 14.733 chains distance, monumented with a stainless steel post, 2 1/2 inches diameter, set and marked as described in the concurrent resurvey of Township 39 South, Range 24 East.

S. 34° 29.5' W., along the 3rd mile of the reservation boundary in section 3.

12.328 Angle Point 8, monumented with an iron post, 1 inch diameter, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1942 survey.

Corner falls on the West bank of Rock Canyon Wash.

**DEPENDENT RESURVEY OF A PORTION OF THE OLD WEST BOUNDARY
OF THE NAVAJO INDIAN RESERVATION
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH.**

CHAINS

S. 34° 30.3' W., on the reservation boundary, in section 3.

19.007 Intersect the section line of sections 3 and 4, not monumented.

36.538 Angle Point 9, monumented with an iron post, 1 inch diameter, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1942 survey.

S. 45° 13.8' W., along the 3rd mile of the reservation boundary in section 4.

2.221 Mile Post 3, identical to Angle Point 10, monumented with an iron post, 3 inches diameter, projecting 18 inches above ground, with brass cap marked as described in the official record of the 1942 survey.

S. 55° 00.4' W., along the 4th mile of the reservation boundary in section 4.

4.500 Point for Angle Point 11, at proportionate distance; there is no remaining evidence of the original Angle Point.

Set a brass tablet, 3 ¼ inch diameter, with a 3 ½ inch stem, flush with sandstone, over a magnet, in cement bond, into a drill hole on solid rock, marked:

T40SR24E
S4
NIR
AP11
2003

N. 87° 59.6' W., along the reservation boundary in section 4.

6.700 Angle Point 12, at proportionate distance: there is no remaining evidence of the original Angle Point.

Set a brass tablet, 3 ¼ inch diameter, with a 3 ½ inch stem, flush with sandstone, over a magnet, in cement bond, into a drill hole on solid rock, marked:

T40SR24E
AP12 S4
NIR
2003

Raise a mound of stone, 3 ft. base, 2 ft. high, North of the corner.

**DEPENDENT RESURVEY OF A PORTION OF THE OLD WEST BOUNDARY
OF THE NAVAJO INDIAN RESERVATION
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH.**

CHAINS

N. 63° 29.6' W., along the reservation boundary in section 4.

- 9.498** Angle Point 13, monumented with an iron post, 1 inch diameter, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1942 survey.

N. 86° 45.1' W., along the reservation boundary in section 4.

- 35.646** Angle Point 14, monumented with an iron post, 1 inch diameter, projecting 18 inches above ground, with brass cap marked as described in the official record of the 1942 survey.

S. 35° 29.3' W., along the reservation boundary in section 4.

- 14.986** Angle Point 15, monumented with an iron post, 1 inch diameter, projecting 20 inches above ground, with brass cap marked as described in the official record of the 1942 survey.

Point falls on south sloping ledge.


S. 70° 28.3' W., along the reservation boundary in section 4.

- 4.895** Intersect the section line of sections 4 and 5, not monumented.

- 8.607** Mile Post 4, identical to Angle Point 16, monumented with a mound of stone.

At the corner point (center of mound)

Set a stainless steel post, 30 inches long, 2 ½ inches in diameter, 6 inches in ground, to solid rock, and in a mound of stone, 6 ft. base to top of brass cap marked:



Located 30 lks. W. of ledge.

Deposit a Deep 1 magnet at the base of the steel post.

S. 66° 59.4' W., along the 5th mile of the reservation boundary in section 5.

- 51.417** Angle Point 17, monumented with an iron post, 1 inch diameter, projecting 20 inches above ground, with brass cap marked as described in the official record of the 1942 survey.

**DEPENDENT RESURVEY OF A PORTION OF THE OLD WEST BOUNDARY
OF THE NAVAJO INDIAN RESERVATION
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH.**

CHAINS

S. 29° 42.1' W., along the reservation boundary in section 5.

- 7.988** Intersect the section line of sections 5 and 8, not monumented.
- 27.850** Angle Point 18, monumented with an iron post, 1 inch diameter, projecting 22 inches above ground, with brass cap marked as described in the official record of the 1942 survey.

S. 64° 04.0' W., along the reservation boundary in section 8.

- 0.700** Mile Post 5, identical to Angle Point 19, found remnants of original mound of stone, and found original iron post, 3 inch diameter, at bottom of 30 ft. cliff, with brass cap marked as described in the official record of the 1942 survey.

At corner point (center of mound)

Reset the iron post on solid sandstone, and in a mound of stone, 4 ft. base to top of brass cap.

Deposit a Deep 1 magnet at the base of the iron post.


S. 64° 13.8' W, along the 6th mile of the reservation boundary in section 8.

- 15.384** Angle Point 20, monumented with an iron post, 1 inch diameter, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1942 survey.

S. 38° 44.2' W., along the reservation boundary in section 8.

- 0.838** Intersect the section line of sections 7 and 8, not monumented.
- 13.797** Point for Angle Point 21, at proportionate distance: there is no remaining evidence of the original Angle Point.

Set stainless steel post, 30 inches long, 2 ½ inches in diameter, 18 inches in ground, to solid rock, and in a mound of stone, 3ft. base to top of brass cap marked:



Deposit a Deep 1 magnet at base of post.

Raise a mound of stone along side.

**DEPENDENT RESURVEY OF A PORTION OF THE OLD WEST BOUNDARY
OF THE NAVAJO INDIAN RESERVATION
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH.**

CHAINS

S. 30° 29.1' W., along the reservation boundary in section 7.

50.790 Mile Post 6, identical to Angle Point 22, found sandstone with "X" marked on top.

At the corner point,

Set stainless steel post, 30 inches long, 2 ½ inches in diameter, on solid rock over "X", with brass cap marked:

```

T40SR24E
S7 / AP22
    / NIR
    / MP6
    / 2003
  
```

Deposit a Deep 1 magnet at base of post.

Raise a mound of stone, 4' base to top of brass cap.

S. 30° 29.0' W., along the 7th mile of the reservation boundary in section 7.

1.195 Intersect the section line of sections 7 and 18, not monumented.

40.103 Angle Point 23, monumented with an iron post, 1 inch diameter, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1942 survey.

S. 9° 42.0' E., along the reservation boundary in section 18.

14.510 Point for Angle Point 24, at proportionate distance; there is no remaining evidence of the original Angle Point.

Set a brass tablet, 3 ¼ inch diameter, with a 3 ½ inch stem, flush with sandstone, over a magnet, in cement bond, into a drill hole on solid rock, marked:

```

T40SR24E
S18 / AP24
    / NIR
    / 2003
  
```

Corner falls on a flat southwest facing boulder, in an outcropping of boulders.

S. 69° 33.0' W., along the reservation boundary in section 18.

**DEPENDENT RESURVEY OF A PORTION OF THE OLD WEST BOUNDARY
OF THE NAVAJO INDIAN RESERVATION
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH.**

CHAINS

- 13.810** Angle Point 25, monumented with an iron post, 1 inch diameter, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1942 survey.
-
- S. 58° 09.4' W., along the reservation boundary in section 18.
- 5.898** Angle Point 26, monumented with an iron post, 1 inch diameter, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1942 survey.
-
- S 3° 15.5' W., along the reservation boundary in section 18.
- 5.586** Mile post 7, identical to Angle Point 27, monumented with an iron post, 1 inch diameter, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1942 survey.
-
- S 3° 15.2' W., along the 8th mile of the reservation boundary in section 18.
- 18.755** Intersect the section line of sections 18 and 19, not monumented.
- 29.888** Angle Point 28, monumented with an iron post, 1 inch diameter, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1942 survey.
-
- S. 28° 58.4' W., along the reservation boundary in section 19.
- 16.113** Intersect the west boundary of T.40 S., R.24 E., not monumented.
- 40.230** Angle Point 29, monumented with an iron post, 1 inch diameter, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1942 survey.

Dependent Resurvey of the South Boundary,
(Eighth Standard Parallel South),
Township 40 South, Range 24 East, Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by A.D. Ferron in 1884,
and the resurvey Executed by Page & Lentz in 1899,
and R.C. Yundt & A. Nelson in 1953

From the standard corner of Township 40 South, Ranges 24 and 25 East, monumented with a 3/8 inch rebar. This is harmoniously related with identified original corners in the area, and is accepted as the best available evidence of the original corner position.

**DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
(EIGHTH STANDARD PARALLEL SOUTH),
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH.**

CHAINS

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 24 inches in the ground, with brass cap marked:

SC
T40S
R24E R25E
<u>S36 S31</u>
2003

Deposit a Deep 1 magnet at base of post.

Place rebar inside of post.

S. 89° 56.1' W., on the south boundary of section 36.

- 39.916** The standard ¼ section corner of section 36 only, monumented with a sandstone 18 X 10 X 6 inches, set in a mound of stone, with ¼ plainly marked on the north face.

At the corner point,

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 18 inches in ground, to solid rock, and in a collar of stone with brass cap marked:

SC
T40S R24E
1/4 S36
<hr style="width: 50%; margin: 0 auto;"/>
T41S R24E
2003

Deposit a Deep 1 magnet at base of post.

N. 89° 54.3' W., beginning new measurement.

- 40.034** The standard corner of sections 35 and 36 only, monumented with a sandstone 18 X 10 X 4 inches, set in a mound of stone, plainly marked with "SC" on the west, 5 grooves on south, and 1 groove on west faces, ½ inch rebar alongside.

At the corner point,

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, on solid rock, and in a mound of stone, 6 ft. base to top of brass cap marked:

SC
T40S R24E
<u>S35 S36</u>
2003

**DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
(EIGHTH STANDARD PARALLEL SOUTH),
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH.**

CHAINS

Deposit a Deep 1 magnet at base of post.

Place rebar face down, inside post.

Place 4' X 1/2" fiberglass rod next to corner.

N. 89° 59.0' W., on the south boundary of section 35.

- 39.931** Point for the standard ¼ section corner of section 35 only, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, with brass cap marked:

SC
T40S R24E
1/4 S35
T41S R24E
2003

Deposit a Deep 1 magnet at base of post.

- 79.862** The standard corner of sections 34, and 35 only, monumented with a sandstone 18 X 12 X 4 inches, firmly set, in a mound of stone, and no visible markings.

At the corner point,

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 10 inches in ground, to solid rock, and in a mound of stone, 4 ft. base to top of brass cap marked:

SC
T40S R24E
S34 | S35
T41S R24E
2003

Deposit a Deep 1 magnet at base of post.

Corner falls on steep easterly slope.

N. 89° 59.0' W., on the south boundary of section 34.

- 39.931** Point for the standard ¼ section corner of section 34 only, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, with brass cap marked:

**DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
(EIGHTH STANDARD PARALLEL SOUTH),
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH.**

CHAINS

SC
T40S R24E
1/4 S34
T41S R24E
2003

Deposit a Deep 1 magnet at base of post.

Corner falls 30 feet south of road.

- 79.685** Point selected for the witness corner to the standard corner of sections 33 and 34 only.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 6 inches in ground, to solid rock, and in a mound of stone, 4 ft. base to top of brass cap marked:

WC
SC
T40S R24E
S33 | S34
2003

Deposit a Deep 1 magnet at base of post.

Corner falls on top of 8 foot ledge.

- 79.862** True point for the standard corner of sections 33 and 34 only, at proportionate distance; there is no remaining evidence of the original corner, point falls on face of 8 ft. ledge where it is impracticable to establish a permanent monument.

N. 89° 59.0' W., on the south boundary of section 33.

- 39.931** True point for the standard ¼ section corner of section 33 only, at proportionate distance; there is no remaining evidence of the original corner, point falls on south facing cliff where it is impracticable to establish a permanent monument.

- 42.902** Point selected for the witness corner to the standard ¼ section corner of section 33 only.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, with brass cap marked:

WC
SC
T40S R24E
1/4 S33
T41S R24E
2003

Deposit a Deep 1 magnet at base of post.

**DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
(EIGHTH STANDARD PARALLEL SOUTH),
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH.**

CHAINS

- 79.852** The standard corner of sections 32 and 33 only, monumented with a wooden hub in center of mound of stone, and is accepted as the best available evidence of the original corner position.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 14 inches in ground, to solid rock, and in a mound of stone, 3 ft. base to top of brass cap marked:

SC
T40S R24E
S32 | S33
2003

Deposit a Deep 1 magnet at base of post.

N. 89° 56.8' W., on the south boundary of section 32.

- 20.543** Point for the standard E 1/16 section corner of section 32 only.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 30 inches in ground, with brass cap marked:

SC
T40S R24E
E 1/16 S32
T41S R24E
2003

I received permission from resident to set stainless steel post flush with ground in yard.

Corner falls 2 ft. south of E-W fence, and 13 ft. S24°W from SW corner of house.

- 41.086** The standard ¼ section corner of section 32 only, monumented with an iron post, 2 ½ inches diameter, projecting 8 inches above ground, with brass cap marked:

SC
1/4 S32
1953

Corner falls 1 1/2 ft. south of a 6 ft. chain link fence corner, with 3 strains of barbed wire on top. Fences bear north and west.


S. 89° 57.3' W., beginning new measurement.

**DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
(EIGHTH STANDARD PARALLEL SOUTH),
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH.**

CHAINS

- 13.650** Point selected for the witness meander corner of sections 5 and 32, on the right bank of the San Juan River, there is no remaining evidence of the 1953 iron post.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 18 inches in ground, to solid rock, and in a mound of stone, 3 ft. base to top of brass cap marked:



- 24.750** Point for the original meander corner of sections 5 and 32, at proportionate distance, falls in the San Juan River, not monumented.
- 40.000** Point for the standard corner of sections 31 and 32 only, falls in San Juan River, not monumented.

S. 89° 57.3' W., on the south boundary of section 31.

- 10.400** Point for the 1953 reference monument, at proportionate distance, there is no remaining evidence of the 1953 iron post.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, with brass cap marked:

SC
T40S R24E
S31 REFR PT
T41S R24E
2003

- 40.000** The standard ¼ section corner of section 31 only, monumented with an iron post, 2 ½ inches diameter, projecting 4 inches above ground, with brass cap marked:

SC
1/4 S31
1953

Place a steel fence post west of corner.

S. 89° 57.0' W., beginning new measurement

- 38.702** The standard corner of Township 40 South, Ranges 23 and 24 East, monumented with an iron post, 2 ½ inches diameter, projecting 14 inches above ground, with brass cap marked:

**DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
(EIGHTH STANDARD PARALLEL SOUTH),
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH.**

CHAINS

T40S	
R23E	R24E
S36	S31
1953	

Point falls on North rim of pit in an E-W 4 ft. high fence line with 1 strand of barb wire.

Dependent Resurvey of the East Boundary,
Township 40 South, Range 24 East, Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by A.D. Ferron in 1884,
and the Resurvey Executed by Page & Lentz in 1899

From the standard corner of Township 40 South, Ranges 24 and 25 East, hereinbefore described.

N. 0° 01.9' W., between sections 31 and 36.

40.140 The ¼ section corner of sections 31 and 36, monumented with a sandstone, 17 X 14 X 6 inches, firmly set and plainly marked ¼ on the west face.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 24 inches in ground, with brass cap marked:

T40S	
R24E	R25E
1/4	
S36	S31
2003	

Raise a mound of stone 3 ft. base, 1 ½ ft. high, west of corner.

Deposit the marked stone alongside the corner.

Deposit a Deep 1 magnet at base of post.

N. 0° 18.2' E., beginning new measurement.

40.051 The corner of sections 25, 30, 31, and 36, monumented with a sandstone, 18 X 6 X 4 inches, firmly set, in a mound of stone, plainly marked with 1 notch on south, and 3 notches on north edges.

At the corner point

**DEPENDENT RESURVEY OF THE EAST BOUNDARY,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH.**

CHAINS

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 10 inches in ground, to solid rock, and in a mound of stone, 3 ft. base to top of brass cap marked:

T40S
R24E R25E
S25 | S30
S36 | S31
2003

Deposit the marked stone alongside the corner.

Deposit a Deep 1 magnet at base of post.

N. 0° 23.6' W., between sections 25 and 30.

- 39.633** The ¼ section corner of sections 25, and 30, monumented with a 5 ft. steel fence post, projecting 18 inches above ground, in a mound of stone. This is harmoniously related with other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, and in a collar of stone, 3 ft. base to top of brass cap marked:

T40S
R24E R25E
1/4
S25 | S30
2003

Set the steel fence post alongside.

Deposit a Deep 1 magnet at base of post.

N. 0° 15.1' E., beginning new measurement.

- 39.347** Point for the corner of sections 19, 24, 25, and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, with brass cap marked:

T40S
R24E R25E
S24 | S19
S25 | S30
2003

Deposit a Deep 1 magnet at base of post.

**DEPENDENT RESURVEY OF THE EAST BOUNDARY,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH.**

CHAINS

Raise a mound of stone 3 ft. base, 2 ft. high, west of corner.

Corner falls in river bed.

N. 0° 15.1' E., between sections 19 and 24.

39.347 Point for the ¼ section corner of sections 19, and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, and in a collar of stone, with brass cap marked:

T40S
R24E R25E
1/4
S24 | S19
2003

Deposit a Deep 1 magnet at base of post.

78.694 The corner of sections 13, 18, 19, and 24, monumented with a sandstone, 17 X 12 X 6 inches, firmly set, in a mound of stone, dimly marked 3 notches on south edge.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 18 inches in ground, to solid rock, and in a mound of stone, 4 ft. base to top of brass cap marked:

T40S
R24E R25E
S13 | S18
S24 | S19
2003

Deposit a Deep 1 magnet at base of post.

Deposit marked stone alongside.

N. 0° 16.8' E., between sections 13 and 18.

41.120 Point for the ¼ section corner of sections 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, with brass cap marked:

**DEPENDENT RESURVEY OF THE EAST BOUNDARY,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH.**

CHAINS

T40S
R24E R25E
1/4
S13 | S18
2003

Deposit a Deep 1 magnet at base of post.

- 82.240** The corner of sections 7, 12, 13, and 18, monumented with a sandstone, 20 X 7 X 8 inches, firmly set, in a mound of stone, plainly marked with 4 notches on south, and 2 on north edges.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, and in a collar of stone, with brass cap marked:

T40S
R24E R25E
S12 | S7
S13 | S18
2003

Deposit a Deep 1 magnet at base of post.

Deposit marked stone alongside in a mound of stone.

N. 0° 37.5' W., between sections 7 and 12.

- 39.762** Point for the ¼ section corner of sections 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, with brass cap marked:

T40S
R24E R25E
1/4
S12 | S7
2003

Deposit a Deep 1 magnet at base of post.

- 79.524** The corner of sections 1, 6, 7, and 12, monumented with a sandstone, 15 X 8 X 4 inches, firmly set, in a mound of stone, and no visible markings, with ½ inch rebar alongside.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, with rebar inside post, and brass cap marked:

**DEPENDENT RESURVEY OF THE EAST BOUNDARY,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH.**

CHAINS

T40S
R24E R25E
S1 | S6
S12 | S7
2003

Deposit a Deep 1 magnet at base of post.

Deposit unmarked stone alongside post.

Place rebar face down, inside post.

N. 0° 03.2' W., between sections 1 and 6.

- 39.872** The ¼ section corner of sections 1 and 6, monumented with a sandstone, 18 X 12 X 3 inches, firmly set, in a mound of stone, plainly marked ¼ on west face.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, and in a collar of stone, with brass cap marked:

T40S
R24E R25E
1/4
S1 | S6
2003

Deposit a Deep 1 magnet at base of post.

Deposit marked stone alongside post.

N. 0° 10.0' E., beginning new measurement.

- 40.116** The corner of Townships 39 and 40 South, Ranges 24 and 25 East, monumented with a sandstone, 28 X 16 X 9 inches, in a scattered mound of stone, marks have been obliterated.

At the corner point

Set a brass tablet, 3 ¼ inch diameter, with a 3 ½ inch stem, flush with sandstone, over a magnet, in cement bond, into a drill hole on solid rock, marked:

T39S
R24E R25E
S36 | S31
S1 | S6
T40S
2003

**DEPENDENT RESURVEY OF THE EAST BOUNDARY,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH.**

CHAINS

Deposit marked stone in a mound of stone, 3 ft. base, 2 ft. high, to the north.

Dependent Resurvey of the West Boundary,
Township 40 South, Range 24 East,
Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by A.D. Ferron in 1884,
and the Resurvey Executed by Page & Lentz in 1899,
R.C. Yundt & A. Nelson in 1953, and D. Buhler in 1980

From the standard corner of Township 40 South, Ranges 23 and 24 East, hereinbefore described.

N. 0° 00.8' W., between sections 31 and 36.

- 40.011** The ¼ section corner of sections 31 and 36 only, monumented with an iron post, 2 ½ inches diameter, firmly set, in collar of stones, with brass cap marked:

1/4
S36 | S31
1953

N. 0° 00.5' W., beginning new measurement.

- 36.562** Point for the 1953 meander corner, at proportionate distance, not monumented.
- 36.812** The witness corner to the meander corner on the right bank of the San Juan river, monumented with an iron post, 2 ½ inches diameter, projecting 3 inches above ground, in collar of stone, with brass cap marked:

T40S
R23E R24E
S36 | S31
WC MC
1953

- 40.012** The corner of sections 25, 30, 31, and 36, monumented with an iron post, 2 ½ inches diameter, projecting 4 inches above ground, with brass cap marked:

T40S
R23E R24E
NIRAP 33
S25 | S30
S36 | S31
1942

**DEPENDENT RESURVEY OF THE WEST BOUNDARY,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

N. 0° 01.6' W., between sections 25 and 30.

- 40.003** The ¼ section corner of sections 25 and 30, which is also the southwest corner of allotment #033380, monumented with an iron post, 2 ½ inches diameter, projecting 12 inches above ground, with mound of stone to west, and brass cap marked:

1/4
S25 | S30
1942

Place a steel fence post alongside.

Add 380 to NE quadrant of cap.

N. 0° 00.2' E., beginning new measurement.

- 39.891** The corner of sections 19, 24, 25, and 30, which is also the northwest corner of allotment #033380, monumented with an iron post, 2 ½ inches diameter, projecting 4 inches above ground, with mound of stone to west, and brass cap marked:

T40S
R23E R24E
S24 | S19
S25 | S30
1980

Add 380 to SE quadrant of cap.

N. 0° 03.3' E., between sections 19 and 24.

- 39.997** The ¼ section corner of sections 19 and 24, monumented with a sandstone, 20 X 10 X 6 inches, with no visible markings.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 10 inches in ground, to solid rock, and in a mound of stone, 4 ft. base to top of brass cap marked:

T40S
R23E R24E
1/4
S24 | S19
2003

Deposit a Deep 1 magnet at base of post

Deposit sandstone alongside.

N. 0° 07.2' E., beginning new measurement.

**DEPENDENT RESURVEY OF THE WEST BOUNDARY,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

15.067 Intersect the old west boundary of the Navajo Indian Reservation between Angle Point 28 and Angle Point 29, not monumented.

40.297 The corner of sections 13, 18, 19, and 24, monumented with an iron post, 2 ½ inches diameter, firmly set, in a mound of stone, with brass cap marked:

T40S
R23E R24E
S13 | S18
S24 | S19
1980

Corner falls on top of 30 ft. cliff running N-S.

N. 0° 00.8' W., between sections 13 and 18.

40.032 The ¼ section corner of sections 13 and 18, monumented with an aluminum post, 2 ½ inches diameter, projecting 4 inches above ground, firmly set, in a mound of stone, with aluminum cap marked:

T40S
R23E R24E
1/4
S13 | S18
1980

N. 0° 00.1' W., beginning new measurement.

40.030 Point for the corner of sections 7, 12, 13, and 18, determined latitudinally at record distance from the south using the 1980 resurvey, and longitudinally by extension of fences to the north and south.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, with brass cap marked:

T40S
R23E R24E
S12 | S7
S13 | S18
2003

Deposit a Deep 1 magnet at base of post.

N. 0° 05.7' E., between sections 7 and 12.

40.093 Point for the ¼ section corner of sections 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF THE WEST BOUNDARY,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a brass tablet, 3 ¼ inch diameter, with a 3 ½ inch stem, flush with a 15 X 25 ft. sandstone, over a magnet, in cement bond, into a drill hole, marked:

T40S
R23E R24E
1/4
S12 | S7
2003

- 80.186** The corner of sections 1, 6, 7, and 12, monumented with a sandstone, 23 X 10 X 6 inches, dimly marked 1 notch on north, and 5 notches on south edges.

At the corner point

Set a brass tablet, 3 ¼ inch diameter, with a 3 ½ inch stem, flush with a sandstone, over a magnet, in cement bond, into a drill hole on solid rock, marked:

T40S
R23E R24E
S1 | S6
S12 | S7
2003

Raise a mound of stone 3 ft. base, 1 ½ ft. high, west of corner.

Deposit marked stone in mound of stone.

Corner falls on a sandstone outcropping.

N. 0° 03.8' E., between sections 1 and 6.

- 39.509** The ¼ section corner of sections 1 and 6, monumented with a sandstone, 17 X 16 X 6 inches, firmly set and plainly marked ¼ on west face.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 16 inches in ground, to solid rock, and in a mound of stone, 3 ft. base to top of brass cap marked:

T40S
R23E R24E
1/4
S1 | S6
2003

Deposit a Deep 1 magnet at base of post.

Deposit marked stone alongside.

**DEPENDENT RESURVEY OF THE WEST BOUNDARY,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

N. 0° 06.3' E., beginning new measurement.

- 40.016** The corner of Townships 39 and 40 South, Ranges 23 and 24 East, monumented with a sandstone, 20 X 12 X 6 inches, firmly set and plainly marked with 6 notches on North, South, East, and West edges, along with scribing.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 26 inches in ground, with brass cap marked:

T39S
R23E R24E
S36 | S31
S1 | S6
T40S
2003

Deposit a Deep 1 magnet at base of post.

Deposit marked stone alongside.

Raise a mound of stone, 4 ft. base, 2 ft. high, south of corner.

Dependent Resurvey of the North Boundary,
Township 40 South, Range 24 East,
Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by A.D. Ferron in 1899,
and the Resurvey Executed by Page & Lentz in 1899,
and D.B. Miller & J.C. Thoma in 1912

From the corner of Townships 39 and 40 South, Ranges 24 and 25 East, hereinbefore described.

N. 89° 34.9' W., between sections 1 and 36.

- 40.260** The ¼ section corner of sections 1 and 36 monumented with a sandstone 14 X 12 X 4 inches, firmly set, in a mound of stone, plainly marked ¼ on west face.

At the corner point

Set a stainless steel post, 30 inches long, 2½ inches diameter, 20 inches in ground, in a collar of stone, with brass cap marked:

T39S R24E
S 36
1/4 —————
S 1
2003

**DEPENDENT RESURVEY OF THE NORTH BOUNDARIES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Deposit marked stone alongside.

Raise a mound of stone alongside.

Deposit a Deep 1 magnet at base of post.

Corner is located on top on north facing bench, in scattered sage brush, 33 links distance, south of a two track road.

N. 89° 59.5' W., beginning new measurement.

- 40.110** The corner of sections 1, 2, 35, and 36, monumented with a sandstone 19 X 12 X 6 inches, no visible marks, firmly set, with a mound of stone to the west.

At the corner point

Set a stainless steel post, 30 inches long, 2½ inches diameter, 4 inches in ground, to solid rock, and in a mound of stone, 5 ft. base to top of brass cap marked:

T39S	R24E
S35	S36
S2	S1
T 40 S	
2003	

Deposit a Deep 1 magnet at base of post.

Deposit marked stone alongside.

N. 89° 51.1' W., between sections 2 and 35.

- 39.898** Point for the ¼ section corner of sections 2 and 35, at proportionate distance; there is no remaining evidence of the original corner,

Set a stainless steel post, 30 inches long, 2½ inches diameter, 22 inches in ground, with brass cap marked:

T39S	R24E
S35	
1/4	_____
S2	
T40S R24E	
2003	

Deposit a Deep 1 magnet at base of post.

Corner is located in the Montezuma creek wash, in dense tamarisk.

**DEPENDENT RESURVEY OF THE NORTH BOUNDARIES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

79.796 The corner of sections 2, 3, 34, and 35 monumented with a sandstone 20 X 8 X 8 inches, firmly set and dimly marked 4 notches on south, and 2 notches on east edges, ½ inch rebar alongside.

At the corner point

Set a stainless steel post, 30 inches long, 2½ inches diameter, 26 inches in ground, with brass cap marked:

T39S	R24E
S34	S35
S3	S2
T40S	
2003	

Deposit a Deep 1 magnet at base of post.

Deposit marked stone and rebar alongside.

Raise a mound of stone 2 ft. base, 1 ft. high, to the west.

Corner is located 13 links distance, west of a two track road bearing NE - SW.

N. 89° 58.8' W., on the north boundary of section 3.

39.910 Point for the ¼ section corner of section 34 only, T. 39 S., R. 24 E., at proportionate distance; there is no remaining evidence of the original corner,

Set a stainless steel post, 30 inches long, 2½ inches diameter, 8 inches in ground, to solid rock, and in a mound of stone, 5 ft. base to top of brass cap marked:

T39S	R24E
1/4	S34
T40S	
2003	

Deposit a Deep 1 magnet at base of post.

Corner is located on flat mesa bench in scattered sage and boulders 1 chain distance, south of an old dozed road.

40.270 Point for the ¼ section corner of section 3 only, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2½ inches diameter, 16 inches in ground, to solid rock, and in a mound of stone, 3 ft. base to top of brass cap marked:

**DEPENDENT RESURVEY OF THE NORTH BOUNDARIES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

T39S
1/4 ———
S3
T40S R24E
2003

Deposit a Deep 1 magnet at base of post.

Corner is located on flat mesa bench in scattered sage and boulders 1 chain distance, south of an old dozed road.

62.456 Intersect the old west boundary of the Navajo Indian Reservation between Angle Point 7 and Angle Point 8, not monumented.

79.820 Point for the corner of sections 33 and 34, T. 39 S., R. 24 E., at proportionate distance; there is no remaining evidence of the original corner,

Set a stainless steel post, 30 inches long, 2½ inches diameter, 6 inches in ground, to solid rock, and in a mound of stone, 6 ft. base to top of brass cap marked:

T39S R24E
S33 | S34
———
T40S
2003

Deposit a Deep 1 magnet at base of post.

Corner is located on steep east slope in scatted sage brush and black rock boulders.

80.530 Point for the corner of sections 3 and 4, only at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2½ inches diameter, 19 inches in ground, to solid rock, and in a mound of stone, 3 ft. base to top of brass cap marked:

T39S
S4 | S3
———
T40S | R24E
2003

S. 89° 53.2' W., on the north boundary of section 4.

39.428 Point for the ¼ section corner of section 33 only, T. 39 S., R. 24 E. at proportionate distance; there is no remaining evidence of the original corner,

Set a stainless steel post, 30 inches long, 2½ inches diameter, 4 inches into a crack between two rocks, and in a mound of stone, 4 ft. base to top of brass cap marked:

**DEPENDENT RESURVEY OF THE NORTH BOUNDARIES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

T39S R24E
S33
1/4 _____
T40S
2003

Deposit a Deep 1 magnet at base of post.

Corner is located on an east slope 15 links distance from a sink hole to the NE.

- 39.606** Point for the $\frac{1}{4}$ section corner of section 4 only, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, $2\frac{1}{2}$ inches diameter, 5 inches in ground, to solid rock, and in a mound of stone, 4 ft. base to top of brass cap marked:

T39S

1/4 S4
T40S R24E
2003

Deposit a Deep 1 magnet at base of post.

Corner is located on an east slope.

- 79.212** The corner of sections 4 and 5, monumented with a sandstone 24 X 20 X 2 inches, plainly marked with 4 notches on the East and 2 notches on the West edges, firmly set, in a mound of stone.

At the corner point

Set a stainless steel post, 30 inches long, $2\frac{1}{2}$ inches diameter, 24 inches in ground, with brass cap marked:

T39S

S5 | S4
T40S R24E
2003

Deposit a Deep 1 magnet at base of post.

Deposit marked stone alongside.

Raise a mound of stone 4 ft. base, 2 ft. high to the south.

Corner is located South, 45 links distance, from a wash course SE - NW.

S. $89^{\circ}57.6'$ W., on the north boundary of section 5.

- 0.354** The corner of sections 32 and 33 only, monumented with a sandstone 18 X 12 X 4 inches, dimly marked with 3 visible notches on the East edge, loosely set in a mound of stone.

**DEPENDENT RESURVEY OF THE NORTH BOUNDARIES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

At the corner point

Set a stainless steel post, 30 inches long, 2½ inches diameter, 18 inches in ground, to solid rock, and in a mound of stone, 4 ft. base to top of brass cap marked:

T39S	R24E
S32	S33

T40S	
2003	

Deposit a Deep 1 magnet at base of post.

- 39.996** The ¼ section corner of section 32 only, T. 39 S., R. 24 E., monumented with a sandstone, 14 X 10 X 6 inches, firmly set and plainly marked with ¼ on south face, in a scattered mound of stone.

Set a stainless steel post, 30 inches long, 2½ inches diameter, 10 inches in ground, to solid rock, and in a mound of stone, 4 ft. base to top of brass cap marked:

T39S	R24E
	S32
1/4	-----
	T40S
	2003

Deposit a Deep 1 magnet at base of post.

Corner is located east, 30 links distance from a drainage course N - S.

- 40.924** Point for the ¼ section corner of section 5 only, at proportionate distance; based on the irregular boundary adjustment, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2½ inches diameter, 20 inches in ground, and in a collar of stone, with brass cap marked:

	T39S
1/4	-----
	S5
	T40S R24E
	2003

Deposit a Deep 1 magnet at base of post.

S. 89° 47.6' W., beginning new measurement.

- 38.436** The corner of sections 5 and 6 only, at proportionate distance; based on the irregular boundary adjustment, there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF THE NORTH BOUNDARIES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel post, 30 inches long, 2½ inches diameter, 6 inches in ground, to solid rock, and in a mound of stone, 4 ft. base to top of brass cap marked:

T39S	
S5	S6
T40S	R24E
2003	

Deposit a Deep 1 magnet at base of post.

Place a steel fence post alongside.

Corner is located on gradual east slope.

N. 89° 45.3' W., on the north boundary of section 6.

- 0.152** The corner of sections 31 and 32, T. 39 S., R 24 E., monumented with a sandstone 16 X 6 X 6 inches, marked with 5 notches on the East, 1 notch on the West, firmly set, in a mound of stone.

At the corner point

Set a stainless steel post, 30 inches long, 2½ inches diameter, 14 inches in ground, to solid rock, and in a mound of stone, 4 ft. base to top of brass cap marked:

T39S	R24E
S31	S32
T40S	
2003	

Deposit a Deep 1 magnet at base of post.

- 39.884** Point for the ¼ section corner of section 6 only, at proportionate distance; based on the irregular boundary adjustment, there is no remaining evidence of the original corner.

Set a brass tablet, 3 ¼ inch diameter, with a 3 ½ inch stem, flush with sandstone, over a magnet, in cement bond, into a drill hole on solid rock, marked:

T39S	

1/4	S6
T40S	R24E
2003	

Raise a mound of stone 3 ft. base, 1 ft. high, west of corner.

Corner is located on a south slope, on the SE edge of a mesa top.

N. 89° 58.4' W., beginning new measurement.

**DEPENDENT RESURVEY OF THE NORTH BOUNDARIES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

0.660 Point for the $\frac{1}{4}$ section corner of section 31 only, at proportionate distance; based on the irregular boundary adjustment, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, $2\frac{1}{2}$ inches diameter, 10 inches in ground, to solid rock, and in a mound of stone, 4 ft. base to top of brass cap marked:

T39S R24E
S31
1/4 —————
T40S
2003

Deposit a Deep 1 magnet at base of post.

Corner is located on south point of mesa top.

39.335 The corner of Townships 39 and 40 South, Ranges 23 and 24 East, hereinbefore described.

Dependent Resurvey of the Subdivisional Lines,
Township 40 South, Range 24 East,
Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by,
Page & Lentz in 1899

From the standard corner of sections 35 and 36, on the south boundary of the Township, hereinbefore described.

N. $0^{\circ} 17.2'$ E., between sections 35 and 36.

39.884 Point for the $\frac{1}{4}$ section corner of sections 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set a brass tablet, $3\frac{1}{4}$ inch diameter, with a $3\frac{1}{2}$ inch stem, flush with sandstone, over a magnet, in cement bond, into a drill hole on solid rock, marked:

T40S R24E
1/4
S35 | S36
2003

Raise a mound of stone 4 ft. base, $2\frac{1}{2}$ ft. high, west of corner.

Corner falls in dry ravine.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

- 79.768** Point for the corner of sections 25, 26, 35, and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 12 inches in ground, to solid rock, and in a mound of stone, 3 ft. base to top of brass cap marked:

T40S R24E
 S26 | S25
 S35 | S36
 2003

Deposit a Deep 1 magnet at base of post.

From the corner of sections 25, 30, 31, and 36 on the east boundary of the Township, hereinbefore described.

S. 89° 46.6' W., between sections 25 and 36.

- 38.935** The ¼ section corner of sections 25 and 36, monumented with a sandstone, 16 X 14 X 4 inches, firmly set, in a mound of stone, and no visible markings. Found a lath and stake alongside.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter 20 inches in ground, and in a collar of stone, with brass cap marked:

T40S R24E
 S25
 1/4 _____
 S36
 2003

Deposit a Deep 1 magnet at base of post.

S. 89° 38.7' W., beginning new measurement.

- 40.791** The corner of sections 25, 26, 35, and 36.
-

N. 0° 26.7' E., between sections 25 and 26.

- 39.884** Point for the ¼ section corner of sections 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 24 inches in ground, with brass cap marked:

T40S R24E
 1/4
 S26 | S25
 2003

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Deposit a Deep 1 magnet at base of post.

- 79.768** The corner of sections 23, 24, 25, and 26, monumented with a sandstone, 17 X 10 X 4 inches, firmly set, in a mound of stone, and no visible markings.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, with brass cap marked:

T40S R24E	
S23	S24
S26	S25
2003	

Deposit a Deep 1 magnet at base of post.

Deposit marked stone alongside.

Raise a mound of stone 3 ft. base, 1 ½ ft. high, west of corner.

From the corner of sections 19, 24, 25, and 30, on the east boundary of the Township, hereinbefore described.

N. 88° 51.4' W., between sections 24 and 25.

- 39.078** The ¼ section corner of sections 24 and 25, monumented with a sandstone, 18 X 10 X 3 inches, firmly set, in a mound of stone, and no visible markings.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, with brass cap marked:

T40S R24E	
S25	
1/4	_____
S36	
2003	

Deposit a Deep 1 magnet at base of post.

Raise a mound of stone 3 ft. base, 1 ½ ft. high to the north.

S. 89° 25.8' W., beginning new measurement.

- 39.924** The corner of sections 23, 24, 25, and 26.
-

N. 0° 35.9' W., between sections 23 and 24.

- 40.464** Point for the ¼ section corner of sections 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 20 inches in ground, with brass cap marked:

T40S R24E
1/4
S23 | S24
2003

Deposit a Deep 1 magnet at base of post.

Corner falls 80 links north of an E-W road, on a NE slope.

- 80.928** Point for the corner of sections 13, 14, 23, and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 24 inches in ground, with brass cap marked:

T40S R24E
S14 | S13
S23 | S24
2003

Deposit a Deep 1 magnet at base of post.

Deposit a steel fence post alongside.

Raise a mound of stone 3 ft. base, 2 ft. high, west of corner.

Corner falls north of a 20 ft. X 30 ft. concrete pad.

From the corner of sections 13, 18, 19, and 24, on the east boundary of the Township, hereinbefore described.

N. 88° 08.0' W., between sections 13 and 24.

- 40.104** Point for the ¼ section corner of sections 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, and in a mound of stone, 5 ft. base to top of brass cap marked:

T40S R24E
S13
1/4 _____
S24
2003

Deposit a Deep 1 magnet at base of post.

- 80.208** The corner of sections 13, 14, 23, and 24.
-

N. 0° 27.1' E., between sections 13 and 14.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

- 40.464** Point for the $\frac{1}{4}$ section corner of sections 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 22 inches in ground, and in a collar of stone, with brass cap marked:

T40S R24E
1/4
S14 | S13
2003

Deposit a Deep 1 magnet at base of post.

- 80.928** The corner of sections 11, 12, 13, and 14, monumented with a sandstone, 27 X 8 X 8 inches, plainly marked, and firmly set, in ground.

At the corner point

Set a stainless steel post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 6 inches in ground, to solid rock, and in a mound of stone, 4 ft. base to top of brass cap marked:

T40S R24E
S11 | S12
S14 | S13
2003

Deposit a Deep 1 magnet at base of post.

From the corner of sections 7, 12, 13, and 18, on the east boundary of the Township, hereinbefore described.

N. 89° 57.4' W., between sections 12 and 13.

- 41.010** The $\frac{1}{4}$ section corner of sections 12 and 13, monumented with a sandstone, 18 X 12 X 6 inches, firmly set and plainly marked $\frac{1}{4}$ on west face.

At the corner point

Set a stainless steel post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 26 inches in ground, with brass cap marked:

T40S R24E
S12
1/4 ———
S13
2003

Deposit a Deep 1 magnet at base of post.

Raise a mound of stone 3 ft. base, 1 $\frac{1}{2}$ ft. high to the north.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

N. 88° 08.0' W., beginning new measurement.

38.928 The corner of sections 11, 12, 13, and 14.

N. 1° 30.3' W., between sections 11 and 12.

38.795 The ¼ section corner of sections 11 and 12, monumented with a sandstone, 17 X 9 X 5 inches, firmly set and plainly marked ¼ on west face.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 20 inches in ground, and in a collar of stone, with brass cap marked:

T40S R24E
1/4
S11 | S12
2003

Deposit a Deep 1 magnet at base of post.

N. 0° 04.8' W., beginning new measurement.

39.706 The corner of sections 1, 2, 11, and 12, monumented with a sandstone, 20 X 8 X 5 inches, firmly set, in a mound of stone, and plainly marked with 1 notch on east, and 5 on south edges.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 6 inches in ground, to solid rock, and in a mound of stone, 6 ft. base to top of brass cap marked:

T40S R24E
S1 | S2
S11 | S12
2003

Deposit a Deep 1 magnet at base of post.

From the corner of sections 1, 6, 7, and 12, on the east boundary of the Township, hereinbefore described.

N. 89° 48.6' W., between sections 1 and 12.

40.054 Point for the ¼ section corner of sections 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 14 inches in ground, to solid rock, and in a mound of stone, 3 ft. base to top of brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S R24E
S1
1/4 _____
S12
2003

Deposit a Deep 1 magnet at base of post.

80.108 The corner of sections 1, 2, 11, and 12.

N. 0° 08.5' W., between sections 1 and 2.

39.962 Point for the ¼ section corner of sections 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 2 inches in ground, to solid rock, and in a mound of stone, 6 ft. base to top of brass cap marked:

T40S R24E
1/4
S2 | S1
2003

80.023 The corner of sections 1, 2, 35, and 36, on the north boundary of the Township, hereinbefore described.

From the standard corner of sections 34 and 35, on the south boundary of the Township, hereinbefore described.

N. 0° 15.9' W., between sections 34 and 35.

39.966 The ¼ section corner of sections 34 and 35, monumented with a sandstone, 15 X 9 X 8 inches, firmly set, in a mound of stone, plainly marked ¼ on west face.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 12 inches in ground, to solid rock, and in a mound of stone, 4 ft. base to top of brass cap marked:

T40S R24E
1/4
S34 | S35
2003

Deposit a Deep 1 magnet at base of post.

N. 0° 04.3' E., beginning new measurement.

39.516 The corner of sections 26, 27, 34, and 35, monumented with an "X" chiseled on a sandstone ledge, with a mound of stone to the west.

At the corner point

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a brass tablet, 3 ¼ inch diameter, with a 3 ½ inch stem, flush with sandstone, over a magnet, in cement bond, into a drill hole on solid rock, marked:

T40S	R24E
S27	S26
S34	S35
2003	

Raise a mound of stone 3 ft. base, 2 ft. high to the west.

From the corner of sections 25, 26, 35, and 36.

N. 89° 46.7' W., between sections 26 and 35.

- 40.811** The ¼ section corner of sections 26 and 35, monumented with a sandstone, 15 X 8 X 5 inches, firmly set, in a mound of stone, and plainly marked ¼ on west face.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, and in a collar of stone, with brass cap marked:

T40S	R24E
S26	
1/4	_____
S35	
2003	

Deposit a Deep 1 magnet at base of post.

S. 89° 23.5' W., beginning new measurement.

- 39.571** The corner of sections 26, 27, 34, and 35.
-

N. 0° 13.3' W., between sections 26 and 27.

- 40.266** The ¼ section corner of sections 26 and 27, monumented with a black sandstone, 14 X 12 X 6 inches, firmly set and dimly marked ¼ on west face.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, and in a collar of stone, with brass cap marked:

T40S	R24E
1/4	
S27	S26
2003	

Deposit a Deep 1 magnet at base of post.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Deposit marked stone alongside.

Corner is located on a sandy south slope.

N. 0° 07.5' E., beginning new measurement.

- 39.919** The corner of sections 22, 23, 26, and 27, monumented with a sandstone, 15 X 10 X 5 inches, firmly set, in a mound of stone, and plainly marked with 2 notches on both south and east edges.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 4 inches in ground, to solid rock, and in a mound of stone, 4 ft. base to top of brass cap marked:

T40S	R24E
S22	S23
S27	S26
2003	

Deposit a Deep 1 magnet at base of post.

Deposit marked stone alongside.

Corner is located on a steep rocky slope, 20 ft. distance south of power lines bearing E-W.

From the corner of sections 23, 24, 25, and 26.

N. 89° 53.3' W., between sections 23 and 26.

- 40.527** Point for the ¼ section corner of sections 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 14 inches in ground, to solid rock, and in a mound of stone, 3 ft. base to top of brass cap marked:

T40S	R24E
S23	
1/4	_____
S26	
2003	

Deposit a Deep 1 magnet at base of post.

- 81.054** The corner of sections 22, 23, 26, and 27.
-

N. 0° 04.2' W., between sections 22 and 23.

- 40.238** The ¼ section corner of sections 22 and 23, monumented with a black sandstone, 18 X 10 X 6 inches, firmly set, in a mound of stone, and plainly marked ¼ on west face.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 24 inches in ground, with brass cap marked:

T40S R24E
1/4
S22 | S23
2003

Deposit marked stone alongside.

Corner falls on a gentle SW slope.

N. 0° 40.6' E., beginning new measurement.

- 39.722** The corner of sections 14, 15, 22, and 23, monumented with a sandstone, 16 X 10 X 5 inches, firmly set, in a mound of stone, dimly marked 3 notches on south edge only.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, on solid rock, and in a mound of stone, 4 ft. base to top of brass cap marked:

T40S R24E
S15 | S14
S22 | S23
2003

Deposit a Deep 1 magnet at base of post.

Deposit marked stone alongside.

Corner falls on a rocky north slope.

From the corner of sections 13, 14, 23, and 24.

S. 89° 30.8' W., between sections 14 and 23.

- 40.084** The ¼ section corner of sections 14 and 23, monumented with a sandstone, 12 X 12 X 4 inches, firmly set and plainly marked ¼ on west face.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 18 inches in ground, to solid rock, and in a mound of stone, 3 ft. base to top of brass cap marked:

T40S R24E
S14
1/4 ———
S23
2003

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Deposit a Deep 1 magnet at base of post.

Deposit marked stone alongside.

Corner falls on steep NW slope.

S. 89° 19.4' W., beginning new measurement.

39.692 The corner of sections 14, 15, 22, and 23.

N. 0° 24.8' W., between sections 14 and 15.

40.472 The $\frac{1}{4}$ section corner of sections 14 and 15, monumented with a sandstone, 17 X 15 X 5 inches, firmly set and plainly marked $\frac{1}{4}$ on west face.

At the corner point

Set a stainless steel post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 26 inches in ground, with brass cap marked:

T40S R24E
1/4
S15 | S14
2003

Raise a mound of stone 3 ft. base, 2 ft. high, to the west.

Deposit marked stone alongside.

N. 0° 08.7' W., beginning new measurement.

39.952 The corner of section 10, 11, 14, and 15, monumented with a black sandstone, 16 X 13 X 9 inches, firmly set, in a mound of stone, and plainly marked 4 notches on south, and 2 notches on east edges.

At the corner point

Set a stainless steel post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 26 inches in ground, with brass cap marked:

T40S R24E
S10 | S11
S15 | S14
2003

Raise a mound of stone 3 ft. base, 2 ft. high, to the west.

Deposit marked stone alongside.

From the corner of sections 11, 12, 13, and 14.

S. 89° 04.3' W., between sections 11 and 14.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

- 40.400** Point for the $\frac{1}{4}$ section corner of sections 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 4 inches in ground, to solid rock, and in a mound of stone, 6 ft. base to top of brass cap marked:

T40S R24E
S11
1/4 _____
S14
2003

Raise a mound of stone 6 ft. base, to top of post.

- 80.800** The corner of sections 10, 11, 14, and 15.

N. 0° 06.7' W., between sections 10 and 11.

- 39.884** The $\frac{1}{4}$ section corner of sections 10 and 11, monumented with a sandstone, 16 X 6 X 5 inches, firmly set, in a mound of stone, and dimly marked $\frac{1}{4}$ on west face.

At the corner point

Set a stainless steel post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 4 inches in ground, to solid rock, and in a mound of stone, 5 ft. base to top of brass cap marked:

T40S R24E
1/4
S10 | S11
2003

Deposit a Deep 1 magnet at base of post.

Deposit marked stone alongside.

N. 0° 06.4' W., beginning new measurement.

- 40.037** The corner of section 2, 3, 10, and 11, which is also the southwest corner of allotment #033362, and the southeast corner of allotment #033363, monumented with a broken sandstone, 10 X 6 X 6 inches, in a mound of stone, and marked with 5 notches on south, and 1 notch on east edges.

At the corner point

Set a stainless steel post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 14 inches in ground, to solid rock, and in a mound of stone, 3 ft. base to top of brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S R24E
363 362
S3 | S2
S10 | S11
2003

Deposit a Deep 1 magnet at base of post.

Deposit marked stone alongside, with steel fence post.

From the corner of sections 1, 2, 11, and 12.

N. 89° 54.7' W., between sections 2 and 11.

- 39.925** Point for the ¼ section corner of sections 2 and 11, which is also the southeast corner of allotment #033362, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 24 inches in ground, with brass cap marked:

T40S R24E
362
S2
1/4 _____
S11
2003

Deposit a Deep 1 magnet at base of post.

Place steel fence post alongside.

- 79.850** The corner of sections 2, 3, 10, and 11.
-

N. 0° 06.8' W., between sections 2 and 3.

- 40.052** Point for the ¼ section corner of sections 2 and 3, which is also the northwest corner of allotment #033362, and the northeast corner of allotment #033363, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 24 inches in ground, with brass cap marked:

T40S R24E
1/4
S3 | S2
363 362
2003

Deposit a Deep 1 magnet at base of post.

Place a steel fence post alongside.

- 80.104** The corner of sections 2, 3, 34, and 35, on the north boundary of the Township, hereinbefore described.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

From the true point for the standard corner of sections 33 and 34, on the south boundary of the Township, hereinbefore described.

N. 0° 00.7' E., between sections 33 and 34.

- 39.786** Point for the $\frac{1}{4}$ section corner of sections 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 22 inches in ground, with brass cap marked:

T40S R24E
1/4
S33 | S34
2003

Deposit a Deep 1 magnet at base of post.

- 79.572** The corner of sections 27, 28, 33, and 34, monumented with a sandstone, 19 X 12 X 4 inches, firmly set and dimly marked with 1 notch on south, and 3 notches on east edges.

At the corner point

Set a stainless steel post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 26 inches in ground, with brass cap marked:

T40S R24E
S28 | S27
S33 | S34
2003

Deposit a Deep 1 magnet, and broken glass at base of post.

Deposit marked stone alongside.

Raise a mound of stone 3 ft. base, 1 ft. high to the west.

Corner falls about 20 ft. west of a road bearing south-southeast, and north.

From the corner of sections 26, 27, 34, and 35.

N. 89° 57.4' W., between sections 27 and 34.

- 39.859** The $\frac{1}{4}$ section corner of sections 27 and 34, monumented with a broken sandstone, 30 X 16 X 4 inches, plainly marked $\frac{1}{4}$ on west face.

At the corner point

Set a stainless steel post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 4 inches in ground, to solid rock, with brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S R24E
S27
1/4 ———
S34
2003

Deposit a Deep 1 magnet at base of post.

Raise a mound of stone 6 ft. base, to top of post.

N. 89° 52.8' W., beginning new measurement.

39.836 The corner of sections 27, 28, 33, and 34.

N. 0° 10.7' E., between sections 27 and 28.

39.807 The ¼ section corner of sections 27 and 28, monumented with a sandstone, 14 X 10 X 6 inches, firmly set and dimly marked ¼ on west face.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 26 inches in ground, with brass cap marked:

T40S R24E
1/4
S28 | S27
2003

Deposit a Deep 1 magnet at base of post.

Deposit marked stone alongside.

N. 0° 31.7' W., beginning new measurement.

40.712 The corner of sections 21, 22, 27, and 28, monumented with a mound of stone with steel fence post alongside. This is harmoniously related with other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, and in a collar of stone, with brass cap marked:

T40S R24E
S21 | S22
S28 | S27
2003

Deposit a Deep 1 magnet at base of post.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Place steel fence post alongside.

From the corner of sections 22, 23, 26, and 27.

N. 89° 40.8' W., between sections 22 and 27.

- 39.932** Point for the ¼ section corner of sections 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, with brass cap marked:

T40S R24E
S22
1/4

S27
2003

Deposit a Deep 1 magnet at base of post.

- 79.864** The corner of sections 21, 22, 27, and 28.
-

N. 0° 12.7' W., between sections 21 and 22.

- 40.040** The ¼ section corner of sections 21 and 22, monumented with a sandstone, 18 X 16 X 6 inches, no visible marks, firmly set, with mound of stone to the west.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 20 inches in ground, with brass cap marked:

T40S R24E
1/4
S21 | S22
2003

Deposit a Deep 1 magnet at base of post.

Deposit unmarked stone alongside.

N. 0° 05.8' E., beginning new measurement.

- 39.842** The corner of sections 15, 16, 21, and 22, monumented with a sandstone, 17 X 10 X 8 inches, firmly set, in a mound of stone, marked 24E on one side, and S21 on another side. At the center of mound is a ¼ inch pipe, with a 2 ½ X 2 ½ inch steel plate marked:

T40S

16 | 15
21 | 22
R24E

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 14 inches in ground, to solid rock, and in a mound of stone, 3 ft. base to top of brass cap marked:

T40S	R24E
S16	S15
S21	S22
2003	

Deposit a Deep 1 magnet at base of post.

Place ¼ inch pipe, face down, inside stainless steel post.

Place marked stone in a mound of stone alongside corner.

From the corner of sections 14, 15, 22, and 23.

N. 89° 44.1' W., between sections 15 and 22.

- 40.174** Point for the ¼ section corner of sections 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 26 inches in ground, with brass cap marked:

T40S	R24E
S15	
1/4	_____
S22	
2003	

Corner falls in a N-S oil service road.

- 80.348** The corner of sections 15, 16, 21, and 22.

N. 0° 11.5' E., between sections 15 and 16.

- 39.981** Point for the ¼ section corner of sections 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 24 inches in ground, with brass cap marked:

T40S	R24E
1/4	
S16	S15
2003	

Deposit an 18 inch drill bit alongside.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

- 79.962** The corner of sections 9, 10, 15, and 16, monumented with a sandstone, 19 X 11 X 7 inches, firmly set, in a mound of stone, and plainly marked with 4 notches on south, and 3 notches on east edges, with a 1 inch iron pipe alongside with cap marked:

T40S R24E	
9	10
16	15

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 16 inches in ground, to solid rock, and in a mound of stone, 3 ft. base to top of brass cap marked:

T40S R24E	
S9	S10
S16	S15
2003	

Deposit a Deep 1 magnet at base of post.

Deposit marked stone, and pipe alongside.

From the corner of sections 10, 11, 14, and 15.

S. 89° 56.0' W., between sections 10 and 15.

- 39.835** Point for the ¼ section corner of sections 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 24 inches in ground, with brass cap marked:

T40S R24E	
S10	
1/4	_____
S15	
2003	

Raise a mound of stone 3 ft. base, 2 ft. high to the north.

- 79.670** The corner of sections 9, 10, 15, and 16.
-

N. 0° 08.1' W., between sections 9 and 10.

- 40.022** Point for the ¼ section corner of sections 9 and 10, which is also the southwest corner of allotment #033364, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 20 inches in ground, with brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S R24E
1/4
364
S9 | S10
2003

Raise a mound of stone at base of post.

Deposit a Deep 1 magnet at base of post.

Place a steel fence post alongside.

- 80.044** Point for the corner of sections 3, 4, 9, and 10, which is also the southwest corner of allotment #033361, and the northwest corner of allotment #033364, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 20 inches in ground, with brass cap marked:

T40S R24E
361
S4 | S3
S9 | S10
364
2003

Deposit a Deep 1 magnet at base of post.

Place a steel fence post alongside.

Corner is located on east edge of wash below and next to a 6 ft. bank.

From the corner of sections 2, 3, 10, and 11.

N. 89° 58.7' W., between sections 3 and 10.

- 39.845** Point for the ¼ section corner of sections 3 and 10, which is also the northeast corner of allotment #033364, and the southeast corner of allotment #033361, and the southwest corner of allotment #033363, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 24 inches in ground, with brass cap marked:

T40S R24E
361 363
S3
1/4 _____
S10
364
2003

Deposit a Deep 1 magnet at base of post.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Place a steel fence post alongside.

Corner falls at the bottom of a clay drop off, to the west.

79.690 The corner of sections 3, 4, 9, and 10.

N. 0° 43.5' W., between sections 3 and 4.

40.024 True point for the ¼ section corner of sections 3 and 4, which is also the northwest corner of allotment #033361, point falls on face of ledge where it is impracticable to establish a permanent monument, at proportionate distance; there is no remaining evidence of the original corner.

40.074 Point selected for the witness corner to the ¼ section corner of sections 3 and 4, and the northwest corner of allotment #033361, Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 4 inches in ground, to solid rock, and in a mound of stone, 5 ft. base to top of brass cap marked:

T40S R24E
WC
1/4
S4 | S3
↓ 361
2003

Deposit a Deep 1 magnet at base of post.

54.276 Intersect the line between Angle Point 8, and Angle Point 9, on the old west boundary of the Navajo Indian Reservation, not monumented.

80.108 The corner of sections 3 and 4 only, on the north boundary of the township, hereinbefore described.

From the standard corner of sections 32 and 33, on the south boundary of the Township, hereinbefore described.

N. 0° 31.4' E., between sections 32 and 33.

19.932 Point for the S 1/16 section corner of sections 33 and 34.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, with brass cap marked:

T40S R24E
S 1/16
S32 | S33
2003

Deposit a Deep 1 magnet at base of post.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Corner falls in river bed at base of the south bank.

- 39.864** The $\frac{1}{4}$ section corner of sections 32 and 33, monumented with a sandstone, 16 X 12 X 7 inches, firmly set, in a mound of stone, and plainly marked $\frac{1}{4}$ on west face, with steel fence post alongside.

At the corner point

Set a stainless steel post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 26 inches in ground, with brass cap marked:

T40S R24E
1/4
S32 | S33
2003

Deposit a Deep 1 magnet at base of post.

Deposit marked stone alongside.

Place the steel fence post alongside.

N. 0° 33.4' W., beginning new measurement.

- 39.990** The corner of sections 28, 29, 32, and 33, monumented with a sandstone, 21 X 12 X 5 inches, firmly set and plainly marked with 4 notches on north, and 1 notch on south edges.

At the corner point

Set a stainless steel post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 4 inches in ground, to solid rock, and in a mound of stone, 6 ft. base to top of brass cap marked:

T40S R24E
S29 | S28
S32 | S33
2003

Deposit a Deep 1 magnet at base of post.

From the corner of sections 27, 28, 33, and 34.

N. 89° 36.0' W., between sections 28 and 33.

- 40.852** The $\frac{1}{4}$ section corner of sections 28 and 33, monumented with a sandstone, 20 X 9 X 7 inches, firmly set and plainly marked $\frac{1}{4}$ on west face.

At the corner point

Set a stainless steel post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 26 inches in ground, with brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S R24E
S28
¼ _____
S33
2003

Deposit a Deep 1 magnet at base of post.

Deposit marked stone alongside.

Raise a mound of stone 3 ft. base, 2 ft. high to the north.

N. 89° 58.6' W., beginning new measurement.

39.036 The corner of sections 28, 29, 32, and 33.

N. 0° 04.4' E., between sections 28 and 29.

39.978 Point for the ¼ section corner of sections 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 20 inches in ground, with brass cap marked:

T40S R24E
1/4
S29 | S28
2003

Deposit a Deep 1 magnet at base of post.

79.956 The corner of sections 20, 21, 28, and 29, monumented with a mound of stone, and a 5/8 inch rebar, 18 inches long, and a ½ inch rebar, 12 inches long alongside, and is accepted as the best available evidence of the original corner position.

At the corner point (center of mound)

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 20 inches in ground, with brass cap marked:

T40S R24E
S20 | S21
S29 | S28
2003

Deposit a Deep 1 magnet at base of post.

Place rebars face down, inside post.

Raise a mound of stone 3 ft. base, 1 ½ ft. high to the west.

From the corner of sections 21, 22, 27, and 28.

S. 89° 48.7' W., between sections 21 and 28.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

- 38.822** Point selected for the witness corner to the $\frac{1}{4}$ section corner of sections 21 and 28.

Set a stainless steel post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 22 inches in ground, with brass cap marked:

T40S R24E
S21
1/4 _____
S28
WC
2003

Deposit a Deep 1 magnet at base of post.

- 39.760** True point for the $\frac{1}{4}$ section corner of sections 21 and 28, point falls in a dirt road, where it is impracticable to establish a permanent monument.

- 79.520** The corner of sections 20, 21, 28, and 29.

N. 0° 03.8' E., between sections 20 and 21.

- 38.128** The $\frac{1}{4}$ section corner of sections 20 and 21, which is also the southeast corner of allotment #033508, monumented with a sandstone, 17 X 7 X 3 inches, firmly set, in a mound of stone, with no visible markings, and a $\frac{1}{2}$ inch rebar, 12 inches long alongside.

At the corner point

Set a stainless steel post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 8 inches in ground, to solid rock, and in a mound of stone, 4 ft. base to top of brass cap marked:

T40S R24E
1/4
508
S20 | S21
2003

Deposit a Deep 1 magnet at base of post.

Place rebar face down, inside post.

N. 0° 04.9' E., beginning new measurement.

- 41.754** The corner of sections 16, 17, 20, and 21, which is also the northeast corner of allotment #033508, southeast corner of allotment #033370, monumented with a sandstone, 18 X 14 X 6 inches, firmly set and plainly marked 3 notches on the South and 4 notches on the East.

At the corner point

Set a stainless steel post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 22 inches in ground, with brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S R24E
370
S17 | S16
S20 | S21
508
2003

Deposit a Deep 1 magnet at base of post.

Place a steel fence post alongside.

From the corner of sections 15, 16, 21, and 22.

S. 89° 48.7' W., between sections 16 and 21.

- 39.660** Point for the ¼ section corner of sections 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 24 inches in ground, with brass cap marked:

T40S R24E
S16
1/4 _____
S21
2003

Deposit a Deep 1 magnet at base of post.

- 79.320** The corner of sections 16, 17, 20, and 21.
-

N. 0° 02.6' E., between sections 16 and 17.

- 40.383** Point for the ¼ section corner of sections 16 and 17, which is also on the east boundary of allotment #033370, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 20 inches in ground, with brass cap marked:

T40S R24E
1/4
370 S17 | S16
2003

Corner falls in the center of a large tamarack on the west bank of main wash, draining S.

Place a steel fence post alongside.

- 80.766** The corner of sections 8, 9, 16, and 17, which is also the northeast corner of allotment #033370, and the southeast corner of allotment #033509, monumented with a sandstone, 17 X 11 X 7 inches, firmly set, in a mound of stone, and plainly marked with 4 notches on the south and east edges. There is also a 1 inch iron post alongside, marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

T40
8 9
17 16
370
R24

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 24 inches in ground, with brass cap marked:

T40S	R24E
509	
S8	S9
S17	S16
370	
2003	

Deposit a Deep 1 magnet at base of post.

Deposit marked stone, and iron post alongside.

Place a steel fence post alongside.

From the corner of sections 9, 10, 15, and 16.

N. 89° 02.0' W., between sections 9 and 16.

- 39.529** The ¼ section corner of sections 9 and 16, monumented with a sandstone, 12 X 12 X 2 inches, firmly set, in a mound of stone, and plainly marked ¼ on west face.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, over an "X" on solid rock, and in a mound of stone, 5 ft. base to top of brass cap marked:

T40S	R24E
S9	
1/4	_____
S16	
2003	

Deposit marked stone at base of post.

Corner falls in bottom of draw running S-SW.

S. 89° 49.4' W., beginning new measurement.

- 39.987** The corner of sections 8, 9, 16, and 17.
-

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

N. 0° 23.2' W., between sections 8 and 9.

- 39.847** Point for the ¼ section corner of sections 8 and 9, which is also the northeast corner of allotment #033509, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 28 inches in ground, with brass cap marked:

T40S R24E
1/4
S8 | S9
509
2003

Deposit a Deep 1 magnet at base of post.

Corner falls on south edge of an E-W dirt road.

- 79.694** Point for the corner of sections 4, 5, 8, and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 6 inches in ground, to solid rock, and in a mound of stone, 6 ft. base to top of brass cap marked:

T40S R24E
S5 | S4
S8 | S9
2003

Deposit a Deep 1 magnet at base of post.

Corner falls 30 links north of north rim of canyon.

From the corner of sections 3, 4, 9, and 10.

N. 89° 51.7' W., between sections 4 and 9.

- 39.923** Point for the ¼ section corner of sections 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 20 inches in ground, and in a collar of stone, with brass cap marked:

T40S R24E
S4
1/4 _____
S9
2003

Deposit a Deep 1 magnet at base of post.

Corner falls on a northwest slope of small knoll.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

79.846 The corner of sections 4, 5, 8, and 9.

N. 0° 17.0' W., between sections 4 and 5.

28.142 Intersect the line between Angle Point 15, and Angle Point 16, which is also mile post 4, on the old west boundary of the Navajo Indian Reservation, not monumented.

39.846 Point for the ¼ section corner of sections 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, and in a collar of stone, with brass cap marked:

T40S R24E
1/4
S5 | S4
2003

Deposit a Deep 1 magnet at base of post.

Corner falls on west side of ravine running N-S.

79.752 The corner of sections 4 and 5 only, on the north boundary of the Township, hereinbefore described.

From the corner of sections 29, 30, 31, and 32, which is also the southeast corner of allotment #033373, monumented with a ½ inch rebar, 12 inches long, in a mound of stone, and a 5 inch diameter cedar post, 5 ft. long east of rebar, and a steel fence post north of rebar. This is harmoniously related with other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, with brass cap marked:

T40S R24E
373
S30 | S29
S31 | S32
2003

Deposit a Deep 1 magnet at base of post.

Place rebar face down, inside post.

Left the steel fence post, and cedar post in place.

S. 0° 03.0' E., between sections 31 and 32, at record bearing.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

20.000 Point for the N 1/16 section corner of sections 31 and 32.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 20 inches in ground, with brass cap marked:

T40S R24E
N 1/16
S31 | S32
2003

Deposit a Deep 1 magnet at base of post.

40.000 True point for the ¼ section corner of sections 31 and 32, at record distance, point falls on a landing strip, where it is impracticable to establish a permanent monument.

55.450 Bank of the San Juan river, point for the meander corner of sections 31 and 32, at record distance. There is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 14 inches in ground, to solid rock, and in a mound of stone, 4 ft base to top of brass cap marked:

T40S R24E
S31 | S32
MC
2003

Deposit a Deep 1 magnet at base of post.

From the corner of sections 28, 29, 32, and 33.

S. 89° 34.4' W., between sections 29 and 32.

40.842 The ¼ section corner of sections 29 and 32, monumented with a sandstone, 28 X 10 X 8 inches, firmly set, with no visible markings.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 14 inches in ground, to solid rock, and in a mound of stone, 5 ft. base to top of brass cap marked:

T40S R24E
S29
1/4
S32
2003

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit a Deep 1 magnet at base of post.

Deposit unmarked stone alongside.

N. 89° 00.4' W., beginning new measurement.

19.322 Point for the W 1/16 section corner of sections 29 and 32, not monumented.

38.644 The corner of sections 29, 30, 31, and 32.

S. 89° 49.2' W., between sections 30 and 31.

20.089 Point for the E 1/16 section corner of sections 30 and 31, which is also the southwest corner of allotment #033373.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, with brass cap marked:

T40S R24E
S30 373
E1/16 _____
S31
2003

Deposit a Deep 1 magnet at base of post.

Place a steel fence post alongside.

40.178 Point for the ¼ section corner of sections 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, with brass cap marked:

T40S R24E
S30
¼ _____
S31
2003

Deposit a Deep 1 magnet at base of post.

80.266 The corner of sections 25, 30, 31 and 36, on the west boundary of the Township, hereinbefore described.

From the corner of sections 29, 30, 31, and 32.

N. 0° 29.3' W., between sections 29 and 30.

19.892 Point for the S 1/16 section corner of sections 29 and 30, which is also the northeast corner of allotment #033373, and the southeast corner of allotment #033372.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, with brass cap marked:

T40S R24E
S 1/16
372 |
 S30 | S29
373 |
 2003

Deposit a Deep 1 magnet at base of post.

Place a steel fence post alongside.

Corner falls in river bottom.

- 39.784** Point for the ¼ section corner of sections 29 and 30, which is also on the east boundary of allotment #033372, at proportionate distance; there is no remaining evidence of the original corner.

Set a brass tablet, 3 ¼ inch diameter, with a 3 ½ inch stem, flush with sandstone, over a magnet, in cement bond, into a drill hole on solid rock, marked:

T40S R24E
1/4
372 S30 | S29
2003

Place a steel fence post alongside.

Corner falls on a sandstone outcropping.

- 59.676** Point for the N 1/16 section corner of sections 29 and 30, which is also the northeast corner of allotment #033372.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, with brass cap marked:

T40S R24E
N1/16
S30 | S29
372
2003

Deposit a Deep 1 magnet at base of post.

Place a steel fence post alongside.

- 79.568** The corner of sections 19, 20, 29, and 30, monumented with a sandstone, 20 X 10 X 6 inches, in a mound of stone, and marked with 2 notches on east, and 5 notches on south edges.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, with brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S	R24E
S19	S20
S30	S29
2003	

Deposit a Deep 1 magnet at base of post.

Deposit marked stone alongside.

Raise a mound of stone 2 ft. base, 1 ft. high to the west.

From the corner of sections 20, 21, 28, and 29.

S. 89° 59.0' W., between sections 20 and 29.

- 40.123** Point for the ¼ section corner of sections 20 and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 18 inches in ground, with brass cap marked:

T40S	R24E
S20	
1/4	_____
S29	
2003	

Deposit a Deep 1 magnet at base of post.

Corner falls in river bed.

- 80.246** The corner of sections 19, 20, 29, and 30.
-

N. 89° 56.7' W., between sections 19 and 30.

- 39.888** Point for the ¼ section corner of sections 19 and 30, at proportionate distance; point falls in center of house, where it is impracticable to set, not monumented.

- 59.832** Point for the W 1/16 section corner of sections 19 and 30, which is also the northeast corner of allotment #033380.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 26 inches in ground, with brass cap marked:

T40S	R24E
S19	
W1/16	_____
380	S30
2003	

Deposit a Deep 1 magnet at base of post.

Place a steel fence post alongside.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Corner falls 24.5 ft. west of N-S fence, and 31 ft. south of E-W fence.

- 79.586** The corner of sections 19, 24, 25, and 28, on the west boundary of the Township, hereinbefore described.

From the corner of sections 19, 20, 29, and 30.

N. 0° 07.0' E., between sections 19 and 20.

- 39.954** The ¼ section corner of sections 19 and 20, monumented with a sandstone, 12 X 10 X 8 inches, firmly set, with mound of stone to the west, and plainly marked ¼ on west face.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, with brass cap marked:

T40S R24E
1/4
S19 | S20
2003

Deposit a Deep 1 magnet at base of post.

Deposit marked stone alongside.

Raise a mound of stone 3 ft. base, 1 ½ ft. high, to the west.

N. 0° 19.8' E., beginning new measurement.

- 40.235** The corner of sections 17, 18, 19, and 20, monumented with a sandstone, 15 X 7 X 6 inches, firmly set and plainly marked with 3 notches on the south, and 5 notches on the east edges, and a steel fence post alongside.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches on ground, with brass cap marked:

T40S R24E
S18 | S17
S19 | S20
2003

Deposit a Deep 1 magnet at base of post.

Deposit marked stone alongside.

From the corner of sections 16, 17, 20, and 21.

N. 89° 33.3' W., between sections 17 and 20.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

- 20.060** Point for the E 1/16 section corner of sections 17 and 20, which is also the southwest corner of allotment #033370, and on the north boundary of allotment #033508.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 24 inches in ground, with brass cap marked:

T40S R24E
370
S17
E1/16 _____
S20
508
2003

Deposit a Deep 1 magnet at base of post.

Place a steel fence post alongside.

- 40.120** The ¼ section corner of sections 17 and 20, which is also the northwest corner of allotment #033508, monumented with a ½ inch rebar, 24 inches long, with a mound of stone to the west. This is harmoniously related with other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, with brass cap marked:

T40S R24E
S17
1/4 _____
S20
508
2003

Deposit a Deep 1 magnet at base of post.

Place rebar face down, inside post.

Raise a mound of stone 3 ft. base, 1 ft. high, to the north.

Place a steel fence post alongside.

S. 89° 57.5' W., beginning new measurement.

- 39.901** The corner of sections 17, 18, 19, and 20.

N. 89° 52.2' W., between sections 18 and 19.

- 40.030** Point for the ¼ section corner of sections 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 24 inches in ground, with brass cap marked:

T40S R24E
S18
1/4 _____
S19
2003

Deposit a Deep 1 magnet at base of post.

- 71.376** Intersect the line between Angle Point 27, which is also mile post 7, and Angle Point 28, on the old west boundary of the Navajo Indian Reservation, not monumented.
- 79.760** The corner of sections 13, 18, 19, and 24, on the west boundary of the Township, hereinbefore described.

From the corner of sections 17, 18, 19, and 20.

N. 0° 14.9' W., between sections 17 and 18.

- 40.143** The ¼ section corner of sections 17 and 18, monumented with an unmarked sandstone, 18 X 7 X 5 inches, firmly set, in a mound of stone.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, and in a collar of stone, with brass cap marked:

T40S R24E
1/4
S18 | S17
2003

Corner is located in a sandy area.

N. 0° 01.8' W., beginning new measurement.

- 40.114** The corner of sections 7, 8, 17, and 18, monumented with a 5/8 inch rebar, 18 inches long, in a mound of stone, with a fence post alongside. This is harmoniously related with other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 14 inches in ground, to solid rock, and in a mound of stone, 3 ft. base to top of brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S	R24E
S7	S8
S18	S17
2003	

Deposit a Deep 1 magnet at base of post.

Place rebar face down, inside post.

Place the steel fence post alongside.

From the corner of sections 8, 9, 16, and 17.

S.89° 48.2' W., between sections 8 and 17.

- 20.063** Point for the E 1/16 section corner of sections 8 and 17, which is also the northwest corner of allotment #033370, and on the south boundary of allotment #033509.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 20 inches in ground, and in a collar of stone, with brass cap marked:

T40S	R24E
509	
S8	
E1/16	_____
S17	
	370
	2003

Deposit a Deep 1 magnet at base of post.

Place a steel fence post alongside.

- 40.126** The ¼ section corner of sections 8 and 17, which is also the southwest corner of allotment #033509, monumented with a sandstone, 17 X 12 X 4 inches, firmly set and plainly marked ¼ on north face.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, and in a collar of stone, with brass cap marked:

T40S	R24E
509	
S8	
1/4	_____
S17	
	2003

Deposit a Deep 1 magnet at base of post.

Deposit marked stone alongside.

Raise a mound of stone alongside.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

S. 89° 52.4' W., beginning new measurement.

40.135 The corner of sections 7, 8, 17, and 18.

S. 89° 57.8' W., between sections 7 and 18.

34.548 Intersect the line between Angle Point 22, which is also mile post 6, and Angle Point 23, on the old west boundary of the Navajo Indian Reservation, not monumented.

40.048 The ¼ section corner of sections 7 and 18, monumented with a 5/8 inch rebar, and a steel fence post alongside. This is harmoniously related with other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 16 inches in ground, to solid rock, and in a mound of stone, 3 ft. base to top of brass cap marked:

T40S R24E
S7
1/4 _____
S18
2003

Deposit a Deep 1 magnet at base of post.

Place rebar face down, inside post.

Place the steel fence post alongside.

Corner falls on the west side of drainage, draining SE.

N. 89° 59.2' W., beginning new measurement.

39.513 The corner of sections 7, 12, 13, and 18, on the west boundary of the Township, hereinbefore described.

From the corner of sections 7, 8, 17, and 18.

N. 0° 04.0' W., between sections 7 and 8.

39.862 True point for the ¼ section corner of sections 7 and 8, falls on a steep clay slope, where it is impracticable to establish a permanent monument, from which an off line witness corner bears N. 85° 10.9' W., 0.539 chains distance.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 20 inches in ground, with brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

WC
T40S R24E
1/4
S7 | S8
2003

Deposit a Deep 1 magnet at base of post.

Place a steel fence post alongside.

54.884 Intersect the line between Angle Point 20, and Angle Point 21, on the old west boundary of the Navajo Indian Reservation, not monumented.

79.724 Point for the corner of sections 5, 6, 7, and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 20 inches in ground, and in a collar of stone, with brass cap marked:

T40S R24E
S6 | S5
S7 | S8
2003

From the corner of sections 4, 5, 8, and 9.

S. 89° 51.5' W., between sections 5 and 8.

39.900 Point for the ¼ section corner of sections 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 14 inches in ground, to solid rock, and in a mound of stone, 4 ft. base to top of brass cap marked:

T40S R24E
S5
1/4 _____
S8
2003

Deposit a Deep 1 magnet at base of post.

Corner falls in bottom of ravine bearing N.20°W., and S.20°E.

54.924 Intersect the line between Angle Point 17, and Angle Point 18, on the old west boundary of the Navajo Indian Reservation, not monumented.

79.800 The corner of sections 5, 6, 7, and 8.

N. 89° 40.7' W., between sections 6 and 7.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS**39.880**

True point for the $\frac{1}{4}$ section corner of sections 6 and 7, at proportionate distance; there is no remaining evidence of the original corner, falls on large stone, where it is impracticable to establish a permanent monument, from which an off line witness corner bears N. $78^{\circ} 02.5'$ E., 0.070 chains distance.

Set a brass tablet, 3 $\frac{1}{4}$ inch diameter, with a 3 $\frac{1}{2}$ inch stem, flush with sandstone, over a magnet, in cement bond, into a drill hole on solid rock, marked:

T40S R24E
WC ← S6
1/4 ←
S7
2003

Corner falls on top of a brushy mesa, about $\frac{1}{2}$ chains distance west of edge of ledges.

79.320

The corner of sections 1, 6, 7, and 12, on the west boundary of the Township, hereinbefore described.

From the corner of sections 5, 6, 7, and 8.

N. $0^{\circ} 01.3'$ E., between sections 5 and 6.

39.862

Point for the $\frac{1}{4}$ section corner of sections 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 18 inches in ground, to solid rock, and in a mound of stone, 4 ft. base to top of brass cap marked:

T40S R24E
1/4
S6 | S5
2003

Deposit a Deep 1 magnet at base of post.

Corner falls on top of spear run bearing N. 10° E., and S. 10° W.

79.784

The corner of sections 5 and 6, on the north boundary of the Township, hereinbefore described.

The Subdivision of Section 2,
Township 40 South, Range 24 East,
Salt Lake Meridian, Utah.

From the $\frac{1}{4}$ section corner of sections 2 and 11.

N. $0^{\circ} 07.6'$ W., on the N-S center line of section 2.

40.008

Point for the center $\frac{1}{4}$ section corner of section 2, which is also the northeast corner of allotment #033362, at intersection with the E-W center line.

**THE SUBDIVISION OF SECTION 2,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 24 inches in ground, with brass cap marked:

T40S R24E
C ¼
S2
362
2003

Raise a mound of stone 3 ft. base, 2 ft. high to the west.

Place a steel fence post alongside.

Corner falls on a gradual sandy slope, facing west.

- 80.064** The ¼ section corner of sections 2 and 35, on the north boundary of the Township, hereinbefore described.

From the ¼ section corner of sections 1 and 2.

N. 89° 50.8' W., on the E-W center line of section 2.

- 39.911** The center ¼ section corner of section 2.

- 79.822** The ¼ section corner of sections 2 and 3.

The Subdivision of section 3,
Township 40 South, Range 24 East,
Salt Lake Meridian, Utah.

From the ¼ section corner of sections 3 and 10.

N. 0° 25.3' W., on the N-S center line of section 3.

- 40.038** Point for the center ¼ section corner of section 3, which is also the northeast corner of allotment #033361, and the northwest corner of allotment #033363, at intersection with the E-W center line.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 24 inches in ground, with brass cap marked:

T40S R24E
C ¼
S3
361 363
2003

Deposit a Deep 1 magnet at base of post.

Place a steel fence post alongside.

- 80.106** The ¼ section corner of section 3 only, on the north boundary of the Township, hereinbefore described.

From the ¼ section corner of sections 2 and 3.

West, on the E-W center line of section 3.

**THE SUBDIVISION OF SECTION 3,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

- 40.060** The center $\frac{1}{4}$ section corner of section 3.
- 80.110** True point for the $\frac{1}{4}$ section corner of sections 3 and 4.

The Subdivision of Section 8,
Township 40 South, Range 24 East,
Salt Lake Meridian, Utah.

From the $\frac{1}{4}$ section corner of sections 8 and 17.

N. $0^{\circ} 13.8'$ W., on the N-S center line of section 8.

- 39.879** Point for the center $\frac{1}{4}$ section corner of section 8, which is also the northwest corner of allotment #033509, at intersection with the E-W center line.

Set a stainless steel post, 30 inches long, $2\frac{1}{2}$ inches diameter, 20 inches in ground, and in a collar of stone, with brass cap marked:

T40S R24E
C 1/4
S8
509
2003

Deposit a Deep 1 magnet at base of post.

Place a steel fence post alongside.

- 79.733** The $\frac{1}{4}$ section corner of sections 5 and 8.

From the $\frac{1}{4}$ section corner of sections 8 and 9.

S. $89^{\circ} 50.9'$ W., on the E-W center line of section 8.

- 40.013** The center $\frac{1}{4}$ section corner of section 8.
- 80.030** The true point for the $\frac{1}{4}$ section corner of sections 7 and 8.

The Subdivision of Section 10,
Township 40 South, Range 24 East,
Salt Lake Meridian, Utah.

From the $\frac{1}{4}$ section corner of sections 10 and 15.

N. $0^{\circ} 07.4'$ W., on the N-S center line of section 10.

- 39.954** Point for the center $\frac{1}{4}$ section corner of section 10, which is also the southeast corner of allotment #033364, at intersection with the E-W center line.

Set a stainless steel post, 30 inches long, $2\frac{1}{2}$ inches diameter, 18 inches in the ground to solid rock, and in a collar of stone, with brass cap marked:

**THE SUBDIVISION OF SECTION 10,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S R24E
364
C 1/4
S10
2003

Place a steel fence post alongside.

Corner is located on top of flat mesa approximately 3 chains east of the west edge of mesa bearing north and south.

79.984 The ¼ section corner of sections 3 and 10.

From the ¼ section corner of sections 10 and 11.

N. 89° 58.0' W., on the E-W center line of section 10.

39.841 The center ¼ section corner of section 10.

79.683 The ¼ section corner of sections 9 and 10.

The Subdivision of Section 17,
Township 40 South, Range 24 East,
Salt Lake Meridian, Utah.

From the ¼ section corner of sections 17 and 20.

N. 0° 02.0' E., on the N-S center line of section 17.

40.092 Point for the center ¼ section corner of section 17, at intersection with the E-W center line.

Set a brass tablet, 3 ¼ inch diameter, with a 3 ½ inch stem, flush with sandstone, over a magnet, in cement bond, into a drill hole on solid rock, marked:

T40S R24E
C 1/4
S17
2003

Corner falls ½ chains distance, east of N-S dirt road.

80.316 The ¼ section corner of sections 8 and 17.

From the ¼ section corner of sections 16 and 17.

N. 89° 58.2' W., on the E-W center line of section 17.

20.061 Point for the center E 1/16 section corner of section 17.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 24 inches in ground, and in a collar of stone, with brass cap marked:

**THE SUBDIVISION OF SECTION 17,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S R24E
E1/16
C — C
S17
2003

Deposit a Deep 1 magnet at base of post.

Corner falls on steep northerly slope, 31 ft. north of E-W right-of-way fence.

40.122 The center ¼ section corner of section 17.

80.216 The ¼ section corner of sections 17 and 18.

From the center E 1/16 section corner of section 17.

N. 0° 02.3' E., on the N-S center line of the NE ¼ of section 17.

40.304 The E 1/16 section corner of sections 8 and 17.

From the E 1/16 section corner of sections 17 and 20.

N. 0° 02.3' E., on the N-S center line of the SE ¼ of section 17.

40.238 The center E 1/16 section corner of section 17.

The Subdivision of Section 20,
Township 40 South, Range 24 East,
Salt Lake Meridian, Utah.

From the ¼ section corner of sections 20 and 29.

N. 0° 04.2' E., on the N-S center line of section 20.

39.041 Point for the center ¼ section corner of section 20, which is also the southwest corner of allotment #033508, at intersection with the E-W center line.

Set a brass tablet, 3 ¼ inch diameter, with a 3 ½ inch stem, flush with sandstone, over a magnet, in cement bond, into a drill hole on solid rock, marked:

T40S R24E
508
C 1/4
S20
2003

Raise a mound of stone 3 ft. base, 2 ft. high to the west.

80.206 The ¼ section corner of sections 17 and 20.

From the ¼ section corner of sections 20 and 21.

N. 88° 42.8' W., on the E-W center line of section 20.

**THE SUBDIVISION OF SECTION 20,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

- 40.124** The center $\frac{1}{4}$ section corner of section 20.
80.220 The $\frac{1}{4}$ section corner of sections 19 and 20.

The Subdivision of Section 30,
Township 40 South, Range 24 East,
Salt Lake Meridian, Utah.

From the $\frac{1}{4}$ section corner of sections 30 and 31.

N. $0^{\circ} 17.1'$ W., on the N-S center line of section 30.

- 19.947** Point for the center S $\frac{1}{16}$ section corner of section 30, which is also the southwest corner of allotment #033372.

Set a stainless steel post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 21 inches in ground, with brass cap marked:

372
T40S R24E
C
S1/16 | S30
C
2003

Deposit a Deep 1 magnet at base of post.

Place a steel fence post alongside.

- 39.894** Point for the center $\frac{1}{4}$ section corner of section 30, and on the west boundary of allotment #033372, at intersection with the E-W center line.

Set a stainless steel post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 20 inches in ground, with brass cap marked:

T40S R24E
C 1/4
S30 372
2003

Deposit a Deep 1 magnet at base of post.

Place a steel fence post alongside.

Corner falls in a dry river bed.

- 59.813** Point for the center N $\frac{1}{16}$ section corner of section 30, which is also the northwest corner of allotment #033372.

Set a stainless steel post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 24 inches in ground, with brass cap marked:

T40S R24E
C
N1/16 | S30
372
C
2003

Deposit a Deep 1 magnet at base of post.

**THE SUBDIVISION OF SECTION 30,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Place a steel fence post alongside.

79.732 The point for the $\frac{1}{4}$ section corner of sections 19 and 30.

From the $\frac{1}{4}$ section corner of sections 29 and 30.

S. $89^{\circ} 58.6'$ W., on the E-W center line of section 30.

20.017 Point for the center E $\frac{1}{16}$ section corner of section 30, not monumented.

40.034 The center $\frac{1}{4}$ section corner of section 30.

60.055 Point for the center W $\frac{1}{16}$ section corner of section 30, which is also the southeast corner of allotment #033380.

Set a stainless steel post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 20 inches in ground, with brass cap marked:

T40S R24E
380 W1/16
C — C
S30
2003

Deposit a Deep 1 magnet at base of post.

Place a steel fence post alongside.

79.936 The $\frac{1}{4}$ section corner of sections 25 and 30, on the west boundary of the Township, hereinbefore described.

From the N $\frac{1}{16}$ section corner of sections 29 and 30.

N. $89^{\circ} 59.1'$ W., on the E-W center line of the NE $\frac{1}{4}$ of section 30.

39.961 The center N $\frac{1}{16}$ section corner of section 30.

From the E $\frac{1}{16}$ section corner of sections 30 and 31.

N. $0^{\circ} 23.2'$ W., on the N-S center line of the SE $\frac{1}{4}$ of section 30.

19.920 Point for the SE $\frac{1}{16}$ section corner of section 30, which is also the northwest corner of allotment #033373, and on the south boundary of allotment #033372, at intersection with the E-W center line of the SE $\frac{1}{4}$ of section 30.

Set a stainless steel post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 22 inches in ground, with brass cap marked:

372
T40S R24E
SE1/16
S30
373
2003

**THE SUBDIVISION OF SECTION 30,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Deposit a Deep 1 magnet at base of post.

Place a steel fence post alongside.

39.840 The center E 1/16 section corner of section 30.

From the S 1/16 section corner of sections 29 and 30.

S. 89° 53.9' W., on the E-W center line of the SE 1/4 of section 30.

20.053 The SE 1/16 section corner of section 30.

40.106 The center S 1/16 section corner of section 30.

From the center W 1/16 section corner of section 30.

N. 0° 10.6' W., on the N-S center line of the NW 1/4 of section 30.

39.865 The W 1/16 section corner of sections 19 and 30.

The Subdivision of Section 32,
Township 40 South, Range 24 East,
Salt Lake Meridian, Utah.

From the ¼ section corner of section 32 only, on the south boundary of the Township, hereinbefore described.

N. 0° 09.2' E., on the N-S center line of section 32.

20.004 Point for the center S 1/16 section corner of section 32, not monumented.

40.008 Point for the center ¼ section corner of section 32, at intersection with the E-W center line, monumented with a 5/8 inch rebar, and cap marked ALTA SURVEYING, and a steel fence post alongside.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, with brass cap marked:

T40S R24E
C ¼
S32
2003

Deposit a Deep 1 magnet at base of post.

Place rebar face down, inside post.

Place the steel fence post alongside.

59.758 Point for the center N 1/16 section corner of section 32, not monumented.

79.508 The ¼ section corner of sections 29 and 32.

**THE SUBDIVISION OF SECTION 32,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

From the $\frac{1}{4}$ section corner of sections 32 and 33.

N. $89^{\circ} 44.8'$ W., on the E-W center line of section 32.

20.670 Point for the center E $\frac{1}{16}$ section corner of section 32, not monumented.

41.340 The center $\frac{1}{4}$ section corner of section 32.

60.590 Point for the center W $\frac{1}{16}$ section corner of section 32.

Set a stainless steel post, 30 inches long, $2\frac{1}{2}$ inches diameter, 22 inches in ground, with brass cap marked:

T40S R24E
W1/16
C ——— C
S32
2003

Deposit a Deep 1 magnet at base of post.

Point falls 7.7 ft. north of an E-W fence, inside Montezuma Creek tank farm.

79.840 The point for the $\frac{1}{4}$ section corner of sections 31 and 32.

From the E $\frac{1}{16}$ section corner of section 32 only, on the south boundary of the Township, hereinbefore described.

N. $0^{\circ} 20.3'$ E., on the N-S center line of the SE $\frac{1}{4}$ of section 32.

19.968 Point for the SE $\frac{1}{16}$ section corner of section 32, at intersection with the E-W center line of the SE $\frac{1}{4}$ of section 32, monumented with a $\frac{5}{8}$ inch rebar, and cap marked ALTA SURVEYING, and a steel fence post alongside.

Set a stainless steel post, 30 inches long, $2\frac{1}{2}$ inches diameter, 22 inches in ground, with brass cap marked:

T40S R24E
SE1/16
S30
2003

Deposit a Deep 1 magnet at base of post.

Place rebar face down, inside post.

Place the steel fence post alongside.

39.936 The point for the center E $\frac{1}{16}$ section corner of section 32.

From the S $\frac{1}{16}$ section corner of sections 32 and 33.

**THE SUBDIVISION OF SECTION 32,
TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

N. 89° 50.8' W., on the E-W center line of the SE 1/4 of section 32.

20.607 The SE 1/16 section corner of section 32.

41.214 The point for the center S 1/16 section corner of section 32.

From the center W 1/16 section corner of section 32.

N. 0° 03.0' E., on the N-S center line of the NW 1/4 of section 30.

19.875 Point for the NW 1/16 section corner of section 32, at intersection with the E-W center line of the NW ¼ of section 32.

Set a stainless steel post, 30 inches long, 2 ½ inches diameter, 22 inches in ground, with brass cap marked:

T40S R24E
NW1/16
S32
2003

Deposit a Deep 1 magnet at base of post.

Corner falls 1.3 ft. south of an E-W fence.

39.750 The W 1/16 section corner of sections 29 and 32.

From the point for the center N 1/16 section corner of section 32.

N. 89° 22.6' W., on the E-W center line of the NW 1/4 of section 32.

19.286 The NW 1/16 section corner of section 32.

38.572 The N 1/16 section corner of sections 31 and 32.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Ronald K. Baugh	Supervisory Cadastral Surveyor
M. Ross Workman	Supervisory Cadastral Surveyor
Brandon Sanchez	Survey Technician
C. Scott Bishop	Survey Technician
