

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE WEST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS  
7, 18, 19, 20, 29 AND 30.

IN

TOWNSHIP 2 SOUTH, RANGE 5 WEST,

OF THE

UINTAH SPECIAL MERIDIAN,

IN THE STATE OF UTAH.

EXECUTED BY

**SCOTT A. BURKHARDT,**  
*Cadastral Surveyor*

Under Special Instructions dated **April 22, 2003**, approved **April 22, 2003**, which provided for the surveys included under **Group No. 960**, and Assignment Instructions dated **April 22, 2003**.

*Survey commenced June 13, 2003*

*Survey completed August 27, 2003*

# INDEX DIAGRAM

Township 2 South, Range 5 West

13	6	5	4	3	2	1
	40					
11	7	8	9	10	11	12
	38					
	37					
9	18	17	16	15	14	13
	35					
	33	33				
7	19	20	21	22	23	24
	30	20				
	28	26				
5	30	29	28	27	26	25
	24	17				
	23	21				
2	31	32	33	34	35	36

The Subdivision of Section 7.....Page 42  
 The Subdivision of Section 18.....Page 45  
 The Subdivision of Section 19.....Page 46  
 The Subdivision of Section 20.....Page 54  
 The Subdivision of Section 29.....Page 59  
 The Subdivision of Section 30.....Page 64  
 Index for Original Field Notes.....Page 68  
 Outline of Original Field Notes.....Page 73

## TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of the west boundary, a portion of the subdivisional lines, and the subdivision of sections 7, 18, 19, 20, 29, and 30, of Township 2 South, Range West, Uintah Special Meridian, Utah.

**History of Surveys**

<b>Surveyed by</b>	<b>Retr. or Resurveyed by</b>
<b>SOUTH BOUNDARY</b>	
All A. J. Stewart Jr. & A.L. Booth 1903	
<b>EAST BOUNDARY (First Guide Meridian West)</b>	
All D.G. Major 1882	
All	A.J. Stewart Jr. & A.L. Booth 1903
<b>WEST BOUNDARY</b>	
All A.J. Stewart Jr. & A.L. Booth 1903	Corrective Survey 1905
<b>NORTH BOUNDARY</b>	
All D.G. Major 1882	
All	A.J. Stewart Jr. & A.L. Booth 1903
<b>SUBDIVISION</b>	
All A.J. Stewart Jr. & A.L. Booth 1903	Corrective Survey 1905

The survey was executed in accordance with the specifications set forth in the *Manual of Surveying Instructions, 1973*, and the Special Instructions for Group No. 960, Utah, dated April 22, 2003.

The directions of lines were determined by references to true meridians established by the Global Positioning System, utilizing Real Time Kinematic (RTK) survey techniques observed with Trimble 4700 model Global Positioning System receivers.

Preliminary to the resurvey the lines of the original survey and portions of the corrective survey were retraced and search was made for all corners and other calls of the record.

Identified corners were remonumented in their original positions, or corrective positions; lost corners were restored and monumented at proportionate positions based on the original record. The Retracement data were thoroughly verified and only the true line Field Notes are given herein.

## TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

Geodetic control was derived from Global Positioning System (GPS) static post observations processed by National Geodetic Survey, Online Positioning User Service (OPUS).

The geographic positions, in NAD83 (CORS96), epoch date 2002.00 for the corners listed below were determined by Global Positioning System (GPS) observations to a Network Accuracy of less than 0.10 meter, 95 percent confidence circle, as defined in *Standards and Guidelines for Cadastral Surveys Using Global Positioning Systems Methods, May 9, 2001, Version 1.0.*

The corner of Townships 1 and 2 South, Ranges 5 and 6 West, is as follows:

**Latitude 40° 20' 33.997" N., Longitude 110° 30' 05.276" W., 6330 ft.**  
height above the ellipsoid.

The ¼ section corner of sections 17 and 20, Township 2 South, Range 5 West, is as follows:

**Latitude 40° 17' 58.500" N., Longitude 110° 28' 27.590" W., 6506 ft.**  
height above the ellipsoid.

The corner of sections 28, 29, 32, and 33, Township 2 South, Range 5 West, is as follows:

**Latitude 40° 16' 14.717" N., Longitude 110° 27' 53.792" W., 6104 ft.**  
height above the ellipsoid.

The mean magnetic declination is 13° E.

---

**Dependent Resurvey of the West Boundary,  
Township 2 South, Range 5 West, Uintah Special Meridian, Utah**

---

Restoring the survey executed by  
Stewart & Booth, in 1903

---

Beginning at the corner of Townships 2 and 3 South, Ranges 5 and 6 West, monument with the original sandstone, 17 x 15 x 12 ins., marked with faint notches on two corners, was found lying loose.

from which the remains of an original bearing tree

A piñon snag, 13 ins. diameter, bears S. 30° W., 35 links distance, marked T3S R6W S1 BT.

from which bearing trees of unknown origin

A piñon, 15 ins. diameter, bears N. 11° E., 4.26 chains distance, marked T2S R5W S31 BT.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

A piñon, 16 ins. diameter, bears N. 20° E., 2.41 chains distance, improperly marked T3S R5W S6 BT.

A piñon, 14 ins. diameter, bears N. 17° W., 3.33 chains distance, marked T2S R6W S36 BT.

At the corner point

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 18 ins. in the ground, at record bearing and distance from piñon snag, with aluminum cap marked:

	T 2 S	
R 6 W		R 5 W
S 36		S 31
S 1		S 6
	T 3 S	
	2003	

from which new bearing trees

A piñon, 12 ins. diameter, bears N. 64° E., 74 links distance, marked T2S R5W S31 BT.

A juniper, 4 ins. diameter, bears S. 55° E., 54 links distance, marked X BT.

A piñon, 6 ins. diameter, bears N. 69° W., 48 links distance, marked T2S R6W S36 BT.

Buried the original sandstone on South side of aluminum post.

The corner is located on steep South facing slope, with vertical cliff bands above and below corner, and is surrounded by scattered piñon and juniper, with soft and crumbly sandstone.

**N. 0°14.2' E.**, between sections 31 and 36, on the West boundary of the Township.

**40.322** The ¼ section corner of sections 31 and 36, determined at record bearing and distance from the remaining original bearing tree

A piñon, 10 ins. diameter, bears S. 30° E., 15 links distance, marked ¼ S31 BT.

The remains of a dead and downed piñon, 10 ins. diameter, bears West, 50 links distance, marked ¼ S36 BT, could not establish the location of the root hole.

At the corner point

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 20 ins. in the ground, encircled by a collar of stone, 3 ft. diameter, to top aluminum cap marked:

T 2 S	
1/4	
R 6 W	R 5 W
S 36	S 31
2003	

from which a new bearing tree

A juniper, 12 ins. diameter, bears N. 79° W., 57 ½ links distance, marked ¼ S36 BT.

The corner is located on a gentle slope, surrounded by scattered piñon and juniper.

---

N. 0°05.4' W., beginning new measurement.

**39.323**

The corner of sections 25, 30, 31, and 36, monumented with a sandstone, 16 x 11 x 6 ins., marked with 1 notch on the South face and 5 notches on the North face, firmly set, projecting 4 ins. above the ground.

from which the original bearing trees

A piñon, 13 ins. diameter, bears N. 31° E., 72 links distance, marked T2S R5W S30 BT.

A dead and downed piñon, 6 ins. diameter, bears S. 81° E., 61 links distance, marked T2S R5W S31 BT.

A dead and downed piñon, 5 ins. diameter, bears S 63° W., 49 links distance, marked T2S R6W S36 BT (Record: S. 31° W., 24 links distance).

A cedar, 11 ins. diameter, bears N. 31° W., 26 links distance, marked T2S R5W S25 BT (Record: 24 links).

At the corner point

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 23 ins. in the ground, encircled by a collar of stone, 2 ft. diameter, with aluminum cap marked:

T 2 S	
R 6 W	R 5 W
S 25	S 30
S 36	S 31
2003	

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

from which new bearing trees

A juniper, 5 ins. diameter, bears S. 29° E., 43 links  
distance, marked T2S R5W S31 BT.

A juniper, 6 ins. diameter, bears S. 37° W., 21 ½ links  
distance, marked T2S R6W S36 BT.

Deposit a magnet, in a white plastic case, at the base of the  
aluminum post.

Buried the original sandstone on West side of aluminum post.

**N. 0°06.7' E.**, between sections 25 and 30, on the West boundary  
of the Township.

**39.740** Point for the ¼ section corner of sections 25 and 30 at  
proportionate distance; there is no remaining evidence of the  
original corner.

from which a tree of unknown origin

A piñon, 5 ins. diameter, bears N. 20° E., 38 links  
distance, blazed and marked with axe marks but no  
scribe.

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 20 ins.  
in the ground, encircled by a collar of stone, 4 ft. diameter,  
to the top of aluminum cap marked:

T 2 S	
1/4	
R 6 W	R 5 W
S 25	S 30
2003	

from which new bearing trees

A juniper, 6 ins. diameter, bears S. 38° E., 63 links  
distance, marked X BT.

A piñon, 6 ins. diameter, bears N. 43° W., 21 links  
distance, marked ¼ S25 BT.

Deposit a magnet, in a white plastic case, at the base of the  
aluminum post.

The corner lies on the shelf of a steep South facing slope,  
above the road in Sand Wash, surrounded by piñon and juniper.

**59.610** Point for the North 1/16 section corner of sections 25 and 30.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, to bedrock, in a supporting mound of stone, 5 ft. diameter, to the top of aluminum cap marked:

N 1/16	
S 25	S 30
2003	

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

**79.480**

The corner of sections 19, 24, 25, and 30, monumented with a sandstone, 18 x 17 x 6 ins., firmly set, marked with 4 notches on the North and 2 notches on the South.

from which the original bearing trees

A piñon, 6 ins. diameter, bears S. 51° 15' E., 95 links distance, marked T2S R5W S30 BT (Record: 90 links).

A piñon, 9 ins. diameter, bears S. 58° W., 29 links distance, with visible marks S25 BT (Record: 31 links marked T2S R6W S25 BT).

No remains found of other two original bearing trees.

At the corner point

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 23 ins. in the ground, with aluminum cap marked:

T 2 S	
R 6 W	R 5 W
S 24	S 19
-----	
S 25	S 30
2003	

from which new bearing trees

A piñon, 5 ins. diameter, bears N. 62° E., 63 links distance, marked T2S R5W S31 BT.

A piñon, 8 ins. diameter, bears N. 33° W., 61 ½ links distance, marked T2S R6W S36 BT.

Buried the original sandstone alongside aluminum post.

The corner is located on a steep North facing slope surrounded by scattered piñon and juniper.

From this point an iron rebar, 5/8 in. diameter, projecting 6 ins. above ground, firmly set, with aluminum cap, 1 ½ inches diameter, marked LS 148951, encircled by a loose collar of

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

stone, 2 ft. diameter, bears S. 35° 04' W., 82 links distance. This monument is shown on LS 148951 plat dated June 2003 and is on record at the County Clerk and Recorder's Office, Duchesne County, Utah. It was not utilized in this survey as it does not accurately represent the original corner location.

**N. 0°07.7' E.**, between sections 19 and 24, on the West boundary of the Township.

**19.852** Point for the South 1/16 section corner of sections 19 and 24.

Set a brass tablet, 3 ¼ ins. diameter, 3 ½ ins. stem, cemented in a drill hole in solid rock, with brass tablet marked:

S 1/16  
S 24 | S 19  
2003

from which

A sandstone vertical North - East face, chiseled with X BO bears N. 3° W., 13 links distance.

A piñon, 13 ins. diameter, bears S. 39° W., 76 links distance, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY.

The corner lies on a rock spur, 320 vertical ft. above Duchesne River, on the North - East facing slope.

**38.704** Point selected for the Witness Corner to the ¼ section corner of sections 19 and 24, on the West boundary

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 24 ins. in the ground, with aluminum cap marked:

WC  
T 2 S  
1/4  
S 24 ↑ S 19  
R 6 W ↑ R 5 W  
2003

from which

A fence corner post, 6 x 9 ins., projecting 6 ft. above the ground, bears N. 46° E., 2.87 chains, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY.

Set a steel fence post to the North of corner.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

**39.704** True point for the  $\frac{1}{4}$  section corner of sections 19 and 24, at proportionate distance falls on the South bank of the Duchesne River, subject to flooding during periods of high water.

**45.37** Record position for the original Witness Corner of the  $\frac{1}{4}$  section corner of sections 19 and 24, on the West boundary, set in 1903 currently falls in Duchesne River. There is no remaining evidence of the original Witness Corner.

**59.556** Point for the North  $\frac{1}{16}$  section corner of sections 19 and 24, on the West boundary.

Set an aluminum post, 28 ins. long, 2  $\frac{1}{2}$  ins. diameter, buried 6 ins. below the ground in a cultivated field, with aluminum cap marked:

N  $\frac{1}{16}$   
S 24 | S 19  
2003

from which

A juniper fence post, 6 ins. diameter, bears East, 9 links distance, marked with a brass washer, 1  $\frac{1}{2}$  ins. diameter, marked BLM CADASTRAL SURVEY.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

The corner is located West, 8  $\frac{1}{2}$  links. distance from a 4-strand barbed wire fence extending North and South, on near level ground, in an alfalfa field.

**79.408** The corner of sections 13, 18, 19, and 24, monumented with a cobblestone, 15 x 9 x 7 ins., firmly set, projecting 11 ins. above the ground, encircled by a collar of stone, 3 ft. diameter, marked with 3 notches on the North - East corner and 3 notches on South - West corner.

from which the remains of the original bearing trees

A dead and downed piñon, 12 ins. diameter, bears N.  $27^\circ$  E., 46  $\frac{1}{2}$  links distance, marked T2S R5W S18 BT (Record: N.  $29^\circ$  E., 49 links).

A piñon snag, 17 ins. diameter, bears S.  $31^\circ$  E., 48  $\frac{1}{2}$  links distance, marked T2S R5W S19 BT (Record: S.  $33^\circ$  E., 48 links).

A piñon snag, 7 ins. diameter, bears S.  $76^\circ$  W., 52  $\frac{1}{2}$  links distance, marked T2S R6W S24 BT.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

A dead and downed piñon, 5 ins. diameter, bears N. 52° W.,  
83 ½ links distance, marked T2S R6W S13 BT.

At the corner point

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 20 ins.  
in the ground, encircled by a collar of stone, 2 ft. diameter,  
to the top of aluminum cap marked:

	T 2 S	
R 6 W	R 5 W	
S 13	S 18	
S 24	S 19	
2003		

from which new bearing trees

A juniper, 9 ins. diameter, bears N. 37° E., 98 links  
distance, marked T2S R5W S18 BT.

A juniper, 6 ins. diameter, bears S. 83° W., 29 links  
distance, marked T2S R6W S24 BT.

A piñon, 7 ins. diameter, bears N. 31° W., 53 links  
distance, marked T2S R6W S13 BT.

Buried the original cobblestone on South side of aluminum post.

Corner located on gentle South - East facing slope, surrounded  
by scattered piñon and juniper.

N. 0°05.4' E., between sections 13 and 18, on the West boundary.

**39.616**

The ¼ section corner of sections 13 and 18, monumented with a  
sandstone 19 x 11 x 6 ins., marked ¼ on flat face, laying loose  
at original position.

from which original bearing trees

A piñon, 12 ins. diameter, bears N. 85° E., 78 links  
distance, marked ¼ S18 BT.

A dead and downed piñon, 12 ins. diameter, bears  
S. 73° W., 27 links distance, marked ¼ S13 BT (Record:  
S. 87° W., 23 links), could not establish the location  
of the root hole.

At the corner point

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 20 ins.  
in the ground, encircled by a collar of stone, 4 ft. base to top

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

of post, determined by record bearing and distance from the remaining original bearing tree, with aluminum cap marked:

T 2 S	
1/4	
R 6 W	R 5 W
S 13	S 18
2003	

from which a new bearing tree

A piñon, 8 ins. diameter, bears S. 80° W., 32 links distance, marked ¼ S13 BT.

Bury the original sandstone on North side of aluminum post.

**N. 0°24.5' E.**, beginning new measurement.

**40.399**

The corner of sections 7, 12, 13 and 18, monumented with a sandstone 22 x 12 x 6 ins., firmly set, embedded in a collar of stone, 2 ft. diameter, projecting 7 ins. above the ground, marked with 4 notches on the South face and 2 notches on the North face.

from which original bearing trees

A piñon snag, 7 ins. diameter, bears N. 37° E., 72 links distance, marked T2S R5W S7 BT (Record N. 42° E.).

A dead and downed piñon, 8 ins. diameter, bears S. 72° E., 61 links distance, marked T2S R5W S18 BT (Record: S. 69° 45' E., 59 links distance).

A dead and downed piñon, 8 ins. diameter, bears S. 82° W., 39 ½ links distance, marked T2S R6W S13 BT (Record: S. 77° 30' W., 43 links distance).

A dead and downed piñon, 10 ins. diameter, bears N. 77° W., 57 links distance, with illegible scribe marks (Record: N. 56° W.).

At the corner point

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 16 ins. in the ground, encircled by a collar of stone, 2 ½ ft. diameter, 1 ft. high, with aluminum cap marked:

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

	T 2 S	
R 6 W		R 5 W
S 12		S 7
S 13		S 18
2003		

from which new bearing trees and object

A sandstone vertical face, chiseled with X BO bears  
N. 3 ° W., 27 links distance.

A juniper, 10 ins. diameter, bears S. 64° E., 41 links  
distance, marked T2S R5W S18 BT.

A piñon, 5 ins. diameter, bears S. 28° W., 58 links  
distance, marked X BT.

A juniper, 12 ins. diameter, bears N. 59° W., 67 links  
distance, marked T2S R6W S12 BT.

Deposit a magnet, in a white plastic case, at the base of the  
aluminum post.

Buried the original sandstone on North side of aluminum post.

**N. 0°06.8' W.**, between sections 7 and 12 on the West boundary.

**39.345**

The ¼ section corner of sections 7 and 12, monumented with a  
sandstone, 8 x 10 x 18 ins., firmly set, in an embedded mound of  
stone, 2 ft. diameter, projecting 5 ins. above the ground, no  
legible marks found.

from which the original bearing trees

A piñon, 6 ins. diameter, bears S. 28° 30' E., 33 links  
distance, marked ¼ S7 BT (Record: S. 29° E.).

A piñon, 9 ins. diameter, bears S. 36° W., 61 links  
distance, marked ¼ S12 BT.

At the corner point

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 18 ins.  
in the ground, encircled by a collar of stone, 4 ft. diameter,  
projecting 10 ins. high, with aluminum cap marked:

	T 2 S	
	1/4	
R 6 W		R 5 W
S 12		S 7
2003		

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

from which new bearing object

An X BO chiseled on a vertical sandstone face, bears  
N. 3° W., 27 links distance.

Deposit a magnet, in a white plastic case, at the base of the  
aluminum post.

Buried the original sandstone on North side of aluminum post.

The corner is located near the top of a steep West facing slope,  
surrounded by scattered piñon and juniper.

---

**N. 0°11.0' E.,** beginning new measurement.

39.960

The corner of sections 1, 6, 7, and 12, monumented with an iron  
rebar, ½ in. diameter, firmly set, projecting 5 ins. above the  
ground, in a loose mound of stone, 3 ft. diameter, with plastic  
cap marked PLS 148951. No marked stone found.

from which original bearing trees

A piñon, 10 ins. diameter, bears N. 63° E., 81 links  
distance, marked T2S R5W S6 BT (Record: 76 links  
distance).

A piñon, 17 ins. diameter, bears S. 40° E., 1.30 chains  
distance, marked T2S R5W S7 BT.

A piñon, 12 ins. diameter, bears S. 79° W., 78 links  
distance, marked T2S R6W S12 BT.

No evidence found of remaining bearing tree.

This monument harmoniously fits the original corners and is on  
record at the County Clerk and Recorder's Office, Duchesne  
County, Utah. It is accepted as a careful and faithful  
perpetuation of the corner.

At the corner point

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 23 ins.  
in the ground, encircled by a collar of stone, 3 ft. diameter,  
to the top of aluminum cap marked:

	T 2 S	
R 6 W		R 5 W
S 1		S 6
S 12		S 7
2003		

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

from which a new bearing tree

A piñon, 14 ins. diameter, bears N. 40° W., 1.00 chain distance, marked T2S R6W S1 BT.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Placed local rebar and cap inside of aluminum post.

Corner located on top of mesa, 50 ft. South - East of mesa edge.

**N. 0°26.5' E.**, between sections 1 and 6, on the West boundary of the township.

**40.248** Point for the  $\frac{1}{4}$  section corner of sections 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 28 ins. long, 2  $\frac{1}{2}$  ins. diameter, 20 ins. in the ground, encircled by a collar of stone, 3  $\frac{1}{2}$  ft. diameter, to the top of aluminum cap marked:

T 2 S	
1/4	
R 6 W	R 5 W
S 1	S 6
2003	

from which

A piñon, 11 ins. diameter, bears N. 37° E., 58 links distance, marked  $\frac{1}{4}$  S6 BT.

A juniper, 13 ins. diameter, bears S. 46° W., 57 links distance, marked  $\frac{1}{4}$  S1 BT.

Corner located on West facing slope, slightly above rocky bottom.

**80.295** Point for the corner of Townships 1 and 2 South, Ranges 5 and 6 West, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 28 ins. long, 2  $\frac{1}{2}$  ins. diameter, 16 ins. in the ground, encircled by a collar of stone, 3 ft. diameter, to the top of aluminum cap marked:

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

	T 1 S	
R 6 W	R 5 W	
S 36	S 31	
S 1	S 6	
	T 2 S	
	2003	

from which new bearing trees

A piñon, 4 ins. diameter, bears N. 30° E., 28 links distance, marked X BT.

A piñon, 9 ins. diameter, bears S. 20° E., 27 links distance, marked X BT.

A juniper, 10 ins. diameter, bears S. 10° W., 50 links distance, marked T2S R6W S1 BT.

A piñon, 6 ins. diameter, bears N. 18° W., 51 links distance, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Corner is located on a West facing slope, above the Rock Creek drainage, surrounded by scattered piñon and juniper.

From this point the corner of sections 25 and 36, only, T. 1 S., R. 6 W., bears **N. 0°15.9' W., 80.495 chains** distance, determined latitudinally by proportionate measurement between the bearing trees in sections 25 and 31 and longitudinally by proportionate measurement between the bearing trees in sections 31 and 36.

from which the original bearing trees

A piñon, 7 ins. diameter, bears S. 25° E., 16 links distance, with visible marks R5W S31 BT. (Record: 45 links distance).

A multi-trunk juniper, 6 ins. diameter, bears S. 4° W., 85 links distance, marked T1S R6W S36 BT. (Record: piñon bears S. 40° W., 30 links distance).

A piñon, 13 ins. diameter, bears N. 61° W., 20 links distance, with visible marks R6W S25 BT. (Record: N. 50° W., 44 links distance).

At the corner point

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 26 ins. in the ground, in a supporting collar of stone, 6 ft. diameter by 4 ft. high, with aluminum cap marked:

	T 1 S	
R 6 W		R 5 W
S 25		
S 36		S 31
	2003	

from which new bearing trees

A juniper, 12 ins. diameter, bears N. 09° E., 44 links distance, marked T1S R6W S31 BT.

A juniper, 10 ins. diameter, bears S. 76° W., 20 links distance, marked T1S R6W S36 BT.

This control line was fully retraced, and no evidence of the intervening corner was found.

From this same point, the ¼ corner of section 31 only, on the South boundary of T. 1 S., R. 5 W., bears **N. 88°50.7' E., 38.242 chains** distance, monumented with an iron rebar, ½ in. diameter, firmly set, projecting 8 ins. above the ground, with a plastic cap, 1 in. diameter, marked PEATROSS RLS 155666. This monument harmoniously fits the original corners and is accepted as a careful and faithful perpetuation of the position of the original corner.

from which the original bearing trees

A piñon, 17 ins. diameter, bears N. 38° E., 32 links distance, with visible marks ¼ S31 BT (Record: N. 43° E., 55 links distance).

A piñon snag, 17 ins. diameter, bears S. 19° E., 31 links distance, with visible marks ¼ S6 BT (Record: S. 40° W., 13 links distance).

At the corner point

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 20 ins. in the ground, encircled by a collar of stone, 2 ½ ft. diameter, to the top of aluminum cap marked:

T 1 S	R 5 W
1/4	S 31
2003	
T 2 S	
2003	

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

from which new bearing tree

A juniper, 14 ins. diameter, bears S. 33° W., 23 links distance, marked ¼ S6 BT.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Placed local rebar and cap inside aluminum post.

Corner located on a flat mesa, surrounded by scattered piñon and juniper.

From this same point the ¼ section corner of sections 1 and 36, Townships 1 and 2 South, Range 6 West, bears **N. 89°52.9' W., 40.041 chains** distance, determined at record bearing and distance from root hole of dead and downed original bearing tree. No evidence of the original stone or second bearing tree remains.

from which the root hole of the original bearing tree

A stump hole of dead and downed piñon, 8 ins. diameter, bears N. 60° W., 15 links distance, with visible marks 36 B.

At the corner point

Set an aluminum rod, 36 ins. long, ¾ ins. diameter, 26 ins. in the ground, encircled by a collar of stone, 4 ft. diameter, to the top of aluminum cap marked:

T 1 S R 6 W  
S 36  
1/4 ———  
S 1  
T 2 S  
2003

from which new bearing trees

A juniper, 11 ins. diameter, bears S. 55° E., 20 ½ links distance, marked ¼ S1 BT.

A juniper, 7 ins. diameter, bears N. 46° W., 28 links distance, marked ¼ S36 BT.

Deposit a magnet, in a white plastic case, next to the drive rod.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

---

Restoring the Survey Executed by  
A.J. Stewart & A.L. Booth  
in 1903

---

From the section corner of sections 28, 29, 32, and 33, monumented with an aluminum post, 2 ½ ins. diameter, firmly set, projecting 12 ins. above the ground, encircled by a collar of stone, 4 ft. diameter by 1 ft. high, with aluminum cap marked:

Duchesne County Survey

T 2 S	R 5 W
S 29	S 28
S 32	S 33
1988	

from which the original bearing trees

A piñon, 14 ins. diameter, bears S. 28° E., 41 links distance, with illegible scribe marks (Record: S. 15° E., 83 links).

A juniper, 6 ins. diameter, bears S. 28° W., 80 links distance, marked T2S R5W S32 BT (Record: S. 30° W., 1.29 chains).

No evidence found of remaining bearing trees.

from which new bearing trees

A juniper, 8 ins. diameter, bears N. 58° E., 36 links distance, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY.

A juniper, 6 ins. diameter, bears N. 04° W., 48 links distance, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY.

This monument harmoniously fits the original corners and is on record at the County Clerk and Recorder's Office, Duchesne County, Utah. It is accepted as a careful and faithful perpetuation of the corner.

Corner is located on the South edge of rock outcropping.

**N. 0°03.8' E.**, between sections 28 and 29.

**19.942** Point for the South 1/16 section corner of sections 28 and 29.

Set a brass tablet, 3 ¼ ins. diameter, 3 ½ ins. stem, cemented in a drill hole in sandstone, with top marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

S 1/16  
S 29 | S 28  
2003

from which

A juniper, 9 ins. diameter, bears S. 05° E., 16 links  
distance, marked S1/16 S28 BT.

A juniper, 6 ins. diameter, bears S. 82° W., 22 ½ links  
distance, marked S1/16 S29 BT.

Raised a mound of stone, 3 ft. diameter by 1 ½ ft. high, to the  
West of monument.

Corner located on top of ridge bearing S. 60° E., and N. 60° W.,  
surrounded by scattered juniper.

**39.884** The ¼ section corner of sections 28 and 29, monumented with an  
iron rebar, ½ in. diameter, firmly set, projecting 2 ins. above  
the ground, with aluminum cap, 1 ½ ins. diameter, marked LS  
148951. Found a wooden post, 5 ins. diameter by 7 ft. long  
laying next to monument.

Duchesne County Monument Record indicates the position of the  
corner was determined by old existing fence line ties from a  
previous survey. This monument harmoniously fits the original  
corners and is accepted as a careful and faithful establishment  
of the corner.

At the corner point

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 24 ins.  
in the ground, with aluminum cap marked:

T 2 S R 5 W  
1/4  
S 29 | S 28  
2003

No suitable accessories within accepted tolerances.

Deposit a magnet, in a white plastic case, at the base of the  
aluminum post.

Deposit rebar and cap inside the aluminum post.

Witnessed by a steel fence post North - East of monument.

Corner is located South - West, ½ link of intersection of fences  
extending South and East, with cultivated fields to the North  
and West.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

N. 0°06.6' W., beginning new measurement.

**19.892** Point for the North 1/16 section corner of sections 28 and 29.

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 20 ins. in the ground, encircled by a collar of stone, 3 ft. diameter, to the top of aluminum cap marked:

IA N 1/16  
668  
S 29 | S 28  
2003

from which

A wooden fence post, 5 ins., bears S. 57° W., 46 links distance, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY, nailed to the top.

A wooden fence post bears N. 36° W., 1.06 chains distance, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY, nailed to the top.

Set a steel fence post 2 ft. North of corner.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

From this point an iron rebar, 3/8 in. diameter, firmly set, projecting 10 ins. above the ground, with no cap, bears S. 5° 05' E., 19 ½ links distance. This monument was not utilized during the course of this survey.

From this same point an iron rebar, ½ in. diameter, firmly set, projecting 7 ins. above the ground, with no cap, 1 link South - East of corner of fences extending North and West, bears S. 87° 38' W., 5.00 chains distance. This monument was not utilized during the course of this survey.

**21.088** The right bank Duchesne River, course S. 62° E.

**39.784** The corner of sections 20, 21, 28, and 29, monumented with an iron rebar 5/8 in. diameter, firmly set, buried 2 ins. below the ground, with an aluminum cap, 1 ½ ins. diameter, marked LS 148951.

This monument is located at proportionate distance between controlling corners and is accepted as a careful and faithful reestablishment of the position of the corner.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

Set an aluminum rod, 36 ins. long,  $\frac{3}{4}$  ins. diameter, 6 ins. below the ground, with aluminum cap marked:

T 2 S		R 5 W
S 20		S 21
S 29		S 28
IA 668		
2003		

No suitable accessories.

Deposit a magnet, in a white plastic case, and private survey cap below the BLM cap.

Corner is located West, 6  $\frac{1}{2}$  links of new 4-strand barbed wire fence extending North and South, in a cultivated area surrounded by numerous structures.

**N. 0°19.1' E.**, between sections 20 and 21.

**19.892** The South  $\frac{1}{16}$  section corner of sections 20 and 21, monumented with an iron rebar,  $\frac{5}{8}$  in. diameter, firmly set, projecting 6 ins. above the ground, with 1  $\frac{1}{2}$  in. aluminum cap marked PEATROSS RLS 259966.

Not remonumented.

This monument harmoniously fits the controlling corners and is accepted as a careful and faithful establishment of the corner.

**39.784** The  $\frac{1}{4}$  section corner of sections 20 and 21, monumented with an aluminum post, 2  $\frac{1}{2}$  ins. diameter, firmly set, projecting 15 ins. above the ground, encircled by a collar of stone, 3  $\frac{1}{2}$  ft. diameter to top of cap, marked

Duchesne County Survey		
T 2 S		R 5 W
1/4		
S 20		S 21
1979		

from which the original bearing trees

A juniper, 9 ins. diameter, bears N. 84° E., 66 links distance, with visible marks 21 BT. (Record: S. 79° E., 59 links distance).

A piñon, 10 ins. diameter, bears N. 69° W., 24 links distance, with visible marks BT. (Record: S. 70° W., 30 links distance).

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

from which new bearing trees

A juniper, 8 ins. diameter, bears S. 34° E., 94 ½ links  
distance, marked ¼ S21 BT.

A piñon, 5 ins. diameter, bears S. 48° W., 67 links  
distance, marked ¼ S20 BT.

This monument harmoniously fits the original corners and is  
accepted as a careful and faithful perpetuation of the corner.

Corner is located West, 1 ½ links of 4-strand barbed wire fence  
extending N. 7° E., and S. 7° W., and North, 9 links of rock  
gabion, 3 ft. diameter, by 5 ft. high.

From the section corner of sections 28, 29, 32, and 33.

N. 89°58.6' W., between sections 29 and 32.

**19.984** Point for the East 1/16 section corner of sections 29 and 32.

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 8 ins. in  
the ground, with aluminum cap marked:

S 29  
E 1/16 ———  
S 32  
2003

from which

A piñon, 5 ins. diameter, bears N. 30° E., 25 links  
distance, marked with a brass washer, 1 ½ ins. diameter,  
marked BLM CADASTRAL SURVEY, nailed to the South - West  
face.

A juniper, 4 ins. diameter, bears N. 35° W., 17 links  
distance, marked with a brass washer, 1 ½ in. diameter  
marked BLM CADASTRAL SURVEY, nailed to a blaze on the  
South - East face.

Corner is located South, 2.27 chains of gravel road bears East  
and West.

**39.968** The ¼ section corner of sections 29 and 32, monumented with an  
aluminum post, 2 ½ ins. diameter, firmly set, projecting 9 ins.  
above the ground, witnessed by a steel fence post to the West,  
with an unmarked stone, 16 x 7 x 6 ins., along side, with cap  
marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

## Duchesne County Survey

T 2 S R 5 W

S 29

1/4 ———

S 32

1984

from which the remains of the original bearing tree

A dead and downed piñon, 9 ins. diameter, bears N. 32° W.,  
3.11 chains distance, with visible marks S29 BT (Record:  
N. 40° W., 2.30 chains distance).

No remains of other bearing tree remains.

This monument harmoniously fits the original corners and is on  
record at the County Clerk and Recorder's Office, Duchesne  
County, Utah. It is accepted as a careful and faithful  
perpetuation of the corner.

from which new bearing trees

A juniper, 11 ins. diameter, bears N. 01° E., 97 links  
distance, marked with a brass washer, 1 ½ ins. diameter,  
marked BLM CADASTRAL SURVEY.

A juniper, 28 ins. diameter, bears S. 73° E., 1.02 chains  
distance, marked with a brass washer, 1 ½ ins. diameter,  
marked BLM CADASTRAL SURVEY.

Corner is located in valley bottom, North of dry creek bed.

**S. 89°48.2' W.**, beginning new measurement.

**39.889**

The section corner of sections 29, 30, 31, and 32, monumented  
with an iron rebar, 5/8 in. diameter, firmly set, projecting 5  
ins. above the ground, with aluminum cap, 1 ½ ins. diameter,  
marked LS 148951. A sandstone, 2 x 9 x 7 ins., firmly set,  
projecting 12 ins. above the ground, marked with 5 notches on  
the East, 1 notch on the South, set alongside rebar.

from which original bearing trees

A piñon, 13 ins. diameter, bears N. 63° E., 9 links  
distance, marked T2S R5W S32 BT. (Record: N. 77° E., 55  
links distance, marked T2S R5W S29 BT.).

A piñon, 9 ins. diameter, bears S. 51° E., 33 links  
distance, marked T2S R5W S31 BT. (Record: S. 62° E., 18  
links distance, marked T2S R5W S32 BT).

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

A dead and downed piñon, 6 ins. diameter, bears S. 69° W.,  
45 links distance, marked T2S R5W S31 BT. (Record:  
S. 27° W., 92 links distance, marked T2S R5W S31 BT.).

A piñon, 12 ins. diameter, bears N. 57° W., 30 links  
distance, marked T2S R5W S30 BT. (Record: N. 42° W.,  
1.02 chains distance, marked T2S R5W S30 BT.).

from which a tree of unknown origins

A piñon, 11 ins. diameter, bears N. 14° E., 62 links  
distance, marked with illegible scribe marks.

This monument harmoniously fits the original corners and is on  
record at the County Clerk and Recorder's Office, Duchesne  
County, Utah. It is accepted as a careful and faithful  
perpetuation of the corner.

At the corner point

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 20 ins. in  
the ground, encircled by a collar of stone, 2 ft. diameter, to  
the top of aluminum cap marked:

T 2 S	R 5 W
S 30	S 29
S 31	S 32
2003	

Deposit a magnet, in a white plastic case, at the base of the  
aluminum post.

Placed the rebar inside the aluminum post.

Buried the original sandstone on North side of aluminum post.

**N. 89°26.0' W.**, between sections 30 and 31.

**39.034** The ¼ section corner of sections 30 and 31, monumented with a  
sandstone, 6 x 12 x 10 ins., firmly set, projecting 5 ins. above  
the ground, marked ¼ on North face.

from which the original bearing trees

A piñon, 10 ins. diameter, bears N. 9° E., 22 links  
distance, with illegible scribe marks.

A dead and downed piñon, 10 ins. diameter, bears  
S. 17° W., 78 links distance, marked 1/4 S31 BT.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 21 ins. in the ground, encircled by a mound of stone, with aluminum cap marked:

T 2 S R 5 W  
S 30  
1/4 ———  
S 31  
2003

from which new bearing trees

A juniper, 6 ins. diameter, bears N. 58° E., 26 links distance, marked ¼ S30 BT.

A piñon, 5 ins. diameter, bears S. 39° E., 41 links distance, marked ¼ S31 BT.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Buried the original sandstone on West side of aluminum post.

---

S. 88°17.8' W., beginning new measurement.

**36.948** The corner of sections 25, 30, 31, and 36, on the West boundary, hereinbefore described.

---

From the corner of sections 29, 30, 31, and 32.

N. 0°09.8' W., between sections 29 and 30.

**39.754** The ¼ section corner of sections 29 and 30, monumented with an iron rebar, ½ ins. diameter, firmly set, projecting 10 ins. above the ground, with a yellow plastic cap, 1 in. diameter, marked LS 148951. An unmarked sandstone, 20 x 6 x 9 ins., firmly set, projecting 12 ins. above the ground, set alongside rebar.

from which a bearing tree of unknown origin

A juniper, 6 ins. diameter, bears S. 35° E., 48 links distance, with visible marks BT, and marked with a metal ring, 1 in. diameter, marked SURVEY POINT RLS 3817.

This monument harmoniously fits the original corners and is on record at the County Clerk and Recorder's Office, Duchesne County, Utah. It is accepted as a careful and faithful perpetuation of the corner.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 12 ins. in the ground, encircled by a collar of stone, 2 ft. diameter, to the top of aluminum cap marked:

T 2 S R 5 W  
1/4  
S 30 | S 29  
2003

from which a new bearing tree and bearing object

A juniper, 8 ins. diameter, bears N. 72° E., 49 links distance, marked 1/4 S29 BT.

An X B0, chiseled 6 ft. high on vertical sandstone face, bears N. 11° W., 37 links distance.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Placed the rebar and cap inside the aluminum post.

Buried unmarked sandstone alongside aluminum post.

---

N. 0°15.7' W., beginning new measurement.

**19.724** Point for the North 1/16 section corner of sections 29 and 30.

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 22 ins. in the ground, encircled by a collar of stone, 3 ft. diameter, to the top of aluminum cap marked:

N 1/16  
S 30 | S 29  
2003

from which

A piñon, 4 ins. diameter, bears N. 63° E., 40 links distance, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY, nailed to blaze on South - West face.

A juniper, 5 ins. diameter, bears S. 87° W., 40 ½ links distance, marked with a brass washer, marked BLM CADASTRAL SURVEY, nailed to blaze on East face.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

- 39.448** The corner for sections 19, 20, 29, and 30, monumented with an aluminum post, 2 ½ ins. diameter, firmly set, projecting 9 ins. above the ground, with aluminum cap marked:

SECTION CORNER  
 T 2 S  
 S 19 | S 20  
 S 30 | S 29  
 R 5 W  
 LS 4779  
 ALLRED-PEATROSS ASSOC.

from which

A weathered squared-off post, 2 x 2 ins. diameter, firmly set, projecting 32 ins. above the ground, to the East of corner, marked with illegible scribes.

This monument harmoniously fits other found original corners and is accepted as a careful and faithful perpetuation of the corner.

Not remonumented.

Corner is located at the intersection of 2-strand barbed wire fences extending North, South, East, and West.

From the corner of sections 20, 21, 28, and 29, hereinbefore described.

**S. 89°25.4' W.**, between sections 20 and 29.

- 20.062** Point for the East 1/16 section corner of sections 20 and 29, monumented with an iron rebar, 5/8 ins. diameter, firmly set, projecting 5 ins. above the ground, with a yellow plastic cap, 1 ¼ ins. diameter, marked LS 148951.

This monument harmoniously fits the controlling corners and is on record at the County Clerk and Recorder's Office, Duchesne County, Utah. It is accepted as a careful and faithful establishment of the corner.

At the corner point

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 20 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

S 20  
E 1/16           
S 29  
          
IA 668  
2003

No suitable accessories near corner.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Placed the rebar inside the aluminum post.

Corner of old fences extending North, South, and West, bears N. 27° E., 31 ½ links distance from corner.

Corner is located in bottom of the valley, North of the Duchesne River.

- 40.124** The ¼ section corner of sections 20 and 29, monumented with an aluminum post, 2 ½ ins. diameter, firmly set, projecting 12 ins. above the ground, with cap marked:

ALLRED-PEATROSS ASSOC.  
T 2 S R 5 W  
S 20  
          
S 29  
1/4 COR  
1980

No evidence remains of original bearing trees.

from which a new bearing object

A power pole, 12 ins. diameter, bears S. 87° W., 17 links distance, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY.

Witnessed by a steel fence post to the North of corner

This monument harmoniously fits the original corners and is accepted as a careful and faithful perpetuation of the corner.

Corner located in 5-strand barbed wire fence extending East and West.

\_\_\_\_\_

**S. 89°44.2' W.**, beginning new measurement.

- 19.989** Point for the West 1/16 section corner of sections 20 and 29.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 21 ins. in the ground, with aluminum cap marked:

IA 573    IA 689  
          S 20  
W 1/16 ———  
          S 29  
          2003

from which

A juniper fence post, 6 ins. diameter, bears S. 72° W., 5 links distance, marked with a brass washer, marked BLM CADASTRAL SURVEY.

A cottonwood, 8 ins. diameter, bears N. 62° W., 31 links distance, marked X BT.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Corner is located on level ground, North, 3 links of a barbed wire fence extending S. 86° W., and N. 86° E., among cottonwood timber.

**39.978** The corner of sections 19, 20, 29, and 30.

---

From the corner of sections 19, 20, 29, and 30.

**S. 89°40.2' W.**, between sections 19 and 30.

**19.858** Point for the East 1/16 section corner of sections 19 and 30.

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 19 ins. in the ground, encircled by a collar of stone, 4 ft. diameter, by 6 ins. high, with aluminum cap marked:

IA 348  
┌—————  
  S 19  
E 1/16 ———  
          S 30  
          2003

from which

A cottonwood, 14 ins. diameter, bears S. 24° W., 27 links distance, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

A cottonwood, 8 ins. diameter, bears S. 84° W., 47 links distance, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Corner is located in valley bottom, North, 36 links from dry fork of stream bed, drains S. 10° W., surrounded by dense cottonwoods and brush.

**39.716** Point for the ¼ section corner of sections 19 and 30, at proportionate distance, there is no remaining evidence of the original corner.

Buried an aluminum post, 28 ins. long, 2 ½ ins. diameter, 2 ins. below the ground, with aluminum cap marked:

T 2 S R 5 W  
S 19  
1/4 ———  
S 30  
2003

from which

An iron post, 2 ins. diameter, firmly set, projecting 1 in. above the ground, bears S. 25° W., 54 links distance, with a brass cap marked STATE ROAD RIGHT OF WAY MARKER C/L 50 STA 65-174-72 1973.

A power pole, 8 ins. diameter, bears S. 81° 35' W., 1.34 chains distance, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY, nailed to the East face.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Corner located on South edge of State Hwy #35, bears S. 45° E., and N. 45° W.

From this point an iron rebar, 5/8 in. diameter, firmly set, projecting 3 ins. above the ground, with an orange plastic cap, 1 in. diameter, marked PLS 148951, bears S. 34° 59' W., 42 ½ links distance. This monument was not utilized during the course of this survey.

**59.574** Point for the West 1/16 section corner of sections 19 and 30.

Set an aluminum rod, 36 ins. long, ¼ ins. diameter, 26 ins. in the ground, encircled by a collar of stone, 3 ½ ft. diameter, to the top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

S 19  
W 1/16 ———  
S 30  
2003

from which

An X B0 chiseled on the West face of a sandstone boulder,  
4 x 4 x 3 ft., bears N. 80° E., 46 links distance.

A juniper, 4 ins. diameter, bears S. 61° E., 79 links  
distance, marked with a brass washer, 1 ½ ins. diameter,  
marked BLM CADASTRAL SURVEY, nailed to a blaze on the  
West face.

**75.500** The corner of sections 19, 24, 25, and 30.

---

From the corner of sections 19, 20, 29, and 30.

**N. 0°17.8' E.**, between sections 19 and 20.

**19.944** Point for the South 1/16 section corner of sections 19 and 20.

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 24 ins.  
in the ground, encircled by a collar of stone, 6 ins. diameter,  
to the top of aluminum cap marked:

S 1/16  
S 19 | S 20  
IA 348 | IA 573  
2003

from which

A railroad tie fence post, 6 ½ ins. by 8 ½ ins., bears  
N. 41° W., 24 links distance, marked with a brass washer,  
1 ½ ins. diameter, marked BLM CADASTRAL SURVEY, nailed to  
South side of post.

A fence post, 6 ins. diameter, at the corner of fences  
extending North, South, and West, bears N. 17° W., 53  
links distance, marked with a brass washer, 1 ½ ins.  
diameter, marked BLM CADASTRAL SURVEY, nailed to the  
post.

Deposit a magnet, in a white plastic case, at the base of the  
aluminum post.

Corner is located in an open field, East, 16 ½ links of 4-strand  
barbed wire fence extending North and South.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

Corner is witnessed by a steel fence post to the West.

- 39.888** The  $\frac{1}{4}$  section corner of sections 19 and 20, monumented with an aluminum post, 2  $\frac{1}{2}$  ins. diameter, firmly set, projecting 13 ins. above the ground, in an irregular collar of stone, with aluminum cap marked:

ALLRED-PEATROSS ASSOC.

T 2 S R 5 W  
1/4  
S 19 | S 20  
1979

from which original bearing trees

A piñon, 12 ins. diameter, bears N. 41° E., 1.14 chains distance, marked with visible marks  $\frac{1}{4}$  BT. (Record: cedar, blaze faces N. 61° W.).

A juniper, 5 ins. diameter, bears N. 23° W., 56 links distance, marked  $\frac{1}{4}$  S19 BT. (Record: blaze faces N. 22° E.).

This monument harmoniously fits the original corners and is accepted as a careful and faithful perpetuation of the corner.

from which a new bearing tree

A juniper, 7 ins. diameter, bears N. 61° E., 46 links distance, marked  $\frac{1}{4}$  S20 BT.

Set a fence post to the East of monument.

Corner is located on flat ground surrounded by dense piñon and juniper.

---

**N. 0°05.6' E.**, beginning new measurement.

- 20.004** Point for the North  $\frac{1}{16}$  section corner of sections 19 and 20.

Not monumented.

- 40.008** The corner of sections 17, 18, 19, and 20, monumented with aluminum post, 2  $\frac{1}{2}$  ins. diameter, firmly set, projecting 14 ins. above the ground, encircled by a collar of stone, 2 ft. diameter by 8 ins. high, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

## ALLRED-PEATROSS ASSOC.

S 18	S 17
S 19	S 20
1980	

from which the original bearing trees

A juniper, 4 ins. diameter, bears N. 59° E., 52 links distance, marked T2S R5W S17 BT.

A juniper, 6 ins. diameter, bears S. 75° E., 54 links distance, marked T2S R5W S20 BT.

A dead and downed piñon, 8 ins. diameter, bears N. 14° W., 1.69 chains distance, the scribe is axed out (Record: N. 45° W., 1.37 chains distance).

No evidence found of remaining bearing tree.

This monument harmoniously fits the original corners and is accepted as a careful and faithful perpetuation of the corner.

from which new bearing trees

A multi-trunk juniper, 8 ins. diameter, bears S. 45° W., 19 links distance, marked T2S R5W S19 BT.

A multi-trunk juniper, 10 ins. diameter, bears N. 34° W., 54 links distance, marked T2S R5W S18 BT.

Corner witnessed by a steel fence post to the South - East.

Rehabilitate collar of stone, 4 ft. diameter by 8 ins. high.

From the ¼ section corner of sections 17 and 20, monumented with an iron rebar, ½ in. diameter, firmly set, projecting 12 ins. above the ground with an aluminum cap marked:

## ALLRED-PEATROSS

¼
S 17
-----
S 20
1980

A sandstone, 12 x 11 x 7 ins. diameter, firmly set, projecting 12 ins. above the ground, marked ¼ on the North face, set alongside the iron rebar, encircled by a collar of stone, 3 ft. diameter.

from which the original bearing trees

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

A juniper, 6 ins. diameter, bears N. 45° E., 44 ½ links distance, marked ¼ S17 BT (Record: N. 40° 15' E., 46 links distance).

A piñon, 7 ins. diameter, bears S. 06° W., 17 ½ links distance, marked ¼ S20 BT.

This monument harmoniously fits the original corners and is accepted as a careful and faithful perpetuation of the corner.

At the corner point

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 17 ins. in the ground, encircled by a collar of stone, 3 ft. diameter, to the top of aluminum cap marked:

T 2 S R 5 W  
S 17  
1/4 —  
S 20  
2003

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Placed the rebar and cap inside the aluminum post, and buried the original sandstone alongside aluminum post.

Set steel fence post North of monument.

**S. 89° 43.1' W.**, between sections 17 and 20.

**40.156** The corner of sections 17, 18, 19, and 20.

---

From the corner of sections 17, 18, 19, and 20.

**S. 89°18.1' W.**, between sections 18 and 19.

**19.938** Point for the East 1/16 section corner of sections 18 and 19.

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, on a sandstone outcropping, cut a cross (X) at the exact corner point, supported post with a mound of stone 5 ft. base and 2 ft. high, with aluminum cap marked:

S 18  
E 1/16 —  
S 19  
2003

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

from which

A juniper, 10 ins. diameter, bears N. 47° E., 32 links distance, marked X BT.

A juniper, 4 ins. diameter, bears S. 28° W., 41 links distance, marked E1/16 S19 BT.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Corner is located on a sandstone outcropping of West facing slope, above the main road in the Rock Creek drainage.

**38.876** Point selected for the Witness Corner to the ¼ section corner of sections 18 and 19.

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 22 ins. in the ground, encircled by a collar of stone, 2 ft. diameter, to the top of aluminum cap marked:

WC  
T 2 S R 5 W  
S 18  
1/4 ←  
S 19  
2003

from which

A cottonwood, 14 ins. diameter, bears N. 86° E., 35 links distance, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY.

A piñon, 3 ins. diameter, bears S. 21° E., 13 links distance, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Corner is located in an open meadow, surrounded by scattered cottonwood, Russian olive trees, and brush.

**39.876** True point for the ¼ section corner of sections 18 and 19, at proportionate distance falls in a branch of Rock Creek, 10 ft. wide, course South, where it is impracticable to establish a permanent monument; there is no remaining evidence of the original corner.

**59.814** Point for the West 1/16 section corner of sections 18 and 19.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 19 ins. in the ground, encircled by a collar of stone, 2 ft. diameter, to the top of aluminum cap marked:

S 18  
W 1/16 ———  
S 19  
2003

from which

A juniper, 8 ins. diameter, bears S. 28° E., 1.09 chains distance, marked with brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY.

A juniper, 6 ins. diameter, bears N. 52° W., 27 links distance, marked with brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Corner is located on near level ground, surrounded by scattered piñon and juniper.

**75.585** The corner of sections 13, 18, 19, and 24, on the West boundary, hereinbefore described.

---

From the corner of sections 17, 18, 19, and 20.

**N. 0°22.2' E.**, between sections 17 and 18.

**40.197** The ¼ section corner of sections 17 and 18, determined at the distance/distance intersection from the two original bearing trees. No evidence remains of original stone.

from which the original bearing trees

A piñon snag, 6 ins. diameter, bears N. 19° E., 85 links distance, marked with visible marks 17 BT.

A piñon, 12 ins. diameter, bears N. 36° W., 66 links distance, marked ¼ S18 BT.

At the corner point

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 22 ins. in the ground, in a supporting collar of stone, 5 ft. base to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

T 2 S R 5 W  
1/4  
S 18 | S 17  
2003

from which new bearing tree

A piñon, 11 ins. diameter, bears N. 89° E., 37 links  
distance, marked ¼ S17 BT.

Corner located on steep North - West facing slope.

N. 0°03.4' W., beginning new measurement.

## 39.837

The corner of sections 7, 8, 17, and 18, monumented with an iron rebar, ½ ins. diameter, firmly set, flush to ground, with a yellow plastic cap, 1 in. diameter, marked RLS 4779. Found a sandstone, 9 x 5 x 4 ins., unmarked, loosely set on the South side of rebar.

from which the original bearing trees

A juniper, 13 ins. diameter, bears N. 36° E., 95 ½ links  
distance, marked T2S R5W S8 BT (Record: 99 links).

A dead and downed piñon, 5 ins. diameter, bears S. 80° E.,  
63 links distance, marked T2S R5W S17 BT. (Record: S.  
78° E., 79 links distance).

A juniper, 17 ins. diameter, bears S. 48° W., 46 links  
distance, marked T2S R5W S18 BT. (Record: 52 links  
distance).

A juniper, 12 ins. diameter, bears N. 85° W., 29 links  
distance, with visible marks 7 BT, in a partially healed  
blaze. (Record: N. 80° W., 27 links distance).

This monument harmoniously fits the original corners and is on record at the County Clerk and Recorder's Office, Duchesne County, Utah. It is accepted as a careful and faithful perpetuation of the corner.

At the corner point

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 21 ins. in the ground, with aluminum cap marked:

T 2 S R 5 W  
S 7 | S 8  
S 18 | S 17  
2003

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

from which a new bearing tree

A piñon, 5 ins. diameter, bears S. 80° E., 70 links distance, marked T2S R5W S17 BT.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Placed the rebar and cap inside the aluminum post.

Buried unmarked sandstone alongside aluminum post.

Corner is located in valley bottom, surrounded by scattered piñon and juniper.

From the corner of sections 7, 8, 17, and 18.

S. 88°55.4' W., between sections 7 and 18.

19.860

Point for the East 1/16 section corner of sections 7 and 18.

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 24 ins. in the ground, with aluminum cap marked:

S 7  
E 1/16 ———  
S 18  
2003

from which

A multi-trunked juniper, 10 ins. diameter, bears North, 25 links distance, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY, nailed to blaze on East face.

A piñon, 22 ins. diameter, bears West, 26 links distance, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY, nailed to a blaze on the South face.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Corner located on steep North - West facing slope, surrounded by scattered piñon and juniper.

39.720

The ¼ section corner of sections 7 and 18, monumented with a cobblestone, 6 x 14 x 12 ins., firmly set, projecting 6 ins. above an embedded collar of stone, 2 ft. diameter, marked ¼ on North face.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

from which the original bearing tree

A dead and downed piñon, 17 ins. diameter, bears  
S. 40° E., 57 links distance, marked ¼ S18 BT (Record:  
S. 33° E.).

No evidence found of remaining bearing trees.

At the corner point

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 19 ins.  
in the ground, in a supporting collar of stone, 2 ft. diameter  
by 3 ft. high, with aluminum cap marked:

T 2 S R 5 W  
S 7  
1/4 ———  
S 18  
2003

from which

An X B0 chiseled into a 5 x 4 ft., sandstone ledge, bears  
N. 13° E., 25 links distance, marked XBO, approximately  
3 ft. above the ground.

A juniper, 7 ins. diameter, bears S. 57° W., 28 links  
distance, improperly marked ¼ 18 BT.

Deposit a magnet, in a white plastic case, at the base of the  
aluminum post.

Buried the cobblestone on North - East side of aluminum post.

Corner located half way up on a very steep South - West facing  
slope, above Rock Creek drainage.

---

S. 89°41.3' W., beginning new measurement.

**35.719** The corner of sections 7, 12, 13, and 18, on the West boundary,  
hereinbefore described.

---

From the corner of sections 7, 8, 17, and 18.

N. 0°37.4' W., between sections 7 and 8.

**40.087** Point for the ¼ section corner of sections 7 and 8, at  
proportionate distance, found original sandstone, 7 x 9 x 15  
ins., marked ¼, lying loose in a ravine; found dead and downed  
piñon, 8 ins. diameter, with visible marks 4 8 BT; unable to  
determine root hole.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

Set an aluminum post, at proportionate distance, 28 ins. long, 2 ½ ins. diameter, 21 ins. in the ground, encircled by a collar of stone, 2 ft. diameter, to the top of aluminum cap marked:

T 2 S R 5 W  
1/4  
S 7 | S 8  
2003

from which new bearing trees

A piñon, 6 ins. diameter, bears S. 78° E., 67 links distance, marked ¼ S8 BT.

A juniper, 6 ins. diameter, bears S. 83° W., 16 links distance, marked ¼ S7 BT.

Buried the original sandstone on West side of aluminum post.

Corner is located at the edge of a mesa, overlooking a ravine, bearing North - East and South - West, surrounded by scattered piñon and juniper.

**80.174**

The corner of sections 5, 6, 7, and 8, monumented with an iron rebar, ½ in. diameter, firmly set, projecting 10 ins. above the ground, with a orange plastic cap, 1 in. diameter, marked RLS 148951, encircled by a loose collar of stone, 2 ft. diameter. An unmarked sandstone, 16 x 8 x 12 ins., set on the South side of rebar.

from which the original bearing trees

A piñon, 11 ins. diameter, bears N. 63° E., 1.07 chains distance, marked T2S R5W S5 BT. (Record: N. 50° E., 65 links).

A piñon, 8 ins. diameter, bears S. 23° W., 67 links distance, marked T2S R5W S7 BT. (Record: S. 45° W., 62 links).

No evidence found of remaining bearing trees.

from which a tree of unknown origin

A piñon, 12 ins. diameter, bears N. 05° E., 77 links distance, marked with illegible scribe marks.

This monument harmoniously fits the original corners and is on record at the County Clerk and Recorder's Office, Duchesne County, Utah. It is accepted as a careful and faithful perpetuation of the corner.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 20 ins. in the ground, encircled by a collar of stone, 3 ft. diameter, to the top of aluminum cap marked:

T 2 S	R 5 W
S 6	S 5
S 7	S 8
2003	

from which the new bearing trees

A juniper, 6 ins. diameter, bears S. 48° E., 70 links distance, marked T2S R5W S8 BT.

A piñon, 5 ins. diameter, bears N. 35° W., 15 ½ links distance, marked X BT.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Placed the rebar and cap inside the aluminum post.

Buried the unmarked sandstone on West side of aluminum post.

Corner is located near the top of South - East facing slope, above a deep ravine, surrounded by scattered piñon and juniper.

From the corner of sections 5, 6, 7, and 8.

S. 89°34.8' W., between sections 6 and 7.

**39.500**

The ¼ section corner of sections 6 and 7, monumented with an iron rebar, 5/8 ins. diameter, firmly set, projecting 8 ins. above the ground, in a loose collar of stone, 2 ft. diameter, with a plastic yellow cap, 1 in. diameter, marked LS 3817. Found an embedded, unmarked stone, 15 x 10 x 6 ins., set North of rebar.

from which

A juniper, 12 ins. diameter, bears S. 01° E., 55 links distance, with illegible scribe marks (Record: S. 10° E., marked ¼ S7 BT).

No evidence found of remaining bearing tree.

This monument harmoniously fits the original corners and is on record at the County Clerk and Recorder's Office, Duchesne County, Utah. It is accepted as a careful and faithful perpetuation of the corner.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 18 ins. in the ground, encircled by a collar of stone, 3 ft. diameter, to the top of aluminum cap marked:

T 2 S R 5 W  
S 6  
1/4 ———  
S 7  
2003

from which

A piñon, 8 ins. diameter, bears N. 54° E., 67 links distance, marked ¼ S6 BT.

A juniper, 4 ins. diameter, bears S. 14° W., 37 links distance, marked ¼ S7 BT.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Placed the rebar and cap inside the aluminum post.

Corner is located on a gently sloping South - East facing mesa, surrounded by scattered piñon and juniper. Significant wood cutting in the area.

---

S. 87°31.1' W., beginning new measurement.

**19.789** Point for the West 1/16 section corner of sections 6 and 7.

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 21 ins. in the ground, encircled by a collar of stone, 4 ft. diameter, to the top of aluminum cap marked:

S 6  
W 1/16 ———  
S 7  
2003

from which

A juniper, 18 ins. diameter, bears N. 20° E., 56 links distance, marked W 1/16 S6 BT.

A juniper, 5 ins. diameter, bears S. 24° E., 24 links distance, marked W 1/16 S7 BT.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

From this point an iron rebar,  $\frac{1}{2}$  in. diameter, firmly set, projecting 23 ins. above the ground, encircled by a collar of stone, 2 ft. diameter by 6 ins. high, with cap marked PEATROSS RLS 155666, bears N.  $43^{\circ} 53'$  E., 2.960 chains distance. The purpose of this monument is unknown and it was not utilized during the course of this survey.

From this point a PVC pipe, 2 ins. diameter, projecting 15 ft. above the ground, bears West, 10 links distance.

Corner is located in a shallow gully bearing East, at the base of a small hill, surrounded by scattered piñon and juniper.

- 35.026** The corner of sections 1, 6, 7, and 12, on the West boundary, hereinbefore described.

---

**Subdivision of Section 7,  
Township 2 South, Range 5 West, Uintah Special Meridian, Utah**

---

From the  $\frac{1}{4}$  section corner of sections 7 and 18, hereinbefore described.

**N.  $0^{\circ}28.5'$  W.**, on the North and South center line of section 7.

- 19.973** The Center South  $\frac{1}{16}$  section corner of section 7, monumented with an iron rebar,  $\frac{1}{2}$  in. diameter, firmly set, projecting 9 ins. above the ground, with a plastic cap marked: LS 148951.

This is accepted as a careful and faithful establishment of the corner.

Not remonumented.

---

**N.  $0^{\circ}28.4'$  W.**, beginning new measurement.

- 19.972** The Center  $\frac{1}{4}$  section corner of section 7, at the intersection with the East and West center line, monumented with an iron rebar,  $\frac{5}{8}$  in. diameter, firmly set, projecting 14 ins. above the ground, with a yellow plastic cap marked RLS 148951.

This monument harmoniously fits the controlling corners and is on record at the County Clerk and Recorder's Office, Duchesne County, Utah. It is accepted as a careful and faithful establishment of the corner.

At the corner point

Set an aluminum post, 28 ins. long,  $2\frac{1}{2}$  ins. diameter, 18 ins. in the ground, encircled by a collar of stone, 3 ft. diameter, to the top of aluminum cap marked:

SUBDIVISION OF SECTION 7,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

T 2 S R 5 W  
C 1/4 S 7  
2003

from which

A juniper, 4 ins. diameter, bears S. 37° E., 13 links distance, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY, nailed to a blaze on the North - West face.

A juniper, 3 ins. diameter, bears S. 28° W., 13 ½ links distance, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY, nailed to a blaze on the North - East face.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Placed the rebar and cap inside the aluminum post.

- 30.148** The Center South - North 1/64 section corner of section 7, monumented with an iron rebar, 5/8 in. diameter, firmly set, projecting 10 ins. above the ground, with a yellow plastic cap marked RLS 178951.

This monument harmoniously fits the controlling corners and is on record at the County Clerk and Recorder's Office, Duchesne County, Utah. It is accepted as a careful and faithful establishment of the corner.

Not remonumented.

- 40.317** The Center North 1/16 section corner of section 7, monumented with an iron rebar, ½ in. diameter, firmly set, projecting 12 ins. above the ground, with a yellow plastic cap marked RLS 148951.

This monument harmoniously fits the controlling corners and is on record at the County Clerk and Recorder's Office, Duchesne County, Utah. It is accepted as a careful and faithful establishment of the corner.

Not remonumented.

- 50.488** The Center North - North 1/64 section corner of section 7, monumented with an iron rebar, ½ in. diameter, firmly set, projecting 15 ins. above the ground, with an illegibly marked yellow plastic cap.

SUBDIVISION OF SECTION 7,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

This monument harmoniously fits the controlling corners and is on record at the County Clerk and Recorder's Office, Duchesne County, Utah. It is accepted as a careful and faithful establishment of the corner.

Not remonumented.

**60.655** The ¼ section corner of sections 6 and 7.

---

From the ¼ section corner of sections 7 and 8.

**S. 88° 43.1' W.**, on the East and West center line of section 7.

**29.711** The Center West - East 1/64 section corner of section 7, monumented with an iron rebar, 5/8 in. diameter, firmly set, projecting 6 ins. above the ground, with a yellow plastic cap marked RLS 148951.

This monument harmoniously fits the controlling corners and is on record at the County Clerk and Recorder's Office, Duchesne County, Utah. It is accepted as a careful and faithful establishment of the corner.

Not remonumented.

---

**S. 88°42.9' W.**, beginning new measurement.

**9.901** The Center ¼ section corner of section 7.

---

**S. 88°43.0' W.**, beginning new measurement.

**19.978** Point for the Center West 1/16 section corner of section 7.

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 24 ins. in the ground, with aluminum cap marked:

W 1/16  
C ——— C  
S 7  
2003

from which

A juniper, 13 ins. diameter, bears N. 25° E., 21 links distance, marked X BT.

A juniper, 16 ins. diameter, bears N. 62° W., 23 links distance, marked C W 1/16 S7 BT.

SUBDIVISION OF SECTION 7,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

- 35.471** The  $\frac{1}{4}$  section corner of sections 7 and 12, on the West boundary, hereinbefore described.

---

From the Center West  $\frac{1}{16}$  section corner of section 7, hereinbefore described.

**N.  $0^{\circ}11.6'$  W.**, on the North and South center line of the North - West  $\frac{1}{4}$  of section 7.

- 40.273** The West  $\frac{1}{16}$  section corner of sections 6 and 7.

---

**Subdivision of Section 18,  
Township 2 South, Range 5 West, Uintah Special Meridian, Utah**

---

From the True Point for the  $\frac{1}{4}$  section corner of sections 18 and 19.

**N.  $0^{\circ}16.0'$  E.**, on the North and South center line of section 18.

- 39.891** Point for the Center  $\frac{1}{4}$  section corner of section 18, at the intersection with the East and West center line.

Set an aluminum post, 28 ins. long,  $2\frac{1}{2}$  ins. diameter, 18 ins. in the ground, encircled by a collar of stone, 3 ft. diameter, to the top of aluminum cap marked:

T 2 S R 5 W  
C  $\frac{1}{4}$  S 18  
2003

from which

A cottonwood, 15 ins. diameter, bears S.  $70^{\circ}$  E., 41 links distance, marked with a brass washer,  $1\frac{1}{2}$  ins. diameter, marked BLM CADASTRAL SURVEY, nailed to the blaze on the North - West face.

Corner located East,  $63\frac{1}{2}$  links of left bank of Rock Creek, course South.

- 79.774** The  $\frac{1}{4}$  section corner of sections 7 and 18.

---

From the  $\frac{1}{4}$  section corner of sections 17 and 18.

**S.  $88^{\circ} 51.9'$  W.**, on the East and West center line of section 18.

SUBDIVISION OF SECTION 18,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

**19.975** Point for the Center East 1/16 section corner of section 18.

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 14 ins. in the ground, encircled by a collar of stone, 3 ½ ft. diameter, to the top of aluminum cap marked:

E 1/16  
C———C  
S 18  
2003

from which

A juniper, 11 ins. diameter, bears N. 37° E., 15 ½ links distance, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY, nailed to South - West face.

A piñon, 17 ins. diameter, bears West, 29 links distance, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY, nailed to a blaze on the East face.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Corner is located at the base of a West facing slope.

**39.950** The Center ¼ section corner of section 18.

**75.782** The ¼ section corner of sections 13 and 18 on the West boundary, hereinbefore described.

---

From the Center East 1/16 section corner of section 18.

**N. 0°06.3' E.**, on the North and South center line of the North - East ¼ of section 18.

**39.860** The East 1/16 section corner of sections 7 and 18, hereinbefore described.

---

From the East 1/16 section corner of sections 18 and 19, hereinbefore described.

**N. 0°19.1' E.**, on the North and South center line of the South - East ¼ of section 18.

**40.044** The Center East 1/16 section corner of section 18.

SUBDIVISION OF SECTION 19,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

---

**Subdivision of Section 19,  
Township 2 South, Range 5 West, Uintah Special Meridian, Utah**

---

From the  $\frac{1}{4}$  section corner of sections 19 and 30.

**N. 0°04.6' E.**, on the North and South center line of section 19.

**19.896** Point for the Center South 1/16 section corner of section 19.

Set an aluminum post, 30 ins. long, 2  $\frac{1}{2}$  ins. diameter, 25 ins. in the ground, encircled by a collar of stone, 2 ft. diameter, to the top of aluminum cap marked:

IA	IA
526	561
	C
S 1/16	S 19
	C
	2003

from which

A multi-trunk cottonwood, 12 ins. diameter, bears  
N. 69° W., 1.05 chains distance, marked with a brass  
washer, 1  $\frac{1}{2}$  ins. diameter, marked BLM CADASTRAL SURVEY,  
nailed to a blaze on the East face.

A wood gate post, 4 ins. diameter, 8 ft. high, bears  
N. 10° W., 1.06 chains distance, marked with a brass  
washer marked BLM CADASTRAL SURVEY, nailed to the South  
face.

Deposit a magnet, in a white plastic case, at the base of the  
aluminum post.

Corner is located South, 1.05 chains distance of a fence  
extending East and West.

From this point, a locally established corner bears  
N. 22° 07' W., 1.12 chains distance, monumented with a wooden  
stake, 2 ins. squared, firmly set, projecting 18 ins. above the  
ground, illegibly scribed on the North - East, South - East, and  
South - West faces, with an iron rebar, 5/8 in., with an orange  
plastic cap, 1 in. diameter, marked PLS 148951, set along the  
North - West side of wooden stake. This monument is located  
West, 5 links of corner of fences extending East, West, and  
North. This monument was not utilized during the course of this  
survey.

SUBDIVISION OF SECTION 19,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

From this same point an iron rebar, 5/8 in. diameter, firmly set, projecting 4 ins. above the ground, with an orange plastic cap, 1 in. diameter, marked PLS 148951, bears S. 35° 20' W., 32 ¼ links distance. This monument was not utilized during the course of this survey.

**39.792** Point for the Center ¼ section corner of section 19, at the intersection with the East and West center line.

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 25 ins. in the ground, encircled by a collar of stone, 3 ft. diameter, to the top of aluminum cap marked:

IA  
525  
T 2 S R 5 W  
C 1/4 S 19  
2003  
IA IA  
526 561

from which

A wood fence post, 3 ins. diameter, bears S. 83° W., 43 links distance, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY, nailed to the East face.

A wood gate post, 8 x 6 ins., bears N. 19° W., 1.23 chains distance, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY, nailed to the top.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Set a steel fence post to the North of corner.

Corner is located East, 42 ½ links of a fence extending North and South.

From this point an iron rebar, 5/8 in. diameter, firmly set, projecting 5 ins. above the ground, with an orange plastic cap, 1 in. diameter, marked PLS 148951, bears S. 35° 24' W., 21 ½ links distance. This monument was not utilized during the course of this survey.

From this same point an iron rebar, 5/8 in. diameter, firmly set, projecting 4 ins. above the ground, with an orange plastic cap, 1 in. diameter, marked 148951, bears N. 20° 14' W., 1.24 chains distance. This monument was not utilized during the course of this survey.

**59.716** Point for the Center North 1/16 section corner of section 19.

SUBDIVISION OF SECTION 19,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 19 ins. in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{C} \\ \text{N } 1/16 \quad | \quad \text{S } 19 \\ \hline \text{IA } 525 \quad | \\ \text{2003} \end{array}$$

from which

A multi-trunk cottonwood, 8 ins. diameter, bears S. 27° E., 41 ½ links distance, marked with brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Corner is located West, ½ link distance, of 4 strand barbed wire fence extending N. 20° E. and S. 20° W.

**79.640** True point for the ¼ section corner of sections 18 and 19, hereinbefore described.

---

From the ¼ section corner of sections 19 and 20.

**S. 89°31.9' W.**, on the East and West center line of section 19.

**19.933** Point for the Center East 1/16 section corner of section 19.

Buried an aluminum rod, 36 ins. long, ¾ ins. diameter, 5 ½ ins. beneath dirt road, with aluminum cap marked:

$$\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 19 \\ \hline \text{IA } 561 \\ \text{2003} \end{array}$$

from which

An aluminum post, 28 ins. long, 2½ ins. diameter, set 17 ins. in the ground, encircled by a collar of stone, 1 ½ ft. diameter, by 6 ins. high, for a reference monument, bears N. 81° E., 51 links distance with brass cap marked RM 33.4 FT. CE 1/16 S19 2003 and an arrow pointing to the corner. Deposit a magnet, in a white plastic case, at the base of the aluminum post.

SUBDIVISION OF SECTION 19,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

An aluminum post, 28 ins. long, 2½ ins. diameter, set 20 ins. in the ground, encircled by a collar of stone, 2 ft. diameter, to cap, for a reference monument, bears N. 12° W., 45 ½ links distance with brass cap marked RM 30.0 FT. CE 1/16 S 19 2003 and an arrow pointing to the corner. Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Deposit a magnet, in a white plastic case, at the base of the aluminum rod.

Corner is located North, 12 links distance, from center line of dirt road, 20 ft. wide, bears S. 63° E., and N. 67° W.

**39.866** The Center ¼ section corner of section 19.

**59.764** The Center West 1/16 section corner of section 19, monumented with an iron rebar, 5/8 in. diameter, firmly set, projecting 8 ins. above the ground, with a plastic cap, 1 ½ ins. diameter, marked PLS 148951.

This monument harmoniously fits the controlling corners and is on record at the County Clerk and Recorder's Office, Duchesne County, Utah. It is accepted as a careful and faithful establishment of the corner.

At the corner point

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 24 ins. in the ground, with aluminum cap marked:

IA 525  
W 1/16  
C———C  
S 19  
IA 527 IA 526  
2003

from which

A juniper fence post, bears S. 14° E., 9 links distance, marked with brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Placed the rebar and cap inside the aluminum post.

Corner is located on near level ground, among dense river bottom brush.

SUBDIVISION OF SECTION 19,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

Fence post bears S. 14° E., 8 ¾ links from fence line extending East.

- 75.612** True point for the ¼ section corner of sections 19 and 24, on the West boundary of the township, hereinbefore described.
- 

From the Center East 1/16 section corner of section 19.

**N. 0°05.1' E.**, on the North and South center line of the North - East ¼ of section 19.

- 19.964** Point for North - East 1/16 section corner of section 19, at intersection with the East and West center line of the North - East ¼ of section 19.

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 20 ins. in the ground, encircled by a collar of stone, 2 ft. base, to the top of aluminum cap marked:

NE 1/16 S 19  
2003

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Corner is located on level ground, East, 44 links of sandstone ledge, surrounded by piñon and juniper.

- 39.928** The East 1/16 section corner of sections 18 and 19, hereinbefore described.
- 

From the point for the North 1/16 section corner of sections 19 and 20, not monumented:

**S. 89°25.0' W.**, on the East and West center line of the North - East ¼ of section 19.

- 19.935** The North East 1/16 section corner of section 19.

- 39.870** The Center North 1/16 section corner of section 19.
- 

From the East 1/16 section corner of sections 19 and 30.

**N. 0°11.2' E.**, on the North and South center line of the South - East ¼ of section 19.

- 19.920** Point for the South - East 1/16 section corner of section 19, at intersection with the East and West center line of the South - East ¼ of section 19.

SUBDIVISION OF SECTION 19,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 22 ins. in the ground, encircled by a collar of stone, 3 ft. diameter, to the top of aluminum cap marked:

IA  
561  
SE 1/16 S 19  
2003  
IA  
348

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

From this point the corner of fences extending East, West, and North, bears N. 20° E., 86 ⅓ links distance, with wood post, 2 x 2 ins., 3 ½ ft. long, wired to East face.

Corner is located in an open field, South, 84 ¾ links of fence extending East and West.

**39.840** The Center East 1/16 section corner of section 19.

---

From the South 1/16 section corner of sections 19 and 20,

**S. 89°36.1' W.**, on the East and West center line of the South - East ¼ of section 19.

**19.896** The South East 1/16 section corner of section 19.

**39.792** The Center South 1/16 section corner of section 19.

---

From the West 1/16 section corner of sections 19 and 30.

**N. 0°01.0' E.**, on the North and South center line of the South - West ¼ of section 19.

**17.629** Point selected for a Witness Corner to the South - West 1/16 section corner of section 19.

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 21 ins. in the ground, encircled by a collar of stone, 2 ½ ft. diameter, to the top of aluminum cap marked:

WC  
IA 527 ↑ IA 526  
SW 1/16 S 19  
2003

SUBDIVISION OF SECTION 19,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

from which

A wood power pole, 10 ins. diameter, bears S. 84° W., 15 links distance, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Corner is located North, 77 ¼ links of the center line of Duchesne County Hwy. #35, bears S. 64° E., and N. 64° W.

Corner is located South, 1.00 chain of right bank of the Duchesne River, course is generally South - East.

Corner falls South, 4 ½ links of a barbed wire fence, extending N. 72° W. and S. 56° E.

**19.871** True point for the South - West 1/16 section corner of section 19, at the intersection of the East and West center line of the South - West ¼ of section 19, falls near the right bank of the Duchesne River. It is impracticable to establish a permanent monument.

**39.742** The Center West 1/16 section corner of section 19.

---

From the Center South 1/16 section corner of section 19.

**S. 89°36.1' W.**, on the East and West center line of the South - West ¼ of section 19.

**19.878** True point for the South - West 1/16 section corner of section 19.

**35.765** The South 1/16 section corner of sections 19 and 24, on the West boundary of the township, hereinbefore described.

---

From the Center West 1/16 section corner of section 19.

**N. 0°01.0' E.**, on the North and South center line of the North - West ¼ of section 19.

**19.884** Point for the North - West 1/16 section corner of section 19, at the intersection with the East and West center line of the North - West ¼.

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 19 ins. in the ground, with aluminum cap marked:

SUBDIVISION OF SECTION 19,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

NW 1/16 S 19  
IA 525  
2003

from which

A piñon, 6 ins. diameter, bears N. 30° E., 13 ½ links distance, marked with brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY.

A juniper, 6 ins. diameter, bears N. 74° W., 12 ½ links distance, marked with brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Corner is located on a South slope, North, 10 ½ links distance from the center line of an abandoned irrigation ditch, 3 ft. wide, course S. 70° E., surrounded by piñon and juniper.

**39.768** The West 1/16 section corner of sections 18 and 19.

---

From the Center North 1/16 section corner of section 19.

**S. 89°25.0' W.**, on the East and West center line of the North - West ¼ of section 19.

**19.918** The North - West 1/16 section corner of section 19.

**35.728** The North 1/16 section corner of sections 19 and 24, on the West boundary of the township, hereinbefore described.

---

**Subdivision of Section 20,  
Township 2 South, Range 5 West, Uintah Special Meridian, Utah**

---

From the ¼ section corner of sections 20 and 29.

**N. 0°19.6' E.**, on the North and South center line of section 20.

**19.973** Point for the Center South 1/16 section corner of section 20, monumented with an iron rebar, 5/8 in. diameter, firmly set, projecting 15 ins. above the ground, with an orange plastic cap, 1 ¼ ins. diameter, marked PLS 148951. Found a wood post, 2 x 2 ins., alongside rebar, marked with illegible scribes.

SUBDIVISION OF SECTION 20,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

This monument harmoniously fits the controlling corners and is on record at the County Clerk and Recorder's Office, Duchesne County, Utah. It is accepted as a careful and faithful establishment of the corner.

At the corner point

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 18 ins. in the ground, in a collar of stone, 3 ft. diameter by 6 ins high, with aluminum cap marked:

C S 1/16 S 20  
IA 689 |  
2003

from which

A piñon, 4 ins. diameter, bears S. 83° E., 36 links distance, marked X BT.

A juniper, 6 ins. diameter, bears S. 29° W., 16 links distance, marked X BT.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Placed the rebar and cap inside the aluminum post.

A mound of stone, 3 ft. base, 2 ft. high, bears N. 29° E., 26 links distance.

**39.946**

The Center ¼ section corner of section 20, at the intersection with the East and West center line, monumented with an iron rebar, 5/8 in. diameter, firmly set, projecting 14 ins. above the ground, with a plastic cap, 1 ¼ ins. diameter, marked RLS 148951.

This monument harmoniously fits the controlling corners and is on record at the County Clerk and Recorder's Office, Duchesne County, Utah. It is accepted as a careful and faithful establishment of the corner.

At the corner point

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 20 ins. in the ground, encircled by a collar of stone, 3 ft. diameter, to the top of aluminum cap marked:

T 2 S R 5 W  
C 1/4 S 20  
2003

SUBDIVISION OF SECTION 20,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

from which

A piñon, 5 ins. diameter, bears S. 53° W., 49 links distance, marked X BT.

A juniper, 6 ins. diameter, bears N. 62° W., 51 links distance, marked C $\frac{1}{4}$  S20 BT.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Placed the rebar and cap inside the aluminum post.

Corner is located on a steep East facing slope, slightly below the top of the slope, surrounded by scattered piñon and juniper.

- 59.930** Point for the Center North 1/16 section corner of section 20, monumented with an iron rebar, 5/8 in. diameter, firmly set, projecting 14 ins. above the ground, with a yellow plastic cap, 1  $\frac{3}{4}$  ins. diameter, marked RLS 148951.

This monument harmoniously fits the controlling corners and is on record at the County Clerk and Recorder's Office, Duchesne County, Utah. It is accepted as a careful and faithful establishment of the corner.

Not remonumented.

- 79.913** The  $\frac{1}{4}$  section corner of sections 17 and 20.

---

From the  $\frac{1}{4}$  section corner of sections 20 and 21.

---

S. 89°39.3' W., on the East and West center line of section 20.

- 20.056** Point for the Center East 1/16 section corner of section 20, monumented with an iron rebar, 5/8 in. diameter, firmly set, projecting 13 ins. above the ground, encircled by a collar of stone, 2 ft. diameter, by 8 ins. high, with a plastic cap, 1  $\frac{1}{4}$  ins. diameter, marked RLS 148951.

This monument harmoniously fits the controlling corners and is on record at the County Clerk and Recorder's Office, Duchesne County, Utah. It is accepted as a careful and faithful establishment of the corner.

Not remonumented.

Corner falls on the North edge of a large, flat mesa, surrounded by scattered piñon and juniper.

SUBDIVISION OF SECTION 20,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

From this point an iron rebar, 5/8 in. diameter, firmly set, projecting 16 ins. above the ground, with a yellow plastic cap, 1 1/4 ins. diameter, marked 3817, bears S. 89° 52' W., 10.0 chains distance. This monument was not utilized during the course of this survey.

**40.112** The Center 1/4 section corner of section 20.

**60.110** Point for the Center West 1/16 section corner of section 20.

Not monumented.

**80.108** The 1/4 section corner of sections 19 and 20.

---

From the East 1/16 section corner of sections 20 and 29.

**N. 0°19.4' E.**, on the North and South center line of the South - East 1/4 of section 20.

**19.932** Point for the South - East 1/16 section corner of section 20, at the intersection with the East and West center line of the South - East 1/4 of section 20, monumented with an iron rebar, 5/8 in. firmly set, projecting 11 ins. above the ground, encircled by a collar of stone, 2 ft. diameter by 6 ins. high, with an aluminum cap, 1 1/2 ins. diameter, marked RLS 259966 PEATROSS.

This monument harmoniously fits the controlling corners and is on record at the County Clerk and Recorder's Office, Duchesne County, Utah. It is accepted as a careful and faithful establishment of the corner.

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diameter, 18 ins. in the ground, encircled by a collar of stone, 3 ft. diameter, to the top of aluminum cap marked:

SE 1/16 S 20  
2003

from which

A piñon, 7 ins. diameter, bears S. 49° W., 36 links distance, marked with a brass washer, 1 1/2 ins. diameter, marked BLM CADASTRAL SURVEY.

A juniper, 4 ins. diameter, bears N. 48° W., 20 links distance, marked with a brass washer, 1 1/2 ins. diameter, marked BLM CADASTRAL SURVEY.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

SUBDIVISION OF SECTION 20,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

Placed the rebar and cap inside the aluminum post.

Corner is located at the edge of a mesa, which immediately falls off to the South, to a road below.

**39.864** The Center East 1/16 section corner of section 20.

---

From the South 1/16 section corner of sections 20 and 21.

**S. 89°32.3' W.**, on the East and West center line of South - East ¼ of section 20.

**20.059** The South - East 1/16 section corner of section 20.

**30.091** Point for the Center West - South - East 1/64 of section 20, monumented with an iron rebar, 5/8 in. diameter, firmly set, projecting 18 ins. above the ground, with an orange cap, 1 ¼ ins. diameter, marked RLS 148951.

This monument harmoniously fits the controlling corners and is on record at the County Clerk and Recorder's Office, Duchesne County, Utah. It is accepted as a careful and faithful establishment of the corner.

Not remonumented.

---

**S. 89°32.7' W.**, beginning new measurement.

**10.026** The Center South 1/16 section corner of section 20.

---

From the West 1/16 section corner of sections 20 and 29.

**N. 0°18.7' E.**, on the North and South center line of the South - West ¼ of section 20.

**19.959** Point for the South - West 1/16 section corner of section 20 at intersection of the East and West center line of the South - West ¼ of section 20, monumented with an iron rebar, 5/8 in. diameter, firmly set, projecting 5 ins. above the ground, with an orange plastic cap, 1 ¼ ins. diameter, marked PLS 148951.

This monument harmoniously fits the controlling corners and is accepted as a careful and faithful establishment of the corner.

At the corner point

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 20 ins. in the ground, with aluminum cap marked:

SUBDIVISION OF SECTION 20,  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

SW 1/16 S 20	
IA 573	IA 689
2003	

from which

A deciduous tree, 9 ins. diameter, bears S. 52° E.,  
9 links distance, marked with a brass washer, 1 ½ ins.  
diameter, marked BLM CADASTRAL SURVEY.

A juniper, 4 ins. diameter, bears S. 64° W., 35 links  
distance, marked X BT.

Deposit a magnet, in a white plastic case, at the base of the  
aluminum post.

Placed the rebar and cap inside the aluminum post.

Corner is located South, 53 links of center line of paved road,  
44 links wide, bears East and West.

**39.918** The Center West 1/16 section corner of section 20.

---

From the Center South 1/16 section corner of section 20.

**S. 89°41.8' W.**, on the East and West center line of the South -  
West ¼ of section 20.

**19.994** The South - West 1/16 section corner of section 20.

**39.988** The South 1/16 section corner of sections 19 and 20.

---

**Subdivision of Section 29,  
Township 2 South, Range 5 West, Uintah Special Meridian, Utah**

---

From the ¼ section corner of sections 29 and 32.

**N. 0°08.5' W.**, on the North and South center line of section 29.

**19.871** Point for the Center South 1/16 section corner of section 29.

Set a brass tablet, 3 ¼ ins. diameter, 3 ½ ins. stem, cemented  
in a drill hole in sandstone rock, with top marked:

C	
S 1/16	S 29
C	
2003	

SUBDIVISION OF SECTION 29  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

from which

A juniper, 4 ins. diameter, bears S. 42° E., 18 links distance, marked X BT.

A juniper, 10 ins. diameter, bears S. 71° W., 52 links distance, marked S 1/16 S29 BT.

Corner is located on a gentle South - West facing slope, North - West of oil field production pad, surrounded by sandstone outcrops and scattered piñon and juniper.

**39.742** Point for the Center ¼ section corner of section 29, at the intersection with the East and West center line.

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 18 ins. in the ground, encircled by a collar of stone, 3 ft. diameter, by 7 ins. high, with aluminum cap marked:

T 2 S R 5 W  
C 1/4 S 29  
2003

from which

A piñon, 8 ins. diameter, bears N. 32° E., 48 links distance, marked X BT.

A juniper, 8 ins. diameter, bears S. 33° E., 25 links distance marked C¼ S29 BT.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Corner is located on South facing slope, surrounded by scattered piñon and juniper.

**56.593** Center line of Utah State Hwy. #35, bears S. 60° E., and N. 60° W.

**57.248** The North right-of-way fence for Utah State Hwy. #35, bears S. 60° E., and N. 60° W.

**59.495** Point for the Center North 1/16 section corner of section 29.

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, flush with the ground, marked:

C  
N 1/16 | S 29  
C  
2003

SUBDIVISION OF SECTION 29  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

from which

The center of western-most rock pillar of entrance gate,  
2½ x 2½ x 7 ft., bears S. 8° E., 2.39 chains distance.

The corner of fences extending S. 35° E., N. 35° W., and  
West, bears S. 51° E., 31 links distance.

The center of vertical stand pipe of a well, 6 ft.  
diameter, bears S. 17° W., 44 links distance.

A vertical steel pipe, 1 ¼ ins. diameter, projecting 3 ft.  
above the ground, for water faucet, bears S. 29° 30' W.,  
23 ½ links distance.

Deposit a magnet, in a white plastic case, at the base of the  
aluminum post.

From this point, an iron rebar, 5/8 in. diameter, firmly set,  
projecting 4 ins. above the ground, with a yellow plastic cap,  
marked PLS 148951, located in the North right-of-way fence of  
State Hwy. #35, bears S. 87°32' W., 9.99 chains distance. This  
monument was not utilized during the course of this survey.

**79.248** The ¼ section corner of sections 20 and 29.

---

From the ¼ section corner of sections 28 and 29.

**S. 89°49.2' W.**, on the East and West center line of section 29.

**20.053** Point for the Center East 1/16, not monumented.

**40.106** The Center ¼ section corner of section 29.

**80.007** The ¼ section corner of sections 29 and 30.

---

From the point for the Center East 1/16 section corner of  
section 29, not monumented.

**N. 0°07.5' W.**, on the North and South center line of the North -  
East ¼ of section 29.

**19.823** Point for the North - East 1/16 section corner of section 29, at  
the intersection of the East and West center line of the North -  
East ¼.

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 24 ins.  
in the ground, with aluminum cap marked:

SUBDIVISION OF SECTION 29  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

IA  
668  
NE 1/16 S 29  
2003

from which

A wood fence post, bears N. 31° W., 80 links distance, marked with brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY, nailed to the top.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Corner is located in a fence line, extending North and South, North, 9 links of corner of fences extending East, West, and North.

From this point an iron rebar, ½ in. diameter, no cap, South, ½ link distance from corner of fences extending East, West, and North, bears S. 01° 49' W., 9.7 links distance. This monument was not utilized during the course of this survey.

From this same point an iron rebar, ½ in. diameter, firmly set, projecting 3 ins. above the ground, no cap, South - West, ½ link distance of corner of fences extending North and East, bears S. 89° 03' E., 5.03 chains distance. This monument was not utilized during the course of this survey.

**39.646** The East 1/16 section corner of sections 20 and 29, hereinbefore described.

---

From the North 1/16 section corner of sections 28 and 29.

**S. 89°37.3' W.**, on the East and West center line of North - East ¼ of section 29.

**20.057** The North - East 1/16 section corner of section 29.

**40.114** The Center North 1/16 section corner of section 29.

---

From the East 1/16 section corner of sections 29 and 32.

**N. 0°02.3' W.**, on the North and South center line of South - East ¼ of section 29.

**19.906** Point for the South - East 1/16 section corner of section 29, at the intersection of the East and West center line of the South - East ¼ of section 29.

SUBDIVISION OF SECTION 29  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 21 ins. in the ground, encircled by a collar of stone, 3 ft. diameter, to the top of aluminum cap marked:

SE 1/16 S 29  
2003

from which

A juniper, 14 ins. diameter, bears N. 17° E., 9 ½ links distance, marked X BT.

A multi-trunk juniper, 20 ins. diameter, bears N. 89° E., 33 links distance, marked SE 1/16 S29 BT.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Corner is located on a gently sloping hill, surrounded by piñon and juniper.

**39.812** Point for the Center East 1/16 section corner of section 29, not monumented.

---

From the South 1/16 section corner of sections 28 and 29.

**S. 89°55.3' W.**, on the East and West center line of the South - East ¼ of section 29.

**20.018** The South - East 1/16 section corner of section 29.

**40.036** The Center South 1/16 section corner of section 29.

---

From the Center North 1/16 section corner of section 29.

**S. 89°46.7' W.**, on the East and West center line of the North - West ¼ of section 29.

**9.636** Intersect fence line extending North and South, 25 ft. north of Right-of-Way fence of Utah State Hwy. #35.

**18.515** The Center line of Utah State Hwy. #35, bears S. 80° E., N. 80° W.

**39.940** The North 1/16 section corner of sections 29 and 30.

---

**Subdivision of Section 30,  
Township 2 South, Range 5 West, Uintah Special Meridian, Utah**

---

SUBDIVISION OF SECTION 30  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

From the  $\frac{1}{4}$  section corner of sections 30 and 31.

**N. 0°43.1' W.**, on the North and South center line of section 30.

**38.993**

Point for the Center  $\frac{1}{4}$  section corner of section 30, at the intersection with the East and West center line.

Buried an aluminum rod, 36 ins. long,  $\frac{3}{4}$  ins. diameter, 6 ins. below the ground, with aluminum cap marked:

T 2 S R 5 W  
C 1/4 S 30  
2003

from which

An aluminum rod, 36 ins. long,  $\frac{3}{4}$  ins. diameter, set 31 ins. in the ground for a reference monument, bears S. 12° W., 11  $\frac{1}{2}$  links distance with aluminum cap marked RM 7.5 FT. C1/4 S30 and an arrow pointing to the corner.

An aluminum rod, 36 ins. long,  $\frac{3}{4}$  ins. diameter, set 31 ins. in the ground for a reference monument, bears N. 75° W., 8  $\frac{1}{2}$  links distance with aluminum cap marked RM 5.6 FT. C1/4 S30 and an arrow pointing to the corner.

Corner is located North - West, 7  $\frac{1}{2}$  links of a pipeline, 6 ins. diameter, bearing S. 40° E.

Corner is located 13  $\frac{1}{2}$  links from center line of a dirt road, 30 links wide, bearing S. 40° E.

**58.793**

Point for the North  $\frac{1}{16}$  section corner of section 30.

Set an aluminum post, 28 ins. long, 2  $\frac{1}{2}$  ins. diameter, in a crack of a sandstone outcropping, in a supporting mound of stone, 4 ft. diameter, to the top of aluminum cap marked:

C  
N 1/16 | S 30  
C  
2003

from which

A piñon, 8 ins. diameter, bears N. 26° E., 14  $\frac{1}{2}$  links distance, marked X BT.

A cross, chiseled on a South facing sandstone cliff, bears N. 67° W., 8  $\frac{1}{2}$  links distance.

**78.593**

The  $\frac{1}{4}$  section corner of sections 19 and 30.

SUBDIVISION OF SECTION 30  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

---

From the  $\frac{1}{4}$  section corner of sections 29 and 30.

**S. 89°27.1' W.**, on the East and West center line of section 30.

**19.703** Point for the Center East 1/16 section corner of section 30.

Set an aluminum rod, 12 ins. long,  $\frac{3}{4}$  ins. diameter, 5 ins. into bedrock, set in cement and projecting 7 ins., with aluminum cap marked:

E 1/16  
C————C  
S 30  
2003

from which

A juniper, 18 ins. diameter, bears N. 23° E., 73 links distance, marked CE 1/16 S30 BT.

A juniper, 6 ins. diameter, bears S. 52° E., 27  $\frac{1}{2}$  links distance, marked CE 1/16 S30 BT.

**39.406** The Center  $\frac{1}{4}$  section corner of section 30.

**59.521** Point for the Center West 1/16 section corner of section 30.

Set an aluminum post, 28 ins. long, 2  $\frac{1}{2}$  ins. diameter, 18 ins. in the ground, encircled by a collar of stone, 3 ft. diameter, to the top of aluminum cap marked:

W 1/16  
C————C  
S 30  
2003

from which

A juniper, 4 ins. diameter, bears North, 9  $\frac{1}{2}$  links distance, marked CW1/16 S30 BT.

A piñon, 4 ins. diameter, bears N. 84° E., 28 links distance, marked X BT.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

Corner is located on flat ground above a ravine, South, 53 links from pipeline, 6 ins. diameter, bearing East and West, surrounded by scattered piñon and juniper.

SUBDIVISION OF SECTION 30  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

Sand Wash road lies North of corner.

- 75.769** The  $\frac{1}{4}$  section corner of sections 25 and 30, on the West boundary of the township, hereinbefore described.

---

From the Center East  $\frac{1}{16}$  section corner of section 30.

**N. 0°29.4' W.**, on the North and South center line of the North - East  $\frac{1}{4}$  of section 30.

- 19.762** Point for the North - East  $\frac{1}{16}$  section corner of section 30.

Set an aluminum post, 28 ins. long, 2  $\frac{1}{2}$  ins. diameter, 24 ins. in the ground, encircled by a collar of stone, 3 ft. diameter, to the top of aluminum cap marked:

NE 1/16 S 30  
2003

from which

A piñon, 5 ins. diameter, bears S. 26° W., 25 links distance, marked X BT.

A piñon, 5 ins. diameter, bears N. 28° W., 28  $\frac{1}{2}$  links distance, marked with a brass washer, 1  $\frac{1}{2}$  ins. diameter, marked BLM CADASTRAL SURVEY, nailed to a blaze on the South - East face.

- 39.524** The East  $\frac{1}{16}$  section corner of sections 19 and 30.

---

From the North  $\frac{1}{16}$  section corner of sections 29 and 30.

**S. 89°33.7' W.**, on the East and West center line of the North - East  $\frac{1}{4}$  of section 30.

- 19.780** The North - East  $\frac{1}{16}$  section corner of section 30.

- 39.560** The Center North  $\frac{1}{16}$  section corner of section 30.

---

From the Center West  $\frac{1}{16}$  section corner of section 30.

**N. 0°21.0' W.**, on the North and South center line of the North - West  $\frac{1}{4}$  of section 30.

- 19.838** Point for the North - West  $\frac{1}{16}$  section corner of section 30.

SUBDIVISION OF SECTION 30  
TOWNSHIP 2 SOUTH, RANGE 5 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

Set an aluminum post, 28 ins. long, 2 ½ ins. diameter, 6 ins. in the ground, encircled by a collar of stone, supported by a mound of stone, 5 ft. diameter, to the top of aluminum cap marked:

NW 1/16 S 30  
2003

from which

A forked piñon, 10 ins. diameter, bears N. 20° E., 44 links distance, marked with a brass washer, 1 ½ ins. diameter, marked BLM CADASTRAL SURVEY, nailed to a blaze on the South face.

A juniper, 9 ins. diameter, bears S. 28° E., 49 links distance, marked X BT.

Deposit a magnet, in a white plastic case, at the base of the aluminum post.

**39.676** The West 1/16 section corner of sections 19 and 30.

---

From the Center N 1/16 section corner of section 30.

**S. 89°33.6' W.**, on the East and West center line of the North - West ¼ of section 30.

**19.987** The North - West 1/16 section corner of section 30.

**36.074** The North 1/16 section corner of sections 25 and 30 on the West boundary of the township, hereinbefore described.

---

---

**INDEX FOR ORIGINAL FIELD NOTES**


---

**BOOK VOLUME - A - 270**

<b>PAGE</b>	<b>DESCRIPTION</b>		
337	T01S R04W	USM	East & South Exterior Boundaries
348	T01S R04W	USM	Interior Section Lines
391	T01S R04W	USM	Sub-Divisional Lines
467	T01S R04W	USM	Completion End

---

**BOOK VOLUME - A - 272**

<b>PAGE</b>	<b>DESCRIPTION</b>		
135	T03S R04W	USM	South & North Exterior Boundaries
147	T03S R04W	USM	Interior Section Lines
181	T03S R04W	USM	Sub-Divisional Lines
248	T03S R05W	USM	South Exterior Boundary
253	T03S R05W	USM	Interior Section Lines
257	T03S R05W	USM	Sub-Divisional Lines

---

**BOOK VOLUME - A - 273**

<b>PAGE</b>	<b>DESCRIPTION</b>		
001	T01S R05W	USM	South Exterior Boundary
008	T01S R05W	USM	Interior Section Lines
044	T01S R05W	USM	Sub-Divisional Lines

---

**INDEX FOR ORIGINAL FIELD NOTES**

---

**BOOK VOLUME - A - 317**

<b>PAGE</b>	<b>DESCRIPTION</b>		
003	T02S R04W	USM	Index Diagram
005	T03S R04W	USM	Index Diagram
007	T01S R05W	USM	Index Diagram
011	T03S R05W	USM	Index Diagram
077	T02S R04W	USM	South, & North Exterior Boundaries
081	T02S R04W	USM	South Exterior Boundary
084	T02S R04W	USM	North Exterior Boundary
103	T02S R04W	USM	East Exterior Boundary
119	T02S R04W	USM	Corrective South, East & North Exterior
133	T02S R04W	USM	West Boundary, First Guide Meridian
153	T02S R04W	USM	Corrective First Guide Meridian West
163	T02S R04W	USM	Interior Section Lines
233	T02S R04W	USM	Corrective Interior Section Lines
261	T03S R04W	USM	East Exterior Boundary
273	T03S R04W	USM	Interior Section Lines
291	T03S R04W	USM	Interior Section Lines
301	T03S R04W	USM	Corrective Interior Section Lines
313	T01S R05W	USM	West Exterior Boundary
331	T01S R05W	USM	Interior Section Lines
347	T01S R05W	USM	Interior Section Lines

---

**INDEX FOR ORIGINAL FIELD NOTES**


---

**BOOK VOLUME - A - 317**

<b>PAGE</b>	<b>DESCRIPTION</b>		
365	T02S R05W	USM	West Boundary, First Standard Parallel
491	T03S R04W	USM	West Boundary, First Guide Meridian
509	T03S R05W	USM	West & North Exterior Boundaries
533	T03S R05W	USM	Corrective West & North Exterior
545	T03S R05W	USM	Interior Section Lines
617	T03S R05W	USM	Corrective Interior Section Lines
644	T03S R05W	USM	Completion End

---

**BOOK VOLUME - A - 318**

<b>PAGE</b>	<b>DESCRIPTION</b>		
001	T02S R05W	USM	Index Diagram
005	T03S R06W	USM	Index Diagram
007	T02S R06W	USM	Index Diagram
008	T01S R06W	USM	Index Diagram
009	T02S R05W	USM	West Exterior Boundary
027	T02S R05W	USM	Corrective West Exterior Boundary
041	T02S R05W	USM	North Exterior Boundary
053	T02S R05W	USM	Interior Section Lines
129	T02S R05W	USM	Corrective Interior Section Lines

---

**INDEX FOR ORIGINAL FIELD NOTES**


---

**BOOK VOLUME - A - 318**

<b>PAGE</b>	<b>DESCRIPTION</b>		
285	T03S R06W	USM	West & North Exterior Boundaries
309	T03S R06W	USM	Interior Section Lines
379	T03S R06W	USM	Corrective Interior Section Lines
397	T02S R06W	USM	West & North Exterior Boundaries
421	T02S R06W	USM	Interior Section Lines
491	T02S R06W	USM	Corrective Interior Section Lines
507	T01S R06W	USM	West Exterior Boundary
525	T01S R06W	USM	Interior Section Lines
600	T01S R06W	USM	Completion End

---

**BOOK VOLUME - A - 323**

<b>PAGE</b>	<b>DESCRIPTION</b>		
059	T03S R05W	USM	Duchesne Town Site, Section 2.
114	T03S R05W	USM	Duchesne Town Site Section 36.

---

**BOOK VOLUME - A - 416**

<b>PAGE</b>	<b>DESCRIPTION</b>		
005	T03S R04W	USM	Index Diagram
221	T03S R04W	USM	West Exterior Boundary
234	T03S R04W	USM	North Exterior Boundary

**INDEX FOR ORIGINAL FIELD NOTES**

---

**BOOK VOLUME - A - 416**

<b>PAGE</b>	<b>DESCRIPTION</b>		
245	T03S R04W	USM	East Exterior Boundary
256	T03S R04W	USM	South Exterior Boundary
270	T03S R04W	USM	Interior Section Lines
346	T03S R04W	USM	Meanders Exterior Boundary

---

OUTLINE OF ORIGINAL FIELD NOTES  
BOOK VOLUME - A - 273  
TOWNSHIP 01 SOUTH, RANGE 05 WEST  
UINTAH SPECIAL MERIDIAN

---

DANIEL G. MAJOR  
CONTRACT NUMBER 000, DATE FEBRUARY 23, 1882

---

SOUTH BOUNDARY

CHAINS

At the corner of sections 5, 6, 31, and 32. On the South boundary of the Township.

**West**, between sections 6, and 31.

- 40.00** Set Sandstone, 25 x 5 x 5 ins. marked 1/4 on East face; in mound of earth, 2 1/2 feet diameter at base 18 ins. high for 1/4 section corner situated on high hill.
- 80.00** Set a Sandstone, 40 x 30 x 30 ins. marked on North, East, South, and West faces with 6 grooves, for the corner to Townships 1 and 2 South, Ranges 5 and 6 West, in mound of earth 6 feet diameter at base and 3 feet high situated near foot of rocky bluff. West 10 chains to Rock Creek a mountain stream of excellent water about 150 links wide, one of the principal tributary of the Duchene River.
-

**OUTLINE OF ORIGINAL FIELD NOTES  
BOOK VOLUME - A - 317  
TOWNSHIP 03 SOUTH, RANGE 05 WEST  
UINTAH SPECIAL MERIDIAN**

---

**ANDREW J. STEWART JR. & ALFRED L. BOOTH  
CONTRACT NUMBER 270, DATE JULY 22, 1903**

---

**WEST BOUNDARY**

**CHAINS**

At the corner of Sections 1, 6, 7, and 12.

Set Sandstone, 32 x 10 x 6 ins. 24 ins. in the ground, for corner of sections, 1, 6, 7, and 12, marked with 5 notches on South edge, and 1 notch on the North edge;

from which;

A Pinion Pine, 14 ins. diameter, bears N. 48° E. 75 links distance, marked T3S R5W S6 BT.

A Pinion Pine, 14 ins. diameter, bears S 19° E., 48 links distance, marked T3S R5W S7 BT.

A Pinion Pine, 16 ins. diameter, bears S. 24° W. 47 links distance, marked T3S R6W S12 BT.

A Pinion Pine, 16 ins. diameter, bears N 49° W., 68 links distance, marked T3S R6W S1 BT.

**North**, between sections 1 and 6.

**40.00** Set Sandstone, 18 x 9 x 6 ins. 12 ins. in the ground, for 1/4 section corner marked 1/4 on West face,

from which;

A Cedar, 8 ins. diameter, bears N. 60° E., 50 links distance, marked 1/4 S6 BT.

A Pinion Pine, 10 ins. diameter, bears S. 15° W., 42 links distance, marked 1/4 S1 BT.

**80.00** Set temporary corner of Township 2 and 3 South, Ranges 5 and 6 West.

**NOTE:** The permanent corner of Township 2 and 3 South, Ranges 5 and 6 West. As afterwards set at 80.00 chains, is a Sandstone, 20 x 14 x 4 ins. 15 ins. in the ground, for corner of sections 5, and 6 West, marked with 2S on North-East, 5W on South-East, 3S on South-West, and 6W on North-West faces, with 6 notches on each edges,

**OUTLINE OF ORIGINAL FIELD NOTES  
WEST BOUNDARY**

**CHAINS**

from which;

A Pinion Pine, 12 ins. diameter, bears S. 30° W., 35 links distance, marked T3S R6W S1 BT.

No other trees within limits, raise a mound of stone 2 feet base, 1 1/2 feet high, South of corner.

---

From the corner of Townships 2 and 3 South, Ranges 4 and 5 West, heretofore described.

**West** on a random line along North Boundary of Township, setting temporary corners at intervals of 40.00 chains, and at 476.50 chains intersect West Boundary of Township, 84 links North of the temporary corner of Townships 2 and 3 South, Ranges 5 and 6 West, the falling answers to a correction of 6 feet or 14 links North per mile counting from the corner of Township 2 and 3 South, Ranges 5 and 6 West.

The falling is within 21 minutes of arc; therefore established the temporary corner as permanent corner of Township 2 and 3 South, Ranges 5 and 6 West, marked 2S on North-East, 5W on South-East, 3S on South-West, and 6W on North-West faces with 6 notches on Each edge,

from which;

A Pinion Pine, 12 ins. diameter, bears S. 30° W., 35 links distance, marked T3S R5W S1 BT.

No other trees within limits, raise a mound of stone 2 feet base, 1 1/2 feet high, South of corner.

---

ORIGINAL FIELD NOTES  
 BOOK VOLUME - A - 318  
 TOWNSHIP 02 SOUTH, RANGE 05 WEST  
 UINTAH SPECIAL MERIDIAN

ANDREW J. STEWART JR. & ALFRED L. BOOTH  
 CONTRACT NUMBER 270, DATE JULY 22, 1903

PAGE	DESCRIPTION FOR BOOK 318
001	INDEX DIAGRAM
009 - 028>	WEST BOUNDARY
027 - 040>	WEST BOUNDARY CORRECTION
041 - 052>	NORTH BOUNDARY
053 - 128>	SUBDIVISION INTERIOR
129 - 158>	SUBDIVISION CORRECTION

**WEST BOUNDARY**

*CHAINS*

At the corner of Townships 2 and 3 South, Ranges 5 and 6 West,  
 Latitude 40° 15' 54" North, Longitude 110° 32' 07" West.

**North**, between sections 31 and 36.

**40.00** Set Sandstone, 18 x 12 x 10 ins. 12 ins. in the ground, for 1/4  
 section corner, marked 1/4 on West face;

from which;

A Pinion Pine, 10 ins. diameter, bears S. 30° E. 15 links  
 distance, marked 1/4 S31 BT.

A Pinion Pine, 10 ins. diameter, bears West, 50 links  
 distance, marked 1/4 S31 BT.

**80.00** Set Sandstone, 20 x 12 x 12 ins. 15 ins. in the ground, for  
 corner of sections 25, 30, 31, and 36, marked with 1 notch on  
 South, and 5 notches on North edges;

from which;

A Pinion Pine, 8 ins. diameter, bears N. 40° E., 40 links  
 distance, marked T2S R5W S30 BT.

A Pinion Pine, 10 ins. diameter, bears S. 60° E., 120 links  
 distance, marked T2S R5W S31 BT.

A Pinion Pine, 8 ins. diameter, bears S. 45° W., 65 links  
 distance, marked T2S R6W S36 BT.

**OUTLINE OF ORIGINAL FIELD NOTES  
WEST BOUNDARY**

**CHAINS**

A Pinion Pine, 8 ins. diameter, bears N. 50° W., 55 links  
distance, marked T2S R6W S25 BT.

**North**, between sections 25 and 30.

**40.00** Set Sandstone, 16 x 12 x 12 ins. 11 ins. in the ground, for 1/4 section corner, marked 1/4 on West face;

from which;

A Pinion Pine, 8 ins. diameter, bears S. 50° W. 30 links  
distance, marked 1/4 S25 BT.

No, other trees within limits; and raise a mound of stone, 2 feet base, 1 1/2 feet high, West of the corner.

**80.00** Set Sandstone, 16 x 14 x 8 ins. 11 ins. in the ground, for corner of sections 19, 24, 25, and 30, marked with 2 notch on South, and 4 notches on North edges;

from which;

A Pinion Pine, 12 ins. diameter, bears N. 81° E., 54 links  
distance, marked T2S R5W S19 BT.

A Pinion Pine, 6 ins. diameter, bears S. 51° E., 58 links  
distance, marked T2S R5W S30 BT.

A Pinion Pine, 5 ins. diameter, bears S. 69° W., 26 links  
distance, marked T2S R6W S25 BT.

A Pinion Pine, 8 ins. diameter, bears N. 6° W., 33 links  
distance, marked T2S R6W S24 BT.

**North**, between sections 19 and 24

**40.00** Point for 1/4 section corner falls in river

**43.85** Set Sandstone, 18 x 9 x 6 ins. 12 ins. in the ground, for Witness Corner, to 1/4 section corner, marked W.C. 1/4 on West face; and raise a mound of stone, 2 feet base, 1 1/2 feet high, West of corner.

**80.00** Set Hard Cobble Stone, 16 x 10 x 8 ins. 11 ins. in the ground, for corner of sections 13, 18, 19, and 24, marked with 3 notch on South, and 3 notches on North edges;

from which;

**OUTLINE OF ORIGINAL FIELD NOTES  
WEST BOUNDARY**

**CHAINS**

- A Cedar, 10 ins. diameter, bears N. 47° E., 89 links distance, marked T2S R5W S18 BT.
- A Pinion Pine, 20 ins. diameter, bears S. 45° E., 10 links distance, marked T2S R5W S19 BT.
- A Pinion Pine, 12 ins. diameter, bears S. 40° W., 40 links distance, marked T2S R6W S24 BT.
- A Pinion Pine, 15 ins. diameter, bears N. 10° W., 125 links, distance, marked T2S R6W S13 BT.

**North**, between sections 13 and 18.

- 40.00** Set Sandstone, 16 x 12 x 6 ins. 11 ins. in the ground, for 1/4 section corner, marked 1/4 on West face;

from which;

A Pinion Pine, 16 ins. diameter, bears N. 45° E. 73 links distance, marked 1/4 S 18 BT.

A Cedar, 6 ins. diameter, bears S 86° W., 35 links distance, marked 1/4 S13 BT.

- 80.00** Set Sandstone, 20 x 12 x 6 ins. 15 ins. in the ground, for corner of sections 7, 12, 13, and 18, marked with 4 notches on South, and 2 notches on North edges;

from which;

A Pinion Pine, 10 ins. diameter, bears N. 41° E., 110 links distance, marked T2S R5W S7 BT.

A Pinion Pine, 10 ins. diameter, bears S. 60° 30' E., 91 links distance, marked T2S R5W S 19 BT.

A Pinion Pine, 8 ins. diameter, bears S. 60° W., 53 links distance, marked T2S R6W S13 BT.

A Pinion Pine, 11 ins. diameter, bears N. 35° W., 101 links distance, marked T2S R6W S 12 BT.

**North**, between sections 7 and 12.

- 40.00** Set Sandstone, 16 x 10 x 6 ins. 11 ins. in the ground, for 1/4 section corner, marked 1/4 on West face; and raise a mound of stone, 2 feet base, 1 1/2 feet high, West of corner.

**OUTLINE OF ORIGINAL FIELD NOTES  
WEST BOUNDARY**

**CHAINS**

**80.00** Set Sandstone, 18 x 8 x 6 ins. 12 ins. in the ground, for corner of sections 1, 6, 7, and 12, marked with 5 notches on South, and 1 notch on North edges;

from which;

A Pinion Pine, 9 ins. diameter, bears N. 42° E., 37 links distance, marked T2S R5W S6 BT.

A Pinion Pine, 7 ins. diameter, bears S. 25° E., 70 links distance, marked T2S R5W S7 BT.

A Pinion Pine, 11 ins. diameter, bears S. 33° W., 48 links distance, marked T2S R6W S12 BT.

A Pinion Pine, 8 ins. diameter, bears N. 66° W., 53 links distance, marked T2S R6W S1 BT.

**North,** between sections 1 and 6.

**40.00** Set Sandstone, 18 x 11 x 4 ins. 12 ins. in the ground, for 1/4 section corner, marked 1/4 on West face;

from which;

A Pinion Pine, 24 ins. diameter, bears N. 53° E. 75 links distance, marked 1/4 S6 BT.

A Cedar, 14 ins. diameter, bears N 18° 30' W., 14 links distance, marked 1/4 S1 BT.

**79.80** The corner of Townships 1 and 2 South, Ranges 5 and 6 West, heretofore described.

**OUTLINE OF ORIGINAL FIELD NOTES  
WEST BOUNDARY CORRECTION**

*CHAINS*

---

West boundary of Townships 2 South, Ranges 5 and 6 West.

At the corner of sections 25, 30, 31, and 36,  
Latitude 40° 16' 47" North, Longitude 110° 32' 07" West.

From the corner of sections 25, 30, 31, and 36, which is a  
Sandstone 12 x 12 x 5 ins. above ground, firmly set

from which

A Pinion Pine, 6 ins. diameter, bears N. 31° E., 72 links  
distance, marked T2S R5W S30 BT.

A Pinion Pine, 6 ins. diameter, bears S. 81° E., 61 links  
distance, marked T2S R5W S31 BT.

A Pinion Pine, 14 ins. diameter, bears S. 31° W., 24 links  
distance, marked T2S R6W S36 BT.

A Cedar, 9 ins. diameter, bears N. 31° W., 24 links  
distance, marked T2S R6W S 25 BT.

**North**, between sections 25 and 30.

**40.15** Intersect the 1/4 section corner between sections 25 and 30.

**NOTE:** Move the corner South 15 links.

**40.00** Set Sandstone, 16 x 12 x 12 ins. 11 ins. in the ground, for 1/4  
section corner, marked 1/4 on West face;

from which;

A Cedar, 4 ins. diameter, bears S. 60° E. 115 links  
distance, marked 1/4 S30 BT.

A Pinion Pine, 6 ins. diameter, bears N. 73° W., 48 links  
distance, marked 1/4 S25 BT.

**NOTE:** Destroy all traces of the old corner.

**80.25** Fall West 22 links of the Corner of sections 19, 24, 25, and 30.

**NOTE:** Move the corner South 25 links, and West 22 links.

**80.00** Set Sandstone, 16 x 14 x 8 ins. 11 ins. in the ground, for corner  
of sections 19, 24, 25, and 30, marked with 2 notches on South,  
and 4 notches on North edges;

**OUTLINE OF ORIGINAL FIELD NOTES  
WEST BOUNDARY CORRECTION**

**CHAINS**

from which;

A Pinion Pine, 4 ins. diameter, bears N. 66° E., 62 links distance, marked T2S R5W S19 BT.

A Pinion Pine, 4 ins. diameter, bears S. 51° 15' E., 90 links distance, marked T2S R5W S 30 BT.

A Pinion Pine, 8 ins. diameter, bears S. 58° W., 31 links distance, marked T2S R6W S25 BT.

A Pinion Pine, 8 ins. diameter, bears N. 64° 15' W., 46 links distance, marked T2S R6W S 24 BT.

**NOTE:** Destroy all traces of the old corner.

---

**North,** between sections 19 and 24.

**40.00** Point for 1/4 section corner falls in river.

**45.37** The Witness Corner to 1/4 section corner.

Described properly in the original Field Notes

**80.00** The corner of sections 13, 18, 19, and 24, on line, which is a Cobblestone, 10 x 8 x 5 ins. above ground, firmly set,

from which,

A Pinion Pine, 9 ins. diameter, bears N. 29° E., 49 links distance, marked T2S R5W S18 BT.

A Pinion Pine, 14 ins. diameter, bears S. 33° E., 48 links distance, marked T2S R5W S19 BT.

A Pinion Pine, 6 ins. diameter, bears S. 76° 15' W., 53 links distance, marked T2S R6W S24 BT.

A Pinion Pine, 5 ins. diameter, bears N. 52° W., 84 links distance, marked T2S R6W S13 BT.

---

**North,** between sections 13 and 18.

**39.85** Fall East 3 links of 1/4 section corner.

**NOTE:** Move the corner North 15 links, and East 3 links.

**40.00** Set a Sandstone, 16 x 10 x 8 ins. 11 ins. in the ground, for 1/4 section corner, marked 1/4 on West face;

**OUTLINE OF ORIGINAL FIELD NOTES  
WEST BOUNDARY CORRECTION**

*CHAINS*

from which

A Pinion Pine, 12 ins. diameter, bears N. 84° 30' E., 78 links distance, marked 1/4 S13 BT.

A Pinion Pine, 12 ins. diameter, bears S. 87° W., 23 links distance, marked 1/4 S19 BT.

**NOTE:** Destroy all traces of the old corner.

**80.30** The corner of sections 7, 12, 13, and 18, on line.

**NOTE:** Move the corner South 30 links.

**80.00** Set a Sandstone, 20 x 12 x 6 ins. 15 ins. in the ground, for corner of sections 7, 12, 13, and 18, marked with 4 notches on South, and 2 notches on North edges;

from which;

A Pinion Pine, 14 ins. diameter, bears N. 42° E., 72 links distance, marked T2S R5W S7 BT.

A Pinion Pine, 10 ins. diameter, bears S. 69° 45' E., 59 links distance, marked T2S R5W S 18 BT.

A Pinion Pine, 6 ins. diameter, bears S. 77° 30' W., 43 links distance, marked T2S R6W S13 BT.

A Pinion Pine, 14 ins. diameter, bears N. 75° W., 56 links distance, marked T2S R6W S12 BT.

**NOTE:** Destroy all traces of the old corner.

**North,** between sections 7 and 12.

**40.22** The 1/4 section corner between sections 7 and 12, on line.

**NOTE:** Move the corner South 22 links.

**40.00** Set a Sandstone, 16 x 10 x 6 ins. 11 ins. in the ground, for 1/4 section corner, marked 1/4 on West face;

from which;

A Pinion Pine, 6 ins. diameter, bears S. 28° 30' E. 33 links distance, marked 1/4 S7 BT.

A Pinion Pine, 8 ins. diameter, bears S 36° W., 61 links distance, marked 1/4 S12 BT.

**OUTLINE OF ORIGINAL FIELD NOTES  
WEST BOUNDARY CORRECTION**

*CHAINS*

**NOTE:** Destroy all traces of the old corner.

**80.00** The corner of sections 1, 6, 7, and 12, on line, which is a Sandstone, 8 x 6 x 6 ins. above ground, firmly set, and marked as described by the original Field Notes;

from which

A Pinion Pine, 6 ins. diameter, bears N. 63° E., 76 links distance, marked T2S R5W S6 BT.

A Pinion Pine, 20 ins. diameter, bears S. 40° E., 130 links distance, marked T2S R5W S7 BT.

A Pinion Pine, 12 ins. diameter, bears S. 79° W., 78 links distance, marked T2S R6W S12 BT.

A Pinion Pine, 12 ins. diameter, bears N. 61° W., 93 links distance, marked T2S R6W S1 BT.

---

**North,** between sections 1 and 6.

**40.00** The 1/4 section corner between sections 1 and 6, on line, properly described in the original Field Notes.

**79.80** The corner of Townships 1, and 2 South, Ranges 5 and 6 West, properly described in the original Field Notes.

---

**OUTLINE OF ORIGINAL FIELD NOTES  
NORTH BOUNDARY**

*CHAINS*

From the corner of Township 1 and 2 South, Ranges 5 and 6 West.

**East**, on a Retracement line between sections 6, and 31.

- 38.20** The 1/4 Section Corner between sections 6 and 31, which is a Sandstone, 8 x 5 x 5 ins. above ground, firmly set and marked and witnessed as described by the Surveyor General, bears North 65 links distance.

To better perpetuate the corner, marked trees as follows.

A Pinion Pine, 16 ins. diameter, bears N. 43° E., 56 links distance, marked 1/4 S31 BT.

A Pinion Pine, 24 ins. diameter, bears S. 40° 30' W., 13 links distance, marked 1/4 S6 BT.

- 78.19** The corner of sections 5, 6, 31, and 32, which is Sandstone, 12 x 12 x 5 ins. Above ground firmly set and marked and witnessed as described by the Surveyor General bears North, 128 links distance.

The course of this line is therefore S. 89° 04' W., 78.20 chains.

---

**OUTLINE OF ORIGINAL FIELD NOTES  
SUBDIVISION INTERIOR**

*CHAINS*

---

From the corner of Sections 4, 5, 32, and 33, on the South boundary of Townships 2 and 3 South, Ranges 5 West,

**N. 00° 03' W.**, between sections 32 and 33.

**40.00** Set Sandstone, 24 x 12 x 7 ins. 18 ins. in the ground, for 1/4 section corner, marked 1/4 on West face;

from which;

A Cedar, 6 ins. diameter, bears S. 40° E. 210 links distance, marked 1/4 S33 BT.

A Cedar, 6 ins. diameter, bears S. 45° W., 192 links distance, marked 1/4 S 32 BT.

**80.00** Set Sandstone, 18 x 10 x 10 ins. in mound of stone on solid rock, for corner of sections 28, 29, 32, and 33, marked with 1 notch on South, and 4 notches on East edges;

from which;

A Pinion Pine, 10 ins. diameter, bears N. 25° E., 30 links distance, marked T2S R5W S28 BT.

A Pinion Pine, 12 ins. diameter, bears S. 15° E., 83 links distance, marked T2S R5W S33 BT.

A Cedar, 4 ins. diameter, bears S. 30° W., 129 links distance, marked T2S R5W S32 BT.

A Pinion Pine, 11 ins. diameter, bears N. 80° W., 33 links distance, marked T2S R5W S29 BT.

---

From the corner of Sections 28, 29, 32, and 33.

**N. 00° 03' W.**, between sections 28 and 29.

**40.00** Set a Sandstone, 18 x 12 x 4 ins. 12 ins. in the ground, for 1/4 section corner, marked 1/4 on West face; dig pits, 18 x 18 x 12 ins. North and South of stone, 3 feet distance; and raise a mound of earth 3 1/2 feet base, 1 1/2 feet high, West of corner.

**80.00** Set a Sandstone, 18 x 8 x 8 ins. 12 ins in the ground for corner of sections 20, 21, 28, and 29, marked with 2 notches on South, and 4 notches on East edges; dig pits, 18 x 18 x 12 ins. in each section, 5 1/2 feet distance; and raise a mound of earth, 4 feet base, 2 feet high, West of corner.

**OUTLINE OF ORIGINAL FIELD NOTES  
SUBDIVISION INTERIOR**

*CHAINS*

---

From the corner of Sections 20, 21, 28, and 29.

**N. 00° 03' W.**, between sections 20 and 21.

**40.00** Set a Sandstone, 20 x 14 x 4 ins. 15 ins. in the ground, for 1/4 section corner, marked 1/4 on West face;

from which;

A Cedar, 8 ins. diameter, bears S. 79° E. 59 links  
distance, marked 1/4 S21 BT.

A Pinion Pine, 6 ins. diameter, bears S. 70° W., 30 links  
distance, marked 1/4 S20 BT.

**80.00** Set a Sandstone, 18 x 10 x 8 ins. 12 ins. in the ground, for corner of sections 16, 17, 20, and 21, marked with 3 notches on South, and 4 notches on East edges;

from which;

A Pinion Pine, 16 ins. diameter, bears N. 60° E., 22 links  
distance, marked T2S R5W S16 BT.

A Cedar, 8 ins. diameter, bears S. 23° E., 51 links  
distance, marked T2S R5W S21 BT.

A Pinion Pine, 8 ins. diameter, bears S. 40° W., 70 links  
distance, marked T2S R5W S20 BT.

No other trees within limits; raise a mound of stone, 2 feet base, 1 1/2 feet high, West of corner.

---

From the corner of Sections 5, 6, 31, and 32, on the South boundary of Townships 2 and 3 South, Ranges 5 West.

**N. 00° 04' W.**, between sections 31 and 32.

**40.00** Set a Sandstone, 24 x 6 x 4 ins. 18 ins. in the ground, for 1/4 section corner, marked 1/4 on West face;

from which;

A Cedar, 11 ins. diameter, bears N. 80° E. 15 links  
distance, marked 1/4 S32 BT.

A Cedar, 9 ins. diameter, bears N. 40° W., 55 links  
distance, marked 1/4 S31 BT.

**OUTLINE OF ORIGINAL FIELD NOTES  
SUBDIVISION INTERIOR**

*CHAINS*

**80.00** Set a Sandstone, 18 x 8 x 7 ins. 12 ins. in the ground, for corner of sections 29, 30, 31, and 32, marked with 1 notch on South, and 5 notches on East edges;

from which;

A Pinion Pine, 10 ins. diameter, bears N. 50° E., 150 links distance, marked T2S R5W S29 BT.

A Pinion Pine, 12 ins. diameter, bears S. 30° E., 95 links distance, marked T2S R5W S32 BT.

A Pinion Pine, 11 ins. diameter, bears S. 85° W., 45 links distance, marked T2S R5W S31 BT.

A Pinion Pine, 9 ins. diameter, bears North-West, 83 links distance, marked T2S R5W S30 BT.

From the corner of Sections 28, 29, 32, and 33.

**N. 89° 56' W.**, on a true line between sections 29 and 32.

**40.11** Set a Sandstone, 18 x 12 x 4 ins. 12 ins. in the ground, for 1/4 section corner, marked 1/4 on North face;

from which;

A Pinion Pine, 10 ins. diameter, bears N. 40° W. 230 links distance, marked 1/4 S29 BT.

A Cedar, 12 ins. diameter, bears S. 89° W., 265 links distance, marked 1/4 S32 BT.

**80.22** The corner of sections 29, 30, 31, and 32.

From the corner of Sections 29, 30, 31, and 32.

**N. 89° 56' W.**, on a true line between sections 30 and 31.

**40.00** Set a Sandstone, 15 x 13 x 4 ins. 10 ins. in the ground, for 1/4 section corner, marked 1/4 on North face;

from which;

A Pinion Pine, 8 ins. diameter, bears N. 50° E. 40 links distance, marked 1/4 S30 BT.

A Pinion Pine, 6 ins. diameter, bears S. 10° W., 35 links distance, marked 1/4 S31 BT.

**OUTLINE OF ORIGINAL FIELD NOTES  
SUBDIVISION INTERIOR**

*CHAINS*

**76.27** The corner of sections 25, 30, 31, and 36.

---

From the corner of Sections 29, 30, 31, and 32.

**N. 00° 04' W.**, between sections 29 and 30.

**40.00** Set a Sandstone, 20 x 15 x 6 ins. 15 ins. in the ground, for 1/4 section corner, marked 1/4 on West face;

from which;

A Pinion Pine, 15 ins. diameter, bears S. 75° E. 105 links distance, marked 1/4 S29 BT.

A Pinion Pine, 11 ins. diameter, bears N. 45° W., 125 links distance, marked 1/4 S30 BT.

**80.00** Set a Quartzite Stone, 15 x 8 x 6 ins. 10 ins. in the ground, for corner of sections 19, 20, 29, and 30, marked with 2 notches on South, and 5 notches on East edges;

from which;

A Cottonwood, 10 ins. diameter, bears N. 10° E., 60 links distance, marked T2S R5W S20 BT.

A Cottonwood, 7 ins. diameter, bears S. 65° E., 150 links distance, marked T2S R5W S29 BT.

A Cottonwood, 10 ins. diameter, bears S. 35° W., 50 links distance, marked T2S R5W S30 BT.

A Cottonwood, 9 ins. diameter, bears N. 35°W., 30 links distance, marked T2S R5W S19 BT.

---

From the corner of Sections 20, 21, 28, and 29.

**N. 89° 54' W.**, between sections 20 and 29.

**40.10** Set a Sandstone, 18 x 9 x 5 ins. 12 ins. in the ground, for 1/4 section corner, marked 1/4 on North face;

from which;

A Cottonwood, 4 ins. diameter, bears N. 50° E. 20 links distance, marked 1/4 S20 BT.

A Cottonwood, 4 ins. diameter, bears S. 10° W., 30 links distance, marked 1/4 S29 BT.

**OUTLINE OF ORIGINAL FIELD NOTES  
SUBDIVISION INTERIOR**

*CHAINS*

**80.20** The corner of sections 19, 20, 29, 30.

---

From the corner of Sections 19, 20, 29, and 30.

**S. 89° 54' W.**, between sections 19 and 30.

**40.00** Set a Sandstone, 18 x 8 x 6 ins. 12 ins. in the ground, for 1/4 section corner, marked 1/4 on North face; and raise a mound of stone, 2 feet base, 1 1/2 feet high, North of corner.

**76.04** The corner of sections 19, 24, 25, 30.

---

From the corner of Sections 19, 20, 29, and 30.

**N. 00° 04' W.**, between sections 19 and 20.

**40.00** Set a Hard Sandstone, 15 x 14 x 8 ins. 10 ins. in the ground, for 1/4 section corner, marked 1/4 on West face;

from which;

A Pinion Pine, 8 ins. diameter, bears S. 75° E. 59 links distance, marked 1/4 S20 BT.

A Cedar, 4 ins. diameter, bears S. 45° W., 55 links distance, marked 1/4 S19 BT.

**80.00** Set a Sandstone, 18 x 8 x 5 ins. 12 ins. in the ground, for corner of sections 17, 18, 19, and 20, marked with 3 notches on South, and 5 notches on East edges;

from which;

A Pinion Pine, 6 ins. diameter, bears N. 74° E., 62 links distance, marked T2S R5W S17 BT.

A Cedar, 8 ins. diameter, bears S. 49° E., 104 links distance, marked T2S R5W S20 BT.

A Cedar, 8 ins. diameter, bears S. 51° W., 48 links distance, marked T2S R5W S19 BT.

A Pinion Pine, 5 ins. diameter, bears N. 45° 30' W., 80 links distance, marked T2S R5W S18 BT.

---

From the corner of Sections 16, 17, 20, and 21.

**S. 89° 56' W.**, on a true line between sections 17 and 20.

**OUTLINE OF ORIGINAL FIELD NOTES  
SUBDIVISION INTERIOR**

*CHAINS*

**40.00** Set a Sandstone, 24 x 10 x 8 ins. 18 ins. in the ground, for 1/4 section corner, marked 1/4 on North face;

from which;

A Pinion Pine, 6 ins. diameter, bears N. 9° 30' W., 52 links distance, marked 1/4 S20 BT.

A Cedar, 8 ins. diameter, bears S. 11° 30' E., 39 links distance, marked 1/4 S29 BT.

**80.00** The corner of sections 17, 18, 19, 20.

From the corner of Sections 17, 18, 19, and 20.

**S. 89° 56' W.**, between sections 18 and 19.

**40.00** Set a Hard Cobble Stone, 15 x 8 x 6 ins. 10 ins. in the ground, for 1/4 section corner, marked 1/4 on North face;

A Cottonwood, 6 ins. diameter, bears N. 30° W. 35 links distance, marked 1/4 S18 BT.

A Cottonwood, 6 ins. diameter, bears S. 40° E., 20 links distance, marked 1/4 S19 BT.

**75.82** The corner of sections 13, 18, 19, 24.

From the corner of Sections 17, 18, 19, and 20.

**N. 00° 04' W.**, between sections 17 and 18.

**40.00** Set a Sandstone, 16 x 10 x 5 ins. 11 ins. in the ground, for 1/4 section corner, marked 1/4 on West face;

from which;

A Pinion Pine, 5 ins. diameter, bears N. 60° E. 28 links distance, marked 1/4 S17 BT.

A Pinion Pine, 8 ins. diameter, bears S. 70° W., 52 links distance, marked 1/4 S18 BT.

**80.00** Set a Sandstone, 20 x 10 x 5 ins. 15 ins. in the ground, for corner of sections 7, 8, 17, and 18, marked with 4 notches on South, and 5 notches on East edges;

from which;

**OUTLINE OF ORIGINAL FIELD NOTES  
SUBDIVISION INTERIOR**

**CHAINS**

A Pinion Pine, 18 ins. diameter, bears N. 22° E., 94 links distance, marked T2S R5W S8 BT.

A Cedar, 12 ins. diameter, bears S. 82° 30' E., 60 links distance, marked T2S R5W S17 BT.

A Cedar, 12 ins. diameter, bears S. 18° W., 87 links distance, marked T2S R5W S18 BT.

A Cedar, 30 ins. diameter, bears N. 62° W., 46 links distance, marked T2S R5W S7 BT.

From the corner of Sections 7, 8, 17, and 18.

**S. 89° 54' W.**, on a true line between sections 7 and 18.

**40.00** Set a Cobble Stone, 20 x 8 x 5 ins. 15 ins. in the ground, for 1/4 section corner, marked 1/4 on North face;

from which;

A Pinion Pine, 10 ins. diameter, bears N. 20° W., 55 links distance, marked 1/4 S7 BT.

A Pinion Pine, 10 ins. diameter, bears S. 60° E., 25 links distance, marked 1/4 S18 BT.

**75.62** The corner of sections 7, 12, 13, 18.

From the corner of Sections 7, 8, 17, and 18.

**N. 00° 04' W.**, between sections 7 and 8.

**40.00** Set a Sandstone, 16 x 8 x 6 ins. 11 ins. in the ground, for 1/4 section corner, marked 1/4 on West face;

from which;

A Pinion Pine, 7 ins. diameter, bears N. 80° E. 20 links distance, marked 1/4 S8 BT.

A Pinion Pine, 6 ins. diameter, bears N. 85°W., 30 links distance, marked 1/4 S7 BT.

**80.00** Set a Sandstone, 18 x 12 x 10 ins. 12 ins. in the ground, for corner of sections 5, 6, 7, and 8, marked with 5 notches on South, and 5 notches on East edges;

from which;

**OUTLINE OF ORIGINAL FIELD NOTES  
SUBDIVISION INTERIOR**

**CHAINS**

A Pinion Pine, 12 ins. diameter, bears N. 50° E., 65 links distance, marked T2S R5W S5 BT.

A Cedar, 6 ins. diameter, bears S. 30° E., 45 links distance, marked T2S R5W S8 BT.

A Pinion Pine, 12 ins. diameter, bears S. 45° W., 62 links distance, marked T2S R5W S7 BT.

A Pinion Pine, 14 ins. diameter, bears N. 18° W., 70 links distance, marked T2S R5W S7 BT.

From the corner of Sections 5, 6, 7, and 8.

**S. 89° 49' W.**, on a true line between sections 6 and 7.

**40.00** Set a Sandstone, 18 x 12 x 6 ins. 12 ins. in the ground, for 1/4 section corner, marked 1/4 on North face;

from which;

A Pinion Pine, 7 ins. diameter, bears North, 20 links distance, marked 1/4 S6 BT.

A Cedar, 12 ins. diameter, bears S. 10° E., 55 links distance, marked 1/4 S7 BT.

**75.40** The corner of sections 1, 6, 7, 12.

**OUTLINE OF ORIGINAL FIELD NOTES  
SUBDIVISION CORRECTION**

*CHAINS*

---

From the corner of Sections 28, 29, 32, and 33, properly described in the original Field Notes,

**N. 00° 03' W.**, between sections 28 and 29.

**40.00** Intersect 1/4 Section Corner on line, properly described in the original Field Notes.

**80.00** The corner of sections 20, 21, 28, and 29, on line, properly described in the original Field Notes.

---

From the corner of Sections 29, 30, 31, and 32, which is a Sandstone 8 x 7 x 6 ins. above ground,

from which;

A Pinion Pine, 20 ins. diameter, bears N. 77° E., 55 links distance, marked T2S R5W S29 BT.

A Pinion Pine, 14 ins. diameter, bears S. 62° E., 18 links distance, marked T2S R5W S32 BT.

A Pinion Pine, 6 ins. diameter, bears S. 27° W., 92 links distance, marked T2S R5W S31 BT.

A Cedar, 6 ins. diameter, bears N. 42° W., 102 links distance, marked T2S R5W S30 BT.

**N. 89° 56' W.**, on a random line between sections 30 and 31.

**40.05** Fall North, 10 links of 1/4 section corner.

**76.27** Intersect West boundary of Township, North 19 links of the corner of sections 25, 30, 31, and 36, properly described in the original Field Notes.

---

**N. 89° 56' E.**, on a true line between sections 30, and 31.

**36.27** Set a Sandstone, 15 x 13 x 4 ins. 12 ins. in the ground, for 1/4 section corner, marked 1/4 on North face;

from which;

A Pinion Pine, 8 ins. diameter, bears N. 9° E. 22 links distance, marked 1/4 S30 BT.

A Pinion Pine, 10 ins. diameter, bears S. 17° W., 78 links distance, marked 1/4 S31 BT.

**OUTLINE OF ORIGINAL FIELD NOTES  
SUBDIVISION CORRECTION**

*CHAINS*

**NOTE:** Destroy all traces of the old corner.

**76.27** The corner of sections 29, 30, 31, and 32.

---

From the corner of Sections 29, 30, 31, and 32.

**N. 00° 04' W.**, between sections 29 and 30.

**39.60** Fall East 3 links of 1/4 section corner.

**NOTE:** Move corner North 40 links, and East 3 links.

Set a Sandstone, 20 x 15 x 6 ins. 15 ins. in the ground, for 1/4 section corner, marked 1/4 on West face;

from which;

A Pinion Pine, 12 ins. diameter, bears N. 57° E. 61 links distance, marked 1/4 S 29 BT.

A Pinion Pine, 6 ins. diameter, bears N. 53° W., 90 links distance, marked 1/4 S30 BT.

**80.50** Fall East 13 links of corner of sections 19, 20, 29, 30.

**NOTE:** Move the corner of sections 19, 20, 29, and 30, South 50 links and East 13 links.

**80.00** Set a Quartzite Stone, 16 x 8 x 6 ins. 11 ins. in the ground, for corner of sections 19, 20, 29, and 30, marked with 2 notches on South, and 5 notches on East edges;

from which;

A Cottonwood, 12 ins. diameter, bears N. 17° E., 78 links distance, marked T2S R5W S20 BT.

**NOTE:** Destroy all traces of the old corner.

---

From the corner of Sections 19, 20, 29, and 30.

**S. 89° 54' E.**, on a random line between sections 20 and 29.

**40.10** Fall North 2 links of the 1/4 section corner.

**80.04** Intersect North and South line, South 51 links of the corner of sections 20, 21, 28, and 29.

**S. 89° 44' W.**, on a true line between sections 20 and 29.

**OUTLINE OF ORIGINAL FIELD NOTES  
SUBDIVISION CORRECTION**

**CHAINS**

**40.02** Set a Sandstone, 18 x 9 x 5 ins. 12 ins. in the ground, for 1/4 section corner, marked 1/4 on North face;

from which;

A Cottonwood, 10 ins. diameter, bears N. 83° E. 43 links distance, marked 1/4 S20 BT.

A Cottonwood, 5 ins. diameter, bears S. 13° W., 18 links distance, marked 1/4 S29 BT.

**NOTE:** Destroy all traces of the old corner.

**80.04** The corner of sections 19, 20, 29, 30.

---

From the corner of Sections 19, 20, 29, and 30.

**S. 89° 54' W.**, on a random line between sections 19 and 30.

**40.30** Fall South 22 links of 1/4 section corner.

**76.04** Intersect West boundary of Township, North 23 links of the corner of sections 19, 24, 25, and 30.

**N. 89° 44' E.**, on a true line between sections 19 and 30.

**36.04** Set a Sandstone, 18 x 8 x 6 ins. 12 ins. in the ground, for 1/4 section corner, marked 1/4 on North face; and raise a mound of stone, 2 feet base, 1 1/2 feet high, North of corner.

**NOTE:** Destroy all traces of the old corner.

**76.04** The corner of sections 19, 20, 29, 30.

---

From the corner of Sections 19, 20, 29, and 30.

**N. 00° 04' W.**, between sections 19 and 20.

**40.10** Fall East 2 links of 1/4 corner

**NOTE:** Move the corner East 2 links and South 10 links.

**40.00** Set a Sandstone, 15 x 14 x 8 ins. 10 ins. in the ground, for 1/4 section corner, marked 1/4 on West face;

from which;

**OUTLINE OF ORIGINAL FIELD NOTES  
SUBDIVISION CORRECTION**

**CHAINS**

A Cedar, 14 ins. diameter, bears N. 40° 30' E. 114 links distance, marked 1/4 S20 BT.

A Cedar, 5 ins. diameter, bears N. 23° W., 56 links distance, marked 1/4 S19 BT.

**NOTE:** Destroy all traces of the old corner.

**80.30** Fall East 10 links of corner of sections 17, 18, 19, 20.

**NOTE:** Move the corner East 10 links and South 30 links.

**80.00** Set a Sandstone, 18 x 10 x 5 ins. 12 ins. in the ground, for corner of sections 17, 18, 19, and 20, marked with 3 notch on South, and 5 notches on East edges;

from which;

A Cedar, 6 ins. diameter, bears N. 56° 30' E., 53 links distance, marked T2S R5W S17 BT.

A Cedar, 8 ins. diameter, bears S. 76° E., 55 links distance, marked T2S R5W S20 BT.

A Cedar, 6 ins. diameter, bears S. 57° W., 14 links distance, marked T2S R5W S19 BT.

A Pinion Pine, 12 ins. diameter, bears N. 44° 30' W., 137 links distance, marked T2S R5W S18 BT.

**NOTE:** Destroy all traces of the old corner.

---

From the corner of Sections 17, 18, 19, and 20.

**N. 89° 56' E.**, on a random line between sections 17 and 20.

**40.15** Fall South 9 links of the 1/4 corner between sections 17, and 20.

**80.00** Intersect North and South line South 23 links of the corner of sections 16, 17, 20, and 21.

**S. 89° 46' W.**, on a true line between sections 17, and 20.

**40.00** Set a Sandstone, 24 x 10 x 8 ins. 12 ins. in mound of rock, for 1/4 section corner, marked 1/4 on North face;

from which;

**OUTLINE OF ORIGINAL FIELD NOTES  
SUBDIVISION CORRECTION**

**CHAINS**

A Cedar, 8 ins. diameter, bears N. 40°15' W., 46 links, distance, marked 1/4 S17 BT.

A Pinion Pine, 8 ins. diameter, bears S. 70° E., 16 links, distance, marked 1/4 S20 BT.

**NOTE:** Destroy all traces of the old corner.

**80.00** The corner of sections 17, 18, 19, 20.

---

From the corner of Sections 17, 18, 19, and 20.

**S. 89° 56' W.**, on a random line between sections 18 and 19.

**40.00** Fall South 23 links of 1/4 section corner.

**75.82** Intersect West boundary of Township, North 38 links of the corner of sections 13, 18, 19, and 24.

**N. 89° 40' E.**, on a true line between sections 18 and 19.

**35.82** Set a Hard Cobble Stone, 15 x 8 x 6 ins. 10 ins. in the ground, for 1/4 section corner, marked 1/4 on North face; and raise a mound of stone, 2 feet base, 1 1/2 feet high, North of corner.

**NOTE:** Destroy all traces of the old corner.

**75.82** The corner of sections 17, 18, 19, 20.

---

From the corner of Sections 17, 18, 19, and 20.

**N. 00° 04' W.**, between sections 17 and 18.

**40.70** Fall West 20 links of 1/4 section corner.

**NOTE:** Move the corner South 70 links and West 20 links.

**40.00** A Boulder in place, 3 x 2 x 2 feet above ground for 1/4 section corner. Mark with a cross at the exact corner point for 1/4 section corner; with 1/4 West of cross;

from which;

A Pinion Pine, 5 ins. diameter, bears N. 24° 15' E. 83 links distance, marked 1/4 S17 BT.

**OUTLINE OF ORIGINAL FIELD NOTES  
SUBDIVISION CORRECTION**

*CHAINS*

A Pinion Pine, 8 ins. diameter, bears N. 27° 30' W., 61 links distance, marked 1/4 S18 BT.

**NOTE:** Destroy all traces of the old corner.

**80.00** The corner of sections 7, 8, 17, and 18, which is a Sandstone, 10 x 5 x 5 ins. above ground, firmly set, and mark, as described by the original Field Notes;

from which;

A Cedar, 16, ins. diameter, bears N. 36° 50' E., 99 links distance, marked T2S R5W S8 BT.

A Pinion Pine, 6 ins. diameter, bears S. 78° E., 79 links distance, marked T2S R5W S17 BT.

A Cedar, 16 ins. diameter, bears S. 49° W., 52 links distance, marked T2S R5W S18 BT.

A Cedar, 12 ins. diameter, bears N. 79° 45' W., 27 links distance, marked T2S R5W S7 BT.

From the corner of Sections 7, 8, 17, and 18.

**S. 89° 54' W.**, on a random line between sections 7 and 18.

**40.03** Fall South 9 links of 1/4 section corner.

**75.62** Intersect West boundary of Township, North 33 links of corner of sections 7, 12, 13, 18.

**N. 89° 40' E.**, on a true line between sections 7, and 18.

**35.62** Set a Cobble Stone, 20 x 8 x 5 ins. 15 ins. in the ground, for 1/4 section corner, marked 1/4 on North face;

from which;

A Pinion Pine, 6 ins. diameter, bears N. 12° W., 12 links distance, marked 1/4 S7 BT.

A Pinion Pine, 14 ins. diameter, bears S. 32° 30' E., 97 links distance, marked 1/4 S18 BT.

**NOTE:** Destroy all traces of the old corner.

**75.62** The corner of sections 7, 8, 17, 18.

---

OUTLINE OF ORIGINAL FIELD NOTES  
BOOK VOLUME - A - 317  
TOWNSHIP 01 SOUTH, RANGE 05 WEST  
UINTAH SPECIAL MERIDIAN

ANDREW J. STEWART JR. & ALFRED L. BOOTH  
CONTRACT NUMBER 270, DATE JULY 22, 1903

---

WEST BOUNDARY

CHAINS

From the corner of Townships 1 and 2 South, Ranges 5 and 6 West, which is a Sandstone 30 x 30 x 15 ins. above ground, firmly set and marked and witnessed as described by the Surveyor General.

Remark the corner with 6 notches on each edge and 1S, on North-East; 5W, on South-East; 2S, on South-West; and 6W, on North-West; faces, and raised a mound of stone 2 feet base, 1 1/2 feet high, South of corner, pits impracticable.

North between 31, and 36.

**40.00** Set a Sandstone, 18 x 10 x 8 ins; 12 ins. in the ground for 1/4 section corner marked 1/4 on West face;

from which;

A Pinion Pine, 6 ins. diameter, bears S. 40° E., 50 links, distance, marked 1/4 S31 BT.

A Cedar, 8 ins. diameter, bears S. 70° W., 275 links, distance, marked 1/4 S36 BT.

**80.00** Set a Sandstone, 20 x 15 x 10 ins. 15 ins. in the ground, for corner of sections 25, 30, 31, and 36, marked with 1 notch on South, and 5 notches on North edges;

from which;

A Pinion Pine, 18 ins. diameter, bears N. 40° E., 60 links distance, marked T1S R5W S30 BT.

A Pinion Pine, 12 ins. diameter, bears S. 25° E., 45 links distance, marked T1S R5W S31 BT.

A Pinion Pine, 4 ins. diameter, bears S. 40° W., 30 links distance, marked T1S R6W S36 BT.

A Pinion Pine, 6 ins. diameter, bears N. 50° W., 44 links distance, marked T1S R6W S25 BT.

---

---

**OUTLINE OF ORIGINAL FIELD NOTES  
BOOK VOLUME - A - 318  
TOWNSHIP 02 SOUTH, RANGE 06 WEST  
UINTAH SPECIAL MERIDIAN**

**ANDREW J. STEWART JR. & ALFRED L. BOOTH  
CONTRACT NUMBER 270, DATE JULY 22, 1903**

---

**NORTH BOUNDARY**

**CHAINS**

At the Corner of Township 1 and 2 South, Ranges 5 and 6 West, heretofore described.

**West** on a random line along North boundary of T2S, R6W, setting temporary 1/4 section and section corners at intervals of 40.00 chains, and at 476.80 chains intersect West boundary of Township 139 links North of the Corner of Township 1 and 2 South, Ranges 6 and 7 West, the falling answers to a correction of 10 or 23 links North per mile, counting from the corner of Township 1 and 2 South, Ranges 6 and 7 West.

**N. 89° 50' E.**, on a true line, between sections 6 and 31.

**80.00** Set Sandstone, 18 x 11 x 4 ins. 12 ins. in the ground for corner of sections 1, 2, 35, and 36, marked with 1 notch on East and 5 notches on West edges;

from which;

A Pinion Pine, 18 ins. diameter, bears N. 65° E., 60 links distance, marked T1S R6W S36 BT.

A Pinion Pine, 18 ins. diameter, bears S. 60° E., 72 links distance, marked T2S R6W S1 BT.

A Red Pine, 18 ins. diameter, bears S. 32° W., 90 links distance, marked T2S R6W S2 BT.

A Pinion Pine, 17 ins. diameter, bears N. 45° W., 35 links distance, marked T1S R6W S35 BT.

**N. 89° 50' E.**, on true line between sections 1, and 36.

**40.00** Set a Sandstone, 18 x 10 x 6 ins. 12 ins. in the ground for 1/4 section corner marked 1/4 on North face;

from which;

A Pinion Pine, 10 ins. diameter, bears S. 15° E., 20 links distance, marked 1/4 S1 BT.

**OUTLINE OF ORIGINAL FIELD NOTES  
NORTH BOUNDARY**

*CHAINS*

A Pinion Pine, 8 ins. diameter, bears N. 60° W., 15 links  
distance, marked 1/4 S36 BT.

**80.00** The corner of Township 1 and 2, South; Ranges 5 and 6 West.

---

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

**FIELD ASSISTANTS**

NAMES	CAPACITY
David W. Ginther	Cadastral Surveyor
George E. Allen	Cadastral Surveyor
Scott L. Twenhofel	Survey Technician
Rebecca M. Bruno	Survey Technician
Michael C. Miller	Survey Technician
Jaymoe Tapoof	Survey Aid
Bryan C. Collings	Survey Aid
Lonnie Favel	Survey Aid

## CERTIFICATE OF SURVEY

I, **Scott A. Burkhardt, Cadastral Surveyor**, hereby certify upon honor that, in pursuance of special instructions bearing the date of the **22nd day of April, 2003**, I have **dependently resurveyed the west boundary, a portion of the subdivisional lines, and subdivided certain sections, in Township 2 South, Range 5 West**, of the **Uintah Special Meridian**, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 10, 2004

Date

Scott A. Burkhardt

(Cadastral Surveyor)

\_\_\_\_\_  
Date

\_\_\_\_\_  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the **dependent resurvey of the west boundary and a portion of the subdivisional lines, and the subdivision of certain sections, in Township 2 South, Range 5 West, Uintah Special Meridian, Utah**,

executed by **Scott A. Burkhardt, Cadastral Surveyor**

having been critically examined and found correct, are hereby approved.

September 7, 2004

Date

Daniel W. Wells

(Chief Cadastral Surveyor for Utah)