

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE EAST BOUNDARY OF

TOWNSHIP 30 SOUTH, RANGE 9 WEST

AND

THE SOUTH BOUNDARY OF

TOWNSHIP 29 SOUTH, RANGE 8 WEST

AND

A PORTION OF THE SUBDIVISIONAL LINES

IN

TOWNSHIP 30 SOUTH, RANGE 8 WEST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

John F. Carroll, Cadastral Surveyor

AND REASSIGNED TO

Ronald K. Baugh, Supervisory Cadastral Surveyor

Under Special Instructions dated **April 25, 2003**, approved **April 25, 2003**, which provided for the surveys included under Group Number **963**, and Assignment Instructions dated **April 25, 2003**, and Reassignment Instructions dated **June 12, 2006**.

Survey commenced **April 30, 2003**
Survey completed **June 5, 2003**

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE EAST BOUNDARY OF

TOWNSHIP 30 SOUTH, RANGE 9 WEST

AND

THE SOUTH BOUNDARY OF

TOWNSHIP 29 SOUTH, RANGE 8 WEST

AND

A PORTION OF THE SUBDIVISIONAL LINES

IN

TOWNSHIP 30 SOUTH, RANGE 8 WEST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

John F. Carroll, Cadastral Surveyor

AND REASSIGNED TO

Ronald K. Baugh, Supervisory Cadastral Surveyor

Under Special Instructions dated **April 25, 2003**, approved **April 25, 2003**, which provided for the surveys included under Group Number **963**, and Assignment Instructions dated **April 25, 2003**, and Reassignment Instructions dated **June 12, 2006**.

Survey commenced **April 30, 2003**
Survey completed **June 5, 2003**

INDEX DIAGRAM

Township 30 South, Range 8 West

	10	10	9	8	7	6
5	6 35	5 28	4 24	3 20	2 16	1
	34	34	28	24	20	15
4	7 33	8 27	9 24	10 19	11 14	12
	32	32	27	23	19	14
3	18 31	17 26	16 23	15 18	14 13	13
	30	29	25	23	18	13
	19	20	21 22	22 17	23 12	24
				21	16	
	30	29	28	27	26	25
	31	32	33	34	35	36

The following field notes are those of the dependent resurvey of a portion of the east boundary of T. 30 S., R. 9 W. and the south boundary of T. 29 S., R. 8 W., and a portion of the subdivisional lines in T. 30 S., R. 8 W., Salt Lake Meridian, Utah.

History of Surveys

Surveyed by		Retr. or Resurveyed by	
SOUTH BOUNDARY (Sixth Standard Parallel South)			
All	T.C Bailey	1881	
All			J.R. Stewart, Q. Stewart 1910
All			R.C. Yundt 1950
EAST BOUNDARY			
All	T.C. Bailey	1881	
Portion			H. Fitzhugh 1882
All			R.C. Yundt 1950
WEST BOUNDARY			
All	T.C. Bailey	1881	
All			R.C. Yundt 1950
Portion			R.K Baugh 1991
NORTH BOUNDARY			
All	J. Bausman	1870	
All			T.C. Bailey 1881
All			R.C. Yundt 1950
SUBDIVISION			
All	R.C. Yundt	1950	
COUNTY SURVEYS			

The Beaver County Surveyor's office has remonumented some corners in the township, with Corner Perpetuation and Filing Records on file in the Beaver County Recorder's office.

T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

This survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 963, dated April 25, 2003.

The direction of the lines was determined by references to true meridians, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards and Guidelines for Cadastral Surveys Using GPS Methods*, dated May 9, 2001, Version 1.0. Trimble model 5700 GPS receivers were used for field collection. Cadastral Measurement Management (CMM) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and their calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Beaver County Survey Control Station "BILL GILLIS" with the published data as follows:

Latitude: **38°15'22.062" N.** Longitude: **112°38'29.058" W.**
N.A.D. 1983.

The geographic position of the corner of sections 23, 24, 25, and 26, determined by using RTK methods from indirect ties made to Beaver County Survey Control Station "BILL GILLIS" is as follows:

Latitude: **38°10'35.595" N.** Longitude: **112°42'48.819" W.**
N.A.D. 1983.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY
T. 30 S., R. 9 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the East Boundary
T. 30 S., R. 9 W., Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by T.C. Bailey in 1881,
and the Resurvey Executed by R.C. Yundt in 1950.

Beginning at the corner of sections 13 and 24 only, monumented
with an iron post 2 inches diameter, firmly set, projecting 6
inches above ground, with brass cap marked as described in the
official record of the 1950 resurvey.

from which the 1950 bearing trees

A piñon, 12 ins. diam., bears S. 22° W., 31 links distance,
scribed T30S R9W S24 BT visible on a partially healed
blaze.

A cedar, 10 ins. diam., bears N. 12° W., 30 links distance,
scribed T30S R9W S13 BT visible on a partially healed
blaze.

Corner falls in a steep rocky wash draining northwest, with
piñon and juniper growth.

From this point, the monumented closing corner of sections 18
and 19, T. 30 S., R. 8 W., bears S. 0° 07.2' E., 2.813 chains
distance, hereinafter described.

N. 0°17.5' W., on the east boundary of section 13.

37.445 The 1/4 section corner of section 18 only, T. 30 S., R. 8 W.,
monumented with an iron post, 2 inches diameter, firmly set,
in a mound of stone, with brass cap marked as described in the
official record of the 1950 resurvey, (Record, 1 inch diameter
iron post).

Set a steel fence post alongside the iron post.

Corner falls on a gradual northeast slope in piñon and juniper
growth.

41.138 The 1/4 section corner of section 13 only, monumented with an
iron post, 1 inch diameter, firmly set, in a mound of stone,
with brass cap marked as described in the official record of
the 1950 resurvey.

Set a steel fence post 1 ft. west of the iron post.

Corner falls on a gradual northeast slope in piñon and juniper
growth.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY
T. 30 S., R. 9 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0°14.5' W., beginning new measurement.

36.284 The closing corner of sections 7 and 18, hereinafter described.

40.838 The corner of sections 12 and 13 only, monumented with an iron post, 2 inches diameter, firmly set, projecting 9 inches above a collar of stone, with brass cap marked as described in the official record of the 1950 resurvey, witnessed with a mound of stone to the east.

Set a steel fence post alongside the iron post.

Corner falls on flat ground in sagebrush, piñon and juniper growth.

N. 1°38.1' E., on the east boundary of section 12.

35.490 The 1/4 section corner of section 7 only, T. 30 S., R 8 W., monumented with an iron post, 2 inches diameter, firmly set in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post alongside the iron post.

Corner falls on flat ground in sagebrush.

N. 1°36.6' E., beginning new measurement.

5.540 The 1/4 section corner of section 12 only, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 resurvey.

Set a steel fence post 1 ft. west of the iron post.

Corner falls on a gradual northwest slope in sagebrush.

N. 0°20.2' E., beginning new measurement.

34.514 True point for the closing corner of sections 6 and 7, hereinafter described.

41.008 The corner of sections 1 and 12 only, monumented with and iron post, 2 inches diameter, firmly set in a mound of stone, with brass cap marked as described in the official record of the 1950 resurvey, witnessed with a mound of stone to the west.

Set a steel fence post alongside the iron post.

Corner falls on a gradual north slope in sagebrush.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY
T. 30 S., R. 9 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 1°29.4' E., on the east boundary of section 1.

- 33.506 Point for the 1/4 section corner of section 6 only, T. 30 S., R. 8 W., at proportionate distance; there is no remaining evidence of the original corner, not monumented.

Corner falls on the edge of pavement of Utah State Highway No. 21, bears N. 50° E. and S. 50° W.

- 40.198 The 1/4 section corner of section 1 only, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 resurvey, witnessed with a mound of stone to the west.

Set a steel fence post 2 ft. west of the iron post.

Corner falls on a northeast slope and 60 ft. south of a draw, drains S. 60° W.

Reestablishment of the Survey Executed by T.C. Bailey in 1881,
the Resurveys Executed by R.C. Yundt in 1950 and
R.K. Baugh in 1991.

N. 1°29.0' E., beginning new measurement.

- 19.719 The N 1/16 section corner of section 1 only, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with aluminum cap marked as described in the official record of the 1991 resurvey, witnessed with a mound of stone to the west.

Set a steel fence post alongside the aluminum post.

Corner falls on a southwest slope, 40 ft. west of a fence line, bears north and south, and 60 ft. north of a fence line, bears east and west.

- 33.302 The 80 1/16 section corner of section 6 only, T. 30 S., R. 8 W., monumented with an iron post, 1 inch diameter, bent to the south, with brass cap marked as described in the official record of the 1950 resurvey, bears East, 0.019 chains distance.

Due to the condition of the original corner, apparently having been disturbed during road grading, measurements were taken at the base of the iron post, and was determined necessary to re-monument the corner point.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY
T. 30 S., R. 9 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet in a clear plastic case at the base, set in a mound of stone, 3 ft. base to top, of aluminum cap marked:

T30S
R9W R8W
| 80 1/16
| S6
2003

Set a steel fence post to the east of the aluminum post.

The iron post was removed from the project area.

Corner falls on the west edge of a dirt road 10 ft. wide, bears north and south, and 12 ft. west of a fence line, bears north and south, in scattered sagebrush.

40.424

The corner of Tps. 29 and 30 S., Rs. 8 and 9 W., monumented with an iron post, 2 inches diameter, set flush with ground, with brass cap marked as described in the official record of the 1950 resurvey.

Corner falls at the intersection of fence lines projecting north, south, and east, and 15 ft. north of the center of a dirt road 10 ft. wide, bears east and west.

Dependent Resurvey of the South Boundary,
T. 29 S. R. 8 W., Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by J. Bausman in 1870,
and the Resurveys Executed by
T.C. Bailey in 1881, and R.C. Yundt in 1950.

From the corner of Tps. 29 and 30 S., Rs. 7 and 8 W., monumented with an iron post, 2 inches diameter, firmly set, 2 inches below ground, with brass cap marked as described in the official record of the 1950 resurvey of the west boundary of T. 30 S., R. 7 W.

From this corner, Beaver County Survey Station "BILL GILLIS", monumented with an iron post, 2 inches diameter, firmly set in concrete, with a 3 1/4 inches diameter brass cap attached and marked BILL GILLIS 1997, bears N. 63°58'52" E., forward bearing and S. 64°00'52" W., back bearing, 260.378 chains distance.

N. 89°46.7' W., on the south boundary of section 36.

39.997

The 1/4 section corner of section 1 only, T. 30 S., R 8 W., monumented with an iron post, 1 inch diameter, projecting 8

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 29 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

inches above ground, with brass cap marked as described in the official record of the 1950 resurvey.

Corner falls on a north slope in sagebrush, 1 ft. north of a fence line, bears east and west, and 44 ft. north of a gravel road 25 ft. wide, bears east and west.

- 40.360 The 1/4 section corner of section 36 only, monumented with an iron post, 1 inch diameter, firmly set, projecting 7 inches above ground, with brass cap marked as described in the official record of the 1950 resurvey.

Corner falls on a north slope in sagebrush 1 ft. north of a fence line bears east and west, and 44 ft. north of a gravel road 25 ft. wide bears east and west.

N. 89°50.2' W., beginning new measurement.

- 39.670 The closing corner of sections 1 and 2 only, hereinafter described.

- 40.367 Point for the corner of sections 35 and 36 only, at proportionate distance; there is no remaining evidence of the original marked stone or the 1950 iron post.

Set a bathy brand t-iron, 18 inches long, driven down with top 6 inches below the surface of the ground, with a magnet in a clear plastic case alongside at the base, with a 3 1/4 inches diameter aluminum cap marked:

T29SR8W
S35|S36
S2
T30S
2003

Corner falls in the middle of a road intersection, projecting east, west, and north.

N. 89°50.2' W., on the south boundary of section 35.

- 39.485 The 1/4 section corner of section 2 only, T. 30 S., R. 8 W., monumented with an iron post, 1 inch diameter, bent to the west, with brass cap missing.

Due to the condition of the original corner, apparently being disturbed during the construction of a fence line.

Measurements were taken at the base of the iron post, and was determined necessary to re-monument the corner point.

At the corner point

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 29 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet in a clear plastic case at the base, with aluminum cap marked:

T29SR8W
1/4 S2
T30SR8W
2003

Deposited the iron post alongside the aluminum post.

Corner falls on flat ground in scattering sagebrush, and 7 ft. north of a fence line, bears east and west.

- 40.367 The 1/4 section corner of section 35 only, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with brass cap marked: LS 174457, 1/4 S35 T30S 1999. This monument is accepted as the best available evidence of the position of the 1950 iron post monument.

Found the iron post monument with the brass cap missing laying on the ground. The monument had apparently been pulled and thrown aside.

The marked stone was recovered nearby and buried alongside the stainless steel post.

The iron post was removed from the project area.

Corner falls on flat ground in sagebrush, 7 ft. north of a fence line, bears east and west.

N. 89°51.2' W., beginning new measurement.

- 39.275 The closing corner of sections 2 and 3, hereinafter described.

- 40.325 The corner of sections 34 and 35 only, monumented with an iron post, 2 inches diameter, firmly set, with brass cap marked as described in the official record of the 1950 resurvey, with a 4 inch diameter wooden post 1.5 feet west.

Raised a small mound of stone north of the iron post.

Corner falls 2.5 ft. west of a fence corner, projecting east and south.

N. 89°53.1' W., on the south boundary of section 34.

- 38.967 The 1/4 section corner of section 3 only, T. 30 S., R. 8 W., monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 resurvey.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 29 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post 3 ft. south of the iron post.

Corner falls on a north slope in sagebrush.

- 40.419 The 1/4 section corner of section 34 only, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 resurvey.

Set a steel fence post 1.5 ft. west of the iron post.

Corner falls on a northeast slope in sagebrush.

N. 89°53.8' W., beginning new measurement.

- 38.525 The closing corner of sections 3 and 4 only, hereinafter described.

- 40.379 The corner of sections 33 and 34, monumented with an iron post, 2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1950 resurvey, witnessed by a mound of stone to the north.

Set a steel fence post 0.5 ft. east of the iron post.

Corner falls on flat ground in sagebrush.

N. 89°47.9' W., on the south boundary of section 33.

- 38.328 The 1/4 section corner of section 4 only, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, 3 ft. base to top of brass cap marked as described in the official record of the 1950 resurvey.

Set a steel fence post alongside the iron post.

Corner falls on flat ground in sagebrush.

- 40.292 The 1/4 section corner of section 33 only, monumented with an iron post, 1 inch diameter, firmly set, projecting 21 inches above ground, with brass cap marked as described in the official record of the 1950 resurvey.

Set a steel fence post 3 ft. west of the iron post.

Corner falls on flat ground in sagebrush.

N. 89°46.5' W., beginning new measurement.

- 38.266 The closing corner of sections 4 and 5 only, hereinafter described.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 29 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.339** The corner of sections 32 and 33 only, monumented with an iron post, 2 inches diameter, firmly set, projecting 8 inches above ground with brass cap marked as described in the official record of the 1950 resurvey, witnessed with a mound of stone, southeast, 4 ft. to center.
- Set a steel fence post 1.5 ft. south of the iron post.
-
- N. 89°55.1' W.**, on the south boundary of section 32.
- 38.055** The 1/4 section corner of section 5 only, T. 30 S., R. 8 W., monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 resurvey.
- Set a steel fence post along south side the iron post.
- Corner falls on flat ground in sagebrush.
- 40.258** The 1/4 section corner of section 32 only, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 resurvey.
- Set a steel fence post along north side the iron post.
- Corner falls on flat ground in sagebrush.
-
- N. 89°49.7' W.**, beginning new measurement.
- 37.964** The true point for the closing corner of sections 5 and 6 only, hereinafter described.
- 40.322** The corner of sections 31 and 32 only, monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 resurvey.
- Set a steel fence post 0.5 ft. west of the iron post.
- Corner falls on a gradual northwest slope in sagebrush.
-
- N. 89°44.0' W.**, on the south boundary of section 31.
- 37.632** The 1/4 section corner of section 6 only, T. 30 S., R. 8 W., monumented with an iron post, 1 inch diameter, bent 90° to the west, with brass cap marked as described in the official record of the 1950 resurvey.
- Due to the condition of the original iron post monument, apparently being disturbed during road grading, measurements were taken at the base of the iron post, and was determined necessary to re-monument the corner point.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 29 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, set with top 18 inches below the surface of the ground, with a magnet in a clear plastic case at the base, with aluminum cap marked:

T29SR8W
1/4 S6
T30SR8W
2003

The iron post was removed from the project area.

The corner falls 10 ft. north of the centerline of a dirt road 10 ft. wide, bears east and west.

- 40.280 The 1/4 section corner of section 31 only, monumented with an iron post, 1 inch diameter, firmly set, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1950 resurvey.

Set a steel fence post 1 ft. east of the iron post.

Corner falls on a gradual northwest slope in sagebrush, 15 ft. north of the centerline of a dirt road 10 ft. wide, bears east and west.

N. 89°52.2' W., beginning new measurement.

- 40.329 The corner of Townships 29 and 30 South, Ranges 8 and 9 West, hereinbefore described.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 8 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
R. C. Yundt in 1950.

From the corner of sections 23, 24, 25, and 26, monumented with an iron post, 2 inches diameter, firmly set, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1950 survey.

from which the original 1950 bearing trees

A juniper, 10 ins. diam., bears N. 65° E., 83 links distance, with illegible scribe marks visible.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

A piñon down and dead, 6 ins. diam., bears S. 80° E., 119 links distance, with scribe marks BT visible on a partially healed blaze.

A piñon down and dead, 12 ins. diam., bears S. 69° W., 78 links distance, scribed T30S R8W S26 BT on a partially healed blaze.

A piñon, 12 ins. diam., bears N. 76° W., 40 links distance, with scribe marks S23 BT visible on a partially healed blaze.

Set a steel fence post alongside the iron post.

Corner falls on a northwest slope in piñon and juniper growth.

N. 0°00.5' E., between sections 23 and 24.

40.020

The 1/4 section corner of sections 23 and 24, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

from which the original 1950 bearing tree

A piñon stump, 6 ins. diam., bears S. 85° E., 68 links distance, with scribe marks T visible on a partially healed blaze. (Record, N. 80° E.)

No remains of the original NW bearing tree was found.

Set a steel fence post 0.5 ft. east of the iron post.

Corner falls 15 ft. west of a dirt road 15 ft. wide, bears N. 20° E. and S. 20° W., and 30 ft. north of same dirt road, bears N. 30° E. and S. 30° W.

N. 0°00.3' E., beginning new measurement.

39.981

The corner of sections 13, 14, 23, and 24, monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone, 2 ft. base to top, with brass cap marked as described in the official record of the 1950 survey.

from which the original 1950 bearing trees

A juniper, 7 ins. diam., bears N. 64° E., 66 links distance, with scribe marks BT visible on an open blaze.

A piñon stump, 9 ins. diam., bears S. 7° E., 62 links distance, no marks visible.

A piñon, 6 ins. diam., bears S. 66° W., 82 links distance, with scribe marks BT visible on a partially healed blaze.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

A juniper, 8 ins. diam., bears N. 50° W., 41 links distance, with scribe marks BT visible on a partially healed blaze.

Set a steel fence post 0.5 ft. north of the iron post.

Corner falls on a gradual northwest slope in piñon and juniper growth.

From the corner of sections 13 and 24 only, on the east boundary of the township, monumented with an iron post, 2 inches diameter, firmly set in a mound of stone, with brass cap marked as described in the official record of the 1950 dependent resurvey of the west boundary of Township 30 South, Range 7 West.

N. 89°50.0' W., between sections 13 and 24.

40.092 The 1/4 section corner of sections 13 and 24, monumented with an iron post, 1 inch diameter, firmly set, projecting 9 inches above ground, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post 1 ft. east of the iron post.

Corner falls on a northeast slope in piñon growth.

S. 89°52.4' W., beginning new measurement.

39.945 The corner of sections 13, 14, 23, and 24.

N. 0°00.1' E., between sections 13 and 14.

39.998 The 1/4 section corner of sections 13 and 14, monumented with an iron post, 1 inch diameter, firmly set, projecting 7 inches above ground, with brass cap marked as described in the official record of the 1950 survey.

from which the original 1950 bearing trees

A juniper branch, 5 ins. diam., bears S. 49° E., 36 links distance, found lying on the ground, no marks visible.

A juniper stump, 9 ins. diam., bears N. 87° W., 55 links distance, no marks visible.

Set a steel fence post 0.5 ft. northwest of the iron post.

Corner falls on a northwest slope in piñon and juniper growth.

N. 0°00.3' W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.018** The corner of sections 11, 12, 13, and 14, monumented with an iron post, 2 inches diameter, firmly set, projecting 2 inches above ground, with brass cap marked as described in the official record of the 1950 survey.
- Set a steel fence post 0.5 ft. west of the iron post.
- Corner falls on flat ground in scattered juniper growth.
-
- From the corner of sections 12 and 13 only, on the east boundary of the township, monumented with an iron post, 2 inches in diameter, firmly set, projecting 9 inches above ground, with brass cap marked as described in the official record of the dependent resurvey of the west boundary of Township 30 South Range 7 West.
- S. 89°43.7' W.**, between sections 12 and 13.
- 39.904** The 1/4 section corner of sections 12 and 13, monumented with an iron post, 1 inch diameter, firmly set, projecting 10 inches above ground, with brass cap marked as described in the official record of the 1950 survey.
- Set a steel fence post 0.5 ft. north of the iron post.
- Corner falls on a northwest slope in scattered piñon and juniper growth.
-
- N. 89°44.1 W.**, beginning new measurement.
- 39.894** The corner of sections 11, 12, 13, and 14.
-
- N. 0°00.4' E.**, between sections 11 and 12.
- 40.015** Point for the 1/4 section corner of sections 11 and 12, at proportionate distance.
- The original 1950 iron post monument was found lying loose in a wash. It was determined that the position of the corner point was lost.
- Reset the original iron post monument, 36 inches long, 1 inch diameter, 34 inches in the ground, with a magnet in a clear plastic case at the base, with the brass cap marked as described in the official record of the 1950 survey. I add the date 2003 to the brass cap.
- Corner falls in a wash 4 ft. deep, drains N. 10° W., in a sagebrush and scattered cedar area.
- from which

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet in a clear plastic case at the base, for a reference monument, bears S. 65°14.1' W., 33.3 links distance, with aluminum cap marked: RM 1/4 S11 22 ft. 2003, with an arrow pointing to the corner. Drive a steel fence post along west side of the aluminum post.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet in a clear plastic case at the base, for a reference monument, bears N. 42°29.7' E., 50.2 links distance, with aluminum cap marked: RM 1/4 S12 33.2 ft. 2003, with an arrow pointing to the corner. Drive a steel fence post along the east side of the aluminum post.

Set a steel fence post alongside the iron post.

80.030 The corner of sections 1, 2, 11, and 12, monumented with an iron post, 2 inches diameter, firmly set, projecting 9 inches above ground, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post 0.5 ft. west of the iron post.

Corner falls on a gradual northwest slope in sagebrush, 1.5 ft. southeast of the intersection of fences projecting north and west.

From the corner of sections 1 and 12, on the east boundary of the township, monumented with an iron post, 2 inches diameter, firmly set, projecting 13 inches above grounds, with brass cap marked as described in the official record of the 1950 dependent resurvey of the west boundary of Township 30 South Range 7 West.

N. 89°59.8' W., between sections 1 and 12.

39.878 The 1/4 section corner of sections 1 and 12, monumented with an iron post, 1 inch diameter, firmly set, projecting 10 inches above ground, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post 0.5 ft. southwest of the iron post.

Corner falls on a gradual northeast slope in sagebrush, 150 ft. east of a fence line, bears N. 10° E., and S. 10° W.

S. 89°59.0' W., beginning new measurement.

39.963 The corner of sections 1, 2, 11, and 12.

N. 0°00.1' W., between sections 1 and 2.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.002 The 1/4 section corner of sections 1 and 2, monumented with an iron post, 1 inch diameter, firmly set, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1950 survey, with a steel fence post set alongside.

Corner falls on flat ground in sagebrush.

N. 0°00.8' E., beginning new measurement.

- 39.994 The 80 1/16 section corner of sections 1 and 2, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey, with a steel fence post alongside.

Corner is located 15 ft. east of a swale, drains northeast.

N. 0°00.8' E., beginning new measurement.

- 5.279 The closing corner of sections 1 and 2, at intersection with the south boundary of section 36, T. 29 S. R. 8 W., monumented with an iron post, 2 inches diameter, firmly set, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1950 survey.

Corner falls in a fence line, bears east and west.

From the corner of sections 23, 24, 25, and 26.

S. 89°50.7' W., between sections 23 and 26.

- 40.119 The 1/4 section corner of sections 23 and 26, monumented with an iron post, 1 inch diameter, 11 inches above ground firmly set, in a collar of stone 1.5 ft. base to top, with brass cap marked as described in the official record of the 1950 survey.

from which the original 1950 bearing tree

A piñon, 10 ins. diam., bears N. 26° E., 74 links distance, with scribe marks BT visible on a partially healed blaze.

No remains of the original SE bearing tree was found.

Raise a mound of stone, 1 1/2 ft. base to top of iron post.

Set a steel fence post along north side the iron post.

Corner falls on a northeast slope in piñon and juniper growth.

S. 89°52.0' W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.091 The corner of sections 22, 23, 26, and 27, monumented with an iron post, 2 inches diameter, firmly set, projecting 14 inches above ground, with brass cap marked as described in the official record of the 1950 survey, witnessed with a mound of stone to the west.

from which the original 1950 bearing trees

A piñon, 10 ins. diam., bears N. 44° E., 37 links distance, with scribe marks BT visible on a partially healed blaze.

A juniper, 7 ins. diam., bears S. 59° E., 19 links distance, with scribed T30S R8W S26 BT on a partially healed blaze.

A juniper, 5 ins. diam., bears S. 34° W., 52 links distance, with scribe marks BT visible on a partially healed blaze.

A juniper, 8 ins. diam., blaze bears N. 25° W., 52 links distance, with scribe marks BT visible on a partially healed blaze.

Set a steel fence post along west side the iron post.

Corner falls on a northwest slope in piñon and juniper growth.

N. 0°02.3' W., between sections 22 and 23.

40.001 The 1/4 section corner of sections 22 and 23, monumented with an iron post, 1 inch diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post 0.5 ft. west of the iron post.

Corner falls on a gradual northwest slope in sagebrush and piñon growth.

N. 0°01.0' W., beginning new measurement.

40.046 The corner of sections 14, 15, 22, and 23, monumented with an iron post, 2 inches diameter, firmly set, projecting 9 inches above the ground, with the brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post along north side the iron post.

Corner falls on flat ground in sagebrush and scattered piñon growth.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 13, 14, 23, and 24.

N. 89°52.8' W., between sections 14 and 23.

- 40.122 The 1/4 section corner of sections 14 and 23, monumented with an iron post, 1 inch diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post along north side the iron post.

Corner falls on a northwest slope in juniper growth.

S. 89°39.5' W., beginning new measurement.

- 40.118 The corner of sections 14, 15, 22, and 23.

N. 0°02.2' W., between sections 14 and 15.

- 40.022 The 1/4 section corner of sections 14 and 15, monumented with an iron post, 1 inch diameter, firmly set, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1950 survey.

from which the original 1950 bearing trees

A juniper, 6 ins. diam., blaze bears N. 49° E., 51 links distance, with illegible scribe marks visible on a partially healed blaze.

A juniper, 6 ins. diam., bears N. 52° W., 74 links distance, with scribe marks BT visible on a partially healed blaze.

Raised a mound of stone 3 ft. base, west of the iron post.

Set a steel fence post 0.5 ft. southeast of the iron post.

Corner falls on a southwest slope, 20 ft. east of a draw, drains N. 10° W., in piñon and juniper with sagebrush undergrowth.

N. 0°07.1' E., beginning new measurement.

- 40.105 Point for the corner of sections 10, 11, 14 and 15, determined at record bearing and distance from the remains of the southeast bearing tree.

from which the original 1950 bearing tree

A juniper, 4 ins. diam., bears S. 38°15' E., 61 links distance, with scribe marks BT visible on a partially healed blaze.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

No remaining evidence of the original NE bearing tree was found.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with a magnet in a clear plastic case at the base, in a mound of stone, 3 ft. base to top of aluminum cap marked:

T30SR8W
S10|S11
S15|S14
2003

Set a steel fence post along west side the aluminum post.

Corner falls on a southwest slope in piñon and juniper growth.

From the corner of sections 11, 12, 13, and 14.

S. 89°53.7' W., between sections 11 and 14.

40.117 The 1/4 section corner of sections 11 and 14, monumented with an iron post, 1 inch diameter, firmly set, projecting 5 inches above ground, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post along west side the iron post.

Corner falls on a gradual east slope in sagebrush.

N. 89°57.5' W., beginning new measurement.

40.047 The corner of sections 10, 11, 14, and 15.

N. 0°10.8' W., between sections 10 and 11.

39.899 The 1/4 section corner of sections 10 and 11, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post 1 ft. southwest of the iron post.

Corner falls on a southeast slope in sagebrush, and 40 ft. west of a dirt road, bears N. 10° E., and South.

N. 0°01.9' W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.016

The corner of sections 2, 3, 10, and 11, monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post 0.5 ft. east of the iron post.

Corner falls on a northeast slope in sagebrush, and 1.5 ft. southwest of the intersection of fences projecting north and east.

From the corner of sections 1, 2, 11, and 12.

S. 89°53.2' W., between sections 2 and 11.

40.153

Point for the 1/4 section corner of sections 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap marked:

T30SR8W
S2
1/4 —
S11
2003

Set a steel fence post 0.5 ft. east of the aluminum post.

Corner falls in a draw, drains northwest, in scattering juniper and sagebrush, and 50 ft. north of a fence line, bears east and west.

80.306

The corner of sections 2, 3, 10, and 11.

N. 0°01.5' W., between sections 2 and 3.

40.055

The 1/4 section corner of sections 2 and 3, monumented with an iron post, 1 inch diameter, firmly set, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post 0.5 ft. east of the iron post.

Corner falls on flat ground in sagebrush, and 30 ft. east of a fence line, bears north and south.

N. 0°02.1' W., beginning new measurement.

40.016

The 80 1/16 section corner of sections 2 and 3, monumented with an iron post, 2 inches diameter, firmly set, projecting 6

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

inches above ground, with brass cap marked as described in the official record of the 1950 survey. (Record, 1 inch diameter iron post)

Set a steel fence post 0.5 ft. east of the iron post.

Corner falls on flat ground in sagebrush, and 70 ft. east of a fence line, bears north and south.

N. 0°01.2' E., beginning new measurement.

- 5.579 The closing corner for sections 2 and 3, at intersection with the south boundary of section 35, T. 29 S., R. 8 W., monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post along north side the iron post.

Corner falls in a fence line, bears east and west, and in a shallow draw, drains north, and sagebrush area.

From the corner of sections 22, 23, 26, and 27.

N. 89°47.4' W., between sections 22 and 27.

- 39.971 The 1/4 section corner of sections 22 and 27, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post 2 ft. north of the iron post.

Corner falls on a northwest slope in piñon and juniper growth.

N. 89°46.4' W., beginning new measurement.

- 40.098 The corner of sections 21, 22, 27, and 28, monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

from which the original 1950 bearing trees

A juniper stump, 12 ins. diam., projecting 50 inches above ground, bears N. 19° E., 99 links distance, scribed T30S R8W S22 BT on a partially healed blaze. (Record, 87 links)

A piñon down and dead, 12 ins. diam., bears S. 75° E., 59 links distance, scribed T30S R8W S27 BT visible on a partially healed blaze.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post 2 ft. west of the iron post.

Corner falls on a northeast slope in piñon and juniper growth.

N. 0°02.0' W., between sections 21 and 22.

40.009

The 1/4 section corner of sections 21 and 22, monumented with an iron post, 1 inch diameter, projecting 10 inches above ground, firmly set, with brass cap marked as described in the official record of the 1950 survey.

from which the original 1950 bearing trees

A piñon, down and dead, bears N. 79° E., 78 links distance, scribed 1/4 S22 BT on fragile remains of the blaze.

A piñon, 6 ins. diam., bears S. 72° W., 39 links distance, with scribe marks BT visible on a partially healed blaze.

Raise a mound of stone, 3 ft. base to top of brass cap. Set a steel fence post along west side the iron post.

Corner falls on flat ground in piñon and juniper growth.

N. 0°02.0' W., beginning new measurement.

40.081

The corner of sections 15, 16, 21, and 22, monumented with an iron post, 2 inches diameter, firmly set, projecting 5 inches above ground, with brass cap marked as described in the official record of the 1950 survey, witnessed with a mound of stone to the east.

from which the original 1950 bearing trees

A juniper, 4 ins. diam., bears N. 3° E., 22 links distance, with scribe marks BT visible on a partially healed blaze.

A piñon down and dead, 4 ins. diam., bears S. 13° E., 22 links distance, with scribe marks BT visible on a partially healed blaze.

A juniper, 4 ins. diam., bears N. 65° W., 69 links distance, with scribe marks BT visible on a partially healed blaze.

Set a steel fence post alongside the iron post.

Corner falls on a northwest slope in piñon and juniper growth.

From the corner of sections 14, 15, 22, and 23.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89°45.7' W., between sections 15 and 22.

40.042 The 1/4 section corner of sections 15 and 22, monumented with an iron post 1 inch diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post along west side the iron post.

Corner falls on a gradual northeast slope in juniper growth.

N. 89°44.5' W., beginning new measurement.

40.020 The corner of sections 15, 16, 21, and 22.

N. 0°02.3' W., between sections 15 and 16.

40.025 The 1/4 section corner of sections 15 and 16, monumented with an iron post, 1 inch diameter, firmly set, projecting 10 inches above ground, with brass cap marked as described in the official record of the 1950 survey, witnessed with a mound of stone to the west.

from which the original bearing trees

A piñon, 11 ins. diam., bears N. 39° E., 7 links distance, scribed 1/4 S15 BT, on a partially healed blaze.

A juniper, 16 ins. diam., bears N. 76° W., 36 links distance, scribed 1/4 S16 BT on a partially healed blaze.

Set a steel fence post 1 ft. southeast of the iron post.

Corner falls on a northwest slope in piñon and juniper growth.

N. 0°01.7' W., beginning new measurement.

40.051 The corner of sections 9, 10, 15, and 16, monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post 2 ft. northwest of the iron post.

Corner falls on a northeast slope in sagebrush.

From the corner of sections 10, 11, 14, and 15.

N. 89°52.0' W., between sections 10 and 15.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.137

The 1/4 section corner of sections 10 and 15, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post along south side the iron post.

Corner falls on a gradual east slope, and 30 ft. west of a draw, drains S. 60° W.

N. 89°42.5' W., beginning new measurement.

40.012

The corner of sections 9, 10, 15, and 16.

N. 0°01.4' W., between sections 9 and 10.

39.951

The 1/4 section corner of sections 9 and 10, monumented with an iron post, 1 inch diameter, firmly set, projecting 11 inches above ground, with brass cap marked as described in the official record of the 1950 survey, witnessed with a mound of stone to the west.

Set a steel fence post along north side the iron post.

Corner falls on a gradual northeast slope in sagebrush.

N. 0°01.4' W., beginning new measurement.

40.029

The corner of sections 3, 4, 9, and 10, monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone 3 ft. base, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post along east side the iron post.

Corner falls on a ridge, bears N. 60° E., in sagebrush.

From the corner of sections 2, 3, 10, and 11.

N. 89°46.1' W., between sections 3 and 10.

40.010

The 1/4 section corner of sections 3 and 10, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post 1 ft. northeast of the iron post.

Corner falls on a gradual north slope in sagebrush.

N. 89°42.7' W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.007 The corner of sections 3, 4, 9, and 10.

N. 0°01.6' W., between sections 3 and 4.

40.044 The 1/4 section corner of sections 3 and 4, monumented with an iron post, 1 inch diameter, firmly set, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1950 survey, witnessed with a mound of stone to the west.

Set a steel fence post along east side the iron post.

Corner falls on flat ground in sagebrush.

N. 0°01.2' W., beginning new measurement.

40.026 The 80 1/16 section corner of sections 3 and 4, monumented with an iron post, 1 inch diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post along the northwest side the iron post.

Corner falls on flat ground in sagebrush.

N. 0°01.2' W., beginning new measurement.

5.371 The closing corner of sections 3 and 4, at intersection with the south boundary of section 34, T. 29 S., R 8 W., monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post along north side the iron post.

Corner falls on flat ground in sagebrush.

From the corner of sections 15, 16, 21, and 22.

S. 89°34.8' W., between sections 16 and 21.

40.095 The 1/4 section corner of sections 16 and 21, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post along south side the iron post.

Corner falls on a gradual northwest slope in scattered piñon and juniper growth.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89°55.7' W., beginning new measurement.

- 40.249 The corner of sections 16, 17, 20, and 21, monumented with an iron post, 2 inches diameter, firmly set, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1950 survey, witnessed with a mound of stone to the north.

from which the original 1950 bearing trees

A piñon dead and standing, 14 ins. diam., bears N. 46° E., 24 links distance, with scribe marks T30S R8W S16 BT on a partially healed blaze.

A piñon, 8 ins. diam., bears S. 54° W., 101 links distance, with scribe marks BT visible on a partially healed blaze.

Set a steel fence post along south side the iron post.

Corner falls on a north slope in piñon and juniper growth.

N. 0°03.5' W., between sections 16 and 17.

- 40.057 The 1/4 section corner of sections 16 and 17, monumented with an iron post, 1 inch diameter, firmly set, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1950 survey.

from which the original 1950 bearing trees

A piñon, 12 ins. diam., bears N. 67° E., 14 links distance, scribed 1/4 S16 BT on a partially healed blaze.

A juniper, 8 ins. diam., bears S. 20° W., 29 links distance, with scribe marks BT visible on a partially healed blaze.

Set a steel fence post 0.5 ft. south of the iron post.

Corner falls on a northwest slope in piñon and juniper growth, and 20 ft. east of a draw, drains N. 50° W.

N. 0°03.6' W., beginning new measurement.

- 40.004 The corner of sections 8, 9, 16, and 17, monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

from which the original 1950 bearing trees

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

A piñon, 13 ins. diam., bears N. 69° E., 209 links distance, with scribe marks BT visible on a partially healed blaze.

A juniper, 8 ins. diam., bears S. 75° W., 168 links distance, with illegible scribe marks visible on a partially healed blaze.

Set a steel fence post 3.5 ft. north of the iron post.

Corner falls on a northwest slope in scattered piñon and juniper growth.

From the corner of sections 9, 10, 15, and 16.

S. 89°49.2' W., between sections 9 and 16.

40.191 The 1/4 section corner of sections 9 and 16, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post alongside the iron post.

Corner falls on a northwest slope in sagebrush and scattered red cedar growth.

S. 89°48.8' W., beginning new measurement.

40.171 The corner of sections 8, 9, 16, and 17.

N. 0°03.6' W., between sections 8 and 9.

40.037 The 1/4 section corner of sections 8 and 9, monumented with an iron post, 1 inch diameter, firmly set, projecting 7 inches above ground, with brass cap marked as described in the official record of the 1950 survey, witnessed with a mound of stone to the west.

Set a steel fence post along east side the iron post.

Corner falls on an east slope in sagebrush.

N. 0°03.1' W., beginning new measurement.

39.992 The corner of sections 4, 5, 8, and 9, monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post 0.5 ft. southeast of the iron post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner falls on a gradual northeast slope in sagebrush, and 80 ft. north of an old dirt road, 8 ft. wide, bears east and west.

From the corner of sections 3, 4, 9, and 10.

S. 89°50.4' W., between sections 4 and 9.

40.200 The 1/4 section corner of sections 4 and 9, monumented with an iron post, 1 inch diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1950 survey.

Set steel fence post 0.5 ft. south of the iron post.

Corner falls on a southwest slope in sagebrush, and 15 ft. north of an old dirt road, 8 ft. wide, bears east and west.

S. 89°51.8' W., beginning new measurement.

40.190 The corner of sections 4, 5, 8, and 9.

N. 0°03.1' W., between sections 4 and 5.

40.021 The 1/4 section corner of sections 4 and 5, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post along east side of the iron post.

Corner falls on a gradual east slope in sagebrush, and 10 ft. west of a dirt road, 8 ft. wide, bears north and S. 10° W.

N. 0°02.8' W., beginning new measurement.

40.035 The 80 1/16 section corner of sections 4 and 5, monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey. (Record, 1 inch diameter iron post)

Set a steel fence post along north side of the iron post.

Corner falls on a north facing slope in sagebrush.

N. 0°03.8' W., beginning new measurement.

5.893 The closing corner of sections 4 and 5, at intersection with the south boundary of section 33, T. 29 S., R. 8 W., monumented with an iron post, 2 inches diameter, projecting 12

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

inches above ground, firmly set, with brass cap marked as described in the official record of the 1950 survey.

Raise a mound of stone, 2 ft. base to top of brass cap. Set a steel fence post 2 ft. south of the iron post.

Corner falls on a southeast slope in sagebrush.

From the corner of sections 16, 17, 20, and 21.

S. 89°43.7' W., between sections 17 and 20.

40.161

The 1/4 section corner of sections 17 and 20, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

from which the original 1950 bearing trees

A cedar, 7 ins. diam., bears South, 33 links distance, with scribe marks BT visible on a partially healed blaze.
(Record, piñon, S. 0°30'E., 34 links)

A piñon, 5 ins. diam., bears N. 1° W., 69 links distance, with scribe marks BT visible on a partially healed blaze. (Record; 68 links)

Set a steel fence post along east side the iron post.

Corner falls on a northeast slope in scattered piñon and juniper growth.

S. 89°41.6' W., beginning new measurement.

40.155

The corner of sections 17, 18, 19, and 20, monumented with an iron post, 2 inches diameter, firmly set, projecting 5 inches above ground, with brass cap marked as described in the official record of the 1950 survey, witnessed with a mound of stone to the east.

from which the original 1950 bearing trees

A piñon dead and standing, 14 ins. diam., bears N. 76° E., 17 links distance, with scribe marks visible on a partially healed blaze, and posted with a BT sign.

A cedar, 10 ins., diam., bears S. 40° E., 62 links distance, with scribe marks visible on a partially healed blaze, and posted with a BT sign.

A piñon, 8 ins. diam., bears S. 25° W., 91 links distance, scribed T30S R8W S19 BT visible on a partially healed blaze, and posted with a BT sign. (Record, 86 links)

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the iron post.

Corner falls on a east slope in piñon and juniper growth.

S. 89°39.7' W., between sections 18 and 19.

40.027

The 1/4 section corner of sections 18 and 19, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone 3 ft. base, to top of brass cap marked as described in the official record of the 1950 survey.

from which the original 1950 bearing trees

A piñon, 10 ins. diam., bears S. 22° E., 72 links distance, scribed 1/4 S19 BT visible on a partially healed blaze, and posted with a BT sign.

A cedar, 10 ins. diam., bears N. 20° W., 56 links distance, with no scribe marks visible on a healed blaze, and posted with a BT sign.

Set a steel fence post alongside the iron post.

Corner falls on a gradual north slope in piñon and juniper growth.

S. 89°40.3' W., beginning new measurement.

40.004

The 80 1/16 section corner of sections 18 and 19, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

from which the original 1950 bearing trees

A piñon, 8 ins. diam., bears S. 71° W., 60 links distance, with scribe marks visible on a partially healed blaze.

A piñon, 12 ins. diam., bears N. 7° W., 35 links distance, with scribe marks visible on a partially healed blaze.

Raised a small mound of stone west of the iron post.

Set a steel fence post alongside the iron post.

Corner falls on a west facing slope in a rock outcropping.

S. 89°41.9' W., beginning new measurement.

6.379

The closing corner for sections 18 and 19, monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone 3 ft. base to top, of brass cap marked as described in the official record of the 1950 survey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

from which the original 1950 bearing trees

A piñon, 12 ins, diam., bears N. 6°15' E., 35 links distance, scribed CC T30S R8W S18 BT on a partially healed blaze. (Record, 38 links)

A piñon, 10 ins. diam., bears S. 75°30' E., 17 links distance, with scribe marks BT visible on a partially healed blaze. (Record, 17.5 links)

Set a steel fence post alongside the iron post.

Corner falls on a east facing slope in a wash, drains north.

From the corner of section 17, 18, 19, and 20.

N. 0°03.6' W., between sections 17 and 18.

40.088 The 1/4 section corner of sections 17 and 18, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone 3 ft, base to top of brass cap marked as described in the official record of the 1950 survey.

from which the original 1950 bearing trees

A cedar dead and standing, 4 ins. diam., bears S. 82°30' E., 49 links distance, with scribe marks BT visible on a partially healed blaze. A BT sign is now posted on the tree.

A juniper dead and standing, 12 ins. diam., blaze bears S. 89°30' W., 49 links distance, with scribe marks BT visible on a partially healed. A BT sign is now posted on the tree. (Record, 35 links)

Corner falls on a north slope in sagebrush and piñon and juniper growth.

N. 0°03.4' W., beginning new measurement.

40.002 The corner of sections 7, 8, 17, and 18, monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post along south side the iron post.

Corner falls on a northwest slope in scattered piñon and juniper growth.

From the corner of sections 8, 9, 16, and 17.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 89°43.8' W., between sections 8 and 17.

40.140 The 1/4 section corner of sections 8 and 17, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

from which the original 1950 bearing trees

A piñon, 8 ins. diam., bears N. 41° E., 38 links distance, with scribe marks BT visible on a partially healed blaze. (Record, 40 links distance)

A piñon, 13 ins. diam., bears S. 9° W., 34 links distance, scribed 1/4 S17 BT visible on a partially healed blaze. (Record, 32 links distance)

Set a steel fence post 2 ft. east of the iron post.

Corner falls on a northwest slope in piñon and juniper growth.

S. 89°44.0' W., beginning new measurement.

40.158 The corner of sections 7, 8, 17, and 18.

S. 89°46.2' W., between sections 7 and 18.

40.050 The 1/4 section corner of sections 7 and 18, monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey. (Record, 1 inch diameter iron post)

No remaining evidence of the original bearing trees was found.

Raised a mound of stone 3 ft. base, north of the iron post.

Set a steel fence post 2 ft. south of the iron post.

Corner falls on flat ground in sagebrush.

S. 89°45.5' W., beginning new measurement.

39.992 The 80 1/16 section corner of sections 7 and 18, monumented with an iron post, 1 inch diameter, projecting 7 inches above ground, firmly set, with brass cap marked as described in the official record of the 1950 survey.

from which the bearing trees not of record

A juniper, 4 ins. diam., bears S. 10° W., 88 links distance, with scribe marks BT visible on a partially healed blaze.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

A juniper 10 ins. diam., bears N. 30° W., 66 links distance, with scribe marks BT visible on a partially healed blaze.

Set a steel fence post along east side the iron post.

S. 89°47.3' W., beginning new measurement.

6.634 The closing corner of sections 7 and 18, at intersection with the east boundary of section 13, T. 30 S., R. 9 W., monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey, hereinbefore described.

Set a steel fence post 1.5 ft. south of the iron post.

Corner falls on a north slope in piñon growth.

From the corner of section 7, 8, 17, and 18.

N. 0°04.2' W., between sections 7 and 8.

40.046 The 1/4 section corner of sections 7 and 8, monumented with an iron post, 1 inch diameter, firmly set, projecting 24 inches above ground, with brass cap marked as described in the official record of the 1950 survey.

from which the original 1950 bearing tree

A juniper, 16 ins. diam., bears N. 8° W., 249 links distance, with illegible scribe marks visible on a partially healed blaze.

Set a steel fence post 2.5 ft. east of the iron post.

Corner falls on a northwest slope in sagebrush, and 30 ft. east of a wash, drains N. 30° W.

N. 0°03.1' W., beginning new measurement.

40.044 The corner of sections 5, 6, 7, and 8, monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post along west side of the iron post.

Corner falls on a gradual northwest slope in sagebrush, and 15 ft. east of a draw, drains N. 20° W.

From the corner of sections 4, 5, 8, and 9.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 89°47.1' W., between sections 5 and 8.

- 40.136 The 1/4 section corner of sections 5 and 8, monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey. (Record, 1 inch diameter iron post)

Set a steel fence post along southwest side of the iron post.

Corner falls on a gradual southwest slope in sagebrush, and 160 ft. north of a dirt road 8 ft. wide, bears east and west.

S. 89°46.0' W., beginning new measurement.

- 40.153 The corner of sections 5, 6, 7, and 8.

S. 89°45.4' W., between sections 6 and 7.

- 40.018 The 1/4 section corner of sections 6 and 7, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post 1.5 ft. east of the iron post.

Corner falls on a northwest slope in sagebrush, and 160 ft. east of a dirt road 8 ft. wide, bears north and S. 10° E.

S. 89°44.9' W., beginning new measurement.

- 40.027 The 80 1/16 section corner of sections 6 and 7, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post 0.5 ft. west of the iron post.

Corner falls on a gradual north slope in sagebrush.

S. 89°46.8' W., beginning new measurement.

- 5.149 The closing corner of sections 6 and 7, monumented with an iron post, 2 inches diameter, firmly set in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

Add the marks AM 2003 to the brass cap.

Set a steel fence post 2.5 ft. southeast of the iron post.

Corner falls on a gradual north slope in sagebrush.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 8 W., SALT LAKE MERIDIAN, UTAH

CHAINS

5.167

True point for the closing corner of sections 6 and 7, at intersection with the east boundary of section 12, T. 30 S., R. 9 W., hereinbefore described, not monumented.

From the corner of sections 5, 6, 7, and 8.

N. 0°04.3' W., between sections 5 and 6.

40.021

The 1/4 section corner of sections 5 and 6, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post 2 ft. south of the iron post.

Corner falls on a gradual northeast slope in sagebrush, and 50 ft. west of a wash 3 ft. deep, drains north.

N. 0°03.6' W., beginning new measurement.

40.007

The 80 1/16 section corner of sections 5 and 6, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

Set a steel fence post 2 ft. south of the iron post.

Corner falls on flat ground in sagebrush.

N. 0°03.6' W., beginning new measurement.

6.340

The closing corner of sections 5 and 6, monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1950 survey.

Add the marks AM 2003 to the brass cap.

Set a steel fence post alongside the iron post.

Corner falls on flat ground in sagebrush.

6.409

True point for the closing corner of sections 5 and 6, at intersection with the south boundary of section 32, T. 29 S., R. 8 W., hereinbefore described, not monumented.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Jeremy Davis	Survey Technician
Tyler Trujillo	Survey Technician

CERTIFICATE OF SURVEY

I, *Ronald K. Baugh*, *Supervisory Cadastral Surveyor*, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing the date of the *25th day of April, 2003*, that *John F. Carroll*, *Cadastral Surveyor*, who no longer is employed by the Bureau of Land Management, Cadastral Survey, Utah, has *dependently resurveyed a portion of the east boundary of Township 30 South, Range 9 West, the south boundary of Township 29 South, Range 8 West, and a portion of the subdivisional lines in Township 30 South, Range 8 West*, of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by him and under his direction, and reassigned to me pursuant to the Reassignment Instructions bearing the date of the *12th day of June, 2006*; and that said survey has been made in strict conformity with said Special Instructions, the 1973 Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Sept. 23, 2010
Date

Ronald K. Baugh
Supervisory Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the east boundary of Township 30 South, Range 9 West, the south boundary of Township 29 South, Range 8 West, and a portion of the subdivisional lines in Township 30 South, Range 8 West, Salt Lake Meridian, Utah*, executed by *John F. Carroll, Cadastral Surveyor* and reassigned to *Ronald K. Baugh, Supervisory Cadastral Surveyor*, having been critically examined and found correct, are hereby approved.

November 19, 2010
Date

Daniel W. Webb
Chief Cadastral Surveyor for Utah