

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL
FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

OF THE SOUTH BOUNDARY,

A PORTION OF THE EAST BOUNDARY,

A PORTION OF THE WEST BOUNDARY,
(GUIDE MERIDIAN)

A PORTION OF THE SUBDIVISIONAL LINES

AND THE

SUBDIVISION OF SECTION 32

IN

TOWNSHIP 4 SOUTH, RANGE 9 WEST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Ronald K. Baugh
Cadastral Surveyor

Under special instructions dated and approved **September 4, 2003**, which provided for the surveys included under Group Number **971**, and assignment instructions dated **September 4, 2003**.

Survey commenced **September 20, 2003**
Survey completed **September 23, 2004**

INDEX DIAGRAM

Township 4 South, Range 9 West

6	5	4	3	2	1 17
7	8	9	10	11 16	12 9 16
18	17	16 25 28	15 21 24	14 15 20	13 8 15
19	20 28 32	21 24 27	22 20 23	23 14 19	24 7 14
11 30 31 30	29 26 30	28 22 26	27 19 22	26 13 18	25 6 13
9 31 29 5	32 25 5	33 21 4	34 18 3	35 12 3	36 6 2

TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

The following field notes describe the dependent resurvey of the south boundary, a portion of the east boundary, a portion of the west boundary, (Guide Meridian) and a portion of the subdivisional lines, and the subdivision of section 32, in Township 4 South, Range 9 West, Salt Lake Meridian, Utah.

HISTORY OF EARLIER SURVEYS

Surveyed by			Retraced or Resurveyed by
SOUTH BOUNDARY			
All	Joseph Gorlinski	1871	
Portion			Elliot Bird 1950
EAST BOUNDARY			
All	Joseph Gorlinski	1871	
WEST BOUNDARY (Guide Meridian)			
All	Joseph Gorlinski	1871	
All			A.J. Stookey 1909
NORTH BOUNDARY			
All	Joseph Gorlinski	1871	
SUBDIVISION			
All	Joseph Gorlinski	1871	

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instruction, 1973 and the Special Instructions for Group No. 971, dated September 4, 2003.

The true meridian direction and length of all lines were determined by Global Positioning System (GPS) utilizing Real-Time Kinematics (RTK) observation using the Trimble 5700 model receiver.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and their calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations, post processed by National Geodetic Survey, Online Positioning User Service, (OPUS), Utilizing Continuously Operating Reference Stations; SALT LAKE CITY COORS ARP, MIDVALE COORS ARP, and MYTON COORS ARP. The N.A.D. 1983 (COORS96) geographic position of the SE corner of section 36 is as follows:

Latitude: 40° 25' 09.155" N. Longitude: 112° 48' 04.449" W.
N.A.V.D., Elevation: 4451.5 ft.

**DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Dependent Resurvey of the South Boundary
Township 4 South, Range 9 West, Salt Lake Meridian, Utah

Reestablishment of the Survey
Executed by J. Gorlinski in 1871

Beginning at the corner of Townships 4 and 5 South and Ranges 8 and 9 West, monumented with a 4 strand barbed wire fence corner from which fences bear N, S and E, with a scattered mound of stone. This position fits with found corner to the N, S, E and W, and is accepted as the best available evidence of the original corner position.

At the corner point. (fence corner)

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	
R9W R8W	
S36	S31
S1	S6
T5S	
2003	

N. 89° 39.0' W., between sections 1 and 36.

40.198

Point for the 1/4 section corner of sections 1 and 36, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W	
S36	
1/4	—————
S1	
T5S	
2004	

80.396

The corner of sections 1, 2, 35 and 36, monumented with a limestone, 13x6x6 inches, dimly marked with 1 notch on E and 5 notches on W edges.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

**DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

	T4S R9W	
S35		S36

S2		S1
T5S		
2003		

Deposit the marked stone alongside the aluminum post.

S. 89° 55.5' W., between sections 2 and 35.

40.148

Point for the 1/4 section corner of sections 2 and 35, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

	T4S R9W	
	S35	
1/4	-----	
	S2	
	T5S	
	2004	

80.296

The corner of sections 2, 3, 34 and 35, monumented with a limestone, 12x8x7 inches, marked with 2 notches on E and 4 notches on W edges.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

	T4S R9W	
S34		S35
S3		S2
T5S		
2003		

Deposit the marked stone and a steel fence post alongside the aluminum post.

S. 89° 51.9' W., between sections 3 and 34.

40.185

The 1/4 section corner of sections 3 and 34, monumented with a broken limestone, 10x7x3 inches, marked with 1/4 on W face.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

**DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

T4S R9W
S34
1/4 ———
S3
T5S
2003

Deposit the broken, marked stone alongside the aluminum post.

S. 89° 54.0' W., beginning new measurement.

40.196

The corner of sections 3, 4, 33 and 34, monumented with a limestone, 12x7x5 inches, plainly marked with 3 notches on E and W edges.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
S33 | S34
———
S4 | S3
T5S
2003

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

S. 89° 58.5' W., between sections 4 and 33.

40.191

The 1/4 section corner of sections 4 and 33, monumented with a granite stone, 10x6x5 inches, plainly marked 1/4 on W face.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T4S R9W
S33
1/4 ———
S4
T5S
2003

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 89° 59.2' W., beginning new measurement.

**DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

- 40.161** The corner of sections 4, 5, 32 and 33, monumented with an iron post 3 inches diameter, firmly set, projecting 14 inches above the ground, with brass cap marked as described in the official record of the 1950 resurvey.

Set a steel fence post alongside the iron post.

Reestablishment of the Survey Executed by J. Gorlinski in 1871
and the Dependent Resurvey by E. Bird in 1950.

S. 89° 47.3' W., between sections 5 and 32.

- 40.228** The 1/4 section corner of sections 5 and 32, monumented with an iron post 3 inches diameter, firmly set, projecting 12 inches above the ground, with brass cap marked as described in the official record of the 1950 resurvey.

Set a steel fence post alongside the iron post.

S. 89° 55.3' W., beginning new measurement.

- 40.206** The corner of section 5, 6, 31 and 32, monumented with an iron post, 3 inches diameter, firmly set, projecting 16 inches above the ground, with brass cap marked as described in the official record of the 1950 resurvey.

Set a steel fence post alongside the iron post.

N. 89° 43.3' W., between sections 6 and 31.

- 40.170** The 1/4 section corner of section 6 and 31, monumented with an iron post 3 inches diameter, firmly set, projecting 16 inches above the ground, with brass cap marked as described in the official record of the 1950 resurvey.

N. 89° 46.6' W., beginning new measurement.

- 40.282** The corner of Tps. 4 and 5 S., Rs. 9 and 10 W., monumented with an iron post 3 inches diameter, firmly set, projecting 16 inches above the ground, with brass cap marked as described in the official record of the 1950 resurvey.
-

Dependent Resurvey of a Portion of the East Boundary,
T. 4 S., R. 9 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by J. Gorlinski in 1871

**DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

From the corner of Tps. 4 and 5 S., Rs. 8 and 9 W., hereinbefore described.

N. 0° 09.9' E., between sections 31 and 36.

- 40.338** Point for the 1/4 section corner of sections 31 and 36, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	
R9W	R8W
1/4	
S36	S31
2004	

Corner is located in a N and S fence line.

- 80.676** The corner of sections 25, 30, 31 and 36, monumented with a quartzite stone, 12x7x4 inches, marked with 1 notch on S and 5 notches on N edges, located in a N and S fence line.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	
R9W	R8W
S25	S30

S36	S31
2003	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 08.1' E., between sections 25 and 30.

- 40.177** The 1/4 section corner of sections 25 and 30, monumented with a quartzite stone, 13x9x6 inches, marked 1/4 on W face, located in N and S fence line.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	
R9W	R8W
1/4	
S25	S30
2003	

**DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 09.2' E., beginning new measurement.

40.113

The corner of sections 19, 24, 25 and 30, monumented with a quartzite stone, 12x8x7 inches, marked with 2 notches on S and 4 notches on N edges, located 2 ft. E of a N and S fence line.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	
R9W	R8W
S24	S19
S25	S30
2003	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 06.5' E., between sections 19 and 24.

40.134

The 1/4 section corner of sections 19 and 24, monumented with a sandstone, 12x7x5 inches, marked with 1/4 on W face, located in a N and S fence line.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	
R9W	R8W
1/4	
S24	S19
2003	

Deposit the marked stone alongside the aluminum post.

N. 0° 09.6' E., beginning new measurement.

40.143

The corner of sections 13, 18, 19 and 24, monumented with a sandstone, 14x9x7 inches, dimly marked with 3 notches on N and S edges, located in a N and S fence line.

At the corner point.

**DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	
R9W	R8W
S13	S18

S24	S19
2003	

Deposit the marked stone alongside the aluminum post.

N. 0° 10.4' E., between sections 13 and 18.

40.183

The 1/4 section corner of sections 13 and 18, monumented with a sandstone, 12x10x4 inches, dimly marked 1/4 on W face, located in N and S fence line.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	
R9W	R8W
1/4	
S13	S18
2004	

Deposit the marked stone alongside the aluminum post.

N. 0° 10.2' E., beginning new measurement.

40.032

The corner of sections 7, 12, 13 and 18, monumented with a sandstone, 12x8x6 inches, marked with 4 notches on S and 2 notches on N edges, located in N and S fence line.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	
R9W	R8W
S12	S7

S13	S18
2004	

Deposit the marked stone alongside the aluminum post.

**DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

N. 0° 07.9' E., between sections 7 and 12.

40.070

Point for the 1/4 section corner of sections 7 and 12, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	
R9W	R8W
1/4	
S12	S7
2004	

Corner is located in a N and S fence line.

40.570

Corner of fences bearing N, S, and E.

80.140

The corner of sections 1, 6, 7 and 12, monumented with a sanstone, 13x8x4 inches, incorrectly marked with 5 notches on N and S edges.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	
R9W	R8W
S1	S6

S12	S7
2004	

Deposit the marked stone alongside the aluminum post.

Located in corner of fences bearing west and south.

Dependent Resurvey of a Portion of the West Boundary,
(Guide Meridian)
Township 4 South, Range 9 West, Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by J. Gorlinski in 1871
And the Retracement Resurvey by A.J. Stookey in 1909

From the corner of Tps. 4 and 5 S., Rs. 9 and 10 W., hereinbefore described.

N. 1° 38.5' E., along the west boundary of section 31. (Guide Meridian)

40.114

Point for the E 1/4 section corner of section 36 only, T. 4 S., R. 10 W.

**DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S
R10W R9W
1/4 |
S36 |
2004

- 40.248** The 1/4 section corner of section 31 only, monumented with a limestone, 10x10x8 inches, firmly set and dimly marked 1/4.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a collar of stone, with aluminum cap marked:

T4S
R10W R9W
| 1/4
| S31
2003

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 37.3' W., beginning new measurement.

- 39.962** The closing corner of sections 25 and 36 only, monumented with limestone, 18x12x10 inches, plainly marked with 1 groove on S, 5 grooves on N faces, and a CC on W face, with a mound of stone, 3 ft. base, 2 ft. high, west of the corner.

Note: The 1909 record set an iron post 3 ft. long, 2 inches diameter. There is no evidence that the iron post was ever set.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S
R10W R9W
S25 |
CC ——— | S31
S36 |
2003

Deposit the marked stone alongside the aluminum post.

**DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

40.553

The corner of sections 30 and 31 only, monumented with limestone, 14x13x5 inches, marked with 1 notch on S and 5 notches on N edges.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

```

T4S
R10W R9W
      S30
S25 |-----
      S31
    2003
  
```

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 02.8' E., along the west boundary of section 30.

39.471

Point for the E 1/4 section corner of section 25 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

```

T4S
R10W R9W
    1/4 |
S25 |
    2003
  
```

Raise a mound of stone, 2 ft. base, 1 ft. high, W of the corner.

40.450

The 1/4 section of section 30 only, monumented with a limestone, 14x7x6 inches, dimly marked with 1/4 on W face.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

```

T4S
R10W R9W
      1/4
      S30
    2003
  
```

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

**DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

N. 0° 14.6' E., beginning new measurement.

39.083 The closing corner of sections 24 and 25 only, monumented with an iron post, 2 inches diameter, firmly set in a mound of stone, with brass cap marked as described in official record of the 1909 resurvey.

40.518 The corner of sections 19 and 30 only, monumented with a limestone, 15x10x6 inches, plainly marked with 2 notches on S and 4 notches on N edges.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 6 inches in the ground to bedrock, in a mound of stone, 4 ft. base to top of aluminum cap marked:

```

T4S
R10W R9W
      | S19
S24  |-----
      | S30
      2003

```

Deposit the marked stone alongside the aluminum post.

Dependent Resurvey of a Portion of the Subdivisional Lines,
Township 4 South, Range 9 West, Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by J. Gorlinski in 1871

From the corner of section 1, 2, 35 and 36, on the south boundary of township, hereinbefore described.

N. 0° 23.6' E., between sections 35 and 36.

40.155 Point for the 1/4 section corner of sections 35 and 36, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

```

T4S R9W
      1/4
S35 | S36
      2004

```

Set a steel fence post alongside the aluminum post.

80.310 Point for the corner of sections 25, 26, 35 and 36, at

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
S26	S25
S35	S36
2004	

Set a steel fence post alongside the aluminum post.

From the corner of section 25, 30, 31 and 36, on the east boundary of township, hereinbefore described.

S. 89° 54.1' W., between sections 25 and 36.

40.203

The 1/4 section corner of sections 25 and 36, monumented with a limestone, 13x7x3 inches, plainly marked with 1/4 on N face.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
	S25
1/4	_____
	S36
2003	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 89° 43.3' W., beginning new measurement.

39.855

The corner of sections 25, 26, 35 and 36.

N. 0° 04.2' E., between sections 25 and 26.

40.154

Point for the 1/4 section corner of sections 25 and 26, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
	1/4
S26	S25
2004	

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a steel fence post alongside the aluminum post.

80.308

Point for the corner of sections 23, 24, 25 and 26, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
S23	S24
S26	S25
2004	

Set a steel fence post alongside the aluminum post.

From the corner of sections 19, 24, 25 and 30, on east boundary of township, hereinbefore described.

N. 89° 53.9' W., between sections 24 and 25.

40.072

Point for the 1/4 section corner of sections 24 and 25, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
	S24
1/4	—
	S25
2004	

Set a steel fence post alongside the aluminum post.

80.144

The corner of sections 23, 24, 25 and 26.

N. 0° 05.4' W., between sections 23 and 24.

40.154

The 1/4 section corner of sections 23 and 24, monumented with a granite stone, 14x7x7 inches, marked with 1/4 on W face.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
	1/4
S23	S24
2003	

Deposit the marked stone alongside the aluminum post.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a steel fence post alongside the aluminum post.

N. 1° 00.2' E., beginning new measurement.

40.178

Point for the corner of sections 13, 14, 23 and 24, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
S14	S13
S23	S24
2004	

Set a steel fence post alongside the monument.

From the corner of sections 13, 18, 19 and 24, on east boundary of township, hereinbefore described.

N. 89° 51.7' W., between sections 13 and 24.

39.837

Point for the 1/4 section corner of sections 13 and 24, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
	S13
1/4	
	S24
2004	

Set a steel fence post alongside the monument.

79.674

The corner of sections 13, 14, 23 and 24.

N. 0° 04.9' W., between sections 13 and 14.

40.172

Point for the 1/4 section corner of sections 13 and 14, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
	1/4
S14	S13
2004	

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a steel fence post alongside the aluminum post.

80.344

The corner of sections 11, 12, 13 and 14, monumented with a limestone, 18x6x5 inches, marked with 4 notches on S and 1 notch on E edges.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
S11	S12

S14	S13
2003	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From the corner of sections 7, 12, 13 and 18, on east boundary of township, hereinbefore described.

N. 89° 33.5' W., between sections 12 and 13.

39.809

The 1/4 section corner of sections 12 and 13, monumented with a sandstone, 12x10x6 inches dimly marked with 1/4 on N face.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
S12	

1/4	
S13	
2004	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 89° 58.7' W., beginning new measurement.

40.202

The corner of sections 11, 12, 13 and 14.

N. 0° 20.9' E., between sections 11 and 12.

40.158

The 1/4 section corner of sections 11 and 12, monumented with a granite stone, 10x18x6 inches plainly marked with 1/4 on W face.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
	1/4
S11	S12
	2003

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 43.1' W., beginning new measurement.

39.938

The corner of sections 1, 2, 11 and 12, monumented with a sandstone, 12x8x6 inches, plainly marked with 5 notches on S and 1 notch on E edges.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
S2	S1
S11	S12
	2003

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From the corner of sections 1, 6, 7 and 12, on east boundary of township, hereinbefore described.

N. 89° 48.3' W., between sections 1 and 12.

40.217

Point for the 1/4 section corner of sections 1 and 12, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
	S1
1/4	———
	S12
	2004

Set a steel fence post alongside the aluminum post.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

80.434 The corner of sections 1, 2, 11 and 12.

From the corner of sections 2, 3, 34 and 35, on the south boundary of township, hereinbefore described.

N. 0° 35.3' E., between sections 34 and 35.

39.955 Point for the 1/4 section corner of sections 34 and 35, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
1/4
S34 | S35
2004

Set a steel fence post alongside the aluminum post.

79.910 Point for the corner of sections 26, 27, 34 and 35, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
S27 | S26

S34 | S35
2004

Set a steel fence post alongside the aluminum post.

From the corner of sections 25, 26, 35 and 36.

S. 89° 38.2' W., between sections 26 and 35.

40.006 Point for the 1/4 section corner of sections 26 and 35, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
S26
1/4 -----
S35
2004

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a steel fence post alongside the aluminum post.

80.012 The corner of sections 26, 27, 34 and 35.

N. 1° 40.4' W., between sections 26 and 27.

39.970 The 1/4 section corner of sections 26 and 27, monumented with a limestone, 17x9x2 inches, marked with 1/4 on W face.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
1/4	
S27	S26
2003	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 1° 17.9' E., beginning new measurement.

40.227 Point for the corner of sections 22, 23, 26 and 27, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
S22	S23
<hr/>	
S27	S26
2004	

Set a steel fence post alongside the aluminum post.

From the corner of sections 23, 24, 25 and 26.

S. 89° 32.3' W., between sections 23 and 26.

40.174 Point for the 1/4 section corner of sections 23 and 26, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

T4S R9W
S23
1/4 ———
S26
2004

Set a steel fence post alongside the aluminum post.

80.348 The corner of sections 22, 23, 26 and 27.

N. 1° 01.1' W., between sections 22 and 23.

40.222 The 1/4 section corner of sections 22 and 23, monumented with a sandstone, 11x10x4 inches, dimly marked with 1/4 on W face.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
1/4
S22 | S23
2003

Deposit the marked sandstone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 2° 12.4' E., beginning new measurement.

40.250 Point for the corner of sections 14, 15, 22 and 23, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
S15 | S14
—————
S22 | S23
2004

Set a steel fence post alongside the aluminum post.

From the corner of sections 13, 14, 23 and 24.

S. 89° 36.9' W., between sections 14 and 23.

40.067 Point for the 1/4 section corner of sections 14 and 23, at proportionate distance, there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
S14
1/4 ———
S23
2004

Set a steel fence post alongside the aluminum post.

80.134 The corner of sections 14, 15, 22 and 23.

N. 1° 44.4' W., between sections 14 and 15.

40.239 The 1/4 section corner of sections 14 and 15, monumented with a limestone, 11x6x3 inches, marked with 1/4 on W face.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
1/4
S15 | S14
2003

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From the corner of sections 3, 4, 33 and 34, on the south boundary of township, hereinbefore described.

N. 0° 24.9' E., between section 33 and 34.

40.216 Point for the 1/4 section corner of sections 33 and 34, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
1/4
S33 | S34
2004

Set a steel fence post alongside the aluminum post.

80.432 The corner of sections 27, 28, 33 and 34, monumented with a

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

limestone, 17x6x5 inches, with 1 notch on S and 3 notches on E edges.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
S28	S27
S33	S34
2003	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From the corner of sections 26, 27, 34 and 35.

N. 89° 55.2' W., between sections 27 and 34.

39.713

The 1/4 section corner of sections 27 and 34, monumented with a limestone, 14x8x6 inches, marked with 1/4 on N face.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
	S27
1/4	_____
	S34
2003	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 89° 34.5' W., beginning new measurement.

40.890

The corner of sections 27, 28, 33 and 34.

N. 0° 17.7' E., between sections 27 and 28.

40.224

The 1/4 section corner of sections 27 and 28, monumented with a limestone, 14x10x3 inches, marked with 1/4 on W face.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

T4S R9W
1/4
S28 | S27
2003

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 26.1' E., beginning new measurement.

40.201

Point for the corner of sections 21, 22, 27 and 28, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
S21 | S22

S28 | S27
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, W of aluminum post.

Set a steel fence post alongside the aluminum post.

From the corner of sections 22, 23, 26 and 27.

N. 89° 33.6' W., between section 22 and 27.

39.910

Point for the 1/4 section corner of sections 22 and 27, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
S22
1/4 —————
S27
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, N of aluminum post.

Set a steel fence post alongside the aluminum post.

79.820

The corner of sections 21, 22, 27 and 28.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

N. $0^{\circ} 28.5'$ E., between sections 21 and 22.

40.201

Point for the 1/4 section corner of sections 21 and 22, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
1/4	
S21	S22
2004	

Set a steel fence post alongside the aluminum post.

80.402

Point for the corner of section 15, 16, 21 and 22 at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
S16	S15
<hr style="width: 100%;"/>	
S21	S22
2004	

Set a steel fence post alongside the aluminum post.

From the corner of sections 14, 15, 22 and 23.

N. $89^{\circ} 35.3'$ W., between sections 15 and 22.

39.985

Point for the 1/4 section corner of sections 15 and 22, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
	S15
1/4	<hr style="width: 100%;"/>
	S22
2004	

Set a steel fence post alongside the aluminum post.

79.970

The corner of sections 15, 16, 21 and 22.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

N. 0° 03.2' E., between sections 15 and 16.

40.199

The 1/4 section corner of sections 15 and 16, monumented with a limestone, 10x9x6 inches, marked 1/4 on W face.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
1/4
S16 | S15
2003

Deposit marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From the corner of sections 4, 5, 32 and 33, on the south boundary of the township, hereinbefore described.

N. 0° 34.7' E., between sections 32 and 33.

20.129

Point for the S 1/16 section corner of sections 32 and 33.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
S 1/16
S32 | S33
2004

Set a steel fence post alongside the aluminum post.

Monument is located on N bank of wash, 50 links wide and 3 ft. deep, drains ENE.

40.258

The 1/4 section corner of sections 32 and 33, monumented with a limestone, 14x8x8 inches, marked with 1/4 on W face.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
1/4
S32 | S33
2003

Deposit marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

N. $0^{\circ} 27.2'$ E., beginning new measurement.

40.327 The corner of sections 28, 29, 32 and 33, monumented with a limestone, 11x11x8, dimly marked, 1 notch on S and 4 notches on E edges.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
S29	S28

S32	S33
2003	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of corner.

From the corner of sections 27, 28, 33 and 34.

S. $89^{\circ} 56.1'$ W., between sections 28 and 33.

39.813 The 1/4 section corner of sections 28 and 33, monumented with a limestone, 8x8x8 inches, marked with 1/4 on N face.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
	S28
1/4	-----
	S33
2003	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. $89^{\circ} 44.0'$ W., beginning new measurement.

40.379 The corner of sections 28, 29, 32 and 33.

N. $0^{\circ} 33.9'$ E., between sections 28 and 29.

40.289 Point for the 1/4 section corner of sections 28 and 29, at

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
	1/4
S29	S28
	2004

Set a steel fence post alongside the aluminum post.

80.578

The corner of sections 20, 21, 28 and 29, monumented with a limestone, 10x7x6 inches, marked with 2 notches on S and 4 notched on E edges.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
S20	S21
S29	S28
	2003

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From the corner of sections 21, 22, 27 and 28.

N. 89° 47.3' W., between sections 21 and 28.

39.946

Point for the 1/4 section corner of sections 21 and 28, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
	S21
1/4	—————
	S28
	2004

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, N of corner.

79.892

The corner of sections 20, 21, 28 and 29.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

N. 0° 28.8' E., between section 20 and 21.

40.604

Point for the 1/4 section corner of sections 20 and 21, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
1/4
S20 | S21
2004

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of corner.

81.208

The corner of sections 16, 17, 20 and 21, monumented with a limestone, 12x8x6 inches, with 3 notches on S and 4 notches on E edges, in a small mound of stone.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
S17 | S16

S20 | S21
2003

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From the corner of sections 15, 16, 21 and 22.

N. 89° 12.6' W., between sections 16 and 21.

39.935

Point for the 1/4 section corner of sections 16 and 21, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
S16
1/4 -----
S21
2004

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a steel fence post alongside the aluminum post.

79.870 The corner of sections 16, 17, 20 and 21.

From the corner of sections 5, 6, 31 and 32, on the south boundary of township, hereinbefore described.

N. 0° 36.1' E., between sections 31 and 32.

20.104 Point for the S 1/16 section corner of sections 31 and 32.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
S 1/16
S31 | S32
2004

Set a steel fence post alongside the aluminum post.

40.208 The 1/4 section corner of sections 31 and 32, monumented with a limestone, 11x7x5 inches, plainly marked with 1/4 on W face.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
1/4
S31 | S32
2003

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 26.5' E., beginning new measurement.

40.239 The corner of sections 29, 30, 31 and 32, monumented with a limestone, 13x10x5 inches, plainly marked with 1 notch on S and 5 notches on E edges.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
S30 | S29

S31 | S32
2003

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From the corner of sections 28, 29, 32 and 33.

N. 89° 40.7' E., between sections 29 and 32.

40.138

The 1/4 section corner of sections 29 and 32, monumented with a broken limestone, 10x9x8 inches, marked with 1/4 on N face.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
S29
1/4 ———
S32
2003

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of corner.

S. 89° 11.6' W., beginning new measurement.

40.277

The corner of sections 29, 30, 31 and 32.

N. 89° 30.6' W., between sections 30 and 31.

40.126

Point for the 1/4 section corner of sections 30 and 31, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
S30
1/4 ———
S31
2004

Set a steel fence post alongside the aluminum post.

80.453

The corner of sections 30 and 31 only, on the west boundary of township, hereinbefore described.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

From the corner of sections 29, 30, 31 and 32.

N. $0^{\circ} 29.1'$ E., between sections 29 and 30.

40.169

Point for the 1/4 section corner of sections 29 and 30, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
1/4	
S30	S29
2004	

Raise a mound of stone, 3 ft. base, 2 ft. high, W of corner.

80.338

The corner of sections 19, 20, 29 and 30, monumented with a broken limestone, 14x10x7 inches, plainly marked with 2 notches on the S and 4 on the E edges.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
S19	S20
<hr/>	
S30	S29
2003	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 2 ft. base, 1 ft. high, W of corner.

From the corner of sections 20, 21, 28 and 29.

S. $89^{\circ} 35.2'$ W., between section 20 and 29.

40.254

Point for the 1/4 section corner of sections 20 and 29, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S	R9W
S20	
1/4	<hr/>
S29	
2004	

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 1 ft. high N. of corner.

80.508 The corner of sections 19, 20, 29 and 30.

N. 89° 04.0' W., between sections 19 and 30.

40.340 Point for the 1/4 section corner of sections 19 and 30, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
S19
1/4 ———
S30
2004

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, N of corner.

80.922 The corner of sections 19 and 30 only, on the west boundary of township, hereinbefore described.

The Subdivision of Section 32
Township 4 South, Range 9 West, Salt Lake Meridian, Utah

From the 1/4 corner of sections 5 and 32, on the south boundary of township, hereinbefore described.

N. 0° 34.3' E., on the N-S center line of section 32.

20.140 Point for the center S 1/16 section corner of section 32.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T4S R9W
C
S1/16 | S32
C
2004

40.280 Point for the center 1/4 section corner of section 32, at intersection with the E-W center line, not monumented.

80.960 The 1/4 section corner of sections 29 and 32.

THE SUBDIVISION OF SECTION 32,
TOWNSHIP 4 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 32 and 33.

S. 89° 49.2' W., on the E-W center line of section 32.

40.228 The point for the center 1/4 section corner of section 32.

80.410 The 1/4 section corner of sections 31 and 32.

From the S 1/16 section corner of sections 32 and 33.

S. 89° 48.2' W., on the E-W center line of the SE 1/4 of section 32.

40.228 The center S 1/16 section corner of section 32.

From the center S 1/16 section corner of section 32.

S. 89° 52.2' W., on the E-W center line of the SW 1/4 of section 32.

40.193 The S 1/16 section corner of section 31 and 32.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Daniel W. Webb	Chief Cadastral Surveyor
Michael L. Thompson	Cadastral Surveyor
David B. Cook	Cartographic Technician

CERTIFICATE OF SURVEY

I **Ronald K. Baugh**, Cadastral Surveyor, hereby certify upon honor, that in pursuance of special instructions bearing the date of the **4th day of September, 2003**, I have **dependently resurveyed the south boundary, a portion of the east boundary, a portion of the west boundary (Guide Meridian), a portion of the subdivisional lines, and the subdivision of section 32, in Township 4 South, Range 9 West,**

of the **Salt Lake Meridian**, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions of the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 26, 2006

Date

Ronald K. Baugh
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The following field notes of the **dependent resurvey of the south boundary, a portion of the east boundary, a portion of the west boundary (Guide Meridian), a portion of the subdivisional lines, and the subdivision of section 32, in Township 4 South, Range 9 West, Salt Lake Meridian, Utah,**

executed by **Ronald K. Baugh**, Cadastral Surveyor having been critically examined and found correct, are hereby approved.

May 2, 2006

Date

Daniel W. Webb

(Chief Cadastral Surveyor for Utah)