

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

OF THE EAST BOUNDARY,

THE NORTH BOUNDARY,

THE SUBDIVISIONAL LINES

AND THE

SUBDIVISION OF SECTIONS 3, 10, 15, AND 21,

IN

TOWNSHIP 40 SOUTH, RANGE 25 EAST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

M. Ross Workman
Cadastral Surveyor

Under special instructions dated and approved **January 28, 2004**, which provided for the surveys included under Group Number **972**, and assignment instructions dated **January 28, 2004**.

Survey commenced **February 18, 2004**

Survey completed **May 6, 2004**

INDEX DIAGRAM

Township 40 South, Range 25 East

11	11	10	9	8	7
6 50	5 41	4 34	3 26	2 19	1 6
50	50	41	33	25	18
7 49	8 40	9 32	10 25	11 18	12 5
48	48	39	31	24	17
18 47	17 39	16 31	15 23	14 16	13 4
47	46	38	30	23	16
19 45	20 37	21 29	22 22	23 15	24 3
45	44	37	29	22	14
30 44	29 36	28 28	27 21	26 14	25 3
43	43	35	28	20	13
31 42	32 34	33 27	34 20	35 12	36 2

The Subdivision of Section 3.....Page 51

The Subdivision of Section 10.....Page 54

The Subdivision of Section 15.....Page 54

The Subdivision of Section 21.....Page 56

TOWNSHIP 40 SOUTH, RANGE 25 EAST, SALT LAKE MERIDIAN

The following field notes describe the dependent resurvey of the east boundary, the north boundary and subdivisional lines, and the subdivision of section 3, 10, 15 and 21 in Township 40 South, Range 25 East, Salt Lake Meridian, Utah.

HISTORY OF EARLIER SURVEYS

Surveyed by		Retraced or Resurveyed by	
SOUTH BOUNDARY (Eighth Standard Parallel South)			
All	A.D. Ferron	1884	
All		H.D. Page & J.M. Lentz	1899
All		J.F. Carroll	2004
EAST BOUNDARY			
All	A.D. Ferron	1884	
All		H.D. Page & J.M. Lentz	1899
WEST BOUNDARY			
All	A.D. Ferron	1884	
All		H.D. Page & J.M. Lentz	1899
All		Merrill D. Cazier	2003
NORTH BOUNDARY			
All	A.D. Ferron	1884	
All		H.D. Page & J.M. Lentz	1899
All		D.B Miller & J.C. Thoma	1912
SUBDIVISION			
All	H. Page & J. Lentz	1899	

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instruction, 1973 and the Special Instructions for Group No. 972, dated January 28, 2004.

This survey was executed with a Trimble 5800, Global Positioning System (GPS), using relative positioning techniques to establish a geographic position for each corner. The true geodetic mean bearings and the true horizontal ground distances were determined by inverting between the established positions.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and their calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations, post processed by National Geodetic Survey, Online Positioning User Service, (OPUS), Utilizing Continuously Operating Reference Stations; (CORS) FREDONIA, CARBON COUNTY COU, AND AZTEC. The N.A.D. 1983 (CORS96) geographic position of the standard corner of sections 31 and 36 (SE corner of the township on the Eighth Standard Parallel South), is as follows:

Latitude: 37° 15' 32.145" N. Longitude: 109° 06' 49.579" W.
 NAD 1983 Elevation: 4815.4 ft.

CHAINS

Dependent Resurvey of the East Boundary
T. 40 S., R 25 E., Salt Lake Meridian, Utah

Reestablishment of the Survey
Executed by A.D. Ferron in 1884
and the Resurvey by H.D. Page & J.M. Lentz in 1899

Beginning at the standard corner of sections 31 and 36 (SE corner of the township on the Eighth Standard Parallel South), monumented with a stainless steel post, 2 1/2 inches diameter, and brass cap marked as described in the official record of the 2004 dependent resurvey of Township 41 South, Range 25 East.

N. 0° 19.9' W., between sections 31 and 36.

37.776

The 1/4 section corner of sections 31 and 36, monumented with a weathered sandstone, 16x11x6 inches, in a mound of stone.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 3 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 6 ft. base to top of brass cap marked:

T40S
R25E R26E
1/4
S36 | S31
2004

Deposit weathered stone alongside the monument.

Monument is located 2 links N of draw, drains SE.

N. 0° 01.1' E., beginning new measurement.

39.944

Point for the corner of sections 25, 30, 31 and 36, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, and in a mound of stone, 6 ft. base to top of brass cap marked:

T40S
R25E R26E
S25 | S30

S36 | S31
2004

Raise a mound of stone 4 ft. base, 3 ft. high, W of monument.

**DEPENDENT RESURVEY OF THE EAST BOUNDARY
T. 40 S., R 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Monument is located about 30 links E of wash, drains SW.

N. 0° 01.1' E., between sections 25 and 30.

39.944

The 1/4 section corner of sections 25 and 30, monumented with a sandstone, 13x9x7 inches, firmly set and plainly marked 1/4 on W face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S
R25E R26E
1/4
S25 | S30
2004

Deposit marked stone alongside the monument.

Raise a mound of stone 2 ft. base, 1 1/2 ft. high, W of monument.

N. 0° 04.4' W., beginning new measurement.

40.008

The corner of sections 19, 24, 25 and 30, monumented with a sandstone, 11x8x8 inches, firmly set and plainly marked 2 notches on S and 4 notches on N edges.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, and brass cap marked:

T40S
R25E R26E
S24 | S19

S25 | S30
2004

Deposit marked stone alongside the monument.

Raise a mound of stone 3 ft. base, 2 ft. high, W of monument.

N. 0° 00.7' E., between sections 19 and 24.

**DEPENDENT RESURVEY OF THE EAST BOUNDARY
T. 40 S., R 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

40.027

Point for the 1/4 section corner of sections 19 and 24, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S
R25E R26E
1/4
S24 | S19
2004

Raise a mound of stone 4 ft. base, 3 ft. high, E of monument.

A large boulder is E of monument.

Monument is located on a moderate to steep E slope.

80.054

The corner of sections 13, 18, 19 and 24, monumented with a broken sandstone, in a mound of stone.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with a magnet at base, and brass cap marked:

T40S
R25E | R26E
S13 | S18

S24 | S19
2004

Deposit broken stone alongside the monument.

N. 0° 03.0' W., between sections 13 and 18.

40.012

The 1/4 section corner of sections 13 and 18, monumented with a sandstone, 16x13x7 inches, firmly set and plainly marked 1/4 on W face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, and in a mound of stone, 6 ft. base to top of brass cap marked:

**DEPENDENT RESURVEY OF THE EAST BOUNDARY
T. 40 S., R 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S
R25E R26E
1/4
S13 | S18
2004

Deposit marked stone alongside the monument.

N. 0° 01.4' W., beginning new measurement.

39.984 Point for the corner of sections 7, 12, 13 and 18, at proportionate distance, falls in dirt road bearing E and W, there is no remaining evidence of the original corner.

Set a railroad spike flush with the surface of the road.

From which,

A boulder in place, marked XBO, bears N. 1° 04.7' W., 86.6 links distance.

A nail in a power pole, bears N. 33° 54.6' W., 94.8 links distance.

N. 0° 01.4' W., between sections 7 and 12.

39.984 The 1/4 section corner of sections 7 and 12, monumented with a sandstone, 21x9x8 inches, firmly set and plainly marked 1/4 on W face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S
R25E R26E
1/4
S12 | S7
2004

Deposit marked stone alongside the monument.

Raise a small mound of stone W of monument.

N. 0° 02.6' E., beginning new measurement.

39.863 The corner of sections 1, 6, 7 and 12, monumented with a sandstone, 17x9x5 inches, firmly set and plainly marked 5 notches on S and 1 notch on N edges.

**DEPENDENT RESURVEY OF THE EAST BOUNDARY
T. 40 S., R 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground, in a collar of stone, and brass cap marked:

T40S	
R25E	R26E
S1	S6

S12	S7
2004	

Deposit marked stone alongside the monument.

Monument is located between 2 large boulders on E slope.

N. 0° 03.9' E., between sections 1 and 6.

40.000

The 1/4 section corner of sections 1 and 6, monumented with a sandstone, 20x8x6 inches, firmly set and plainly marked 1/4 on W face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground to bed rock, in a mound of stone, 6 ft. base, to top of brass cap marked:

T40S	
R25E	R26E
1/4	
S1	S6
2004	

Deposit marked stone alongside the monument.

N. 0° 02.4' E., beginning new measurement.

40.058

The corner of sections 1, 6, 31 and 36, the NE corner of the township, monumented with a sandstone, 20x9x9 inches, firmly set and plainly marked 6 notches on N, S, E and W edges.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, and brass cap marked:

**DEPENDENT RESURVEY OF THE EAST BOUNDARY
T. 40 S., R 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

T39S	
R25E	R26E
S36	S31

S1	S6
T40S	
2004	

Deposit marked stone alongside the monument.

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W of monument.

Dependent Resurvey of the North Boundary
T. 40 S., R. 25 E., Salt Lake Meridian, Utah

Reestablishment of the survey executed by A.D. Ferron in 1884,
The Resurvey by H.D. Page and J.M. Lentz, in 1899, and the
Resurvey by D.B. Miller and J.C. Thoma in 1912.

From the corner of sections 1, 6, 31 and 36, the NE corner of the township.

S. 89° 55.3' W., between sections 1 and 6.

39.968

The 1/4 section corner of sections 1 and 36, monumented with a sandstone, 16x8x5 inches, firmly set and plainly marked 1/4 on N face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, and brass cap marked:

T39S R25E	
S36	
1/4	-----
S1	
T40S	
2004	

Deposit marked stone alongside the monument.

Raise a small mound of stone, N of monument.

Monument is located on flat open land.

N. 89° 59.4' W., beginning new measurement.

**DEPENDENT RESURVEY OF THE NORTH BOUNDARY
T. 40 S., R 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

40.005

The corner of sections 1, 2, 35 and 36, monumented with a sandstone, 21x11x8 inches, firmly set and plainly marked 1 notch on E and 5 notches on W edges, and a 5/8 inch rebar alongside and aluminum cap improperly marked:

	T39	
35		36
2		1 R26
T40		

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, and brass cap marked:

T39S		R25E
S35		S36
S2		S1
T40S		
2004		

Deposit marked stone alongside, and rebar and cap inside monument.

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W of monument.

N. 89° 50.7' W., between sections 2 and 35.

40.050

The 1/4 section corner of sections 2 and 35, monumented with a sandstone, 16x10x7 inches, firmly set and dimly marked 1/4 on N face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 6 ft. base to top of brass cap marked:

T39S		R25E
		S35
1/4		_____
		S2
T40S		
2004		

Deposit marked stone alongside the monument.

Monument is located 30 links E of draw, drains NW.

**DEPENDENT RESURVEY OF THE NORTH BOUNDARY
T. 40 S., R 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

S. 89° 43.6' W., beginning new measurement.

39.872

The corner of sections 2, 3, 34 and 35, monumented with a sandstone, 18x11x5 inches, firmly set and plainly marked 2 notches on E and 4 notches on W edges.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 5 ft. base to top of brass cap marked:

T39S	R25E
S34	S35
S3	S2
T40S	
2004	

Deposit marked stone alongside the monument.

N. 89° 47.6' W., between sections 3 and 34.

20.090

Point for the E 1/16 section corner of sections 3 and 34, not monumented.

40.180

The 1/4 section corner of sections 3 and 34, monumented with a sandstone, 24x9x8 inches, firmly set and plainly marked 1/4 on N face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 6 ft. base to top of brass cap marked:

T39S	R25E
	S34
1/4	_____
	S3
	T40S
	2004

Deposit marked stone alongside the monument.

Monument is located on a S slope.

S. 89° 45.7' W., beginning new measurement.

**DEPENDENT RESURVEY OF THE NORTH BOUNDARY
T. 40 S., R 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS**39.952**

The corner of sections 3, 4, 33 and 34, monumented with a sandstone, 34x11x6 inches, firmly set and plainly marked 3 notches on E and 3 notches on W edges.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, brass cap marked:

T39S	R25E
S33	S34
S4	S3
T40S	
2004	

Deposit marked stone alongside the monument.

S. 89° 53.2' W., between sections 4 and 33.

39.979

The 1/4 section corner of sections 4 and 33, monumented with a sandstone, 16x10x4 inches, loosely set and dimly marked 1/4 on N face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground, with a magnet at the base, and brass cap marked:

T39S	R25E
	S33
1/4	_____
	S4
T40S	
2004	

Deposit marked stone alongside the monument.

A cedar stump bear S, 10.5 links distance.

S. 89° 57.2' W., beginning new measurement.

40.137

The corner of sections 4, 5, 32 and 33, monumented with a sandstone, 17x10x10 inches, firmly set and plainly marked 4 notches on E and 2 notches on W edges.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground, to bedrock, with a magnet at base, and in a mound of stone, 6 ft. base to top of brass cap marked:

**DEPENDENT RESURVEY OF THE NORTH BOUNDARY
T. 40 S., R 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

T39S	R25E
S32	S33

S5	S4
T40S	
2004	

Deposit marked stone alongside the monument.

Monument is located on a steep N slope 75 links S of wash, drains NW.

S. 89° 52.6' W., between sections 5 and 32.

39.957

Point for the 1/4 section corner of sections 5 and 32, at proportionate distance, based on the irregular boundary adjustment, there is no remaining evidence of the 1912 resurvey corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 6 ft. base to top of brass cap marked:

T39S	R25E
	S32
1/4	-----
	S5
T40S	
2004	

Monument is located about 50 links N of wash, drains westerly.

N. 89° 52.4' W., beginning new measurement.

39.887

Point for the corner of sections 5, 6, 31 and 32, at proportionate distance, based on the irregular boundary adjustment, there is no remaining evidence of the 1912 resurvey corner.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, and in a collar of stone, to top of brass cap marked:

T39S	R25E
S31	S32

S6	S5
T40S	
2004	

**DEPENDENT RESURVEY OF THE NORTH BOUNDARY
T. 40 S., R 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Raise a small mound of stone, 4 ft. base, 2 ft. high, W of monument.

Monument is located on a steep E slope.

N. 89° 52.4' W., between sections 6 and 31.

39.887

The 1/4 section corner of sections 6 and 31, monumented with a malpais stone, (basaltic lava), 15x14x6 inches, firmly set and plainly marked 1/4 on N face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 5 ft. base to top of brass cap marked:

T39S R25E
S31
1/4 ———
S6
T40S
2004

Deposit marked stone alongside the monument.

Monument is located on a N slope about 50 links S of a draw, drains NE.

N. 89° 49.8' W., beginning new measurement.

39.300

The corner of sections 1, 6, 31 and 36, NW corner of the township, monumented with a brass tablet flush with sandstone, and brass cap marked as described in the official record of the 2003 dependent resurvey.

Dependent Resurvey of the Subdivisional Lines
T. 40 S., R. 25 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
H.D. Page and J.M. Lentz, in 1899

From the standard corner of sections 35 and 36, (Eighth Standard Parallel South) on the S boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, and brass cap marked as described in the official record of the 2004 dependent resurvey of Township 41 South, Range 25 East.

N. 0° 04.2' W., between sections 35 and 36.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS**39.908**

Point for the 1/4 section corner of sections 35 and 36, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, and brass cap marked:

T40S	R25E
	1/4
S35	S36
	2004

Raise a mound of stone, 4 ft. base, 3 ft. high, W of monument.

Monument is located on W side of a spur sloping N.

79.816

The corner of sections 25, 26, 35 and 36, monumented with a sandstone, 20x12x6 inches, firmly set and plainly marked 1 notch on S and E edges.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with a magnet at the base, and brass cap marked:

T40S	R25E
S26	S25
S35	S36
	2004

Deposit marked stone alongside the monument.

From the corner of sections 25, 30, 31 and 36, on the E boundary of the township, hereinbefore described.

S. 89° 58.0' W., between sections 25 and 36.

40.063

Point for the 1/4 section corner of sections 25 and 36, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 6 ft. base to top of brass cap marked:

T40S	R25E
	S25
1/4	_____
	S36
	2004

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Monument is located about 50 links W of wash, in bottom of a canyon, drains SW.

80.126 The corner of sections 25, 26, 35 and 36.

N. 0° 01.1' E., between sections 25 and 26.

40.029 Point for the 1/4 section corner of sections 25 and 26, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S	R25E
1/4	
S26	S25
2004	

Raise a mound of stone, 4 ft. base, 3 ft. high, W of monument.

80.058 The corner of sections 23, 24, 25 and 26, monumented with a sandstone, 16x12x5 inches, firmly set and plainly marked 1 notch on E and 2 notches on S edges.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S	R25E
S23	S24

S26	S25
2004	

Deposit marked stone alongside the monument.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of monument.

From the corner of sections 19, 24, 25 and 30, on the E boundary of the township, hereinbefore described.

S. 89° 42.2' W., between sections 24 and 25.

40.041 The 1/4 section corner of sections 24 and 25, monumented with a sandstone, 18x9x8 inches, firmly set and dimly marked 1/4 on N face.

At the corner point.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 6 ft. base to top of brass cap marked:

T40S R25E
S24
1/4 ———
S25
2004

Deposit marked stone alongside the monument.

N. 89° 37.2' W., beginning new measurement.

40.005 The corner of sections 23, 24, 25 and 26.

N. 0° 02.6' W., between sections 23 and 24.

39.975 The 1/4 section corner of sections 23 and 24, monumented with a sandstone, 11x10x5 inches, firmly set and plainly marked 1/4 on W face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
1/4
S23 | S24
2004

Deposit marked stone alongside the monument.

Raise a mound of stone 3 ft. base, 2 ft. high, W of monument.

Monument is located about 6 links N of a wash, drains SW.

N. 0° 02.2' E., beginning new measurement.

39.910 The corner of sections 13, 14, 23 and 24, monumented with a sandstone, 18x15x5 inches, firmly set, marks have been obliterated.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S	R25E
S14	S13

S23	S24
2004	

Deposit stone alongside the monument.

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W of monument.

From the corner of section 13, 18, 19 and 24 on the E boundary of the township, hereinbefore described.

S. 89° 55.2' W., between sections 13 and 24.

40.025

Point for the 1/4 section corner of sections 13 and 24, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, and in a collar of stone, and brass cap marked:

T40S	R25E
	S13
1/4	-----
	S24
2004	

Raise a mound of stone, 4 ft. base, 2 ft. high, N of monument.

Monument is located in sandy soil.

80.050

The corner of sections 13, 14, 23 and 24.

N. 0° 00.8' E., between sections 13 and 14.

40.030

The 1/4 section corner of sections 13 and 14, monumented with a sandstone, 15x9x6 inches, firmly set and plainly marked 1/4 on W face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S	R25E
	1/4
S14	S13
2004	

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Deposit marked stone alongside the monument.

Raise a mound of stone 3 ft. base, 2 ft. high, W of monument.

Monument is located at base of steep ascent to the E.

N. 0° 05.7' W., beginning new measurement.

40.028

The corner of sections 11, 12, 13 and 14, monumented with a sandstone, 16x15x4 inches, firmly set and plainly marked 1 notch on E and 4 notches on S edges.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with a magnet at base, and brass cap marked:

T40S	R25E
S11	S12
S14	S13
2004	

Deposit marked stone alongside the monument.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of monument.

From the corner of sections 7, 12, 13 and 18, on the E boundary of the township, hereinbefore described.

N. 89° 50.0' W., between sections 12 and 13.

39.911

The 1/4 section corner of sections 12 and 13, monumented with a sandstone, 28x12x5 inches, firmly set, marks have been obliterated.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 6 ft. base to top of brass cap marked:

T40S	R25E
S12	
1/4	
S13	
2004	

Deposit stone alongside the monument.

Monument is located 144 links W of a ledge.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

S. 89° 45.9' W., beginning new measurement.

40.131 The corner of sections 11, 12, 13 and 14.

N. 0° 10.3' W., between sections 11 and 12.

40.170 The 1/4 section corner of sections 11 and 12, monumented with a mound of stone.

At the corner point. (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S	R25E
	1/4
S11	S12
	2004

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W of monument.

N. 0° 02.5' W., beginning new measurement.

40.000 The corner of sections 1, 2, 11 and 12, monumented with a sandstone, 16x12x6 inches, firmly set, marks have been obliterated.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S	R25E
S2	S1
<hr/>	
S11	S12
	2004

Deposit stone alongside the monument.

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W of monument.

From the corner of sections 1, 6, 7 and 12, on the E boundary of the township, hereinbefore described.

N. 89° 50.1' W., between sections 1 and 12.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

39.935 The 1/4 section corner of sections 1 and 12, monumented with a sandstone, 15x12x4 inches, firmly set and plainly marked 1/4 on N face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground to bed rock, in a mound of stone, 5 ft. base to top of brass cap marked:

T40S R25E
S1
1/4 _____
S12
2004

Deposit marked stone alongside the monument.

N. 89° 46.5' W., beginning new measurement.

40.250 The corner of sections 1, 2, 11 and 12.

N. 0° 12.5' E., between sections 1 and 2.

39.832 The 1/4 section corner of sections 1 and 2, monumented with a weathered sandstone, 19x13x2 inches, lying on the ground E of a mound of stone, marks have been obliterated.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
1/4
S2 | S1
2004

Deposit stone alongside the monument.

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W of monument.

N. 0° 10.7' E., beginning new measurement.

39.906 The corner of sections 1, 2, 35 and 36, on the N boundary of township, hereinbefore described.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

From the standard corner of sections 34 and 35, (Eighth Standard Parallel South), on the S boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, with a brass cap marked as described in the official record of the 2004 dependent resurvey, of Township 41 South, Range 25 East.

N. 0° 26.3' E., between sections 34 and 35.

39.996

The 1/4 section corner of sections 34 and 35, monumented with a mound of stone.

At the corner point. (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, and brass cap marked:

T40S	R25E
	1/4
S34	S35
	2004

Raise a mound of stone 2 ft. base, 1 1/2 ft. high, W of monument.

N. 0° 29.3' W., beginning new measurement.

39.946

The corner of sections 26, 27, 34 and 35, monumented with a sandstone, 16x8x6 inches, firmly set in a mound of stone, marks have been obliterated.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S	R25E
S27	S26
— —	
S34	S35
	2004

Deposit stone alongside the monument.

Raise a mound of stone 2 ft. base, 1 1/2 ft. high, W of monument.

From the corner of sections 25, 26, 35 and 36.

N. 89° 55.7' W., between sections 26 and 35.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

40.165 The 1/4 section corner of sections 26 and 35, monumented with a sandstone, 18x10x7 inches, firmly set and plainly marked 1/4 on N face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
S26
1/4 ———
S35
2004

Deposit marked stone alongside the monument.

Raise a mound of stone, 4 ft. base, 2 ft. high, N of monument.

Monument is located on a gradual N slope about 50 links S of a draw, drains E.

N. 89° 57.2' W., beginning new measurement.

39.750 The corner of sections 26, 27, 34 and 35.

N. 0° 06.9' E., between sections 26 and 27.

39.817 The 1/4 section corner of sections 26 and 27, monumented with a sandstone, 18x12x3 inches, firmly set and plainly marked 1/4 on W face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bed rock, with a magnet at base, and in a mound of stone, 5 ft. base to top of brass cap marked:

T40S R25E
1/4
S27 | S26
2004

Deposit marked stone alongside the monument.

N. 0° 06.3' W., beginning new measurement.

40.029 The corner of sections 22, 23, 26 and 27, monumented with a weathered sandstone, 21x12x5 inches, firmly set, in a mound of stone, marks have been obliterated.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 23 inches in the ground, with a magnet at base, and brass cap marked:

T40S	R25E
S22	S23
S27	S26
2004	

Deposit stone alongside the monument.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of monument.

From the corner of sections 23, 24, 25 and 26.

S. 89° 45.5' W., between sections 23 and 26.

39.929

The 1/4 section corner of sections 23 and 26, monumented with a sandstone, 16x9x4 inches, firmly set and dimly marked 1/4 on N face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 6 ft. base to top of brass cap marked:

T40S	R25E
	S23
1/4	_____
	S26
2004	

Deposit marked stone alongside the monument.

N. 89° 56.7' W., beginning new measurement.

39.991

The corner of sections 22, 23, 26 and 27.

N. 0° 06.7' W., between sections 22 and 23.

39.997

Point for the 1/4 section corner of sections 22 and 23, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S R25E
1/4
S22 | S23
2004

Monument is located in sandy soil.

79.994

Point for the corner of sections 14, 15, 22 and 23, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 8 ft. base to top of brass cap marked:

T40S R25E
S15 | S14

S22 | S23
2004

Monument is located in a small drainage, drains E, and 50 links E of the base of 30 ft. high ledges.

From the corner of sections 13, 14, 23 and 24.

S. 89° 59.1' W., between sections 14 and 23.

40.028

Point for 1/4 section corner of sections 14 and 23, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 6 ft. base to top of brass cap marked:

T40S R25E
S14
1/4 -----
S23
2004

80.056

The corner of sections 14, 15, 22 and 23.

N. 0° 09.3' W., between sections 14 and 15.

39.997

The 1/4 section corner of sections 14 and 15, monumented with a mound of stone.

At the corner point. (center of mound)

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 6 ft. base to top of brass cap marked:

T40S R25E
1/4
S15 | S14
2004

N. 0° 21.8' E., beginning new measurement.

39.879

The corner of sections 10, 11, 14 and 15, monumented with a sandstone, 23x10x8 inches, firmly set in a mound of stone, marks have been obliterated.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
S10 | S11

S15 | S14
2004

Deposit stone alongside the monument.

Raise a mound of stone, 4 ft. base, 2 ft. high, W of monument.

From the corner of sections 11, 12, 13 and 14.

S. 89° 56.0' W., between sections 11 and 14.

39.856

The 1/4 section corner of sections 11 and 14, monumented with a broken sandstone.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
S11
1/4 -----
S14
2004

Deposit broken stone alongside the monument.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Raise a small mound of stone, N of monument.

S. 89° 46.4' W., beginning new measurement.

39.983 The corner of sections 10, 11, 14 and 15.

N. 0° 05.7' E., between sections 10 and 11.

39.981 Point for the 1/4 section corner of sections 10 and 11, at proportionate distance, there in no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S	R25E
	1/4
S10	S11
	2004

79.962 The corner of sections 2, 3, 10 and 11, monumented with a sandstone, 16x10x4 inches, firmly set and plainly marked 5 notches on S and 2 notches in E edges.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S	R25E
S3	S2
<hr/>	
S10	S11
	2004

Deposit marked stone alongside the monument.

From the corner of sections 1, 2, 11 and 12.

S. 89° 36.7' W., between sections 2 and 11.

39.835 The 1/4 section corner of sections 2 and 11, monumented with a sandstone, 18x14x3 inches, firmly set and plainly marked 1/4 on N face.

At the corner point.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 6 ft. base to top of brass cap marked:

T40S R25E
S2
1/4 —————
S11
2004

Deposit marked stone alongside the monument.

S. 89° 47.8' W., beginning new measurement.

39.709 The corner of sections 2, 3, 10 and 11.

N. 0° 26.3' W., between sections 2 and 3.

19.997 Point for the S 1/16 section corner of sections 2 and 3.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
S 1/16
S3 | S2
2004

Monument is located on a sagebrush flat.

39.994 The 1/4 section corner of sections 2 and 3, monumented with a sandstone, 20x10x10 inches, firmly set and plainly marked 1/4 on W face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
1/4
S3 | S2
2004

Deposit marked stone alongside the monument.

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W of monument.

Monument is located about 100 links N of a wash, drains W.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

N. 0° 16.2' E., beginning new measurement.

20.023 Point for the N 1/16 section corner of sections 2 and 3, not monumented.

40.076 The corner of sections 2, 3, 34 and 35, on the N boundary of the township, hereinbefore described.

From the standard corner of section 33 and 34, (Eighth Standard Parallel South), on the S boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, with a brass cap marked as described in the official record of the 2004 dependent resurvey, of Township 41 South, Range 25 East.

N. 0° 01.9' E., between sections 33 and 34.

39.890 Point for the 1/4 section corner of sections 33 and 34, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S	R25E
	1/4
S33	S34
	2004

Raise a mound of stone, 3 ft. base, 2 ft. high, W of monument.

79.780 The corner of sections 27, 28, 33 and 34, monumented with a sandstone, 18x10x7 inches, firmly set and plainly marked 1 notch on S and 3 notches on E edges.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S	R25E
S28	S27
<hr/>	
S33	S34
	2004

Deposit marked stone alongside the monument.

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W of monument.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

From the corner of sections 26, 27, 34 and 35.

S. 89° 35.3' W., between sections 27 and 34.

39.776

The 1/4 section corner of sections 27 and 34, monumented with a sandstone 14x14x8 inches, firmly set and plainly marked 1/4 on N face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
S27
1/4 ———
S34
2004

Deposit marked stone alongside the monument.

Raise a mound of stone, 3 ft. base, 2 ft. high, N of monument.

N. 89° 50.0' W., beginning new measurement.

40.071

The corner of sections 27, 28, 33 and 34.

N. 0° 02.2' E., between sections 27 and 28.

40.117

The 1/4 section corner of sections 27 and 28, monumented with a mound of stone.

At the corner point. (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 6 ft. base to top of brass cap marked:

T40S R25E
1/4
S28 | S27
2004

N. 0° 14.7' W., beginning new measurement.

39.976

The corner of sections 21, 22, 27 and 28, monumented with a sandstone 16x10x8 inches, firmly set in a mound of stone, and plainly marked 2 notches on S and 3 notches on E edges.

At the corner point.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, and brass cap marked:

T40S	R25E
S21	S22

S28	S27
2004	

Deposit marked stone alongside the monument.

Raise a mound of stone, 5 ft. base, 3 ft. high, W of monument.

From the corner of sections 22, 23, 26 and 27.

S. 89° 52.2' W., between sections 22 and 27.

39.864

The 1/4 section corner of sections 22 and 27, monumented with a broken sandstone, with an old wooden hub alongside.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S	R25E
	S22
1/4	-----
	S27
2004	

Deposit broken stone, and hub alongside the monument.

Raise a mound of stone 4 ft. base, 2 ft. high, N of monument.

N. 89° 45.6' W., beginning new measurement.

40.120

The corner of sections 21, 22, 27 and 28.

N. 0° 08.0' W., between sections 21 and 22.

40.014

The 1/4 section corner of sections 21 and 22, monumented with a sandstone 16x11x6 inches, firmly set and dimly marked 1/4 on W face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, and brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S R25E
1/4
S21 | S22
2004

Deposit marked stone alongside the monument.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of monument.

N. 0° 12.8' W., beginning new measurement.

39.886

The corner of sections 15, 16, 21 and 22, monumented with a weathered sandstone 15x11x4 inches, loosely set, marks have been obliterated.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
S16 | S15

S21 | S22
2004

Deposit weathered stone alongside the monument.

Raise a mound of stone, 4 ft. base, 2 ft. high, W of monument.

From the corner of sections 14, 15, 22 and 23.

S. 89° 59.3' W., between sections 15 and 22.

40.028

Point for the 1/4 section corner of sections 15 and 22 at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
S15
1/4 ———
S22
2004

Monument is located 15 links S of wash, 4 ft. deep, drains westerly.

80.056

The corner of sections 15, 16, 21 and 22.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

N. 0° 24.9' E., between sections 15 and 16.

39.933

The 1/4 section corner of sections 15 and 16, monumented with a sandstone, 18x10x9 inches, firmly set and dimly marked 1/4 on W face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
1/4
S16 | S15
2004

Deposit marked stone alongside the monument.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of monument.

Monument is located 100 links S of a gravel road, bears NE and SW.

N. 0° 29.4' W., beginning new measurement.

40.047

The corner of sections 9, 10, 15 and 16, monumented with a sandstone, 15x10x6 inches, firmly set and plainly marked 4 notches on S and 3 notches on E edges.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
S9 | S10

S16 | S15
2004

Deposit marked stone alongside the monument.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of monument.

From the corner of sections 10, 11, 14 and 15.

N. 89° 56.3' W., between sections 10 and 15.

20.060

Point for the E 1/16 section corner of 10 and 15.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
S10
E 1/16 ———
S15
2004

Monument is located in a sagebrush flat.

- 40.120** Point for the 1/4 section corner of sections 10 and 15, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
S10
1/4 ———
S15
2004

Monument is located on flat sandy land.

- 60.180** Point for the W 1/16 section corner of sections 10 and 15.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
S10
W 1/16 ———
S15
2004

Monument is located in a sagebrush flat.

- 80.240** The corner of sections 9, 10, 15 and 16.

N. 0° 11.1' E., between sections 9 and 10.

- 39.976** Point for the 1/4 section corner of sections 9 and 10, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S R25E
1/4
S9 | S10
2004

Monument is located 20 links W of a trail road.

79.952

The corner of sections 3, 4, 9 and 10, monumented with a cross (X) on a ledge with 5 notches on S and 3 notches on E sides.

At the corner point.

Set a brass tablet, 3 1/4 inch diameter, with a 3 1/2 inch stem, flush with sandstone, in cement bound, into a drill hole on solid rock marked:

T40S R25E
S4 | S3

S9 | S10
2004

Raise a mound of stone 4 ft. base, 2 ft. high, W of monument.

Monument is located 1 chain E and 50 ft. below ledge.

From this corner, a vertical control station established by NGS in 1984, monumented with a standard 3 inch brass tablet, set in rock outcropping marked, "C379 1984", bears S. 86° 22.2' E., 18.645 chains distance. The geographic position of the point is as follows:

Latitude: 37° 19' 50.700" N. Longitude: 109° 09' 50.524" W.
NAD 1983, Elevation: 5190.23

From the corner of sections 2, 3, 10 and 11.

N. 89° 56.8' W., between sections 3 and 10.

20.024

Point for the E 1/16 section corner of sections 3 and 10, not monumented.

40.048

Point for the 1/4 section corner of sections 3 and 10, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 5 ft. base to top of brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S R25E
S3
1/4—
S10
2004

80.096 The corner of sections 3, 4, 9 and 10.

N. 0° 12.3' W., between sections 3 and 4.

39.681 The 1/4 section corner of sections 3 and 4, monumented with a weathered sandstone, firmly set in a mound of stone, marks have been obliterated.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 6 ft. base to top of brass cap marked:

T40S R25E
1/4
S4 | S3
2004

Deposit sandstone alongside the monument.

Monument is located on W edge of wash in canyon, drains northerly.

N. 0° 02.3' W., beginning new measurement.

40.290 The corner of sections 3, 4, 33 and 34, on the N boundary of township, hereinbefore described.

From the standard corner of sections 32 and 33 (Eighth Standard Parallel South), on the S boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, with a brass cap marked as described in the official record of the 2004 dependent resurvey, of Township 41 South, Range 25 East.

N. 1° 04.0' E., between sections 32 and 33.

39.978 The 1/4 section corner of sections 32 and 33, monumented with a sandstone, 14x12x6 inches, firmly set and plainly marked 1/4 on W face.

At the corner point.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 6 ft. base to top of brass cap marked:

T40S R25E
1/4
S32 | S33
2004

Deposit marked stone alongside the monument.

Monument is located about 75 links E of 12 ft. ledge.

N. 0° 39.8' W., beginning new measurement.

39.832

The corner of sections 28, 29, 32 and 33, monumented with a sandstone, 16x6x6 inches, plainly marked 1 notch on S and 4 notches on E edges.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 6 ft. base to top of brass cap marked:

T40S R25E
S29 | S28

S32 | S33
2004

Deposit marked stone alongside the monument.

Monument is located 30 links W of edge of wash, drains SE.

From the corner of sections 27, 28, 33 and 34.

N. 89° 53.6' W., between sections 28 and 33.

39.803

The 1/4 section corner of sections 28 and 33, monumented with a sandstone, 18x10x4 inches, loosely set and dimly marked 1/4 on N face, with a mound of stone to the N.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 6 ft. base to top of brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S R25E
S28
1/4 ———
S33
2004

Deposit marked stone alongside the monument.

S. 89° 54.4 W, beginning new measurement.

39.899 The corner of sections 28, 29, 32 and 33.

N. 0° 10.0' W., between sections 28 and 29.

39.870 The 1/4 section corner of sections 28 and 29, monumented with a sandstone, 14x9x5 inches, firmly set and plainly marked 1/4 on W face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
1/4
S29 | S28
2004

Deposit marked stone alongside the monument.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of monument.

Monument is located under a power line, bears E and W.

N. 0° 33.2' W., beginning new measurement.

40.127 The corner of sections 20, 21, 28 and 29, monumented with a sandstone, 18x7x7 inches, firmly set and plainly marked 2 notches on S and 4 notches on E edges.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
S20 | S21
———
S29 | S28
2004

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Deposit marked stone alongside the monument.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of monument.

From the corner of sections 21, 22, 27 and 28.

S. 89° 56.2' W., between sections 21 and 28.

40.022 Point for the 1/4 section corner of sections 21 and 28, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
S21
1/4 ———
S28
2004

80.044 The corner of sections 20, 21, 28 and 29.

N. 0° 02.4' W., between sections 20 and 21.

39.972 Point for the 1/4 section corner of sections 20 and 21, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
1/4
S20 | S21
2004

Raise a mound of stone, 4 ft. base, 2 ft. high, W of monument.

Monument is located at the confluence of two small washes, draining westerly.

59.958 Point for the N 1/16 section corner of sections 20 and 21,

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, and brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S R25E
N1/16
S20 | S21
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, W of monument.

A fence corner, projecting N and E, bears N. 15° 30.5' E., 94.4 links distance.

- 79.944** Point for the corner of sections 16, 17, 20 and 21, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 4 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 6 ft. base to top of brass cap marked:

T40S R25E
S17 | S16

S20 | S21
2004

A fence corner, projecting S and E bears N. 22° 56.9' E., 100.6 links distance.

From the corner of section 15, 16, 21 and 22.

S. 89° 58.0' W., between sections 16 and 21.

- 39.922** Point for the 1/4 section corner of sections 16 and 21, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
S16
1/4 -----
S21
2004

Raise a small mound of stone N of monument.

- 59.883** Point for the W 1/16 section corner of sections 16 and 21.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, and brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S R25E
S16
W1/16 —————
S21
2004

Raise a small mound of stone N of monument.

A fence corner, projecting S and W, bears N. 28° 02.8' E., 88.1 links distance.

79.844 The corner of sections 16, 17, 20 and 21.

N. 0° 24.2' W., between sections 16 and 17.

39.972 The 1/4 section corner of sections 16 and 17, monumented with a mound of stone.

At the corner point. (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 8 ft. base to top of brass cap marked:

T40S R25E
1/4
S17 | S16
2004

N. 0° 06.8' E., beginning new measurement.

39.965 The corner of sections 8, 9, 16 and 17, monumented with a sandstone, 16x11x3 inches, firmly set in a mound of stone, dimly marked 4 notches on 1 edge only.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
S8 | S9

S17 | S16
2004

Deposit marked stone alongside the monument.

From the corner of sections 9, 10, 15 and 16.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

N. 89° 58.4' W., between sections 9 and 16.

39.855

The 1/4 section corner of sections 9 and 16, monumented with a broken sandstone, 14x10x6 inches, in a mound of stone, dimly marked 1/4 on N face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
S9
1/4 ———
S16
2004

Deposit broken stone alongside the monument.

S. 89° 51.0' W., beginning new measurement.

40.122

The corner of sections 8, 9, 16 and 17.

N. 0° 17.4' E., between sections 8 and 9.

40.319

Point for the 1/4 section corner of sections 8 and 9, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
1/4
S8 | S9
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, W of monument.

80.638

The corner of sections 4, 5, 8 and 9, monumented with a sandstone, 16x10x6 inches loosely set, and a small mound of stone to the W, marks have been obliterated.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S	R25E
S5	S4

S8	S9
2004	

Deposit stone alongside the monument.

Monument is located 150 links S of a paved road, bears E and W.

From the corner of sections 3, 4, 9 and 10.

N. 89° 31.6' W., between sections 4 and 9.

40.048

The 1/4 section corner of sections 4 and 9, monumented with a broken sandstone, in a mound of stone, marks have been obliterated.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S	R25E
	S4
1/4	-----
	S9
2004	

Deposit broken stone alongside the monument.

N. 89° 36.9' W., beginning new measurement.

39.766

The corner of sections 4, 5, 8 and 9.

N. 0° 21.2' W., between sections 4 and 5.

39.620

Point for the 1/4 section corner of sections 4 and 5, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 8 ft. base to top of brass cap marked:

T40S	R25E
	1/4
S5	S4
2004	

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

79.260

The corner of sections 4, 5, 32 and 33, on the north boundary of township, hereinbefore described.

From the standard corner of sections 31 and 32, (Eight Standard Parallel South), on the south boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, with a brass cap marked as described in the official record of the 2004 dependent resurvey, of Township 41 South, Range 25 East.

N. 0° 25.9' E., between sections 31 and 32.

39.930

The 1/4 section corner of sections 31 and 32, monumented with a sandstone, 17x11x4 inches, firmly set and plainly marked 1/4 on W face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
1/4
S31 | S32
2004

Deposit marked stone alongside the monument.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of monument.

N. 0° 31.8' W., beginning new measurement.

39.827

The corner of sections 29, 30, 31 and 32, monumented with a sandstone, 20x10x4 inches, firmly set and plainly marked 1 notch on S and 5 notches on E edges.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
S30 | S29

S31 | S32
2004

Deposit marked stone alongside the monument.

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W of monument.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

From the corner of sections 28, 29, 32 and 33.

N. 89° 47.6' W., between sections 29 and 32.

40.037

The 1/4 section corner of sections 29 and 32, monumented with a sandstone, 22x11x5 inches, firmly set in a mound of stone, and plainly marked 1/4 on N face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground, with a magnet at base, and in a mound of stone, 6 ft. base to top of brass cap marked:

T40S R25E
S29
1/4 ———
S32
2004

Deposit marked stone alongside the monument.

S. 89° 50.8' W., beginning new measurement.

40.211

The corner of sections 29, 30, 31 and 32.

S. 89° 55.7' W., between sections 30 and 31.

39.864

The 1/4 section corner of sections 30 and 31, monumented with a broken sandstone, top portion is marked 1/4.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
S30
1/4 ———
S31
2004

Deposit broken stone alongside the monument.

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N of monument.

N. 89° 10.8' W., beginning new measurement.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

39.780 The corner of sections 25, 30, 31 and 36, on the W boundary of township, monumented with a stainless steel post, 2 1/2 inches diameter, with a brass cap marked as described in the official record of the 2003 dependent resurvey, of Township 40 South, Range 24 East.

From the corner of sections 29, 30, 31 and 32.

N. 0° 01.4' W., between sections 29 and 30.

40.069 Point for the 1/4 section corner of sections 29 and 30, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 6 ft. base to top of brass cap marked:

T40S R25E
1/4
S30 | S29
2004

80.138 True point for the corner of sections 19, 20, 29 and 30, at proportionate distance, falls in a wash that drains S, there is no remaining evidence of the original corner.

From the corner of sections 20, 21, 28 and 29.

N. 89° 52.3' W., between sections 20 and 29.

39.881 Point for the 1/4 section corner of sections 20 and 29, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 6 ft. base to top of brass cap marked:


T40S R25E
S20
1/4 ———
S29
2004

79.004 Point selected for the witness corner to the corner of sections 19, 20, 29 and 30.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with a magnet at base, and brass cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS




Raise a mound of stone, 4 ft. base, 2 ft. high, N of monument.

79.762 The true point for the corner of sections 19, 20, 29 and 30.

S. 89° 32.4' W., between sections 19 and 30.

39.912 Point for the 1/4 section corner of sections 19 and 30, at proportionate distance, there is no remaining evidence of the original corner, point falls on a solid sandstone ledge.

Set a brass tablet 3 1/4 inch diameter, with a 3 1/2 stem, flush with sandstone, in cement bound, into a drill hole on solid rock marked:



Monument is located at base of a 10 ft. ledge.

79.694 The corner of sections 19, 24, 25 and 30, on the W boundary of township, monumented with a stainless steel post, 2 1/2 inches diameter with a brass cap marked as described in the official record of the 2003 dependent resurvey, of Township 40 South, Range 24 East.


From the true point for the corner of sections 19, 20, 29 and 30.

N. 0° 06.0' E., between sections 19 and 20.

40.069 The 1/4 section corner of sections 19 and 20, monumented with a sandstone, 14x10x8 inches, firmly set and plainly marked 1/4 on W face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:



**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Deposit marked stone alongside the monument.

Raise a small mound of stone, W of monument.

Monument is located on top of a spur bearing E, in a faint trail road.

N. 0° 15.8' W., beginning new measurement.

40.013

The corner of sections 17, 18, 19 and 20, monumented with a sandstone, 10x10x9 inches, firmly set in a mound of stone, and plainly marked 3 notches on E edge, other marks have been obliterated.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, and brass cap marked:

T40S	R25E
S18	S17
S19	S20
2004	

Deposit marked stone alongside the monument.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of monument.

From the corner of sections 16, 17, 20 and 21.

N. 89° 46.2' W., between sections 17 and 20.

39.902

Point for the 1/4 section corner of sections 17 and 20, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S	R25E
	S17
1/4	S20
2004	

Raise a mound of stone, 4 ft. base, 3 ft. high, N of monument.

79.804

The corner of sections 17, 18, 19 and 20.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

S. 89° 55.6' W., between sections 18 and 19.

- 39.902** The 1/4 section corner of sections 18 and 19, monumented with a sandstone, 16x7x7 inches, set on solid rock and in a mound of stone, plainly marked 1/4 on N face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, on solid rock, in a mound of stone, 8 ft. base to top of brass cap marked:

T40S R25E
S18
1/4 ———
S19
2004

Deposit marked stone in mound of stone alongside the monument.

S. 87° 07.2' W., beginning new measurement.

- 39.366** The corner of sections 13, 18, 19 and 24, on the W boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, with a brass cap marked as described in the official record of the 2003 dependent resurvey, of Township 40 South, Range 24 East.

From the corner of sections 17, 18, 19 and 20.

N. 0° 14.0' E., between sections 17 and 18.

- 40.154** The 1/4 section corner of sections 17 and 18, monumented with a sandstone, 22x10x7 inches, firmly set in a mound of stone, and plainly marked 1/4 on W face.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground, with a magnet at base, and in a mound of stone, 3 ft. base to top of brass cap marked:

T40S R25E
1/4
S18 | S17
2004

Deposit marked stone alongside the monument.

N. 0° 05.7' W., beginning new measurement.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

39.985

The corner of sections 7, 8, 17, and 18, monumented with a sandstone, 18x7x6 inches, firmly set in a mound of stone, and plainly marked 4 notches on S and 5 notches on E edges.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 4 ft. base to top of brass cap marked:

T40S	R25E
S7	S8
S18	S17
2004	

Deposit marked stone alongside the monument.

From the corner of sections 8, 9, 16 and 17.

N. 89° 37.4' W., between sections 8 and 17.

39.745

Point for the 1/4 section corner of sections 8 and 17, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 6 ft. base to top of brass cap marked:

T40S	R25E
	S8
1/4	
	S17
2004	

79.490

The corner of sections 7, 8, 17 and 18.

N. 89° 56.7' W., between sections 7 and 18.

39.616

Point for the 1/4 section corner of sections 7 and 18, at proportionate distance, there is no remaining evidence of the original corner.

Set a brass tablet 3 1/4 inch diameter, with a 3 1/2 inch stem, flush with sandstone, in cement bound, into a drill hole on solid rock, marked:

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S	R25E
	S7
1/4	_____
	S18
	2004

Raise a mound of stone, 3 ft. base, 2 ft. high, N of monument.

78.895

The corner of sections 7, 12, 13 and 18, on the W boundary of township, monumented with a stainless steel post, 2 1/2 inches diameter, with brass cap marked as described in the official record of the 2003 dependent resurvey, of Township 40 South, Range 24 East.

From the corner of sections 7, 8, 17 and 18.

N. 0° 11.8' W., between sections 7 and 8.

39.897

The 1/4 section corner of sections 7 and 8, monumented with a mound of stone.

At the corner point. (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, in a collar of stone, and brass cap marked:

T40S	R25E
	1/4
S7	S8
	2004

N. 0° 10.4' W., beginning new measurement.

39.885

The corner of sections 5, 6, 7 and 8, monumented with a sandstone, 16x10x4 inches, loosely set and plainly marked 5 notches on the S and E edges.

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S	R25E
S6	S5

S7	S8
	2004

Deposit marked stone alongside the monument.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

From the corner of sections 4, 5, 8 and 9.

S. 89° 28.4' W., between sections 5 and 8.

40.603

The 1/4 section corner of sections 5 and 8, monumented with a mound of stone.

At the corner point. (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
S5
1/4 ———
S8
2004

N. 89° 56.5' W., beginning new measurement.

39.537

The corner of sections 5, 6, 7 and 8.

S. 89° 52.0' W., between sections 6 and 7.

39.970

Point for the 1/4 section corner of sections 6 and 7, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
S6
1/4 ———
S7
2004

79.491

The corner of sections 1, 6, 7 and 12, on the W boundary of township, monumented with a stainless steel post, 2 1/2 inches diameter, with a brass cap marked as described in the official record of the 2003 dependent resurvey, of Township 40 South, Range 24 East.

From the corner of sections 5, 6, 7 and 8.

N. 0° 22.6' W., between sections 5 and 6.

40.208

The 1/4 section corner of sections 5 and 6, monumented with a sandstone, 22x10x4 inches, firmly set and dimly marked 1/4 on W face.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

At the corner point.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
1/4
S6 | S5
2004

Deposit marked stone alongside the monument.

Raise a small mound of stone, W of monument.

N. 0° 04.7' E., beginning new measurement.

- 39.388** The corner of sections 5, 6, 31 and 32, on the N boundary of township, hereinbefore described.

The Subdivision of Section 3
T. 40 S., R. 25 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 3 and 10.

N. 0° 11.1' W., on the N-S center line of section 3.

- 19.918** Point for the center S 1/16 section corner of section 3, not mounumented.

- 39.836** Point for the center 1/4 section corner of section 3, at intersection with the E-W center line.

Set a brass tablet, 3 1/4 inch diameter, with a 3 1/2 inch stem, flush with sandstone, in cement bound, into a drill hole on solid rock marked:

T40S R25E
C 1/4
S3
2004

Raise a mound of stone, 4 ft. base, 3 ft. high, W of monument.

Monumented is located in the W track of a trail road, bears N and S.

- 59.993** Point for the center N 1/16 section corner of section 3.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

**THE SUBDIVISION OF SECTION 3
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S R25E
C
N1/16 | S3
C
2004

Raise a mound of stone, 6 ft. base, 3 ft. high, W of monument.

Monument is located on steep E slope among large boulders.

- 80.175** The 1/4 section corner of sections 3 and 34, on the N boundary of township, hereinbefore described.

From the 1/4 section corner of sections 2 and 3.

S. 89° 49.9' W., on the E-W center line of section 3.

- 19.933** Point for the center E 1/16 section corner of section 3.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
E1/16
C——C
S3
2004

Raise a mound of stone, 6 ft. base, 4 ft. high, W of monument.

Monument is location on a steep E slope among large boulders.

- 39.866** The center 1/4 section corner of section 3.

- 79.926** The 1/4 section corner of sections 3 and 4.

From the center E 1/16 section corner of section 3.

N. 0° 02.5' E., on the N-S center line of the NE 1/4 of section 3.

- 20.090** Point for the NE 1/16 section corner of section 3, at intersection with the E-W center line of the NE 1/4.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 8 ft. base to top of brass cap marked:

**THE SUBDIVISION OF SECTION 3
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S R25E
NE 1/16
S3
2004

Monument is located in bottom of small canyon, drains W.

- 40.207** The point for the E 1/16 section corner of sections 3 and 34, on the N boundary of township, hereinbefore described.
-

From the point for the N 1/16 section corner of sections 2 and 3.

N. 89° 58.6' W., on the E-W center line of the NE 1/4 of section 3.

- 20.011** The NE 1/16 section corner of section 3.

- 40.022** The center N 1/16 section corner of section 3.
-

From the point for the E 1/16 section corner of sections 3 and 10.

N. 0° 18.7' W., on the N-S center line of the SE 1/4 of section 3.

- 19.957** Point for the SE 1/16 section corner of section 3, at intersection with the E-W center line of the SE 1/4.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
SE 1/16
S3
2004

Monument is located in a sagebrush flat.

- 39.914** The center E 1/16 section corner of section 3.
-

From the S 1/16 section corner of sections 2 and 3.

S. 89° 56.6' W., on the E-W center line of the SE 1/4 of section 3.

- 19.979** The SE 1/16 section corner of section 3.

- 39.958** The point for the center S 1/16 section corner of section 3.

**THE SUBDIVISION OF SECTION 10
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

The Subdivision of Section 10
T 40 S., R. 25 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 10 and 15.

N. 0° 08.4' E., on the N-S center line of section 10.

39.979 Point for the center 1/4 section corner of section 10, at intersection with the E-W center line.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
C 1/4
S10
2004

Monument is located at the point of a spur sloping W and at the confluence of 2 washes, draining westerly.

79.958 The 1/4 section corner of sections 3 and 10.

From the 1/4 section corner of sections 10 and 11.

N. 89° 56.5' W., on the E-W center line of section 10.

40.084 The center 1/4 section corner of section 10.

80.168 The 1/4 section corner of sections 9 and 10.

The Subdivision of Section 15
T 40 S., R. 25 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 15 and 22.

N. 0° 02.0' E., on the N-S center line of section 15.

39.964 Point for the center 1/4 section corner of section 15 at intersection with the E-W center line

Set a brass tablet, 3 1/4 inch diameter, with a 3 1/2 inch stem, flush with sandstone, in cement bound, into a drill hole on solid rock marked:

T40S R25E
C 1/4
S15
2004

**THE SUBDIVISION OF SECTION 15
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Raise a mound of stone, 4 ft. base, 3 ft. high, W of monument.
Monument is located on a ledge.

79.926 The 1/4 section corner of sections 10 and 15.

From the 1/4 section corner of sections 14 and 15.

S. 89° 56.5' W., on the E-W center line of section 15.

19.947 Point for the center E 1/16 section corner of section 15.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, on solid rock, in a mound of stone, 8 ft. base to top of brass cap marked:

T40S R25E
E 1/16
C ————— C
S15
2004

39.894 The center 1/4 section corner of section 15.

59.773 Point for the center W 1/16 section corner of section 15.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

T40S R25E
W 1/16
C ————— C
S15
2004

Monument is located in flat sandy soil.

79.652 The 1/4 section corner of sections 15 and 16.

From the center E 1/16 section corner of section 15.

N. 0° 11.9' E., on the N-S center line of the NE 1/4 of section 15.

39.920 The E 1/16 section corner of sections 10 and 15.

From the center W 1/16 section corner of section 15.

N. 0° 13.7' W., on the N-S center line of the NW 1/4 of section 15.

THE SUBDIVISION OF SECTION 15
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS
40.004

The W 1/16 section corner of sections 10 and 15.

The Subdivision of Section 21
T 40 S., R. 25 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 21 and 28.

N. 0° 06.4' W., on the N-S center line of section 21.

39.992 Point for the center 1/4 section corner of section 21, at intersection with the E-W center line.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 6 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 8 ft. base to top of brass cap marked:

T40S R25E
C 1/4
S21
2004

59.956 Point for the center N 1/16 section corner of section 21, not monumented.

79.920 The 1/4 section corner of sections 16 and 21.

From the 1/4 section corner of sections 21 and 22.

S. 89° 54.4' W., on the E-W center line of section 21.

40.000 The center 1/4 section corner of section 21.

59.986 Point for the center W 1/16 section corner of section 21, not monumented.

79.972 The 1/4 section corner of sections 20 and 21.

From the point for the center W 1/16 section corner of section 21.

N. 0° 04.4' W., on the N-S center line of the NW 1/4 of section 21.

19.975 Point for the NW 1/16 section corner of section 21, at intersection with the E-W center line of the NW 1/4.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and brass cap marked:

**THE SUBDIVISION OF SECTION 21
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

T40S R25E
NW 1/16
S21
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, W of monument.

Monument is located 41 links S of the center line of a dirt road, bears E and W.

A fence corner projecting N and W, bears N. 18° 36.1' E., 81.5 links distance.

39.950 The W 1/16 section corner of sections 16 and 21.

From the point for the center N 1/16 section corner of section 21.

S. 89° 56.2' W., on the E-W center line of the NW 1/4 of section 21.

19.973 The NW 1/16 section corner of section 21.

39.946 The N 1/16 section corner of sections 20 and 21.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Glen B. Hatch Matthew Peck	Cadastral Surveyor Survey Aide

CERTIFICATE OF SURVEY

I **M. Ross Workman, Cadastral Surveyor**, hereby certify upon honor, that in pursuance of special instructions bearing the date of the **28th day of January, 2004**, I have **dependently resurveyed the east boundary, the north boundary, and the subdivisional lines, and subdivided sections 3, 10, 15 and 21 in Township 40 South, Range 25 East,**

of the **Salt Lake** Meridian, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special and supplemental special instructions, the Manual of Instructions of the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

2-10-05

Date

M. Ross Workman
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The following field notes of the **dependent resurvey of the east boundary, the north boundary, and the subdivisional lines, and the subdivision of sections 3, 10, 15 and 21 in Township 40 South, Range 25 East, Salt Lake Meridian, Utah,**

executed by **M. Ross Workman, Cadastral Surveyor** having been critically examined and found correct, are hereby approved.

February 11, 2005
Date

Daniel W. Webb
Chief Cadastral Surveyor of Utah