

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF
PORTIONS OF THE BASE LINE THROUGH RANGE 2 EAST,
WEST BOUNDARY,
SUBDIVISIONAL LINES,
SECTION SUBDIVISIONAL LINES,
AND THE SURVEY OF THE SUBDIVISION OF CERTAIN SECTIONS,

IN

TOWNSHIP 1 NORTH, RANGE 2 EAST
OF THE UINTAH SPECIAL MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

David W. Ginther
Cadastral Surveyor

Under Special Instructions dated **April 30, 2004**, approved **April 30, 2004**, which provided for the surveys included under group number **974**, and assignment instructions dated **April 30, 2004**.

Survey commenced **May 25, 2004**

Survey completed **July 22, 2004**

INDEX DIAGRAM

Township 1 North, Range 2 East

6 30	5	4	3	2	1
11 7	8	9	10	11	12
10 18 29 28	17 17 27	16	15	14	13
8 19 25 24	20 15 23	21	22	23	24
7 30 21 20	29 14 19	28	27	26	25
31 18 6	32 12 3	33	34	35	36

Dependent Resurvey of a Portion of the subdivision of Section 7	Page 30
Dependent Resurvey of a Portion of the subdivision of Section 8	Page 31
The Subdivision of Section 7.....	Page 32
The Subdivision of Section 17.....	Page 33
The Subdivision of Section 19.....	Page 39
The Subdivision of Section 20.....	Page 41
The Subdivision of Section 29.....	Page 44
The Subdivision of Section 30.....	Page 48
The Subdivision of Section 31.....	Page 50
The Subdivision of Section 32.....	Page 53

**TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

The following field notes describe the dependent resurvey of portions of the base line through Range 2 East, west boundary, subdivisional lines, section subdivisional lines, and the survey of the subdivision of certain sections, of Township 1 North, Range 2 East, Uintah Special Meridian, Utah.

History of Surveys

Surveyed by			Retr. or Resurvey by	
SOUTH BOUNDARY (Uintah Special Base Line)				
All	J.H. Martineau	1903		
EAST BOUNDARY (Uintah Indian Reservation Boundary)				
All	C.L. DuBois	1875		
ALL			A.H.&F.M. Brown	1903
Portion			S.P.&J.R. Stewart	1906
Portion			R.A. Zaninovich	1990
WEST BOUNDARY				
Portion	C.L. DuBois	1875		
All	J.H. Marineau	1904	J.H. Marineau	1904
Portion			R.A. Zaninovich	1990
NORTH BOUNDARY				
All	J.H. Martineau	1904		
All			R.A. Zaninovich	1990
SUBDIVISION				
All	J.H. Martineau	1904		
Portion			R.A. Zaninovich	1990

**TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

The survey was executed in accordance with the specifications as set forth in the **Manual of Instructions for the Survey of the Public Lands of the United States, 1973**, and the Special Instructions for Group No. 974, Utah, dated April 30, 2004.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 4800 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a diligent search was made for any evidence of the original survey record, as well as pertinent evidence of previously established local surveys. Identified corners were remonumented in their original positions. Lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) Red Butte, Carbon County, and Myton 1.

The geographic positions, in NAD83 (CORS96), epoch date 2002.00, for the corners listed below were determined by Global Positioning System (GPS) observations to a Network Accuracy of less than 0.10 meters, 95 percent confidence circle, as defined in Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods, May 9, 2001, Version 1.0.

The standard corner of sections 31 and 32:

Latitude: 40°25'57.889" N. Longitude: 109°48'09.828" W.
N.A.D. 1983, N.A.V.D. 1988 Elevation 5770 Ft.

The corner of sections 7, 12, 13, and 18, on the West boundary of the Township:

Latitude: 40°29'28.052" N. Longitude: 109°49'17.560" W.
N.A.D. 1983, N.A.V.D. 1988 Elevation 6468 Ft.

The 1/4 section corner of sections 6 and 7:

Latitude: 40°30'20.261" N. Longitude: 109°48'43.787" W.
N.A.D. 1983, N.A.V.D. 1988 Elevation 6514 Ft.

**TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

The corner of sections 19, 20, 29, and 30:

Latitude: 40°27'42.352" N. Longitude: 109°48'09.864" W.
N.A.D. 1983, N.A.V.D. 1988 Elevation 5803 Ft.

The corner of sections 17, 18, 19, and 20:

Latitude: 40°28'35.237" N. Longitude: 109°48'10.139" W.
N.A.D. 1983, N.A.V.D. 1988 Elevation 6300 Ft.

The corner of sections 20, 21, 28, and 29:

Latitude: 40°27'42.921" N. Longitude: 109°47'01.837" W.
N.A.D. 1983, N.A.V.D. 1988 Elevation 6154 Ft.

The 1/4 section corner of sections 16 and 17:

Latitude: 40°29'01.266" N. Longitude: 109°47'01.941" W.
N.A.D. 1983, N.A.V.D. 1988 Elevation 6289 Ft.

**DEPENDENT RESURVEY OF A PORTION OF THE BASE LINE,
THROUGH RANGE 2 EAST, (SOUTH BOUNDARY),
TOWNSHIP 1 NORTH, RANGE 2 EAST, UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Reestablishment of the Survey Executed by
J.H. Martineau, in 1903

Beginning at the standard corner of sections 32, and 33, monumented with a sandstone, 16x8x4 inches, firmly set, projecting 14 inches above the ground, clearly marked SC on the West face, 4 grooves on the North face, and 2 grooves on the South face, improperly oriented, and encircled with a collar of stone, 2 ½ foot base, 6 inches high.

At the corner point

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 21 inches in the ground, with cap marked:

**DEPENDENT RESURVEY OF A PORTION OF THE BASE LINE,
THROUGH RANGE 2 EAST, (SOUTH BOUNDARY),
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

SC
T 1 N R 2 E
S 32 | S 33

2004

Bury the original marked stone alongside the aluminum post.

Deposit a DEEP-1 magnet at the base of the monument.

Raise a mound of stone, 2 ½ foot base, 12 inches high, to the North of the corner.

Corner is located on near level ground, North, 7 links distance from a woven wire fence, extending East and West.

From this point the closing corner of sections 4 and 5 of Township 1 South, Range 2 East bears S. 38°04.0' W., 9.9 links distance, monumented with a sandstone, 9x4 inches exposed, firmly set, projecting 12 inches above the ground, marked CC on the North face, 4 grooves on the West face, and 2 grooves on the East face, improperly oriented.

From this same point, a rebar, ½ inch diameter, firmly set, projecting 1 inch and in a stone mound, 2 foot base, 6 inches high, with no cap or marks bears S. 30°55.5' W., 12.4 links distance.

S. 89°45.9' W., on the Base Line, (South Boundary of Section 32).

19.912 The point for the standard East 1/16 section corner of section 32.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 22 inches in the ground, with cap marked:

SC
T 1 N R 2 E
E 1/16 S 32

2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside.

Corner is located on near level ground among greasewood.

39.824 The standard ¼ section corner of section 32, monumented with a rebar, ½ inch diameter, 18 inches long, firmly set, projecting 1 inch above the ground, with no cap or marks, established by

**DEPENDENT RESURVEY OF A PORTION OF THE BASE LINE,
THROUGH RANGE 2 EAST, (SOUTH BOUNDARY),
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

person(s) unknown, with a steel T fence post alongside, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 21 inches in the ground, encircle with a collar of stone, 2 ½ foot base, to the top, with cap marked:

SC
T 1 N R 2 E
1/4 S 32

2004

Bury the ½ inch rebar inside the aluminum post.

Deposit a Deep-1 magnet at the base of the aluminum post.

Raise a mound of stone 2 ½ foot base, 18 inches high, to the North of the corner.

Corner is located on a rocky and steep southeast facing slope, among scattering juniper timber.

N. 89°56.0' W., beginning new measurement.

39.764

The standard corner of sections 31 and 32, monumented with a sandstone, 18x10x7 inches, firmly set, projecting 14 inches above the ground, clearly marked SC on the north face, 5 notches on the east edge, and 1 notch on the west edge, with a mound of stone, 4 foot base, 14 inches high, to the north of the corner.

At the corner point

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 19 inches in the ground, encircle with a collar of stone, 3 foot base, to the top, with cap marked:

SC
T 1 N R 2 E
S 31 | S 32

2004

Bury the original marked stone alongside the aluminum post.

Deposit Deep-1 magnet at the base of the aluminum post.

**DEPENDENT RESURVEY OF A PORTION OF THE BASE LINE,
THROUGH RANGE 2 EAST, (SOUTH BOUNDARY),
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Rehabilitate mound of stone, 4 foot base, 2 foot high, to the north of the corner.

Set a steel T fence post alongside the corner.

Corner is located on a rocky west facing slope, East, 6.14 chains distance from the center of a canal, 33 links wide, course S. 12° E., and among juniper timber.

From this point the closing corner of sections 5 and 6 of Township 1 South, Range 2 East bears S. 85°22.2' W., 38.9 links distance, monumented with a sandstone, 16x8x6 inches, firmly set, projecting 10 inches above the ground, marked 5 grooves on the east face, and 1 groove on the west face, with a scattered mound of stone, 3 foot base, 16 inches high, to the South of the corner, and with a steel T fence post lying loose on the ground alongside.

N. 89°58.2' W., on the Base Line, (South Boundary of Section 31).

19.856

The point for the standard East 1/16 section corner of section 31.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 20 inches in the ground, encircle with a collar of stone, 2 ½ foot base, to top, with cap marked:

SC
T 1 N R 2 E
E 1/16 S 31

2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Raise a mound of stone, 3 foot base, 18 inches high, to the north of the corner.

Set a steel T fence post alongside.

Corner is located on near level ground, among juniper timber.

39.712

The point for the standard ¼ section corner of section 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, encircle with a collar of stone, 2 foot base, to top, with cap marked:

**DEPENDENT RESURVEY OF A PORTION OF THE BASE LINE,
THROUGH RANGE 2 EAST, (SOUTH BOUNDARY),
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

SC
T 1 N R 2 E
1/4 S 31

2004

from which

A brass washer, 1 ½ inch diameter, marked BLM CADASTRAL SURVEY, attached to a wood fence post, bears N. 16° E., 13.3 links distance.

A brass washer, 1 ½ inch diameter, marked BLM CADASTRAL SURVEY, attached to a wood fence post, bears S. 18° E., 36.9 links distance.

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside.

Corner is located on near level ground, North, 8.3 links distance, from the northern edge of the county road, asphalt surface, extending east and west.

79.424

The standard corner of Townships 1 North, Ranges 1 and 2 East, monumented with a rebar, 5/8 inch diameter, firmly set, projecting 6 inches above the ground, with no cap or marks, established by person(s) unknown, with a weathered red sandstone, 12x9x4 inches, with no legible marks, lying loose alongside. This monument is accepted as a good faith perpetuation of the original corner.

Not remonumented

Corner is located on near level ground, in a wire fence, extending north and south.

**Dependent Resurvey of a Portion of the West Boundary,
Township 1 North, Range 2 East,
Uintah Special Meridian, Utah**

Restoring the survey executed by C.L. DuBois in 1875,
and the retracement executed by J. H. Martineau, in 1904

From the corner of sections 25, 30, 31, and 36, on the west boundary of the township, monumented with a steel bar, 5/8 inch diameter, firmly set, 6 inches under the surface of an asphalt surfaced county road, with no cap or marks, reestablished by John T. Kay, Utah Registered Land Surveyor, R.L.S. No. 18319.

**DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Despite seemingly incompatible and vague private survey information regarding the location of this particular corner, it is accepted as the best available evidence of the original corner location.

from which

A USGS bench mark, monumented with a brass tablet, 3 ½ inches diameter, set in rectangular concrete slab, 6x6 inches, bears S. 20°02.0' W., 0.478 chains distance, with top marked: 35 EAM 1963 ELEVATION ABOVE SEA 5667 FEET

from which

A local reference, a nail in a three way fence corner post, bears S. 40°30.9' E., 0.605 chains distance, with fences extending East, S. 4° E., and West.

N. 0°11.5' E., between sections 25 and 30, on the West boundary of township.

40.082 Point for the ¼ section corner of sections 25 and 30, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

From this point, a rebar 5/8 inch diameter, firmly set, projecting 7 inches above the ground, with 1 ¼ inch aluminum cap, marked UINTAH COUNTY SURVEY, bears N. 79°39.3' E., 0.674 chains distance, and was not utilized during the course of this survey.

80.164 The corner of sections 19, 24, 25, and 30, on the West boundary of the township, perpetuated by a rebar, 5/8 inch diameter, firmly set, flush with the surface of the ground, with a plastic cap, 1 ¼ inches diameter, marked RMS UT PLS 161259, and with the original stone, a sandstone, 17x12x4 inches, marked 4 grooves on one face and 2 grooves on another face, lying loose alongside. Not remonumented.

Corner is located on near level ground, at the corner of barbed wire fences, extending South and West, and adjacent to a stack of milled timbers.

Restoring the survey executed by
J.H. Martineau, in 1904

From the ¼ section corner of sections 19 and 24, on the West boundary of the township, monumented with a galvanized steel post, 2 ½ inches diameter, firmly set, projecting 13 inches above the ground, with cap marked:

**DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

1963
|
S24 1/4 S19
|
T1NR1E T1NR2E

This monument was established by person(s) unknown, is utilized by adjacent landowners to facilitate the orderly settlement in this area, and is accepted as the best available evidence of the original corner position.

Corner is located at the corner of barbed wire fences, extending N. 10° E. and S. 84° W., and South, 1.63 chains distance, from the center of a canal, 23 links wide, course S. 88° E.

N. 0°12.1' W., between sections 19 and 24, on the west boundary of the township.

19.863

The N 1/16 section corner of sections 19 and 24, on the west boundary of the township, monumented with a galvanized steel post, 2 1/2 inches diameter, firmly set, projecting 17 inches above the ground, and with cap marked:

1963
S24 N1/16 S19
T1NR1E | T1NR2E

This monument was established by person(s) unknown, is utilized by adjacent landowners to facilitate the orderly settlement in this area, and is accepted as the corner position.

No further monumentation was deemed necessary.

Corner is located on a steep, eroded South facing slope, at the end of a barbed wire fence, extending South.

N. 0°11.2' W., beginning new measurement.

19.338

The corner of sections 13, 18, 19, and 24, on the west boundary of the township, monumented with a sandstone, 19x8x8 inches, firmly set, projecting 15 inches above the ground, clearly marked 3 grooves on the north face, 3 grooves on the south face, with a scattered mound of stone, 2 ft. base, 8 inches high, to the west of the corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 19 inches in the ground, encircle with a collar of stone, 3 foot base, to the top, with cap marked:

**DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

	T 1 N	
R 1 E		R 2 E
S 13		S 18
S 24		S 19
2004		

Bury the original marked stone alongside the aluminum post.

Deposit a Deep-1 magnet at the base of the aluminum post.

Rehabilitate the mound of stone to the west, 3 foot base, 2 foot high.

Corner is located on a near level bench area of a spur ridge, among juniper timber, and at the corner of barbed wire fences, extending North and West.

N. 0°14.9' W., between sections 13 and 18, on the west boundary of the township.

40.760

Point for the ¼ section corner of sections 13 and 18, on the west boundary of the township, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 20 inches in the ground, encircle with a collar of stone, 3 foot base, to the top, with cap marked:

	T 1 N	
	1/4	
R 1 E		R 2 E
S 13		S 18
2004		

Corner is located on a rocky and steep south facing slope, in a barbed wire fence, extending North and South, among juniper timber.

81.520

The corner of sections 7, 12, 13, and 18, on the west boundary of the township, monumented with aluminum post, 2 ½ inches diameter, firmly set, projecting 8 inches above the ground, with a mound of stone, 3 foot base, 12 inches high, to the west of the corner, and with cap marked: as described in the official record of the 1990 Dependent Resurvey of a Portion of the West Boundary of Township 1 North Range 2 East.

**DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Corner is located on near level ground, in a barbed wire fence, extending North and South, among sagebrush and scattering juniper timber.

Restoring the Survey Executed by J.H. Martineau in 1904,
and the Dependent Resurvey, Executed by
Richard Zaninovich, in 1990

From the $\frac{1}{4}$ section corner of sections 7 and 12, on the west boundary of the township, monumented with an aluminum post, 2 $\frac{1}{2}$ inches diameter, firmly set, projecting 8 inches above the ground, with a mound of stone, 3 foot base, 14 inches high, to the west of the corner, and with cap marked: as described in the official record of the 1990 Dependent Resurvey of a Portion of the West Boundary of Township 1 North Range 2 East.

Corner is located on near level ground, in a barbed wire fence, extending North and South, among sagebrush.

N. $0^{\circ}02.5'$ E., between sections 7 and 12, on the west boundary of the township.

19.990

Point for the North $\frac{1}{16}$ section corner of sections 7 and 12, on the west boundary of the township.

Set an aluminum post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 22 inches in the ground, encircle with a collar of stone, 2 foot base, to the top, with cap marked:

T1N
R1E R2E
N $\frac{1}{16}$
S 12 | S 7
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Raise a mound of stone, 2 $\frac{1}{2}$ foot base, 14 inches high, to the west of the corner.

Corner is located on near level ground, in a barbed wire fence, extending North and South, and West, 13 $\frac{1}{2}$ links distance, from the center of a trail road, 15 links wide, also extending North and South.

39.980

The corner of sections 1, 6, 7, and 12, on the west boundary of the township, monumented with an aluminum post, 2 $\frac{1}{2}$ inches diameter, firmly set, projecting 8 inches above the ground, encircled with a collar of stone, 2 $\frac{1}{2}$ foot base, to top, with cap marked: as described in the official record of the 1990

**DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Dependent Resurvey of a Portion of the West Boundary of
Township 1 North Range 2 East.

Corner is located on near level ground, in a barbed wire fence,
extending North and South, among sagebrush and juniper timber.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
Township 1 North, Range 2 East, Uintah Special Meridian, Utah**

Restoring the survey executed by
J. H. Martineau, in 1904

From the standard corner of sections 32 and 33, on the Base Line
(South boundary of the township), hereinbefore described.

N. 0°02.3' W., between sections 32 and 33.

20.017 Point for the South 1/16 section corner of sections 32 and 33,
falls on the erosive slope of a draw, where it is not practical
to establish a durable permanent monument.

20.312 Point selected for the witness South 1/16 section corner of
sections 32 and 33.

Set an aluminum post, 30 inches long, 2 ¼ inches diameter,
20 inches in the ground, encircle with a collar of stone, 3 foot
base, to the top, with cap marked:

WC
T 1 N R 2 E
S 1/16
S 32 ↓ S 33
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the corner.

Witness Corner is located in a draw, North, 30 links distance
from the bottom of the draw, course S. 44° W., among scattering
juniper timber.

40.034 The ¼ section corner of sections 32 and 33, monumented with a
sandstone, 20x10x6 inches, firmly set, projecting 16 inches
above the ground, clearly marked 1/4 on the west face.

At the corner point

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 22 inches in the ground, encircle with a collar of stone, 2 ½ foot base, to the top, with cap marked:

T 1 N R 2 E
1/4
S 32 | S 33
2004

Bury the original marked stone alongside the aluminum post.

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the corner.

Corner is located at the corner of barbed wire fences, extending North and East, and on the north facing slope of a draw, among juniper timber.

N. 0°07.4' E., beginning new measurement.

20.154

The North 1/16 section corner of sections 32 and 33, monumented with a rebar, ½ inch diameter, firmly set, projecting 9 inches above the ground, with no cap or marks, established by person(s) unknown, with a steel T fence post set alongside, and is accepted as a faithful determination of the corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 24 inches in the ground, encircle with a collar of stone, 2 ½ foot base, to the top, with cap marked:

T 1 N R 2 E
N 1/16
S 32 | S 33
2004

Bury the ½ inch rebar inside the aluminum post.

Deposit a Deep-1 magnet at the base of the aluminum post.

Corner is located on near level ground, North, 18 ½ links distance, from a two way fence corner, extending South and West, among sagebrush.

N. 0°02.9' W., beginning new measurement.

20.145

The corner of sections 28, 29, 32, and 33, monumented with a sandstone, 15x8x6 inches, firmly set, projecting 10 inches above

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

the ground, clearly marked 4 grooves on the east face, 1 groove on the south face, encircled with a collar of stone, 2 ½ foot base, 8 inches high.

At the corner point

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 19 inches in the ground, encircle with a collar of stone, 2 ½ foot base, to the top, with cap marked:

T 1 N R 2 E	
S 29	S 28
S 32	S 33
2004	

Bury the original marked stone alongside the aluminum post.

Deposit a Deep-1 magnet at the base of the aluminum post.

Corner is located on a very gentle east slope, among juniper timber.

N. 0°12.7' E., between sections 28 and 29.

19.968 Point for the South 1/16 section corner of sections 28 and 29, not monumented.

39.936 The ¼ section corner of sections 28 and 29, monumented with a sandstone, 12x8x6 inches, firmly set, projecting 8 inches above the ground, clearly marked 1/4 on west face, with an embedded mound of stone, 2 ½ foot base, 6 inches high, to the east.

At the corner point

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 22 inches in the ground, with cap marked:

T 1 N R 2 E	
1/4	
S 29	S 28
2004	

Bury the original marked stone alongside the aluminum post.

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the corner.

Corner is located on a gentle southeast facing slope, among juniper timber.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

N. 0°17.8' E., beginning new measurement.

20.353 Point for the North 1/16 section corner of sections 28 and 29.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 24 inches in the ground, encircle with a collar of stone, 2 foot base, to the top, with cap marked:

T 1 N	R 2 E
N 1/16	
S 29	S 28
2004	

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the corner.

Corner is located on near level ground, at the eastern edge of a large alfalfa field, and East, 3 links distance from a barbed wire fence, extending North and South.

40.706 The corner of sections 20, 21, 28, and 29, monumented with a sandstone, 14x8x8 inches, firmly set, projecting 7 inches above the ground, encircled with a collar of stone, 2 ½ foot base, 5 inches high, marked 4 grooves on the east face, and 2 grooves on the south face.

At the corner point

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 20 inches in the ground, encircle with a collar of stone, 2 ½ foot base, to the top, with cap marked:

T 1 N	R 2 E
S 20	S 21
S 29	S 28
2004	

Bury the original marked stone alongside the aluminum post.

Deposit a Deep-1 magnet at the base of the aluminum post.

Corner is located on near level ground, East, 12 links distance from a barbed wire fence, extending North and South, and near the eastern edge of a large irrigated alfalfa field.

N. 0°11.0' W., between sections 20 and 21.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

40.039 The $\frac{1}{4}$ section corner of sections 20 and 21, monumented with a sandstone, 12x8x6 inches, firmly set, projecting 5 inches above the ground, faintly marked $\frac{1}{4}$ on the west face, and in an embedded collar of stone, 2 foot base, 3 inches high.

At the corner point

Set an aluminum post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 22 inches in the ground, encircle with a collar of stone, 2 $\frac{1}{2}$ foot base, to the top, with cap marked:

T 1 N	R 2 E
1/4	
S 20	S 21
2004	

Bury the original marked stone alongside the aluminum post.

Deposit a Deep-1 magnet at the base of the aluminum post.

Corner is located on near level ground, South, 1.07 chains distance, from the center of an irrigation ditch, 6 links wide, course N. 76° E., among sagebrush.

N. 0°05.3' W., beginning new measurement.

20.033 Point for the North 1/16 section corner of sections 20 and 21, not monumented.

40.066 The corner of sections 16, 17, 20, and 21, monumented with a sandstone, 16x9x7 inches, firmly set, projecting 9 inches above the ground, marked 4 grooves on the east face, 3 grooves on the south face, and encircled with an embedded collar of stone, 2 foot base, 6 inches high.

At the corner point

Set an aluminum post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 20 inches in the ground, encircle with a collar of stone, 3 foot base, to the top, with cap marked:

T 1 N	R 2 E
S 17	S 16
S 20	S 21
2004	

Bury the original marked stone alongside the aluminum post.

Deposit a Deep-1 magnet at the base of the aluminum post.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Corner is located on near level ground, in a barbed and woven wire fence, extending North and South, among juniper timber.

N. 0°05.8' E., between sections 16 and 17.

20.027 Point for the South 1/16 section corner of sections 16 and 17.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 21 inches in the ground, encircle with a collar of stone, 2 ½ foot base, to the top, with cap marked:

T 1 N R 2 E
S 1/16
S 17 | S 16
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Corner is located on a north facing slope, N. 66° E., 5 links distance from a three way corner of barbed wire fences, extending North, South, and West, among juniper timber.

40.054 The ¼ section corner of sections 16 and 17, monumented with a sandstone, 18x10x6 inches, firmly set, projecting 8 inches above the ground, encircled with a collar of stone, 2 foot base, 6 inches high, faintly marked ¼ on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 20 inches in the ground, encircle with a collar of stone, 3 foot base, to the top, with cap marked:

T 1 N R 2 E
1/4
S 17 | S 16
2004

Bury the original marked stone alongside the aluminum post.

Deposit a Deep-1 magnetic at the base of the aluminum post.

Corner is located on near level ground, in a barbed wire fence, extending North and South, among sagebrush and scattering juniper timber.

N. 0°01.4' E., beginning new measurement.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

20.040 Point for the North 1/16 section corner of sections 16 and 17, not monumented.

40.080 The corner of sections 8, 9, 16, and 17, monumented with a galvanized steel post, 2 ½ inches diameter, firmly set, projecting 18 inches above the ground, encircled with a collar of stone, 2 ½ foot base, 10 inches high, with cap marked: as described in the official record of the 1990 Dependent Resurvey of a Portion of the Subdivisional Lines, except that the cap marking is rotated 90° clockwise.

Corner is located on near level ground, in a barbed wire fence, extending North and South.

From the standard corner of sections 31 and 32, on the Base Line (South boundary of the township), hereinbefore described.

N. 0°05.3' E., between sections 31 and 32.

20.047 Point for the South 1/16 section corner of sections 31 and 32, not monumented.

40.094 The ¼ section corner of sections 31 and 32, monumented with a sandstone, 20x8x5 inches, firmly set, projecting 14 inches above the ground, encircled with a collar of stone, 2 ½ foot base, 8 inches high, and clearly marked ¼ on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 19 inches in the ground, encircle with a collar of stone, 3 foot base, to the top, with cap marked:

T 1 N R 2 E
1/4
S 31 | S 32
2004

Bury the original marked stone alongside the aluminum post.

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the corner.

Corner is located on a broken west facing slope, among juniper timber.

N. 0°39.0' E., beginning new measurement.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

- 20.143** Point for the North 1/16 section corner of sections 31 and 32, not monumented.
- 40.286** True point for the corner of sections 29, 30, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. The corner point falls on a highly erosive slope of a draw, where it is impracticable to establish a durable permanent monument.

From the corner of sections 28, 29, 32, and 33.

S. 89°24.1' W., between sections 29 and 32.

- 20.043** Point for the East 1/16 section corner of sections 29 and 32.
- Set an aluminum post, 30 inches long, 2 ½ inches diameter, 20 inches in the ground, encircle with a collar of stone, 3 foot base, to the top, with cap marked:

T 1 N R 2 E
S 29
E 1/16 ———
S 32
2004

Deposit Deep-1 magnet at the base of the aluminum post.

Corner is located on a southwest facing slope, in a barbed wire fence, extending North and South, among scattering juniper timber.

- 40.086** The ¼ section corner of sections 29 and 32, monumented with a steel bar, ¼ inch diameter, firmly set, projecting 4 inches above the ground, with no cap or marks, established by person(s) unknown. This corner monument is at a two way corner of fences, and at the clear corner of occupation and use, and is accepted as the best available evidence of the corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 25 inches in the ground, encircle with a collar of stone, 2 ½ foot base, to the top, with cap marked:

T 1 N R 2 E
S 29
1/4 ———
S 32
2004

Bury the steel bar inside the aluminum post.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Deposit a Deep-1 magnet at the base of the aluminum post.

Corner is located on a gentle east facing slope, at a corner of fences, extending North and West, and West, 1 chain distance from the center of a gravel surfaced access road, 30 links wide, extending N. 28° E., and S. 34° W.

N. 89°29.7' W., beginning new measurement.

19.505 Point for the West 1/16 section corner of sections 29 and 32.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 25 inches in the ground, encircle with a collar of stone, 1 ½ foot base, to the top, with cap marked:

T 1 N R 2 E
S 29
W 1/16 ———
S 32
2004

Deposit Deep-1 magnet at base of the aluminum post.

Set a steel T fence post alongside the corner.

Corner is located on near level ground, East, 3 links distance from a barbed wire fence, extending S. 16° E. and N. 16° W., and at the western edge of a large alfalfa field, and East, 35 links distance from the center line of an asphalt surfaced county road, 40 links wide, extending S. 28° E. and N. 6° W., along the arc of the curve.

39.010 The true point for the corner of sections 29, 30, 31 and 32.

S. 89°16.5' W., between sections 30 and 31.

19.456 Point for the East 1/16 section corner of sections 30 and 31.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 20 inches in the ground, encircle with a collar of stone, 3 foot base, to the top, with cap marked:

T 1 N R 2 E
S 30
E 1/16 ———
S 31
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set a steel T fence post alongside the corner.

38.912 The $\frac{1}{4}$ section corner of sections 30 and 31, monumented with a rebar $\frac{1}{2}$ inch diameter, firmly set, 2 inches under the surface of the ground, with a plastic cap, 1 inch diameter, marked PEATROSS RLS 155666, with another contorted rebar $\frac{1}{4}$ inch diameter, with no cap or marks, buried horizontally alongside. This corner position, although not fitting well, has been utilized by a number of private surveyors, and is thus a well established and recorded local condition, which has been perpetuated by a number of private surveyors, and as a longstanding local condition, it is accepted as the best available evidence of the original corner position.

from which

An aluminum post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, set 24 inches in the ground, for a reference monument, bears N. $8^{\circ}02.3'$ E., 33.4 links distance, with aluminum cap marked:: RM T1N R2E 1/4 S30 22.0 FT TO COR 2004 and an arrow pointing to the corner.

An aluminum post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, set 24 inches in the ground, for a reference monument, bears N. $74^{\circ}57.4'$ E., 49.0 links distance, with aluminum cap marked:: RM T1N R2E S30 32.3 FT TO COR 2004 and an arrow pointing to the corner.

Raise a mound of stone, 4 foot base, 3 foot high to the North of the corner.

Corner is located on near level ground, North, 43.5 links distance from the southern right-of-way fence, constructed of barbed wire, extending East and West, and at the northern edge of an asphalt surfaced county road, 9 links wide, extending East and West.


From the true point for the corner of sections 29, 30, 31, and 32.

N. $0^{\circ}48.8'$ E., between sections 29 and 30.

2.588 Point selected for the witness corner of sections 29, 30, 31, and 32.

Set an aluminum post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 21 inches in the ground, encircle with a collar of stone, 2 foot base, to the top, with cap marked:

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Deposit a Deep-1 magnet at the base of the aluminum post.

Corner is located on the crest of a west sloping spur ridge.

40.288

The $\frac{1}{4}$ section corner of sections 29 and 30, monumented with a sandstone, 18x12x6 inches, firmly set, projecting 16 inches above the ground, marked $\frac{1}{4}$ on the west face, with a scattered mound of stone, 2 foot base, 8 inches high, to the West of the corner.

At the corner point

Set an aluminum post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 19 inches in the ground, with cap marked:



Bury the original marked stone alongside the aluminum post.

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the corner.

Corner is located on near level ground, on top of a mesa, in juniper timber.

N. 1°37.9' W., beginning new measurement.

39.578

The corner of sections 19, 20, 29, and 30, monumented with a sandstone, 17x10x6 inches, firmly set, projecting 12 inches above the ground, marked X on the top, 5 notches on the eastern edge, 2 grooves on the south face, and with a scattered mound of stone, 2 foot base, 8 inches high, to the west of the corner.

At the corner point

Set an aluminum post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 20 inches in the ground, with cap marked:

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

T 1 N	R 2 E
S 19	S 20
S 30	S 29
2004	

Bury the original marked stone alongside the aluminum post.

Deposit a Deep-1 magnet at the base of the aluminum post.

Rehabilitate the mound of stone, 3 foot base, 2 foot high, to the West of the corner.

Corner is located at the base of a north facing slope, among sagebrush and scattering juniper timber.

From the corner of sections 20, 21, 28, and 29.

S. 89°22.7' W., between sections 20 and 29.

19.925 Point for the East 1/16 section corner of sections 20 and 29, not monumented.

39.850 The ¼ section corner of sections 20 and 29, monumented with a rebar, 5/8 inch diameter, 24 inches long, firmly set, projecting 2 inches above the ground, with a plastic cap, 1 ¼ inches diameter, marked RMS UT PLS 161259, established by Arnelton T. Davis, Utah Professional Land Surveyor, Utah RLS number 161259, and is accepted as a faithful reestablishment of the corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 23 inches in the ground, with cap marked:

T 1 N	R 2 E
	S 20
1/4	—
	S 29
2004	

Bury the 5/8 inch rebar inside the aluminum post.

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the corner.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Corner is located on near level ground, at the western edge of an alfalfa field, and east, 91 links distance from the center of Deep Creek, 8 links wide, course S. 30° E.

S. 89°22.4' W., beginning new measurement.

19.923

The point for the West 1/16 section corner of sections 20 and 29, monumented with a rebar, 5/8 inch diameter, 24 inches long, firmly set, projecting 8 inches above the ground, with a plastic cap, 1 ¼ inches diameter, marked RMS UT PLS 161259, established by Arnelton T. Davis, Utah Professional Land Surveyor, Utah RLS number 161259, and is accepted as a faithful establishment of the corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 23 inches in the ground, with cap marked:

T 1 N R 2 E
S 20
W 1/16 ———
S 29
2004

Bury the 5/8 inch rebar inside the aluminum post.

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the corner.

Corner is located on a steep, rocky west facing slope in juniper timber.

S. 89°21.9' W., beginning new measurement.

19.925

The corner of sections 19, 20, 29, 30.

S. 89°57.9' W., between sections 19 and 30.

19.852

Point for the East 1/16 section corner of sections 19 and 30.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 22 inches in the ground, with cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

T 1 N R 2 E
S 19
E 1/16 ———
S 30
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the corner.

Corner is located on near level ground, North, 81.4 links distance from the center of a gravel surfaced county road, 43 links wide, extending N. 80° E. and S. 80° W.

39.704 Point for the $\frac{1}{4}$ section corner of sections 19 and 30, at proportionate distance, falls at the southern edge of a scattered mound of stone, 3 foot base, 8 inches high.

Set an aluminum post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 21 inches in the ground, encircle with a collar of stone, 2 foot base, to the top, with cap marked:

T 1 N R 2 E
S 19
1/4 ———
S 30
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the corner.

Corner is located on near level ground, among juniper timber.

78.792 The corner of sections 19, 24, 25, and 30, on the west boundary of the township, hereinbefore described.

From the corner of sections 19, 20, 29, and 30.

N. 0°13.6' W., between sections 19 and 20.

20.279 Point for the South 1/16 section corner of sections 19 and 20, not monumented.

40.558 Point for the $\frac{1}{4}$ section corner of sections 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 21 inches in the ground, with cap marked:

T 1 N R 2 E
1/4
S 19 | S 20
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the corner.

Corner is located on near level ground, on top of a mesa, East, 1.03 chains distance from the edge of a bluff, with edge extending generally S. 10° W., and N. 40° W.

From this point, a galvanized steel post, 2 ½ inches diameter, lying loose on the ground, bears N. 26°18.1' W., 48.4 links distance, with cap marked:

1963
|
19 1/4 20
|
T1N R2E

This monument appears to have been established by the Bureau of Indian Affairs, (BIA). At the time of this survey, no record of it's establishment or existence was located, it was found loose and out of the ground, is not harmoniously related to verifiable found adjacent original corner evidence, and is not utilized within the scope of this survey. Bury this galvanized steel post in place.

81.116

The corner of sections 17, 18, 19, and 20, monumented with a sandstone, 16x10x5 inches, firmly set, projecting 12 inches above the ground, clearly marked 5 grooves on the east face, 3 grooves on the south face, with a scattered mound of stone, 2 ½ foot base, 14 inches high, to the north of the corner.

At the corner point

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 20 inches in the ground, with cap marked:

T 1 N R 2 E
S 18 | S 17
S 19 | S 20
2004

Bury the original marked stone alongside the aluminum post.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Deposit a Deep-1 magnet at the base of the aluminum post.

Rehabilitate the mound of stone, 2 ½ foot base, 18 inches high, to the north of the corner

Corner is located on near level ground, among sagebrush.

From the corner of sections 16, 17, 20, and 21.

N. 89°54.0' W., between sections 17 and 20.

19.951

Point for the East 1/16 section corner of sections 17 and 20.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 20 inches in the ground, encircle with a collar of stone, 3 foot base, to the top, with cap marked:

T 1 N R 2 E
S 17
E 1/16 ———
S 20
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Corner is located on near level ground, South, 13 links distance, from a barbed wire fence, extending N. 86° E., and S. 86° W., and East, 49 links distance, from the center of an abandoned irrigation ditch, course S. 30° W., among sagebrush.

From this point, a galvanized steel post, 2 ½ inches diameter, lying loose on the ground, bears N. 21°13.7' W., 5.1 links distance, with cap marked:

1965
S 17
———E 1/16 ———
S 20
T1NR2E

This monument appears to have been established by the Bureau of Indian Affairs, (BIA). At the time of this survey, no record of it's establishment or existence was located, it was found loose and out of the ground, is not harmoniously related to verifiable found adjacent original corner evidence, and is not utilized within the scope of this survey. Bury this galvanized steel post alongside the aluminum post.

39.902

Point for the ¼ section corner of sections 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set a steel railroad spike, flush with the surface of the county road.

from which

An aluminum post, 30 inches long, 2 ½ inches diameter, set 19 inches in the ground, for a reference monument, bears S. 25°44.2' W., 1.040 chains distance, with aluminum cap marked:: RM T1N R2E 1/4 S20 68.6 FT TO COR 2004 and an arrow pointing to the corner.

An aluminum post, 30 inches long, 2 ½ inches diameter, set 22 inches in the ground, for a reference monument, bears N. 25°44.8' W., 1.040 chains distance, with aluminum cap marked:: RM T1N R2E 1/4 S17 68.6 FT TO COR 2004 and an arrow pointing to the corner.

Corner is located in the county road, asphalt surface, 38 links wide, extending North and South.

79.804 The corner of sections 17, 18, 19, 20.

S. 89°37.5' W., between sections. 18 and 19.

39.926 True point for the ¼ section corner of sections 18 and 19, at proportionate distance; there is no remaining evidence of the original corner. The corner point falls on a very steep and erosive slope, where it is impractical to establish a permanent monument.

40.496 Point selected for the witness ¼ section corner of sections 18 and 19.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 24 inches in the ground, with cap marked:

WC
T 1 N R 2 E
S 18
1/4 →
S 19
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the corner.

Corner is located on the crest of a spur ridge, among scattering juniper timber.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

78.614 The corner of sections 13, 18, 19, and 24, on the west boundary of the township, hereinbefore described.

From the corner of sections 17, 18, 19, and 20.

N. 0°12.1' E., between sections 17 and 18.

40.270 The ¼ section corner of sections 17 and 18, monumented with a sandstone, 20x12x8 inches, firmly set, projecting 16 inches above the ground, marked 1/4 on the west face, with a scattered mound of stone, 2 ½ foot base, 8 inches high, to the west of the corner.

At the corner point

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 19 inches in the ground, encircle with a collar of stone, 2 ½ foot base, to the top, with cap marked:

T 1 N R 2 E
1/4
S 18 | S 17
2004

Bury the original marked stone alongside the aluminum post.

Deposit a Deep-1 magnet at the base of the aluminum post.

Rehabilitate the mound of stone, 3 foot base, 2 foot high, to the west of the corner.

Corner is located on near level ground, among sagebrush and widely scattering juniper timber.

N. 0°03.1' E., beginning new measurement.

20.037 Point for the North 1/16 section corner of sections 17 and 18.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 20 inches in the ground, with cap marked:

T 1 N R 2 E
N 1/16
S 18 | S 17
2004

Set a steel T fence post alongside the aluminum post.

Corner is located on a very gentle northeast slope, among sagebrush.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

40.074

The corner of sections 7, 8, 17, and 18, monumented with and aluminum post, 2 ½ inches diameter, firmly set, projecting 3 inches above the ground, with a mound of stone, 3 foot base, 16 inches high, to the west of the corner, and with cap marked: as described in the official record of the 1990 Dependent Resurvey of a Portion of the Subdivisional Lines.

Restoring the Survey Executed by J.H. Martineau in 1904,
and the Dependent Resurvey, Executed by
Richard Zaninovich, in 1990

From the ¼ section corner of sections 6 and 7, monumented with and aluminum post, 2 ½ inches diameter, firmly set, projecting 5 inches above the ground, with an embedded mound of stone, 2 1/2 foot base, 10 inches high, to the north, with the cap marked: as described in the official record of the 1990 Dependent Resurvey of a Portion of the Subdivisional Lines.

S. 89°50.9' W., between sections 6 and 7.

20.319

Point for the West 1/16 section corner of section 6 and 7.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 20 inches in the ground, encircle with a collar of stone, 3 foot base, to the top, with cap marked:

T 1 N R 2 E
 S 6
W 1/16 ———
 S 7
 2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the corner.

Corner is located on near level ground, among sagebrush and scattering juniper timber.

39.478

The corner of sections 1, 6, 7, and 12, on the west boundary of the township, hereinbefore described.

**Dependent Resurvey of a Portion of the Subdivision of Section 7,
Township 1 North, Range 2 East, Uintah Special Meridian, Utah**

Restoring the survey executed by
R. A. Zaninovich, in 1990

**DEPENDENT RESURVEY OF A PORTION OF THE, SUBDIVISION OF SECTION 7,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

From the Center $\frac{1}{4}$ section corner of section 7, monumented with and aluminum post, 2 $\frac{1}{2}$ inches diameter, firmly set, projecting 8 inches above the ground, encircled with a collar of stone, 3 foot base, to the top, with the cap marked: as described in the official record of the 1990 Survey of the Subdivision of Section 7.

N. 0°30.4' E., on the North and South center line of section 7.

- 20.187** The Center-North $\frac{1}{16}$ section corner of section 7, monumented with rebar, $\frac{5}{8}$ inch diameter, firmly set, projecting 10 inches above the ground, with a 1 $\frac{1}{2}$ inch diameter aluminum cap marked: LS 148951, established by Jerry D. Allred, Utah Professional Land Surveyor, Utah RLS number 148951, and is accepted as a good faith establishment of the corner position. Not remonumented.

Corner is located on near level ground, with a railroad tie set upright alongside, among sagebrush.

N. 0°30.4' E., beginning new measurement.

- 20.187** The $\frac{1}{4}$ section corner of sections 6 and 7.

From the Center $\frac{1}{4}$ section corner of section 7.

N. 89°34.6' W., on the East and West center line of section 7.

- 20.138** Point for the Center - West $\frac{1}{16}$ section corner of section 7. Not monumented.

- 39.156** The $\frac{1}{4}$ section corner of sections 7 and 12, on the west boundary of the township, hereinbefore described.

**Dependent Resurvey of a Portion of the Subdivision of Section 8,
Township 1 North, Range 2 East, Uintah Special Meridian, Utah**

Restoring the survey executed by
R. A. Zaninovich, in 1990

From the Center $\frac{1}{4}$ section corner of section 8, monumented with and aluminum post, 2 $\frac{1}{2}$ inches diameter, firmly set, projecting 8 inches above the ground, encircled with a collar of stone, 3 foot base, to the top, with the cap marked: as described in the official record of the 1990 Survey of the Subdivision of Section 8.

N. 89°39.4' W., on the East and West center line of section 8.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION OF SECTION 8,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

19.928 The Center-West 1/16 section corner of section 8, monumented by a rebar, 5/8 inch diameter, firmly set, projecting 4 inches above the ground, with an aluminum cap, 1 1/2 inch diameter, marked LS 148951, established by Jerry D. Allred, Utah Professional Land Surveyor, Utah RLS number 148951, and is accepted as a good faith establishment of the corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, encircle with a collar of stone, 2 1/2 foot base, to the top, with cap marked:

T1N R2E
W 1/16
C ————— C
S 8
2004

Bury the 5/8 inch rebar inside the aluminum post.

Deposit a Deep-1 magnet at the base of the aluminum post.

Corner is located on near level ground, with a railroad tie set upright alongside, among sagebrush and scattering juniper timber.

N. 89°39.9' W., beginning new measurement.

19.930 The 1/4 section corner of sections 7 and 8, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above the ground, with a mound of stone, 3 foot base, 12 inches high, to the west of the corner, and with the cap marked: as described in the official record of the 1990 Dependent Resurvey of a Portion of the Subdivisional Lines.

**Survey of the Subdivision of Section 7,
Township 1 North, Range 2 East, Uintah Special Meridian, Utah**

From the point for the Center - West 1/16 section corner of section 7.

N. 0°14.8' E., on the North and South center line of the Northwest 1/4 of section 7.

20.086 Point for the Northwest 1/16 section corner of section 7, at intersection with the East and West center line of the Northwest 1/4 of section 7.

**SURVEY OF THE SUBDIVISION OF SECTION 7,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 21 inches in the ground, encircle with a collar of stone, 2 ½ foot base, to the top, with cap marked:

T 1 N R 2 E
NW 1/16 S 7
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located on near level ground, North, 38.5 links distance from the center of Little Water Creek, 6 links wide, course S. 36° E.

40.171 The West 1/16 section corner of sections 6 and 7.

From the Center-North 1/16 section corner of section 7.

N. 89°52.0' W., on the East and West center line of the Northwest ¼ of section 7.

20.228 The Northwest 1/16 section corner of section 7.

39.316 The North 1/16 section corner of sections 7 and 12, on the west boundary of the township, hereinbefore described.

**Survey of the Subdivision of Section 17,
Township 1 North, Range 2 East, Uintah Special Meridian, Utah**

From the ¼ section corner of sections 17 and 20.

N. 0°05.4' E., on the North and South center line of section 17.

20.078 Point for the Center-South 1/16 section corner of sections 17.

Set a steel magnetic nail, 2 ½ inches long, with a brass washer, 1 ½ inch diameter, marked BLM CADASTRAL SURVEY, underneath, flush with the surface of the county road.

from which

**SURVEY OF THE SUBDIVISION OF SECTION 17,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

An aluminum post, 30 inches long, 2 ½ inches diameter, set 22 inches in the ground, for a reference monument, bears S. 79°20.9' E., 52.3 links distance, with aluminum cap marked:: RM T1N R2E C-S 1/16 S17 34.5 FT TO COR 2004 and an arrow pointing to the corner.

An aluminum post, 30 inches long, 2 ½ inches diameter, set 22 inches in the ground, for a reference monument, bears S. 79°26.0' W., 52.3 links distance, with aluminum cap marked:: RM T1N R2E C-S 1/16 S17 34.5 FT TO COR 2004 and an arrow pointing to the corner.

Corner is located in an asphalt surfaced county road, 45 links wide, extending North and South.

40.156

Point for the Center ¼ section corner of section 17, at intersection with the East and West center line.

Set a steel magnetic nail, 2 ½ inches long, with a brass washer, 1 ½ inch diameter, marked BLM CADASTRAL SURVEY, underneath, flush with the surface of the county road.

from which

An aluminum post, 30 inches long, 2 ½ inches diameter, set 24 inches in the ground, for a reference monument, bears S. 35°52.2' E., 81.0 links distance, with aluminum cap marked:: RM T1N R2E C 1/4 S17 53.4 FT TO COR 2004 and an arrow pointing to the corner.

An aluminum post, 30 inches long, 2 ½ inches diameter, set 22 inches in the ground, for a reference monument, bears S. 35°47.9' W., 81.0 links distance, with aluminum cap marked:: RM T1N R2E C 1/4 S17 53.4 FT TO COR 2004 and an arrow pointing to the corner.

Corner is located in an asphalt surfaced county road, 47 links wide, extending North and South.

60.197

Point for the Center-North 1/16 section corner of section 17.

Set a steel magnetic nail, 2 ½ inches long, with a brass washer, 1 ½ inch diameter, marked BLM CADASTRAL SURVEY, underneath, flush with the surface of the county road.

from which

**SURVEY OF THE SUBDIVISION OF SECTION 17,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

An aluminum post, 30 inches long, 2 ½ inches diameter, set 20 in the ground, for a reference monument, bears N. 35°56.5' E., 97.5 links distance, with aluminum cap marked:: RM T1N R2E C-N 1/16 S17 64.4 FT TO COR 2004 and an arrow pointing to the corner.

An aluminum post, 30 inches long, 2 ½ inches diameter, set 20 in the ground, for a reference monument, bears S. 36°00.5' E., 97.5 links distance, with aluminum cap marked:: RM T1N R2E C-N 1/16 S17 64.4 FT TO COR 2004 and an arrow pointing to the corner.

Corner is located in an asphalt surfaced county road, 45 links wide, extending North and South.

80.238 The ¼ section corner of sections 8 and 17, monumented with a railroad spike, 5 inches under the surface of an asphalt surface county road.

from which

A reference monument, monumented with an aluminum post, 2 ½ inches diameter, firmly set, projecting 5 inches above the ground, bears N. 45°15.3' E., 70.8 links distance, with aluminum cap marked: as described in the official record of the 1990 Dependent Resurvey of a Portion of the Subdivisional Lines, T.1 N., R.2 E.

A reference monument, monumented with an aluminum post, 2 ½ inches diameter, firmly set, projecting 3 inches above the ground, bears S. 44°42.9' E., 70.7 links distance, with aluminum cap marked: as described in the official record of the 1990 Dependent Resurvey of a Portion of the Subdivisional Lines, T.1 N., R.2 E.

From the ¼ section corner of sections 16 and 17.

N. 89°45.0' W., on the East and West center line of section 17.

19.949 Point for the Center-East 1/16 section corner of section 17.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 20 inches in the ground, encircle with a collar of stone, 2 ½ foot base, to the top, with cap marked:

T 1 N R 2 E
E 1/16
C ——— C
S 17
2004

**SURVEY OF THE SUBDIVISION OF SECTION 17,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Deposit a Deep-1 magnet at the base of the aluminum post.

Corner is located on near level ground, North, 37.3 links distance from the center of a gravel surface driveway, extending West and bending toward the South, and in a barbed wire fence, extending North and South

39.898 The Center $\frac{1}{4}$ section corner of section 17.

59.813 Point for the Center-West $\frac{1}{16}$ section corner of section 17.

Set an aluminum post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 18 inches in the ground, encircle with a collar of stone, 3 $\frac{1}{2}$ foot base, to the top, with cap marked:

T 1 N R 2 E
W 1/16
C ——— C
S 17
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located on near level ground, among scattering juniper timber.

79.728 The $\frac{1}{4}$ section corner of sections 17 and 18.

From the Center-East $\frac{1}{16}$ section corner of section 17.

N. $0^{\circ}03.2'$ W., on the North and South center line of the Northeast $\frac{1}{4}$ of section 17.

20.000 Point for the Northeast $\frac{1}{16}$ section corner of section 17, determined at the three way intersection of fences; accepted as a faithful establishment of the corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 20 inches in the ground, encircle with a collar of stone, 2 $\frac{1}{2}$ foot base, to the top, with cap marked:

T 1 N R 2 E
NE 1/16 S 17
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

**SURVEY OF THE SUBDIVISION OF SECTION 17,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Corner is located on near level ground, at the corner of fences, extending North, East, and South, among sagebrush.

N. 0°09.6' E., beginning new measurement.

- 20.079** The East 1/16 section corner of sections 8 and 17, monumented with an aluminum post, 2 ½ inches diameter, firmly set, projecting 2 inches above the ground, encircled with a collar of stone, 2 foot base, 8 inches high, with the aluminum cap marked: as described in the official record of the 1990 Dependent Resurvey of a Portion of the Subdivisional Lines, T.1 N. R.2 E.
-

From the point for the North 1/16 section corner of sections 16 and 17.

N. 89°51.9' W., on the East and West center line of the Northeast ¼ of section 17.

- 19.975** The Northeast 1/16 section corner of section 17.
-

N. 89°39.8' W., beginning new measurement.

- 19.903** The Center-North 1/16 section corner of section 17.
-

From the East 1/16 section corner of sections 17 and 20.

N. 0°11.5' E., on the North and South center line of the Southeast ¼ of section 17.

- 20.096** Point for the Southeast 1/16 section corner of section 17, determined at the two way intersection of fences; accepted as a faithful establishment of the corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 20 inches in the ground, encircle with a collar of stone, 2 ½ foot base, to the top, with cap marked:

T 1 N R 2 E
SE 1/16 S 17
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

**SURVEY OF THE SUBDIVISION OF SECTION 17,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Corner is located on near level ground, at the corner of fences, extending North, and East, among sagebrush.

N. 0°00.1' E., beginning new measurement.

20.017 The Center-East 1/16 section corner of sections 17.

From the South 1/16 section corner of sections 16 and 17.

N. 89°42.6' W., on the East and West center line of the Southeast ¼ of section 17.

19.918 The Southeast 1/16 section corner of section 17.

N. 89°56.7' W., beginning new measurement.

19.987 The Center-South 1/16 section corner of section 17.

From the Center-West 1/16 section corner of section 17.

N. 0°04.3' E., on the North and South center line of the Northwest ¼ of section 17.

20.039 Point for the Northwest 1/16 section corner of section 17, at intersection with the East and West center line of the Northwest ¼ of section 17.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 18 inches in the ground, encircle with a collar of stone, 3 foot base, to the top, with cap marked:

T 1 N R 2 E
NW 1/16 S 17
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located on near level ground, South, 36.8 links distance, from the center of Little Water Creek, 6 links wide, course S. 44° E., among tall sagebrush.

40.081 The West 1/16 section corner of sections 8 and 17, monumented with an aluminum post, 2 ½ inches diameter, firmly set, projecting 3 inches above the ground, with a mound of stone, 3 foot base, 16 inches high, to the north of the corner, and with the aluminum cap marked: as described in the official record of

**SURVEY OF THE SUBDIVISION OF SECTION 17,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

the 1990 Dependent Resurvey of a Portion of the Subdivisional Lines, T.1 N. R.2 E.

From the Center-North 1/16 section corner of section 17.

N. 89°45.3' W., on the East and West center line of the Northwest ¼ of section 17.

19.918 The Northwest 1/16 section corner of section 17.

39.838 The North 1/16 section corner of sections 17 and 18.

**Survey of the Subdivision of Section 19,
Township 1 North, Range 2 East, Uintah Special Meridian, Utah**

From the ¼ section corner of sections 19 and 30.

N. 0°23.7' W., on the North and South center line of section 19.

20.503 Point for the Center-South 1/16 section corner of section 19, not monumented.

41.006 Point for the Center ¼ section 19, at intersection with the East and West center line.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 22 inches in the ground, with cap marked:

T 1 N R 2 E
C 1/4 S 19
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Raise a mound of stone, 2 ½ foot base, 12 inches high, to the west of the corner.

Corner is located on near level ground, in a plowed field, a portion of which is in trespass.

From this point, a galvanized steel post, 18 inches long, was found loose out of the ground, and propped up on the top of a steel T fence post, with cap marked: 1963 S19 C ¼ T1N R2E, bears S. 10°53.3' W., at distance of 33.2 links. This monument appears to have been established by the Bureau of Indian Affairs, (BIA), although I have found no record of its establishment or existence, and was apparently plowed out by

**SURVEY OF THE SUBDIVISION OF SECTION 19,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

subsequent agricultural activities. I bury this BIA monument alongside the aluminum post.

60.941 Point for the Center-North 1/16 section corner of section 19.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 20 inches in the ground, encircle with a collar of stone, 3 foot base, to the top, with cap marked:

T 1 N R 2 E
C
N 1/16 | S 19
C
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located on a very gentle south facing slope, among juniper timber.

80.876 The true point for the ¼ section corner of sections 18 and 19.

From the ¼ section corner of sections 19 and 20.

N. 89°23.3' W., on the East and West center line of section 19.

19.906 Point for the Center-East 1/16 section corner of section 19.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 17 inches in the ground, to underlying rock, supported by a collar of stone, 4 foot base, to the top, with cap marked:

T 1 N R 2 E
E 1/16
C———C
S 19
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located on a very gentle south facing slope, among juniper timber.

39.812 The Center ¼ section corner of section 19.

78.644 The ¼ section corner of sections 19 and 24, on the west boundary of the township, hereinbefore described.

**SURVEY OF THE SUBDIVISION OF SECTION 19,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

From the East 1/16 section corner of sections 19 and 30.

N. 0°18.2' W., on the North and South center line of the Southeast ¼ of section 19.

20.390 Point for the Southeast 1/16 section corner of section 19, at intersection with the East and West center line of the Southeast ¼ of section 19.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 24 inches in the ground, encircle with a collar of stone, 2 ½ foot base, to the top, with cap marked:

T 1 N R 2 E
SE 1/16 S 19
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located on near level ground, among sparse sagebrush.

40.781 The Center-East 1/16 section corner of section 19.

From the point for the South 1/16 section corner of sections 19 and 20.

N. 89°42.6' W., on the East and West center line of the Southeast ¼ of section 19.

19.875 The Southeast 1/16 section corner of section 19.

39.750 The point for the Center-South 1/16 section corner of section 19.

From the Center-North 1/16 section corner of section 19.

N. 89°29.6' W., on the East and West center line of the Northwest ¼ of section 19.

38.764 The North 1/16 section corner of sections 19 and 24, on the west boundary of the township, hereinbefore described.

**Survey of the Subdivision of Section 20,
Township 1 North, Range 2 East, Uintah Special Meridian, Utah**

**SURVEY OF THE SUBDIVISION OF SECTION 20,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

From the $\frac{1}{4}$ section corner of sections 20 and 29.

N. $0^{\circ}10.8'$ W., on the North and South center line of section 20.

40.295 Point for the Center $\frac{1}{4}$ section corner of section 20, at the intersection with the East and West center line of section 20.

Set an aluminum post, 30 inches long, $2\frac{1}{2}$ inches diameter, 22 inches in the ground, encircle with a collar of stone, $2\frac{1}{2}$ foot base, to the top, with cap marked:

T 1 N R 2 E
C 1/4 S 20
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located N. 20° E., 19.5 links distance, from a three way corner of fences, extending N. 54° E., South, and N. 10° W., and in the vicinity of an underground irrigation pipeline.

60.450 Point for the Center-North $1/16$ section corner of section 20, not monumented.

80.605 The $\frac{1}{4}$ section corner of sections 17 and 20.

From the $\frac{1}{4}$ section corner of sections 20 and 21.

S. $89^{\circ}44.8'$ W., on the East and West center line of section 20.

19.913 Point for the Center-East $1/16$ section corner of section 20.

Set an aluminum post, 30 inches long, $2\frac{1}{2}$ inches diameter, 24 inches in the ground, encircle with a collar of stone, $2\frac{1}{2}$ foot base, to the top, with cap marked:

T 1 N R 2 E
E 1/16
C ——— C
S 20
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located East, 20.2 links distance from a barbed wire fence, extending North and South.

SURVEY OF THE SUBDIVISION OF SECTION 20,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

39.826 The Center $\frac{1}{4}$ section corner of section 20.

59.772 Point for the Center-West $\frac{1}{16}$ section corner of section 20.

Set an aluminum post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 20 inches in the ground, encircle with a collar of stone, 3 $\frac{1}{2}$ foot base, to the top, with cap marked:

T 1 N R 2 E
W 1/16
C ————— C
S 20
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located on a steep and rocky west facing slope of a spur ridge, among scattering juniper timber.

79.718 The $\frac{1}{4}$ section corner of sections 19 and 20.

From the Center-East $\frac{1}{16}$ section corner of section 20.

N. $0^{\circ}08.5'$ W., on the North and South center line of the Northeast $\frac{1}{4}$ of section 20.

20.094 Point for the Northeast $\frac{1}{16}$ section corner of section 20, at intersection with the East and West center line of the Northeast $\frac{1}{4}$ of section 20.

Set an aluminum post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 24 inches in the ground, with cap marked:

T 1 N R 2 E
NE 1/16 S 20
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located on near level ground, among tall sagebrush.

40.188 The East $\frac{1}{16}$ section corner of sections 17 and 20.

From the point for the North $\frac{1}{16}$ section corner of sections 20 and 21.

**SURVEY OF THE SUBDIVISION OF SECTION 20,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

S. 89°55.4' W., on the East and West center line of the Northeast ¼ of section 20.

19.932 The Northeast 1/16 section corner of section 20.

39.864 The point for the Center-North 1/16 section corner of section 20.

From the West 1/16 section corner of sections 20 and 29.

N. 0°12.3' W., on the North and South center line of the Southwest ¼ of section 20.

40.425 The Center-West 1/16 section corner of section 20.

**Survey of the Subdivision of Section 29,
Township 1 North, Range 2 East, Uintah Special Meridian, Utah**

From the ¼ section corner of sections 29 and 32.

N. 0°12.4' E., on the North and South center line of section 29.

20.246 Point for the Center-South 1/16 section corner of section 29.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 22 inches in the ground, encircle with a collar of stone, 2 foot base, to the top, with cap marked:

T 1 N R 2 E
C
S 1/16 | S 29
C
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located at the western edge of a hay field, East, 8.3 links distance from a barbed and woven wire fence, extending North and South, and N. 89°38.7' E., 13.1 links distance from an irrigation pipeline riser.

40.492 Point for the Center ¼ section corner of section 29, at intersection with the East and West center line of section 29.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 22 inches in the ground, encircle with a collar of stone, 2 ¼ foot base, to the top, with cap marked:

SURVEY OF THE SUBDIVISION OF SECTION 29,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

T 1 N R 2 E
C 1/4 S 29
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located at the base of a west facing slope, East, 6.1 links distance from a barbed wire fence, extending North and South, and among tall sagebrush.

60.560 Point for the Center-North 1/16 section corner of section 29.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 24 inches in the ground, encircle with a collar of stone, 2 ½ foot base, to the top, with cap marked:

T 1 N R 2 E
C
N 1/16 | S 29
C
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located on near level ground, East, 15.0 links distance from a barbed wire fence, extending North and South, and N. 19°07' W., 45.6 links distance from a three way fence corner, extending S. 88° E., South, and N. 8° W.

80.628 The ¼ section corner of sections 20 and 29.

From the ¼ section corner of sections 28 and 29.

N. 89°48.0' W., on the East and West center line of section 29.

19.895 Point for the Center-East 1/16 section corner of section 29.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 22 inches in the ground, encircle with a collar of stone, 2 ½ foot base, to the top, with cap marked:

T 1 N R 2 E
E 1/16
C———C
S 29
2004

**SURVEY OF THE SUBDIVISION OF SECTION 29,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located on a gentle west facing slope, among sagebrush and scattering juniper timber.

39.790 The Center $\frac{1}{4}$ section corner of section 29.

59.077 Point for the Center-West $\frac{1}{16}$ section corner of section 29.

Set an aluminum post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 30 inches in the ground, flush with the surface of the ground at the request of the adjacent landowner, and with cap marked:

T 1 N R 2 E
W 1/16
C ——— C
S 29
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Corner is located on near level ground, in an alfalfa field, and East, 76.1 links distance from a 5 strand barbed wire fence, extending N. 2° E. and S. 2° W.

78.364 The $\frac{1}{4}$ section corner of sections 29 and 30.

From the Center-East $\frac{1}{16}$ section corner of section 29.

N. 0°15.5' E. on the North and South center line of the Northeast $\frac{1}{4}$ of section 29.

20.210 Point for the Northeast $\frac{1}{16}$ section corner of section 29, at intersection with the East and West center line of the Northeast $\frac{1}{4}$ of section 29.

Set an aluminum post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 24 inches in the ground, encircle with a collar of stone, 2 foot base, to the top, with cap marked:

T 1 N R 2 E
NE 1/16 S 29
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

**SURVEY OF THE SUBDIVISION OF SECTION 29,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Corner is located on near level ground, at the western edge of a large alfalfa field, and West, 3.0 links distance from a barbed wire fence, extending North and South, and N. 8°42' W., 25.3 links distance from a three way corner of fences, extending North, N. 88° E., and S. 88° W.

40.420 The point for the East 1/16 section corner of sections 20 and 29.

From the North 1/16 section corner of sections 28 and 29.

S. 89°47.3' W., on the East and West center line of the Northeast ¼ of section 29.

19.910 The Northeast 1/16 section corner of section 29.

39.820 The Center-North 1/16 section corner of section 29.

From the East 1/16 section corner of sections 29 and 32.

N. 0°32.0' W., on the North and South center line of the Southeast ¼ of section 29.

20.186 The Southeast 1/16 section corner of section 29, monumented with a rebar, ½ inch diameter, firmly set, projecting 2 inches above the ground, with no cap or marks, established by person(s) unknown, accepted as a faithful determination of the corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 24 inches in the ground, encircle with a collar of stone, 2 ½ foot base, to the top, with cap marked:

T 1 N R 2 E
SE 1/16 S 29
2004

Bury the ½ inch diameter rebar inside the aluminum post.

Deposit a Deep-1 magnet at the base of the aluminum post.

Corner is located on near level ground, at the corner of fences, extending South and West, among juniper timber.

N. 0°32.0' E., beginning new measurement.

20.029 The Center-East 1/16 section corner of section 29.

**SURVEY OF THE SUBDIVISION OF SECTION 29,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

From the point for the South 1/16 section corner of sections 28 and 29.

N. 89°58.6' W., on the East and West center line of the Southeast ¼ of section 29.

20.156 The Southeast 1/16 section corner of section 29.

S. 89°34.3' W., beginning new measurement.

19.781 The Center-South 1/16 section corner of section 29.

From the West 1/16 section corner of sections 29 and 32.

N. 0°30.2' E., on the North and South center line of the Southwest ¼ of section 29.

40.387 The Center-West 1/16 section corner of section 29.

From the Center-West 1/16 section corner of sections 29.

N. 0°41.9' W., on the North and south center line of the Northwest ¼ of section 29.

39.852 The West 1/16 section corner of sections 20 and 29.

**Survey of the Subdivision of Section 30,
Township 1 North, Range 2 East, Uintah Special Meridian, Utah**

From the ¼ section corner of sections 30 and 31.

N. 0°58.5' W., on the North and South center line of section 30.

20.245 Point for the Center-South 1/16 section corner of section 30.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 22 inches in the ground, encircle with a collar of stone, 2 ½ foot base, to the top, with cap marked:

T 1 N R 2 E
C
S 1/16 | S 30
C
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

**SURVEY OF THE SUBDIVISION OF SECTION 30,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set a steel T fence post alongside the aluminum post.

Corner is located on near level ground, West, 4.14 chains distance from the center of a canal, 23 links wide, course S. 40° E., among greasewood.

40.490 Point for the Center $\frac{1}{4}$ section corner of section 30, at intersection with the East and West center line of section 30.

Set an aluminum post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 20 inches in the ground, encircle with a collar of stone, 2 $\frac{1}{2}$ foot base, to the top, with cap marked:

T 1 N R 2 E
C 1/4 S 30
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located on near level ground, among sagebrush and scattering juniper timber.

60.404 Point for the Center-North $\frac{1}{16}$ section corner of section 30.

Set an aluminum post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 19 inches in the ground, to underlying rock, supported by a collar of stone, 4 foot base, to the top, with cap marked:

T 1 N R 2 E
C
N 1/16 | S 30
C
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located on near level ground, North, 79 links distance, from an abandoned fence line, extending East and West, among sagebrush and scattering juniper timber.

80.318 The $\frac{1}{4}$ section corner of sections 19 and 30.

From the $\frac{1}{4}$ section corner of sections 29 and 30.

S. 89°35.6' W., on the East and West center line of section 30.

**SURVEY OF THE SUBDIVISION OF SECTION 30,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

- 40.153** The Center $\frac{1}{4}$ section corner of section 30.
- 80.053** The $\frac{1}{4}$ section corner of sections 25 and 30, on the west boundary of the township, hereinbefore described.

**Survey of the Subdivision of Section 31,
Township 1 North, Range 2 East, Uintah Special Meridian, Utah**

From the standard $\frac{1}{4}$ section corner of section 31, on the Base Line, (South Boundary of Section. 31), hereinbefore described.

N. $0^{\circ}56.3'$ E., on the North and South center line of section 31.

- 20.005** Point for the Center-South $\frac{1}{16}$ section corner of section 31.

Set an aluminum post, 30 inches long, $2\frac{1}{2}$ inches diameter, 20 inches in the ground, encircle with a collar of stone, $2\frac{1}{2}$ foot base, to the top, with cap marked:

T 1 N R 2 E
C
S $\frac{1}{16}$ | S 31
C
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located on near level ground, N. 74° W., 5.8 links distance from a 4 way corner of barbed wire fences, extending North, East, South, and West.

- 40.010** Point for the Center $\frac{1}{4}$ section corner of section 31, at intersection with the East and West center line of section 31.

Set an aluminum post, 30 inches long, $2\frac{1}{2}$ inches diameter, 26 inches in the ground, encircle with a collar of stone, 2 foot base, to the top, with cap marked:

T 1 N R 2 E
C $\frac{1}{4}$ S 31
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located on near level ground, at the projected intersection of fences, extending East and South.

**SURVEY OF THE SUBDIVISION OF SECTION 31,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

59.944 Point for the Center-North 1/16 section corner of section 31, not monumented.

79.878 The ¼ section corner of sections 30 and 31.

From the ¼ section corner of sections 31 and 32.

S. 89°54.0' W., on the East and West center line of section 31.

19.553 Point for the Center-East 1/16 section corner of section 31.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 19 inches in the ground, encircle with a collar of stone, 4 foot base, to the top, with cap marked:

T 1 N R 2 E
E 1/16
C———C
S 31
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a carsonite survey marker alongside the aluminum post.

Corner is located on near level ground, East, 1.69 chains distance from the center of a canal, 26 links wide, course S. 28° W., among juniper timber.

39.106 The Center ¼ section corner of section 31.

79.128 The ¼ section corner of sections 31 and 36, on the west boundary of the township, monumented with a weathered sandstone, 16x8x5 inches, lying loose on the ground, marked ¼ on one face, perpetuated by a rebar, 5/8 inch diameter, firmly set alongside, projecting 7 inches above the ground, set by person/s unknown, with no cap or marks, is accepted as the best available evidence of the original cor. position. In addition, the accepted rebar described above, is witnessed by another rebar, 5/8 inch diameter, firmly set, projecting 6 inches above the ground, with no cap or marks, bears N. 78° E., at 0.7 links distance.

Corner is located on near level ground, at the corner of barbed wire fences, extending South and West.

Corner point not remonumented.

From the Center-East 1/16 section corner of section 31.

**SURVEY OF THE SUBDIVISION OF SECTION 31,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

N. $0^{\circ}47.6'$ E., on the North and South center line of the Northeast $\frac{1}{4}$ of section 31.

- 20.039** Point for the Northeast $\frac{1}{16}$ section corner of section 31, at intersection with the East and West center line of the Northeast $\frac{1}{4}$ of section 31.

Set an aluminum post, 30 inches long, $2\frac{1}{2}$ inches diameter, 20 inches in the ground, encircle with a collar of stone, 3 foot base, to the top, with cap marked:

T 1 N R 2 E
NE $\frac{1}{16}$ S 31
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located on a gentle west facing slope of a spur ridge, East, 3.67 chains distance from the center of a canal, 26 links wide, course S. 30° E.

- 40.078** The East $\frac{1}{16}$ section corner of sections 30 and 31.

From the point for the North $\frac{1}{16}$ section corner of sections 31 and 32.

S. $89^{\circ}35.3'$ W., on the East and West center line of the Northeast $\frac{1}{4}$ of section 31.

- 19.504** The Northeast $\frac{1}{16}$ section corner of section 31.

- 39.008** The point for the Center-North $\frac{1}{16}$ section corner of section 31.

From the standard East $\frac{1}{16}$ section corner of section 31, on the base line (South boundary of section 31), hereinbefore described.

N. $0^{\circ}30.2'$ E., on the North and South center line of the Southeast $\frac{1}{4}$ section 31.

- 20.025** Point for the Southeast $\frac{1}{16}$ section corner of section 31, at intersection with the East and West center line of the Southeast $\frac{1}{4}$ of section 31.

Set an aluminum post, 30 inches long, $2\frac{1}{2}$ inches diameter, 22 inches in the ground, encircle with a collar of stone, $2\frac{1}{2}$ foot base, to the top, with cap marked:

**SURVEY OF THE SUBDIVISION OF SECTION 31,
TOWNSHIP 1 NORTH, RANGE 2 EAST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

T 1 N R 2 E
SE 1/16 S 31
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located on near level ground, between two canals, West, 8.32 chains distance from the center of the upper canal, 18 links wide, course S. 5° W., and East, 4.38 chains distance, from the center of the lower canal, 21 links wide, course S. 2° E.,

40.050 The Center-East 1/16 section corner of section 31.

From the point for the South 1/16 section corner of sections 31 and 32.

S. 89°57.9' W., on the East and West center line of the Southeast ¼ of section 31.

19.702 The Southeast 1/16 section corner of section 31.

39.404 The Center-South 1/16 section corner of section 31.

**Survey of the Subdivision of Section 32,
Township 1 North, Range 2 East, Uintah Special Meridian, Utah**

From the standard ¼ section corner of section 32, on the Base Line, (South Boundary of Section. 32), hereinbefore described.

N. 0°10.2' W., on the North and South center line of section 32.

20.084 Point for the Center-South 1/16 section corner of section 32.

Set an aluminum post, 30 inches long, 2 ¼ inches diameter, 20 inches in the ground, encircle with a collar of stone, 3 foot base, to the top, with cap marked:

T 1 N R 2 E
C
S 1/16 | S 32
C
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

**SURVEY OF THE SURVEY OF THE SUBDIVISION OF SECTION 32,
TOWNSHIP 2 SOUTH, RANGE 2 WEST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Corner is located on near level ground, on top of a spur ridge, among sagebrush.

40.168 Point for the Center $\frac{1}{4}$ section corner of section 32, at intersection with the East and West center line.

Set an aluminum post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 20 inches in the ground, encircle with a collar of stone, 3 foot base, to the top, with cap marked:

T 1 N R 2 E
C 1/4 S 32
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located on near level ground, West, 1.36 chains distance from the center of an asphalt surface county road, 36 links wide, extending S. 24° E. and N. 24° W.

60.123 Point for the Center-North $\frac{1}{16}$ section corner of section 32.

Set an aluminum post, 30 inches long, 2 $\frac{1}{2}$ inches diameter, 22 inches in the ground, encircle with a collar of stone, 2 $\frac{1}{2}$ foot base, to the top, with cap marked:

T 1 N R 2 E
C
N 1/16 | S 32
C
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located on near level ground, East, 5.7 links distance from a barbed and woven wire fence, extending North and South.

80.078 The $\frac{1}{4}$ section corner of sections 29 and 32.

From the $\frac{1}{4}$ section corner of sections 32 and 33.

S. 89°57.5' W., on the East and West center line of section 32.

19.952 Point for the Center-East $\frac{1}{16}$ section corner of section 32.

**SURVEY OF THE SURVEY OF THE SUBDIVISION OF SECTION 32,
TOWNSHIP 2 SOUTH, RANGE 2 WEST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 24 inches in the ground, with cap marked:

T 1 N R 2 E
E 1/16
C———C
S 32
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located on near level ground, in a barbed and woven wire fence, extending East and West.

39.904 The Center ¼ section corner of section 32.

59.696 Point for the Center-West 1/16 section corner of section.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 25 inches in the ground, with cap marked:

T 1 N R 2 E
W 1/16
C———C
S 32
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Raise a mound of stone, 4 foot base, 2 foot high, to the North of the corner.

Set a steel T fence post alongside the aluminum post.

Corner is located at the base of an East slope, among scattering juniper timber.

79.488 The ¼ section corner of sections 31 and 32.

From the Center-East 1/16 section corner of section 32.

N. 0°02.5' W., on the North and South center line of the Northeast ¼ section 32.

20.054 Point for the Northeast 1/16 section corner of section 32, at intersection with the East and West center line of the Northeast ¼ of section 32.

**SURVEY OF THE SURVEY OF THE SUBDIVISION OF SECTION 32,
TOWNSHIP 2 SOUTH, RANGE 2 WEST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 22 inches in the ground, encircle with a collar of stone, 4 foot base, to the top, with cap marked:

T 1 N R 2 E
NE 1/16 S 32
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

Corner is located on near level ground, East, 1.39 chains distance from the center of a creek, 53 links wide, course S. 14° W.

40.104 The East 1/16 section corner of sections 29 and 32.

From the North 1/16 section corner of sections 32 and 33.

S. 89°40.5' W., on the East and West center line of the Northeast ¼ of section 32.

20.013 The Northeast 1/16 section corner of section 32.

40.007 The Center-North 1/16 section corner of section 32.

From the standard East 1/16 section corner of section 32, on the Base Line, (South Boundary of Section. 32), hereinbefore described

N. 0°06.8' W., on the North and South center line of the Southeast ¼ of section 32.

20.050 Point for the Southeast 1/16 section corner of section 32, at intersection with the East and West center line of the Southeast ¼ of section 32.

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 22 inches in the ground, encircle with a collar of stone, 2 ½ foot base, to the top, with cap marked:

T 1 N R 2 E
SE 1/16 S 32
2004

Deposit a Deep-1 magnet at the base of the aluminum post.

Set a steel T fence post alongside the aluminum post.

**SURVEY OF THE SURVEY OF THE SUBDIVISION OF SECTION 32,
TOWNSHIP 2 SOUTH, RANGE 2 WEST,
UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Corner is located on near level ground, East, 1.31 chains distance from the center of Deep Creek, 15 links wide, course S. 18° W., among greasewood.

40.101 The Center-East 1/16 section corner of section 32.

From the true point for the South 1/16 section corner of sections 32 and 33.

S. 89°51.7' W., on the East and west center line of the Southeast ¼ of section 32.

19.929 The Southeast 1/16 section corner of section 32.

39.858 The Center-South 1/16 section corner of section 32.

From the Center-West 1/16 section corner of section 32.

N. 0°14.5' E., on the North and South center line of the Northwest ¼ of section 32.

40.099 The West 1/16 section corner of sections 29 and 32.

GENERAL DESCRIPTION

The area encompassed in this survey is located in Uintah County, approximately 14 miles westerly from the city of Vernal, Utah. Access to the area is provided by a number of county roads, which reach northerly from State Highway No. 121, near the vicinity of the rural community of Lapoint, Utah. The terrain in the region is predominately comprised of rolling contour, dominated by a few prominent ridge networks. The area is drained primarily by Deep Creek, which is fed by several smaller gulches, and drains generally in a southerly direction. The elevation in the area ranges from about 5500 to 6500 feet. Vegetation consists primarily of juniper timber, sagebrush, greasewood, with Russian Olive, Tamarisk, and some sparse and isolated pockets of cottonwood timber occurring in some of the irrigated areas and along Deep Creek. The area is utilized for agricultural related activities such as the cultivation of hay and alfalfa, livestock grazing, as well as an industry of irrigation type activities, with a number of ditches, canals and water pipelines apparent throughout the region.

The surveyed area lies within the "Lapoint, Utah Quadrangle" and "Lake Mountain, Utah Quadrangle" 7.5 minute series United States Geological Survey (Topographic) maps.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Clint D. Markham	Survey Technician
Jonas D. Grant Jr.	Survey Aid
Adrian M Kurip	Survey Aid

CERTIFICATE OF SURVEY

I, **David W. Ginther, Cadastral Surveyor**, hereby certify upon honor that, in pursuance of special instructions bearing the date of the **30th day of April, 2004**, I have **executed a dependent resurvey of portions of the baseline through Range 2 East, west boundary, subdivisional lines, section subdivisional lines, and the survey of the subdivision of certain sections in Township 1 North, Range 2 East**, of the **Uintah Special Meridian**, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

03/03/05

Date

David W. Ginther

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the dependent resurvey of portions of the baseline through Range 2 East, west boundary, subdivisional lines, section subdivisional lines and the survey of the subdivision of certain sections in Township 1 North, Range 2 East, Uintah Special Meridian, Utah, executed by *David W. Ginther, Cadastral Surveyor*, having been critically examined and found correct, are hereby approved.

September 26, 2005

Date

David W. Webb

Chief Cadastral Surveyor for Utah

~~CERTIFICATE OF TRANSCRIPT~~

~~I certify that the foregoing transcript of the field notes of the above described surveys in *T. 1 N., R. 2 E., Uintah Special Meridian, Utah*, is a true copy of the original field notes.~~

~~_____~~
Date

~~_____~~
(Cadastral Surveyor)