

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

## FIELD NOTES

OF

THE DEPENDENT RESURVEY OF A PORTION OF THE SOUTH AND WEST BOUNDARIES,  
A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 19, 20, 29, 30, 31 AND 32

IN

**TOWNSHIP 1 SOUTH, RANGE 7 WEST**

OF THE UINTAH SPECIAL MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

**John F. Carroll**  
**Cadastral Surveyor**

Under special instructions dated **April 30, 2004**, approved **April 30, 2004**, which provided for the surveys included under Group Number **976**, and assignment instructions dated **April 30, 2004**

Survey commenced **August 16, 2004**  
Survey completed **February 3, 2005**

## INDEX DIAGRAM

Township 1 South, Range 7 West  
 Uintah Special Meridian, Utah

<b>6</b>	<b>5</b>	<b>4</b>	<b>3</b>	<b>2</b>	<b>1</b>
<b>7</b>	<b>8</b>	<b>9</b>	<b>10</b>	<b>11</b>	<b>12</b>
<b>18</b>	<b>17</b>	<b>16</b>	<b>15</b>	<b>14</b>	<b>13</b>
25 24	22 23				
5 19	22 20	14 21	22	23	24
4 21	19 20	13			
4 30	18 29	13 28	27	26	25
3 17	16 16	11 12	9		
<b>31</b>	15 <b>32</b>	11 <b>33</b>	9 <b>34</b>	<b>35</b>	<b>36</b>
8	7 6	6 5	5		

The Subdivision of Section 19.....Page 25  
 The Subdivision of Section 20.....Page 27  
 The Subdivision of Section 29.....Page 29  
 The Subdivision of Section 30.....Page 30  
 The Subdivision of Section 31.....Page 35  
 The Subdivision of Section 32.....Page 38

The following field notes are those of the dependent resurvey of a portion of the South and West boundaries, a portion of the subdivisional lines and the subdivision of sections 19, 20, 29, 30, 31 and 32, in T. 1 S., R. 7 W., Uintah Special Meridian, Utah.

### History of Surveys

	Surveyed by		Retr. or Resurveyed by
<b>SOUTH BOUNDARY</b>			
All	A. J. Stewart & A. L. Booth	1903	
<b>EAST BOUNDARY</b>			
All	A. J. Stewart & A. L. Booth	1903	
All			G. C. Swan & F. C. Ferron 1904
<b>WEST BOUNDARY (Uintah Special Meridian)</b>			
All	G. C. Swan & F. C. Ferron	1903	
<b>NORTH BOUNDARY (Uintah Special Base Line)</b>			
Portion	H. D. Heist	1903	
Portion	F. M. Lyman Jr.	1903 (cancelled)	
Portion	(This survey maybe cancelled)		G. C. Swan & F. M. Lyman Jr. 1904
Portion	F. M. Lyman Jr.	1905	F. M. Lyman Jr. 1905
<b>SUBDIVISION</b>			
All	G. C. Swan & F. C. Ferron	1904	
<b>LOCAL PLATS</b>			
Townsite Plat of Tabiona	1915	J. B. Peterson	C. E. (filed in Duchesne County Recorders Office)
Local Plats (B-E) unrecorded			
Jerry D. Allred and Associates	(B)	06-03-1986	
Jerry D. Allred and Associates	(C)	09-12-1989	
Jerry D. Allred and Associates	(D)	09-12-1989	
Jerry D. Allred and Associates	(E)	03-07-1992	
Local Recorded Plats ((Duchesne County Surveyors File) #)			
Clinton S. Peatross		(191)	
Jerry D. Allred and Associates		(258)	
Peatross Land Surveys		(353)	
Jerry D. Allred and Associates		(359)	
Clinton S. Peatross		(403)	
Jerry D. Allred and Associates		(506)	

Peatross Land Surveys	(620)
Peatross Land Surveys	(635)
Jerry D. Allred and Associates	(743)
Peatross Land Surveys	(792)
Jerry D. Allred and Associates	(803)
Registered Surveyors Corporation	(863)
Peatross Land Surveys	(1045)
Peatross Land Surveys	(1116)
Jerry D. Allred and Associates	(1317)

#### Corner Records

Jerry D. Allred		09/13/1989
Jerry D. Allred		09/14/1989
Jerry D. Allred	(A3)	08/29/1994
Jerry D. Allred	(A4)	08/29/1994
Jerry D. Allred	(A5)	08/29/1994
Jerry D. Allred	(A1)	08/31/1994
Jerry D. Allred	(A2)	08/31/1994
Jerry D. Allred		12/21/1998

Assessors Plats for Sections 19, 29, 30, 31, 32, 33, T. 1 S., R. 7 W., U.S.M., Ut.

Assessors Plat for Sections 4, 5, and 6, T. 2 S., R. 7 W., U.S.M., Ut.

## T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 976, dated April 30, 2004.

The direction of the lines were determined by mean geodetic inverse between corners. Global Positioning System (GPS) utilizing Real-time kinematic (RTK) was used throughout the survey. Cadastral Measurement Management (CMM) was utilized during the course of the survey.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the 1/4 sec. cor. of secs. 6 and 31, Tps. 1 and 2 S., R. 7 W., as determined by a tie to the National Geodetic Survey Control Station "S101", utilizing GPS, using RTK techniques, is as follows:

Latitude: 40°20'32.489" N. Longitude: 110°43'05.623" W.  
N.A.D. 1983 (CORS96) (EPOCH:2002.0000)  
Elevation: 6739 ft. (Geoid 03 NAVD 88)

The geographic position of National Geodetic Survey Control Station "S101" was determined utilizing Online Position Users System (OPUS). Base stations used were "RBUT RED BUTTE CORS ARP", "PUC CARBON COUNTY COU CORS ARP" and "MYTON 1 CORS ARP". The geographic position is as follows :

Latitude: 40°20'26.574" N. Longitude: 110°41'26.540" W.  
N.A.D. 1983 (CORS96) (EPOCH:2002.0000)  
Elevation: 6448 ft. (Geoid 03 NAVD 88)

---

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

---

Dependent Resurvey of a Portion of the West Boundary,  
T. 1 S., R. 7 W., Uintah Special Meridian, Utah

---

Reestablishment of the Resurvey Executed by  
G. C. Swan and F. C. Ferron in 1903

---

Beginning at the cor. of secs. 25, 30, 31 and 36, T. 1 S.,  
Rs. 7 and 8 W., monumented with a rebar, 5/8 in. diam., firmly  
set, projecting 4 ins. above ground, with plastic cap mkd.  
155666, with a limestone, 18X10X6 ins., clearly mkd. with 5  
notches on the south and 4 notches on the north edges, from  
which the original bearing trees

A pinon, 16 ins. diam., bears N. 50° E., 103 lks.  
dist., with scribe marks WS3 visible on partially  
healed blaze (Record; 123 lks.)

A pinon, 10 ins. diam., bears S. 12° E., 143 lks.  
dist., with illegible scribe marks visible on partially  
healed blaze. (Record; S. 32° E., 137 lks.)

The cor. was recovered by Peatross Land Surveys as recorded in  
Duchesne County Survey File Number 635 and by Jerry D. Allred  
and Associates as recorded in Duchesne County Survey File  
Number 803, and is accepted as a faithful and careful  
perpetuation of the original cor.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25  
ins. in the ground with magnet at base, in a collar of stone,  
2 ft. base, with brass cap mkd.:

T1S	
T8W R7W	
S25	S30
-----	
S36	S31
2004	

Bury rebar and cap on north side of stainless steel post.

Bury mkd. stone on east side of stainless steel post.

Cor. is located on gentle east slope in pinon and juniper, 3  
ft. South of fence, bears E-W, and 15 ft. South of a dirt  
road, 7 ft. wide, bears E-W.

N. 0°02.1' W., bet. secs. 25 and 30.

**20.087** Point for the S 1/16 sec. cor. of secs. 25 and 30. Not  
monumented.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

- 40.174** The 1/4 sec. cor. of secs. 25 and 30, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, flush with ground, in a collar of stone, with aluminum cap mkd. T1S 1/4 DUCHESNE COUNTY SURVEY S25 S30 R8W R7W 1994, on August 31, 1994 in the Duchesne County Survey Monument Record, has been utilized by numerous local surveys, and is accepted as a careful and faithful perpetuation of the original cor.

---

N. 0°11.7' E., bet. secs. 25 and 30, beginning new measurement.

- 20.020** True point for the N 1/16 sec. cor. of secs. 25 and 30, falls within the banks of the Duchesne River, where it is impractical to monument.

- 40.040** The cor. of secs. 19, 24, 25 and 30, monumented with a spindle, firmly set, 3 ins. below paved surface, from which the local reference objects

A pipe post, bears N. 20° E., 26.4 lks. dist.

A power pole, 14 ins. diam., bears S. 30° E., 27.0 lks. dist. to a nail and washer.

A slightly bent fence cor., bears E and SE, bears S. 1° E. 24.6 lks. dist.

No remaining evidence of other local reference objects was recovered.

This cor. was recovered by Jerry D. Allred as an iron rod below asphalt road surface. He set a spindle flush with asphalt road surface, as recorded in the Duchesne County Monument Survey Record on December 21, 1998. The spindle has been utilized by numerous local surveys as the sec. cor. and is accepted as the best available evidence of the position of the original cor.

Cor. is located in center of paved road, bears E-W.

---

N. 0°04.2' W., bet. secs. 19 and 24.

- 20.034** Point for the S 1/16 sec. cor. of secs. 19 and 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with brass cap mkd.:

S 1/16  
S24 | S19  
2004

Cor. is located in pasture, 4 ft. North of a fence cor., bears E and S.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

**40.068** The 1/4 sec. cor. of secs. 19 and 24, monumented with a rebar, 5/8 in. diam., firmly set, 2 ins. below ground, with plastic cap mkd. PEATROSS 155666, as recovered by Daniel W. Peatross, P.L.S. 259966, as recorded in Duchesne County Survey File Number 863, and is accepted as the best available evidence of the position of the original cor. Not remonumented.

Cor. is located in pasture at intersection of fences bearing N and E.

---

Dependent Resurvey of a Portion of the South Boundary,  
T. 1 S., R. 7 W., Uintah Special Meridian, Utah

---

Reestablishment of the Survey Executed by  
A. J. Stewart and A. L. Booth in 1903

---

From the cor. of secs. 3, 4, 33 and 34, monumented with a rebar, 5/8 in. diam., firmly set, projecting 5 ins. above ground, with plastic cap mkd. PEATROSS 155666, and a sandstone, 18X10X5 ins. clearly mkd. with 3 notches on the east and 3 notches on the west edges, along the south side of the rebar and cap, with a reference mound of stone to the west, as recorded in Duchesne County Survey File Number 1045, and is accepted as a faithful and careful perpetuation of the original cor.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with brass cap mkd.:

T1S R7W	
S33	S34
-----	
S4	S3
T2S	
2004	

Bury rebar and plastic cap inside stainless steel post.

Bury mkd. stone along south side of stainless steel post.

Cor. is located 1 ft. South of the intersection of fences bearing N-S, and E-W.

S. 89°56.5' W., bet. secs. 4 and 33.

**39.936** Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist.; there is no remaining evidence of the original cor.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, in a collar of stone, with aluminum cap mkd.:

T1S R7W  
S33  
1/4 ———  
S4  
T2S  
2005

Cor. is located in pasture, 3 ft. East of the intersection of fences bearing N-S and E.

**79.872** The cor. of secs. 4, 5, 32 and 33, at proportionate dist., there is no remaining evidence of the original cor.

Set an aluminum drive in monument, 30 ins. long, 5/8 in. diam., 25 ins. in the ground, with aluminum cap mkd.:

T1S  
R7W  
S32 | S33  
———  
S5 | S4  
T2S  
2004

Cor. is located at intersection of fences, bearing E-W, and N., at SW fence cor. of sewage pond.

S. 89°56.5' W., bet. secs. 5 and 32.

**19.968** Point for the E 1/16 sec. cor. of secs. 5 and 32, falls on paved road surface.

Set a PK-nail flush with road surface.

from which the reference objects

A reflector paddle, bears N. 46°35.5' E., 51.2 lks. dist.

A power pole, 12 ins. diam., bears S. 46°49.0' E., 145.2 lks. dist. to a PK-nail.

A reflector paddle, bears S. 22°39.5' E., 17.2 lks. dist.

Cor. is located on paved road surface, bears NW and SE.

**39.936** Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

Note: The original witness cor. to the 1/4 sec. cor. of secs. 5 and 32 was not recovered.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 27 ins. in the ground with magnet at base, in a mound of stone, 3 ft. diam., to top, with brass cap mkd.:

T1S R7W  
S32  
1/4 ———  
S5  
T2S  
2004

From this point, a rebar, 1/2 in. diam., firmly set, with plastic cap mkd. PEATROSS RLS 155666, bears N. 84°38.6' W., 0.171 chs. dist., as recorded in Duchesne County Survey File Number 1045, set using incorrect procedures and is not utilized during the course of this resurvey.

Cor. is located on the west bank of the Duchesne River.

**59.904** Point for the W 1/16 sec. cor. of secs. 5 and 32.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with brass cap mkd.:

S32  
W1/16 ———  
S5  
2004

from which the reference objects

A railroad tie fence post, at west end of E-W fence, bears S. 45° W., 18.8 lks. dist., to a PK-nail.

A peeler pole fence post, 4 ins. diam., bears N. 45° W., 39.1 lks. dist., to a PK-nail.

Cor. is located in pasture, 10 ft. North of a fence, bears E-W, 16 ft. South of a fence, bears E-W, and 68.8 lks. S. 70° E. of intersection of fences, bears E-W, and N.

**79.872** Point for the cor. of secs. 5, 6, 31 and 32 at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, in a collar of stone, with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

T1S R7W	
S31	S32
-----	
S6	S5
T2S	
2004	

From this point, a rebar, 1/2 in. diam., firmly set, with plastic cap mkd. PEATROSS RLS 155666, bears N. 88°21.7' W., 0.315 chs. dist., as recorded in Duchesne County Survey File Number 1045, set using incorrect procedures and is not utilized during the course of this resurvey. No evidence of the intersection of fences was recovered as recorded in Duchesne County Survey File Number 1045.

From this same point, a quartzite stone, 16X14X8 ins., firmly set, projecting 4 ins. above ground, clearly mkd. 1/4 on west face, from which a pinyon, 7 ins. diam., bears S. 57° W., 46 lks. dist. (record; S. 57° W., 60 lks. dist.), with scribe marks visible on open blaze, bears S. 0°03.6' E., 39.673 chs. dist. No positive remains of the northeast bearing tree was recovered.

---

S. 89°56.5' W., bet. secs. 6 and 31.

**39.936** The 1/4 sec. cor. of secs. 6 and 31, monumented with a quartzite, 16X8X6 ins., firmly set, clearly mkd. 1/4 on north face, in a mound of stone, 3 ft. diam. (Record; no mound of stone), from which the original bearing trees

A pinon, 10 ins. diam., bears N. 1° E., 59 lks. dist., with illegible marks visible on partially healed blaze. (Record; 25 lks. dist.)

No remains of southeast bearing tree was recovered.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to solid rock with magnet at base, in a mound of stone, 3 ft. diam., to top, with brass cap mkd.:

T1S R7W	
S31	
1/4	-----
S6	
T2S	
2004	

Bury mkd. stone on north side of stainless steel post.

Rebuild mound of stone to 3 ft. diam. around stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

Cor. is located on north slope in pinon and juniper, 1 ft. South of a fence, bears E-W.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 1 S., R. 7 W., Uintah Special Meridian, Utah

---

Reestablishment of the Survey Executed by  
G. C. Swan and F. C. Ferron in 1904

---

From the cor. of secs. 3, 4, 33 and 34, Tps. 1 and 2 S., R. 7 W.

N. 0°00.9' E., bet. secs. 33 and 34.

- 40.043** The 1/4 sec. cor. of secs. 33 and 34, monumented with a limestone, 16X8X6 ins., firmly set, clearly mkd. 1/4 on west face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, with brass cap mkd.:

T1S R7W  
1/4  
S33 | S34  
2004

Bury mkd. stone along east side of stainless steel post.

Cor. is located on a flat, with sagebrush to the east and an alfalfa field to the west, in a fence, bears N-S.

---

N. 0°00.5' W., beginning new measurement.

- 40.073** The cor. of secs. 27, 28, 33 and 34, determined at record bearing and dist. from the NE, SE and NW original bearing trees, from which

A cedar, 15 ins. diam. bears N. 25 1/2° E., 82 lks. dist., with scribe marks 7S S2 BT visible on partially healed over blaze.

A pinon, 18 ins. diam., bears S. 14° E., 35 lks. dist., with scribe marks 1S 7W S34BT visible on partially healed over blaze.

A cedar, 12 ins. diam., bears N. 24° W., 74 lks. dist., with scribe marks T 7 2 BT visible on partially healed over blaze on west side of bearing tree and the mark W visible on different blaze (facing cor. on south side of bearing tree)

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 1 S., R. 7 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

from which the original SW bearing tree

A pinon, 20 ins. diam. branch, bears S. 40° W., 59 lks. dist., with scribe marks T1SR7WS33BT visible on partially healed over blaze. (Record; 62 lks.)

Note: The original marked stone was not recovered. All four of the original bearing trees were recovered. The point (within a small locus) for the cor. could not be determined using the record bearing and dist. of the original bearing trees. Using the record bearing and dist. of NE, SE and NW bearing trees, the cor. point could be determined within a small locus. The determination was made to use the NE, SE and NW original bearing and dist. and make a new tie to the original SW bearing tree. This method of cor. restoration isolates the original error in dist. to the SW bearing tree.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with brass cap mkd.:

T1S R7W	
S28	S27
S33	S34
2004	

Note: A limestone, 20X8X8 ins., laying on the ground in the vicinity of the point for the cor. was recovered. There were no identifying marks on the limestone.

Cor. is located on north easterly slope in juniper and pinon, 2 ft. South of intersection of fences, bears S and W.

From the cor. of secs. 4, 5, 32 and 33, hereinbefore described.

N. 0°42.4' E., bet. secs. 32 and 33.

**20.192** Point for the S 1/16 sec. cor. of secs. 32 and 33, falls on south tire track of dirt road, bears W.

Set a rebar, 18 ins. long, 5/8 in. diam., 19 ins. in the ground, with 2 ins. diam. aluminum cap mkd.:

S 1/16	
S32	S33
2004	

from which the reference objects

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

A fence cor., bears South, 6 lks. dist., fence bears S and W.

A fence cor. bears North, 21 1/5 lks. dist., fence bears N and W.

Cor. is located on alfalfa pasture.

- 40.384** Point for the 1/4 sec. cor. of secs. 32 and 33, at intersection of fences bearing N, E, S and W. This point is in agreement with the original cor. of secs. 28, 29, 32 and 33, and has been utilized by private surveys as recorded in Duchesne County Survey File Numbers 566 and 620, and is accepted as the best available evidence of the original cor.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with brass cap mkd.:

T1S R7W  
1/4  
S32 | S33  
2004

Cor. is located at the easterly edge of pasture, with pinon, cottonwood, aspen and cedar to the NE.

---

N. 0°54.0' W., beginning new measurement.

- 40.113** The cor. of secs. 28, 29, 32 and 33, monumented with a limestone, 16X8X7 ins., loosely set, clearly mkd. with 4 notches on the east and 1 notch on the south edges, from which the original bearing trees

A forked juniper, with 9 ins. diam. fork, bears N. 10° E., 17 lks. dist., with illegible scribe marks visible on partially healed over blaze. (Record; cedar)

A cedar, 15 ins. diam., bears S. 38° E., 9 lks. dist., with dim and illegible scribe marks visible.

A forked cedar, with 4 ins. diam. fork, bears S. 37° W., 10 lks. dist., with no marks visible on open blaze.

A cedar, 12 ins. diam., bears N. 32° W., 17 lks. dist., with marks R7W S29BT visible on partially healed over blaze.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with brass cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH  
CHAINS

T1S R7W	
S29	S28
S32	S33
2004	

Bury mkd. stone on south side of stainless steel post.

Cor. is located on south slope in cedar, juniper and pinon, at the intersection of fences bearing E-W.

From the cor. of secs. 27, 28, 33 and 34, hereinbefore described.

N. 88°55.7' W., bet. secs. 28 and 33.

**39.883** The point for the 1/4 sec. cor. of secs. 28 and 33, determined at record bearing and dist. from the original NE bearing tree, from which

A cedar, 26 ins. diam., bears N. 30° E., 59 lks. dist., with dim scribe marks 1/4 S visible on partially healed over blaze.

from which the remains of the original SW bearing tree

A pine, dead and down, 6 ins. diam., bears S. 42° W., 43 lks. dist., with scribe marks 1/4S33BT visible on open blaze. No remains of the pine root crown were recovered. This bearing tree is on a south slope. It appears that the bearing tree is not in its original position. The determination was made to not use this original bearing tree and to reestablish the cor. at record bearing and dist. from the original NE bearing tree. The determination was made to make a new tie to the original SW bearing tree. (Record; S. 42° W., 36 lks.)

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, in a mound of stone, 3 ft. diam., to top, with brass cap mkd.:

T1S R7W	
S28	
1/4	—
S33	
2004	

Cor. is located on south slope in juniper and pinon, 9 ft. South of a fence, bears E-W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

S. 89°21.0' W., beginning new measurement.

**40.120** The cor. of secs. 28, 29, 32 and 33, hereinbefore described.

---

N. 0°43.7' E., bet. secs. 28 and 29.

**39.495** The point for the 1/4 sec. cor. of secs. 28 and 29, determined at record bearing and dist. from the original NE bearing tree, from which

A pinon, 12 ins. diam., bears N. 65° E., 38 lks. dist., with scribe marks 1/4S28BT visible on partially healed blaze. (Record; cedar)

from which the original SW bearing tree

A cedar, 8 ins. diam., dead and down, bears S. 70° W., 55 lks. dist., with scribe marks 1/4S29BT visible on open blaze. Note: This bearing tree is on a steep northerly slope. It appears that the bearing tree is not in its original position. The determination was made to not use this original bearing tree and to reestablish the cor. at record bearing and dist. from the original NE bearing tree. The determination was made to make a new tie to the original SW bearing tree. (Record; 53 lks. dist.)

At the corner point

Set a stainless steel post, 30 ins. long, 26 ins. in the ground with magnet at base, with brass cap mkd.:

T1S R7W  
1/4  
S29 | S28  
2004

Cor. is located on a steep northerly slope in pinon and cedar, in a fence, bears N-S.

---

N. 0°46.3' W., beginning new measurement.

**40.260** The cor. of secs. 20, 21, 28 and 29, monumented with a galvanized iron pipe, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with galvanized iron cap, 2 1/2 ins. diam., mkd.:

20 | 21  
----- T1S  
32 | 33

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

A limestone, clearly mkd. with 4 notches on one side and 2 notches on another side is along the south side of the galvanized iron pipe. The galvanized iron pipe and limestone are encased in concrete. 1959 is stamped in concrete. Similar galvanized iron pipe have been recovered in the immediate area. These iron pipe were set during a remonumentation project by the BIA in 1959. No records of where BIA monuments were set was recovered. The galvanized iron pipe and cap are accepted as a faithful and careful perpetuation of the original cor.

Add the marks 2004 to galvanized iron cap.

Cor. is located on a slight SW slope in grass and sagebrush, at intersection of fences, bearing S and W.

N. 0°04.4' E., bet. secs. 20 and 21.

**19.996** Point for the S 1/16 sec. cor. of secs. 20 and 21. Not monumented.

**39.992** The 1/4 sec. cor. of secs. 20 and 21, monumented with a galvanized iron pipe, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with galvanized iron cap mkd.:

1/4	T1S
S20	S21
R7W	

A limestone, 15X10X6 ins., firmly set, dimly mkd. 1/4 on south face. The galvanized iron pipe and mkd. stone are encased in concrete, with a reference mound of stone to the north. (Record; reference mound of stone to the west). Similar galvanized iron pipe have been recovered in the immediate area. These iron pipe were set during a remonumentation project by the BIA in 1959. No records of where BIA monuments were set was recovered. The galvanized iron pipe and cap are accepted as a faithful and careful perpetuation of the original cor.

Add the marks 2004 to the galvanized iron cap.

Cor. is located in grass and on a slight southerly slope.

From the cor. of secs. 5, 6, 31 and 32, hereinbefore described.

N. 0°10.6' W., bet. secs. 31 and 32.

**20.089** Point for the S 1/16 sec. cor. of secs. 31 and 32.

Set an aluminum drive in rod, 30 ins. long, 5/8 in. diam., 31 ins. in the ground, with 2 ins. diam. aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

S 1/16  
S31 | S32  
2004

Cor. is located 4 ft. South of intersection of fences bearing E-W, and N, in line with the fence bearing N.

**40.178** The point for the 1/4 sec. cor. of secs. 31 and 32.

Note: This cor. was recovered and remonumented by Jerry D. Allred as recorded in the Duchesne County Survey Monument Record on September 14, 1989. This record indicates that "Found old fence corner with unmarked stone at the position of the corner." This same record also indicates "Set a 1" diam. aluminum rod with plastic cap alongside stone for the corner and re-built stone mound around corner." The aluminum rod with plastic cap were not recovered. Remains of the re-built mound of stone and old fence corner were recovered. The recovered fence cor., remains of the mound of stone and local record dist. agrees with the sketch for the Monument Record. Numerous other local surveyors have utilized this point as the 1/4 sec. cor. of secs. 31 and 32. The center of the remains of the mound of stone is accepted as the best available evidence of the original cor.

At the corner point

Set a rebar, 18 ins. long, 14 ins. in the ground, in a mound of stone, 3 ft. diam., with 2 ins. diam. aluminum cap mkd.:

T1S R7W  
1/4  
S31 | S32  
2004

Cor. is located on a flat in cottonwood and at the intersection of fences, bearing S and W.

---

N. 0°04.2' E., beginning new measurement.

**20.131** The N 1/16 sec. cor. of secs. 31 and 32, monumented with a PK-nail, 1/2 in. below top of paved surface. This point was reestablished by Jerry D. Allred, on unrecorded plat dated September 12, 1989. This point is in agreement with the unrecorded Townsite of Tabiona plat by J. B. Peterson C. E. on November 6, 1915. The PK-nail is accepted as a faithful and careful reestablishment of the cor. Not remonumented.

---

N. 0°04.2' E., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

**19.996** The cor. of secs. 29, 30, 31 and 32, monumented with a rebar, 1/2 in. diam., firmly set, 5 ins. below ground, with plastic cap and illegible marks. This point was originally recovered by Jerry D. Allred as recorded in the Duchesne County Survey Monument Record dated September 13, 1989. This point has been utilized on numerous local survey plats and is in agreement with the unrecorded Townsite of Tabiona plat by J. B. Peterson C. E. and the recovered original 1/4 sec. cor. of secs. 29 and 32, and is accepted as the best available evidence of the position of the original cor. Not remonumented.

from which the local reference objects

A power pole, 12 ins. diam., bears S. 44°34.7' W., 60.2 lks. dist. to a nail and washer. (Local Record; 50.0 lks.)

A brace pole, bears N. 46°42.7' W., 48.0 lks. dist.

From the cor. of secs. 28, 29, 32 and 33, hereinbefore described.

S. 89°44.7' W., bet. secs. 29 and 32.

**39.955** The 1/4 sec. cor. of secs. 29 and 32, monumented with a sandstone, 16X8X8 ins., loosely set, dimly mkd. 1/4 on north face, in a mound of stone, from which the original bearing trees

A forked pinon, with 14 ins. diam. branch, bears N. 35° W., 29 lks. dist., with scribe marks 1/4S29 T visible on partially healed blaze. (Record; 20 lks.)

A cedar, 7 ins. diam., bears S. 34° E., 39 1/2 lks. dist., with scribe marks 1/4S32 visible on partially healed blaze. (Record; pine, South, 25 lks.)

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, in a mound of stone, 3 ft. diam., to top, with brass cap mkd.:

T1S R7W  
S29  
1/4 ———  
S32  
2004

Bury mkd. stone alongside stainless steel post.

Cor. is located on a southwesterly slope in cedar and pinon, 20 ft. South of fence, bears E-W, and 8 ft. East of the top of a cut bank (for a buried water line).

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

S. 89°52.4' W., beginning new measurement.

- 19.923** Point for the W 1/16 sec. cor. of secs. 29 and 32, falls on gravel road, bears E-W.

Set a rebar, 6 ins. long, 5/8 in. diam., 7 ins. in the ground, with 2 ins. diam. aluminum cap mkd.:

S29  
W1/16 ———  
S32  
2004

from which the reference objects

A cedar fence post, 4 ins. diam., bears N. 4° W., 19.2 ft. dist. to PK-nail.

A power pole, 10 ins. diam., S. 70° W., 28.8 ft. dist. to PK-nail.

- 39.846** The cor. of secs. 29, 30, 31 and 32, hereinbefore described.
- 

S. 89°51.8' W., bet. secs. 30 and 31.

- 19.981** The E 1/16 sec. cor. of secs. 30 and 31, monumented with a spike, firmly set, 4 ins. below paved surface. This point was set by Jerry D. Allred as recorded in Duchesne County Survey File Number 359. This point has been utilized on numerous local survey plats and is in agreement with the unrecorded Townsite of Tabiona plat by J. B. Peterson C. E., and is accepted as a careful and faithful determination of the position of the cor.
- 

S. 89°44.7' W. beginning new measurement.

- 19.939** The 1/4 sec. cor. of secs. 30 and 31, at intersection of fences, bearing N, E, S and W. This point was utilized by Clinton S. Peatross as recorded in Duchesne County Survey File Number 191, and is accepted as the best available evidence of the position of the original cor.

At the corner point

Set a rebar, 18 ins. long, 5/8 in. diam., 14 ins. in the ground, with 2 ins. diam. aluminum cap mkd.:

T1S R7W  
S30  
1/4 ———  
S31  
2004

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

Cor. is located on west side of 10 ins. diam. wooden post and in cottonwood.

---

S. 89°53.4' W., beginning new measurement.

**20.119** Point for the W 1/16 sec. cor. of secs. 30 and 31.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 21 ins. in the ground with magnet at base, in a collar of stone, with brass cap mkd.:

S30  
W1/16 ———  
S31  
2004

Cor. is located on a steep northerly slope in scruboak and 15 ft. North of a fence, bears E-W.

**35.661** The cor. of secs. 25, 30, 31 and 36, hereinbefore described.

---

From the cor. of secs. 29, 30, 31 and 32, hereinbefore described.

N. 0°10.7' E., bet. secs. 29 and 30.

**19.969** Point for the S 1/16 sec. cor. of secs. 29 and 30, falls on gravel road, 20 ft. wide, bears N-S, over a culvert.

Set a 60-penny nail, 1 in. below road surface.

from which the reference objects

A cedar fence post, 6 ins. diam., bears East, 22.6 lks. dist. to a PK-nail.

A railroad tie, bears S. 58° W., 37.3 lks. dist. to a PK-nail on cor. of railroad tie.

**39.938** The 1/4 sec. cor. of secs. 29 and 30, monumented with a rebar, 5/8 in. diam., with plastic cap mkd. S 3817, as recorded in Duchesne County Survey File Number 359. This point has been utilized on numerous local survey plats and is accepted as the best available evidence of the position of the original cor.

---

N. 0°26.0' E., beginning new measurement.

**19.964** Point for the N 1/16 sec. cor. of secs. 29 and 30. Not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

**39.928** The cor. of secs. 19, 20, 29 and 30, monumented with an iron pipe, 1/2 in. diam., firmly set, projecting 4 ins. above ground, at intersection of fences bearing N, S, E-W, by Jerry D. Allred as recorded in Duchesne County Survey File Number 359. The iron pipe is in agreement with original cors. to the N and E, and local cors. to the S and W, and is accepted as the best available evidence of the position of the original cor.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. diam., with brass cap mkd.:

T1S R7W	
S19	S20
S30	S29
2004	

Bury iron pipe inside stainless steel post.

A cobblestone, 14X12X8 ins., clearly mkd. with 5 notches on one side, was recovered in the vicinity. The determination was made that the cobblestone had been moved and should not be utilized as the cor. of secs. 19, 20, 29 and 30. The cobblestone was buried on the west side of the stainless steel post.

From this point, a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above ground, in a collar of stone, with aluminum cap mkd. LS 148951, bears S. 89°34.5' W., 0.251 chs. dist. This monument was set by Clinton S. Peatross as recorded in Duchesne County Survey File Number 792 and utilized by Jerry D. Allred as recorded in Duchesne County Survey File Number 1317. This monument does not agree existing original corners the N and E, and local cors. to the S and W, and existing fences. The determination was made that this monument was set using incorrect procedures and is not utilized during the course of this resurvey.

From the cor. of secs. 20, 21, 28 and 29, hereinbefore described.

S. 89°53.5' W., bet. secs. 20 and 29.

**19.832** Point for the E 1/16 sec. cor. of secs. 20 and 29. Not monumented.

**24.790** Point for the E-W-E 1/256 sec. cor. of secs. 20 and 29.

Set a stainless steel post, 30 ins. long, 24 ins. in the ground with magnet at base, with brass cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

S20  
E-W-E 1/256             
S29  
2004

Cor is located in grass and weeds, 5 ft. South of a fence, bears E-W.

**29.748** Point for the W-E 1/64 sec. cor. of secs. 20 and 29. Not monumented.

**39.664** Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, with brass cap mkd.:

T1S R7W  
S20  
1/4             
S29  
2004

Cor. is located 4 ft. North of a fence, bears E-W, 2 ft. East of an irrigation ditch, 2 ft. wide, flows South, and 2 1/2 ft. South of irrigation ditch, 2 ft. wide, flows West.

**59.496** Point for the W 1/16 sec. cor. of secs. 20 and 29. Not monumented.

**64.454** Point for the E-W-W 1/256 sec. cor. of secs. 20 and 29.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, with brass cap mkd.:

S20  
E-W-W 1/256             
S29  
2004

Cor. is located on south bank of irrigation channel, with canal approximately 140 ft. West.

**69.412** Point for the W-W 1/64 sec. cor. of secs. 20 and 29. Not monumented.

**79.328** The cor. of secs. 19, 20, 29 and 30, hereinbefore described.

---

N. 89°48.4' W., bet. secs. 19 and 30.

**20.167** Point for the E 1/16 sec. cor. of secs. 19 and 30, falls on paved surface in the vicinity of underground utilities.

Set a PK-nail flush with paved surface.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH  
CHAINS

from which the reference object

A concrete cylinder, 14 ins. diam., firmly set, 4 ins. above ground, with recessed US Coast and Geodetic Bench Mark brass cap, 3 1/4 ins. diam., mkd. V101 1962, bears S. 17°38.2' E., 73.9 lks. dist.

Cor. is located on easterly edge of paved surface, 19 ft. East of painted double yellow line in center of 5000 North, and south entrance to Tabiona Redcliff Cemetery.

- 40.334** The 1/4 sec. cor. of secs. 19 and 30, monumented with a spindle, 4 ins. below pave surface. This monument was set by Jerry D. Allred as recorded in Duchesne County Survey Monument Record on August 29, 1994, has been accepted as the 1/4 sec. cor. of secs. 19 and 30 on numerous local survey plats and is accepted as the best available evidence of the position of the original cor.

from which the local reference objects

A fence cor., bears N. 2°10.9' E., 25.1 lks. dist. to a nail and washer.

A cottonwood, 25 ins. diam., bears N. 83°18.9' E., 198.6 lks. dist. to a nail and washer.

A concrete headwall, bears S. 11°54.7' E., 60.2 lks. dist. to a chiseled X.

A power pole, 12 ins. diam., bears S. 76°54.6' W., 85.4 lks. dist. to a nail and washer.

Cor. is located in center of pave road, 18 ft. wide, bears E-W.

---

N. 89°59.0' W., beginning new measurement.

- 20.081** Point for the W 1/16 sec. cor. of secs. 19 and 30, falls on paved surface.

Set a PK-nail, flush with paved surface.

from which the reference objects

A power pole, 12 ins. diam., bears S. 30° E., 25.2 lks. dist. to a PK-nail.

A cedar fence post, 4 ins. diam., bears N. 55° E., 36.3 lks. dist. to PK-nail on SW side.

Cor. is located on paved surface, 20 ft. wide, bears E-W.

- 35.544** The cor. of secs. 19, 24, 25 and 30, hereinbefore described.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH  
CHAINS

---

From the cor. of secs. 19, 20, 29 and 30, hereinbefore described.

N. 0°09.7' W., bet. secs. 19 and 20.

- 20.042** Point for the S 1/16 sec. cor. of secs. 19 and 20. Not monumented.
- 40.084** The 1/4 sec. cor. of secs. 19 and 20, monumented with a galvanized iron pipe, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with galvanized iron cap mkd.:

1959  
1/4 |  
19 | 20 T1S  
R7W

A sandstone, 15X10X6 ins., clearly mkd. 1/4 on north face, alongside the galvanized iron pipe. The galvanized iron pipe and sandstone are encased in concrete. 1959 is stamped in concrete. Similar galvanized iron pipe have been recovered in the immediate area. These iron pipe were set during a remonumentation project by the BIA in 1959. No records of where BIA monuments were set was recovered. The galvanized iron pipe and cap are accepted as a faithful and careful perpetuation of the original cor.

Add the marks 2004 to the galvanized iron cap.

Cor. is located on a slight easterly slope at the intersection of fences, bearing N-S, and W.

---

N. 0°07.3' W., beginning new measurement.

- 20.092** The N 1/16 sec. cor. of secs. 19 and 20, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above ground, with aluminum cap mkd. RLS PEATROSS 259966, as recorded in Duchesne County Survey File Number 863, and is accepted as a faithful and careful determination of the position of the cor. Not remonumented.
- 

N. 0°09.5' W., beginning new measurement.

- 20.092** The cor. of secs. 17, 18, 19 and 20, monumented with a galvanized iron pipe, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with galvanized iron cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH  
CHAINS

1959		
18		17
-----		
19		20
R7W		

T1S

A sandstone, 16X10X8 ins., firmly set, clearly mkd. with 5 notches on the east and 3 notches on the south edges, along west side of galvanized iron pipe. The galvanized iron pipe and mkd. stone are encased in concrete. A rebar, 5/8 in. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd. RLS259966 PEATROSS, as recorded in Duchesne County Survey File Number 863, bears S. 45° W., 0.015 chs. dist., set using incorrect procedures and is not utilized during the course of this resurvey. (Note: This local survey did not recover the 1959 galvanized iron pipe.) Similar galvanized iron pipe have been recovered in the immediate area. The iron pipe were set during a remonumentation project by the BIA in 1959. No records of where BIA monuments were set was recovered. The galvanized iron pipe and cap are accepted as a faithful and careful perpetuation of the original cor.

Add the marks 2004 to the galvanized iron cap.

Cor. is located on a flat in greasewood and grass, at intersection of fences, bearing S and W.

From the 1/4 sec. cor. of secs. 17 and 20, monumented with a galvanized iron pipe, 2 1/2 ins. diam., firmly set in concrete, with galvanized iron cap mkd.:

1959	
17	
1/4	----- T1S
20	
R7W	

With a sandstone, 12X9X5 ins., clearly mkd. 1/4 on one face, loosely set, along north side of galvanized iron pipe.

Place sandstone, mkd. side down, along north side of galvanized iron pipe.

Add the marks 2004 to the galvanized iron cap.

Cor. is located on a gentle southerly slope in greasewood and grass.

N. 89°49.1' W., bet. secs. 17 and 20.

**39.869** The cor. of secs. 17, 18, 19 and 20.

S. 89°54.5' W., bet. secs. 18 and 19.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

**20.005** The E 1/16 sec. cor. of secs. 18 and 19, monumented with a rebar, 5/8 in. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd. RLS PEATROSS 259966, as recorded in Duchesne County Survey File Number 863, and is accepted as a faithful and careful determination of the position of the cor. Not remonumented.

---

S. 89°55.1' W., beginning new measurement.

**19.982** The 1/4 sec. cor. of secs. 18 and 19, monumented with a rebar, 5/8 in. diam., firmly set, projecting 5 ins. above ground, with aluminum cap mkd. RLS259966 PEATROSS, with a cobblestone, 12X10X5 ins., loosely set, clearly mkd. 1/4 on north face, in a mound of stone, with aluminum cap mkd. RLS Peatross 259966, as recorded in Duchesne County Survey File Number 863, and is accepted as a faithful and careful perpetuation of the position of the cor., from which the original bearing trees

A pine, 9 ins. diam., bears N. 50° W., 26 lks. dist., with scribe marks 1/4S18 visible on partially healed blaze. (Record; N. 6° W.)

A forked pinon, with 10 ins. diam. fork, bears S. 58° W., 25 lks. dist., with scribe marks 1/4S19BT visible on partially healed blaze. (Record; S. 65° W., 20 lks.)

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at base, in a mound of stone, 3 ft. diam., to top, with brass cap mkd.:

T1S R7W  
S18  
1/4 ———  
S19  
2004

Bury mkd. stone on south side of stainless steel post.

Bury rebar and aluminum cap inside stainless steel post.

Cor. is located on northeasterly slope in juniper and pinon, 1 ft. South of fence, bears E-W.

---

N. 89°39.4' W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

**20.106** The W 1/16 sec. cor. of secs. 18 and 19, monumented with a rebar, 5/8 in. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd. RLS PEATROSS 259966, with aluminum cap mkd. RLS Peatross 259966, as recorded in Duchesne County Survey File Number 863, and is accepted as a faithful and careful determination of the position of the cor. Not remonumented.

Cor. is located on NE slope, 7 ft. North of fence, bears E-W.

N. 89°40.1' W., beginning new measurement.

**15.542** The cor. of secs. 13, 18, 19 and 24, monumented with a rebar, 5/8 in. diam., firmly set, projecting 5 ins. above ground, with aluminum cap mkd. RLS259966 PEATROSS and is accepted as a faithful and careful perpetuation of the original cor., from which the original bearing tree

A pinon, 21 ins. diam., bears S. 1° E., 95 lks. dist., with faint scribe marks R7WBT S19 (on two different lines and marks from the bottom of blaze to top of blaze) on one vertical blaze.

At the corner point

Set a stainless steel post, 30 ins. long, 24 ins. in the ground with magnet at base, with brass cap mkd.:

T1S	
R8W	R7W
S13	S18
S24	S19
2004	

Bury rebar and aluminum cap inside stainless steel post.

Cor. is located on a steep west slope in juniper and pinon, at intersection of fences, bearing N-S and E-W.

---

Survey of the Subdivision of Section 19,  
T. 1 S., R. 7 W., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 19 and 30.

N. 0°05.0' E., on the N-S center line of sec. 19.

**20.008** Point for the center S 1/16 sec. cor. of sec. 19.

Set an aluminum drive in rod, 30 ins. long, 5/8 in. diam., 30 ins. in the ground, with 2 ins. diam. aluminum cap mkd.:

SURVEY OF THE SUBDIVISION OF SECTION 19,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

C  
S1/16|S19  
C  
2004

Cor. is located in pasture, 2 ft. North of a fence, bears E-W, and 6 1/2 ft. N. 70° E. of the center of the intersection of fences, bears N, S, E-W.

- 40.016** Point for the center 1/4 sec. cor. of sec. 19, at intersection with the E-W centerline of sec. 19. Not monumented.
- 60.042** The center N 1/16 sec. cor. of sec. 19, monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with aluminum cap mkd. RLS PEATROSS 259966, as recorded in Duchesne County Survey File Number 863, and is accepted as a faithful and careful determination of the position of the cor. Not remonumented.

---

N. 0°06.8' E., beginning new measurement.

- 20.026** The 1/4 sec. cor. of secs. 18 and 19.

---

From the 1/4 sec. cor. of secs. 19 and 20.

N. 89°53.8' W., on the E-W center line of sec. 19.

- 40.158** Point for the center 1/4 sec. cor. of sec. 19.
- 60.281** Point for the center W 1/16 sec. cor. of sec. 19. Not monumented.
- 75.806** The 1/4 sec. cor. of secs. 19 and 24.

---

From the W 1/16 sec. cor. of secs. 19 and 30.

N. 0°01.3' E., on the N-S center line of the SW 1/4 of sec. 19.

- 20.026** Point for the SW 1/16 sec. cor. of sec. 19, at intersection with the E-W center line of the SW 1/4 of sec. 19.

Set an aluminum drive in rod, 30 ins. long, 5/8 in. diam., 24 ins. in the ground, with 2 ins. diam. aluminum cap mkd.:

SW 1/16  
X  
S19  
2004

SURVEY OF THE SUBDIVISION OF SECTION 20,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

Cor. is located in pasture, 1 ft. North of fence, bears E-W, 7 ft. North of irrigation headgate, 10 ft. West of intersection of fences, bearing E-W, and S, and 7 ft. East of intersection of fences, bearing E-W, and N.

**40.047** Point for the center W 1/16 sec. cor. of sec. 19.

---

From the center S 1/16 sec. cor. of sec. 19.

N. 89°56.5' W., on the E-W center line of the SW 1/4 of sec. 19.

**20.103** The SW 1/16 sec. cor. of sec. 19.

**35.597** The S 1/16 sec. cor. of secs. 19 and 24.

---

Survey of the Subdivision of Section 20,  
T. 1 S., R. 7 W., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 20 and 29.

N. 0°00.3' E., on the N-S center line of sec. 20.

**20.019** Point for the center S 1/16 sec. cor. of sec. 20.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, with brass cap mkd.:

C  
S1/16|S20  
C  
2004

Cor. is located on a southerly slope in tall sagebrush, 60 ft. South of fence, bears E-W.

**40.038** Point for the center 1/4 sec. cor. of sec. 20, at intersection with the E-W center line of sec. 20. Not monumented.

**80.066** The 1/4 sec. cor. of secs 17 and 20.

---

From the 1/4 sec. cor. of secs. 20 and 21.

S. 89°57.4' W., on the E-W center line of sec. 20.

**19.851** Point for the center E 1/16 sec. cor. of sec. 20. Not monumented.

**39.702** Point for the center 1/4 sec. cor. of sec. 20.

**59.588** Point for the center W 1/4 sec. cor. of sec. 20. Not monumented.

SURVEY OF THE SUBDIVISION OF SECTION 20,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

**79.474** The 1/4 sec. cor. of secs. 19 and 20.

---

From the point for the E 1/16 sec. cor. of secs. 20 and 29.

N. 0°02.3' E., on the N-S center line of the SE 1/4 of sec. 20.

**20.006** Point for the SE 1/16 sec. cor. of sec. 20, at intersection with the E-W center line of the SE 1/4 of sec. 20. Not monumented.

**40.012** Point for the center E 1/16 sec. cor. of sec. 20.

---

From the point for the S 1/16 sec. cor. of secs. 20 and 21.

S. 89°55.6' W., on the E-W center line of the SE 1/4 of sec. 20.

**19.840** Point for the SE 1/16 sec. cor. of sec. 20.

**24.800** Point for the center E-W-SE 1/256 sec. cor. of sec. 20.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, with brass cap mkd.:

C-E-W-SE 1/256

X

S20

2004

Cor. is located on a flat in sagebrush, 15 ft. East of a fence, bears N-S.

**29.760** Point for the center W-SE 1/64 center cor. of sec. 20. Not monumented.

**39.680** The center S 1/16 sec. cor. of sec. 20.

---

From the E-W-E 1/256 sec. cor. of secs. 20 and 29.

N. 0°01.9' E., on the N-S center line of the E 1/2 of the SW 1/4 of the SE 1/4 of sec. 20.

**20.011** The center E-W-SE 1/256 sec. cor. of sec. 20.

---

From the point for the W 1/16 sec. cor. of secs 20 and 29.

N. 0°04.7' W., on the N-S center line of the SW 1/4 of sec. 20.

**20.031** Point for the SW 1/16 sec. cor. of sec. 16, at intersection with the E-W center line of the SW 1/4 of sec. 20. Not monumented.

SURVEY OF THE SUBDIVISION OF SECTION 20,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

**40.057** Point for the center W 1/16 sec. cor. of sec. 20.

---

From the center S 1/16 sec. cor. of sec. 20.

S. 89°55.3' W., on the E-W center line of the SW 1/4 of sec. 20.

**19.856** Point for the SW 1/16 sec. cor. of sec. 20.

**24.820** Point for the center E-W-SW 1/256 sec. cor. of sec. 20.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, with brass cap mkd.:

C-E-W-SW 1/256

X

S20

2004

Cor. is located on a gradual NE slope in sagebrush, approximately 45 ft. West of irrigation canal, flows N. 30° W., and 35 ft. S. 35° E. of the intersection of fences, bearing E and S, and 20 ft. East of a fence, bears S.

**29.784** Point for the center W-SW 1/64 sec. cor. of sec. 20. Not monumented.

**39.712** Point for the S 1/16 sec. cor. of secs. 19 and 20.

---

From the E-W-W 1/256 sec. cor. of secs. 20 and 29.

N. 0°05.9' W., on the N-S center line of E 1/2 of the SW 1/4 of the SW 1/4 of sec. 20.

**20.032** The center E-W-SW 1/256 sec. cor. of sec. 20.

---

Survey of the Subdivision of Section 29,  
T. 1 S., R. 7 W., Uintah Special Meridian, Utah

---

From the 1/4 sec. cor. of secs. 29 and 32.

N. 0°10.6' E., on the N-S center line of sec. 29.

**19.880** Point for the center S 1/16 sec. cor. of sec. 29. Not monumented.

**39.760** Point for the center 1/4 sec. cor. of sec. 29, at intersection with the E-W center line of sec. 29. Not monumented.

**79.851** The 1/4 sec. cor. of secs. 20 and 29.

---

SURVEY OF THE SUBDIVISION OF SECTION 29,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

From the 1/4 sec. cor. of secs. 28 and 29.

N. 89°52.3' W., on the E-W center line of sec. 29.

**40.329** Point for the center 1/4 sec. cor. of sec. 29.

**60.249** Point for the center E 1/16 sec. cor. of sec. 29. Not monumented.

**80.169** The 1/4 sec. cor. of secs. 29 and 30.

---

From the W 1/16 sec. cor. of secs. 29 and 32.

N. 0°10.7' E., on the N-S center line of the SW 1/4 of sec. 29.

**19.921** Point for the SW 1/16 sec. cor. of sec. 29, at intersection with the E-W center line of the SW 1/4 of sec. 29.

Set a rebar, 18 ins. long, 5/8 in. diam., 14 ins. in the ground, with 2 ins. diam. aluminum cap mkd.:

SW 1/16  
S29  
2004

Cor. is located 5 ft. North of the intersection of fences, bearing N-S, and W.

**39.842** Point for the center W 1/16 sec. cor. of sec. 29.

---

From the point for the center S 1/16 sec. cor. of sec. 29.

N. 89°59.9' W., on the E-W center line of the SW 1/4 of sec. 29.

**19.921** The SW 1/16 sec. cor. of sec. 29.

**39.842** The S 1/16 sec. cor. of secs. 29 and 30.

---

Survey of the Subdivision of Section 30,  
T. 1 S., R. 7 W., Uintah Special Meridian, Utah

---

From the 1/4 sec. cor. of secs. 30 and 31.

N. 0°02.0' W., on the N-S center line of sec. 30.

**20.046** Point for the center S 1/16 sec. cor. of sec. 30.

Set a rebar, 18 ins. long, 5/8 in. diam., 19 ins. in the ground, with 2 ins. diam. aluminum cap mkd.:

SURVEY OF THE SUBDIVISION OF SECTION 30,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

C  
S1/16|S30  
C  
2004

from which the reference objects

A power pole, 16 ins. diam., bears S. 60° E., 13.9 lks. dist., to a PK-nail.

A gate brace post, bears North, 36.7 lks. dist.

Cor. is located bet. east edge of paved road and west of right-of-way fence.

- 40.092** The center 1/4 sec. cor. of sec. 30, monumented with a rebar, 5/8 in. diam., firmly set, 1 in. below ground, with plastic cap mkd. LS3817 as recorded in Duchesne County Survey File Number 359, and is accepted as a faithful and careful determination of the position of the cor. Not remonumented.

---

N. 0°02.3' E., beginning new measurement.

- 20.021** Point for the center N 1/16 sec. cor. of sec. 30.  
Set an aluminum drive in rod, 30 ins. long, 5/8 in. diam., 30 ins. in the ground, with 2 ins. diam., aluminum cap mkd.:

C  
N1/16|S30  
C  
2004

Cor. is located in pasture, 3 ft. East of fence, bears N-S, 9 ft. S. 10° E. of intersection of fences, bearing N-S, E-W, and on south bank of irrigation ditch.

- 40.042** The 1/4 sec. cor. of secs. 19 and 30.

---

From the 1/4 sec. cor. of secs. 29 and 30.

N. 89°58.7' W., on the E-W center line of sec. 30.

- 20.032** The center E 1/16 sec. cor. of sec. 30, determined from local record bearings and dists. of the Duchesne County Survey Monument Record filed on August 29, 1994 by Jerry D. Allred, falls on newly paved road surface, from which the local reference objects

A power pole, 8 ins. diam., bears N. 34°54'49" E., 82.0 lks. dist. to a nail and washer.

SURVEY OF THE SUBDIVISION OF SECTION 30,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

A vertical cattle guard post, 3 ins. diam., bears  
N. 49°32'41" E., 64.5 lks. dist.

A vertical cattle guard post, 3 ins. diam., bears N.  
73°10'50" E., 51.3 lks. dist.

A power pole, 11 ins. diam., bears S. 40°12'38" W.,  
62.5 lks. dist., to face on northwesterly side of power  
pole.

At the corner point

Set a PK-nail flush with paved surface.

Note: The local monument spike was established as recorded on  
Duchesne County Survey File Number 369 by Jerry D. Allred but  
was not recovered.

Cor. is located on paved surface, 27 ft. wide, bears N-S.

---

N. 89°58.0' W., beginning new measurement.

**20.032** The center 1/4 sec. cor. of sec. 30.

---

N. 89°58.4' W., beginning new measurement.

**20.134** Point for the center W 1/16 sec. cor. of sec. 30.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 21  
ins. in the ground with magnet at base, with brass cap mkd.:

W 1/16  
C ——— C  
S30  
2004

Drive a steel fence post N. 45° E., 0.9 ft. of stainless steel  
post.

**35.658** The 1/4 sec. cor. of secs. 25 and 30.

---

From the center E 1/16 sec. cor. of sec. 30.

N. 0°14.1' E., on the N-S center line of the NE 1/4 of sec. 30.

**19.996** Point for the NE 1/16 sec. cor. of sec. 30, at intersection  
with the E-W center line of the NE 1/4 of sec. 30, falls on  
paved surface, 27 ft. wide, bears N-S.

Set a PK-nail flush with paved surface.

from which the reference objects

SURVEY OF THE SUBDIVISION OF SECTION 30,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

A cedar fence post, 6 ins. diam., bears N. 80° E., 43.8 lks. dist., to a PK-nail, at intersection of fences, bearing N-S, and E.

A cedar fence post, 5 ins. diam., bears N. 85° W., 66.9 lks. dist., at intersection of fences, bearing N and W.

**39.987** The E 1/16 sec. cor. of secs 19 and 30.

---

From the point for the N 1/16 sec. cor. of secs. 29 and 30.

N. 89°53.6' W., on the E-W center line of sec. 30.

**20.100** The NE 1/16 sec. cor. of sec. 30.

**40.199** The center N 1/16 sec. cor. of sec. 30.

---

From the E 1/16 sec. cor. of secs. 30 and 31.

N. 0°06.0' E., on the N-S center line of the SE 1/4 of sec. 30.

**20.001** The SE 1/16 sec. cor. of sec. 30, monumented with a spike, 3 ins. below paved surface, as recorded in Duchesne County Survey File Number 863, and is accepted as a faithful and careful determination of the position of the cor. Not remonumented. From which the local reference objects as recorded on Duchesne County Survey Monument Record filed on August 29, 1994 by Jerry D. Allred.

A railroad tie, bears N. 70° E., 58.0 lks. dist., to nail and washer on NW side of railroad tie.

A power pole, 10 ins. diam., bears N. 60° W., 44.2 lks. to a nail and shiner on NE side of power pole.

Cor. is located on paved surface, 27 ft. wide, bears N-S.

---

N. 0°06.4 E., beginning new measurement.

**19.991** The center E 1/16 sec. cor. of sec. 30.

---

From the S 1/16 sec. cor. of secs. 29 and 30.

S. 89°57.0' W., on the E-W center line of the SE 1/4 of sec. 30.

**20.008** The SE 1/16 sec. cor. of sec. 30.

---

S. 89°52.5' W., beginning new measurement.

**19.984** The center S 1/16 sec. cor. of sec. 30.

SURVEY OF THE SUBDIVISION OF SECTION 30,  
T. 1 S., R. 7 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

---

From the W 1/16 sec. cor. of secs. 30 and 31.

N. 0°03.5' W., on the N-S center line of the SW 1/4 of sec. 30.

- 20.071** Point for the SW 1/16 sec. cor. of sec. 30, at intersection with the E-W center line of the SW 1/4 of sec. 30, falls on dirt road, 10 ft. wide, bears N-S.

Set a rebar, 18 ins. long, 5/8 in. diam., flush with the ground, with 2 ins. diam. aluminum cap mkd.:

SW 1/16  
S30  
2004

Cor. is located in alfalfa and pasture, 13 ft. West of a fence, bears N-S, 21 ft. S. 30° W. of the intersection of fences, bearing N-S, and E.

- 40.137** Point for the center W 1/16 sec. cor. of sec. 30.
- 

From the center S 1/16 sec. cor. of sec. 30.

S. 89°57.3' W., on the E-W center line of the SW 1/4 of sec. 30.

- 20.126** The SW 1/16 sec. cor. of sec. 30.

- 35.659** Point for the S 1/16 sec. cor. of secs. 25 and 30.
- 

From the center W 1/16 sec. cor. of sec. 30.

N. 0°06.6' E., on the N-S center line of the NW 1/4 of sec. 30.

- 20.021** Point for the NW 1/16 sec. cor. of sec. 30, at intersection with the E-W center line of the NW 1/4 of sec. 30, falls in pasture.

Set a rebar, 18 ins. long, 5/8 in. diam., 19 ins. in the ground, with 2 ins. diam. aluminum cap mkd.:

NW 1/16  
S30  
2004

Cor. is located 5 ft. South of fence, bears E-W, and approximately 15 ft. S. 70° W. of the intersection of fences, bearing N-S, and W.

- 40.042** The W 1/16 sec. cor. of secs. 19 and 30.
-

SURVEY OF THE SUBDIVISION OF SECTION 30,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS**


From the center N 1/16 sec. cor. of sec. 30.

N. 89°58.9' W., on the E-W center line of the NW 1/4 of sec. 30.

**20.108** The NW 1/16 sec. cor. of sec. 30.

**34.548** Point selected for the witness cor. to the N 1/16 sec. cor. of secs. 25 and 30.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, in a collar of stone, with brass cap mkd.:



Witness cor. is located 6 ft. South of fence, bears E-W.

**35.601** True point for the N 1/16 sec. cor. of secs. 25 and 30.

Survey of the Subdivision of Section 31,  
T. 1 S., R. 7 W., Uintah Special Meridian, Utah

From the 1/4 sec. cor. of secs. 6 and 31.

N. 0°02.9' W., on the N-S center line of sec. 31.

**40.068** Point for the center 1/4 sec. cor. of sec. 31, at intersection with the E-W center line of sec. 31, falls within a corral.

Set a rebar, 6 ins. long, 5/8 in. diam., 7 ins. in the ground, with 2 ins. diam. aluminum cap mkd.:

C 1/4  
S31  
2004

Cor. is located 22 ft. South of a fence, bears E-W, 16.3 ft. S. 54°54.5' E. of the high point of the letter A in the word IRRIGATION on a manhole cover.

**60.137** Point for the center N 1/16 sec. cor. of sec. 31, falls on paved surface.

Set a PK-nail flush with paved surface.

from which the reference objects

A fence post, 8 ins. diam., bears N. 30° E., 38.0 lks. dist.

SURVEY OF THE SUBDIVISION OF SECTION 31,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

A fence post, 4 ins. diam., at intersection of fences bearing N. 20° W. and E, bears East, 34.7 lks. dist. to a PK-nail.

- 80.206** Point for the 1/4 sec. cor. of secs. 30 and 31.

---

From the 1/4 sec. cor. of secs. 31 and 32.

S. 89°47.4' W., on the E-W center line of sec. 31.

- 19.921** Point for the center E 1/16 sec. cor. of sec. 31, falls in an alfalfa field.

Set an aluminum drive in rod, 30 ins. long, 5/8 in. diam., 31 ins. in the ground, with 2 ins. diam., aluminum cap mkd.:

$$\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S31} \\ \text{2004} \end{array}$$

Cor. is located 3 ft. South of a fence, bears E-W, 21 ft. West of the intersection of fence, bears E-W, and North.

- 39.842** Point for the center 1/4 sec. cor. of sec. 27.

- 60.035** Point for the center W 1/6 sec. cor. of sec. 31, falls in pasture.

Set an aluminum drive in rod, 30 ins. long, 5/8 in. diam., 30 ins. in the ground, with 2 ins. diam., aluminum cap mkd.:

$$\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S31} \\ \text{2004} \end{array}$$

Cor. is located 60 ft. East of a fence, bears N-S.

- 75.816** The 1/4 sec. cor. of secs. 31 and 36, monumented with a cobblestone, 20X14X8 ins., firmly set, in a mound of stone (not of record) clearly mkd. 1/4 S (S not of record) on west face, from which the original bearing trees

A cedar, 17 ins. diam., bears N. 85° E., 19 lks. dist., with scribe marks 1/4S31BT visible on open blaze.

A cedar branch, with 9 ins. diam. branch, bears N. 15° W., 9 1/2 lks. dist., with dim scribe marks 1/4S36BT visible on open blaze. (Record; cedar, 11 lks.)

At the corner point

SURVEY OF THE SUBDIVISION OF SECTION 31,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to solid rock with magnet at base, in a mound of stone, 4 ft. diam., to top, with brass cap mkd.:

T1S  
R8W R7W  
1/4  
S36|S31  
2004

Bury mkd. stone on south side of stainless steel post.

Cor. is located on NE slope in juniper and pinon.

---

From the center E 1/16 sec. cor. of sec. 31.

N. 0°09.4' W., on the N-S center line of the NE 1/4 of sec. 31.

**20.226** Point for the NE 1/16 sec. cor. of sec. 31, at record dist. of 20.000 chs. (1320.0 ft. on the unrecorded Townsite of Tabiona plat by J. B. Peterson C. E.) from the N 1/16 sec. cor. of secs. 31 and 32, is in agreement with existing town improvements.

Set a rebar, 6 ins. long, 5/8 in. diam., 6 ins. in the ground, with 2 ins. diam. aluminum cap mkd.:

NE 1/16  
S31  
2004

from which the reference objects

A power pole, 8 ins. diam., bears S. 80° E., 31.2 lks. dist. to a PK-nail.

An angle iron fence post, bears S. 70° W., 16.1 lks. dist. to a chiseled X, 1 ft. above base of angle iron fence post.

---

N. 0°07.2' E., beginning new measurement.

**19.926** The E 1/16 sec. cor. of secs. 30 and 31.

---

From the N 1/16 sec. cor. of secs. 31 and 32.

N. 89°56.2' W., on the E-W center line of the NE 1/4 of sec. 31.

**20.000** The NE 1/16 sec. cor. of sec. 31.

---

S. 89°20.5' W., beginning new measurement.

SURVEY OF THE SUBDIVISION OF SECTION 31,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

**19.882** The center N 1/16 sec. cor. of sec. 31.

---

From the center W 1/16 sec. cor. of sec. 31.

N. 0°03.3' E., on the N-S center line of the NW 1/4 of sec. 31.

**40.172** The W 1/16 sec. cor. of secs. 30 and 31.

---

Survey of the Subdivision of Section 32,  
T. 1 S., R. 7 W., Uintah Special Meridian, Utah

---

From the 1/4 sec. cor. of secs. 5 and 32.

N. 0°06.8' W., on the N-S center line of sec. 32.

**20.138** Point for the center S 1/16 sec. cor. of sec. 32.

Set a rebar, 18 ins. long, 5/8 in. diam., 19 ins. in the ground, with 2 ins. diam. aluminum cap mkd.:

C  
S1/16|S32  
C  
2004

Cor. is located 18.5 ft. South of fence, bears E-W, 7.0 ft. East of a fence, bears N-S, and under the forward seat of an ancient (horse drawn) McCormick Deering No. 7 hay mower.

**40.276** Point for the center 1/4 sec. cor. of sec. 32, at intersection with the E-W center line of sec. 32.

Set an aluminum drive in monument, 30 ins. long, 5/8 in. diam., flush with ground, with 3 1/4 in. diam. aluminum cap mkd.:

T1S R7W  
C 1/4 X S32  
2004

Cor. is located in pasture, 7 ft. South of a fence, bears E-W, 5 ft. East of a fence, bears N-S, 8 1/2 ft. S. 20° E., of the intersection of fences, bears E-W, and S.

**60.313** Point for the center N 1/16 sec. cor. of sec. 32, falls on a bank for an irrigation canal.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground with magnet at base, with brass cap mkd.:

SURVEY OF THE SUBDIVISION OF SECTION 31,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

C  
N 1/16|S32  
C  
2004

from which the reference objects

A cedar fence post, 6 ins. diam., bears S. 30° W., 56.8 lks. dist. to a PK-nail.

A cedar fence post, 4 ins. diam., bears N. 45° W., 62.9 lks. dist. to a PK-nail.

From this point, an unrecorded rebar, 1/2 in. diam., firmly set, projecting 4 ins. above ground, bears West, 0.030 chs. dist., set using incorrect procedures and is not utilized during the course of this survey.

Cor. is located 25 ft. South of irrigation canal, 7 ft. wide, flows S. 25° E.

**80.350** The 1/4 sec. cor. of secs. 29 and 32.

---

From the 1/4 sec. cor. of secs. 32 and 33.

S. 89°47.9' W., on the E-W center line of sec. 32.

**20.255** Point for the center E 1/16 sec. cor. of sec. 32, falls in pasture.

Set a rebar, 18 ins. long, 5/8 in. diam., flush with ground, with 2 ins. diam. aluminum cap mkd.:

E 1/16  
C———C  
S32  
2004

Cor. is located 8 ft. South of a fence, bears E-W, 24 ft. West of the intersection of fences, bears E-W.

**40.510** The center 1/4 sec. cor. of sec. 32.

**60.498** Point for the center W 1/16 sec. cor. of sec. 32, falls in pasture.

Set a rebar, 18 ins. long, 5/8 in. diam., 18 ins. in the ground with 2 ins. diam. aluminum cap mkd.:

SURVEY OF THE SUBDIVISION OF SECTION 32,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

W 1/16  
C ——— C  
S32  
2004

Cor. is located in pasture, 9.0 ft. South of a fence, bears E-W, 8.7 ft. East of a fence, bears N-S, 11.8 ft. S. 45° E. of the intersection of fences, bearing N-S, and E-W.

**80.486** The 1/4 sec. cor. of secs. 31 and 32.

---

From the E 1/16 sec. cor. of secs. 5 and 32.

N. 0°17.9' E., on the N-S center line of the SE 1/4 of sec. 32.

**20.165** Point for the SE 1/16 sec. cor. of sec. 32, at intersection with the E-W center line of the SE 1/4 of sec. 32, falls in pasture.

Set a rebar, 18 ins. long, 5/8 in. diam., 19 ins. in the ground, with 2 ins. diam. aluminum cap mkd.:

SE 1/16  
S32  
2004

Cor. is located 18 ft. South of a fence, bears E-W, 20 ft. S. 45° W. of the intersection of fences, bears E-W, and W, 25 ft. NW of a curve in a fence, concave to the SE, 8 ft. East of a fence, bears N-S, 18 ft. S. 45° E. of the intersection of fences, bearing E-W, and S.

**40.330** The center E 1/16 sec. cor. of sec. 32.

---

From the S 1/16 sec. cor. of secs. 32 and 33.

S. 89°51.9' W., on the E-W center line of the SE 1/4 of sec. 32.

**20.111** The SE 1/16 sec. cor. of sec. 32.

**40.222** The center S 1/16 sec. cor. of sec. 32.

---

From the W 1/16 sec. cor. of secs. 5 and 32.

N. 0°08.7' W., on the N-S center line of the SW 1/4 of sec. 32.

**20.116** Point for the SW 1/16 sec. cor. of sec. 32, at intersection with the E-W center line of the SW 1/4 of sec. 32.

Set a rebar, 18 ins. long, 5/8 in. diam., 14 ins. in the ground, with 2 ins. diam. aluminum cap mkd.:

SURVEY OF THE SUBDIVISION OF SECTION 32,  
T. 1 S., R. 7 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

SW 1/16  
S32  
2004

Cor. is located in cottonwood and 7.0 ft. South of a fence,  
bears E-W.

**40.227** The center W 1/16 sec. cor. of sec. 32.

---

From the center S 1/16 sec. cor. of sec. 32.

S. 89°52.5' W., on the E-W center line of the SW 1/4 of sec.  
32.

**19.978** The SW 1/16 sec. cor. of sec. 32.

**39.956** The S 1/16 sec. cor. of secs. 31 and 32.

---

From the center W 1/16 sec. cor. of sec. 32.

N. 0°01.3' W., on the N-S center line of the NW 1/4 of sec. 32.

**20.081** Point for the NW 1/16 sec. cor. of sec. 32, at intersection  
with the E-W center line of the NW 1/4 of sec. 32, falls on  
gravel road, 20 ft. wide, bears E-W.

Set a PK-nail 3 ins. below gravel surface to solid rock.

from which the reference objects

A fence post, 6 ins. diam., bears S. 40° E., 66.5 lks.  
dist. to a PK-nail.

A cedar fence post, bears S. 10° W., 45.8 lks. dist. to  
a PK-nail.

**40.102** The W 1/16 sec. cor. of secs 29 and 32.

---

From the center N 1/16 sec. cor. of sec. 32.

S. 89°55.9' W., on the E-W center line of the NW 1/4 of sec.  
32.

**19.955** The NW 1/16 sec. cor. of sec. 32.

**39.910** The N 1/16 sec. cor. of secs. 31 and 32.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Jerry L. Thomas	Cadastral Surveyor
Jonas Grant Jr.	Survey Aide
Adrian Kurip	Survey Aide

---

## CERTIFICATE OF SURVEY

I, *John F. Carroll, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *30th day of April, 2004*, I have *executed a dependent resurvey of a portion of the south and west boundaries, a portion of the subdivisional lines, and the subdivision of sections 19, 20, 29, 30, 31 and 32, in Township 1 South, Range 7 West*, of the *Uintah Special Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

09/23/05

Date

*John F. Carroll*  
(Cadastral Surveyor)

\_\_\_\_\_  
Date

\_\_\_\_\_  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the dependent resurvey of a portion of the south and west boundaries, a portion of the subdivisional lines, and the subdivision of sections 19, 20, 29, 30, 31 and 32, in Township 1 South, Range 7 West, Uintah Special Meridian, Utah, executed by *John F. Carroll, Cadastral Surveyor*, having been critically examined and found correct, are hereby approved.

September 27, 2005

Date

*Daniel W. Webb*

Chief Cadastral Surveyor for Utah