

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL
FIELD NOTES

OF
THE DEPENDENT RESURVEY OF
A PORTION OF THE SUBDIVISIONAL LINES,
THE SUBDIVISION OF SECTION 11,
AND A METES AND BOUNDS SURVEY IN SECTION 11

IN
TOWNSHIP 3 SOUTH, RANGE 4 WEST
OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY
RONALD K. BAUGH
Cadastral Surveyor

Under special instructions dated and approved **April 5, 2004**, which
provided for the surveys included under Group Number **980**, and
assignment instructions dated **April 5, 2004**

Survey commenced **April 12, 2004**
Survey completed **November 2, 2005**

INDEX DIAGRAM

Township 3 South, Range 4 West

6	5	4	3	2	1
7	8	9	10	4 11	12
18	17	16	15	3 14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

The Subdivision of Section 11.....Page 5

The Metes and Bounds of Section 11.....Page 8

TOWNSHIP 3 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, the subdivision of section 11, and a metes and bounds survey in Section 11, in T. 3 S., R. 4 W., Salt Lake Meridian, Utah.

History of Earlier Surveys

Surveyed by		Retr. or Resurveyed by	
SOUTH BOUNDARY			
Portion	C.L. Craig	1856	
Portion	A. Jesson	1879	A. Jesson 1879
Portion			A.J. Stewart Jr. 1896
EAST BOUNDARY			
Portion	C.L. Craig	1856	
Portion	A. Jesson	1879	A. Jesson 1879
Portion	A.J. Stewart, Jr.	1896	A.J. Stewart, Jr. 1896
Portion			Workman & Baugh 1996
WEST BOUNDARY			
All	C.L. Craig	1856	
NORTH BOUNDARY			
Portion	C.L. Craig	1856	
Portion	A.J. Stewart, Jr.	1879	A.J. Stewart, Jr. 1879
Portion			Workman & Baugh 1996
SUBDIVISION			
Portion	C.L. Craig	1856	
Portion	A. Jesson	1879	A. Jesson 1879
Portion	A.J. Stewart, Jr.	1896	A.J. Stewart, Jr. 1896
Portion			Workman & Baugh 1996

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 980, dated April 5, 2004.

The true meridian direction and length of all lines were determined by Global Positioning System (GPS) utilizing Real-Time Kinematics (RTK) observations using the Trimble 4000 model receiver.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and their calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations, post processed by National Geodetic Survey, Online Positioning User Service, (OPUS), Utilizing Continuously Operating Reference Stations; (CORS) SALT LAKE CITY, SALT LAKE WAAS, and MIDVALE. The N.A.D. 1983 (CORS96)

TOWNSHIP 3 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

geographic position of the 1/4 section corner of sections 11 and 12 is as follows:

Latitude: 40°34'23.754" N. Longitude: 112°15'20.312" W.

N.A.V.D. 1988 Elevation: 4855.2 ft.

The Dependent Resurvey of a Portion of the Subdivisional Lines
Township 3 South, Range 4 West, Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
C.L. Craig in 1856, and the Dependent Resurvey
Executed by R.K. Baugh and M.R. Workman in 1996

CHAINS Beginning at the 1/4 section corner of sections 11 and 12, monumented with a Tooele County brass cap, 2 inches diameter, firmly set, flush with ground, with brass cap marked:

T3S R4W
11 | 12
1984

This corner is accepted as the best available evidence of the original corner position.

Corner is located 1 ft. southwest of corner of fences projecting north and east.

N. 1° 02.8' W., between sections 11 and 12.

19.787 Point for the N 1/16 section corner of sections 11 and 12. This corner will also function as Angle Point 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T3S R4W
N 1/16
S11 | S12
2005

Corner is located 7.2 ft. south and 0.5 ft. west of a corner of fences projecting west, north and south.

39.574 The corner of sections 1, 2, 11, and 12, monumented with a Tooele County brass cap, 2 inches diameter, firmly set in concrete, 2 inches below ground, with brass cap marked:

T3S R4W
2 | 1
11 | 12
1981

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 3 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

This corner is accepted as the best available evidence of the original corner position. This corner will also function as Angle Point 14.

Corner is located 0.8 ft. south of corner, in the fence line, from which fences project north, south, and west.

From the 1/4 section corner of sections 11 and 14, monumented with a Tooele County brass cap, 2 inches diameter, firmly set in road, with brass cap marked:

T3S R4W
11
14
1982

This corner is accepted as the best available evidence of the original corner position.

S. 89° 36.9' W., between sections 11 and 14.

- 6.266 Set PK nail flush with paved road.
- 9.102 Set PK nail flush with paved road.
- 20.077 Point for the W 1/16 section corner of sections 11 and 14, not monumented.
- 40.154 The corner of sections 10, 11, 14, and 15, monumented with a Tooele County brass cap, 2 inches diameter, firmly set at intersection of road, with brass cap marked:

T3S R4W
10 | 11
15 | 14
1982

This corner is accepted as the best available evidence of the original corner position.

N. 0° 54.5' W., between sections 10 and 11.

- 22.500 Point for Angle Point 1, of a metes and bounds survey. Point determined at record distance taken from the second addition of Lincoln Subdivision plat, recorded in the office of the Tooele County Recorder.

Set a railroad spike flush with paved road.
- 40.078 The 1/4 section corner of sections 10 and 11, monumented with a Tooele County brass cap, 2 inches diameter, firmly set in center of road, with brass cap marked:

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 3 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T3S R4W
10 | 11
1982

This corner is accepted as the best available evidence of the original corner position. This corner will also function as Angle Point 2.

N. 0° 54.5' W., beginning new measurement.

- 20.036** Point for the N 1/16 section corner of sections 10 and 11, not monumented.
- 40.072** The corner of sections 2, 3, 10, and 11, monumented with a Tooele County brass cap, 2 inches diameter, firmly set in center of road, with brass cap marked:

T3S R4W
3 | 2

10 | 11
1982

This corner is accepted as the best available evidence of the original corner position.

From the corner of sections 1, 2, 11 and 12.

S. 89° 44.8' W., between sections 2 and 11.

- 40.139** The 1/4 section corner of sections 2 and 11, monumented with a Tooele County brass cap, 2 inches diameter, firmly set in concrete, flush with ground, with brass cap marked:

T3S R4W
2
11
1981

Corner is set 7.4 ft. west of a fence projecting north and south and 7.8 ft. north of a fence projecting east and west.

This corner is accepted as the best available evidence of the original corner position. This corner will also function as Angle Point 13.

S. 89° 44.6' W., beginning new measurement.

- 10.114** Point for Angle Point 12, at the extension of fence to the south.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 3 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T3S R4W
S2
PROP/BLM AP12
COR/ S11
2005

Set a 6 ft. steel fence post alongside the monument.

Corner is set 18.5 ft. north of corner of fences projecting east, west and south.

- 20.071** Point for the W 1/16 section corner of sections 2 and 11, not monumented.
- 40.142** The corner of sections 2, 3, 10, and 11.

The Subdivision of Section 11,
Township 3 South, Range 4 West, Salt Lake Meridian, Utah

From the 1/4 section corner of section 11 and 14.

N. 0° 54.8' W., on the N-S centerline of section 11.

- 12.278** Intersect the line between Angle Points 17 and 18, not monumented.
- 37.649** Intersect the line between Angle Points 6 and 7, not monumented.
- 40.237** Point for the center 1/4 section corner of section 11 at intersection with the E-W centerline of section 11, not monumented.
- 48.184** Intersect the line between Angle Points 8 and 9, not monumented.
- 60.149** Point for the center N 1/16 section corner of section 11, not monumented.
- 80.061** The 1/4 section corner of section 2 and 11.

From the 1/4 section corner of section 11 and 12.

S. 89° 23.3' W., on the E-W centerline of section 11.

- 33.710** Intersect the line between Angle Points 17 and 18, not monumented.
- 39.115** Intersect the line between Angle Points 7 and 8, not monumented.
- 40.234** The point for the center 1/4 section corner of section 11.
- 60.307** Point for the center W 1/16 section corner of section 11. This corner will also function as Angle Point 3.

THE SUBDIVISION OF SECTION 11,
TOWNSHIP 3 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T3S R4W
W 1/16
C———C
AP3 S11
2005

Set a 5 ft. steel fence post alongside the monument.

Corner is located in an open field about 200 ft. east of a corner of fences projecting south and west.

79.880 Point selected for a witness point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

WP
S11
C———C
2005

80.380 The 1/4 section corner of sections 10 and 11.

From the N 1/16 section corner of section 11 and 12.

S. 89° 34.0' W., on the E-W centerline of the NE 1/4 of section 11.

28.788 Point for Angle Point 16 on the west side of a ditch, as per deed description.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

AP 16 / BLM PROP COR 2005

Corner is set 5.5 ft. south and 16 ft. west of a corner of fences projecting east and south.

40.186 The point for the center N 1/16 section corner of section 11.

From the point for the W 1/16 section corner of sections 11 and 14.

N. 0° 54.7' W., on the N-S centerline of the SW 1/4 of section 11.

20.480 Point for Angle Point 29 at record distance from AP 30.

THE SUBDIVISION OF SECTION 11,
TOWNSHIP 3 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

BLM
PROP COR
AP29
2005

Set a 5 ft. steel fence post alongside the monument.

Corner is located 7.5 ft. east of a fence projecting north and south.

- 22.500** Point for Angle Point 30, at record distance from the south line of section 11.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

BLM
PROP COR
AP30
2005

Set a 5 ft. steel fence post alongside the monument.

Corner is located 7.5 ft. east of a fence projecting north and south and 36 ft. south of a fence projecting east and west.

- 34.556** Point for Angle Point 4, at the intersection with fence bearing northwest and southeast.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

PROP COR
BLM
AP4
2005

- 40.157** The center W 1/16 section corner of section 11.

N. 0° 54.6' W., on the N-S centerline of the NW 1/4 of section 11.

- 10.763** Point for Angle Point 9, at the extension of a fence to the east.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

THE SUBDIVISION OF SECTION 11,
TOWNSHIP 3 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

PROP COR

BLM
AP9
2005

Set a 5 ft. steel fence post alongside the monument.

- 19.974** Point for the NW 1/16 section corner of section 11, at intersection with the E-W centerline of the NW 1/4 of section 11. This corner will also function as Angle Point 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T3S R4W
NW 1/16 AP
S11 10
2005

Set a 6 ft. steel fence post alongside the monument.

Located in open land with no fences.

- 39.948** The point for the W 1/16 section corner of sections 2 and 11.

From the point for the center N 1/16 section corner of section 11.
S. 89° 33.9' W., on the E-W centerline of the NW 1/4 of section 11.

- 11.074** Point for Angle Point 11 at intersection with the N-S fence line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

PROP
COR
AP11 BLM
2005

Set a 6 ft. steel fence post alongside the monument.

- 20.072** The NW 1/16 section corner of section 11.

- 40.144** The point for the N 1/16 section corner of sections 10 and 11.

The Metes and Bounds Survey,
Township 3 South, Range 4 West, Salt Lake Meridian, Utah

THE METES AND BOUNDS SURVEY,
TOWNSHIP 3 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The Metes and Bounds Survey is based upon the Warranty Deed, EXHIBIT "A", PARCEL 39, dated April 2, 1996, and filed with the Tooele County Recorder April 4, 1996. Book 419 of records pages 653-661. KENNECOTT UTAH COPPER CORPORATION, Grantor and UNITED STATES OF AMERICA, Grantee.

From Angle Point 1, on the line between sections 10 and 11, hereinbefore described.

N. 0° 54.5' W., between sections 10 and 11 identical with line 1-2.

17.578 The 1/4 section corner of sections 10 and 11, also Angle Point 2.

N. 89° 23.3' E., on the E-W centerline of section 11, identical with line 2-3.

20.073 The center W 1/16 section corner of section 11, also Angle Point 3.

S. 0° 54.7' E., on the N-S centerline of the SW 1/4 of section 11, identical with line 3-4.

5.601 Angle Point 4, hereinbefore described.

S. 70° 04.5' E., on line 4-5.

13.343 Point for Angle Point 5, in E-W fence and on the east bank of ditch as per deed description.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

PROP COR
BLM
AP5
2005



Set a 5 ft. steel fence post alongside the monument.

N. 12° 10.6' E., on line 5-6.

8.755 Point for Angle Point 6, at proportionate distance.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

THE METES AND BOUNDS SURVEY,
TOWNSHIP 3 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

PROP COR

AP6
BLM
2005

Set a 5 ft. steel fence post alongside the monument.

Corner is located in an open field.

S. 82° 04.4' E., on line 6-7.

5.688 Intersect the N-S centerline of section 11, not monumented.

6.258 Point for Angle Point 7, at record distance from Angle Point 8 and in north-south fence.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

PROP COR

BLM
AP7
2005

Corner is located in a fence line projecting north and south.

N. 10° 50.0' E., on line 7-8.

2.727 Intersect the E-W centerline of section 11, not monumented.

10.449 Point for Angle Point 8, at the corner of fences bearing east, west and south.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, with aluminum cap marked:

PROP COR

BLM
AP8
2005

N. 82° 37.7' W., on line 8-9.

2.719 Intersect the N-S centerline of section 11, not monumented.

23.002 Angle Point 9, hereinbefore described.

N. 0° 54.6' W., on the N-S centerline of the NW 1/4 of section 11, identical with line 9-10.

9.211 The NW 1/16 section corner of section 11, also Angle Point 10.

THE METES AND BOUNDS SURVEY,
TOWNSHIP 3 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89° 33.9' E., on the E-W centerline of the NW 1/4 of section 11, identical with line 10-11.

8.998 Angle Point 11, hereinbefore described.

N. 1° 50.7' E., on line 11-12.

19.959 Angle Point 12, hereinbefore described.

N. 89° 44.6' E., between sections 2 and 11, identical with line 12-13.

10.114 The 1/4 section corner of sections 2 and 11, also Angle Point 13.

N. 89° 44.8' E., between sections 2 and 11, identical with line 13-14.

40.139 The corner of sections 1, 2, 11 and 12, also Angle Point 14.

S. 1° 02.8' E., between sections 11 and 12, identical with line 14-15.

19.787 The N 1/16 section corner of sections 11 and 12, also Angle Point 15.

S. 89° 34.0' W., on the E-W centerline of the NE 1/4 of section 11, identical with line 15-16.

28.788 Angle Point 16, hereinbefore described.

S. 13° 13.4' W., on line 16-17.

13.399 Angle Point 17, monumented with a 5/8 inch rebar, with yellow cap marked DL BAILEY 175754.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

PROP COR
BLM
AP17
2005

Set rebar with yellow cap marked DL BAILEY 175754, alongside the monument.

THE METES AND BOUNDS SURVEY,
TOWNSHIP 3 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located in a corner of fences projecting north, south and west.

S. 12° 14.2' W., on line 17-18.

- 7.043** Intersect the E-W centerline of section 11, not monumented.
- 35.719** Intersect the N-S centerline of section 11, not monumented.
- 42.453** Point for Angle Point 18 at record bearing and distance from Angle Point 19.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

BLM
PROP COR
AP18
2005



Set a 5 ft. steel fence post alongside the monument.

South, on line 18-19.

- 3.485** Point for Angle Point 19, at record bearing and distance, based on the Tooele County records, Exhibit "A", Order No. B. 12973.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

BLM
PROP COR
AP19
2005



West, on line 19-20.

- 1.897** Point for Angle Point 20, at record bearing and distance, based on the Tooele County records.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

BLM
PROP COR
AP20
2005



Set a 5 ft. steel fence post alongside the monument.

THE METES AND BOUNDS SURVEY,
TOWNSHIP 3 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

S. 5° 45.0' E., on line 20-21.

- 1.741** Angle Point 21, monumented with a 5/8 inch rebar, with a yellow cap marked, OR-4103.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

BLM
PROP COR
AP21
2005

Deposit the rebar and cap inside aluminum post, and a magnet at base.

Corner is located 33 ft. north of section line.

S. 89° 36.9' W., on line 21-22.

- 2.836** Angle Point 22, monumented with a 5/8 inch rebar, no cap.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

BLM
PROP COR
AP22
2005

Corner is located 33 ft. north of section line.

N. 8° 21.6' E., on line 22-23.

- 5.607** Point for Angle Point 23, at record distance and in N-S fence.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

BLM
PROP COR
AP23
2005

N. 8° 09.9' E., on line 23-24.

- 6.742** Point for Angle Point 24, at record distance, and in line with fence to the south.

THE METES AND BOUNDS SURVEY,
TOWNSHIP 3 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

BLM
PROP COR
AP24
2005

N. 22° 41.5' W., on line 24-25.

0.706 Point for Angle Point 25, at record distance and in N-S fence.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

BLM
PROP COR
AP25
2005

N. 8° 08.2' E., on line 25-26.

8.638 Point for Angle Point 26, at proportionate distance.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

BLM
PROP COR
AP26
2005

Set a 5 ft. steel fence post alongside the monument.

From this Angle Point, a fence corner bears N. 43° 03' E., 38 ft. distance, fences projecting south and west.

N. 82° 38.8' W., on line 26-27.

6.880 Point for Angle Point 27, at proportionate distance.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

BLM
PROP COR
AP27
2005

THE METES AND BOUNDS SURVEY,
TOWNSHIP 3 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a 5 ft. steel fence post alongside the monument.

Corner is located 29 ft. south of a fence line projecting east and west.

S. 89° 51.2' W., on line 27-28.

3.187 Point for Angle Point 28, at proportionate distance.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

BLM
PROP COR
AP28
2005

Set a 5 ft. steel fence post alongside the monument.

Corner is located 46 ft. south of a fence line projecting east and west.

S. 70° 51.2' W., on line 28-29.

7.339 Angle Point 29, hereinbefore described.

N. 0° 54.7' W., on the N-S centerline of the SW 1/4 of section 11.

2.020 Angle Point 30, hereinbefore described.

S. 89° 36.9' W., on line 30-1.

19.575 Point for a witness point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

WP
BLM
PROP COR
AP01
2005

Corner is located 2.2 ft. east of a fence line projecting north and south, and 25.6 ft. south of fence line projecting east.

20.075 Angle Point 1 and Point of Beginning.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

T. 3 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

FIELD ASSISTANTS

Name	Capacity
Ross Workman	Cadastral Surveyor
Glen B. Hatch	Cadastral Surveyor
Tyler Trujillo	Survey Technician

CERTIFICATE OF SURVEY

I, **Ronald K. Baugh, Cadastral Surveyor**, hereby certify upon honor that, in pursuance of special instructions bearing the date of the **5th day of April, 2004**, I have **executed a dependent resurvey of a portion of the subdivisional lines, the subdivision of section 11, and a metes and bounds survey in section 11, in Township 3 South, Range 4 West,**

of the **Salt Lake Meridian**, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Jan 27, 2006
Date

Ronald K. Baugh
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the **dependent resurvey of a portion of the subdivisional lines, the subdivision of section 11, and a metes and bounds survey in section 11, in Township 3 South, Range 4 West, Salt Lake Meridian, Utah,**

executed by **Ronald K. Baugh, Cadastral Surveyor,**

having been critically examined and found correct, are hereby approved.

February 14, 2006
Date

Daniel W. Webb
Chief Cadastral Surveyor for Utah