

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL
FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE SUBDIVISIONAL LINES,

THE SUBDIVISION OF SECTIONS 3 AND 10,

THE DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEYS 6192 AND 6792,

THE SURVEY OF THE NORTH AND SOUTH RIGHT-OF-WAY LINES
OF UTAH STATE HIGHWAY No. 248,

AND THE

CENTER LINE OF THE OLD RAILROAD BED AND PATHWAY

IN

TOWNSHIP 2 SOUTH, RANGE 4 EAST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

M. Ross Workman
Cadastral Surveyor

Under special instructions dated and approved **May 4, 2004**, which provided
for the surveys included under Group Number **984**, and assignment
instructions dated **May 4, 2004**.

Survey commenced **May 10, 2004**

Survey completed **June 7, 2004**

INDEX DIAGRAM

Township 2 South, Range 4 East

6	5	4	3	2 2	1
7	8	9	4 10	2 11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

The Subdivision of Section 3.....Page 5

The Subdivision of Section 10.....Page 8

Dependent Resurvey of Mineral Survey 6192.....Page 9

Dependent Resurvey of Mineral Survey 6792.....Page 11

North Right of Way of Highway 248.....Page 14

South Right of Way of Highway 248.....Page 16

Center lines of the Old Railroad Bed and Pathway.....Page 18

TOWNSHIP 2 SOUTH, RANGE 4 EAST, SALT LAKE MERIDIAN, UTAH

The following field notes describe the dependent resurvey of a portion of the subdivisional lines, the subdivision of section 3 and 10, the dependent resurvey of portions of Mineral Surveys 6192 and 6792, and the survey of the north and south right-of-way lines of Utah State Highway No. 248 and the center line of the old railroad bed and pathway, in Township 2 South, Range 4 East, Salt Lake Meridian, Utah.

History of Surveys

Surveyed by		Retr./ or Resurveyed by	
SOUTH BOUNDARY			
All	A.J. Stewart, Jr.	1895	
All			A.P. Hansen 1901
EAST BOUNDARY			
All	J. Gorlinski	1869	
All			A.J. Stewart, Jr. 1895
Portion			R.K. Baugh 1994-95
WEST BOUNDARY			
Portion	J. Gorlinski	1869	
Portion	J.E. Freeman	1871	
Portion	A.J. Stewart, Jr.	1895	
All			A.P. Hansen 1901
All			R. Gentry 1938-44
NORTH BOUNDARY			
All	J. Gorlinski	1869	
All			A.J. Stewart, Jr. 1895
SUBDIVISION			
Portion	J. Gorlinski	1869	
Portion	C.P. Brooks	1876	C.P. Brooks 1876
Portion	A.J. Stewart, Jr.	1895	A.J. Stewart, Jr. 1895
Portion			R.K. Baugh 1994-95
Portion			T.R. Warburton 2000-02

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instruction, 1973 and the Special Instructions for Group No. 984, dated May 4, 2004.

The true meridian direction and length of all lines were determined by Global Positioning System (GPS) utilizing Real-Time Kinematics (RTK) observation using the Trimble 5800 model receiver.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and their calls of record. Identified corners were remonumented in their original positions. Lost

TOWNSHIP 2 SOUTH, RANGE 4 EAST, SALT LAKE MERIDIAN, UTAH

corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations, post processed by National Geodetic Survey, Online Positioning User Service, (OPUS), utilizing Continuously Operating Reference Stations; (CORS) RED BUTTE, SALT LAKE CITY, and MIDVALE. The N.A.D. 1983 (CORS96) geographic position of the 1/4 section corner of sections 2 and 3, is as follows:

Latitude: 40° 40' 32.004" N. Longitude: 111° 28' 22.318" W.
Elevation: 6733 ft.

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 2 S., R. 4 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
J. Gorkinski in 1869

CHAINS

Beginning at the 1/4 section corner of sections 10 and 11, monumented with an iron post, 2 1/2 inches diameter, with a 3 inch brass cap marked:

PARK CITY
1934
BOUNDARY MARKER

Raise a mound of stone, 3 ft. base, 2 ft. high, north of monument.

This monument is accepted as a careful and faithful establishment of the original corner position.

N. 0° 21.2' E., between sections 10 and 11.

40.307

The corner of section 2, 3, 10 and 11, monumented with an iron post, 2 1/2 inches diameter, with a 3 inch brass cap marked:

PARK CITY
1934
BOUNDARY MARKER

Raise a mound of stone, 3 ft. base, 2 ft. high, north of monument.

This monument is accepted as a careful and faithful establishment of the original corner position.

N. 0° 26.9' W. between sections 2 and 3.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 2 S., R. 4 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

9.375 Intersect line 4-1, Clegg No. 1 Lode, Mineral Survey 6792.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

```

S3 | S2
  | |
  C|1
  | |
  6792
  2004
  
```

9.748 Intersect line 2-3, Potosi Lode, Mineral Survey 6192, not monumented.

19.887 Point for the S 1/16 section corner of section 2 and 3, falls on the north shoulder of Utah State Highway No. 248.

Drill a 3 inch deep hole in pavement.

from which:

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, for a reference monument, bears N. 20° 03.2' E., 77.0 lks. distance, with a magnet at base, and aluminum cap marked: "RM S 1/16 50.80 FT S2 2004", and an arrow pointing to the true corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, bears N. 57° 20.0' W., 79.6 lks. distance, with a magnet at base, and aluminum cap marked: "RM S 1/16 52.50 FT S3 2004", and an arrow pointing to the true corner.

from this same corner point:

A fence corner bears N. 28° 24.7' W., 1.348 chains distance. Fences bear E, W, and N.

39.774 The 1/4 section corner of sections 2 and 3, monumented with a conglomerate stone, 12x9x8 inches, plainly marked 1/4 on face, with a rebar alongside and at the corner of fences projecting east, west and south.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

```

T2S R4E
  1/4
S3 | S2
  | |
  2004
  
```

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 2 S., R. 4 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Deposit marked stone alongside the aluminum post, with rebar inside.

From the 1/4 section corner of sections 9 and 10, monumented with a quartzite sandstone, 10x8x10 inches, plainly marked 1/4 on west face, with a one inch pipe without a cap, alongside stone.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, in a collar of stone, with aluminum cap marked:

T2S R4E
1/4
S9 | S10
2004

Deposit marked stone alongside the aluminum post, with 1 inch pipe inside.

N. 0° 10.4' E. between sections 9 and 10.

- 40.421** The corner of sections 3, 4, 9 and 10, monumented with a brass cap, flush with the ground in grass, marked:

PARK CITY
1934
BOUNDARY MARKER

Located east of a paved road that runs between schools.

This monument is accepted as a careful and faithful establishment of the original corner position.

From the corner of sections 2, 3, 10 and 11.

N. 89° 53.2' W. between sections 3 and 10.


- 20.050** Point for the E 1/16 section corner of sections 3 and 10, not monumented.

- 24.178** Intersect line 3-4, Woodrow No. 2 Lode, Mineral Survey 6792.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 2 S., R. 4 E., SALT LAKE MERIDIAN, UTAH**

CHAINS




35.722 Intersect the center line of the old railroad bed and pathway, not monumented.

40.100 Point for the 1/4 section corner of sections 3 and 10, at proportionate distance based on the Hidden Meadow Property Survey, executed by Alliance Engineering Inc. Surveyor John Dewkowitz, dated January 25, 1995, filed with Summit County Recorder, dated February 17, 1995 falls in a swamp. There is no remaining evidence of the original corner.

S. 89° 42.2' E. beginning new measurement.

0.844 Point selected for the witness corner to the 1/4 section corner for section 3 and 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:



5.928 Intersect the south right-of-way line at the R/W 54 marker of Utah State Highway No. 248, monumented with an iron post, 2 inches diameter, projecting 6 inches above ground, with brass cap marked: LS 161249, C/L 18.0613, STA 12+453.25, ELEV 2042.65, YEAR 1999.

39.980 The corner of sections 3, 4, 9 and 10.

The Subdivision of Section 3
T. 2 S., R. 4 E., Salt Lake Meridian

From the true point for the 1/4 section corner of sections 3 and 10.

N. 0° 44.8' E. on the N-S center line of section 3.


1.265 Intersect the south right-of-way line between R/W 53 and R/W 54 of Utah State Highway No. 248, not monumented.

**THE SUBDIVISION OF SECTION 3
T. 2 S., R. 4 E., SALT LAKE MERIDIAN**

CHAINS


- 4.345** Intersect the north right-of-way line between R/W 9 and R/W 10 of Utah State Highway No. 248.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 2 ft. base to top of aluminum cap marked:



- 20.115** Point for the center S 1/16 section corner of section 3.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:



- 40.230** The center 1/4 section corner of section 3, monumented with a metal fence post, 3 inches diameter, projecting 5 ft. above ground, in a concrete base. This position is harmoniously related with identified existing original corners in the area and is accepted as a careful and faithful establishment of the corner position.

Fences project N, E, SE and W.

From the 1/4 section corner of sections 2 and 3.

N. 89° 13.3' W. on the E-W center line section 3.

- 19.632** Point for the center E 1/16 section corner of section 3, not monumented.

- 39.264** The center 1/4 section corner of section 3.

From the point for the E 1/16 section corner of sections 3 and 10.

N. 0° 09.2' E. on the N-S center line of the SE 1/4 of section 3.

- 2.118** Intersect line 3-4, Woodrow No. 2 Lode, Mineral Survey 6792.

**THE SUBDIVISION OF SECTION 3
T. 2 S., R. 4 E., SALT LAKE MERIDIAN**

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

S3
CL SE 1/4
|
6792
W2
2004

6.815 Intersect the center lines of the old railroad bed and pathway, not monumented.

10.192 Intersect the south right-of-way line between R/W 45 and R/W 50 of Utah State Highway No. 248.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with a magnet at base, with aluminum cap marked:

R/W
C
| SE 1/4
C
2004

Set a 2 inch square wood post, 7 feet long, 2 feet in the ground, alongside aluminum post.

13.834 Intersect the north right-of-way line between R/W 12 and R/W 13 of Utah State Highway No. 248.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

C S3
SE 1/4 |
C
R/W
2004

20.000 Point for the SE 1/16 section corner of section 3, at intersection with the E-W centerline of the SE 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and in a collar of stone, with aluminum cap marked:

SE 1/16
S3
2004

**THE SUBDIVISION OF SECTION 3
T. 2 S., R. 4 E., SALT LAKE MERIDIAN**

CHAINS

40.000 The point for the center E 1/16 section corner of section 3, not monumented.

From the S 1/16 section corner of sections 2 and 3.

N. 89° 33.6' W. on the E-W center line of the SE 1/4 of section 3.

0.297 Intersect line 3-4, Eldorado Lode, Mineral Survey 6192.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with a magnet at base, with aluminum cap marked:

$$\begin{array}{c} \text{S3} \\ \text{CL SE } 1/4 \text{ ---} \\ \text{E} \\ 6192 \\ 2004 \end{array}$$

Monument is located under guard rail along north side of highway.

3.787 Intersect the north right-of-way line between R/W 16 and R/W 17, of Utah State Highway No. 248.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with a magnet at base, with aluminum cap marked:

$$\begin{array}{c} \text{S3} \\ \text{CL SE } 1/4 \text{ ---} \\ \text{R/W} \\ 2004 \end{array}$$

19.841 The SE 1/16 section corner of section 3.

39.682 The center S 1/16 section corner of section 3.

The Subdivision of Section 10
T. 2 S., R. 4 E., Salt Lake Meridian

From the true point for 1/4 section corner of sections 3 and 10.

S. 0° 15.8' W. on the N-S center line of section 10, on a mean bearing between the east and west boundaries of the north 1/2 of section 10.

2.526 Intersect the center lines of the old railroad bed and pathway, not monumented.

**THE SUBDIVISION OF SECTION 3
T. 2 S., R. 4 E., SALT LAKE MERIDIAN**

CHAINS

8.603 Intersect line 3-4, Woodrow No. 1 Lode, Mineral Survey, 6792.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

CL |
S10 /
6792 W1
2004

40.507 Point for the center 1/4 section corner of section 10 at intersection with the east-west center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T2S R4E
C 1/4
S10
2004

From the 1/4 section corner of sections 10 and 11.

S. 89° 49.5' W. on the E-W center line of section 10.

40.044 The center 1/4 section corner of section 10.

79.965 The 1/4 section corner of sections 9 and 10.

The Dependent Resurvey of Mineral Survey 6192
T. 2 S., R. 4 E., Salt Lake Meridian, Utah

From corner No. 2, Potosi Lode, Mineral Survey 6192 in section 2, monumented with a 4x4x36 inch wood post, scribed: 2 6192, with a railroad spike and rebar alongside.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

6192
P
2 /
2004

**THE DEPENDENT RESURVEY OF MINERAL SURVEY 6192
T. 2 S., R. 4 E., SALT LAKE MERIDIAN, UTAH**


CHAINS

Deposit the wood post, spike and rebar alongside the aluminum post.

S. 78° 36.8' W., on line 2-3, Potosi Lode.

- 0.695** Intersect line 4-1, Clegg No. 1 Lode, Mineral Survey 6792, not monumented.
- 8.461** Intersect the section line between sections 2 and 3, not monumented.
- 8.474** Point for corner No. 3, Potosi Lode, identical with corner No. 2, El Dorado Lode, same survey, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:




Corner is located 10 feet north of a trail.

S. 89° 21.9' W. on line 2-3, Eldorado Lode, same survey.

- 14.304** Corner No. 3, Eldorado Lode Mineral Survey 6192, monumented with a 1 inch square rod, with cap and illegible marking on it, in a mound of stone. This is accepted as the best available evidence of the original corner position.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, and in a collar of stone, with aluminum cap marked:




Raise a mound of stone, 4 foot base, 2 foot high, southwest of corner.

N. 50° 13.0' E., on record bearing of line 3 and 4, Eldorado Lode.

**THE DEPENDENT RESURVEY OF MINERAL SURVEY 6192
T. 2 S., R. 4 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

- 2.268** Intersect center lines of the old railroad bed and pathway, not monumented.
- 12.998** Intersect the south right-of-way line between R/W 41 and R/W 42, of Utah State Highway No. 248, not monumented. This intersect point is on a record Meridian Engineering and surveying bearing, on the south right-of-way line, between R/W 41 and R/W 42.
- 18.049** Intersect the E-W center line of the SE 1/4 of section 3.
- 23.735** Corner No. 4, Eldorado Lode, at record bearing and distance from corner No. 3. Corners No. 1, 2 and 4 could not be found.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:



The Dependent Resurvey of Mineral Survey 6792
T. 2 S., R. 4 E., Salt Lake Meridian

From the point for corner No. 3, Woodrow No. 1 Lode, Mineral Survey 6792, on line 2-3, Sunrise Lode, Mineral Survey 5490, in section 10, not monumented, there is no remaining evidence of the original corner. This point was reestablished by the Grant Boundary method.


From this point, corner No. 2, Woodrow No. 1 Lode, Mineral Survey 6792 in section 10, identical with corner No. 4, Woodrow No. 3, same survey, and on line 2-3 Little Bessie Lode, Mineral Survey 5490, monumented with a mound of stone, bears S. 41° 01.2' E., 9.277 chains distance. This mound is excepted as the best available evidence of the original corner position.

At the corner point (center of the mound)

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

**THE DEPENDENT RESURVEY OF MINERAL SURVEY 6792,
T. 2 S., R. 4 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS



Raise a mound of stone, 3 ft. base, 2 ft. high, west of monument.


N. 60° 09.8' E., on line 3-4, Woodrow No. 1 Lode.

15.003 Intersect the N-S center line of section 10.

22.753 Corner No. 4, Woodrow No. 1 Lode, identical with corner No. 3, Woodrow No. 2 Lode, same survey, monumented with a 5/8 inch rebar, with yellow cap marked: ALLIANCE ENGR LS 6164, in a mound of stone and an old wood post 4x4 inches square, marked W NO 2, lying alongside.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:



Deposit the rebar and cap inside the aluminum post.

Reset the 4x4 post alongside the aluminum post.

N. 62° 57.6' E., on line 3-4, Woodrow No. 2 Lode, Mineral Survey 6792.

10.373 Intersect the section line between sections 3 and 10.

15.014 Intersect the N-S center line of the SE 1/4 of section 3.


22.751 Corner No. 4, Woodrow No. 2 Lode, on line 2-1, Clegg No. 1 Lode, same survey, monumented with a 5/8 inch rebar, with yellow cap marked: ALLIANCE ENGR LS 6164, in a mound of stone with old wood post 4x4 inches square.

At the corner point.

**THE DEPENDENT RESURVEY OF MINERAL SURVEY 6792,
T. 2 S., R. 4 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:



Deposit the rebar and cap inside the aluminum post.

Reset the 4x4 post alongside the aluminum post.

Raise a mound of stone 2 ft. base, 1 ft. high, north of aluminum post.


N. 43° 54.6' W., on line 2-1, Clegg No. 1 Lode, Mineral Survey 6792.

0.470

Corner No. 1, Clegg No. 1 Lode, monumented with a 5/8 inch rebar, with yellow cap marked: ALLIANCE ENGR LS 6164, in a mound of stone, with an old wood post 4x4 inches square.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 4 ft. base to top of aluminum cap marked:



Deposit rebar and cap inside the aluminum post.

Reset the 4x4 post alongside the aluminum post.

N. 75° 55.5' E., on line 1-4, Clegg No. 1 Lode, Mineral Survey 6792.

13.821

Intersect the section line between sections 2 and 3.

21.668

Intersect line 2-3, Potosi Lode, Mineral Survey 6192, not monumented.


22.722

Point for corner No. 4, Clegg No. 1 Lode, determined from a record calculated tie to corner No. 2, Potosi Lode, Mineral Survey 6192, bears S. 70° 26.9' W., 0.363 chains distance.

**THE DEPENDENT RESURVEY OF MINERAL SURVEY 6792,
T. 2 S., R. 4 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:



From this corner, a rebar bears S. 77° 23.5' E., 8.5 feet distance. The rebar was removed and placed inside the aluminum post.

North Right-of-Way Line of Utah State Highway No. 248
T. 2 S., R. 4 E., Salt Lake Meridian, Utah

Note: The north and south right-of-way lines, of Utah State Highway No. 248, in section 3 is based on the as built survey by Meridian Engineering and Surveying, LC, surveyor certificate on plats dated October 1 2001.

From corner R/W 5, a Utah State Highway No. 248, monument, located on the north right-of-way line on the east side of Park City, monumented with an iron post, 2 inches diameter, projecting 6 inches above ground, with brass cap marked: LS 161249, C/L 18.85, STA 12+189.85, ELEV 2045.74, YEAR 1999.

N. 29° 26.7' E., on north right-of-way line between R/W 5 and R/W 6.

3.932 Point for corner R/W 6 at proportionate distance, there is no remaining evidence of the original corner position, not remonumented.

S. 61° 46.6' E., on north right-of-way line between R/W 6 and R/W 7.

5.206 Point for corner R/W 7 at proportionate distance. Meridian Engineering and Surveying did not monument this corner position, not monumented.

N. 79° 24.1' E., on north right-of-way line between R/W 7 and R/W 8.

5.273 Point for corner R/W 8 at proportionate distance. Meridian Engineering and Surveying did not monument this corner position, not monumented.


**NORTH RIGHT-OF-WAY LINE OF UTAH STATE HIGHWAY No. 248,
T. 2 S., R. 4 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

N. 84° 24.6' E., on north right-of-way line, between R/W 8 and R/W 9.

- 5.317** Point for corner R/W 9 at proportionate distance. Meridian Engineering and Surveying did not monument this corner position.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 2 ft. base to top of aluminum cap marked:

S3

 R/W 9
 2004

N. 64° 36.3' E., on north right-of-way line between R/W 9 and R/W 10.

- 2.485** Intersect the N-S center line of section 3.

- 2.530** Point for corner R/W 10 at proportionate distance. Meridian Engineering and Surveying did not monument this corner position, not monumented.

N. 64° 21.8' E., on north right-of-way line between R/W 10 and R/W 12.

Note: Corner R/W 11 was not monumented by Meridian Engineering and Surveying.

- 18.469** Point for corner R/W 12 at proportionate distance. Meridian Engineering and Surveying did not monument this corner position.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

S3

 R/W 12
 2004

N. 66° 40.7' E., on north right-of-way line between R/W 12 and R/W 13.

- 3.636** Intersect the N-S center line of the SE 1/4 of section 3.

**NORTH RIGHT-OF-WAY LINE OF UTAH STATE HIGHWAY No. 248,
T. 2 S., R. 4 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

- 7.895** Corner R/W 13, on north right-of-way line, monumented with an iron post, 2 inches diameter, with brass cap marked: LS 161249, C/L 37.47, STA 13+126.62, ELEV 2047.64, YEAR 1999.
- No other improvements were made at this corner position.
-
- N. 36° 21.3' E., on north right-of-way line between R/W 13 and R/W 14.
- 1.013** Corner R/W 14, on north right-of-way line, monumented with an iron post, 2 inches diameter, with brass cap marked: LS 161249, C/L 48.06, STA 13+143.75, ELEV 2048.99, YEAR 1999.
- No other improvements were made at this corner position.
-
- S. 76° 01.8' E., on north right-of-way line between R/W 14 and R/W 15.
- 1.336** Corner R/W 15, on north right-of-way line, monumented with an iron post, 2 inches diameter, with brass cap marked: LS 161249, C/L 32.32, STA 13+165.18, ELEV 2046.69, YEAR 1999.
- No other improvements were made at this corner position.
-
- N. 69° 21.9' E., on north right-of-way line, between R/W 15 and R/W 16.
- 10.880** Point for corner R/W 16 at proportionate distance. Meridian Engineering and Surveying did not monument this corner position, not monumented.
-
- N. 69° 22.5' E., on north right-of-way line, between R/W 16 and R/W 17.
- 0.084** Intersect the E-W center line of the SE 1/4 of section 3.
- 4.798** Corner R/W 17, on north right-of-way line in section 2, monumented with an iron post, 2 inches diameter, with brass cap marked: LS 161249, C/L 32.0322, STA 13+480.01, ELEV 2048.10, YEAR 1999.

South Right-of-Way Line of Utah State Highway No. 248,
T. 2 S., R. 4 E., Salt Lake Meridian, Utah

From the intersect point on the south right-of-way line and line 3-4, Eldorado Lode, Mineral Survey 6192, not monumented.

**SOUTH RIGHT-OF-WAY LINE OF UTAH STATE HIGHWAY NO. 248,
T. 2 S., R. 4 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

S. 69° 26.4' E., on a record Meridian Engineering and Surveying bearing, on south right-of-way line, between R/W 41 and R/W 42.

- 2.744** Corner R/W 42, on south right-of-way line, monumented with an iron post, 2 inches diameter, with brass cap marked: LS 161249, C/L 26.5044, STA 13+299.50, ELEV 2040.20, YEAR 1999.
-

S. 22° 12.7' W., on south right-of-way line, between R/W 42 and R/W 43.

- 0.911** Corner R/W 43, on south right-of-way line, monumented with an iron post, 2 inches diameter, with brass cap marked: LS 161249, C/L 39.9559, STA 13+287.06, ELEV 2038.06, YEAR 1999.
-

S. 69° 22.1' W., on south right-of-way line, between R/W 43 and R/W 44.

- 3.730** Corner R/W 44, on south right-of-way line, monumented with an iron post, 2 inches diameter, with brass cap marked: LS 161249, C/L 39.9673, STA 13+212.02, ELEV 2038.35, YEAR 1999.
-

N. 59° 21.8' W., on south right-of-way line, between R/W 44 and R/W 45.

- 0.932** Point for corner R/W 45 at proportionate distance; there is no remaining evidence of the original corner position, not monumented.
-

Note: R/W 46 to R/W 49 was never monumented by Meridian Engineering and Surveying.

S. 65° 59.1' W., on south right-of-way line, between R/W 45 and R/W 50.

- 9.284** Intersect the N-S center line of the SE 1/4 of section 3.

- 12.336** Corner R/W 50, on south right of way line, monumented with an iron post, 2 inches diameter, with brass cap marked: LS 161249, C/L 27.2914, STA 12+949.89, ELEV 2028.75, YEAR 1999.
-

S. 70° 52.8' W., on south right-of-way line, between R/W 50 and R/W 51.

- 4.209** Point for corner R/W 51, on south right-of-way line, at proportionate distance, falls in swamp. Meridian Engineering and Surveying did not monument this corner position, not monumented.
-

**SOUTH RIGHT-OF-WAY LINE OF UTAH STATE HIGHWAY NO. 248,
T. 2 S., R. 4 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Note: Corners R/W 52 and R/W 53 were never monumented by Meridian Engineering and Surveying.

S. 64° 42.0' W., on south right-of-way line, between R/W 51 and R/W 53.

14.635 Point for corner R/W 53, on south right-of-way line, at proportionate distance, falls in swamp, not monumented.

S. 77° 42.8' W., on south right-of-way line, between R/W 53 and R/W 54.

0.066 Intersect the N-S center line of section 3, falls in swamp, not monumented.

6.149 Corner R/W 54, on south right-of-way line, at intersection with, the line between sections 3 and 10, hereinbefore described.

Survey of Center Line of Old Railroad Bed and Pathway
T. 2 S., R. 4 E., Salt Lake Meridian, Utah

From the point for the corner B 1, on center line on top of old railroad bed and also center line of pathway, in section 10.

Drive a PK nail in the pavement.

N. 59° 02.5' E.

2.526 Intersect the N-S center line of section 10, not monumented.

4.939 Point for corner B 2 on center lines of old railroad bed and pathway.

Drive a PK nail in the pavement.

N. 61° 11.9' E.

2.657 Intersect the section line between sections 3 and 10, not monumented.

4.223 Point for corner B 3 on center lines of old railroad bed and pathway.

Drive a PK nail in the pavement.

N. 64° 31.8' E.

**SURVEY OF CENTER LINE OF OLD RAILROAD BED AND PATHWAY
T. 2 S., R. 4 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

5.193 Point for corner B 4 on center lines of old railroad bed and pathway.

Drive a PK nail in the pavement.

N. 68° 29.1' E.

10.350 Intersect the N-S center line of the SE 1/4 of section 3, not monumented.

18.359 Intersect line 3-4, Eldorado Lode, Mineral Survey 6192, not monumented.

33.083 Point for corner B 5 on center lines of old railroad bed and pathway in section 2.

Drive a PK nail in the pavement.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Glen B. Hatch Tyler Trujillo	Cadastral Surveyor Survey Technician

CERTIFICATE OF SURVEY

I, **M. Ross Workman, Cadastral Surveyor**, hereby certify upon honor, that in pursuance of special instructions bearing the date of the **4th day of May, 2004**, I have **dependently resurveyed a portion of the subdivisional lines, the subdivision of sections 3 and 10, the dependent resurvey of portions of Mineral Surveys 6192 and 6792. Survey of the North and South Right-of-Way Lines of Utah State Highway No. 248, and the center line of the old Railroad bed and pathway, in Township 2 South, Range 4 East,**

of the **Salt Lake Meridian**, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special and supplemental special instructions, the Manual of Instructions of the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

3-28-2005
Date

M. Ross Workman
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The following field notes of the **dependent resurvey of a portion of the subdivisional lines, the subdivision of sections 3 and 10, the dependent resurvey of portions of Mineral Surveys 6192 and 6792. Survey of the North and South Right-of-Way Lines of Utah State Highway No. 248, and the center line of the old Railroad bed and pathway, in Township 2 South, Range 4 East, Salt Lake Meridian, Utah,**

executed by **M. Ross Workman, Cadastral Surveyor** having been critically examined and found correct, are hereby approved

April 19, 2005
Date

Daniel W. Webb
(Chief Cadastral Surveyor)