

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE INVESTIGATIONAL RETRACEMENT,  
INDEPENDENT RESURVEY,

AND

DEPENDENT RESURVEY  
OF THE  
EAST PORTION OF THE SOUTH BOUNDARY,  
SOUTH PORTION OF THE EAST BOUNDARY

AND THE

SUBDIVISIONAL LINES FOR  
SECTIONS 25, 26, 35, 36 AND TRACT 37

WITHIN

TOWNSHIP 14 NORTH, RANGE 03 EAST

OF THE SALT LAKE MERIDIAN IN THE STATE OF UTAH

EXECUTED BY

**FRANK C. PROFAIZER**  
**CADASTRAL SURVEYOR**

Under Special Instructions dated **February 14, 2005**, which provided for the surveys included within Group Number **990**, approved **February 14, 2005**, and Assignment Instructions dated **February 14, 2005**.

Investigational Retracement commenced under the authority of the Cache National Forest on **August 9, 2004**, under the direction of Thomas L. Tidwell, Forest Supervisor.

Independent Resurvey and Dependent Resurvey commenced on **July 06, 2005**.  
Independent Resurvey and Dependent Resurvey completed on **October 21, 2005**.

# INDEX DIAGRAM

Township 14 North, Range 03 East

6	5	4	3	2	1
7	8	9	<b>25</b> 10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
				<b>24</b>	<b>30</b> <b>18</b>
30	29	28	27	26 <b>32</b>	<b>23</b> 25 <b>17</b>
				<b>29</b> <b>21</b>	<b>28</b> <b>15</b>
31	32	33	34	35 <b>18</b>	<b>25</b> 36 <b>14</b>
				<b>12</b> <b>11</b> <b>9</b>	<b>7</b> <b>6</b>

Tract 37 .....	Page 32
Location of the Iron Rod .....	Page 33
The Subdivision of Section 25 .....	Page 34
The Subdivision of Section 36 .....	Page 35
General Description .....	Page 46

The following Field Notes describe the Investigational Retracement, Independent Resurvey, and Dependent Resurvey of the East Portion of the South Boundary, the South Portion of the East Boundary, and the Subdivisional Lines for Sections 25, 26, 35, and 36, along with the segregation of Tract 37, within Sections 25 and 26, that is situated in the South West One Quarter of Section 25, of Township 14 North, Range 03 East, Salt Lake Meridian, Utah.

#### HISTORY OF SURVEYS

<u>BOUNDARIES</u>	<u>SURVEYED BY</u>		<u>RESURVEYED BY</u>	
SOUTH	J. H. Martineau	1881	F. E. Joy	1904
EAST	J. H. Martineau	1881	F. E. Joy F. C. Profaizer	1904 1982-83
WEST	J. H. Martineau	1881		
NORTH	J. H. Martineau	1881		
SUBDIVISION	J. H. Martineau	1881	F. D. Reynolds	1968

**Note:** Portions of the above Official Field Note Record are transcribed into the body of these Field Notes using "Italicized Script". The original Field Notes are on file within the Bureau of Land Management.

The Resurvey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions 1973, and the Special Instructions for Group Number 990, Utah dated February 14, 2005.

Preliminary to the Independent Resurvey and Dependent Resurvey, the lines of the Original Survey were retraced and a thorough search was made for all corners and other calls of the official record. Identified corners were remonumented in their original positions, lost corners were restored and monumented at record and proportionate positions based on the Original Record. The Retracement data were thoroughly verified with the Official Field Notes and only the true lines are given herein.

Previous to the Independent Resurvey and Dependent Resurvey, an Investigation Retracement was conducted by the Wasatch-Cache National Forest Service (NFS), under the direction of Sandy Lewis, Lead Land Surveyor for the Utah Zone Boundary and Title Management. All of the surveying pertaining to the Investigation Retracement was done under the authority of the Wasatch-Cache National Forest Service and under the authorization of Thomas L. Tidwell, Forest Supervisor.

The Investigational Retracement for the Boundary between Sections 25 and 26, identified an "Iron Rod" in the direction of **S 81° 26.5' W**; and a chain distance of **01.543**; from the One Quarter Section Corner for Sections 25 and 26. From research conducted on official documents provided by Mr. Richard Israelsen that was sent to the Wasatch-Cache National Forest on May 25, 2004, it was determined that Mr. Erwin U. Moser was most likely the one who set or perpetuated the "Iron Rod" position. Apparently Mr. Erwin U. Moser was the Engineer and Land Surveyor for Cache County. His License Number 101386-2202 was issued on January 01, 1910, and had an expiration date of April 30, 1986.

The property ownership for the South-West One Quarter for Section 25 was established from the TAX UNIT NUMBER 19, which is recorded on the Survey Plat on file with the Cache County Courthouse. The Survey Plat was filed on August 27, 1966 by Ms. M. Lynne McKee.

Mr. Paul B. Crookston, a resident of the area for many years and owner of parcel Number 18-064-002; within the South-West One Quarter of Section 25, furnished a signed statement that is attached to and made a part of these Field Notes, attesting to the corner position for the "Iron Rod".

The controlling exterior alignment for the South-West One Quarter of Section 25, and the newly created Tract 37, was established from the following controlling monuments;

1. The Section Corner for Sections 25, 30, 31, and 36, on the East Boundary of the Township.
2. The Section Corner for Sections 19, 24, 25, and 30, on the East Boundary of the Township.
3. The Section Corner for Sections 25, 26, 35, and 36.
4. The East One Quarter Section Corner for Sections 35.
5. The One Quarter Section Corner for Sections 26 and 35.
6. The One Quarter Section Corner for Sections 25 and 26.
7. The identified "Iron Rod" and Witness Point for Tract 37.

The "Iron Rod" a Witness Point for Tract 37, was also identified by Nicholas Welch Crookston, who apparently put a "Cedar Post" next to the "Iron Rod" and pointed it out to Robert Burns Crookston. At a later time in 1947, Robert Burns Crookston informed Lyle E. Israelsen of the location for the "Iron Rod". This position was indicated at the North-West Corner of the South-West Quarter Section of Section 25. Township 14 North, Range 03 East, Salt Lake Meridian, Utah.

It has also been supposed that James H. Martineau, the Cache County Surveyor from 1860 to 1884, was most likely responsible in setting the "Iron Rod" for the One Quarter Section Corner of Sections 25 and 26. After a thorough review of the official survey done under Contract Number 100, for the United States General Land Office and the Biographical Events for James H. Martineau, it would not be feasible for that discharge of duties to occur.

**Fact One:** James H. Martineau was called to a L.D.S. Church position, as a Second Counselor to President Christopher Layton. This occurred in the year of 1884, when James H. Martineau was 56 years old, and required him to relocate in Arizona.

**Fact Two:** James H. Martineau did not return to Utah until 1903, at which time he established temporary residence in Salt Lake City. James H. Martineau was 75 years old and was starting to have difficulties with rigors of hiking and traversing the rugged mountainous terrain with his aging body.

**Fact Three:** The Homestead Entry was filed on October 14, 1896, by Nicholas Welch Crookston for the South-West One Quarter of Section 25, Township 14 North, Range 03 East, Salt Lake Meridian, Utah. It was at this time that the James H. Martineau residence was at Colonia Juarez, Mexico.

**Fact Four:** On November 23, 1905 the United States Land Office, notified Nicholas Welch Crookston that he needed to file proof of reclamation on his land and make final payment for 160 acres of "Un-Surveyed Land", within the

South-West 1/4 of Section 25, Township 14 North, Range 03 East, Salt Lake Meridian, Utah. The date of action shows that James H. Martineau still had his main residence at Colonia Juarez, Mexico.

[ NOTE: ]

The following attachments; "Documentary of Historical Evidence" have been provided to explain the events leading up to the acceptances of the "Iron Rod" and the designation of the Witness Point for Tract 37. The transcribed documents have been included at the end of these Field Notes after the General Description to show historical evidence.

Biographical Events for James Henry Martineau was transcribed from segments within the L.D.S. Biographical Encyclopedia, Andrew Jenson, (Vol. 3, page 156) and the Utah Historical Quarterly "Running the Line; James Henry Martineau's Surveys in Northern Utah, 1860-1882" by Noel A. Carmack.

- { 01 } 2004/07/07 Affidavit Letter by: Lyle E. and Marianna Israelsen.
- { 02 } 2004/06/03 Affidavit Statement by: Paul B. Crookston.
- { 03 } 2004/04/29 Affidavit Letter by: Lyle E. and Marianna Israelsen.
- { 04 } 1905/11/23 Letter from Commissioner for General Land Office.
- { 05 } 1896/10/14 Historical Index for T14N R03E, Section 25.
- { 06 } 1881/03/19 Contract No. 100: Index for Deputy Surveyor Field Notes.
- { 07 } 1881/03/19 Contract No. 100: Cross-Examination of Work Schedule.
- { 08 } 1881/03/19 Contract No. 100: Results for Cross-Examination.
- { 09 } 1828/03/13 Biographical Events for James Henry Martineau.
- { 10 } Search Areas of Controlling Corner Positions.

The Directions of lines were determined by reference to true meridians established by the Global Positioning System, utilizing fast static survey techniques observed with Trimble (5800) model Global Positioning System equipment based on the following information.

This survey is based on the **North American Datum of 1983**, with International Feet being ( 1 Meter = 3.280839895 Feet ) and U. S. Survey Feet being ( 1 Meter = 3.280833333 Feet ), with a **Project Elevation of 6,000 feet** above mean sea level.

The Geodetic Coordinates shown have been converted using; U. S. Army Corps of Engineers Conversion Software Corpscon ver. 5.11.08, from the published U.S.G.S. and N.A.D 1927 Coordinates.

**NATIONAL GEODETIC SURVEY TRIANGULATION STATION: "SINKER"**

National Geodetic Survey Data Sheet:

North American Datum 1927	Utah North Zone ( SPC 4301 UT-N )
Latitude: 41° 53' 25.15"	Northing: 0,567,285.176 US Feet
Longitude: 111° 31' 51.40"	Easting: 1,991,573.874 US Feet
Elevation: 8589.00 US Feet	Elevation: 8589.00 US Feet

Army Corps of Engineers Conversion Software:

North American Datum 1983	Utah North Zone ( SPC 4301 UT-N )
Latitude: 041° 53' 24.9063"	Northing: 3,848,110.456 INT Feet
Longitude: 111° 31' 54.1626"	Easting: 1,631,785.074 INT Feet
Elevation: 8593.37 INT Feet	Elevation: 8593.37 INT Feet

## Wasatch-Cache National Forest Service GPS Occupancy:

North American Datum 1983	Utah North Zone ( SPC 4301 UT-N )
Latitude: 041° 53' 24.92290"	Northing: 3,848,112.135 INT Feet
Longitude: 111° 31' 54.09450"	Easting: 1,631,790.225 INT Feet
Elevation: 8538.581 INT Feet	Elevation: 8538.581 INT Feet

**NATIONAL GEODETIC SURVEY "OPUS" SOLUTION REPORT FOR  
CONTROL POINTS WITHIN FRANKLIN BASIN**

## Base Station Number One:

Forest Service GPS	Utah North Zone ( SPC 4301 UT-N )
Latitude: 041° 55' 58.2109"	Northing: 3,863,634.766 INT Feet
Longitude: 111° 34' 06.6456"	Easting: 1,621,776.744 INT Feet
Elevation: 6638.54 INT Feet	Elevation: 6638.54 INT Feet

## Base Station Number Two:

Forest Service GPS	Utah North Zone ( SPC 4301 UT-N )
Latitude: 041° 55' 51.3419"	Northing: 3,862,938.491 INT Feet
Longitude: 111° 33' 50.2668"	Easting: 1,623,014.256 INT Feet
Elevation: 6656.62 INT Feet	Elevation: 6656.62 INT Feet

## Base Station Number Three:

Bureau of Land Management GPS	Utah North Zone ( SPC 4301 UT-N )
Latitude: 041° 55' 15.6812"	Northing: 3,859,327.504 INT Feet
Longitude: 111° 33' 28.6129"	Easting: 1,624,648.651 INT Feet
Elevation: 6665.55 INT Feet	Elevation: 6665.55 INT Feet

**GEOGRAPHIC POSITION FOR:** The South-East Township Corner of Township 14 North, Range 03 East, Salt Lake Meridian, Utah, is as follows:

Corner Point Identity: <b>E700N100</b>	Utah North Zone ( SPC 4301 UT-N )
Latitude: 041° 54' 21.6391"	Northing: 3,853,855.228 INT Feet
Longitude: 111° 32' 50.0586"	Easting: 1,627,560.411 INT Feet
Elevation: 7591.54 INT Feet	Elevation: 7591.54 INT Feet

**DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

Restoring the Surveys Executed By J. H. Martineau in 1881, and  
F. E. Joy in 1904

---

**ITALICIZED SCRIPT USED FOR RECORD HISTORY**

**Record:** (For the Original Survey of J. H. Martineau  
commenced on June 24, 1881)

**Note:** (This information is found in the General Land  
Office Book 174, on page 145)

At corner point for Townships 13 and 14 North, Ranges 3 and 4  
East, SLM.

Set Limestone 15 x 12 x 4 inches, with a mound of stone,  
marked 6 notches on the North, South, East, and West edges,  
for the corner to Townships 13 and 14 North, Ranges 3 and 4  
East, on high Mountain that bears North and South. From this  
corner a high peak bears S 62° 30' W, about one mile distance.  
A High rocky point of a Mountain bears N 73° 30' W, about 2  
miles distance.

**Record:** (For the Dependent Resurvey of F. E. Joy commenced  
on October 18, 1904)

**Note:** (This information is found in General Land Office  
Book 329, on pages 126-127)

At corner point for Townships 13 and 14 North, Ranges 3 and 4  
East, SLM.

Find no trace of the corner set in 1881 by J. H. Martineau  
after conducting a retracement of boundaries North-South and  
East-West. Set iron U.S. Forest Reserve Boundary Post Number  
70, which is an iron post 4 feet long, 4 inches diameter, 3  
feet in the ground for corner of Townships 13 and 14 North,  
Ranges 3 and 4 East, with brass cap marked:

( U.S. FOREST RESERVE )

N/W Quadrant with: ( R3E S 36 )

N/E Quadrant with; ( T14N S 31 )

S/W Quadrant with; ( T13N S 01 )

S/E Quadrant with; ( R4E S 06 )

( No. 70 )

Raise a mound of stone 2 feet base, 1 1/2 feet high South of  
Corner.

From which a Pine 8 inches diameter bears N 31° 45' E, 284  
links distance, marked T14N R4E S31 BT.

---

**DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

**Beginning** at the Township Corner of Townships 13 and 14 North, and Ranges 03 and 04 East, monumented with an Iron Post 3 inches diameter, firmly set, projecting 22 inches above ground, as described in the official record of the 1904 Dependent Resurvey with Brass cap marked:

U S FOREST RESERVE  
T14N  
R3E S 36 | S 31 R4E  
S 1 | S 6  
T13N  
No. 70

No original bearing trees were found.

Corner Point Identity: **E700N100**  
Latitude: **41° 54' 21.639"**  
Longitude: **111° 32' 50.059"**  
Elevation: **7,591.54 ft.**

From this Township Corner the **National Geodetic Survey, Triangulation Station "SINKER"** bears **S 36° 21' 42.3" E** on a forward bearing and **N 36° 21' 04.9" W** on a back bearing, with a chain distance of **108.084** and a mean elevation of **8,092.50** feet.

---

From the South-East Township Corner, heretofore described.

Corner Point Identity: **E700N100**

**S 89° 02.0' W**, Beginning new measurement between sections 1 and 36, on a new bearing direction, along South Boundary of Township.

---

**ITALICIZED SCRIPT USED FOR RECORD HISTORY**

**Record:** (*For the Original Survey of J. H. Martineau commenced on August 2, 1881*)

**Note:** (*This information is found in the General Land Office Book 174, on page 164*)

At corner point for the 1/4 Section Corner of Sections 1, and 36, on South Boundary of Township. Set a Limestone 14 x 12 x 12 inches, 11 inches in the ground with a mound of stone marked 1/4 on North side for 1/4 Section Corner.

**Record:** (*For the Dependent Resurvey of F. E. Joy completed in 1904*)

**Note:** (*This information is found in the General Land Office Book 329, on page 126*)

**DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

At corner point for the 1/4 Section Corner of Sections 1, and 36, on South Boundary of Township. This Corner was established on October 19, 1904. Thence run West on a Random Line on East Half, between Sections 1 and 36. At 47.19 chains intersect North and South line 5.52 chains North of 1/4 section corner on South Boundary of Section 36, which is a Limestone 8 x 8 x 6 inches above ground, marked and witnessed as described by the General Land Office. To further establish corner marked two Bearing Trees.

An Aspen, 6 inches diameter, bears S 80° 50' E., 68 links distance, marked 1/4 S 1 BT.

An Aspen 4 inches diameter, bears N 87° 10' W, 41 links distance, marked 1/4 S 36 BT.

**41.800**

Point for the 1/4 Section Corner of Sections 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 20 inches in the ground, with aluminum cap marked:

T14N R3E  
S 36  
1/4 —————  
S 1  
T13N  
2005

Raise a mound of stone, 3 feet base, 2 feet high, encircling corner to top of cap.

Corner bears 13 feet North of East-West fence line.

Corner Point Identity: **E640N100**

Latitude: **41° 54' 21.179"**

Longitude: **111° 33' 26.522"**

Elevation: **6,648.44 ft.**

From the 1/4 Section Corner for Sections 1 and 36, on South Boundary of Township, heretofore described.

Corner Point Identity: **E640N100**

**S 89° 02.0' W**, Continuing between Sections 1 and 36, along South boundary of Township.

**DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

**ITALICIZED SCRIPT USED FOR RECORD HISTORY**

**Record:** (For the Dependent Resurvey of F. E. Joy commenced on October 18, 1904 )  
**Note:** (This information is found in the General Land Office Book 329, on page 126 )

At Witness Corner point for Boundary Post Number 71, Set an iron post 4 feet long, 4 inches diameter, 3 feet in the ground, with brass cap for Forest Reserve Boundary line post marked on cap Number 71.

**66.193**

Point of Intersection with tie direction of **S 00° 58' E** and chain distance of **2.330** to Witness Corner set by F.E. Joy for Forest Reserve Boundary Mile Post Number 71. monumented with an Iron Post 3 inches diameter, firmly set, projecting 22 inches above ground, with brass cap marked as described in the official record of the 1904 Dependent Resurvey.

Corner Point Identity: **E617N095**  
 Latitude: **41° 54' 19.394"**  
 Longitude: **111° 33' 47.774"**  
 Elevation: **6,376.25 ft.**

From the Point of Intersection on the South Boundary of Section 36, heretofore described.

Corner Point Identity: **E617N100**

**S 89° 02.0' W**, Continuing between Sections 1 and 36, along South Boundary of Township.

**ITALICIZED SCRIPT USED FOR RECORD HISTORY**

**Record:** (For the Original Survey of J. H. Martineau commenced on August 2, 1881)  
**Note:** (This information is found in the General Land Office Book 174, on page 165)

At corner point for Sections 1, 2, 35, and 36, on the South Boundary of Township. Set Sandstone 16 x 12 x 10 inches, 11 inches in the ground with a mound of stone marked 1 notch on East and 5 notches on West edges for the corner.

**Record:** (For the Dependent Resurvey of F. E. Joy commenced on October 18, 1904)  
**Note:** (This information is found in the General Land Office Book 329, on page 128)

**DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

At corner point for Sections 1, 2, 35, and 36, found Granite Stone 10 x 8 x 4 inches above ground marked and witnessed as described by the General Land Office, with mound of stone to North. To further establish corner marked the following Bearing Trees.

An Aspen 8 ins. diameter, bears N 31° 30' E, 27 links distance, marked T14N R3E S36BT.

An Aspen 8 ins. diameter, bears S 21° 15' E, 26 links distance, marked T13N R3E S1 BT.

An Aspen 8 ins. diameter, bears S 71° 30' W, 06 links distance, marked T13N R3E S2 BT.

An Aspen 6 ins. diameter, bears N 40° 30' W, 23 links distance, marked T14NR3E S35BT.

From which the corner point for the Forest Reserve Boundary Post Number 72, bears **N 83° 35' W** for chain distance of **00.06**.

Set an iron post 4 feet long, 4 inches diameter, 3 feet in the ground for Witness Corner to Corner of Sections 1, 2, 35, and 36, with brass cap marked:

( W.C. )  
( US FOREST RESERVE )  
( T14N R3E )  
N/W Quadrant with: ( S 35 )  
N/E Quadrant with; ( S 36 )  
S/W Quadrant with; ( S 02 )  
S/E Quadrant with; ( S 01 )  
( T13N )  
( NO. 72 )

**83.600**

The Corner of Sections 1, 2, 35, and 36, monumented with a Sandstone 20 x 8 x 4 inches with 5 grooves on the West and 1 groove on the East.

At the corner point;

Set an Iron post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground, with aluminum cap marked, encircled with a collar of stone.

T14N R3E	
S 35	S 36
S 2	S 1
T13N	
2005	

Corner Point Identity: **E600N100**  
Latitude: **41° 54' 20.720"**

**DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

Longitude: **111° 34' 02.989"**  
Elevation: **6,513.55 ft.**

Deposit the marked stone along side the iron post from which a Witness Corner set by F.E. Joy for Forest Reserve Boundary Mile Post Number 72, direction of **N 20° 24.6' W**; at chains distance of **00.183**, monumented with an Iron Post 3 inches diameter, firmly set, projecting 22 inches above ground, as described in the official record of the 1904 Dependent Resurvey with brass cap marked:

WC  
U S FOREST RESERVE  
T14N R3E  
S 35 | S 36  
S 2 | S 1  
T13N  
No. 72

Corner Point Identity: **E580N103**  
Latitude: **41° 54' 20.832"**  
Longitude: **111° 34' 03.045"**  
Elevation: **6,512.58 ft.**

From the Section Corner for Sections 1, 2, 35, and 36, heretofore described.

Corner Point Identity: **E600N100**

**N 89° 58.0' W**, Beginning new measurement between Sections 2 and 35, along South boundary of Township.

***ITALICIZED SCRIPT USED FOR RECORD HISTORY***

**Record:** (*For the Original Survey of J. H. Martineau commenced on August 2, 1881*)

**Note:** (*This information is found in the General Land Office Book 174, on page 165*)

*At corner point for 1/4 Section Corner of Sections 2 and 35, on South Boundary of Township.*

*Set a Sandstone 15 x 12 x 5 inches, 10 inches in the ground with a mound of stones, marked 1/4 on North side for 1/4 Section Corner.*

**Record:** (*For the Dependent Resurvey of F. E. Joy commenced on October 24, 1904*)

**DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

**Note:** (This information is found in the General Land Office Book 329, on page 130)

At corner point for 1/4 Section Corner of Sections 2 and 35, on South Boundary of Township.

Find no trace of the corner set in 1881 by J. H. Martineau after conducting a Retracement of boundaries East-West. Set a Limestone 18 x 12 x 7 inches, 14 inches in the ground for 1/4 Section Corner marked 1/4 on North face, From which following trees where marked:

An Aspen 9 inches diameter bears N 17° 00' E, 22 links distance, marked 1/4 S35 BT.

An Aspen 7 inches diameter bears S 9° 30' W, 37 links distance, marked 1/4 S2 BT.

**40.558**

The 1/4 Section Corner of Sections 2 and 35, monumented with a Limestone 18 x 12 x 7 inches, projecting 8 inches above ground, marked 1/4 on North face.

At the corner point;

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 20 inches in the ground, with aluminum cap marked:

T14N R3E
S 35
1/4 —————
S 2
T13N
2005

No original bearing trees were found.

Deposit the marked stone alongside the aluminum post. Raise a mound of stone, 3 feet base, 2 feet high, encircling corner to top of cap.

Corner Point Identity: **E540N100**

Latitude: **41° 54' 20.734"**

Longitude: **111° 34' 38.380"**

Elevation: **6,936.21 ft.**

From the 1/4 Section Corner for Sections 2 and 35, heretofore described.

Corner Point Identity: **E540N100**

**N 89° 59.0' W**, Beginning new measurement between Sections 2 and 35, along South boundary of Township.

**DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

**ITALICIZED SCRIPT USED FOR RECORD HISTORY**

**Record:** (For the Original Survey of J. H. Martineau  
commenced on August 2, 1881)  
**Note:** (This information is found in the General Land  
Office Book 174, on page 165)

At corner point for the Sections 2, 3, 34, and 35, on South  
Boundary Township.

Set a Sandstone 14 x 10 x 10 inches, 10 inches in the ground  
with mound of stones marked 2 notches on East and 4 notches on  
West edges, for corner to Sections 2, 3, 34, and 35 on South  
slope of ridge 200 feet high.

**Record:** (For the Dependent Resurvey of F. E. Joy commenced  
on October 24, 1904)  
**Note:** (This information is found in the General Land  
Office Book 329, on page 130)

At corner point for the Sections 2, 3, 34, and 35, on South  
Boundary Township.

Find no trace of the corner set in 1881 by J. H. Martineau  
after conducting a retracement of boundaries East and West.  
Set U.S. Forest Reserve Boundary Post Number 73.

Which is an iron post 4 feet long, 4 inches diameter, 3 feet  
in the ground for corner of Sections 2, 3, 34, and 35, with  
brass cap marked with;

( US FOREST RESERVE )  
( T14N R3E )  
N/W Quadrant with: ( S 34 )  
N/E Quadrant with; ( S 35 )  
S/W Quadrant with; ( S 03 )  
S/E Quadrant with; ( S 02 )  
( T13N )  
( No. 73 )

From which the following Bearing Trees where marked:

An Aspen 9 ins. diameter, bears S 21° 20' E, 83 links  
distance, marked T13NR3E S6 BT.

An Aspen 7 ins, diameter, bears S 20° 50' W, 72 links  
distance, marked T13NR3E S1 BT.

**40.327**

The corner of Sections 2, 3, 34, and 35, monumented with an  
Iron Post 3 inches diameter, firmly set, projecting 22 inches  
above ground, as described in the official record of the 1904  
Dependent Resurvey, with brass cap marked:

**DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

CHAINS

U S FOREST RESERVE  
T14N  
R3E S 34 | S 35 R4E  
S 3 | S 2  
T13N  
No. 73

No original bearing trees were found.

Corner Point Identity: **E500N100**  
Latitude: **41° 54' 20.742"**  
Longitude: **111° 35' 13.568"**  
Elevation: **7,058.69 ft.**

From this Section Corner, the Township Corner of Townships 13 and 14 North, and Ranges 02 and 03 East, has a **MEAN** bearing direction of **N 89° 58' 23" W**, and a chain measurement of **320.213**, monumented with an Iron Post 3 inches diameter, firmly set, projecting 22 inches above ground, with brass cap marked as described in the official record of the 1904 Dependent Resurvey.

Corner Point Identity: **E100N100**  
Latitude: **41° 54' 20.839"**  
Longitude: **111° 39' 52.977"**  
Elevation: **9,000.00**

---

**DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

---

Restoring the Surveys Executed By J. H. Martineau in  
1881, and F. E. Joy in 1904.

---

From the heretofore described Township Corner for Townships 13 and 14 North, and Ranges 03 and 04 East.

Corner Point Identity: **E700N100**

**N 00° 57.2' E**, Beginning new measurement between Sections 31 and 36, along East Boundary of Township.

---

***ITALICIZED SCRIPT USED FOR RECORD HISTORY***

**Record:** *(For the Original Survey of J. H. Martineau  
commenced on June 24, 1881)*

**Note:** *(This information is found in the General Land  
Office Book 174, on page 146)*

**DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

At corner point for 1/4 Section Corner of Sections 31 and 36. Set a Limestone 30 x 20 x 12 inches, with a mound of stone marked 1/4 on West side for 1/4 Section Corner on West slope of mountains.

**Record:** (For the Dependent Resurvey of F. E. Joy commenced on October 24, 1904)

**Note:** (This information is found in the General Land Office Book 329, on page 131)

At corner point for 1/4 Section Corner of Sections 31 and 36. Find no trace of the corner set in 1881 by J. H. Martineau after conducting a Retracement of boundaries North-South. Set a Granit Stone 15 x 10 x 6 inches, 10 inches in the ground for 1/4 Section Corner marked 1/4 on West face, from which the following trees where marked:

A Maple 4 inches diameter bears N 27° 45' E, 20 links distance, marked 1/4 S31 BT.

An Aspen 8 inches diameter bears S 36° 30' W, 144 links distance, marked 1/4 S36 BT.

**39.327**

The 1/4 Section Corner of Sections 31 and 36, monumented with a Sandstone 14 x 10 x 6 inches, plainly marked 1/4, firmly set, projecting 7 inches above ground, and encircled with a collar of stone.

At the corner point;

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground with aluminum cap marked:

T14N  
R3E R4E  
1/4  
S 36 | S 31  
2005

No original bearing trees were found.

Deposit the marked stone alongside the aluminum post.

Corner Point Identity: **E700N135**

Latitude: **41° 54' 47.269"**

Longitude: **111° 32' 49.482"**

Elevation: **7148.48 ft.**

**DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

From the 1/4 Section Corner for Sections 31 and 36, heretofore described.

Corner Point Identity: **E700N135**

**N 00° 57.8' E**, Beginning new measurement between Sections 31 and 36, along East Boundary of Township.

---

**ITALICIZED SCRIPT USED FOR RECORD HISTORY**

**Record:** (*For the Original Survey of J. H. Martineau commenced on August 2, 1881*)

**Note:** (*This information is found in the General Land Office Book 174, on page 147*)

*At corner point for the Section Corner of Sections 25, 30, 31, and 36.*

*Set Limestone 24 x 15 x 10 inches, with mound of stone, marked 1 notch on South, 5 Notches on North for corner to Sections 25, 30, 31, and 36, on mountain slopes South.*

**Record:** (*For the Dependent Resurvey of F. E. Joy commenced on October 24, 1904*)

**Note:** (*This information is found in the General Land Office Book 329, on page 131*)

*At corner point for the Section Corner of Sections 25, 30, 31, and 36. Found Limestone 10 x 6 x 6 inches above ground marked and witnessed as described by the General Land Office.*

**39.373**

The Corner of Sections 25, 30, 31, and 36, monumented with an Iron Post, 2 1/2 inches diameter, firmly set, projecting 5 inches above ground, with brass cap marked as described in the official record of the 1982-83 Dependent Resurvey.

T14N	
R3E R4E	
S 25	S 30
S 36	S 31
1982	

Corner is encircled with a collar of stone, and is located on South-West slope.

Corner Point Identity: **E700N180**

Latitude: **41° 55' 12.931"**

Longitude: **111° 32' 48.904"**

Elevation: **7,099.49 ft.**

---

**DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

From the Section Corner for Sections 25, 30, 31, and 36, heretofore described.


Corner Point Identity: **E700N180**

**N 00° 35.5' W**, Beginning new measurement between Sections 25 and 30, along East Boundary of Township.

**04.482**

Point of Intersection on the East Boundary of Township, which identifies the Closing Corner for the East-West Lot Line extending from the North-East Corner of Section 35.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 29 inches in the ground with aluminum cap marked:



Raise a mound of stone, 3 feet base, 2 feet high, 2 feet East of corner.

Corner Point Identity: **E700N200**

Latitude: **41° 55' 15.852"**

Longitude: **111° 32' 48.945"**

Elevation: **7,153.93 ft.**

From the Point of Intersection along the East Boundary of Township, heretofore described.

Corner Point Identity: **E700N200**

**N 00° 35.5' W**, Continuing between Sections 25 and 30, along East boundary of Township.

***ITALICIZED SCRIPT USED FOR RECORD HISTORY***

**Record:** *(For the Original Survey of J. H. Martineau commenced on August 2, 1881)*

**Note:** *(This information is found in the General Land Office Book 174, on page 147)*

*At corner point for the 1/4 Section Corner for Sections 25 and 30, on East Boundary of Township.*

*Set a Limestone 15 x 8 x 6 inches, with a mound of stones, marked 1/4 on West side for 1/4 Section Corner on North Slope of mountain.*

**DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS****44.852**

Point for the 1/4 corner of Sections 25 and 30. There is no remaining evidence of the original corner. This corner will now function for Section 25 only.

Point for the intersection on the East Boundary of Township, which identifies the Closing Corner for the East-West Center Line of Section 25.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 29 inches in the ground with aluminum cap marked:

T14N	
R 3 E	R 4 E
E 1/4 C	S 30
S 25 C	S 30
2005	

Raise a mound of stone, 3 feet base, 2 feet high, 3 links east of the corner.

Corner Point Identity: **E700N240**

Latitude: **41° 55' 42.162"**

Longitude: **111° 32' 49.304"**

Elevation: **7,054.03 ft.**

From the Point of Intersection along the East Boundary of Township, heretofore described.

Corner Point Identity: **E700N240**

**N 00° 35.5' W**, Continuing between Sections 25 and 30, along East boundary of Township.

**ITALICIZED SCRIPT USED FOR RECORD HISTORY**

**Record:** (*For the Original Survey of J. H. Martineau commenced on August 2, 1881*)

**Note:** (*This information is found in the General Land Office Book 174, on page 148*)

At corner point for the Section Corner of Sections 19, 24, 25, and 30. Set a Limestone 36 x 10 x 8 inches with a mound of stone marked 2 notches on South and 4 notches on North for corner to Sections 19, 24, 25, and 30, near top of mountain that bears East and West.

**DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS  
84.820**

The Corner of Sections 19, 24, 25, and 30, monumented with an Iron Post, 2 1/2 inches diameter, firmly set, projecting 5 inches above ground, as described in the official record of the 1982 Dependent Resurvey, with brass cap marked:

T14N	
R3E	R4E
S 24	S 19
S 25	S 30
1982	

Corner is encircled with a collar of stone, and is located on South-West slope.

Corner Point Identity: **E700N300**  
 Latitude: **41° 56' 08.216"**  
 Longitude: **111° 32' 49.679"**  
 Elevation: **7,476.80 ft.**

**INDEPENDENT RESURVEY AND DEPENDENT RESURVEY OF THE  
SUBDIVISIONAL LINES FOR SECTIONS 25, 26, AND 36,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

Restoring the Surveys Executed By J. H. Martineau in 1881.

From the Section Corner for Sections 1, 2, 35, and 36, on the South Boundary of Township, heretofore described.

Corner Point Identity: **E600N100**

**N 00° 31.7' W**, Beginning new measurement between Sections 35 and 36.

**40.052**

The Point for the West 1/4 Section Corner of Section 36 only, is at midpoint on West Boundary of Section 36.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground aluminum cap marked:

T14N	R3E
	1/4
	S 36
2005	

Raise a mound of stone, 3 feet base, 2 feet high, encircling corner to top of cap.

Corner Point Identity: **E600N135**  
 Latitude: **41° 54' 46.826"**  
 Longitude: **111° 34' 03.308"**  
 Elevation: **6,603.85 ft.**

**INDEPENDENT RESURVEY AND DEPENDENT RESURVEY OF THE  
SUBDIVISIONAL LINES FOR SECTIONS 25, 26, AND 36,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

From the West 1/4 Section Corner for Sections 36 only, heretofore described.

Corner Point Identity: **E600N135**

**N 00° 31.7' W**, Continuing between Sections 35 and 36.

---

**ITALICIZED SCRIPT USED FOR RECORD HISTORY**

**Record:**       *(For the Original Survey of J. H. Martineau commenced on August 10, 1881)*

**Note:**         *(This information is found in the General Land Office Book 174, on page 190)*

*At corner point for the 1/4 Section Corner of Sections 35 and 36. Set Sandstone 18 x 10 x 5 inches 12 inches in the ground, with mound of stone marked 1/4 on West side for 1/4 Section Corner on ridge slopes East.*

**44.734**

The East 1/4 Section Corner of Sections 35 only, monumented with a Sandstone 20 x 8 x 4 inches, plainly marked 1/4, firmly set, projecting 10 inches above ground, and encircled with a collar of stone. This corner was also perpetuated by Jeff S. Hansen, Registered Land Surveyor, Utah R.L.S. No. 325023, representing JSH Surveying & Drafting Inc. of Nibley, Utah. The corner was monumented with a 5/8 rebar with aluminum cap marked: T14N R3E 1/4 S 35 | S 36.

At the corner point;

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 18 inches in the ground with aluminum cap marked:

T14N	R3E
1/4	
S 35	
	2005

Deposit the marked stone alongside of post and set rebar with cap inside post.

Corner is encircled with a collar of stone, and is located on East slope.

Corner Point Identity: **E600N140**

Latitude: **41° 54' 49.876"**

Longitude: **111° 34' 03.345"**

Elevation: **6,662.64 ft.**

---

**INDEPENDENT RESURVEY AND DEPENDENT RESURVEY OF THE  
SUBDIVISIONAL LINES FOR SECTION 25, 26, AND 36,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

From the East 1/4 Section Corner for Sections 35 only,  
heretofore described.

Corner Point Identity: **E600N140**

**N 00° 14.1' W**, Beginning new measurement between Sections 35  
and 36.

**15.343**

Point for the North 1/16 Section Corner of Section 36 only.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long,  
24 inches in the ground with aluminum cap marked:

T14N	R3E
	N 1/16
	S 36
2005	

Corner is encircled with a collar of stone.

Corner Point Identity: **E600N155**

Latitude: **41° 54' 59.878"**

Longitude: **111° 34' 03.401"**

Elevation: **6,603.89 ft.**

---

From the North 1/16 Section Corner on the West Boundary of  
Section 36 only, heretofore described.

Corner Point Identity: **E600N155**

**N 00° 14.1' W**, Continuing between Sections 35 and 36.

**19.924**

Point for the North 1/16 Section Corner, on the East Boundary  
of Section 35 only.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long,  
24 inches in the ground with aluminum cap marked:

T14N	R3E
N 1/16	
S 35	
2005	

Corner is encircled with a collar of stone.

Corner Point Identity: **E600N160**

Latitude: **41° 55' 02.864"**

Longitude: **111° 34' 03.418"**

Elevation: **6,603.90 ft.**

---

**INDEPENDENT RESURVEY AND DEPENDENT RESURVEY OF THE  
SUBDIVISIONAL LINES FOR SECTION 25, 26, AND 36,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

From the North 1/16 Section Corner on the East Boundary of Section 35 only, heretofore described.

Corner Point Identity: **E600N160**

**N 00° 14.1' W**, Continuing between Sections 35 and 36.

**25.356**

Point for the North-North 1/64 Section Corner, on the West Boundary of Section 36 only.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground with aluminum cap marked:

T14N	R3E
	N N 1/64
	S 36
2005	

Corner is encircled with a collar of stone.

Corner Point Identity: **E600N175**

Latitude: **41° 55' 06.405"**

Longitude: **111° 34' 03.438"**

Elevation: **6,603.92 ft.**

From the North-North 1/64 Section Corner, on the West Boundary of Sections 36 only, heretofore described.

Corner Point Identity: **E600N175**

**N 00° 14.1' W**, Continuing between 35 and 36.

**35.369**

Point of Intersection on the East Boundary of Section 35, which identifies the Closing Corner for the East-West Section Line between Section 25, 36, and Tract 37. This Boundary Line was extended from the Section Corner for Sections 25, 30, 31, and 36 on the East Boundary of Township.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground with aluminum cap marked:

T14N	R3E
	C S 25
	C S 36
2005	

Raise a mound of stone, 3 feet base, 2 feet high, encircling corner to top of cap.

Corner Point Identity: **E600N180**

Latitude: **41° 55' 12.931"**

Longitude: **111° 34' 03.474"**

Elevation: **6,598.94 ft.**

**INDEPENDENT RESURVEY AND DEPENDENT RESURVEY OF THE  
SUBDIVISIONAL LINES FOR SECTION 25, 26, AND 36,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

From the Closing Corner for Sections 25 and 36, and Tract 37, on the East Boundary of Section 35 only, heretofore described. Corner Point Identity: **E600N180**

**N 00° 14.1' W**, Continuing between Section 35 and Tract 37.

---

**ITALICIZED SCRIPT USED FOR RECORD HISTORY**

**Record:**      *(For the Original Survey of J. H. Martineau commenced on August 2, 1881)*

**Note:**        *(This information is found in the General Land Office Book 174, on page 190)*

*At corner point for the Section Corner of Sections 25, 26, 35, and 36. Set Sandstone 24 x 18 x 4 inches, 18 inches in the ground with mound of stones, marked 1 notch on South and 1 notch on East edges for corner and on a rocky point slopes East.*

**39.850**

The North-East Corner of Section 35 only, monumented with a Sandstone 22 x 17 x 5 inches, dimly marked with one notch on South side, projecting 10 inches out of a mound of stone. This corner was also perpetuated by Jeff S. Hansen, Registered Land Surveyor, Utah R.L.S. No. 325023, representing JSH Surveying & Drafting Inc. Nibley Utah. The corner was monumented with a 5/8 rebar with aluminum cap marked: T14N R3E S25 S26 S35 S36.

At the Corner Point;

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground with aluminum cap marked:

T14N	R3E	
S 25	T37	
S 35	2005	

Deposit marked stone alongside of post and set rebar with cap inside post.

Raised a mound of stone 3 feet base to top of cap.

Corner Point Identity: **E600N200**  
Latitude:    **41° 55' 15.852"**  
Longitude: **111° 34' 03.491"**  
Elevation: **6667.25 ft.**

---



**INDEPENDENT RESURVEY AND DEPENDENT RESURVEY OF THE  
SUBDIVISIONAL LINE BETWEEN SECTIONS 25, 26, AND 36,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

Corner is encircled with a collar of stone, and is located at base of East slope.

Corner Point Identity: **E600N240**  
Latitude: **41° 55' 42.162"**  
Longitude: **111° 34' 03.452"**  
Elevation: **6,592.71 ft.**

From the 1/4 Section Corner for Sections 25 and 26, heretofore described.

Corner Point Identity: **E600N240**

**N 00° 03.6' E**, Beginning new measurement between Sections 25 and 26.

***ITALICIZED SCRIPT USED FOR RECORD HISTORY***

**Record:** *(For the Original Survey of J. H. Martineau commenced on August 2, 1881)*

**Note:** *(This information is found in the General Land Office Book 174, on page 193 )*

*At corner point for the Section Corner of Sections 23, 24, 25, and 26.*

*Set Limestone 16 x 14 x 12 inches, 11 inches in the ground with mound of stones marked 2 notches on South and 1 notch on East edges and on small island in river.*

**39.966**

Point of Intersection for the Corner of Sections 23, 24, 25, and 26. There is no remaining evidence of the original corner. The Latitudinal Point of Intersection was determined by projecting the **East-West** bearing from the Section Corner for Sections 19, 24, 25, and 30, which is located on East Boundary of Township.

The Longitudinal Point of Intersection was projected on a bearing of **N 00° 03.6' E**, from the North-East Section Corner for Section 35 only, and having the bearing projected through the 1/4 Section Corner of Sections 25 and 26.

The above Survey Procedure was used for Latitudinal and Longitudinal position due to unresolved and insufficient recovery of controlling monumentation. During the Investigation Retracement a thorough search was conducted at ( 18 ) "Controlling Corner Positions" and other calls of official record. Attachment Number {10}; "Search Areas for Controlling Corner Positions" is provided after attachments for "Documentary of Historical Evidence", which have been included at the end of these Field Notes.

**INDEPENDENT RESURVEY AND DEPENDENT RESURVEY OF THE  
SUBDIVISIONAL LINE BETWEEN SECTIONS 25, 26, AND 36,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

At the Point of Intersection;

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 26 inches in the ground with aluminum cap marked:

T14N	R3E
S 23	S 24
S 26	S 25
2005	

Raise a mound of stone 3 Feet base, 2 Feet high, West of Corner.

Corner Point Identity: **E600N300**  
 Latitude: **41° 56' 08.216"**  
 Longitude: **111° 34' 03.414"**  
 Elevation: **6,654.14 ft.**

---

From this Corner Point, the 1/4 Section Corner for Sections 9, and 10, has a forward bearing direction of **N. 38° 04' 40" W.**, and a backward bearing direction of **S. 38° 06' 10" E.**, with a chain distance of **253.891**, monumented with an Iron Post, 2 1/2 inches diameter, firmly set, projecting 14 inches above ground and encircled by a mound of stone 3 1/2 feet base to top of brass cap marked as described in the official record of the 1968 Re-Monumentation of Corners under Group 447.

Corner Point Identity: **E400N540**  
 Latitude: **41° 58' 18.466"**  
 Longitude: **111° 36' 20.187"**  
 Elevation: **7,694.00 ft.**

---

**INDEPENDENT RESURVEY AND DEPENDENT RESURVEY OF THE  
SECTIONS 25, 36, AND TRACT 37,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

From the Section Corner for Sections 25, 30, 31, and 36, On the East Boundary of Township, heretofore described.

Corner Point Identity: **E700N180**

**WEST**, Beginning new measurement on cardinal bearing, along occupation line between Sections 25 and 36,

---

***ITALICIZED SCRIPT USED FOR RECORD HISTORY***

**INDEPENDENT RESURVEY AND DEPENDENT RESURVEY OF THE  
SECTIONS 25, 36, AND TRACT 37,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

**Record:** (For the Original Survey of J. H. Martineau  
commenced on August 2, 1881)

**Note:** (This information is found in the General Land  
Office Book 174, on page 191)

At corner point for the 1/4 Section Corner of Sections 25 and 36. Set Sandstone 15 x 12 x 8 inches, 10 inches in the ground with mound of stones, marked 1/4 on North side for 1/4 Section Corner on smooth hill course North and South.

**42.720**

Point for the 1/4 Section Corner of Sections 25, 36, and the South-East Corner of Tract 37, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground, with aluminum cap marked:

T14N	R3E
TR 37	S 25
1/4	S 36
2005	

Raise a mound of stone, 3 feet base, 2 feet high, encircling corner to top of cap.

Corner Point Identity: **E640N180**  
Latitude: **41° 55' 12.931"**  
Longitude: **111° 33' 26.189"**  
Elevation: **6,653.95 ft.**

From the 1/4 Section Corner for Sections 25, and 36, heretofore described.

Corner Point Identity: **E640N180**

**WEST**, Continuing between Section 36 and Tract 37.

**64.080**

Point for the West 1/16 Section Corner, on the North Boundary of Section 36 only.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground, with aluminum cap marked:

T14N	R3E
TR 37	
W 1/16	
S 36	
2005	

**INDEPENDENT RESURVEY OF THE BOUNDARY BETWEEN  
SECTIONS 25, 36, AND TRACT 37,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

Raise a mound of stone, 3 feet base, 2 feet high, encircling corner to top of cap.

Corner Point Identity: **E620N180**  
Latitude: **41° 55' 12.931"**  
Longitude: **111° 33' 44.832"**  
Elevation: **6,503.95 ft.**

---

From the West 1/16 Section Corner, on the North Boundary of Sections 36 only, heretofore described.

Corner Point Identity: **E640N180**

**WEST**, Continuing between Section 36 and Tract 37.

**69.420**

Point for the East-West-West 1/256 Section Corner, on the North Boundary of Section 36 only.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground, with aluminum cap marked:

T14N R3E  
TR 37  
E-W-W 1/256  
S 36  
2005

Raise a mound of stone, 3 feet base, 2 feet high, encircling corner to top of cap.

Corner Point Identity: **E615N180**  
Latitude: **41° 55' 12.931"**  
Longitude: **111° 33' 49.492"**  
Elevation: **6,503.95 ft.**

---

From the East-West-West 1/256 Section Corner, on the North Boundary of Section 36 only, heretofore described.

Corner Point Identity: **E615N180**

**West**, Continuing between Section 36 and Tract 37.

**74.760**

Point for the West-West 1/64 Section Corner, on the North Boundary of Section 36 only.

**NOT MONUMENTED**

Corner Point Identity: **E610N180**  
Latitude: **41° 55' 12.931"**  
Longitude: **111° 33' 54.153"**  
Elevation: **6,503.95 ft.**

---

**INDEPENDENT RESURVEY OF THE BOUNDARY BETWEEN  
SECTIONS 25, 36, AND TRACT 37,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

From the West-West 1/64 Section Corner, on the North Boundary of Section 36 only, heretofore described.

Corner Point Identity: **E610N180**

**WEST**, Continuing between Section 36 and Tract 37.

**85.440**

Point of Intersection on the East Boundary of Section 35, which identifies the Closing Corner for the East-West Line extended along the North Boundary of Section 36, and the South Boundary of Tract 37, heretofore described.

Corner Point Identity: **E600N180**

From the North-East Section Corner of Section 35 only, heretofore described.


Corner Point Identity: **E600N200**

**EAST**, Beginning a tie measurement along the abandoned Rectangular Line, through Tract 37.

**42.712**

Point for the Witness Point on the East Boundary of Tract 37, which also identifies the Point of Intersection with the North-South Center Line and the West Terminus for the East-West Lot Line within the South-East 1/4 of Section 25.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground with aluminum cap marked and encircled with a collar of stone.



Point is located on South slope.

Corner Point Identity: **E640N200**

Latitude: **41° 55' 15.852"**

Longitude: **111° 33' 26.208"**

Elevation: **6,653.96 ft.**

From the Witness Point on the East Boundary of Tract 37, and the North-South Center Line of Section 25, heretofore described.

Corner Point Identity: **E640N200**

**INDEPENDENT RESURVEY OF THE BOUNDARY BETWEEN  
SECTIONS 25, 36, AND TRACT 37,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

**EAST**, Beginning new measurement along the East-West Lot Line within the South-East 1/4 of Section 25.

**42.700**

Point for the Closing Corner on the East Boundary of Township, which also identifies the Point of Intersection with the East Terminus of the East-West Lot Line extending from the North-East Corner of Section 35, heretofore described.

Corner Point Identity: **E700N200**

---

**DEPENDENT RESURVEY OF THE BOUNDARY BETWEEN SECTIONS 26 AND 35,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

---

From the North-East Section Corner of Section 35, heretofore described.

Corner Point Identity: **E600N200**

**S 89° 55.9' W**, Beginning new measurement between Sections 26 and 35.

**01.526**

Point for the Closing Corner on the North Boundary of Section 35, and Point of Intersection for the East Boundary of Section 26, and the West Boundary of Tract 37.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground with aluminum cap marked:

T14N	R3E
CC	
S 26	TR 37
S 35	
2005	

Raise a mound of stone, 3 feet base, 2 feet high, encircling corner to top of cap.

Corner Point Identity: **E580N200**

Latitude: **41° 55' 15.851"**

Longitude: **111° 34' 04.823"**

Elevation: **6,603.95 ft.**

---

From the Closing Corner for Section 26, and Tract 37, heretofore described.

Corner Point Identity: **E580N200**

**S 89° 55.9' W**, Continuing between Sections 26 and 35.

---

**DEPENDENT RESURVEY OF THE BOUNDARY BETWEEN SECTIONS 26 AND 35,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

**ITALICIZED SCRIPT USED FOR RECORD HISTORY**

**Record:** (For the Original Survey of J. H. Martineau  
commenced on August 2, 1881)  
**Note:** (This information is found in the General Land  
Office Book 174, on page 203)

At corner point for the 1/4 Section Corner to Sections 26, and 35. Set a Sandstone 18 x 14 x 8 inches, 12 inches in the ground with mound of stones marked 1/4 on North side for 1/4 Section Corner on East slope.

**40.167**

The 1/4 Section Corner of Sections 26 and 35, monumented with a Sandstone 16 x 12 x 7 inches, plainly marked 1/4, projecting 4 inches above mound of stone and encircled with a mound of stone. This corner was also perpetuated by Jeff S. Hansen, Registered Land Surveyor, Utah R.L.S. No. 325023, representing JSH Surveying & Drafting Inc. of Nibley, Utah. The corner was monumented with a 5/8 rebar with aluminum cap marked: T14N R3E 1/4 S26 S35.

At the corner point;

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground with aluminum cap marked:

T14N R3E  
S 26  
1/4 —————  
S 35  
2005

Deposit the marked stone alongside of post and set rebar with cap inside post.

Corner is encircled with a collar of stone, and is located at base of East slope.

Corner Point Identity: **E540N200**  
Latitude: **41° 55' 15.820"**  
Longitude: **111° 34' 38.549"**  
Elevation: **6,889.02 ft.**

**INDEPENDENT RESURVEY OF THE BOUNDARY BETWEEN  
SECTIONS 24 AND 25 TOWNSHIP, 14 NORTH, RANGE 03 EAST,  
SALT LAKE MERIDIAN, UTAH**

From the Section Corner for Sections 19, 24, 25, and 30, on the East Boundary of Township, heretofore described.

**INDEPENDENT RESURVEY OF THE BOUNDARY BETWEEN  
SECTIONS 24 AND 25, TOWNSHIP 14 NORTH, RANGE 03 EAST,  
SALT LAKE MERIDIAN, UTAH**

**CHAINS**

Corner Point Identity: **E700N300**

**WEST**, Beginning new measurement on cardinal bearing, between Sections 24 and 25.

---

**ITALICIZED SCRIPT USED FOR RECORD HISTORY**

**Record:** (*For the Original Survey of J. H. Martineau commenced on August 2, 1881*)

**Note:** (*This information is found in the General Land Office Book 174, on page 194*)

At corner point for the 1/4 Section Corner of Sections 24 and 25.

*Set a Limestone 14 x 12 x 4 inches, 10 inches in the ground with mound of stones marked 1/4 on North side for 1/4 Section Corner on steep Mountain that slopes North and West.*

**42.234**

Point for the 1/4 Section Corner of Sections 24 and 25, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground, with aluminum cap marked:

T14N R3E  
S 24  
1/4 —————  
S 25  
2005

Raise a mound of stone, 3 feet base, 2 feet high, encircling corner to top of cap.

Corner falls 30 feet west of river.

Corner Point Identity: **E640N300**

Latitude: **41° 56' 08.216"**

Longitude: **111° 33' 26.546"**

Elevation: **6,794.14 ft.**

---

From the 1/4 Section Corner for Sections 24 and 25, heretofore described.

Corner Point Identity: **E640N300**

**WEST**, Continuing between Sections 24 and 25.

**84.468**

The Section Corner for Sections 23, 24, 25, and 26, heretofore described.

**INDEPENDENT RESURVEY OF THE BOUNDARY BETWEEN  
SECTIONS 24 AND 25, TOWNSHIP 14 NORTH, RANGE 03 EAST,  
SALT LAKE MERIDIAN, UTAH**

**CHAINS**

Corner Point Identity: **E600N300**

**INDEPENDENT RESURVEY AND DEPENDENT RESURVEY OF THE  
BOUNDARY BETWEEN SECTION 26 AND TRACT 37,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

From the 1/4 Section Corner of Sections 25 and 26, heretofore described.

Corner Point Identity: **E600N240**

**WEST**, Beginning new measurement along the East-West Center Line of Section 26 and the North boundary of Tract 37.

**01.526**

Point selected for the Angle Point that determines the North-West Corner for Tract 37.

The location for the Latitudinal position was determined by projecting the Boundary True West on a cardinal direction from the 1/4 Section Corner of Sections 25 and 26.

The location for the Longitudinal position was determined from the "Iron Rod", a Witness Point on the West boundary of Tract 37, which was identified by local residents of the area and is harmoniously related to their identified property corners. Longitudinal position was projected on a bearing of **N 00° 03.6'E, PARALLEL** to the bearing projected from the North-East Section Corner for Section 35, through the 1/4 Section Corner of Sections 25 and 26.

At the Angle Point;

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 18 inches in the ground with aluminum cap marked:

T14N    R3E  
          AP 1  
S 26 | TR 37  
      2005

Corner is encircled with a mound of stone 4 feet base to top of cap, and is located on South slope.

Corner Point Identity: **E580N240**

Latitude: **41° 55' 42.162"**

Longitude: **111° 34' 04.785"**

Elevation: **6,574.05 ft.**

**INDEPENDENT RESURVEY AND DEPENDENT RESURVEY OF THE  
BOUNDARY BETWEEN SECTIONS 26 AND TRACT 37,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

From the Angle Point for Tract 37, heretofore described.

Corner Point Identity: **E580N240**

**S 00° 03.6' W**, Beginning new measurement along the East Boundary of Section 26, and the West Boundary for Tract 37.

**00.226**

Point for a Witness Point on the West Boundary of Tract 37, which is the location of the **"IRON ROD"** established by a previous Cache County Surveyor according to affidavits by local residents of the area and is harmoniously related to their identified property corners.

Set an Iron Post, 2 1/2 inches diameter, 30 inches long, 26 inches in the ground, over the top of **"IRON ROD"**, with aluminum cap marked:

W P  
IRON ROD  
T14N R3E  
S 26 | TR 37  
2006

Point is located at the Corner of a fence line extending East.

Corner Point Identity: **E580N235**

Latitude: **41° 55' 42.018"**

Longitude: **111° 34' 04.785"**

Elevation: **6,605.81 ft.**

From the Witness Point which identifies the location of the Iron Rod, on the West Boundary of Tract 37, heretofore described.

Corner Point Identity: **E580N235**

**S 00° 03.6' W**, Continuing along the East Boundary of 26, and the West Boundary of Tract 37.

**40.370**

Intersection of the East-West Boundary between Sections 26 and 35, which identifies the Closing Corner for the East Boundary of Section 26 and the West Boundary of Tract 37, heretofore described.

Corner Point Identity: **E580N200**

**SURVEY OF THE SUBDIVISION LINES FOR SECTION 25,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

From the 1/4 Section Corner for Sections 25 and 36, heretofore described.

Corner Point Identity: **E640N180**

**N 00° 16.4' W**, Beginning new measurement continuing along the North-South Center Line for Section 25 and the East boundary of Tract 37.

**04.481**

Point for a Witness Point on the East Boundary of Tract 37, and the West Boundary of the South-East 1/4 of Section 25, heretofore described.

Corner Point Identity: **E640N200**

---

From the Witness Point on the East Boundary of Tract 37, and the West Boundary for South-East 1/4 of Section 25, heretofore described.

Corner Point Identity: **E640N200**

**N 00° 16.4' W**, Continuing along the North-South Center Line for Section 25 and the East boundary of Tract 37.

**44.848**

Point for the Center 1/4 Section Corner of Section 25, at the intersection with the East-West Center Line, which is also the North-East corner of Tract 37.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 18 inches in the ground with aluminum cap marked:

T14N R3E  
C 1/4  
S 25  
2005

Raise a mound of stone, 3 feet base, 2 feet high, encircling corner to top of cap.

Corner Point Identity: **E640N240**

Latitude: **41° 55' 42.162"**

Longitude: **111° 33' 26.378"**

Elevation: **6,754.05 ft.**

---

From the Center 1/4 for Section 25, heretofore described.

Corner Point Identity: **E640N240**

**N 00° 16.4' W**, Continuing along the North-South Center Line for Section 25.

**84.816**

The 1/4 Section Corner for Sections 24 and 25, heretofore described.

Corner Point Identity: **E640N300**

---

**EAST-WEST CENTER LINE FOR THE SUBDIVISION OF SECTION 25,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

From the 1/4 Section Corner for Sections 25 and 26 on the North boundary of Tract 37, heretofore described.

Corner Point Identity: **E600N240**

**EAST**, Beginning new measurement along the East-West Center Line for Section 25 and the North boundary of Tract 37.

**42.474**

Point for the Center 1/4 Section Corner of Section 25 and the North-East corner of Tract 37, at the intersection with the North-South Center Line, heretofore described.

Corner Point Identity: **E640N240**

---

From the Center 1/4 Section Corner for Section 25, heretofore described.

Corner Point Identity: **E640N240**

**EAST**, Continuing along the East-West Center Line for Section 25.

**84.943**

Point for the Closing Corner on the East-West Center Line of Section 25, at the intersection with East Boundary of Township, heretofore described.

Corner Point Identity: **E700N240**

---

**SURVEY OF THE SUBDIVISIONAL LINES FOR SECTION 36,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

---

From the South 1/4 for Sections 1 and 36, on the South Boundary of Township, heretofore described.

Corner Point Identity: **E640N100**

**N 00° 16.7' E**, Beginning new measurement along the North-South Center Line for Section 36.

**39.688**

Point for the Center 1/4 Section Corner of Section 36, at the intersection with the East-West Center Line.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground with aluminum cap marked:

**SURVEY OF THE SUBDIVISIONAL LINES FOR SECTION 36,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

T14N R3E  
C 1/4  
S 36  
2005

Raise a mound of stone, 3 feet base, 2 feet high, encircling corner to top of cap.

Corner Point Identity: **E640N135**  
Latitude: **41° 54' 47.048"**  
Longitude: **111° 33' 26.357"**  
Elevation: **6,603.85 ft.**

---

From the Center 1/4 for Section 36, heretofore described.

Corner Point Identity: **E640N135**

**N 00° 16.7' E**, Continuing along the North-South Center Line for Section 36.

**59.542**

Point for the Center North 1/16 Section Corner of Section 36.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground with aluminum cap marked:

T14N R3E  
C  
N 1/16 | S 36  
C  
2005

Raise a mound of stone, 3 feet base, 2 feet high, encircling corner to top of cap.

Corner Point Identity: **E640N155**  
Latitude: **41° 54' 59.989"**  
Longitude: **111° 33' 26.273"**  
Elevation: **6,603.89 ft.**

---

From the Center North 1/16 Section Corner for Section 36, heretofore described.

Corner Point Identity: **E640N155**

**N 00° 16.7' E**, Continuing along the North-South Center Line for Section 36.

**69.469**

Point for the Center-North-North 1/64 Section Corner of Section 36.

**SURVEY OF THE SUBDIVISIONAL LINES FOR SECTION 36,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground with aluminum cap marked:

T14N R3E  
C  
N-N | 1/64  
C  
S 36  
2005

Raise a mound of stone, 3 feet base, 2 feet high, encircling corner to top of cap.

Corner Point Identity: **E640N175**  
Latitude: **41° 55' 06.460"**  
Longitude: **111° 33' 26.231"**  
Elevation: **6,603.92 ft.**

---

From the Center-North-North 1/64 for Section 36, heretofore described.

Corner Point Identity: **E640N175**

**N 00° 16.7' E**, Continuing along the North-South Center line for Section 36.

**79.396**

The 1/4 Section Corner for Sections 25 and 36, heretofore described.

Corner Point Identity: **E640N180**

---

**EAST-WEST CENTER LINE FOR THE SUBDIVISION OF SECTION 36,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

---

From the 1/4 Section Corner for Sections 31 and 36, on East Boundary of Township, heretofore described.

Corner Point Identity: **E700N135**

**S 89° 32.2' W**, Beginning new measurement along the East-West Center line for Section 36.

**42.257**

Point for the Center 1/4 Section Corner of Section 36, at the intersection with the North-South Center Line, heretofore described.

Corner Point Identity: **E640N135**

---

**EAST-WEST CENTER LINE FOR THE SUBDIVISION OF SECTION 36,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

From the Center 1/4 Section Corner for Section 36, heretofore described.

Corner Point Identity: **E640N135**

**S 89° 32.2' W**, Continuing along the East-West Center line for Section 36.

**63.430**

Point for the Center-West 1/16 Section Corner of Section 36, at the intersection with the North-South Center Line for the West half of Section, falls in a gravel-surfaced road, 20 links wide, bearing N. 45° E. and S. 45° W.;

Drive a Rail-Road Spike flush with surface of road and marked top with X.

Corner Point Identity: **E620N135**

Latitude: **41° 54' 46.937"**

Longitude: **111° 33' 44.832"**

Elevation: **6,433.86 ft.**

From which the following two Reference Monuments were established:

Reference Monument bears **N 69° 44.8' E** direction, for **49.60** feet distance.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground with aluminum cap marked: T14N R3E S36 RM 2006 and an arrow pointing to the corner. Raise a mound of stone, 3 feet base, 2 feet high, encircling corner to top of cap.

Corner Point Identity: **E620N135-A**

Latitude: **41° 54' 47.107"**

Longitude: **111° 33' 44.216"**

Elevation: **6,441.63 ft.**

Reference Monument bears **S 29° 40.9' E** direction, for **86.60** feet distance.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground with aluminum cap marked: T14N R3E S36 RM 2006 and an arrow pointing to the corner. Raise a mound of stone, 3 feet base, 2 feet high, encircling corner to top of cap.

Corner Point Identity: **E620N135-B**

Latitude: **41° 54' 46.194"**

Longitude: **111° 33' 44.265"**

Elevation: **6,438.50 ft.**

---

**EAST-WEST CENTER LINE FOR THE SUBDIVISION OF SECTION 36,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

From the Center-West 1/16 Section Corner for Section 36, heretofore described.

Corner Point Identity: **E620N135**

**S 89° 32.3' W**, continuing along the East-West Center Line for Section 36.

**68.723**

Point for the Center-East, West-West 1/256 Section Corner of Section 36.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground with aluminum cap marked:

T14N R3E  
C E W  
W 1/256  
S 36  
2005

Raise a mound of stone, 4 feet base, 2 feet high, encircling corner to top of cap.

Corner Point Identity: **E615N135**

Latitude: **41° 54' 46.909"**

Longitude: **111° 33' 49.451"**

Elevation: **6,453.85 ft.**

From the Center-East-West-West 1/256 Corner for Section 36, heretofore described.

Corner Point Identity: **E615N135**

**S 89° 32.2' W**, continue along the East-West Center line for Section 36.

**74.016**

The Center-West-West 1/64 Section Corner for Section 36.

**NOT MONUMENTED.**

Corner Point Identity: **E610N135**

Latitude: **41° 54' 46.881"**

Longitude: **111° 33' 54.070"**

Elevation: **6,453.85 ft.**

From the Center-West-West 1/64 Section Corner for Section 36, heretofore described.

Corner Point Identity: **E610N135**

**S 89° 32.2' W**, Continuing along the East-West Center Line for Section 36.

**EAST-WEST CENTER LINE FOR THE SUBDIVISION OF SECTION 36,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**  
**84.602**

The West 1/4 Section Corner for Section 36 only.

Corner Point Identity: **E600N135**

---

**SURVEY OF THE SUBDIVISIONAL LINES FOR THE  
NORTH-WEST 1/4 OF SECTION 36,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

---

From the Center-West 1/16 Section Corner for Section 36,  
heretofore described.

Corner Point Identity: **E620N135**

**North**, Beginning new measurement along the North-South Center  
line of the North-West 1/4 for Section 36.

**19.939**

Point for the North-West 1/16 Section Corner of Section 36.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long,  
30 inches in the ground, flush with surface of Road, and on  
South side of road, with aluminum cap marked:

T14N R3E  
N W 1/16  
S 36  
2005

Corner is located West of Center Line of Road, at the distance  
of 83 Feet.

Corner Point Identity: **E620N155**

Latitude: **41° 54' 59.934"**

Longitude: **111° 33' 44.832"**

Elevation: **6,473.90 ft.**

---

From the North-West 1/16 Section Corner for Section 36,  
heretofore described.

Corner Point Identity: **E620N155**

**North**, Continuing along the North-South Center line of the  
North-West 1/4 for Section 36.

**29.909**

Point for the Center-North, North-West 1/64 Section Corner of  
Section 36.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long,  
24 inches in the ground with aluminum cap marked:

**SURVEY OF THE SUBDIVISIONAL LINES FOR THE  
NORTH-WEST 1/4 OF SECTION 36,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

T14N R3E  
C-N  
N W 1/64  
S 36  
2005

Raise a mound of stone, 4 feet base, 2 feet high, encircling corner to top of cap.

Corner Point Identity: **E620N175**  
Latitude: **41° 55' 06.433"**  
Longitude: **111° 33' 44.832"**  
Elevation: **6,503.93 ft.**

---

From the Center-North, North-West 1/64 Corner for Section 36, heretofore described.

Corner Point Identity: **E620N175**

**North**, Continuing along the North-South Center Line for the North-West 1/4, for Section 36.

**39.879**

Point for the West 1/16 Section Corner, on the North Boundary of Section 36, and the South Boundary of Tract 37, heretofore described.

Corner Point Identity: **E620N180**

---

From the Center-North 1/16 Section Corner for Section 36, heretofore described.

Corner Point Identity: **E640N155**

**S 89° 46.2' W**, Beginning new measurement along the East-West Center Line of the North-West 1/4 for Section 36.

**21.266**

Point for the North-West 1/16 Section Corner of Section 36, heretofore described.

Corner Point Identity: **E620N155**

---

From the North-West 1/16 Section Corner for Section 36, heretofore described.

Corner Point Identity: **E620N155**

**S 89° 46.2' W**, Continuing along the East-West Center Line of the North-West 1/4 for Section 36.

**EAST-WEST CENTER LINE OF THE NORTH-WEST 1/4 OF SECTION 36,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS  
26.585**

Point for the Center-East-West, North-West 1/256 Section  
Corner of Section 36.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long,  
24 inches in the ground with aluminum cap marked:

T14N R3E  
C E W  
N W 1/256  
S 36  
2005

Raise a mound of stone, 3 feet base, 2 feet high, encircling  
corner to top of cap.

Corner is located on East slope and about 2 chains West of  
River.

Corner Point Identity: **E615N155**  
Latitude: **41° 54' 59.920"**  
Longitude: **111° 33' 49.472"**  
Elevation: **6,503.90 ft.**

---

From the Center-East-West, North-West 1/256 Section Corner,  
heretofore described.

Corner Point Identity: **E615N155**

**S 89° 46.2' W**, Continuing along the East-West Center Line for  
the North West 1/4 of Section 36.

**31.904**

Point for the Center-West, North-West 1/64 Section Corner for  
Section 36.

**NOT MONUMENTED.**

Corner Point Identity: **E610N155**  
Latitude: **41° 54' 59.906"**  
Longitude: **111° 33' 54.116"**  
Elevation: **6,473.902 ft.**

---

From the Center-West, North-West 1/64 Section Corner,  
heretofore described.

Corner Point Identity: **E610N155**

**S 89° 46.2' W** Continuing along the East-West Center Line for  
the North-West 1/4 of Section 36.

**42.542**

The North 1/16 Section Corner of Section 36 only.  
Corner Point Identity: **E600N155**

---

**NORTH-EAST 1/4 OF THE NORTH-WEST 1/4 OF SECTION 36,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

From the Center-North-North 1/64 for Section 36, heretofore described.

Corner Point Identity: **E640N175**

**S 89° 53.1' W**, Beginning new measurement along the East-West Center Line of the North-East 1/4 of the North-West 1/4 for Section 36.

**21.314**

The Center-North, North-West 1/64 for Section 36.

Corner Point Identity: **E620N175**

---

**EAST HALF OF THE SOUTH-WEST 1/4 OF THE NORTH-WEST 1/4 OF  
SECTION 36, TOWNSHIP 14 NORTH, RANGE 03 EAST,  
SALT LAKE MERIDIAN, UTAH**

---

From the Center-East, West-West 1/256 for Section 36, heretofore described.

Corner Point Identity: **E615N135**

**N 00° 04.6' W**, Beginning new measurement along the Center Line for the East half of the South-West 1/4 of the North-West 1/4 for Section 36.

**19.961**

Point for the Center-East-West, North-West 1/256 Section Corner of Section 36, heretofore described.  
Corner Point Identity: **E615N155**

---

**NORTH-WEST 1/4 OF THE NORTH-WEST 1/4 OF SECTION 36,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

---

From the Center-West, North-West 1/64 for Section 36, heretofore described.

Corner Point Identity: **E610N155**

**N 00° 07.2' W**, Beginning new measurement along the North-South Center Line for the North-West 1/4 for the North-West 1/4.

**9.991**

Point for the North-West, North-West 1/64 for Section 36.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground with aluminum cap marked:

T14N R3E  
N-W N-W  
1/64  
S 36  
2005

**NORTH-WEST 1/4 OF THE NORTH-WEST 1/4 OF SECTION 36,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

Raise a mound of stone, 3 feet base, 2 feet high, encircling corner to top of cap.

Corner Point Identity: **E610N175**  
Latitude: **41° 55' 06.419"**  
Longitude: **111° 33' 54.135"**  
Elevation: **6,488.92 ft.**

---

From the North-West, North-West 1/64 Section Corner for Sections 25 and 36.

Corner Point Identity: **E610N175**

**N 00° 07.2' W**, Continuing along the North-South Center Line for the North-West 1/4, of the North-West 1/4.

**19.982**

Point for the West-West 1/64 on the North boundary of Section 36, and South boundary of Tract 37. heretofore described.

Corner Point Identity: **E610N180**

---

From the Center-North, North-West 1/64 Corner for Section 36, heretofore described.

Corner Point Identity: **E620N175**

**S 89° 53.1' W**, Beginning new measurement along the East-West Center Line for the North-West 1/4 of the North-West 1/4.

**05.330**

Point for the Center-East, North-West, North-West 1/256 Section Corner of Section 36.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground with aluminum cap marked:

T14N R3E  
C-E N-W  
N-W 1/256  
S 36  
2005

Raise a mound of stone, 3 feet base, 2 feet high, encircling corner to top of cap.

Corner is located on East slope and about 2 chains West of River.

Corner Point Identity: **E615N175**  
Latitude: **41° 55' 06.426"**  
Longitude: **111° 33' 49.483"**  
Elevation: **6,503.93 ft.**

**NORTH-WEST 1/4 OF THE NORTH-WEST 1/4 OF SECTION 36,  
TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**

**CHAINS**

From the Center-East, North-West, North-West 1/256 Section Corner for Section 36, heretofore described.

Corner Point Identity: **E615N175**

**S 89° 53.1' W**, Continuing along the East-West Center Line for the North-West 1/4 of the North-West 1/4, Section 36.

**10.660**

The Corner for the North-West, North-West 1/64 Section Corner, heretofore described.

Corner Point Identity: **E610N175**

---

From the North-West, North-West 1/64 Section Corner, heretofore described.

Corner Point Identity: **E610N175**

**S 89° 53.1' W**, Continuing along the East-West Center Line for the North-West 1/4 of the North-West 1/4.

**21.320**

The North-North 1/64 Section Corner, on the West Boundary of Section 36.

Corner Point Identity: **E600N175**

---

**SOUTH-EAST 1/4 OF THE NORTH-WEST 1/4 OF THE NORTH-WEST 1/4  
OF SECTION 36, TOWNSHIP 14 NORTH, RANGE 03 EAST,  
SALT LAKE MERIDIAN, UTAH**

---

From the Center-East-West, North-West 1/256 Section Corner for Section 36, heretofore described.

Corner Point Identity: **E615N155**

**N 00° 03.6' W**, Beginning new measurement along the North-South Center Line of the South-East 1/4 of the North-West 1/4 of the North-West 1/4 of Section 36.

**09.981**

Point for the Center-East, North-West, North-West 1/256, Section Corner. heretofore described.

Corner Point Identity: **E615N175**

---

**GENERAL DESCRIPTION**  
**TOWNSHIP 14 NORTH, RANGE 03 EAST,**  
**SALT LAKE MERIDIAN, UTAH**  
**(Pg.1 OF 2)**

**UNITED STATES DEPUTY SURVEYOR**  
**FOR CONTRACT NUMBER 100 AUGUST 31, 1881**  
**JAMES H. MARTINEAU**

**NOTE: ITALICIZED SCRIPT IS USED FOR THE RECORD HISTORY**

Much of this Township is covered with timber but most of it has been killed by Forest Fires. In the South part there is a large area of young aspens 1 to 3 inches in diameter and much heavy brush. The Western portion is very high and broken, being a Main Range of the Wasatch Mountains that range from 9,000 to 12,000 feet high. The Mountains slopes being covered with perpetual snow which is now from 10 to 30 feet deep.

Logan River runs through the Eastern part and is a fine Mountain stream of good clear water abounding in trout. Mayhems Mill and some dwellings are situated in Section 36.

Petersons Mill and other houses are in Section 15 and three families were building houses in Section at Hanson's Foggy Saw Mill and other houses are situated in Section 21. Theses Mills use mostly the Fire Killed Timber for Lath, Shingles and Rail-Road Ties for the Utah and Northern Rail-Road.

The Country is too elevated for crops but will sustain Cattle and Horses. No Minerals were discovered and I could hear of none. I therefore return the whole Township as non-mineral. Mr. Holden at whose request the Survey of this Township was made has removed from the Township and sold his house, claims and interest in the Saw Mill to Merriest Card and Nimbly, who still continues the Lumber, Lath, and Shingles business. All three Saw Mills are very substantial buildings as are also the dwellings adjacent.

The Resurvey of Township 14 North, Range 03 East, Salt Lake Meridian, and Township 14 North, Range 04 East, Salt lake Meridian, has revealed the ground measurements reported by James H. Martineau and Francis E. Joy, are inconsistent with the Official Field Note Record.

**Township 14 North, Range 03 East**

- ( 01 )      The East-West measurement between Sections 1, and 36, on the South Boundary of Township shows a distance of **83.600 chains**, which is **237.60 feet** longer than what was reported.
- ( 02 )      The East-West measurement between Sections 25, and 36, shows a distance of **85.440 chains**, which is **355.08 feet** longer than what was reported.
- ( 03 )      The East-West measurement between Sections 24, and 25, shows a distance of **84.468 chains**, which is **284.99 feet** longer than what was reported.

**GENERAL DESCRIPTION**  
**TOWNSHIP 14 NORTH, RANGE 03 EAST,**  
**SALT LAKE MERIDIAN, UTAH**  
**(Pg. 2 OF 2)**

- ( 04 ) The North-South measurement between Sections 31, and 36, on the East Boundary of Township, shows a distance of **78.700 chains**, which is **85.80 feet** shorter than what was reported.
- ( 05 ) The North-South measurement between Sections 25, and 30, on the East Boundary of Township, shows a distance of **84.820 chains**, which is **318.12 feet** longer than what was reported.
- ( 06 ) The North-South measurement between Sections 35, and 36, shows a distance of **84.584 chains**, which is **302.54 feet** longer than what was reported.
- ( 07 ) The North-South measurement between Sections 25, and 26, shows a distance of **80.334 chains**, which is **22.04 feet** longer than what was reported.

**Township 14 North, Range 04 East**

- ( 08 ) The North-South measurement between Sections 27, and 28, shows a distance of **84.875 chains**, which is **321.75 feet** longer than what was reported.
- ( 09 ) The North-South measurement between Sections 28, and 29, shows a distance of **85.070 chains**, which is **334.62 feet** longer than what was reported.
- ( 10 ) The North-South measurement between Sections 29, and 30, shows a distance of **84.748 chains**, which is **313.37 feet** longer than what was reported.

From the above **TEN** examples there are **SIX** that report an average distance of **325.00 feet** longer than survey record. This comparison is within **4.20 feet** of a "**FIVE CHAIN BLUNDER**". The American Heritage Dictionary expressed **BLUNDER** as follows; 1. A stupid and grave mistake, 2. A clumsy and foolish act, 3. To make a stupid mistake because of ignorance or confusion, 4. To botch or bungle thoughtlessly and proceed blindly. For these reasons and the circumstances that have accrued since James H. Martineau commenced his contract survey, it was necessary to use the following guidance from the Manual of Surveying Instructions 1973.

**CONTENT**

**SECTION SERIES**

<b>BONA FIDE RIGHTS OF CLAIMANTS:</b>	{ 6-12 } { 6-13 } { 6-14 } { 6-15 }
	{ 6-16 } { 6-17 } { 6-18 }
<b>THE INDEPENDENT RESURVEY:</b>	{ 6-33 } { 6-34 } { 6-35 }
<b>REESTABLISHMENT OF OUTBOUNDARIES:</b>	{ 6-36 } { 6-37 } { 6-38 }
<b>METES AND BOUNDS SURVEY:</b>	{ 6-39 } { 6-40 } { 6-41 } { 6-42 }
	{ 6-43 } { 6-44 } { 6-45 } { 6-46 }
	{ 6-47 } { 6-48 } { 6-49 }
<b>THE PROJECTION OF NEW LINES:</b>	{ 6-50 } { 6-51 } { 6-52 } { 6-53 }
	{ 6-54 } { 6-55 } { 6-56 }

---

**TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**  
**ATTACHMENT NUMBER 01**  
**AFFIDAVIT LETTER FOR JULY 7, 2004**  
**(PG. 1 of 2)**

Date: July 7, 2004

Mr. Bruce Richeson  
Legislative Assistant

Dear Mr. Richeson,

Thank you for your willingness to hear our case regarding the land dispute we currently find ourselves in with the U.S. Forest Service. The property in question has been in our family since 1890 when it was homesteaded by our grandfather, Nicholas W. Crookston. Until recently, the land bordering ours has been owned by the State of Utah but was a part of a land exchange with the U.S. Forest Service. Prior to the exchange and for the last 112 years, there has never been any dispute or question about the boundaries currently in dispute.

I am including some of the evidence which supports our case. We also have additional evidence such as easements, deeds, field notes from the original surveyor (Martineau), which are not being sent due to the volume involved.

Included in the evidence we have sent you are historical documents and more recent documents all of which reference the quarter section corner which is in dispute. This corner has been used by several Surveyors since the original survey to describe the property boundaries as well as the location of improvements and easements on the property.

We have spent considerable time and resources in the past 10 months trying to come to a resolution with the U.S. Forest Service and have presented them with all these and other evidences. Over the past several months they have requested meetings and all the evidence we have to support our case. Unfortunately, Sandy Lewis, the Lead Surveyor for the Wasatch Cache National Forest has now indicated that she is unable to do anything to resolve the matter.

It seems to us that this situation is accurately described in the Surveyors Manual under "Bona Fide Rights of Claimants", wherein it says that the original survey stands, even if it was done in error.

We have relied in good faith on the original survey and have built a nice family cabin and a hydroelectric generator and other improvements. This new survey moves our property right out from under our cabin.

My wife and I are in our 80's and we are in the process of transferring our property to our 12 children through our Limited Liability Company ( LLC ). However, this process is being delayed by the pending legal description of the property.

**TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**  
**ATTACHMENT NUMBER 01**  
**AFFIDAVIT LETTER FOR JULY 7, 2004**  
**(PG. 2 of 2)**

We would greatly appreciate your assistance in resolving this matter in a timely manner. Please feel free to contact me or my daughter Eve I. Jones, should you have any questions or require additional information regarding this situation.

Sincerely, Lyle E. and Marianna Crookston Israelsen  
Eve I. Jones

---

**TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**  
**ATTACHMENT NUMBER 02**  
**AFFIDAVIT STATEMENT FOR JUNE 3, 2004**  
**(PG. 1 of 2)**

Date: June 3, 2004

TO WHOM IT MAY CONCERN:

I the undersigned Paul B. Crookston, owner of parcel Number 18-064-0002 of land designated as a "Conflict Area" in the North-West Corner of the South-West Corner of Section 25, Township 14 North, Range 03 East, of the Salt Lake Base and Meridian identified by survey of JSH Surveying and Drafting, Inc dated December 30, 2003, do offer the following statement to help clarify knowledge regarding the location of the 1/4 corner marker on the west boundary of above described section.

During the early 1940's my father Robert Burns Crookston began to develop a 17 acre parcel of land in the North West corner of the South-West Corner of the above Section. This was inherited from his father Nicholas Welch Crookston. I was a boy at the time and relished the many trips to this property.

It was either 1942 or 1943 on or about my birthday in June when I went with my father and with a Surveyor introduced to me as Erwin U. Moser ( *Engineer & Land Surveyor License Number 101386-2202 issue in January 01, 1910 and expiration April 30, 1986* ). The purpose of the trip was to establish an East-West line on the North side of the property as well as a North-South line on the West side of the property. I was familiar with the Quarter Section Corner with the "Cedar Post" and "Iron Stake" as my father had taken me to it before.

Mr. Moser enlisted me to hold a tall staff with a flag on the top which he placed by the "Iron Stake" adjacent to the "Cedar Post". He then crossed the Canyon to a marker located in the Center of Section 25, which was a short distance from the "Old Cabin" built by Nicholas Welch Crookston.

There he set up his survey device on a tripod where he could see my flag. He could not see me because of trees. He had my father stand west of me up the hill where they could see each other. Mr. Moser then used hand signals to move my father left or right until he was in line with my flag and the survey equipment. My father marked the spot. Mr. Moser then returned to our location and marked the East-West line by placing an "Iron Peg" East of the Quarter Corner where I had held the flag. This would be our North fence line. He then marked the North-South line and set an "Iron Stake" 100 feet south of the Quarter Corner. That marker exists today and was used to identify the North-West corner of my parcel.

My father later used the line on the North side of the property to install a fence. Also, a fence on the West side was installed East of the West line, below the rocky hill along the West side of the grove of aspen. The fences were designed to keep sheep and cattle out of the area that would later have a cabin.

**TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**  
**ATTACHMENT NUMBER 02**  
**AFFIDAVIT STATEMENT FOR JUNE 3, 2004**  
**(PG. 2 of 2)**

The above Quarter Corner marker has been used at least twice that I am aware of for survey purposes, the one described above; and also, one by my cousin Dean F. Peterson, Dean of the College of Engineering at Utah State University who conducted a survey there to locate his own East-West property line ( see parcel 18-064-0009 ).

I have seen flagging at the marker and among the trees on the West line several times which indicated to me that the marker was being used for other surveys.

My siblings and I have always used this Quarter Corner marker as a true survey point. We have identified our properties together with our road and spring easement from that point. We have also developed a water system including a line that runs along my West boundary to my brother's property adjacent to me on the North. This was no easy task because of a rocky hill of boulders. I have used water on my parcel from this line. This was a dedicated and expensive process and again, was based upon our understanding that the survey lines were truly defined. I have also obtained a building permit to place a home on the site and have paid for a building design that fits the location. The building plans amounted to over \$ 3,095.00.

Accordingly, on the basis of the above, I certify that I have in the past and do now act on an understanding that the above quarter corner was placed there originally by a duly Certified Public Surveyor and has been continually used as a true point of reference by other Licensed Surveyors.

Signed: Paul B. Crookston

[ STATE OF UTAH : COUNTY OF CARBON ]

On the 3rd day of June 2004, personally appeared before me PAUL B. CROOKSTON who affirmed the above to be a true statement and signed the above.

NOTARY PUBLIC:

Angela J. Randall,

RESIDING AT:

675 East, 100 North, Price Utah, 84501

MY COMMISSION EXPIRES:

March 16, 2008

---

TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH  
ATTACHMENT NUMBER 03  
AFFIDAVIT LETTER FOR APRIL 29, 2004  
(PG. 1 of 1)

Date: April 29, 2004

Justin Harding  
Senior Legislative Assistant

Dear Mr. Harding:

Thank you for making the effort to attend our meeting with the Forest Officials in Logan last winter. We regret some of the harsh language that was used there, but I think it reflected our frustration with the total disregard of the overwhelming wishes of the majority public response for multiple uses of the public lands. The local ranger was persuaded by the vocal special interest ski lobby to ignore the public input. We hope this dispute can be resolved before the coming winter.

I am sending supporting evidence in regards to the boundary dispute we are having with the Forest Service. This property has been in the Crookston family for 100 years and the boundary descriptions have been accepted by the Federal Government, the State of Utah and the County.

We have numerous documents signed and notarized , recognizing and accepting the original North West Corner of the South West quarter of Section 25.

It seems to us that this situation is accurately described in the Surveyors Manual under "Bona Fide Rights of Claimants", wherein it says that the original survey stands, even if it was done in error.

We have relied in good faith on the original survey and have built a nice family cabin and a hydro generator shed, etc... The new survey moves our property right out from under our cabin.

My wife and I are in our 80's and we are in the process of transferring our property to our 12 children through our Limited Liability Company ( LLC ). However, this process is being delayed by the pending legal description of the property,

We would appreciate the help of Representative Bishop in resolving this matter in a timely manner.

Sincerely, Lyle E. and Marianna Crookston Israelsen

---

TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH  
ATTACHMENT NUMBER 04  
LETTER FROM THE COMMISSIONER OF THE GENERAL LAND OFFICE  
(PG. 1 of 1)

---

DEPARTMENT OF THE INTERIOR  
UNITED STATES LAND OFFICE

NOVEMBER 23, 1905

Nicholas Welch Crookston  
Logan, Utah

SIR:

You are hereby notified that the desert-land act of March 3, 1877, as amended by the act of March 3, 1891, requires final proof of reclamation of the land and final payment to be made within ( 5 ) years from date of Case Entry.

Case Entry Number is; ( 12474 )

Case entry for; ( 160 acres of Un-Surveyed Land, within the South-West One Quarter of Section 25 Township 14 North, Range 3 East, of the Salt Lake Meridian, Utah )

Case Entry Dated; ( June 23. 1890 )

The time fixed by the statute has expired without the requisite proof and payment being made by you. You will, therefore, within ninety days from date of service of this notice show cause before us why your claim should not be declared forfeited and your entry canceled for noncompliance with the requirements of the law, so that the case may be reported to the Commissioner of the General Land Office for proper action.

Lorenzo R. Thomas Register.

FORM: 4---355a.

---

---

TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH  
ATTACHMENT NUMBER 05  
UNITED STATES DEPARTMENT OF THE INTERIOR  
GENERAL LAND OFFICE  
LAND STATUS RECORDS AND HISTORICAL INDEX  
(PG. 1 of 1)

---

TOWNSHIP 14 NORTH RANGE 03 EAST      SALT LAKE MERIDIAN      UTAH

---

SECTION OR TRACT:            ( 25 )  
SUBDIVISION:                ( *South-West Quarter* )  
ACRES:                        ( 160.00 )  
KIND OF ENTRY:              ( *Home Stead Entry "HE"* )  
SERIAL FILE NUMBER:        ( 12474 )  
DATE OF ACTION:             ( 10/14/1896 )  
REMARKS:                     ( *Relinquish. 12/19/1901* )

---

SECTION OR TRACT:            ( 25 )  
SUBDIVISION:                ( *South-West Quarter* )  
ACRES:                        ( 160.00 )  
KIND OF ENTRY:              ( *State Selection "SS" Normal School* )  
SERIAL FILE NUMBER:        ( 12474 )  
DATE OF ACTION:             ( 07/08/1902 )  
REMARKS:                     ( *Other Description: T14N R03E, Salt Lake Meridian* )

---

**TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**  
**ATTACHMENT NUMBER 06**  
**GENERAL LAND OFFICE RECORDS FOR**  
**INDEX FOR CONTRACT NUMBER 100, AND BOOK NUMBER 174**  
**U. S. DEPUTY SURVEYOR, JAMES H. MARTINEAU MARCH 19, 1881**  
**(PG. 1 of 1)**

INDEX	TOWNSHIP	PAGES	COMMENCED-COMPLETED	
01	T36S R10W	367-498	APR 28	MAY 28

**LIST OF ASSISTANTS NAMES FOR ABOVE TOWNSHIP**

Compass Man: John M. Macfarlane  
Chainman: George Tait  
Chainman: Thomas Urie  
Mound Man: Peter Mackelprang  
Mound Man: Henry S Lunt Jr.  
Axe Man: Randle W. Lunt  
Flag Man: Jesse N Martineau

02	T12N R01E	118-119	JUN 17	JUN 18
03	T12N R02E	120-125	JUN 19	JUN 20
04	T12N R03E	126-133	JUN 21	JUN 22
05	T13N R03E	134-145	JUN 23	JUN 24
06	T15N R03E	153-154	JUN 25	JUN 26

**LIST OF ASSISTANTS NAMES FOR ABOVE TOWNSHIPS**

Compass Man: Edward Hanson  
Chainman: Seth H. Langton  
Chainman: Joseph E. Hyde  
Flag Man: Jesse N. Martineau

07	T14N R04E	270-362	JUL 08	AUG 01
<b>08</b>	<b>T14N R03E</b>	<b>163-264</b>	<b>AUG 02</b>	<b>AUG 31</b>
09	T10N R04E	003-103	SEP 12	OCT 01

**LIST OF ASSISTANTS NAMES FOR ABOVE TOWNSHIPS**

Compass Man: Edward Hanson  
Chainman: Charles E. Anderson  
Chainman: Marion A. Lewis  
Chainman: G. Willis Morse  
Chainman: Charles F. Martineau  
Axe Man: Hans S. Nielson  
Flag Man: Leonard C. Angell

TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH  
ATTACHMENT NUMBER 07  
GENERAL LAND OFFICE RECORDS FOR CONTRACT NUMBER 100 AND BOOK NUMBER 174  
CROSS-EXAMINATION OF WORK SCHEDULE FOR JAMES H. MARTINEAU;  
U. S. DEPUTY SURVEYOR, MARCH 19, 1881  
(PG. 1 of 4)

NUM	DAY	MONTH	PAGES	HOURS	MON	MILES	
117	28	APR	367-379	08	06	03	T36S R10W
118	29	APR		00	00	00	Exterior
119	30	APR	380-384	08	08	04	
120	01	MAY		00	00	00	
121	02	MAY	385-387	08	02	01	
122	03	MAY	388-389	08	02	01	
123	04	MAY		00	00	00	
124	05	MAY	390-390	08	02	01	
125	06	MAY	391-395	08	08	04	
126	07	MAY	396-398	08	06	03	
127	08	MAY		00	00	00	
128	09	MAY	399-403	08	06	03	
129	10	MAY	404-407	08	08	04	
130	11	MAY	408-410	08	04	02	
131	12	MAY		00	00	00	
132	13	MAY	411-418	12	12	06	Exterior
133	14	MAY	419-422	08	02	01	T36S R10W
134	15	MAY		00	00	00	Subdivision
135	16	MAY	423-426	08	08	04	
136	17	MAY	427-432	12	12	06	
137	18	MAY	433-436	08	08	04	
138	19	MAY	437-442	12	12	06	
139	20	MAY	443-448	12	12	06	
140	21	MAY	449-453	10	10	05	
141	22	MAY		00	00	00	
142	23	MAY	454-460	14	14	07	
143	24	MAY	461-467	14	14	07	
144	25	MAY	468-472	10	10	05	
145	26	MAY	473-477	10	10	05	
146	27	MAY	478-483	12	12	06	Subdivision
147	28	MAY	484-498	10	10	05	T36S R10W
148	29	MAY		00	00	00	
149	30	MAY		00	00	00	
150	31	MAY		00	00	00	
151	01	JUN		00	00	00	
152	02	JUN		00	00	00	
153	03	JUN		00	00	00	
154	04	JUN		00	00	00	
155	05	JUN		00	00	00	
156	06	JUN		00	00	00	
157	07	JUN		00	00	00	
158	08	JUN		00	00	00	
159	09	JUN		00	00	00	
160	10	JUN		00	00	00	
161	11	JUN		00	00	00	
162	12	JUN		00	00	00	
163	13	JUN		00	00	00	

TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH  
 ATTACHMENT NUMBER 07  
 GENERAL LAND OFFICE RECORDS FOR CONTRACT NUMBER 100 AND BOOK NUMBER 174  
 CROSS-EXAMINATION OF WORK SCHEDULE FOR JAMES H. MARTINEAU;  
 U. S. DEPUTY SURVEYOR, MARCH 19, 1881  
 (PG. 2 of 4)

NUM	DAY	MONTH	PAGES	HOURS	MON	MILES	
164	14	JUN		00	00	00	
165	15	JUN		00	00	00	STANDARD
166	16	JUN		00	00	00	3rd NORTH
<b>167</b>	<b>17</b>	<b>JUN</b>	<b>112-119</b>	<b>08</b>	<b>02</b>	<b>01</b>	<b>T12N R01E</b>
<b>168</b>	<b>18</b>	<b>JUN</b>	<b>120-122</b>	<b>08</b>	<b>06</b>	<b>03</b>	<b>T12N R02E</b>
169	19	JUN		00	00	00	
<b>170</b>	<b>20</b>	<b>JUN</b>	<b>123-126</b>	<b>08</b>	<b>06</b>	<b>03</b>	<b>T12N R02E</b>
<b>171</b>	<b>21</b>	<b>JUN</b>	<b>127-129</b>	<b>08</b>	<b>06</b>	<b>03</b>	<b>T12N R03E</b>
<b>172</b>	<b>22</b>	<b>JUN</b>	<b>130-136</b>	<b>08</b>	<b>08</b>	<b>04</b>	<b>T12N R03E</b>
<b>173</b>	<b>23</b>	<b>JUN</b>	<b>137-144</b>	<b>10</b>	<b>10</b>	<b>05</b>	<b>GUIDE MER</b>
<b>174</b>	<b>24</b>	<b>JUN</b>	<b>144-148</b>	<b>08</b>	<b>06</b>	<b>03</b>	<b>T13N R03E</b>
<b>175</b>	<b>25</b>	<b>JUN</b>	<b>149-152</b>	<b>08</b>	<b>08</b>	<b>04</b>	<b>T13N R03E</b>
<b>176</b>	<b>26</b>	<b>JUN</b>	<b>153-162</b>	<b>08</b>	<b>02</b>	<b>01</b>	<b>T15N R03E</b>
177	27	JUN		00	00	00	
178	28	JUN		00	00	00	
179	29	JUN		00	00	00	
180	30	JUN		00	00	00	
181	01	JUL		00	00	00	
182	02	JUL		00	00	00	
183	03	JUL		00	00	00	
184	04	JUL		00	00	00	
185	05	JUL		00	00	00	
186	06	JUL		00	00	00	
187	07	JUL		00	00	00	
<b>188</b>	<b>08</b>	<b>JUL</b>	<b>270-277</b>	<b>08</b>	<b>06</b>	<b>03</b>	<b>T14N R04E</b>
<b>189</b>	<b>09</b>	<b>JUL</b>	<b>278-282</b>	<b>10</b>	<b>10</b>	<b>05</b>	<b>Exteriors</b>
190	10	JUL		00	00	00	
191	11	JUL		00	00	00	
<b>192</b>	<b>12</b>	<b>JUL</b>	<b>283-285</b>	<b>08</b>	<b>04</b>	<b>02</b>	
<b>193</b>	<b>13</b>	<b>JUL</b>	<b>286-290</b>	<b>10</b>	<b>10</b>	<b>05</b>	
<b>194</b>	<b>14</b>	<b>JUL</b>	<b>291-299</b>	<b>12</b>	<b>12</b>	<b>06</b>	<b>Exteriors</b>
<b>195</b>	<b>15</b>	<b>JUL</b>	<b>300-301</b>	<b>08</b>	<b>02</b>	<b>01</b>	<b>T14N R04E</b>
<b>196</b>	<b>16</b>	<b>JUL</b>	<b>302-305</b>	<b>08</b>	<b>08</b>	<b>04</b>	<b>Subdivision</b>
197	17	JUL		00	00	00	
<b>198</b>	<b>18</b>	<b>JUL</b>	<b>306-311</b>	<b>12</b>	<b>12</b>	<b>06</b>	
<b>199</b>	<b>19</b>	<b>JUL</b>	<b>312-313</b>	<b>08</b>	<b>04</b>	<b>02</b>	
<b>200</b>	<b>20</b>	<b>JUL</b>	<b>314-317</b>	<b>08</b>	<b>08</b>	<b>04</b>	
<b>201</b>	<b>21</b>	<b>JUL</b>	<b>318-321</b>	<b>08</b>	<b>08</b>	<b>04</b>	
<b>202</b>	<b>22</b>	<b>JUL</b>	<b>322-322</b>	<b>08</b>	<b>02</b>	<b>01</b>	
<b>203</b>	<b>23</b>	<b>JUL</b>	<b>323-326</b>	<b>08</b>	<b>08</b>	<b>04</b>	
204	24	JUL		00	00	00	
<b>205</b>	<b>25</b>	<b>JUL</b>	<b>327-331</b>	<b>10</b>	<b>10</b>	<b>05</b>	
<b>206</b>	<b>26</b>	<b>JUL</b>	<b>332-333</b>	<b>08</b>	<b>04</b>	<b>02</b>	
<b>207</b>	<b>27</b>	<b>JUL</b>	<b>334-339</b>	<b>12</b>	<b>12</b>	<b>06</b>	
<b>208</b>	<b>28</b>	<b>JUL</b>	<b>340-346</b>	<b>14</b>	<b>14</b>	<b>07</b>	
<b>209</b>	<b>29</b>	<b>JUL</b>	<b>347-347</b>	<b>08</b>	<b>02</b>	<b>01</b>	

TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH  
ATTACHMENT NUMBER 07  
GENERAL LAND OFFICE RECORDS FOR CONTRACT NUMBER 100 AND BOOK NUMBER 174  
CROSS-EXAMINATION OF WORK SCHEDULE FOR JAMES H. MARTINEAU;  
U. S. DEPUTY SURVEYOR, MARCH 19, 1881  
(PG. 3 of 4)

NUM	DAY	MONTH	PAGES	HOURS	MON	MILES	
210	30	JUL	348-353	12	12	06	Subdivision
211	31	JUL		00	00	00	
212	01	AUG	354-366	08	08	04	T14N R04E
213	02	AUG	163-164	10	02	01	T14N R03E
214	03	AUG	165-171	12	12	06	Exteriors
215	04	AUG	172-175	08	06	03	
216	05	AUG	176-178	08	04	02	
217	06	AUG	179-181	08	04	02	
218	07	AUG		00	00	00	
219	08	AUG	182-188	06	12	06	Exteriors
220	09	AUG		00	00	00	
221	10	AUG	189-190	08	02	01	T14N R03E
222	11	AUG	191-196	08	12	06	Subdivision
223	12	AUG	197-200	08	08	04	
224	13	AUG		00	00	00	
225	14	AUG	201-204	08	08	04	
226	15	AUG	205-207	08	06	03	
227	16	AUG	208-211	08	08	04	
228	17	AUG	212-214	08	06	03	
229	18	AUG	215-215	08	02	01	
230	19	AUG	216-220	10	10	05	
231	20	AUG	221-226	12	12	06	
232	21	AUG		00	00	00	
233	22	AUG	227-229	08	06	03	
234	23	AUG	230-233	08	08	04	
235	24	AUG	234-238	10	10	05	
236	25	AUG	239-239	08	02	01	
237	26	AUG	240-247	16	16	08	
238	27	AUG	248-254	14	14	07	
239	28	AUG		00	00	00	
240	29	AUG	255-258	08	08	04	
241	30	AUG	259-262	08	08	04	Subdivision
242	31	AUG	263-269	08	06	03	T14N R03E
243	01	SEP		00	00	00	
244	02	SEP		00	00	00	
245	03	SEP		00	00	00	
246	04	SEP		00	00	00	
247	05	SEP		00	00	00	
248	06	SEP		00	00	00	
249	07	SEP		00	00	00	
250	08	SEP		00	00	00	
251	09	SEP		00	00	00	
252	10	SEP		00	00	00	
253	11	SEP		00	00	00	

TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH  
 ATTACHMENT NUMBER 07  
 GENERAL LAND OFFICE RECORDS FOR CONTRACT NUMBER 100 AND BOOK NUMBER 174  
 CROSS-EXAMINATION OF WORK SCHEDULE FOR JAMES H. MARTINEAU;  
 U. S. DEPUTY SURVEYOR, MARCH 19, 1881  
 (PG. 4 of 4)

NUM	DAY	MONTH	PAGES	HOURS	MON	MILES	
254	12	SEP	003-006	08	04	02	T10N R04E
255	13	SEP	007-010	08	08	04	Exteriors
256	14	SEP	011-017	12	12	06	
257	15	SEP	018-024	14	12	06	
258	16	SEP	025-027	10	02	01	
259	17	SEP	028-034	10	10	05	Exteriors
260	18	SEP		00	00	00	
261	19	SEP	035-039	08	06	03	T10N R04E
262	20	SEP	040-046	12	12	06	Subdivision
263	21	SEP	047-051	10	10	05	
264	22	SEP	052-058	14	14	07	
265	23	SEP	059-063	10	10	05	
266	24	SEP	064-069	10	10	05	
267	25	SEP		00	00	00	
268	26	SEP	070-073	08	08	04	
269	27	SEP	074-079	12	12	06	
270	28	SEP	080-086	14	14	07	
271	29	SEP	087-092	12	12	06	
272	30	SEP	093-099	14	14	07	Subdivision
273	01	OCT	100-111	08	08	04	T10N R04E
274	02	OCT		00	00	00	

DAYS	DAYS	PAGES	HOU/DAY	MON	MILES	
116	096	003-498	916 / 115	778	389	TOTAL

**TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**  
**ATTACHMENT NUMBER 08**  
**RESULTS OF CROSS-EXAMINATION FOR CONTRACT NUMBER 100**  
**JAMES H. MARTINEAU**  
**(PG. 1 of 1)**

TOWNSHIP	SPAN	DAYS	HOU/DAY	MON	MILES	AVERAGE
T36S - R10W SLM	31	24	232 / 29	198	99	3.4
3RD STAN NORTH	10	09	074 / 09	054	27	2.9
T14N - R04E SLM	25	20	188 / 24	156	78	3.3
T14N - R03E SLM	30	25	228 / 29	192	96	3.4
T10N - R04E SLM	20	18	194 / 24	178	89	3.7
<b>TOTAL:</b>	<b>116</b>	<b>96</b>	<b>916 / 115</b>	<b>778</b>	<b>389</b>	<b>3.3 MILES</b>

Under Contract Number 100, James H. Martineau surveyed an average of [3.3] miles per day, with a survey crew consisting of the following members;

( 1 to 1 ) Compass-Man  
( 2 to 4 ) Chain-Man  
( 0 to 2 ) Mound-Man  
( 0 to 1 ) Axe-Man  
( 1 to 1 ) Flag-Man

( 4 to 9 ) Crew Member Average of ( 6 ) Personnel.

Each Survey Crew Member would have to walk ( 17,600 feet ) or ( 266.66 chains ) per day.

This would require the Chain-Man to measure 1/2 mile every hour, and set ( 27 ) marks using a 100 foot tape, or set ( 40 ) marks using 66 foot chain.

In 8 hours the Survey Crew would have made ( 216 or 320 ) marks and constructed and set ( 7 ) Monuments.

This amount work would have required a considerable undertaking to cut line through heavy timber and thick vegetation. It would have been a tremendous accomplishment to traverse the extremely rugged mountain's terrain within the time constants identified.

One can only speculate if all the monuments identified as properly marked and set, are where the official record reported them to be ?

**TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**  
**ATTACHMENT NUMBER 09**  
**UNITED STATES DEPUTY SURVEYOR**  
**BIOGRAPHICAL EVENTS FOR JAMES HENRY MARTINEAU**  
**(PG. 1 of 3)**

---

- 1828/03/13** **James Henry Martineau ( JHM )** was born in Amsterdam, Montgomery County, New York, the son of John Martineau and Eliza Mears.
- 1844/08/28** **JHM** Graduated from Monroe Academy, New York, at the age of Sixteen and entered the printing office of the "Cayuga Tocsin" as a compositor and pressman on one of the first Hoe Press made.
- 1846** **JHM** Enlisted in the United States Regular Army to serve during the Mexican War, and was sent to Newport Barracks where he served in various ways on detachments service until the war ended.
- 1848/07** **JHM** was Honorably discharged and returned to Milwaukee Wisconsin.
- 1849** **JHM** started out for California, but on his arrival at the Missouri River he was told that it would be impossible to continue so late in the season and be able to safely cross the plains. JHM stayed the winter in Western Missouri teaching school.
- 1850/Spring** **JHM** started out again on his journey to the Pacific Coast, during which time his life was twice miraculously preserved.
- 1850/ 07/22** **JHM** arrived in Salt Lake City, where he was impressed to stop for the season and go on West the next year. During which time two women, the wife of Elder Parley P. Pratt and the widow of Don Carlos Smith taught him the gospel of the L.D.S Church, where in he was baptized January 19, 1851.
- 1851/02** **JHM** went with William K. Rice to the new town of Parowan that had been established three months earlier. This was the first company to provide reinforcements to the settlement of Parowan. It was at this time JHM joined the Nauvoo Legion under the command of Col. George A. Smith as a Sergeant Major, and there after a Second Lieutenant within the Iron Military District, comprising all of Utah South of Fillmore.
- JHM** was the first County clerk for Iron County and the first City Recorder of Parowan. JHM also served as City Councilor and Alderman, along with other duties as serving as County Surveyor and Town Sheriff.
- JHM** surveyed the town of Parowan, Paragonah, Fort Johnson and Beaver. He kept the records for all military operations, explorations and Indian difficulties, which at times were very serious and threatened their destruction.

**TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH**  
**ATTACHMENT NUMBER 09**  
**UNITED STATES DEPUTY SURVEYOR**  
**BIOGRAPHICAL EVENTS FOR JAMES HENRY MARTINEAU**  
**(PG. 2 of 3)**

---

- 1852/01/08** **JHM** married Susan Ellen Johnson, the daughter of Joel H. Johnson. Susan Ellen Johnson was born in Kirtland, Ohio on July 11, 1836.
- 1857/01/18** **JHM** married Susan Julia Sherman, the daughter of Lyman Royal Sherman and Delcena Disdamie Johnson. Susan Julia was born in Far West, Missouri on October 21, 1838. She became the Mother of eight children. She died January 28, 1874 at the age of 36 years old.
- 1858** **JHM** was with a Military Company of sixty men sent out by Governor Brigham Young to hunt for a place of refuge for the L.D.S. Saints, when the United States Army was to invade Utah. **JHM**, made the historian report of the expedition to Governor Young.
- 1860/07** **JHM** was advised by Governor Brigham Young, that he was needed in Cache Valley as a Surveyor because of the rapid settlement taking place. **JHM** located many large canals and helped install the Logan City water works. It was at this time that **JHM** became County Surveyor, County Clerk and City Recorder for the City of Logan.
- During **JHM's** twenty-four years residence in Logan, Utah, he surveyed large additions to the Logan City Plat.
- JHM** also surveyed the following Utah Cities; Providence, Millville, Hyrum, Paradise, Wellsville, Mendon, Newton, Clarkston, Richmond, Smithfield, Hyde Park, and Benson.
- JHM** also surveyed the following Idaho Cities; Weston, Oxford, Franklin, Blackfoot, and Idaho Falls.
- JHM** also served as United States Deputy Internal Revenue Collector and also as a "Minute Man" for more than twenty years. **JHM** was involved with many military expeditions to counter Indian troubles. He served as a staff member for General Daniel H. Wells and Military Instructor for the Nauvoo legion that consisted of three full regiments.
- 1868** **JHM** assisted as a Topographical Surveyor and Construction Engineer in locating the Union Pacific Railroad from Echo Canyon to central Nevada.
- JHM** helped complete the first western terminal for the Railroad and conducted a Geodetic Survey for the Smithsonian Institute from Central Nevada to Ogden, Utah.

TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH  
ATTACHMENT NUMBER 09  
UNITED STATES DEPUTY SURVEYOR  
BIOGRAPHICAL EVENTS FOR JAMES HENRY MARTINEAU  
(PG. 3 of 3)

---

- 1869 JHM surveyed and located the Railroad from Ogden to Salt Lake City, 1872 and the Utah Northern Railroad from Ogden to Franklin Idaho.
- 1877 JHM laid out the foundations for the Logan Temple and wrote an official history of its construction for the L.D.S. Church record.
- 1881 JHM surveyed and located the following Townships within Public Lands as a United States Deputy Surveyor under three different U.S. Surveyor Generals. T36S-R10W, T10N-R04E, T14N-R03E, & T14N-R04E.
- 1882/11 JHM went with Elders Erastus Snow and Moses Thatcher to Sonora Mexico, and returned in January 1883.
- 1884 JHM was called to Arizona to act as Second Counselor to President Christopher Layton. JHM, helped organize the St. Joseph Stake which was comprised of the Maricopa, Pima, and Mesa settlements. JHM explored Northern Sonora as far South as Magdalena and visited various estates.
- 1903 JHM moved to Salt Lake City, after nearly seventeen years of living in the Mormon colonies that were established within Arizona and Mexico.
- 1903/09/14 JHM completed the baseline in the remote area of North-Eastern Utah, which Charles L. Dubois started in August 30, 1875 as a Deputy Surveyor. Martineau surveys the Uintah baseline that terminated at the intersection with Uintah Indian reservation.
- 1910/09/09 JHM reported in a letter to his son Joel the difficult financial straits he and wife Susan Ellen were experiencing, and that he could hardly stand alone or walk. He also expressed how difficult it was to pick up anything off the floor.
- 1921/06/24 JHM died in Salt Lake City at the age of Ninety-Three. He is buried in Logan City cemetery. His two wives had mothered a total of twenty children.
-

TOWNSHIP 14 NORTH, RANGE 03 EAST, SALT LAKE MERIDIAN, UTAH  
 ATTACHMENT NUMBER 10  
 INVESTIGATION RETRACEMENT SURVEY  
 SEARCH AREAS FOR CONTROLLING CORNER POSITIONS  
 (PG. 1 of 1)

Corner Point Identity	Latitude	Longitude	Elevation
01-E500N140-0095	41° 54' 49.7478"	111° 35' 13.4570"	<u>6353.76</u>
02-E500N140-0419	41° 54' 47.0964"	111° 35' 11.0913"	7237.07
03-E500N200-0070	41° 55' 15.8205"	111° 35' 13.4570"	<u>6353.86</u>
04-E500N200-1011	41° 55' 15.7046"	111° 35' 13.1802"	7261.38
05-E500N240-0069	41° 55' 41.8925"	111° 35' 13.4570"	<u>6353.96</u>
06-E500N245-0416	41° 55' 39.3721"	111° 35' 13.3803"	7163.27
07-E500N300-0073	41° 56' 08.3762"	111° 35' 13.3699"	<u>6354.08</u>
08-E500N300-1015	41° 56' 07.9573"	111° 35' 11.5858"	7467.52
09-E500N340-0097	41° 56' 34.4488"	111° 35' 13.3699"	<u>6354.21</u>
10-E500N400-0098	41° 57' 00.5214"	111° 35' 13.3699"	<u>6354.33</u>
11-E500N440-0106	41° 57' 26.5939"	111° 35' 13.3699"	<u>6354.43</u>
12-E540N300-0071	41° 56' 08.3079"	111° 34' 38.4082"	<u>6354.12</u>
13-E540N400-0105	41° 57' 00.5214"	111° 34' 38.3125"	<u>6354.33</u>
14-E600N300-0072	41° 56' 08.2395"	111° 34' 03.4553"	<u>6354.14</u>
15-E600N300-0116	41° 56' 08.1808"	111° 34' 01.5223"	6611.09
16-E600N340-0103	41° 56' 34.3121"	111° 34' 03.4553"	<u>6354.21</u>
17-E600N400-0099	41° 57' 00.3847"	111° 34' 03.4553"	<u>6354.28</u>
18-E640N400-0107	41° 57' 00.4610"	111° 33' 28.3456"	<u>6354.28</u>

**NOTE: Investigation Retracement was conducted by the Wasatch-Cache National Forest Service under the direction of Sandy Lewis, Lead Land Surveyor.**

**FIELD ASSISTANTS**

---

<b>Name</b>	<b>Capacity</b>
<b><u>National Forest Service; Wasatch-Cache Crew</u></b>	
Sandra Lewis	Lead Land Surveyor
Daniel Gillins	Survey Technician
Calvert Norton	Survey Technician
Ron Keith Batty	Survey Technician
<b><u>Bureau of Land Management; Utah State Office Crew</u></b>	
Ronald K. Baugh	Supervisory Land Surveyor
M. Ross Workman	Land Surveyor
Gregg C. Ostergaard	Survey Technician

---

**CERTIFICATE OF SURVEY**

I, **Frank C. Profaizer, Cadastral Surveyor**, hereby certify upon honor that, in pursuance of Special Instructions bearing the date of the **14th day of February, 2005**, I have **executed an Independent Resurvey and Dependent Resurvey of the East Portion of the South Boundary, and South Portion of the East Boundary, and the Sub-Divisional Lines for Sections 25, 26, 35, and 36, along with the segregation of Tract 37, within the South-West One Quarter of Section 25, of Township 14 North, Range 03 East, of the Salt Lake Meridian, in the State of Utah**, which are represented in the foregoing Field Notes as having been executed by me and under my direction; and that said Survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing Field Notes.

February 20, 2007  
Date

Frank C. Profaizer  
(Cadastral Surveyor)

**CERTIFICATE OF APPROVAL**

**BUREAU OF LAND MANAGEMENT**  
Salt Lake City, Utah

The foregoing Field Notes of the **Independent Resurvey and Dependent Resurvey of the East Portion of the South Boundary, and South Portion of the East Boundary, and the Sub-Divisional Lines Sections 25, 26, 35, and 36, along with the segregation of Tract 37, within the South-West One Quarter of Section 25, of Township 14 North, Range 03 East, of the Salt Lake Meridian, in the State of Utah**,

executed by **Frank C. Profaizer, Cadastral Surveyor**

having been critically examined and found correct, are hereby approved.

February 20, 2007  
Date

Daniel W. Webb  
Chief Cadastral Surveyor for Utah