

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

RETRACEMENT OF A PORTION OF THE UTAH-ARIZONA STATE BOUNDARY
(SOUTH BOUNDARY),

THE DEPENDENT RESURVEY OF THE EAST BOUNDARY,

THE SURVEY OF PORTIONS OF THE NORTH BOUNDARY AND SUBDIVISIONAL

LINES, THE SURVEY OF THE SUBDIVISION OF CERTAIN SECTIONS,

AND THE RESURVEY OF A TRACT AND 2 PARCELS IN SECTIONS 10 AND 11,

OF

TOWNSHIP 43 SOUTH, RANGE 10 EAST,

OF THE SALT LAKE MERIDIAN,

IN THE STATE OF UTAH

EXECUTED BY

Scott A. Burkhardt,
Cadastral Surveyor

Under Special Instructions dated **June 14, 2006**, approved **June 14, 2006**, which provided for the surveys included under Group Number **1006**, and Assignment Instructions dated **June 14, 2006**.

Survey commenced **July 17, 2006**

Survey completed **September 29, 2006**

INDEX DIAGRAM

TOWNSHIP 43 SOUTH, RANGE 10 EAST

| | | | | | |
|-----------|-------------------|-------------------------|-------------------------|-------------------------|------------------------|
| 6 | 5 41 | 17 4 33 42 | 16 3 25 34 | 16 2 18 26 | 15 1 8 19 |
| 7 | 8 42 | 9 34 43 | 10 27 35 | 11 19 28 | 12 9 20 |
| 18 | 17 44 | 16 36 45 | 15 28 37 | 14 21 29 | 13 10 22 |
| 19 | 20 45 | 21 37 46 | 22 30 38 | 23 22 31 | 24 12 23 |
| 30 | 29 46 | 28 39 47 | 27 31 40 | 26 23 32 | 25 13 24 |
| 31 | 32 48 3 | 33 40 3 | 34 32 4 | 35 24 5 | 36 14 6 |

| | |
|--------------------------------|---------|
| Subdivision of Section 1..... | Page 49 |
| Subdivision of Section 2..... | Page 49 |
| Subdivision of Section 3..... | Page 50 |
| Subdivision of Section 4..... | Page 51 |
| Subdivision of Section 9..... | Page 52 |
| Subdivision of Section 10..... | Page 53 |
| Subdivision of Section 11..... | Page 54 |
| Subdivision of Section 12..... | Page 55 |
| Subdivision of Section 13..... | Page 55 |

TOWNSHIP 43 SOUTH, RANGE 10 EAST

| | |
|--|---------|
| Subdivision of Section 14..... | Page 56 |
| Subdivision of Section 15..... | Page 57 |
| Subdivision of Section 16..... | Page 58 |
| Subdivision of Section 21..... | Page 58 |
| Subdivision of Section 22..... | Page 59 |
| Subdivision of Section 23..... | Page 60 |
| Subdivision of Section 24..... | Page 61 |
| Subdivision of Section 25..... | Page 61 |
| Subdivision of Section 26..... | Page 62 |
| Subdivision of Section 27..... | Page 63 |
| Subdivision of Section 28..... | Page 64 |
| Subdivision of Section 33..... | Page 65 |
| Subdivision of Section 34..... | Page 65 |
| Subdivision of Section 35..... | Page 66 |
| Subdivision of Section 36..... | Page 67 |
| Resurvey of Navajo Mountain School Tract in Sections 10 & 11 | Page 68 |
| Resurvey of Parcel No. 1 in Section 10 | Page 69 |
| Resurvey of Parcel No. 2 in Section 10 | Page 74 |

T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

The following field notes are those of the retracement of a portion of the Utah-Arizona state boundary (south boundary), the dependent resurvey of the east boundary, survey of portions of the north boundary and subdivisional lines, survey of the subdivision of certain sections, and the metes-and-bounds resurvey of a tract and parcels in sections 10 and 11 of Township 43 South, Range 10 East, Salt Lake Meridian, Utah.

History of Surveys

| Surveyed by | Retr. or Resurveyed by |
|---|-----------------------------|
| SOUTH BOUNDARY (UTAH-ARIZONA STATE BOUNDARY) | |
| All H.B. Carpenter Portion | 1900 C.F. Moore 1925 |
| EAST BOUNDARY | |
| All C.F. Moore & Eddie S.C. Smith | 1925-26 |
| WEST BOUNDARY | |
| All Unsurveyed | |
| SUBDIVISION | |
| All Unsurveyed | |
| PRIVATE SURVEY | |

Douglas E. Pehrson executed survey of a Tract and 2 parcels in sections 10 and 11 with plat dated 12/12/1996.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1006, Utah, dated June 14, 2006.

Preliminary to the resurvey, the lines of prior surveys were retraced and a diligent search was made for any evidence of the original corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The direction of lines refer to the true meridian and were determined by Global Positioning System (GPS) observations in real time kinematic relative positioning mode, using Trimble 4700 receivers.

All monuments set are Navajo Indian Reservation posts or brass tablets.

The geographic positions, in NAD83 (CORS96), epoch date 2002.00, for the corners below, were determined by GPS observations to a network accuracy of less than 0.20 meters, 95 percent confidence circle, as described in the Standards and Guidelines for Cadastral Survey Using Global Positioning System Methods, May 9, 2001, Version 1.0.

T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

The geographic position of National Geodetic Survey Control Station
"NUWAN" is as follows:

Latitude: 37°04 00.89874
NAD 1983 (1994)

N.Latitude: 110°47 06.13602 W.
Elevation: 5889 ft.

The cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.:

Latitude: 37° 01' 37.625" N. Longitude: 110° 44' 19.379" W.
Height above ellipsoid: 5657.3 ft., N.A.V.D. 1983 Elevation: 5728.9 ft.

RETRACEMENT OF A PORTION OF THE UTAH-ARIZONA STATE LINE,
(SOUTH BOUNDARY)

T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

RETRACEMENT OF A PORTION OF THE UTAH-ARIZONA STATE LINE
(SOUTH BOUNDARY)

T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

Restoring the survey executed by
H. B. Carpenter, in 1900

Beginning at the 179th mile cor. on the Utah-Arizona state line, monumented with a sandstone, 24 x 19 x 5 ins., lying face down, partially buried, mkd.: ARIZ on the downward face, UTAH on the upward face, 37NL on an adjacent face, and 179 M on the opposite face. No original bearing trees found.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.:

UT
— 179M —
AZ
2006

From which

A juniper, 20 ins. diam., bears S. 48° E., 52 1/2 lks. dist., mkd.: ARIZONA 179MP BT.

A juniper, 9 ins. diam., bears N. 51° W., 26 1/2 lks. dist., mkd.: UTAH 179MP BT.

Bury the original stone alongside the post.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle S. slope of rolling, sandy terrain in fairly dense piñon, juniper and sagebrush.

N. 89° 25.2' E., on the 180th mile.

12.637 Point for the closing cor. of secs. 32 and 33, hereinafter described.

52.639 Point for the 1/4 sec. cor. of secs. 33, only.

RETRACEMENT OF A PORTION OF THE UTAH-ARIZONA STATE LINE
(SOUTH BOUNDARY)

T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.:

T43S R10E
1/4 S33

2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on gently rolling terrain in sagebrush and small juniper.

79.952 Point for the 180th mile cor. on the Utah-Arizona state line, at proportionate dist.; there is no remaining evidence of the original cor. Not monumented.

N. 89° 25.2' E., on the 181st mile.

12.689 Point for the closing cor. of secs. 33 and 34, hereinafter described.

25.06 Intersect the center line of SJ CR434, a paved road, 22 ft. wide, bears N. 2° 38' E. and S. 2° 38' W.

52.691 Point for the 1/4 sec. cor. of sec. 34, only.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.:

T43S R10E
1/4 S34

2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle E. slope in scattered piñon, juniper and sagebrush.

79.951 The 181st mile cor. on the Utah-Arizona state line, monumented with a sandstone, 18 x 12 x 6 ins., firmly set, projecting 12 ins. above the ground, mkd.: UTAH on the N., ARIZ on the S., 181M on the W. and 37NL on the E., from which

A juniper, 11 ins. diam., bears N. 40° 37' E., 62 1/2 lks. dist., mkd.: UTAH 181M BT. (Record: N. 42° 42' E., 19 lks. dist.)

RETRACEMENT OF A PORTION OF THE UTAH-ARIZONA STATE LINE,
(SOUTH BOUNDARY)

T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

A juniper, 15 ins. diam., bears S. 32° 10' E., 17 1/2 lks. dist., mkd.: ARIZ 181M BT. (Record: S. 37° 20' E., 65 lks. dist.)

At the corner point.

Leave sandstone in place. Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in the top center of the sandstone, with top mkd.:

UT
— 181M —
AZ
2006

Set a steel fence post alongside.

N. 89° 23.7' E., on the 182nd mile.

12.742 Point for the closing cor. of secs. 34 and 35, hereinafter described.

52.744 Point for the 1/4 sec. cor. of sec. 35, only.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., on bedrock slope, in a mound of stone, 4 ft. base, to top, with brass cap mkd.:

T43S R10E
1/4 S35
2006

Deposit a magnet beneath the post.

Raise a mound of stone, 4 ft. base, 2 1/2 ft. high, to the W.

Cor. is located on a S. slope of a narrow, rocky valley, drains easterly into Jackrabbit canyon.

79.456 Point for the 182nd mile cor. on the Utah-Arizona state line, at proportionate dist.; there is no remaining evidence of the original cor. Not monumented.

N. 89° 23.7' E., on the 183rd mile.

13.290 Point for the closing cor. of secs. 35 and 36, hereinafter described.

53.292 Point for the 1/4 sec. cor. of sec. 36, only.

RETRACEMENT OF A PORTION OF THE UTAH-ARIZONA STATE LINE,
(SOUTH BOUNDARY)

T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in the top of a boulder, 7 x 4 x 4 ft., with top mkd.:

T43S R10E
1/4 S36

2006

Raise a mound of stone, 4 ft. base, 2 ft. high, to the W.

Cor. is located on a moderately steep, NW slope in scattered piñon and juniper.

79.457

The 183rd mile cor. on the Utah-Arizona state line, monumented with a sandstone boulder, 6 1/2 x 3 1/2 x 2 ft., mkd.: UTAH on the N., ARIZ on the S., 183M on the W., 37NL on the E. and an X on the top, with a mound of stone, 5 1/2 ft. base, 2 1/2 ft. high, to the E., from which

A juniper, 10 ins. diam., bears S. 0° 14' E., 19 lks. dist., mkd.: ARIZ 183M BT. (Record: South., 19 lks. dist.)

At the corner point

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in the X on top of the boulder, with top mkd.:

UT
—183M —
AZ
2006

Cor. is located on a moderate N. slope of a boulder strewn hill, below cliff to the S.

N. 89° 44.7' E., on the 184th mile.

13.836

The closing cor. of T. 43 S., Rs. 10 and 11 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd.: as described in the official record of the 1925-26 survey of the W. bdy. of T. 43 S., R. 11 E., from which

A juniper, 18 ins. diam., bears N. 20° E., 71 1/2 lks. dist., with partially legible marks S31 CC BT. (Record: N. 19° E., 68 lks. dist.)

RETRACEMENT OF A PORTION OF THE UTAH-ARIZONA STATE LINE
(SOUTH BOUNDARY)

T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

A piñon snag, 11 ins. diam., bears N. 8° W., 66 lks. dist.
(Record: N. 9° 15' W., 68 lks. dist.)

Remove "A" and "U" from the brass cap, and build a mound of stone around the iron post, 3 ft. base, to top.

Cor. is located on a gentle S. slope in scattered piñon and juniper.

79.985 The 184th mile cor. on the Utah-Arizona state line, monumented with a sandstone 14 x 6 ins., firmly set, projecting 28 ins. above the ground, mkd.: UTAH on the N., ARIZ on the S., 184M on the W. and 37NL on the E., with a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, to the E., from which

A juniper, 16 ins. diam., bears N. 45° E., 27 1/2 lks. dist., mkd.: UTAH 184M BT. (Record: N. 46° 30' E., 25 lks. dist.)

A juniper, 11 ins. diam., bears S. 28° E., 71 1/2 lks. dist., mkd.: ARIZ 184M BT. (Record: S. 28° 10' E., 68 lks. dist.)

A juniper, 12 ins. diam., bears S. 30° W., 69 1/2 lks. dist., mkd.: ARIZ 184M BT. (Record: S. 59° W., 70 lks. dist.)

A juniper, 10 ins. diam., bears N. 23° W., 51 lks. dist., mkd.: UTAH 184M BT. (Record: N. 20° 20' W. 51 lks. dist.)

At the corner point

Leave sandstone in place. Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in the top center of the sandstone, with top mkd.:

UT
— 184M —
AZ
2006

Cor. is located on a sandy, NE slope in sagebrush and scattered piñon and juniper.

DEPENDENT RESURVEY OF THE EAST BOUNDARY
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

Restoring the survey executed by
C.F. Moore and Eddie S.C. Smith, in 1925-26

From the cor. of Tps. 42 and 43 S., Rs. 10 and 11 E., determined at the center of a mound of stone, 2 ft. base, 2 ft. high, on bedrock. No iron post or X on bedrock found. From which the remaining original bearing tree

A piñon, 30 ins. diam., bears N. 46° 02' W., 99 lks. dist., with partially legible marks R10E S36 BT. (Record: N. 45° 45' W., 101 lks. dist.)

At the corner point

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in the sandstone bedrock, with top mkd.:

| | | |
|--------|--------|--------|
| | T 42 S | |
| R 10 E | | R 11 E |
| S 36 | | S 31 |
| | | |
| S 1 | | S 6 |
| | T 43 S | |
| | 2006 | |

Raise a mound of stone, to the E. and set a steel fence post in the mound of stone.

Cor. is located on a rocky bench above a valley, bears N. and S.

S. 0° 01.3' E., bet. secs. 1 and 6.

39.910 The 1/4 sec. cor. of secs. 1 and 6, reestablished from the original bearing trees by dist.-dist. intersection

A juniper 8 ins. diam., bears S. 58° 53' E., 65 lks. dist., mkd.: BT. (Record: S. 68° 30' E.)

A piñon, 9 ins. diam., bears N. 2° 37' W., 258 lks. dist., with partially healed blaze. (Record: N. 2° W.)

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.:

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

| | | | |
|--------|--|--------|--|
| T 43 S | | | |
| 1/4 | | | |
| R 10 E | | R 11 E | |
| S 1 | | S 6 | |
| 2006 | | | |

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on S. sandstone slope in scattered piñon and juniper.

S. 0° 06.7' E., beginning new measurement.

39.998 The cor. of secs. 1, 6, 7 and 12, reestablished from the two remaining original bearing trees by dist.-dist. intersection

A juniper, 30 ins. diam., bears N. 7° 02' E., 172 lks. dist., with illegible marks. (Record: N. 7° 45' E.)

A juniper, 36 ins. diam., bears S. 17° 40' E., 169 lks. dist., mkd.: BT. (Record: S. 18° 30' E.)

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

| | | | |
|--------|--|--------|--|
| T 43 S | | | |
| R 10 E | | R 11 E | |
| S 1 | | S 6 | |
| ----- | | | |
| S 12 | | S 7 | |
| 2006 | | | |

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on gentle, S., sandstone slope in scattered brush.

S. 0° 01.5' E., bet. secs. 7 and 12.

40.002 Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 2 ft. base, to top, with brass cap mkd.:

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T 43 S
1/4
R 10 E | R 11 E
S 12 | S 7
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle SW slope in sagebrush and juniper.

48.88 Intersect the center line of SJ CR434, an improved dirt road, 22 ft. wide, bears N. 82° E. and S. 82° W.

79.304 The witness cor. to the cor. of secs. 7, 12, 13 and 18, reestablished from the remaining original bearing tree

A juniper, 15 ins. diam., bears N. 67° E., 216 lks. dist., with partially legible marks R11E S7 C BT.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a mound of stone, 2 ft base, to top, with brass cap mkd.:

WC
T 43 S
R 10 E | R 11 E
S 12 | S 7
S 13 ↓ S 18
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located 67 ft. E. of a drainage, 20 ft. wide, 2 ft. deep, drains S. 55° E.

80.004 True point for the cor. of secs. 7, 12, 13 and 18. Point falls in a wash, drains SE, where it is impractical to establish a permanent monument.

S. 0° 01.5 E., bet. secs. 13 and 18.

4.42 Intersect the center line of SJ CR435, an improved dirt road, 15 ft. wide, bears N. 46° E. and S. 46° W.

40.023 The 1/4 sec. cor. of secs. 13 and 18, reestablished from the original bearing trees by dist.-dist. intersection

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

A juniper, 18 ins. diam., bears N. 75° 58' E., 178 lks.
dist., mkd.: 1/4 S18 BT. (Record: N. 75° 45' E.)

A juniper, 17 ins. diam., bears S. 51° 53' W., 38 lks.
dist., mkd.: 1/4 S13 BT. (Record: S. 52° 30' W.)

Point falls in an embedded mound of stone, 3 ft. base, 1 ft. high.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a mound of stone, 3 ft base, to top, with brass cap mkd.:

| | |
|--------|--------|
| T 43 S | |
| 1/4 | |
| R 10 E | R 11 E |
| S 13 | S 18 |
| 2006 | |

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on gentle, sandy, NW slope in brush and juniper.

S. 0° 02.9' E., beginning new measurement.

39.987

The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd.: as described in the official record of the 1925-26 survey of the W. bdy., T. 43 S., R. 11 E., from which

A juniper, 20 ins. diam., bears N. 49° 12' E., 23 lks.
dist., mkd.: BT. (Record: N. 50° 30' E., 20 lks. dist.)

A juniper, 36 ins. diam., bears S. 17° 07' E., 195 1/2 lks.
dist., mkd.: BT. (Record: S. 17° 15' E., 197 lks. dist.)

A piñon snag, 19 ins. diam., bears S. 74° 30' W., 129 1/2 lks. dist., mkd.: T43S R10E S24 BT. (Record: S. 74° 30' W., 130 lks. dist.)

A piñon, 18 ins. diam., bears N. 53° 39' W., 129 1/2 lks. dist., mkd.: T43S R10E S13 BT. (Record: N. 53° 45' W., 133 lks. dist.)

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on rocky terrain, sloping NW in scattered piñon and juniper.

S. 0° 03.1' E., bet. secs. 19 and 24.

39.787 The witness cor. to the 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above the ground, with brass cap mkd.: as described in the official record of the 1925-26 survey of the W. bdy., T. 43 S., R. 11 E., from which

A juniper, 15 ins. diam., bears N. 71° E., 100 lks. dist., mkd.: 1/4 S19 WC BT.

A juniper, 15 ins. diam., bears N. 84° W., 50 1/2 lks. dist., mkd.: 1/4 S24 WC BT. (Record: N. 83° 45' W., 50 lks. dist.)

Build a mound of stone around the iron post, 4 ft. base, 2 ft. high.

Cor. is located on the N. side of a drainage, drains N. 50° E.

S. 0° 01.8' E., beginning new measurement.

0.200 True point for the 1/4 sec. cor. of secs. 19 and 24, Point falls in a wash, drains NE, where it is impractical to establish a permanent monument.

40.147 The cor. of secs. 19, 24, 25 and 30, reestablished from the two remaining original bearing trees by dist.-dist. intersection

A piñon snag, 8 ins. diam., bears N. 67° 46' E., 121 lks. dist., mkd.: BT. (Record: N. 67° 30' E.)

A triple-trunked piñon, 7 ins. diam., bears S. 11° 32' E., 77 lks. dist., mkd.: BT. (Record: S. 54° 30' E.)

Point falls in an embedded mound of stone, 3 ft. base, 6 ins. high.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.:

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

| | |
|--------|--------|
| T 43 S | |
| R 10 E | R 11 E |
| S 24 | S 19 |
| S 25 | S 30 |
| 2006 | |

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on the N. side of primitive dirt road, 6 ft. wide, bears N. 60° E. and S. 60° W.

S. 0° 01.4' E., bet. secs. 25 and 30.

39.978 True point for the 1/4 sec. cor. of secs. 25 and 30. Point falls on the face of a ledge, where it is impractical to establish a permanent monument.

40.977 The witness cor. to the 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above the ground, with brass cap mkd.: as described in the official record of the 1925-26 survey of the W. bdy., T. 43 S., R. 11 E., from which the remaining original bearing tree

A juniper, 18 ins. diam., bears S. 38° 15' W., 72 lks. dist., mkd.: WC 1/4 S25 BT.

Build a mound of stone around the iron post, 4 ft. base, 18 ins. high.

Cor. is located on a level bench above Jackrabbit canyon, with cliffs above and below cor.

S. 0° 03.9' E., beginning new measurement.

39.002 The cor. of secs. 25, 30, 31 and 36, reestablished from two of the three remaining original bearing trees by dist.-dist. intersection

A juniper, 30 ins. diam., bears N. 68° 03' E., 55 lks. dist., mkd.: T43S R11E S30 BT. (Record: N. 73° 30' E.)

A multi-trunked juniper, 14 ins. diam., bears S. 43° 12' W., 88 lks. dist., mkd.: BT. (Record: S. 40° 30' W.)

From which the third original bearing tree

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

A juniper, 24 ins. diam., bears S. 33° 35' E., 223 1/2 lks. dist., mkd.: BT. (Record: S. 33° 30' E., 228 lks. dist.)

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

| | | | |
|--------|--|--------|--|
| T 43 S | | | |
| R 10 E | | R 11 E | |
| S 25 | | S 30 | |
| ----- | | | |
| S 36 | | S 31 | |
| 2006 | | | |

Deposit a magnet beneath the post.

Cor. is located on a gentle, sandy, N. slope in scattered piñon and juniper.

S. 0° 01.2' W., bet. secs. 31 and 36.

37.879 Point selected for the witness cor. to the 1/4 sec. cor. of secs. 31 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.:

| | | | |
|--------|--|--------|--|
| WC | | | |
| T 43 S | | | |
| 1/4 | | | |
| R 10 E | | R 11 E | |
| S 36 | | S 31 | |
| 2006 | | | |

Deposit a magnet beneath the post.

Cor. is located on the E., rocky bank of an arroyo in scattered piñon and juniper.

39.879 True point for the 1/4 sec. cor. of secs. 31 and 36, reestablished from the remaining original bearing tree

A juniper, 20 ins. diam., bears S. 31° 45' W., 67 lks. dist., mkd.: 1/4 S36 BT.

True point falls in an arroyo, where it is impractical to establish a permanent monument.

S. 0° 12.2' W., beginning new measurement.

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

12.526 The closing cor. of T. 43 S., Rs. 10 and 11 E., on the Utah-Arizona state line, hereinbefore described.

SURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

From the cor. of Tps. 42 and 43 S., Rs. 10 and 11 E., hereinbefore described.

West, bet. secs. 1 and 36.

40.000 Point for the 1/4 sec. cor. of secs. 1 and 36.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in sandstone outcrop, with top mkd.:

T 42 S R 10 E
S 36
1/4 _____
S 1
T 43 S
2006

Raise a mound of stone, 2 ft. base, 2 ft. high, to the W.

Cor. is located on fairly level, open terrain in brush.

80.000 Point for the cor. of secs. 1, 2, 35 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

T 42 S R 10 E
S 35 | S 36
S 2 | S 1
T 43 S

2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle W. slope, W. of the base of a vertical sandstone cliff, 175 ft. high, in scattered brush and boulders.

West, bet. secs. 2 and 35.

SURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.000 Point for the 1/4 sec. cor. of secs. 2 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.:

T 42 S R 10 E
S 35
1/4 ———
S 2
T 43 S
2006

From which

A juniper, 20 ins. diam., bears S. 35° 09' W., 81 1/2 lks. dist., mkd.: X BT.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on open, rolling hills, gently sloping NW, in brush and few trees.

80.000 Point for the cor. of secs. 2, 3, 34 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 7 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.:

T 42 S R 10 E
S 34 | S 35
S 3 | S 2
T 43 S
2006

Deposit a magnet beneath the post.

Set a steel fence post in a mound of stone alongside.

Cor. is located on open, rolling hills, sloping NE, in brush.

West, bet. secs. 3 and 34.

40.000 Point for the 1/4 sec. cor. of secs. 3 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.:

SURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T 42 S R 10 E
S 34
1/4 ———
S 3
T 43 S
2006

From which

A juniper, 28 ins. diam., bears S. 51° 55' W., 48 1/2 lks.
dist., mkd.: X BT.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle, rocky, NW slope above a drainage,
drains N. 30° E.

80.000 Point for the cor. of secs. 3, 4, 33 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13
ins. in the ground to bedrock, in a mound of stone, 4 ft. base,
to top, with brass cap mkd.:

T 42 S R 10 E
S 33 | S 34
S 4 | S 3
T 43 S
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on the E. edge of a very rocky mesa top in
brush.

West, bet. secs. 4 and 33.

12.82 Intersect the center line of an unimproved dirt road, 10 ft.
wide, bears N. 4° E. and S. 4° W.

19.06 Intersect the center line of an unimproved dirt road, 10 ft.
wide, bears N. 29° W. and S. 29° E.

40.000 Point for the 1/4 sec. cor. of secs. 4 and 33.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23
ins. in the ground, in a mound of stone, 4 ft. base, to top,
with brass cap mkd.:

SURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T 42 S R 10 E
S 33
1/4 ———
S 4
T 43 S
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located in sandy soil with boulders, above the W. bank of a narrow wash, flows N. 30° E.

80.000 Point for the cor. of secs. 4, 5, 32 and 33.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.:

T 42 S R 10 E
S 32 | S 33
S 5 | S 4
T 43 S
2006

Deposit a magnet beneath the post.

Cor. is located on a moderately steep, NW, rocky slope in scattered juniper.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

From the cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described.

S. 0° 02.5' E., bet. secs. 1 and 2.

40.000 Point for the 1/4 sec. cor. of secs. 1 and 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

T 43 S R 10 E
1/4
S 2 | S 1
2006

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located in a fairly level, sandy bench in a large valley surrounded by high cliffs.

80.000 Point for the cor. of secs. 1, 2, 11 and 12.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in sandstone outcrop, with top mkd.:

| | |
|--------|--------|
| T 43 S | R 10 E |
| S 2 | S 1 |
| S 11 | S 12 |
| 2006 | |

From which

A piñon, 10 ins. diam., bears S. 66° 29' W., 20 lks. dist.,
mkd.: X BT.

Cor. is located on a S. sloping, sandstone outcrop in piñon and juniper.

From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 56.1' W., bet. secs. 1 and 12.

40.026 Point for the 1/4 sec. cor. of secs. 1 and 12.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

| | |
|--------|--------|
| T 43 S | R 10 E |
| | S 1 |
| 1/4 | _____ |
| | S 12 |
| 2006 | |

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on gently rolling terrain in brush and scattered juniper.

80.052 The cor. of secs. 1, 2, 11 and 12.

S. 0° 02.5' E., bet. secs. 11 and 12.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.000 Point for the 1/4 sec. cor. of secs. 11 and 12.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

T 43 S R 10 E
1/4
S 11 | S 12
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle, sandy, E. slope in scattered brush and juniper.

50.920 Intersect the center line of SJ CR434, an improved dirt road, 20 ft. wide, bears N. 89° W. and S. 89° E.

80.000 Point for the cor. of secs. 11, 12, 13 and 14.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

T 43 S R 10 E
S 11 | S 12

S 14 | S 13
2006

From which

The SW fence cor. of a sewage treatment lagoon, bears N. 47° 10' W., 236 lks. dist.

The SE fence cor. of a sewage treatment lagoon, bears S. 84° 11' E., 229 1/2 lks. dist.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on open, level terrain, S. of a sewage lagoon.

From the true point for the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 56.2' W., bet. secs. 12 and 13.

40.022 Point for the 1/4 sec. cor. of secs. 12 and 13.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

T 43 S R 10 E
S 12
1/4 ———
S 13
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle, sandy, NE slope in brush.

80.044 The cor. of secs. 11, 12, 13 and 14.

S. 0° 02.5' E., bet. secs. 13 and 14.

30.130 Intersect the center line of SJ CR435, an improved dirt road, 15 ft. wide, bears N. 71° E. and S. 71° W.

40.000 Point for the 1/4 sec. cor. of secs. 13 and 14.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

T 43 S R 10 E
1/4
S 14 | S 13
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on rolling, sandy ridges in scattered piñon and juniper, and brush.

80.000 Point for the cor. of secs. 13, 14, 23 and 24.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 3 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
S 14 | S 13
———
S 23 | S 24
2006

Deposit a magnet beneath the post.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on the top of a fairly level mesa, above a valley, bears E. and W., on exposed bedrock in brush.

From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 56.6' W., bet. secs. 13 and 24.

40.026 Point for the 1/4 sec. cor. of secs. 13 and 24.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

T 43 S R 10 E
S 13
1/4 ———
S 24

2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor is located on top of a ridge, bears N. 10° E. and S. 10° W., in scattered brush.

80.052 The cor. of secs. 13, 14, 23 and 24.

S. 0° 02.5' E., bet. secs. 23 and 24.

40.000 Point for the 1/4 sec. cor. of secs. 23 and 24.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
1/4
S 23 | S 24
2006

Deposit a magnet beneath the post.

Cor. is located near the middle of a narrow canyon, 80 ft. deep, course N. 20° E., in scattered piñon and juniper.

80.000 Point for the cor. of secs. 23, 24, 25 and 26.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.:

| | |
|--------|--------|
| T 43 S | R 10 E |
| S 23 | S 24 |
| S 26 | S 25 |
| 2006 | |

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on the S. edge of a primitive dirt road, 6 ft. wide, bears N. 42° E. and S. 42° W., on sandy ground in scattered piñon and juniper, and brush.

From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 53.8' W., bet. secs. 24 and 25.

40.033 Point for the 1/4 sec. cor. of secs. 24 and 25.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.:

| | |
|--------|--------|
| T 43 S | R 10 E |
| | S 24 |
| 1/4 | _____ |
| | S 25 |
| 2006 | |

Deposit a magnet beneath the post.

Cor. is located on a gentle, SE sloping bench on sandstone outcrop in brush.

80.066 The cor. of secs. 23, 24, 25 and 26.

S. 0° 02.5' E., bet. secs. 25 and 26.

40.000 Point for the 1/4 sec. cor. of secs. 25 and 26.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T 43 S R 10 E
1/4
S 26 | S 25
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on rolling, sandy hills in piñon and juniper.

80.000 Point for the cor. of secs. 25, 26, 35 and 36. Point falls on inaccessible cliffs where it is impractical to establish a permanent monument.

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 52.9' W., bet. secs. 25 and 36.

40.043 Point for the 1/4 sec. cor. of secs. 25 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
S 25
1/4 ———
S 36
2006

Deposit a magnet beneath the post.

Cor. is located on the N. side of a shallow drainage, 3 ft. wide, drains S. 70° E., and on the W. side of Jackrabbit canyon, near the base of a 200 ft. high cliff to the W.

80.086 The point for the cor. of secs. 25, 26, 35 and 36.

S. 0° 02.5' E., bet. secs. 35 and 36.

1.000 Point selected for the witness cor. to the cor. of secs. 25, 26, 35 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., on bedrock and in a mound of stone, 3 ft. base, to top of, brass cap mkd.:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

| | | |
|--------|----|--------|
| | WC | |
| T 43 S | ↑ | R 10 E |
| S 26 | | S 25 |
| <hr/> | | |
| S 35 | | S 36 |
| 2006 | | |

Deposit a magnet beneath the post.

Witness cor. is located on a bench, 20 ft. wide, with steep cliffs above and below.

40.000 Point for the 1/4 sec. cor. of secs. 35 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., bet. several large boulders, in a mound of stone, 2 ft. base, to top, with brass cap mkd.:

| | | |
|--------|-----|--------|
| T 43 S | | R 10 E |
| | 1/4 | |
| S 35 | | S 36 |
| 2006 | | |

Deposit a magnet beneath the post.

Cor. is located on the W. side of Jackrabbit canyon, at the base of a vertical cliff, approximately 200 ft. high, in huge sandstone boulders.

53.001 Intersect the Utah-Arizona state line.

Point for the closing cor. of secs. 35 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

| | | |
|--------|----|--------|
| | CC | |
| T 43 S | | R 10 E |
| S 35 | | S 36 |
| <hr/> | | |
| 2006 | | |

Deposit a magnet beneath the post.

Cor. is located on fairly level, sandy terrain, in an open valley of Jackrabbit canyon, with high cliffs surrounding canyon and scattered brush.

From the cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., hereinbefore described.

S. 0° 03.1' E., bet. secs. 2 and 3.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.000 Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in the sandstone bedrock, with top mkd.:

T 43 S R 10 E
1/4
S 3 | S 2
2006

Deposit a magnet at the base of the brass tablet.

Set a steel fence post in a mound of stone, to the S.

Cor. is located on a gentle, rocky, N. sloping hill in scattered juniper.

40.960 Intersect the center line of an unimproved dirt road, 10 ft. wide, bears N. 87° E. and S. 87° W.

42.390 Intersect the center line of an unimproved dirt road, 10 ft. wide, bears N. 39° W. and S. 39° E.

80.000 Point for the cor. of secs. 2, 3, 10 and 11.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.:

T 43 S R 10 E
S 3 | S 2
S 10 | S 11
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle, sandy, N. slope in piñon, juniper and sagebrush.

From the cor. of secs. 1, 2, 11 and 12.

West, bet. secs. 2 and 11.

40.000 Point for the 1/4 sec. cor. of secs. 2 and 11.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T 43 S R 10 E
S 2
1/4 ———
S 11
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on fairly level, sandy terrain in sagebrush, cactus and scattered piñon and juniper.

57.500 Intersect the center line of an improved dirt road, 15 ft. wide, bears N. 56° E. and S. 56° W.

80.000 The cor. of secs. 2, 3, 10 and 11.

S. 0° 03.1' E., bet. secs. 10 and 11.

37.450 Intersect the center line of improved dirt road, 15 ft. wide, bears N. 56° E. and S. 56° W.

40.000 Point for the 1/4 sec. cor. of secs. 10 and 11.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.:

T 43 S R 10 E
1/4
S 10 | S 11
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on level terrain, in W. shoulder of a dirt driveway, 8 ft. wide, bears N. and S.

43.910 Intersect the center line of SJ CR434, a paved road, 18 ft. wide, bears N. 85° W. and S. 85° E.

44.680 Intersect the exterior boundary of the Navajo Mountain School tract, a 6 ft. high chain link fence, extends N. 86° 09.5' W. and S. 86° 09.5' E.

63.430 Intersect the exterior boundary of the Navajo Mountain School tract, a 4 ft. high, 2 strand barbed wire fence, extends N. 10° 10.4' E. and S. 10° 10.1' W.

80.000 Point for the cor. of secs. 10, 11, 14 and 15.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

| | |
|--------|--------|
| T 43 S | R 10 E |
| S 10 | S 11 |
| S 15 | S 14 |
| 2006 | |

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle SE slope, E. of a large juniper tree.

From the cor. of secs. 11, 12, 13 and 14.

West, bet. secs. 11 and 14.

40.000 Point for the 1/4 sec. cor. of secs. 11 and 14.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

| | |
|--------|---------------------|
| T 43 S | R 10 E |
| | S 11 |
| | 1/4 <u> </u> |
| | S 14 |
| 2006 | |

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle E. slope in brush and scattered juniper.

47.670 Intersect the center line of SJ CR434, a paved road, 22 ft. wide, bears N. 14° E. and S. 14° W.

80.000 The cor. of secs. 10, 11, 14 and 15.

S. 0° 03.1' E., bet. secs. 14 and 15.

40.000 Point for the 1/4 sec. cor. of secs. 14 and 15.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground to bedrock, in a mound of stone, 2 ft. base, to top, with brass cap mkd.:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T 43 S R 10 E
1/4
S 15 | S 14
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a S. sloping hill in scattered piñon and juniper.

54.170 Intersect the center line of SJ CR434, a paved road, 22 ft. wide, bears N. 21° E. and S. 21° W.

80.000 Point for the cor. of secs. 14, 15, 22 and 23.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.:

T 43 S R 10 E
S 15 | S 14
S 22 | S 23
2006

From which

A juniper, 30 ins. diam., bears N. 21° E., 15 lks. dist., mkd.: X BT.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on fairly level terrain in scattered piñon and juniper.

From the cor. of secs. 13, 14, 23 and 24.

West, bet. secs. 14 and 23.

40.000 Point for the 1/4 sec. cor. of secs. 14 and 23.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, with brass cap mkd.:

T 43 S R 10 E
S 14
1/4 ———
S 23
2006

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located in a rock crack, N. of large boulder, 6 ft. high, and on the SE side of a rocky, narrow drainage, drains S. 30° W., approximately 15 ft. above bottom.

58.210 Intersect the center line of SJ CR435, an improved dirt road, 15 ft. wide, bears N. 40° E. and S. 40° W.

80.000 The cor. of secs. 14, 15, 22 and 23.

S. 0° 03.1' E., bet. secs. 22 and 23.

26.020 Intersect the center line of SJ CR435, an improved dirt road, 15 ft. wide, bears N. 36° E. and S. 36° W.

40.000 Point for the 1/4 sec. cor. of secs. 22 and 23.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
1/4
S 22 | S 23
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a rocky, N. slope, below mesa top.

80.000 Point for the cor. of secs. 22, 23, 26 and 27.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in the sandstone outcrop, with top mkd.:

T 43 S R 10 E
S 22 | S 23
S 27 | S 26
2006

Raise a mound of stone, 3 ft. base, 2 ft. high, to the NW

Cor. is located on a gentle NW slope of sandstone outcrop in scattered piñon and juniper.

From the cor. of secs. 23, 24, 25 and 26.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

West, bet. secs. 23 and 26.

40.000 Point for the 1/4 sec. cor. of secs. 23 and 26.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
S 23
1/4 ———
S 26
2006

Deposit a magnet beneath the post.

Cor. is located on the S. shoulder of a primitive dirt road, 10 ft. wide, bears E. and W.

80.000 The cor. of secs. 22, 23, 26 and 27.

S. 0° 03.1' E., bet. secs. 26 and 27.

40.000 Point for the 1/4 sec. cor. of secs. 26 and 27.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
1/4
S 27 | S 26
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle N. slope on sandy bedrock in scattered piñon and juniper.

68.920 Intersect the center line of SJ CR4101, an improved dirt road, 15 ft. wide, bears N. 59° W. and S. 59° E.

80.000 Point for the cor. of secs. 26, 27, 34 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

| | |
|--------|--------|
| T 43 S | R 10 E |
| S 27 | S 26 |
| S 34 | S 35 |
| 2006 | |

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located 62 lks. W. of SJ CR4101, an improved dirt road, 15 ft. wide, bears N. 20° E. and S. 20° W.

From the true point for the cor. of secs. 25, 26, 35 and 36.

West, bet. secs. 26 and 35.

40.000 Point for the 1/4 sec. cor. of secs. 26 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

| | |
|--------|---------|
| T 43 S | R 10 E |
| | S 26 |
| | 1/4 ——— |
| | S 35 |
| 2006 | |

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on fairly level terrain in sagebrush and juniper.

79.260 Intersect the center line of SJ CR4101, an improved dirt road, 15 ft. wide, bears N. 20° E. and S. 20° W.

80.000 The cor. of secs. 26, 27, 34 and 35.

S. 0° 03.1' E., bet. secs. 34 and 35.

2.480 Intersect the center line of SJ CR4101, an improved dirt road, 15 ft. wide, bears N. 31° E. and S. 31° W.

40.000 Point for the 1/4 sec. cor. of secs. 34 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T 43 S R 10 E
1/4
S 34 | S 35
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on level terrain in sagebrush and scattered juniper.

53.847 Intersect the Utah-Arizona State line.

Point for the closing cor. of secs. 34 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground to bedrock, in a mound of stone, 2 ft. base, to top, with brass cap mkd.:

CC
T 43 S R 10 E
S 34 | S 35
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on fairly level terrain, in dead piñon, juniper and sagebrush.

From the cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.

S. 0° 03.8' E., bet. secs. 3 and 4.

10.680 Intersect the center line of an unimproved dirt road, 10 ft. wide, bears N. 86° E. and S. 86° W.

40.000 Point for the 1/4 sec. cor. of secs. 3 and 4.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 7 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.:

1/4
T 43 S R 10 E
S 4 | S 3
2006

From which

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

A juniper, 36 ins. diam., bears S. 33° E., 8 lks. dist.,
mkd.: X BT.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

80.000 Point for the cor. of secs. 3, 4, 9 and 10.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.:

| | | | | | |
|---|------|---|---|----|----|
| T | 43 | S | R | 10 | E |
| | S | 4 | | S | 3 |
| | S | 9 | | S | 10 |
| | 2006 | | | | |

Deposit a magnet beneath the post.

Cor. is located on a steep NW ridge, above a drainage, drains N. 60° E.

From the cor. of secs. 2, 3, 10 and 11.

West, bet. secs. 3 and 10.

40.000 Point for the 1/4 sec. cor. of secs. 3 and 10.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.:

| | | | | | |
|---|------|---|----|----|---|
| T | 43 | S | R | 10 | E |
| | | S | | 3 | |
| | 1/4 | | | | |
| | | S | 10 | | |
| | 2006 | | | | |

Deposit a magnet beneath the post.

Cor. is located at the base of sandstone cliffs, in a drainage, drains W., in dense piñon and juniper.

80.000 The cor. of secs. 3, 4, 9 and 10.

S. 0° 03.8' E., bet. secs. 9 and 10.

40.000 Point for the 1/4 sec. cor. of secs. 9 and 10.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
1/4
S 9 | S 10
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located a NE slope of rocky, rolling terrain.

80.000 Point for the cor. of secs. 9, 10, 15 and 16.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

T 43 S R 10 E
S 9 | S 10
S 16 | S 15
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle E. slope of a sandy hill in scattered piñon and juniper.

From the cor. of secs. 10, 11, 14 and 15.

West, bet. secs. 10 and 15.

40.000 Point for the 1/4 sec. cor. of secs. 10 and 15.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
S 10
1/4 ———
S 15
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on fairly level terrain in scattered piñon and juniper.

76.540 Intersect the center line of an improved dirt road, 12 ft. wide, bears N. 6° E. and S. 6° W.

80.000 The cor. of secs. 9, 10, 15 and 16.

S. 0° 03.8' E., bet. secs. 15 and 16.

11.910 Intersect the center line of an improved dirt road, 12 ft. wide, bears N. 30° E. and S. 30° W.

40.000 Point for the 1/4 sec. cor. of secs. 15 and 16.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
1/4
S 16 | S 15
2006

Deposit a 60d nail beneath the post.

Set a steel fence post alongside.

Cor. is located on a moderately steep, rocky, N. slope, high above a drainage, drains E. and W.

80.000 Point for the cor. of secs. 15, 16, 21 and 22.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

T 43 S R 10 E
S 16 | S 15
S 21 | S 22
2006

From which

A piñon, 16 ins. diam., bears N. 12° E., 52 lks. dist., mkd.: X BT.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle, sandy, E. slope in cactus and scattered piñon and juniper.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the cor. of secs. 14, 15, 22 and 23.

West, bet. secs. 15 and 22.

- 3.760 Intersect the center line of SJ CR434, a paved road, 22 ft. wide, bears N. 7° E. and S. 7° W.
- 40.000 True point for the 1/4 sec. cor. of secs. 15 and 22. Point falls on a NE cliff face, where it is impractical to establish a permanent monument.
- 42.015 Point selected for the witness cor. to the 1/4 sec. cor. of secs. 15 and 22.
- Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in the sandstone bedrock, with top mkd.:

WC
T 43 S R 10 E
S 15
1/4 →
S 22
2006

From which

A piñon, 9 ins. diam., bears N. 38° 17' E., 45 lks. dist., mkd.: X BT.

Deposit a magnet beneath the brass tablet.

Cor. is located on a sandstone outcrop in scattered brush and piñon.

- 80.000 The cor. of secs. 15, 16, 21 and 22.

S. 0° 03.8' E., bet. secs. 21 and 22.

- 40.000 Point for the 1/4 sec. cor. of secs. 21 and 22.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
1/4
S 21 | S 22
2006

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From which

A juniper, 22 ins. diam., bears S. 62° E., 47 1/2 lks.
dist., mkd.: X BT.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor is located on a sandy, NW slope on the S. side of a
drainage, drains N. 70° E.

80.000 Point for the cor. of secs. 21, 22, 27 and 28.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10
ins. in the ground to bedrock, in a mound of stone, 4 ft. base,
to top, with brass cap mkd.:

| | |
|--------|--------|
| T 43 S | R 10 E |
| S 21 | S 22 |
| S 28 | S 27 |
| 2006 | |

From which

A juniper, 18 ins. diam., bears N. 45° 07' E., 22 1/2 lks.
dist., mkd.: X BT.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a rocky, NW slope above a drainage, drains N.
60° E.

From the cor. of secs. 22, 23, 26 and 27.

West, bet. secs. 22 and 27.

27.840 Intersect the center line of SJ CR434, a paved road, 22 ft.
wide, bears N. 26° E. and S. 26° W.

40.000 Point for the 1/4 sec. cor. of secs. 22 and 27.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16
ins. in the ground, in a mound of stone, 3 ft. base, to top,
with brass cap mkd.:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T 43 S R 10 E
S 22
1/4 ———
S 27
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle S. slope in scattered brush.

80.000 The cor. of secs. 21, 22, 27 and 28.

S. 0° 03.8' E., bet. secs. 27 and 28.

40.000 Point for the 1/4 sec. cor. of secs. 27 and 28.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
1/4
S 28 | S 27
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a rocky, gentle, S. sloping hill in scattered piñon, juniper and sagebrush.

47.420 Intersect the center line of SJ CR488, a paved road, 20 ft. wide, bears N. 82° E. and S. 82° W.

72.830 Intersect the center of an unimproved dirt road, 10 ft. wide, bears N. 87° W. and S. 87° E.

80.000 Point for the cor. of secs. 27, 28, 33 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.:

T 43 S R 10 E
S 28 | S 27
S 33 | S 34
2006

Deposit a magnet beneath the post.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside.

Cor. is located on gently rolling hills in scattered juniper and sagebrush.

From the cor. of secs. 26, 27, 34 and 35.

West, bet. secs. 27 and 34.

40.000 Point for the sec. cor. of secs. 27 and 34.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in the sandstone bedrock, with top mkd.:

T 43 S R 10 E
S 27
1/4 ———
S 34
2006

Set a steel fence post in a mound of stone, 3 ft. base, 2 ft. high, to the SW.

Cor. is located on level terrain in sagebrush.

56.760 Intersect the center line of SJ CR4101, an improved dirt road, 15 ft. wide, bears N. 46° W. and S. 46° E.

58.760 Intersect the center line of SJ CR4241, an improved dirt road, 18 ft. wide, bears N. and S.

68.880 Intersect the center line of SJ CR434, a paved road, 22 ft. wide, bears N. 15° W. and S. 15° E.

80.000 The cor. of secs. 27, 28, 33 and 34.

S. 0° 03.8' E., bet. secs. 33 and 34.

26.070 Intersect a landing strip, improved dirt, 40 ft. wide, bears N. 48° E. and S. 48° W.

40.000 Point for the 1/4 sec. cor. of secs. 33 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

T 43 S R 10 E
1/4
S 33 | S 34
2006

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle E. slope in sagebrush and scattered juniper.

54.661 Intersect the Utah-Arizona state line.

Point for the closing cor. of secs. 33 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.:

CC
T 43 S R 10 E
S 33 | S 34
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle E. slope in sagebrush and scattered juniper.

From the cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described.

S. 0° 04.4' E., bet. secs. 4 and 5.

40.000 Point for the 1/4 sec. cor. of secs. 4 and 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
1/4
S 5 | S 4
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle, rocky, SE slope in an area recently burned.

80.000 Point for the cor. of secs. 4, 5, 8 and 9.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in the sandstone bedrock, with top mkd.:

| | | | | | |
|---|------|---|---|----|---|
| T | 43 | S | R | 10 | E |
| | S | 5 | | S | 4 |
| | S | 8 | | S | 9 |
| | 2006 | | | | |

Cor. is located on a sandstone bench above on a very steep sandstone slope.

From the cor. of secs. 3, 4, 9 and 10.

West, bet. secs. 4 and 9.

40.000 Point for the 1/4 sec. cor. of secs. 4 and 9.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top, with brass cap mkd.:

| | | | | | |
|---|------|-----|---|----|---|
| T | 43 | S | R | 10 | E |
| | | S | | 4 | |
| | | 1/4 | — | | |
| | | S | | 9 | |
| | 2006 | | | | |

From which

A piñon, 6 ins. diam., bears N. 31° E., 10 1/2 lks. dist., mkd.: X BT.

A juniper, 16 ins. diam., bears S. 26° W., 16 lks. dist., mkd.: X BT.

Deposit a magnet beneath the post.

Cor. is located on a bench of a very steep N. slope on the N. side of Navajo Begay mountain.

80.000 The cor. of secs. 4, 5, 8 and 9.

S. 0° 04.4' E., bet. secs. 8 and 9.

40.000 Point for the 1/4 sec. cor. of secs. 8 and 9.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., on bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T 43 S R 10 E
1/4
S 8 | S 9
2006

Deposit a magnet beneath the post.

Cor. is located on a steep S. slope of Navajo Begay mountain, on the E. edge of a narrow ravine, 3 ft. wide, drains S. 40° W.

80.000 Point for the cor. of secs. 8, 9, 16 and 17.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
S 8 | S 9
S 17 | S 16
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a moderate, rocky, SW slope in scattered juniper and brush.

From the cor. of secs. 9, 10, 15 and 16.

West, bet. secs. 9 and 16.

40.000 True point for the 1/4 sec. cor. of secs. 9 and 16. Point falls on a S. cliff face, where it is impractical to establish a permanent monument.

42.000 Point selected for the witness cor. to the 1/4 sec. cor. of secs. 9 and 16.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in the sandstone bedrock, with top mkd.:

WC
T 43 S R 10 E
S 9
1/4 →
S 16
2006

Cor. is located on a S. sandstone slope above a sandstone bench.

80.000 The cor. of secs. 8, 9, 16 and 17.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 0° 04.4' E., bet. secs. 16 and 17.

15.440 Intersect the center line of an improved dirt road, 12 ft. wide, bears N. 89° E. and S. 89° W.

40.000 True point for the 1/4 sec. cor. of secs. 16 and 17. Point falls in the center of a narrow drainage, drains S. 40° E., where it is impractical to establish a permanent monument.

41.000 Point selected for the witness cor. to the 1/4 sec. cor. of secs. 16 and 17.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.:

WC
T 43 S R 10 E
1/4
S 17 ↑ S 16
2006

From which

A juniper, 11 ins. diam., bears S. 30° E., 10 1/2 lks. dist., mkd.: X BT.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a rocky, SE sloping ridge in dense junipers.

80.000 Point for the cor. of secs. 16, 17, 20 and 21.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
S 17 | S 16
S 20 | S 21
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on the E. side of a rocky ravine, drains S. 70° W., in scattered piñon and juniper.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the cor. of secs. 15, 16, 21 and 22.

West, bet. secs. 16 and 21.

40.000 Point for the 1/4 sec. cor. of secs. 16 and 21.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
S 16
1/4 ———
S 21
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a sandy, N. slope in scattered juniper and dead piñon, and cactus and brush.

80.000 The cor. of secs. 16, 17, 20 and 21.

S. 0° 04.4' E., bet. secs. 20 and 21.

40.000 Point for the 1/4 sec. cor. of secs. 20 and 21.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
1/4
S 20 | S 21
2006

From which

A juniper, 12 ins. diam., bears S. 42° E., 16 1/2 lks. dist., mkd.: X BT.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle, rocky, NE slope in dense piñon and juniper.

80.000 Point for the cor. of secs. 20, 21, 28 and 29.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 3 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.:

| | |
|--------|--------|
| T 43 S | R 10 E |
| S 20 | S 21 |
| S 29 | S 28 |
| 2006 | |

From which

A juniper, 10 ins. diam., bears S. 48.5° W., 35 lks. dist., mkd.: X BT.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle, rocky, SE slope in dense juniper.

From the cor. of secs. 21, 22, 27 and 28.

West, bet. secs. 21 and 28.

40.000

Point for the 1/4 sec. cor. of secs. 21 and 28.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

| | |
|--------|--------|
| T 43 S | R 10 E |
| | S 21 |
| | 1/4 |
| | S 28 |
| 2006 | |

From which

A juniper, 10 ins. diam., bears S. 4° W., 30 lks. dist., mkd.: X BT.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on fairly level, sandy terrain, in scattered piñon and juniper.

80.000

The cor. of secs. 20, 21, 28 and 29.

S. 0° 04.4' E., bet. secs. 28 and 29.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.000 Point for the 1/4 sec. cor. of secs. 28 and 29.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
1/4
S 29 | S 28
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle, boulder covered, NE slope in scattered scraggly juniper.

80.000 Point for the cor. of secs. 28, 29, 32 and 33.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

T 43 S R 10 E
S 29 | S 28
S 32 | S 33
2006

From which

A juniper, 16 ins. diam., bears N. 33.5° E., 36 lks. dist., mkd.: X BT.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located at the N. base of a ridge, bears E. and W., gently sloping E. in scattered piñon and juniper.

From the cor. of secs. 27, 28, 33 and 34.

West, bet. secs. 28 and 33.

40.000 Point for the 1/4 sec. cor. of secs. 28 and 33.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T 43 S R 10 E
S 28
1/4 ———
S 33
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle E. slope in scattered piñon, juniper and brush.

53.230 Intersect an unimproved dirt road, 10 ft. wide, bears N. 54° E. and S. 54° W.

80.000 The cor. of secs. 28, 29, 32 and 33.

S. 0° 04.4' E., bet. secs. 32 and 33.

13.770 Intersect an unimproved dirt road, 10 ft. wide, bears N. 55° E. and S. 55° W.

40.000 Point for the 1/4 sec. cor. of secs. 32 and 33.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

T 43 S R 10 E
1/4
S 32 | S 33
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on gently rolling, sandy, S. sloping hills in scattered piñon and juniper.

55.471 Intersect the Utah-Arizona state line.

Point for the closing cor. of secs. 32 and 33.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.:

CC
T 43 S R 10 E
S 32 | S 33
2006

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit a magnet beneath the post.

Cor. is located near a small cluster of houses and a livestock pen.

SUBDIVISION OF SECTION 1,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

From the 1/4 sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp., hereinbefore described.

S. 0° 03.3' E., on the N. and S. center line of sec. 1.

39.955 Point for the center 1/4 sec. cor. of sec. 1, at intersection with the E. and W. center line.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in the sandstone bedrock, with top mkd.:

T 43 S R 10 E
C 1/4 S 1
2006

Deposit a magnet beneath the brass tablet.

Set a steel fence post in a mound of stone, 2 ft. base, 2 ft. high, to the E.

Cor. is located 48 1/2 lks. S. of a narrow drainage, 10 ft. wide, drains N. 50° E., on a NW sandstone outcrop.

79.954 The 1/4 sec. cor. of secs. 1 and 12.

From the 1/4 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 56.1' W., on the E. and W. center line of sec. 1.

39.982 The center 1/4 sec. cor. of sec. 1.

79.995 The 1/4 sec. cor. of secs. 1 and 2.

SUBDIVISION OF SECTION 2,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

From the 1/4 sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., hereinbefore described.

SUBDIVISION OF SECTION 2,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- S. $0^{\circ} 02.8'$ E., on the N. and S. center line of sec. 2.
- 31.000 Intersect the center line of an unimproved dirt road, 10 ft. wide, bears N. 81° W. and S. 81° E.
- 40.000 Point for the center $1/4$ sec. cor. of sec. 2, at intersection with the E. and W. center line.
- Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 5 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.:
- T 43 S R 10 E
C $1/4$ S 2
2006
- Deposit a magnet beneath the post.
- Set a steel fence post alongside.
- Cor. is located on a gentle, N., sandstone slope in brush.
- 80.000 The $1/4$ sec. cor. of secs. 2 and 11.
-
- From the $1/4$ sec. cor. of secs. 1 and 2.
- West, on the E. and W. center line of sec. 2.
- 40.000 The center $1/4$ sec. cor. of sec. 2.
- 70.91 Intersect the center line of an unimproved dirt road, 10 ft. wide, bears N. 52° E. and S. 52° W.
- 80.000 The $1/4$ sec. cor. of secs. 2 and 3.

SUBDIVISION OF SECTION 3,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

-
- From the $1/4$ sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp., hereinbefore described.
- S. $0^{\circ} 03.5'$ E., on the N. and S. center line of sec. 3.
- 15.390 Intersect the center line of an unimproved dirt road, 10 ft. wide, bears N. 64° W. and S. 64° E.
- 40.000 Point for the center $1/4$ sec. cor. of sec. 3, at intersection with the E. and W. center line.

SUBDIVISION OF SECTION 3,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
C 1/4 S 3
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on the E. side of a shallow drainage, drains N. 30° E. in brush and scattered juniper.

80.000 The 1/4 sec. cor. of secs. 3 and 10.

From the 1/4 sec. cor. of secs. 2 and 3.

West, on the E. and W. center line of sec. 3.

10.540 Intersect the center line of an unimproved dirt road, 10 ft. wide, bears N. 60° W. and S. 60° E.

12.570 Intersect the center line of an unimproved dirt road, 10 ft. wide, bears N. 73° E. and S. 73° W.

19.290 Intersect the center line of an unimproved dirt road, 10 ft. wide, bears N. 70° W. and S. 70° E.

40.000 The center 1/4 sec. cor. of sec. 3.

80.000 The 1/4 sec. cor. of secs. 3 and 4.

SUBDIVISION OF SECTION 4,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

From the 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp., hereinbefore described.

S. 0° 04.1' E., on the N. and S. center line of sec. 4.

40.000 Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.:

SUBDIVISION OF SECTION 4,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T 43 S R 10 E
C 1/4 S 4
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located above a drainage, drains N., and under large juniper and piñon trees.

80.000 The 1/4 sec. cor. of secs. 4 and 9.

From the 1/4 sec. cor. of secs. 3 and 4.

West, on the E. and W. center line of sec. 4.

40.000 The center 1/4 sec. cor. of sec. 4.

80.000 The 1/4 sec. cor. of secs. 4 and 5.

SUBDIVISION OF SECTION 9,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

From the 1/4 sec. cor. of secs. 4 and 9.

S. 0° 04.1' E., on the N. and S. center line of sec. 9.

40.000 Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E. and W. center line.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in the sandstone bedrock, with top mkd.:

T 43 S R 10 E
C 1/4 S 9
2006

From which

A juniper, 9 ins. diam., bears S. 78° 31' W., 32 lks. dist., mkd.: X BT.

Cor. is located on the steep, E. face of Navajo Begay mountain, in unstable rock.

80.000 The true point for the 1/4 sec. cor. of secs. 9 and 16.

SUBDIVISION OF SECTION 9,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 sec. cor. of secs. 9 and 10.
West, on the E. and W. center line of sec. 9.

40.000 The center 1/4 sec. cor. of sec. 9.
80.000 The 1/4 sec. cor. of secs. 8 and 9.

SUBDIVISION OF SECTION 10,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

From the 1/4 sec. cor. of secs. 3 and 10.
S. 0° 03.5' E., on the N. and S. center line of sec. 10.

40.000 Point for the center 1/4 sec. cor. of sec. 10, at intersection
with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26
ins. in the ground, with brass cap mkd.:

T 43 S R 10 E
C 1/4 S 10
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle, sandy, S. slope in sagebrush and
scattered piñon and juniper.

44.300 Intersect the center line of an improved dirt road, 12 ft. wide,
bears N. 69° E. and S. 69° W.

80.000 The 1/4 sec. cor. of secs. 10 and 15.

From the 1/4 sec. cor. of secs. 10 and 11.
West, on the E. and W. center line of sec. 10.

2.040 Intersect the center line of an improved dirt road, 15 ft. wide,
bears N. 14° E. and S. 14° W.

40.000 The center 1/4 sec. cor. of sec. 10.

80.000 The 1/4 sec. cor. of secs. 9 and 10.

SUBDIVISION OF SECTION 11,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

SUBDIVISION OF SECTION 11,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

From the 1/4 sec. cor. of secs. 2 and 11.
S. $0^{\circ} 02.8'$ E., on the N. and S. center line of sec. 11.

34.150 Intersect the center line of an improved dirt road, 15 ft. wide,
bears N. 9° W. and S. 9° E.

40.000 Point for the center 1/4 sec. cor. of sec. 11, at intersection
with the E. and W. center line.

Set a stainless steel post, 28 ins. long, $2 \frac{1}{2}$ ins. diam., 27
ins. in the ground, with brass cap mkd.:

T 43 S R 10 E
C 1/4 S 11
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on an E. slope, on the W. side of a dirt road,
in scattered juniper.

47.270 Intersect the center line of SJ CR434, a paved road, 20 ft.
wide, bears N. 79° W. and S. 79° E.

49.790 Intersect the center line of SJ CR434, a paved road, 20 ft.
wide, bears N. 13° E. and S. 13° W.

80.000 The 1/4 sec. cor. of secs. 11 and 14.

From the 1/4 sec. cor. of secs. 11 and 12.

West, on the E. and W. center line of sec. 11.

39.410 Intersect the center line of an unimproved dirt road, 15 ft.
wide, bears N. 2° W. and S. 2° E.

40.000 The center 1/4 sec. cor. of sec. 11.

80.0 The 1/4 sec. cor. of secs. 10 and 11.

SUBDIVISION OF SECTION 12,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

SUBDIVISION OF SECTION 12,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

From the 1/4 sec. cor. of secs. 1 and 12.

S. 0° 02.0' E., on the N. and S. center line of sec. 12.

40.001 Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
C 1/4 S 12
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on the E. edge of a mesa top, 100 ft. above valley.

53.680 Intersect the center line of SJ CR434, and improved dirt road, 20 ft. wide, bears N. 84° W. and S. 84° E.

80.002 The 1/4 sec. cor. of secs. 12 and 13.

From the 1/4 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 56.1' W., on the E. and W. center line of sec. 12.

40.024 The center 1/4 sec. cor. of sec. 12.

80.048 The 1/4 sec. cor. of secs. 11 and 12.

SUBDIVISION OF SECTION 13,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

From the 1/4 sec. cor. of secs. 12 and 13.

S. 0° 02.3' E., on the N. and S. center line of sec. 13.

SUBDIVISION OF SECTION 13,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- 19.050 Intersect the center line of SJ CR435, an improved dirt road, 15 ft. wide, bears N. 78° E. and S. 78° W.
- 40.012 Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E. and W. center line.
- Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

T 43 S R 10 E
C 1/4 S 13
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor is located on a gentle E. slope in open terrain.

- 80.005 The 1/4 sec. cor. of secs. 13 and 24.

From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 57.2' W., on the E. and W. center line of sec. 13.

- 40.016 The center 1/4 sec. cor. of sec. 13.

- 80.040 The 1/4 sec. cor. of secs. 13 and 14.

SUBDIVISION OF SECTION 14,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

From the 1/4 sec. cor. of secs. 11 and 14.

S. 0° 02.8' E., on the N. and S. center line of sec. 14.

- 40.000 Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. center line.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in the sandstone bedrock, with top mkd.:

T 43 S R 10 E
C 1/4 S 14
2006

Raise a mound of stone, 2 ft. base, 2 ft. high, to the E.

SUBDIVISION OF SECTION 14,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on the NW slope of a hill in sagebrush and scattered piñon and juniper.

57.000 Intersect the center line of SJ CR435, an improved dirt road, 15 ft. wide, bears N. 43° E. and S. 43° W.

80.00 The 1/4 sec. cor. of secs. 14 and 23.

From the 1/4 sec. cor. of secs. 13 and 14.

West, on the E. and W. center line of sec. 14.

20.490 Intersect the center line of SJ CR435, an improved road, 15 ft. wide, bears N. 49° E. and S. 49° W.

40.000 The center 1/4 sec. cor. of sec. 14.

70.650 Intersect the center line of SJ CR434, a paved road, 22 ft. wide, bears N. 37° E. and S. 37° W.

80.000 The 1/4 sec. cor. of secs. 14 and 15.

SUBDIVISION OF SECTION 15,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

From the 1/4 sec. cor. of secs. 10 and 15.

S. 0° 03.5' E., on the N. and S. center line of sec. 15.

40.000 Point for the center 1/4 sec. cor. of sec. 15, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.:

T 43 S R 10 E
C 1/4 S 15
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle NW slope in scattered piñon and juniper.

80.000 The true point for the 1/4 sec. cor. of secs. 15 and 22.

From the 1/4 sec. cor. of secs. 14 and 15.

SUBDIVISION OF SECTION 15,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

West, on the E. and W. center line of sec. 15.

- 40.000 The center 1/4 sec. cor. of sec. 15.
80.000 The 1/4 sec. cor. of secs. 15 and 16.

SUBDIVISION OF SECTION 16,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

From the true point for the 1/4 sec. cor. of secs. 9 and 16.

S. 0° 04.1' E., on the N. and S. center line of sec. 16.

- 16.540 Intersect the center line of an improved dirt road, 12 ft. wide,
bears E. and W.
40.000 Point for the center 1/4 sec. cor. of sec. 16, at intersection
with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26
ins. in the ground, with brass cap mkd.:

T 43 S R 10 E
C 1/4 S 16
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on top of a ridge, bears E. and W., in scattered
juniper.

- 80.000 The 1/4 sec. cor. of secs. 16 and 21.

From the 1/4 sec. cor. of secs. 15 and 16.

West, on the E. and W. center line of sec. 16.

- 40.000 The center 1/4 sec. cor. of sec. 16.
80.000 True point for the 1/4 sec. cor. of secs. 16 and 17.

SUBDIVISION OF SECTION 21,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

From the 1/4 sec. cor. of secs. 16 and 21.

SUBDIVISION OF SECTION 21,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 0° 04.1' E., on the N. and S. center line of sec. 21.

40.000 Point for the center 1/4 sec. cor. of sec. 21, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
C 1/4 S 21
2006

Deposit a magnet beneath the post.

Set a steel fence post in a mound of stone, 3 ft. base, 2 ft. high, to the NE.

Cor. is located on a rocky NE hillside in a shallow wash, drains N. 55° E.

80.000 The 1/4 sec. cor. of secs. 21 and 28.

From the 1/4 sec. cor. of secs. 21 and 22.

West, on the E. and W. center line of sec. 21.

40.000 The center 1/4 sec. cor. of sec. 21.

80.000 The 1/4 sec. cor. of secs. 20 and 21.

SUBDIVISION OF SECTION 22,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

From the true point for the 1/4 sec. cor. of secs. 15 and 22.

S. 0° 03.5' E., on the N. and S. center line of sec. 22.

40.000 Point for the center 1/4 sec. cor. of sec. 22, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
C 1/4 S 22
2006

SUBDIVISION OF SECTION 22,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle, rocky, N. hillside in scattered juniper and dead piñon.

80.000 The 1/4 sec. cor. of secs. 22 and 27.

From the 1/4 sec. cor. of secs. 22 and 23.

West, on the E. and W. center line of sec. 22.

10.120 Intersect the center line of SJ CR435, an improved dirt road, 15 ft. wide, bears N. 43° E. and S. 43° W.

11.040 Intersect the center line of SJ CR434, a paved road, 22 ft. wide, bears N. 18° E. and S. 18° W.

40.000 The center 1/4 sec. cor. of sec. 22.

80.0 The 1/4 sec. cor. of secs. 21 and 22.

SUBDIVISION OF SECTION 23,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

From the 1/4 sec. cor. of secs. 14 and 23.

S. 0° 02.8' E., on the N. and S. center line of sec. 23.

40.000 Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
C 1/4 S 23
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle, NW bedrock slope in scattered piñon, juniper and sagebrush.

80.000 The 1/4 sec. cor. of secs. 23 and 26.

SUBDIVISION OF SECTION 23,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 sec. cor. of secs. 23 and 24.

West, on the E. and W. center line of sec. 23.

40.000 The center 1/4 sec. cor. of sec. 23.

80.000 The 1/4 sec. cor. of secs. 22 and 23.

SUBDIVISION OF SECTION 24,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

From the cor. of secs. 13 and 24.

S. 0° 02.5' E., on the N. and S. center line of sec. 24.

39.993 Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
C 1/4 S 24
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on top of a rocky spur, bears N. 40° E. and S. 40° W.

79.966 The 1/4 sec. cor. of secs. 24 and 25.

From the true point for the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 56.1' W., on the E. and W. center line of sec. 24.

40.037 The center 1/4 sec. cor. of sec. 24.

80.067 The 1/4 sec. cor. of secs. 23 and 24.

SUBDIVISION OF SECTION 25,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

SUBDIVISION OF SECTION 25,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 sec. cor. of secs. 24 and 25.

S. 0° 02.6' E., on the N. and S. center line of sec. 25.

39.989 Point for the center 1/4 sec. cor. of sec. 25, at intersection with the E. and W. center line.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in the sandstone bedrock, with top mkd.:

T 43 S R 10 E
C 1/4 S 25
2006

Set a steel fence post in a mound of stone, 2 ft. base, 2 ft. high, to the W.

Cor. is located on a rocky, moderate, NW slope in scattered piñon and juniper.

79.990 The 1/4 sec. cor. of secs. 25 and 36.

From the true point for the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 52.8' W., on the E. and W. center line of sec. 25.

40.024 The center 1/4 sec. cor. of sec. 25.

80.062 The 1/4 sec. cor. of secs. 25 and 26.

SUBDIVISION OF SECTION 26,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

From the 1/4 sec. cor. of secs. 23 and 26.

S. 0° 02.8' E., on the N. and S. center line of sec. 26.

40.000 Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
C 1/4 S 26
2006

SUBDIVISION OF SECTION 26,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on fairly level terrain in shallow, sandy soil overlying bedrock.

80.000 The 1/4 sec. cor. of secs. 26 and 35.

From the 1/4 sec. cor. of secs. 25 and 26.

West, on the E. and W. center line of sec. 26.

40.000 The center 1/4 sec. cor. of sec. 26.

80.000 The 1/4 sec. cor. of secs. 26 and 27.

SUBDIVISION OF SECTION 27,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

From the 1/4 sec. cor. of secs. 22 and 27.

S. 0° 03.5' E., on the N. and S. center line of sec. 27.

10.200 Intersect the center line of SJ CR434, a paved road, 22 ft. wide, bears N. 52° E. and S. 52° W.

40.000 Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.:

T 43 S R 10 E
C 1/4 S 27
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located 23 lks. S. of an arroyo, drains N. 65° E.

69.470 Intersect the center line of SJ CR4101, an improved dirt road, 15 ft. wide, bears N. 87° E. and S. 87° W.

80.000 The 1/4 sec. cor. of secs. 27 and 34.

SUBDIVISION OF SECTION 27,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- From the 1/4 sec. cor. of secs. 26 and 27.
- West, on the E. and W. center line of sec. 27.
- 40.000 The center 1/4 sec. cor. of sec. 27.
- 73.000 Intersect the center line of SJ CR434, a paved road, 22 ft. wide, on a curve.
- 80.000 The 1/4 sec. cor. of secs. 27 and 28.

SUBDIVISION OF SECTION 28,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

- From the 1/4 sec. cor. of secs. 21 and 28.
- S. 0° 04.1' E., on the N. and S. center line of sec. 28.
- 40.000 Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E. and W. center line.
- Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.:
- T 43 S R 10 E
C 1/4 S 28
2006
- Deposit a magnet beneath the post.
- Set a steel fence post alongside.
- Cor. is located on the E. bank of a rocky drainage, 15 ft. wide, drains S. 20° W.
- 75.670 Intersect the center line of an unimproved dirt road, 10 ft. wide, bears N. 82° E. and S. 82° W.
- 80.000 The 1/4 sec. cor. of secs. 28 and 33.

- From the 1/4 sec. cor. of secs. 27 and 28.
- West, on the E. and W. center line of sec. 28.
- 40.000 The center 1/4 sec. cor. of sec. 28.
- 80.000 The 1/4 sec. cor. of secs. 28 and 29.

SUBDIVISION OF SECTION 28,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

SUBDIVISION OF SECTION 33,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

From the 1/4 sec. cor of secs. 28 and 33.

S. 0° 04.1' E., on the N. and S. center line of sec. 33.

40.000 Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E. and W. center line.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in the sandstone bedrock, 12 ins. below ground level, with top mkd.:

T 43 S R 10 E
C 1/4 S 33
2006

Deposit a magnet beneath the brass tablet.

Cor. is located in livestock area near a house, and was buried at landowner request.

55.066 The 1/4 sec. cor. of sec. 33, only, on the Utah-Arizona state line, hereinbefore described.

From the 1/4 sec. cor. of secs. 33 and 34.

West, on the E. and W. center line of sec. 33.

15.470 Intersect a landing strip, improved dirt, 40 ft. wide, bears N. 48° E. and S. 48° W.

40.000 The center 1/4 sec. cor. of sec. 33.

80.000 The 1/4 sec. cor. of secs. 32 and 33.

SUBDIVISION OF SECTION 34,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

From the 1/4 sec. cor. of secs. 27 and 34.

S. 0° 03.5' E., on the N. and S. center line of sec. 34.

10.010 Intersect SJ CR4101, an improved dirt road, 15 ft. wide, bears N. 73° W. and S. 73° E.

SUBDIVISION OF SECTION 34,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.000 Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.:

T 43 S R 10 E
C 1/4 S 34
2006

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on fairly level, sandy terrain in sagebrush and scattered piñon and juniper.

54.257 Intersect the 1/4 sec. cor. of sec. 34, only, on the Utah-Arizona state line, hereinbefore described.

From the 1/4 sec. cor. of secs. 34 and 35.

West, on the E. and W. center line of sec. 34.

40.000 The center 1/4 sec. cor. of sec. 34.

64.680 Intersect SJ CR4241, an improved dirt road, 18 ft. wide, bears N. 11° E. and S. 11° W.

66.690 Intersect SJ CR434, a paved road, 22 ft. wide, bears N. 2° E. and S. 2° W.

80.000 The 1/4 sec. cor. of secs. 33 and 34.

SUBDIVISION OF SECTION 35,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

From the 1/4 sec. cor. of secs. 26 and 35.

S. 0° 02.8' E., on the N. and S. center line of sec. 35.

40.000 Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E. and W. center line.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in the sandstone bedrock, with top mkd.:

T 43 S R 10 E
C 1/4 S 35
2006

SUBDIVISION OF SECTION 36,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit a magnet beneath the brass tablet.

Set a steel fence post in a mound of stone, 4 ft. base, 2 ft. high, to the E.

Cor. is located on the SW slope of a mesa in brush and scattered piñon and juniper.

53.424 The 1/4 sec. cor. of sec. 35, only, on the Utah-Arizona state line, hereinbefore described.

From the 1/4 sec. cor. of secs. 35 and 36.

West, on the E. and W. center line of sec. 35.

40.000 The center 1/4 sec. cor. of secs. 35.

80.000 The 1/4 sec. cor. of secs. 34 and 35.

SUBDIVISION OF SECTION 36,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

From the 1/4 sec. cor. of secs. 25 and 36.

S. 0° 00.6' W., on the N. and S. center line of sec. 36.

39.940 Point for the center 1/4 sec. cor. of sec. 36, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

T 43 S R 10 E
C 1/4 S 36
2006

From which

A juniper, 24 ins. diam., bears S. 17° W., 15 lks. dist.,
mkd.: X BT.

Deposit a magnet beneath the post.

Cor. is located on rolling, sandy hills, near center of Jackrabbit canyon.

52.661 The 1/4 sec. cor. of sec. 36, only, on the Utah-Arizona state line, hereinbefore described.

SUBDIVISION OF SECTION 36,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the true point for the 1/4 sec. cor of secs. 31 and 36, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 47.7' W., on the E. and W. center line of sec. 36.

40.041 The center 1/4 sec. cor. of sec. 36.

80.51 The 1/4 sec. cor. of secs. 35 and 36.

RESURVEY OF A TRACT AND 2 PARCELS IN SECTIONS 10 AND 11,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

Navajo Mountain School Tract

Restoring the survey executed by
Douglas E. Pehrson, PLS155675, on December 12, 1996

FEET

Beginning at the U.S. Coast & Geodetic Triangulation Station "NUWAN", monumented with a brass cap, 3 ins. diam., set flush on a sandstone outcrop, mkd.: USGS Tri Station NUWAN 1953.

S. 17° 14.5' E., to the Point of Beginning (Angle Point No. 1) of the Navajo Mountain School Tract.

2747.2 The Point of Beginning (Angle Point No. 1) of the Navajo Mountain School Tract, a 3 in. diam. galvanized post, set in concrete, at the cor. of 2 strand, barbed wire fences, 4 ft. high., extending northeasterly and southerly.

Thence, N. 29° 14.9' E., on line 1-2.

1275.4 Angle Point No. 2, identical with Angle Point No. 6 of Parcel No. 1, a 3 in. diam. galvanized post, 5 1/2 ft. high, set in concrete, at the cor. of 2 strand, barbed wire fence, 4 ft. high, extending southwesterly, and a 6 ft. high chain link fence, extending easterly.

Thence, S. 86° 09.5' E., on line 2-3.

65.9 Angle Point No. 7 of Parcel No. 1, hereinafter described.

1515.1 Intersect the line bet. secs. 10 and 11.

1736.1 Angle Point No. 3, a 3 in. diam. galvanized post, 6 1/2 ft. high, set in concrete, at the cor. of a chain link fence, extending westerly, and 2 strand, barbed wire fence, 4 ft. high, extending southerly.

RESURVEY OF A TRACT AND 2 PARCELS IN SECTIONS 10 AND 11,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

FEET

From which

A rebar, 5/8 in. diam., of unknown origin, firmly set,
projecting 3 ins. above the ground, bears N. 51° 08' W.,
2.6 ft. dist.

Thence, S. 10° 10.1' W., on line 3-4.

1242.6 Intersect the line bet. secs. 10 and 11.

2018.7 Angle Point No. 4, a 3 in. diam. galvanized post, 6 ft. high,
set in concrete, at the cor. of 2 strand, barbed wire fences, 4
ft. high., extending northerly and westerly.

Thence, S. 88° 43.0' W., on line 4-5.

1202.3 Angle Point No. 11 of Parcel No. 1, hereinafter described.

1692.2 Angle Point No. 12 of Parcel No. 1, hereinafter described.

1949.4 Angle Point No. 5, a 3 in. diam. galvanized post, 7 ft. high,
set in concrete, at the cor. of 2 strand, barbed wire fences, 4
ft. high., extending easterly and northerly.

Thence, N. 3° 02.2' E., on line 5-1.

948.1 The Point of Beginning (Angle Point No. 1) of the Navajo
Mountain School Tract.

Parcel No. 1

Restoring the survey executed by
Douglas E. Pehrson, PLS155675, on December 12, 1996

Beginning at Angle Point No. 1 of Parcel No. 1, monumented with
a galvanized pipe, 3/4 ins. diam., firmly set in concrete,
projecting 10 ins. above the ground, and a rebar, 5/8 ins.
diam., set inside the galvanized pipe, with an orange, plastic
cap mkd.: UTAH LS 155675.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27
ins. in the ground, with brass cap mkd.: AP1 PARCEL 1 2006, and
angle lines.

Deposit the pipe and rebar alongside the post.

Deposit a magnet beneath the post.

RESURVEY OF A TRACT AND 2 PARCELS IN SECTIONS 10 AND 11,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

FEET

Set a steel fence post alongside.

Cor. is located in scattered juniper, NW of Navajo Mountain High School.

From this point, U.S. Coast & Geodetic Triangulation Station "NUWAN", bears N. 26° 07.5' W., 2593.0 ft. dist.

Thence, S. 86° 47.9' E., on line 1-2.

335.2

Angle Point No. 2 of Parcel No. 1, monumented with a galvanized pipe, 3/4 ins. diam., 30 ins. long, firmly set in concrete, projecting 6 ins. above the ground, and a rebar, 5/8 ins. diam., set inside the galvanized pipe, with an orange, plastic cap mkd.: UTAH LS 155675.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.: AP2 PARCEL 1 2006, and angle lines.

Deposit the pipe and rebar alongside the post.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located SE of a water tank, and N. of a propane tank.

Thence, N. 4° 09.7' E., on line 2-3.

182.1

Angle Point No. 3 of Parcel No. 1, monumented with a rebar, 5/8 ins. diam., firmly set, projecting 4 ins. above the ground, with an orange, plastic cap mkd.: UTAH LS 155675.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.: AP3 PARCEL 1 2006, and angle lines.

Deposit the rebar inside the post.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle E. slope, NE of a water tank.

RESURVEY OF A TRACT AND 2 PARCELS IN SECTIONS 10 AND 11,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

FEET

Thence, S. 86° 29.0' E., on line 3-4.

- 38.5 Angle Point No. 4 of Parcel No. 1, monumented with a rebar, 5/8 ins. diam., firmly set, 1 in. below the ground, with an orange, plastic cap, marks illegible.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.: AP4 PARCEL 1 2006, and angle lines.

Deposit the rebar alongside the post.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on a gentle E. slope, NE of a water tank.

Thence, N. 16° 13.8' W., on line 4-5.

- 386.1 Angle Point No. 5 of Parcel No. 1, monumented with a rebar, 5/8 ins. diam., firmly set, projecting 3 ins. above the ground, with an orange, plastic cap mkd.: UTAH LS 155675.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.: AP5 PARCEL 1 2006, and angle lines.

Deposit the rebar inside the post.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on the W. bank of gravel road, 22 ft. wide.

Thence, N. 3° 27.0' E., on line 5-6.

- 286.4 Angle Point No. 6 of Parcel No. 1, identical with Angle Point No. 2 of the Navajo Mountain School Tract, hereinbefore described.

Thence, S. 86° 09.5' E., on line 6-7.

- 65.9 Angle Point No. 7 of Parcel No. 1, on line 2-3 of the Navajo Mountain School Tract, monumented with a rebar, 5/8 ins. diam.,

RESURVEY OF A TRACT AND 2 PARCELS IN SECTIONS 10 AND 11,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

FEET

firmly set, projecting 2 ins. above the ground, with an orange, plastic cap mkd.: UTAH LS 155675.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.: AP7 PARCEL 1 2006, and angle lines.

Deposit the rebar inside the post.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located in a chain link fence, extending easterly. and westerly.

Thence, S. 3° 27.0' W., on line 7-8

274.5

Point for Angle Point No. 8 of Parcel No. 1, determined at a position parallel to line 5-6; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.: AP8 PARCEL 1 2006, and angle lines.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on the E. bank of gavel road, 22 ft. wide.

Thence, S. 16° 13.8' E., on line 8-9.

398.3

Point for Angle Point No. 9 of Parcel No. 1, at proportionate position on the line bet. angle points no. 3 and 10; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.: AP9 PARCEL 1 2006, and angle lines.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located N. of Navajo Mountain high school and SW of the Naatsisáán community school.

RESURVEY OF A TRACT AND 2 PARCELS IN SECTIONS 10 AND 11,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

FEET

Thence, S. 86° 29.0' E., on line 9-10.

270.1 Angle Point No. 10 of Parcel No. 1, monumented with a galvanized pipe, 3/4 ins. diam., bent over, 2 ins. below the ground, and a rebar, 5/8 ins. diam., set inside the galvanized pipe.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.: AP10 PARCEL 1 2006, and angle lines.

Deposit the pipe and rebar alongside the post.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on an E. dirt hill, S. of the Naatsisáán community school.

Thence, S. 10° 23.1' W., on line 10-11.

1422.2 Angle Point No. 11 of Parcel No. 1, on line 4-5 of the Navajo Mountain School Tract, monumented with a galvanized pipe, 3/4 ins. diam., firmly set in concrete, projecting 8 ins. above the ground, and a rebar, 5/8 ins. diam., set inside the galvanized pipe, with an orange, plastic cap mkd.: UTAH LS 155675.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.: AP11 PARCEL 1 2006, and angle lines.

Deposit the pipe and rebar alongside the post.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located in a fence line.

Thence, N. 88° 43.0' W., on line 11-12.

489.9 Angle Point No. 12 of Parcel No. 1, monumented with a galvanized pipe, 3/4 ins. diam., firmly set, projecting 4 ins. above the ground, and a rebar, 5/8 ins. diam., set inside the galvanized pipe, with an orange, plastic cap mkd.: UTAH LS 155675.

RESURVEY OF A TRACT AND 2 PARCELS IN SECTIONS 10 AND 11,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

FEET

At the corner point

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in the concrete base of the fence anchor brace, with top mkd.: AP12 PARCEL 1 2006, and angle lines.

Deposit the pipe and rebar alongside the post.

Set a steel fence post alongside.

Cor. is located in a fence line.

Thence, N. 0° 55.5' E., on line 12-1.

1248.4 Angle Point No. 1 of Parcel No. 1, the point of beginning.

Parcel No. 2

Restoring the survey executed by
Douglas E. Pehrson, PLS155675, on December 12, 1996

Beginning at Angle Point No. 1 of Parcel No. 2, monumented with a rebar, 5/8 ins. diam., firmly set flush with the ground, with an orange, plastic cap mkd.: UTAH LS 155675.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.: AP1 PARCEL 2 2006, and angle lines.

Deposit the rebar alongside the post.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on the E. edge of a concrete roadway, 23 1/2 ft. wide, bears N. 18° E. and S. 26° W.

From this point, U.S. Coast & Geodetic Triangulation Station "NUWAN", bears N. 49° 36.8' W., 2934.8 ft. dist.

Thence, S. 80° 14.6' E., on line 1-2.

398.9 Angle Point No. 2 of Parcel No. 2, monumented with a galvanized pipe, 3/4 ins. diam., firmly set in concrete, 2 ins. below the ground, and a rebar, 5/8 ins. diam., set inside the galvanized pipe, with an orange, plastic cap mkd.: UTAH LS 155675.

At the corner point

RESURVEY OF A TRACT AND 2 PARCELS IN SECTIONS 10 AND 11,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

FEET

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.: AP2 PARCEL 2 2006, and angle lines.

Deposit the pipe and rebar alongside the post.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on an E. dirt slope in sagebrush.

Thence, S. 5° 37.8' W., on line 2-3.

307.4 Angle Point No. 3 of Parcel No. 2, monumented with a galvanized pipe, 3/4 ins. diam., firmly set in concrete, bent over, and a rebar, 5/8 ins. diam., set inside the galvanized pipe, with an orange, plastic cap mkd.: UTAH LS 155675.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.: AP3 PARCEL 2 2006, and angle lines.

From which

The SE cor. of a cement block building, 9 x 7 ft., 8 ft. high, bears N. 72° 01' W., 20.2 ft. dist.

Deposit the pipe and rebar alongside the post.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Thence, N. 85° 47.1' W., on line 3-4.

249.8 Point for Angle Point No. 4 of Parcel No. 2, determined by Grant Boundary Adjustment; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam, 28 ins. in the ground, with brass cap mkd.: AP4 PARCEL 2 2006, and angle lines.

From which

The SW cor. of a house, bears N. 51° E., 10.9 ft. dist.

RESURVEY OF A TRACT AND 2 PARCELS IN SECTIONS 10 AND 11,
T. 43 S., R. 10 E., SALT LAKE MERIDIAN, UTAH

FEET

Deposit a magnet beneath the post.

Thence, N. 4° 11.5' E., on line 4-5.

249.8 Point for Angle Point No. 5 of Parcel No. 2, determined by Grant Boundary Adjustment; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam, 28 ins. in the ground, with brass cap mkd.: AP5 PARCEL 2 2006, and angle lines.

From which

The NW cor. of a house bears N. 37° E, 11.5 ft. dist.

Deposit a magnet beneath the post.

Thence, N. 85° 48.3' W., on line 5-6.

159.5 Angle Point No. 6 of Parcel No. 2, monumented with a rebar, 5/8 ins. diam., firmly set, bent over, no cap.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.: AP6 PARCEL 2 2006, and angle lines.

Deposit the rebar alongside the post.

Deposit a magnet beneath the post.

Set a steel fence post alongside.

Cor. is located on the E. edge of a concrete roadway, 25 1/2 ft. wide, bears N. and S., and 2 ft. W. of a chain link fence, bears N. and S.

Thence, N. 16° 00.5' E., on line 6-1.

98.2 Angle Point No. 1 of Parcel No. 2, the point of beginning.

CERTIFICATE OF SURVEY

I, **Scott A. Burkhardt, Cadastral Surveyor**, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the **14th day of June, 2006**, I have **retraced a portion of the Utah-Arizona state boundary (south boundary)**, **dependently resurveyed the east boundary**, **surveyed portions of the north boundary and subdivisional lines**, **surveyed the subdivision of certain sections**, and **resurveyed a tract and 2 parcels in sections 10 and 11, T. 43 S., R. 10 E.**, of the **Salt Lake Meridian**, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

12/10/2007

(Date)

Scott A. Burkhardt

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the **retracement of a portion of the Utah-Arizona state boundary (south boundary)**, **the dependent resurvey of the east boundary**, **the survey of portions of the north boundary and subdivisional lines**, **the survey of the subdivision of certain sections**, and **the resurvey of a tract and 2 parcels in sections 10 and 11, T. 43 S., R. 10 E., Salt Lake Meridian**, in the State of **Utah**, executed by **Scott A. Burkhardt, Cadastral Surveyor**, having been critically examined and found correct, are hereby approved.

December 14, 2007

(Date)

Daniel W. Webb

(Chief Cadastral Surveyor of Utah)