

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF
A PORTION OF THE NORTH BOUNDARY
(EIGHTH STANDARD PARALLEL SOUTH),
A PORTION OF THE SUBDIVISIONAL LINES,
AND
THE SUBDIVISION OF SECTIONS 3 AND 14,
IN
TOWNSHIP 41 SOUTH RANGE 5 WEST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Larry V. Judd
Cadastral Surveyor

Under special instructions dated **August 31, 2005**, approved **August 31, 2005**, which provided for the surveys included under Group Number **1010**, and assignment instructions dated **August 31, 2005**.

Survey commenced **March 27, 2006**
Survey completed **April 26, 2006**

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE NORTH BOUNDARY
(EIGHTH STANDARD PARALLEL SOUTH),

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 3 AND 14,

IN

TOWNSHIP 41 SOUTH RANGE 5 WEST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Larry V. Judd
Cadastral Surveyor

Under special instructions dated **August 31, 2005**, approved **August 31, 2005**, which provided for the surveys included under Group Number **1010**, and assignment instructions dated **August 31, 2005**.

Survey commenced **March 27, 2006**
Survey completed **April 26, 2006**

INDEX DIAGRAM

Township 41 South, Range 5 West

			3	3	
6	5	4	15 3 14	11 2	1
7	8	9	13 10 13	10 11 9	12
18	17	16	12 15	8 14 7	5 13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

The subdivision of section 3..... Page 16
 The subdivision of section 14..... Page 19

T. 41 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of a portion of the north boundary, (Eighth Standard Parallel South), a portion of the subdivisional lines, and the subdivision of sections 3 and 14 in T. 41 S., R. 5 W., Salt Lake Meridian, Utah.

History of Surveys

	Surveyed by	Retr. or Resurveyed by
SOUTH BOUNDARY		
All	J.C. Clark, et al. 1915-16	
Portion		G.E. Reynolds 1984
EAST BOUNDARY		
Portion	Bailey & Burrill 1876	
Portion	J.C. Clark, et al. 1915-16	J.C. Clark, et al. 1915-16
WEST BOUNDARY (Panguitch and Kanab Guide Meridian)		
All	Bailey & Burrill 1876	
Portion		J.C. Clark, et al. 1915-16
Portion		Cannon & Owens 1959
NORTH BOUNDARY (Eighth Standard Parallel South)		
All	Bailey & Burrill 1876	
Portion		A.J. Stewart Jr. 1883
Portion		Nelson & Stumm 1911
Portion		M.R. Workman 1974
SUBDIVISION		
Portion	Bailey & Burrill 1876	
Portion	J.C. Clark, et al. 1915-16	J.C. Clark, et al. 1915-16
PRIVATE SURVEYS		

A survey was executed in 1984 by Lanny Talbot of Talbot Land Surveyors in section 3.

T. 41 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

This survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1010, dated August 31, 2005.

The direction of the lines was determined by references to true meridians, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards and Guidelines for Cadastral Surveys Using GPS Methods*, dated May 9, 2001, Version 1.0. Trimble model 5700 GPS receivers were used for field collection. Cadastral Measurement Management (CMM) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and their calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from National Geodetic Survey Control Station "SKUM", with published data as follows:

Latitude: 37°17'58.63773" N. Longitude: 112°26'45.28838" W.
NAD 1983 (1994), N.A.V.D. 1988, Elevation 7145(feet).

The geographic position for the corner of sections 13 and 14 only, T. 41 S., R. 5 W., as determined by a tie made to National Geodetic Survey Control Station "SKUM" is as follows:

Latitude: 37°14'21.528" N. Longitude: 112°22'34.738" W.
NAD 1983, Network Accuracy = 0.200 meters at 95% confidence.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
 (EIGHTH STANDARD PARALLEL SOUTH),
 T. 40 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the South Boundary
 (Eighth Standard Parallel South),
 T. 40 S., R. 5 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by J.G. Burrill in
 1876, and the Resurvey Executed by M.R. Workman in 1974.

Beginning at the standard 1/4 section corner of section 35 only, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with the brass cap marked as described in the official record of the resurvey executed by M.R. Workman in 1974, and witnessed with a mound of stone to the north.

Corner falls on a gradual east slope in sandy ground, 20 ft. west of a dirt trail road, 8 ft. wide, bears northwest and southeast.

S. 89°50.6' W., along the south boundary of section 35.

30.773 True point for the closing corner of sections 2 and 3, Township 41 South, Range 5 West, hereinafter described.

39.786 The standard corner of sections 34 and 35 only, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 8 inches above ground, with the brass cap marked as described in the official record of the resurvey executed by M.R. Workman in 1974, and witnessed with a mound of stone to the north.

Corner falls on flat ground in a small cove between lava flows.

S. 89°27.3' W., along the south boundary of section 34.

10.786 Point for the E 1/16 section corner of section 3 only, Township 41 South, Range 5 West, not monumented.

30.585 Point for the 1/4 section corner of section 3 only, Township 41 South, Range 5 West, at midpoint in longitude between the closing corners on either side of the section, and on the Eighth Standard Parallel South.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

T41SR5W
 1/4 S3
 2006

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
 (EIGHTH STANDARD PARALLEL SOUTH),
 T. 40 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raise a mound of stone, 3 ft. by 3 ft. base by 1 ft. high, south of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground underneath large junipers on west edge of a lava flow.

- 39.379** The standard 1/4 section corner of section 34 only, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 8 inches above ground in a small mound of stone, with the brass cap marked as described in the official record of the resurvey executed by M.R. Workman in 1974.

from which

A juniper 10 ins. diam., scribed 1/4 S34, bears N. 50° E., 24 links distance.

Corner falls on flat sandy ground in large juniper growth.

S. 89° 36.6' W., beginning new measurement.

- 11.005** Point of the W 1/16 section corner of section 3 only, Township 41 South, Range 5 West, not monumented.

- 30.804** Point for the closing corner of sections 3 and 4 only, Township 41 South, Range 5 West, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

T40S	
C	C
S4	S3
T41SR5W	
2006	

Corner falls on a gradual northeast slope in large mature juniper growth.

- 39.619** The standard corner of sections 33 and 34 only, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 8 inches above ground, with the brass cap marked as described in the official record of the resurvey executed by M.R. Workman in 1974.

from which

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
 (EIGHTH STANDARD PARALLEL SOUTH),
 T. 40 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

A down and dead piñon 24 ins. diam., with faint scribe marks visible on a cut out rotting blaze, bears N. 11° W., 115 links distance to the center of the stump hole.

Corner falls on a gradual southwest slope on sandy ground in piñon and juniper growth.

From this corner, National Geodetic Survey Control Station "SKUM", monumented with a standard aluminum tablet set in a sandstone boulder, with the tablet marked SKUM 1954, bears N. 55°43'50" W., forward bearing and S. 55°44'59" E., back bearing for 168.598 chains distance.

Dependent Resurvey of a Portion of the Subdivisional Lines,
 T. 41 S., R. 5 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
 J.C. Clark, et al. in 1916

From the corner of sections 13 and 14 only, monumented with an iron post, 2 inches diameter, firmly set, projecting 16 inches above ground, with the brass cap marked as described in the official record of the survey executed by J.C. Clark et al. in 1916.

from which

A juniper 16 ins. diam., with faint scribe marks visible on an open blaze, bears N. 40° E., 129 links distance.
 (Record, N. 39°30' E., 132 links distance)

A juniper 24 ins. diam., with faint scribe marks visible on a partially healed blaze, bears N. 1° W., 99 links distance. (Record, N. 30° W., 101 links distance)

Corner falls on a gradual west slope in oak brush and piñon and juniper growth, approximately 40 ft. north of the edge of a vertical rim, which bears N. 70° W., and S. 70° E.

N. 0° 08.7' W., between sections 13 and 14.

40.336

The 1/4 section corner of sections 13 and 14, monumented with an iron post, 1 inch diameter, firmly set, projecting 10 inches above ground, with the brass cap marked as described in the official record of the resurvey executed by J.C. Clark, et al. in 1916.

from which

A dead and standing piñon 12 ins. diam., scribed 1/4 S 13 BT, bears S. 36°30' E., 34 links distance.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

A dead and standing piñon 10 ins. diam., scribed 1/4 S14
BT, bears S. 4° W., 86 links distance.

Corner falls in a patch of manzanita growth on a steep east
slope.

Reestablishment of the Survey Executed by
Bailey and Burrill in 1876, and the Resurvey
Executed by J.C. Clark, et al. in 1916

N. 0°02.3' W., beginning new measurement.

20.047 Point for the N 1/16 section corner of sections 13 and 14, not
monumented.

40.094 The corner of sections 11, 12, 13, and 14, monumented with an
iron post, 2 inches diameter, firmly set with the top 12
inches of the post lying loose on the ground, and with the
brass cap marked as described in the official record of the
resurvey executed by J.C. Clark, et al. in 1916.

from which

A juniper 18 ins. diam., with scribe marks visible through
a partially healed blaze, bears N. 72° E., 100 links
distance. (Record, N. 71° E.)

A down and dead piñon 16 ins. diam., with full scribe marks
visible, not re-measured. (SE bearing tree)

A cedar 18 ins. diam., with scribe marks visible through a
partially healed blaze, bears S. 74° W., 71 links
distance. (Record, piñon, S. 76° W., 66 links distance)

A yellow pine stump 3 ft. diam., 3 ft. high on the down
slope side 1 ft. high on the upper side with no remaining
scribe marks visible, bears N. 12° W., 69 links distance.
(Record, 72 links distance)

Due to the condition of the 1916 iron post, it was determined
necessary to remonument the corner point.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
28 inches in the ground, with the aluminum cap marked:

T41SR5W
S11|S12
S14|S13
2006

Raise a small mound of stone west of the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner falls on a steep north slope.

Deposit the 1916 iron post alongside the aluminum post.

Reestablishment of the Survey Executed by
J.C. Clark, et al. in 1916

From the corner of sections 13 and 14 only.

N. 89° 59.6' W., between sections 14 and 23.

34.435

The 1/4 section corner of section 23 only, monumented with an iron post, 1 inch diameter, firmly set, projecting 14 inches above ground, with a steel fence post alongside, and the brass cap marked as described in the official record of the survey executed by J.C. Clark et al. in 1916.

from which

A piñon stump 16 ins. diam., 3 ft. long lying over, scribed 1/4 S 23 BT, bears S. 5° E., 12 links distance.

A juniper 12 ins. diam., scribed 1/4 S23 BT, bears S. 26° W., 14 links distance.

Corner falls in small grove of juniper trees in old chaining area.

S. 89°47.0' W., beginning new measurement.

4.536

The 1/4 section corner of section 14 only, monumented with an iron post, 1 inch diameter, firmly set, projecting 12 inches above ground, with a steel fence post alongside, and the brass cap marked as described in the official record of the survey executed by J.C. Clark et al. in 1916.

from which

A juniper stump 12 ins. diam., 4 ft. high, scribed 1/4 S14 BT, bears N. 5°30' E., 32 links distance.

A juniper 20 ins. diam., scribed 1/4 S14 BT on a partially healed blaze, bears N. 48° W., 15 links distance.
(Record, 14 links distance)

Reestablishment of the Survey Executed by
Bailey and Burrill in 1876, and the Resurvey
Executed by J.C. Clark, et al. in 1916

West, beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

35.617 The corner of sections 22 and 23 only, monumented with an iron post, 2 inches diameter, firmly set, projecting 10 inches above ground, with a steel fence post alongside, and the brass cap marked as described in the official record of the resurvey executed by J.C. Clark, et al. in 1916.

from which

A juniper 16 ins. diam., with scribe marks visible on a partially healed blaze, bears S. 12° E., 29 links distance. (Record, S. 14°15' E.)

Corner falls on flat ground in old chaining area.

S. 89°56.7' W., beginning new measurement.

4.399 The corner of sections 14 and 15 only, monumented with an iron post, 2 inches diameter, firmly set, projecting 10 inches above ground, with a steel fence post alongside, and the brass cap marked as described in the official record of the resurvey executed by J.C. Clark, et al. in 1916.

from which

A down and dead juniper 29 ins. diam., with full scribe marks visible on an open blaze, not re-measured (NE bearing tree).

No remaining evidence of the NW bearing tree was found.

Corner falls on flat ground in old chaining area with scattered juniper.

N. 0°03.4' W., between sections 14 and 15.

40.006 The 1/4 section corner of sections 14 and 15, monumented with an iron post, 1 inch diameter, firmly set, projecting 12 inches above ground, with a steel fence post alongside, and the brass cap marked as described in the official record of the resurvey executed by J.C. Clark, et al. in 1916.

No remaining evidence of the 1916 NE bearing tree was found.

Corner falls on a gradual northeast slope in on old chaining area and juniper growth.

N. 0°06.4' W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.036** The corner of sections 10, 11, 14, and 15, monumented with an iron post, 2 inches diameter, firmly set, projecting 8 inches above ground, with a steel fence post alongside, and the brass cap marked as described in the official record of the resurvey executed by J.C. Clark, et al. in 1916.

from which

A juniper 16 ins. diam., scribed T41S R5W visible on an open blaze, and a BT sign attached dated 5/6/70, bears S. 4°30' W., 61 links distance.
(Record, 60 links distance)

No remaining evidence of the original or the remaining 1916 bearing trees were found.

From the corner of sections 11, 12, 13, and 14.

S. 89°28.8'W., between sections 11 and 14.

- 18.998** Point for the E 1/16 section corner of section 14 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

E 1/16 S14
2006

Deposit a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raise a mound of stone, 3 ft. base, 1 ft. high, south of the aluminum post.

Corner falls on a steep north slope in piñon, juniper, and ponderosa growth.

- 38.985** Point for the 1/4 section corner of section 14 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

T41SR5W
1/4 S14
2006

Deposit a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raise a small mound of stone south of the aluminum post.

Set a steel fence post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS
39.324

The 1/4 section corner of sections 11 and 14, monumented with an iron post, 1 inch diameter, firmly set in a mound of stone, with the brass cap marked as described in the official record of the resurvey executed by J.C. Clark, et al. in 1916.

This corner will now function for the 1/4 section corner of section 11 only, I remove the marks S14 and add "2006" to the brass cap.

from which

A juniper 20 ins. diam., scribed 1/4 S B on weathered face of tree, bears S. 10° E., 22 links distance.
(Record, S. 7° E.)

A juniper 18 ins. diam., with faint scribe marks visible on a partially healed blaze, bears N. 63° W., 6 links distance.

The corner falls on flat ground in juniper and piñon growth.

S. 89°55.6' W., beginning new measurement.

39.635

The corner of sections 10, 11, 14, and 15.

Reestablishment of the Survey Executed by
Bailey and Burrill in 1876

N. 0° 04.2' E., between sections 10 and 11.

38.378

The 1/4 section corner of sections 10 and 11, monumented with a sandstone 18x8x6 inches, dimly marked 1/4 on one face, lying loose in a scattered mound of stone, alongside a steel fence post.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

T41SR5W
1/4
S10|S11
2006

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raise a small mound of stone west of the aluminum post.

Reset the steel fence post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner falls on a gradual south slope on sandy ground, and 90 ft. south of Road No. 601 of the Grand Staircase Escalante National Monument, 16 ft. wide, bears east and west.

N. 1°02.0' W., beginning new measurement.

40.531

The corner of sections 2, 3, 10, and 11, monumented with a sandstone 14x8x4 inches, firmly set at the corner of fences, projecting north, east and S. 26° W., plainly marked with 5 notches on the south and 2 on the east edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum post marked:

T41SR5W	
S3	S2
S10	S11
2006	

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a clear plastic case at the base of the aluminum post.

The corner falls on flat ground in sagebrush undergrowth.

N. 0° 09.1' E., between sections 2 and 3.

40.077

The 1/4 section corner of sections 2 and 3, monumented with a Talbot Land Surveyors survey monument, an iron post 1 1/2 inches diameter, firmly set 3 inches below ground, with a 3 1/2 inches diameter aluminum cap attached and marked: T41SR5W 1/4 S2 S3 1984, with a steel fence post alongside.

NOTE: According to Lanny Talbot of Talbot Land Surveyors he re-established this corner on the line between found section corners to the north and south and 8 feet south of the south side of a wash as described in the official record of the Bailey and Burrill survey in 1876 as a topo call. He found no remaining evidence of the original marked stone.

During the execution of this survey I searched for and found no evidence of the original marked stone. The monument as set by Lanny Talbot of Talbot Land Surveyors is accepted as a careful and faithful re-establishment of the original 1/4 section corner.

Corner falls 8 ft. south of the south side of a wash 50 ft. wide, bears N. 70° E.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0°09.0' E., beginning new measurement.

19.988 Point for the N 1/16 section corner of sections 2 and 3, not monumented.

39.456 The monumented closing corner of sections 2 and 3, monumented with a lava stone 13x10x8 inches, firmly set in the center of a small mound of stone, plainly marked with 4 notches on west and 2 notches on the east edges. Add the marks AM to the top of the stone and buried it in place.

39.570 True point for the closing corner of sections 2 and 3, at intersection with the Eighth Standard Parallel South.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

T40S
C | C
S3 | S2
T41SR5W
2006

Deposit a magnet enclosed in a clear plastic case at the base of the aluminum post.

Reestablishment of the Survey Executed by
Bailey and Burrill in 1876, and the Resurvey
Executed by J.C. Clark, et al. in 1916

From the 1/4 section corner of sections 15 and 16, monumented with an iron post, 1 inch diameter, firmly set, projecting 12 inches above ground, with the brass cap marked as described in the official record of the resurvey executed by J.C. Clark, et al. in 1916.

from which

A juniper 16 ins. diam., with faint scribe marks visible on a mostly healed blaze, bears S 10° 45' E., 150 links distance.

A juniper 12 ins. diam., scribed 1/4 S16 on a partially healed blaze, bears S 76° W., 168 links distance.
(Record, 167 links distance)

Corner falls on flat ground in juniper growth.

N. 0°11.6' W., between sections 15 and 16.

39.466 The corner of sections 9, 10, 15, and 16, monumented with an iron post, 2 inches diameter, firmly set, projecting 12 inches above ground, with a steel fence post alongside, and the brass

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

cap marked as described in the official record of the resurvey executed by J.C. Clark, et al. in 1916.

Corner falls on flat ground directly north of a small grove of mature juniper trees.

From the corner of sections 10, 11, 14, and 15.

S. 89°23.6' W., between sections 10 and 15.

- 39.632** The 1/4 section corner of sections 10 and 15, monumented with an iron post, 1 inch diameter, firmly set, projecting 12 inches above ground, with a steel fence post alongside, and the brass cap marked as described in the official record of the resurvey executed by J.C. Clark, et al. in 1916, and witnessed with a mound of stone to the north.

This corner will now function for the 1/4 section corner of section 10 only. Removed the mark S15 and add "2006" to the brass cap.

Corner falls on open ground in old chaining area.

S. 89°30.3' W., beginning new measurement.

- 0.372** Point for the 1/4 section corner of section 15 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

T41SR5W
1/4 S15
2006

Deposit a magnet enclosed in a clear plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

- 39.696** The corner of sections 9, 10, 15, and 16.
-

Reestablishment of the Survey Executed by
Bailey and Burrill in 1876

N. 0°31.0' W., between sections 9 and 10.

- 39.598** Point for the 1/4 section corner of sections 9 and 10, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T41SR5W
1/4
S9|S10
2006

Deposit a magnet enclosed in clear plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls within a seasonal pond on the southeasterly side, currently dry.

79.196

The corner of sections 3, 4, 9, and 10, monumented with a Talbot Land Surveyors survey monument, an iron post, 1 1/2 inches diameter, firmly set 4 inches below ground surface, with a 3 1/2 inches diameter aluminum cap attached and marked: T. 41 S., R. 5 W., S3, S4, S9, S10, 1984, with a steel fence post alongside and a BLM location tag attached. Alongside the iron post, found the remains of a cedar post, 30 inches long by 4 inches square. No definitive marks could be seen on the post.

NOTE: According to Lanny Talbot of Talbot Land Surveyors the corner post was identified by the Kanab Office of the Bureau of Land Management prior to a chaining in the early 1970's.

This monument is accepted as the best available evidence of the position of the original section corner.

Corner falls in old chaining area, in scattered juniper, oak brush, and sagebrush growth.

From the corner of sections 2, 3, 10, and 11.

S. 89°39.6' W., between sections 3 and 10.

39.670

Point for the 1/4 section corner of sections 3 and 10, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

T41SR5W
S3
1/4 —
S10
2006

Deposit a magnet enclosed in a clear plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner falls on a gradual south slope in an area of extensive ground disturbance from an old chaining in and around piles of old pushed over juniper trees in a young growth juniper area.

79.340 The corner of sections 3, 4, 9, and 10.

N. 0°19.0' E., between sections 3 and 4.

20.013 Point for the S 1/16 section corner of sections 3 and 4, monumented with a rebar without identifying cap. This monument is accepted as a careful and faithful determination of the S 1/16 section corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

S 1/16
S4|S3
2006

Deposit the rebar at the base of the aluminum post.

Deposit a magnet enclosed in a clear plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground in sagebrush, 76 links north of a fence bears east and west.

From the corner, the corner of fences projecting N. 10° W., S. 50° W., and East, bears S. 81° 31' W., 525 chains distance.

with continuous measurement

40.026 The 1/4 section corner of sections 3 and 4, monumented with a Talbot Land Surveyors survey monument an iron post, 1 1/2 inches diameter, firmly set, projecting 10 inches above ground, with a 3 1/2 inches diameter aluminum cap attached and marked: T41SR5W S3 S4 1984.

According to Lanny Talbot of Talbot Land Surveyors a rebar without cap, with a steel fence post alongside showing evidence as being utilized as the 1/4 section corner was set prior to his survey. Lanny Talbot accepted the rebar as the best available evidence of the position of the original corner.

This monument is accepted as the best available evidence of the original 1/4 section corner position.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner falls in mature piñon and juniper area, with sagebrush undergrowth.

N. 0°10.1' E., beginning new measurement.

20.018 Point for the N 1/16 section corner of sections 3 and 4, not monumented.

39.485 The closing corner of sections 3 and 4, on the Eight Standard Parallel South, hereinbefore described.

The Subdivision of Section 3,
T. 41 S., R. 5 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 3 and 10.

N. 0°11.8' E., on the N - S centerline of section 3.

20.026 Point for the center S 1/16 section corner of section 3.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

C
S1/16 | S3
C
2006

Deposit a magnet enclosed in a clear plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat sandy ground in mature juniper growth, 83 feet north of a B.L.M. drift fence line, net wire on bottom and one strand of barb wire at top, bears easterly and westerly.

40.052 Point for the center 1/4 section corner, at intersection with the E - W centerline of section 3, monumented with a Talbot Land Surveyors survey monument, an iron post, 1 1/2 inches diameter, with a 3 1/2 inches diameter aluminum cap attached and marked: T41SR5W C1/4 S3 1984.

This monument is accepted as a careful determination of the center 1/4 section corner position.

Set a steel fence post alongside the galvanized post.

Corner falls on flat ground in a fenced pasture, 27 feet south of a fence along the south R/W of the main road between Johnson and Alton.

THE SUBDIVISION OF SECTION 3,
T. 41 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.522 Road between Johnson and Alton, 22 feet wide, bears N. 88° E., and S. 88° W.

60.076 Point for the center N 1/16 section corner of section 3.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

$$\begin{array}{c} \text{C} \\ \text{N}1/16 \mid \text{S}3 \\ \text{C} \\ 2006 \end{array}$$

Deposit a magnet enclosed in a clear plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls inside a fenced pasture, 10.5 feet south of a fence projecting east and west.

79.569 The 1/4 section corner of section 3 only, on the Eighth Standard Parallel South, hereinbefore described.

From the 1/4 section corner of sections 2 and 3.

S. 89°37.3' W., on the E - W centerline of section 3.

19.818 Point for the center E 1/16 section corner of section 3.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

$$\begin{array}{c} \text{E } 1/6 \\ \text{C} \text{ --- } \text{C} \\ \text{S}3 \\ 2006 \end{array}$$

Deposit a magnet enclosed in a clear plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls in a wash 60 feet wide, 20 feet north of the main channel 5 feet wide, drains N. 60° E.

The corner of fences projecting N. 80° W. and North bears N. 14° 30' E., 161 chains distance.

39.636 The center 1/4 section corner of section 3.

59.427 Point for the center W 1/16 section corner of section 3.

THE SUBDIVISION OF SECTION 3,
T. 41 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
28 inches in the ground, with the aluminum cap marked:

W1/16
C—C
S3
2006

Deposit a magnet enclosed in a clear plastic case at the base
of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on the east edge of a dirt road 25 feet wide,
bears north and south, and 40 feet north of the road between
Johnson and Alton, the road is 26 feet wide and bears
N. 80° E., and S. 80° W.

79.218 The 1/4 section corner of sections 3 and 4.

From the center E 1/16 section corner of section 3.

N. 0°10.4' E., on the N - S centerline of the NE 1/4 of
section 3.

20.006 Point for the NE 1/16 section corner, at intersection with the
E - W centerline of the NE 1/4 of section 3.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
24 inches in the ground, with the aluminum cap marked:

NE 1/16
S3
2006

Deposit a magnet enclosed in a clear plastic case at the base
of the aluminum post.

Corner falls on flat ground inside a fenced pasture, 3 feet
south of the corner of fences projecting south and west.

39.575 Point for the E 1/16 section corner of section 3 only, on the
Eight Standard Parallel South, hereinbefore described.

From the point for the N 1/16 section corner of sections 2
and 3.

S. 89°40.4' W., on the E - W centerline of the NE 1/4 of
section 3.

19.808 The NE 1/16 section corner of section 3.

39.616 The center N 1/16 section corner of section 3.

THE SUBDIVISION OF SECTION 3,
T. 41 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the center S 1/16 section corner of section 3.

S. 89°38.4' W., on the E - W centerline of the SW 1/4 of section 3.

39.626 The S 1/16 section corner of sections 3 and 4.

From the center W 1/16 section corner of section 3.

N. 0°11.0' E., on the N - S centerline of the NW 1/4 of section 3.

20.021 Point for the NW 1/16 section corner, at intersection with the E - W centerline of the NW 1/4 of section 3.

Set an aluminum post, 30 inches, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

NW 1/16
S3
2006

Deposit a magnet enclosed in a clear plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on top of a ridge, 21.5 feet west of a fence bears north and south.

From this corner, the corner of fences projecting north, south, and east, bears N. 57° E., 38 links distance.

39.940 The point for the W 1/16 section corner of section 3 only, on the Eighth Standard Parallel South, hereinbefore described.

From the center N 1/16 section corner of section 3.

S. 89°36.8' W., on the E - W centerline of the NW 1/4 of section 3.

19.795 The NW 1/16 section corner of section 3.

39.590 The point for the N 1/16 section corner of sections 3 and 4.

The Subdivision of Section 14,
T. 41 S., R. 5 W., Salt Lake Meridian, Utah

From the south 1/4 section corner of section 14 only.

N. 0°06.4' W., on the N - S centerline of section 14.

THE SUBDIVISION OF SECTION 14,
T. 41 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.178 Point for the center 1/4 section corner, at intersection with the E - W centerline of section 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked;

T41SR5W
C 1/4
S14
2006

Deposit a magnet enclosed in a clear plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat sandy ground in scattered piñon and juniper.

60.134 Point for the center N 1/16 section corner of section 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

C
N1/16 | S14
C
2006

Deposit a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raise a small mound of stone west of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on a moderate east slope, 2 feet north of a fence, bears easterly and westerly.

80.090 The north 1/4 section corner of section 14 only.

From the 1/4 section corner of sections 13 and 14.

S. 89°44.8' W., on the E - W centerline of section 14.

18.973 Point for the center E 1/16 section corner of section 14, not monumented.

38.940 The center 1/4 section corner of section 14.

78.917 The 1/4 section corner of sections 14 and 15.

THE SUBDIVISION OF SECTION 14,
T. 41 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the point for the center E 1/16 section corner of section 14.

N. 0°04.6' W., on the N - S centerline of the NE 1/4 of section 14.

20.003 Point for the NE 1/16 section corner, at intersection with the E - W centerline of the NE 1/4 of section 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

NE 1/16
S14
2006

Deposit a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raise a small mound of stone west of the aluminum post.

Corner falls on a steep east slope, 5 feet south of a fence, bears east and west.

40.006 The E 1/16 section corner of section 14 only.

From the point for the N 1/16 section corner of sections 13 and 14.

S. 89°36.8' W., on the E - W centerline of the NE 1/4 of section 14.

18.986 The NE 1/16 section corner of section 14.

38.963 The center N 1/16 section corner of section 14.

CERTIFICATE OF SURVEY

I, *Larry V. Judd, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *31st day of August, 2005*, I have *executed a dependent resurvey of a portion of the north boundary (Eighth Standard Parallel South), a portion of the subdivisional lines and the subdivision of sections 3 and 14, in Township 41 South, Range 5 West,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

8/20/2008
Date

Larry V. Judd
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the north boundary (Eighth Standard Parallel South), a portion of the subdivisional lines, and the subdivision of sections 3 and 14 in Township 41 South, Range 5 West, Salt Lake Meridian, Utah,*

executed by *Larry V. Judd, Cadastral Surveyor,*

having been critically examined and found correct, are hereby approved.

September 12, 2008
Date

Daniel W. Webb
(Chief Cadastral Surveyor for Utah)

~~**CERTIFICATE OF TRANSCRIPT**~~

~~I certify that the foregoing transcript of the field notes of the above-described surveys in *T. 41 S., R. 5 W., Salt Lake Meridian, Utah,* is a true copy of the original field notes.~~

~~_____~~
Date

~~_____~~
(Authorizing Signature)