

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE
DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
A PORTION OF THE EAST AND WEST BOUNDARIES,
A PORTION OF THE SUBDIVISIONAL LINES
AND THE
SUBDIVISION OF SECTIONS 30, 31 AND 33,
IN

TOWNSHIP 12 NORTH, RANGE 12 WEST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Ronald K. Baugh
Supervisory Cadastral Surveyor

Under Special Instructions dated and approved, *October 3, 2005*, which provided for the surveys included under Group Number *1012*, and Assignment Instructions dated *October 3, 2005*.

Survey commenced *October 6, 2005*
Survey completed *May 18, 2006*

TOWNSHIP 12 NORTH, RANGE 12 WEST, SALT LAKE MERIDIAN

The following field notes are those of the dependent resurvey of the south boundary, a portion of the east and west boundaries, and a portion of the subdivisional lines, and the subdivision of sections 30, 31 and 33, in Township 12 North, Range 12 West, Salt Lake Meridian, Utah.

History of Surveys

Surveyed by		Retr. or Resurveyed by	
SOUTH BOUNDARY			
Portion	J. Gorlinski	1872	
Portion	G. V. M. Boutelle	1872	
All			H. Fitzhugh 1883
All			F. R. Chappell 1967
EAST BOUNDARY			
All	J. Gorlinski	1871	
WEST BOUNDARY			
All	G. V. M. Boutelle	1872	
Portion			M. H. Korhn 1987
NORTH BOUNDARY (Third Standard Parallel North)			
Portion	J. Gorlinski	1871	
All	G. V. M. Boutelle	1871-72	
Portion			F. Dickert 1882
SUBDIVISION			
Portion	J. Gorlinski	1872	
Portion	E. W. Koeber	1887	E. W. Koeber 1888

INDEX DIAGRAM

Township 12 North, Range 12 West

6	5	4	3	2	1 19
7	8	9	10 30	25 11 25	18 12 10 18
18	17 38	16	15 29	24 14 23	17 13 9 16
19 37	38 20 37	33 21 32	29 22 22 28	23 16 22	24 8 15
12 30 35	35 29 34	32 28 31	28 27 27	21 26 20	14 25 7 14
11 31 6	34 32 5	31 33 5	26 34 4	20 35 4	13 36 6 3

The Subdivision of Section 30.....Page 39
 The Subdivision of Section 31.....Page 40
 The Subdivision of Section 33.....Page 41

TOWNSHIP 12 NORTH, RANGE 12 WEST, SALT LAKE MERIDIAN

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1012 dated October 3, 2005.

The direction of the lines was determined by references to true meridians, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods*, dated May 9, 2001, Version 1.0. Trimble 5700 model GPS receivers were used for field collection. Cadastral Measurement Management (CMM) software was the primary software utilized for the project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Cadastral Control Network was derived from GPS static observations, post processed by the National Geodetic Survey, Online Positioning Used Service (OPUS), utilizing Continuously Operating Reference Stations (CORS); *HILL72_UT2004*, *POCATELLO*, and *SALT LAKE WAAS 1*.

The geographic position of the southeast corner of section 36, T. 12 N., R. 12 W., SLM, UT, as determined by direct RTK methods from the National Geodetic Survey OPUS solution is as follows:

Latitude 41° 42' 58.098" N., Longitude 113° 09' 07.264" W.
N.A.D. 83, Network Accuracy = 0.200 meter at 95 % confidence.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of the South Boundary,
T. 12 N., R. 12 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
J. Gorlinski in 1871 and the Dependent Resurveys by
H. Fitzhugh in 1883 and F. R. Chappell in 1967-68.

Beginning at the corner of sections 31 and 36 only, T. 12 N., Rs. 11 and 12 W., monumented with an iron post, 2 1/2 inches diameter, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1967 resurvey.

Set a steel fence post alongside the iron post.

From this corner, a fence corner, projecting north, east and west, bears S. 33° 20' E., 99 links distance.

S. 89° 23.9' W., on the south boundary of section 36.

16.007

The closing corner of sections 1 and 6, T. 11 N., Rs. 11 and 12 W., monumented with a sandstone, 8x6x3 inches, set and marked with 6 notches on the east, west and south edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N
S 36
C C
S 1 S 6
R 12 W R 11 W
T 11 N
2005

Corner is located 52 links north of an E-W fence.

Set a steel fence post alongside the aluminum post.

39.897

The 1/4 section corner of section 36 only, monumented with an iron post, 2 1/2 inches diameter, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1967 resurvey.

Corner is located in an east and west wood post fence line.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89° 25.6' W., beginning new measurement.

- 15.772 Point for the 1/4 section corner of section 1 only, T. 11 N., R. 12 W., at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N
1/4 S 1
T 11 N R 12 W
2006

- 39.674 The corner of sections 1, 2, 35 and 36, monumented with an iron post, 2 1/2 inches diameter, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1967 resurvey.

Set a steel fence post alongside the iron post.

Corner is located in a wood post fence line, bears east and west.

N. 89° 42.1' W., between sections 2 and 35.

- 40.138 The 1/4 section corner of sections 2 and 35, monumented with an iron post, 2 1/2 inches diameter, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1967 resurvey.

Set a steel fence post alongside the iron post.

Corner is located in a wood post fence line, bears east and west.

S. 88° 01.6' W., beginning new measurement.

- 41.693 The corner of sections 2, 3, 34 and 35, monumented with an iron post, 2 1/2 inches diameter, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1967 resurvey.

Corner is located in an east and west fence line.

Reestablishment of the Survey Executed by
G. V. M. Boutelle in 1872 and the Dependent Resurveys by
H. Fitzhugh in 1883 and F. R. Chappell in 1967.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 88° 02.5' W., between sections 3 and 34.

39.526 The 1/4 section corner of sections 3 and 34, monumented with an iron post, 2 1/2 inches diameter, projecting 10 inches above ground, with brass cap marked as described in the official record of the 1967 resurvey.

Corner is located in an east and west fence line.

S. 89° 14.2' W., beginning new measurement.

39.487 The corner of sections 3, 4, 33 and 34, monumented with an iron post, 2 1/2 inches diameter, projecting 10 inches above ground, with a brass cap marked as described in the official record of the 1967 resurvey.

Corner is located in an east and west fence line.

S. 89° 51.3' W., between sections 4 and 33.

20.180 Point for the E 1/16 section corner of sections 4 and 33, not monumented.

40.360 The 1/4 section corner of sections 4 and 33, monumented with an iron post, 2 1/2 inches diameter, projecting 8 inches above ground, firmly set, with brass cap marked as described in the official record of the 1967 resurvey.

Set a steel fence post alongside the iron post.

Corner is located in an east and west fence line.

N. 89° 35.6' W., beginning new measurement.

39.889 The corner of sections 4, 5, 32 and 33, monumented with an iron post, 2 1/2 inches diameter, projecting 12 above ground, with brass cap marked as described in the official record of the 1967 resurvey.

Corner is located in an east and west fence line.

N. 86° 59.7' W., between sections 5 and 32.

39.726 The 1/4 section corner of sections 5 and 32, monumented with an iron post, 2 1/2 inches diameter, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1967 resurvey.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the iron post.

S. 88° 52.5' W., beginning new measurement.

- 40.283 The corner of sections 5, 6, 31 and 32, monumented with an iron post, 2 1/2 inches diameter, projecting 10 inches above ground, in a collar of stone, with brass cap marked as described in the official record of the 1967 resurvey.

Set a steel fence post alongside the iron post.

S. 89° 19.9' W., between sections 6 and 31.

- 40.028 The 1/4 section corner of section 31 only, monumented with an iron post, 2 1/2 inches diameter, projecting 10 inches above ground, with brass cap marked as described, except for no date, in the official record of the 1967 resurvey.
-

S. 89° 19.6' W., beginning new measurement.

- 14.259 True point for the N 1/4 section corner of section 6 only, T. 11 N., R. 12 W.

From this true point, the N 1/4 section corner of section 6 only, monumented with an iron post, 2 1/2 inches diameter, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1967 resurvey, bears North, 0.047 chains distance.

- 40.176 The corner of sections 31 and 36 only, T. 12 N., Rs. 12 and 13 W., monumented with an iron post, 2 1/2 inches diameter, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1967 resurvey.

Set a steel fence post alongside the iron post.

Dependent Resurvey of a Portion of the East Boundary,
T. 12 N., R. 12 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
J. Gorlinski in 1871.

From the corner of sections 31 and 36 only, T. 12 N., Rs. 11 and 12 W., hereinbefore described.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 22.7' W., between sections 31 and 36.

40.323 Point for the 1/4 section corner of sections 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	
R 12 W	R 11 W
1/4	
S 36	S 31
2005	

Set a steel fence post alongside the aluminum post.

An old north and south fence line bears east, 24 links distance.

80.646 The corner of sections 25, 30, 31 and 36, monumented with a lava stone, 15x10x6 inches, firmly set in a north and south fence line, marked with 5 notches on the north and 1 notch on the south edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	
R 12 W	R 11 W
S 25	S 30
S 36	S 31
2005	

Deposit marked stone alongside the aluminum post.

Raise a mound of stone, 4 ft. base, 3 ft. high, west of aluminum post.

N. 0° 40.6' W., between sections 25 and 30.

40.385 Point for the 1/4 section corner of sections 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T 12 N
R 12 W R 11 W
1/4
S 25 | S 30
2005

Set a steel fence post alongside the aluminum post.

A north and south fence line bears east, 2.3 links distance.

80.770 Point for the corner of sections 19, 24, 25 and 30, at proportionate distance; the lava stone with 2 and 4 notches, was lying loose on the ground.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N
R 12 W R 11 W
S 24 | S 19
S 25 | S 30
2005

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

A north and south fence line bears east, 4.5 links distance.

N. 0° 40.6' W., between sections 19 and 24.

40.385 Point for the 1/4 section corner of sections 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N
R 12 W R 11 W
1/4
S 24 | S 19
2005

Set a steel fence post alongside the aluminum post.

A north and south fence line bears east, 2.3 links distance.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

80.770

The corner of sections 13, 18, 19 and 24, monumented with a lava stone, 16x15x5 inches, firmly set and plainly marked with 3 notches on the north and south edges, with a 5/8 inch rebar, 24 inches long, with a yellow cap marked: Box Elder County Surveyor.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T 12 N	
R 12 W	R 11 W
S 13	S 18
S 24	S 19
2005	

Set the Box Elder rebar and cap inside the aluminum post.

Deposit the marked stone alongside the aluminum post.

Corner is located in a north and south fence line.

N. 0° 45.9' W., between sections 13 and 18.

40.482

Point for the 1/4 section corner of sections 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	
R 12 W	R 11 W
1/4	
S 13	S 18
2005	

Corner is located in a reseeded area in a north and south fence line.

80.964

The corner of sections 7, 12, 13 and 18, monumented with a lava stone, 18x14x4 inches, firmly set and plainly marked with 2 notches on the north and 4 notches on the south edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T 12 N	
R 12 W	R 11 W
S 12	S 7
S 13	S 18
2005	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

A north and south fence line bears west, 1.5 links distance.

N. $0^{\circ} 45.9'$ W., between sections 7 and 12.

40.032 Point for the 1/4 section corner of sections 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	
R 12 W	R 11 W
1/4	
S 12	S 7
2005	

A north and south fence line bears west, 3 links distance; and its fence corner projecting north, south and east, bears south, 2.50 chains distance.

80.064 The corner of sections 1, 6, 7 and 12, monumented with a lava stone, 18x13x4 inches, marked with 1 notch north and 5 notches on south edges, in a small mound of stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	
R 12 W	R 11 W
S 1	S 6
S 12	S 11
2005	

Deposit marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a mound of stone, 2 ft. base, 1 ft. high, west of aluminum post.

Dependent Resurvey of a Portion of the West Boundary,
T. 12 N., R. 12 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
G. V. M. Boutelle in 1872 and the Dependent Resurvey by
M. H. Korhn in 1987.

From the corner of sections 31 and 36, T. 12 N., Rs. 12 and 13 W.,
hereinbefore described.

N. 0° 37.0' W., between sections 31 and 36.

40.158

The 1/4 section corner of sections 31 and 36, monumented with a
lava stone, 18x12x4 inches, firmly set and marked with a 1/4 on the
west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24
inches in the ground, with a magnet at base, with aluminum cap
marked:

T 12 N
R 13 W R 12 W
1/4
S36 | S 31
2005

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From this corner the 1987 aluminum post, firmly set and projecting
4 inches above ground, bears S. 15°44.1' W., 5.333 chains distance.
This corner was set in error and a corrective resurvey is required.

N. 0° 41.8' W., beginning new measurement.

22.599

Point for the S-S-N-N 1/1024 section corner of sections 31 and 36.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26
inches in the ground, with a magnet at base, with aluminum cap
marked:

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T 12 N
R 13 W R 12 W
S-S-N-N 1/1024
S 36 | S 31
2006

- 40.176 The corner of sections 25, 30, 31 and 36, monumented with a lava stone, 19x10x6 inches, firmly set and plainly marked with 5 notches on the north and 1 notch on the south edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N
R 13 W R 12 W
S 25 | S 30
S 36 | S 31
2005

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From this corner the 1987 aluminum post, firmly set and projecting 4 inches above ground, bears S. 31°31.2' W., 5.369 chains distance. This corner was set in error and a corrective resurvey is required.

Reestablishment of the Survey Executed by
G. V. M. Boutelle in 1872.

N. 0° 07.9' W., between sections 25 and 30.

- 40.281 The 1/4 section corner of sections 25 and 30, monumented with a lava stone, 20x13x4 inches, firmly set and dimly marked 1/4 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N
R 13 W R 12 W
1/4
S 25 | S 30
2005

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 03.4' W., beginning new measurement.

40.245 The corner of sections 19, 24, 25 and 30, monumented with a lava stone, 14x9x4 inches, marked with 4 notches on the north and 2 notches on the south edges, with an old rusty rebar alongside and next to an old cedar post, that projects 3 ft. above ground.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	
R 13 W	R 12 W
S 24	S 19
S 25	S 30
2006	

Set rebar inside the aluminum post.

Set a steel fence post and the cedar post alongside the aluminum post.

From this corner a fence corner bears S. 27°48.8'W, 5.674 chains distance from which fences bear E-W and N.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 12 N., R. 12 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
J. Gorlinski in 1872.

From the corner of sections 1, 2, 35 and 36 on the south boundary of the township, hereinbefore described.

N. 0° 02.3' W., between sections 35 and 36.

40.563 Point for the 1/4 section corner of sections 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	R 12 W
1/4	
S 35	S 36
2005	

Set a steel fence post alongside the aluminum post.

81.126 Point for the corner of sections 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	R 12 W
S 26	S 25
S 35	S 36
2005	

Set a steel fence post alongside the aluminum post.

From the corner of sections 25, 30, 31 and 36 on the east boundary of the township, hereinbefore described.

N. 89° 40.1' W., between sections 25 and 36.

39.536 Point for the 1/4 section corner of sections 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	R 12 W
S 25	
1/4 ———	
S 36	
2005	

79.072 Set a steel fence post alongside the aluminum post.
The corner of sections 25, 26, 35 and 36.

N. 2° 12.6' W., between sections 25 and 26.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.593

Point for the 1/4 section corner of sections 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	R 12 W
1/4	
S 26	S 25
2005	

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, west of aluminum post.

81.186

The corner of sections 23, 24, 25 and 26, monumented with a mound of stone, no marked stone was found. This point is accepted as the best available evidence of the original corner position.

At the corner point (center of the mound of stone)

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 6 ft. base to top of aluminum cap marked:

T 12 N	R 12 W
S 23	S 24
S 26	S 25
2005	

From the corner of sections 19, 24, 25 and 30 on the east boundary of the township, hereinbefore described.

N. 89° 25.3' W., between sections 24 and 25.

40.616

Point for the 1/4 section corner of sections 24 and 25, at proportionate distance; There is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	R 12 W
S 24	
1/4 —————	
S 25	
2005	

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the aluminum post.


81.232 The corner of sections 23, 24, 25 and 26.

N. 0° 02.3' E., between sections 23 and 24.

39.984 Point for the 1/4 section corner of sections 23 and 24, at proportionate distance; there is no remaining evidence of the original corner. This corner position falls in a wash and is unsafe to set a monument, not monumented.

40.272 Point selected for the witness 1/4 section corner of sections 23 and 24.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:




Set a steel fence post alongside the aluminum post.

79.968 The corner of sections 13, 14, 23 and 24, monumented with a lava stone, 16x8x7 inches, firmly set and plainly marked with 1 notch on the east 3 notches on the south edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:



Deposit the marked stone alongside the aluminum post.

From the corner of sections 13, 18, 19 and 24 on the east boundary of the township, hereinbefore described.

N. 89° 59.0' W., between sections 13 and 24.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.100

Point for the 1/4 section corner of sections 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
S 13
1/4 —————
S 24
2005

Set a steel fence post alongside the aluminum post.

80.200

The corner of sections 13, 14, 23 and 24.

N. 0° 25.1' W., between sections 13 and 14.

40.534

The 1/4 section corner of sections 13 and 14, monumented with a lava stone, 12x10x6 inches, firmly set and plainly marked 1/4 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
1/4
S 14 | S 13
2005

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 34.4' E., beginning new measurement.

40.252

Point for the corner of sections 11, 12, 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with a magnet at base, with aluminum post marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T 12 N	R 12 W
S 11	S 12
S 14	S 13
2005	

Set a steel fence post alongside the aluminum post.

Corner is located in a open reseeded area.

From the corner of sections 7, 12, 13 and 18 on the east boundary of the township, hereinbefore described.

S 89° 53.5' W., between sections 12 and 13.

39.498

Point for the 1/4 section corner of sections 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	R 12 W
S 12	
1/4	—————
S 13	
2005	

Set a steel fence post alongside the aluminum post.

Corner is located in a open reseeded area.

78.996

The corner of sections 11, 12, 13 and 14.

Reestablishment of the Survey Executed by
J. Gorlinski in 1872 and the Dependent Resurvey by
E. W. Koeber in 1887.

N. 1° 03.1' W., between sections 11 and 12.

40.256

The 1/4 section corner of sections 11 and 12, monumented with a lava stone, 11x8x3 inches, dimly marked 1/4.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T 12 N R 12 W
1/4
S 11 | S 12
2005

Set a steel fence post alongside the aluminum post.

N. 0° 13.6' W., beginning new measurement.

40.060

The corner of sections 1, 2, 11 and 12, monumented with a lava stone, 15x13x5 inches, in a small mound of stone, marked with 1 notch on the east and 5 notches on the south edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
S 2 | S 1
S 11 | S 12
2005

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 2 ft. base, 1 ft. high, west of the aluminum post.

From the corner of sections 1, 6, 7 and 12 on the east boundary of the township, hereinbefore described.

N. 89° 55.6' W., between sections 1 and 12.

39.404

Point for the 1/4 section corner of sections 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
S 1
1/4 —————
S 12
2005

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the aluminum post.

78.808 The corner of sections 1, 2, 11 and 12.

From the corner of sections 2, 3, 34 and 35 on the south boundary of the township, hereinbefore described.

N. 1° 51.8' E., between sections 34 and 35.

40.969 Point for the 1/4 section corner of sections 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	R 12 W
1/4	
S 34	S 35
2005	

Set a steel fence post alongside the aluminum post.

81.938 The corner of sections 26, 27, 34 and 35, monumented with a quartzite stone, 11x8x6 inches, marked with 2 notches on the east and 1 notch on the south edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, in a collar of stone, with aluminum cap marked:

T 12 N	R 12 W
S 27	S 26
S 34	S 35
2005	

Deposit quartzite stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

Reestablishment of the Survey Executed by
J. Gorlinski in 1872.

From the corner of sections 25, 26, 35 and 36.

S. 89° 40.1' W., between sections 26 and 35.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

39.536

Point for the 1/4 section corner of sections 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 4 ft. base to top of aluminum cap marked:

T 12 N R 12 W
S 26
1/4-----
S 35
2005

79.072

The corner of sections 26, 27, 34 and 35.

Reestablishment of the Survey Executed by
J. Gorlinski in 1872 and the Dependent Resurvey by
E. W. Koeber in 1887.

N. 4° 44.0' W., between sections 26 and 27.

40.544

The 1/4 section corner of sections 26 and 27, monumented with a lava stone, 11x7x6 inches, plainly marked 1/4.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
1/4
S 27 | S 26
2005

Deposit the marked stone alongside the aluminum post.

N. 2° 44.6' E., beginning new measurement.

40.416

The corner of sections 22, 23, 26 and 27, monumented with a quartzite stone, 15x7x3 inches, dimly marked.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T 12 N	R 12 W
S 22	S 23
S 27	S 26
2005	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

Reestablishment of the Survey Executed by
J. Gorlinski in 1872.

From the corner of sections 23, 24, 25 and 26.

S. 89° 24.2' W., between sections 23 and 26.

38.669

Point for the 1/4 section corner of sections 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	R 12 W
S 23	
1/4	—————
S 26	
2005	

Set a steel fence post alongside the aluminum post.

77.338

The corner of sections 22, 23, 26 and 27.

Reestablishment of the Survey Executed by
J. Gorlinski in 1872 and the Dependent Resurvey by
E. W. Koeber in 1887.

N. 0° 33.5' W., between sections 22 and 23.

40.386

The 1/4 section corner of sections 22 and 23, monumented with a lava stone, 15x11x6 inches, marked 1/4, in a small mound of stone.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 3 ft. base to top of aluminum cap marked:

T 12 N	R 12 W
1/4	
S 22	S 23
2005	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 21.9' W., beginning new measurement.

40.073

The corner of sections 14, 15, 22 and 23, monumented with a lava stone, 13x9x4 inches, in a small mound of stone, dimly marked with 3 notches on the south edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 4 ft. base to top of aluminum cap marked:

T 12 N	R 12 W
S 15	S 14
S 22	S 23
2005	

Deposit marked stone alongside the aluminum post.

Reestablishment of the Survey Executed by
J. Gorlinski in 1872.

From the corner of sections 13, 14, 23 and 24.

S. 89° 46.0' W., between sections 14 and 23.

39.011

Point for the 1/4 section corner of sections 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T 12 N R 12 W
S 14
1/4 —————
S 23
2005

Set a steel fence post alongside the aluminum post.

78.022 The corner of sections 14, 15, 22 and 23.

Reestablishment of the Survey Executed by
J. Gorlinski in 1872 and the Dependent Resurvey by
E. W. Koeber in 1887.

N. 0° 54.4' W., between sections 14 and 15.

40.238 The 1/4 section corner of sections 14 and 15, monumented with a lava stone, 17x9x3 inches, dimly marked 1/4, in a small mound of stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 3 ft. base to top of aluminum cap marked:

T 12 N R 12 W
1/4
S 15 | S 14
2005

Deposit the marked stone alongside the aluminum post.

N. 1° 24.3' W., beginning new measurement.

40.384 The corner of sections 10, 11, 14 and 15, monumented with a quartzite stone, 14x8x5 inches, set in a small mound of stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, in a collar of stone, with aluminum cap marked:

T 12 N R 12 W
S 10 | S 11
S 15 | S 14
2005

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From the corner of sections 11, 12, 13 and 14.

S. 89° 38.6' W., between sections 11 and 14.

39.869

Point for the 1/4 section corner of sections 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
S 11
1/4 —————
S 14
2005

Set a steel fence post alongside the aluminum post.

79.738

The corner of sections 10, 11, 14 and 15.

Reestablishment of the Survey Executed by
J. Gorkinski in 1872.

N. 1° 29.3' W., between sections 10 and 11.

40.664

The 1/4 section corner of sections 10 and 11, monumented with a quartzite stone, 14x12x6 inches, plainly marked with 1/4 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 in diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
1/4
S 10 | S 11
2005

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 57.0' W., beginning new measurement.

40.620 The corner of sections 2, 3, 10 and 11, monumented at the corner of fences, bears north, south and west, no marked stone was found. This point is accepted as the best available evidence of the original corner position.

At the corner point, on the east side of fence corner

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	R 12 W
S 3	S 2
S 10	S 11
2005	

From this corner, the 1/4 section corner of sections 2 and 3, bears N. 1°15.7' W., 40.669 chains distance, monumented with a quartzite stone, 18x12x6 inches, firmly set and plainly marked 1/4 on west face. Not remonumented.

From the corner of sections 3, 4, 33 and 34 on the south boundary of the township, hereinbefore described.

N. 0° 46.1' W., between sections 33 and 34.

20.172 Point for the S 1/16 section corner of sections 33 and 34.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	R 12 W
S 1/16	
S 33	S 34
2006	

40.344 The 1/4 section corner of sections 33 and 34, monumented with a sandstone, 14x12x6 inches, marked with a 1/4 on the north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T 12 N R 12 W
1/4
S 33 | S 34
2005

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 44.4' W., beginning new measurement.

40.156

The corner of sections 27, 28, 33 and 34, monumented with a mound of stone, no marked stone was found. This point is accepted as the best available evidence of the original corner position.

At the corner point (center of the mound of stone)

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
S 28 | S 27
S 33 | S 34
2005

Set a steel fence post alongside the aluminum post.

From the corner of sections 26, 27, 34 and 35.

S. 87° 43.7' W., between sections 27 and 34.

41.379

Point for the 1/4 section corner of sections 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
S 27
1/4———
S 34
2005

Set a steel fence post alongside the aluminum post.

82.758

The corner of sections 27, 28, 33 and 34.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 43.8' W., between sections 27 and 28.

40.129 The 1/4 section corner of sections 27 and 28, monumented with a lava stone, 18x12x6 inches, dimly marked 1/4, in a small mound of stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 8 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T 12 N	R 12 W
1/4	
S 28	S 27
2005	

Deposit the marked stone alongside the aluminum post.

N. 0° 45.0' W., beginning new measurement.

40.269 The corner of sections 21, 22, 27 and 28, monumented with a lava stone, 9x7x6 inches, in a small mound of stone, marked with 3 notches on the east and 2 notches on the south edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground to bedrock, in a mound of stone, 3 ft. base to top of aluminum cap marked:

T 12 N	R 12 W
S 21	S 22
S 28	S 27
2005	

Set a steel fence post alongside the aluminum post.

From the corner of sections 22, 23, 26 and 27.

S. 87° 26.9' W., between sections 22 and 27.

41.190 Point for the 1/4 section corner of sections 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 6 ft. base to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T 12 N R 12 W
S 22
1/4-----
S 27
2009

Corner is located on a gentle east slope.

82.380 The corner of sections 21, 22, 27 and 28.

N. 0° 11.1' W., between sections 21 and 22.

41.374 Point for the 1/4 section corner of sections 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
1/4
S 21 | S 22
2006

82.748 The corner of sections 15, 16, 21 and 22, monumented with a lava stone, 13x8x8 inches in a small mound of stone, marked with 3 notches on the east and south edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 3 ft. base to top of aluminum cap marked:

T 12 N R 12 W
S 16 | S 15
S 21 | S 22
2005

Deposit the marked stone alongside the aluminum post.

From the corner of sections 14, 15, 22 and 23.

S. 89°02.2' W., between sections 15 and 22.

40.954 Point for the 1/4 section corner of sections 15 and 22, at proportionate distance, there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 5 feet base to top of aluminum cap marked:

T 12 N R 12 W
S15
1/4 —————
S22
2005

Corner is located on a northeast slope on rocky ground.

81.908 The corner of sections 15, 16, 21 and 22.

From the corner of sections 10, 11, 14 and 15.

S. 89° 55.0' W., between sections 10 and 15.

40.211 The 1/4 section corner of sections 10 and 15, monumented with a lava stone, 14x14x5 inches, dimly marked 1/4, in a small mound of stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
S 10
1/4 —————
S 15
2005

Raise a mound of stone, 3 ft. base, 2 ft. high, north of aluminum post.

S. 88° 58.6' W., beginning new measurement.

40.637 The corner of sections 9, 10, 15 and 16, monumented with a lava stone, 13x8x8 inches, in a small mound of stone, with 3 notches on the east and 4 notches on the south edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 3 ft. base to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T 12 N	R 12 W
S 9	S 10
S 16	S 15
2005	

Deposit the marked stone alongside the aluminum post.

From the corner of sections 4, 5, 32 and 33 on the south boundary of the township, hereinbefore described.

N. 0° 38.3' W., between sections 32 and 33.

40.496

Point for the 1/4 section corner of sections 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 6 ft. base to top of aluminum cap marked:

T 12 N	R 12 W
1/4	
S 32	S 33
2005	

Set a steel fence post alongside the aluminum post.

A north and south fence line bears west, 92.4 links distance.

80.992

Point for the corner of sections 28, 29, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	R 12 W
S 29	S 28
S 32	S 33
2005	

Set a steel fence post alongside the aluminum post.

From the corner of sections 27, 28, 33 and 34.

N. 89° 31.0' W., between sections 28 and 33.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.037

Point for the 1/4 section corner of sections 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
S 28
1/4 —————
S 33
2006

80.074

The corner of sections 28, 29, 32 and 33.

N. 0° 42.9' W., between sections 28 and 29.

40.497

Point for the 1/4 section corner of sections 28 and 29, at proportionate distance; There is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
1/4
S 29 | S 28
2005

Set a steel fence post alongside the aluminum post.

80.994

Point for the corner of sections 20, 21, 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
S 20 | S 21
S 29 | S 28
2005

Set a steel fence post alongside the aluminum post.

From the corner of sections 21, 22, 27 and 28.

N. 89° 05.4' W., between sections 21 and 28.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.017

Point for the 1/4 section corner of sections 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	R 12 W
S 21	
1/4	—————
S 28	
2005	

Set a steel fence post alongside the aluminum post.

80.034

The corner of sections 20, 21, 28 and 29.

N. 0° 30.4' W., between sections 20 and 21.

40.495

Point for the 1/4 section corner of sections 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	R 12 W
1/4	
S 20	S 21
2005	

Set a steel fence post alongside the aluminum post.

80.990

The corner of sections 16, 17, 20 and 21, monumented with a lava stone, 11x8x6 inches, in a small mound of stone, marked with 4 notches of the east and 3 notches on the south edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 20 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 3 ft. base to top of aluminum cap marked:

T 12 N	R 12 W
S 17	S 16
S 20	S 21
2005	

Deposit marked stone alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the aluminum post.

From this corner, a fence corner, with fences projecting north, south and west, bears N. 13° 09.1' W., 2.000 chains distance.

From the corner of sections 5, 6, 31 and 32 on the south boundary of the township, hereinbefore described.

N. 0° 40.6' W., between sections 31 and 32.

39.951

Point for the 1/4 section corner of sections 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	R 12 W
1/4	
S 31	S 32
2005	

Set a steel fence post alongside the aluminum post.

Corner is located in a reseeded area.

79.902

The corner of sections 29, 30, 31 and 32, monumented with a lava stone, 13x8x6 inches, marked with 5 notches on the east and 1 notch on the south edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum post marked:

T 12 N	R 12 W
S 30	S 29
S 31	S 32
2005	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From the corner of sections 28, 29, 32 and 33.

N. 89° 51.4' W., between sections 29 and 32.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

39.985

Point for the 1/4 section corner of sections 29 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
S 29
1/4 —————
S 32
2005

Set a steel fence post alongside the aluminum post.

Corner is located in a reseeded area.

79.970

The corner of sections 29, 30, 31 and 32.

S. 89° 38.7' W., between sections 30 and 31.

40.056

Point for the 1/4 section corner of sections 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
S 30
1/4 —————
S 31
2005

Set a steel fence post alongside the aluminum post.

80.162

The corner of sections 25, 30, 31 and 36 on the west boundary of the township, hereinbefore described.

From the corner of sections 29, 30, 31 and 32.

N. 0° 50.0' W., between sections 29 and 30.

8.138

Point selected for the witness point of sections 29 and 30, at proportionate distance, based on the Warranty Deed dated April 8, 1971, recorded with the Box Elder County Recorder April 16, 1971, Recorders No. 26489H, in book 231, page 558.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

W P
T 12 N R 12 W
S 30 | S 29
2006

Set a steel fence post alongside the aluminum post.

20.346 Point for the S 1/16 section corner of sections 29 and 30.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
S 1/16
S 30 | S 29
2006

Set a steel fence post alongside the aluminum post.

40.692 Point for the 1/4 section corner of sections 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
1/4
S 30 | S 29
2005

Set a steel fence post alongside the aluminum post.

Corner is located in a reseeded area.

81.384 The corner of sections 19, 20, 29 and 30, monumented with a 1/2 inch rebar, at the corner of a new fence line that bears north and west. This rebar is accepted as a careful and faithful determination of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T 12 N	R 12 W
S 19	S 20
S 30	S 29
2005	

Set the 1/2 inch rebar alongside the aluminum post.

From the corner of sections 20, 21, 28 and 29.

N. 89° 34.7' W., between sections 20 and 29.

40.063

Point for the 1/4 section corner of sections 20 and 29, at proportion distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	R 12 W
S 20	
1/4	—————
S 29	
2005	

Set a steel fence post alongside the aluminum post.

80.126

The corner of sections 19, 20, 29 and 30.

S 89° 01.4' W., between sections 19 and 30.

39.600

Point for the 1/4 section corner of sections 19 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	R 12 W
S 19	
1/4	—————
S 30	
2006	

A rebar of unknown origin, 18 inches long, 3/8 diameter, was found at this point.

Deposit rebar alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

79.101

The corner of sections 19, 24, 25 and 30 on the west boundary of the township, hereinbefore described.

From the corner of sections 19, 20, 29 and 30.

N. 0° 45.8' W., between sections 19 and 20.

40.322

Point for the 1/4 section corner of sections 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	R 12 W
1/4	
S 19	S 20
2005	

A rebar of unknown origin, 18 inches long, 3/8 inch diameter, was found at this point. Deposit rebar alongside the aluminum post.

80.644

The corner of sections 17, 18, 19 and 20, monumented with a cobble stone, 8x4x3 inches, plainly marked with 5 notches on the east and 3 notches on the south edges, located at the corner of fences bearing north, south and east.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N	R 12 W
S 18	S 17
S 19	S 20
2005	

Deposit cobble stone alongside the aluminum post.

From the corner of sections 16, 17, 20 and 21.

N. 89° 49.7' W., between sections 17 and 20.

40.232

Point for the 1/4 section corner of sections 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
S 17
1/4 -----
S 20
2005

An east and west fence line bears north, 98.5 links distance.

80.464 The corner of sections 17, 18, 19 and 20.

The Subdivision of Section 30,
T. 12 N., R. 12 W., Salt lake Meridian, Utah

From the 1/4 section corner of sections 30 and 31.

N. 0° 31.1' W., on the N-S centerline of section 30.

8.097 Point selected for the witness point on the N - S centerline of section 30, at proportionate distance, based on the Warranty Deed dated April 8, 1971, recorded with the Box Elder County Recorder April 16, 1971, Recorders No. 26489H, in book 231, page 558.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

W P
T 12 N R 12 W
C
| S 30
C
2006

20.243 Point for the center S 1/16 section corner of section 30.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
C
S 1/16 | S 30
C
2006

40.486 Point for the center 1/4 section corner of section 30, at intersection with the E - W centerline.

THE SUBDIVISION OF SECTION 30,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
C 1/4
S 30
2006

Set a steel fence post alongside the aluminum post.

80.954 The 1/4 section corner of sections 19 and 30.

From the 1/4 section corner of sections 29 and 30.

S. 89° 21.0' W., on the E - W centerline of section 30.

39.828 The center 1/4 section corner of section 30.

79.656 The 1/4 section corner of sections 25 and 30 on the west boundary of the township, hereinbefore described.

From the S 1/16 section corner of sections 29 and 30.

S. 89° 29.9' W., on the E - W centerline of the SE 1/4 of section 30.

39.941 The center S 1/16 section corner of section 30.

From the witness point between sections 29 and 30.

S. 89° 35.2' W., on the lot line between witness points in section 30.

40.010 The witness point on the N - S centerline of section 30.

The Subdivision of Section 31,
T. 12 N., R. 12 W., Salt Lake Meridian, Utah

From the 1/4 section corner of section 31 only, on the south boundary of the township, hereinbefore described.

N. 0° 42.1' W., on the N - S centerline of section 31.

40.053 Point for the center 1/4 section corner of section 31, at intersection with the E - W centerline.

THE SUBDIVISION OF SECTION 31,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
C 1/4
S 31
2006

62.589 Point for the center S-S-N-N 1/1024 section corner of section 31.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
C
C-S-S-N-N | S 31
1/1024 |
C
2006

80.117 The 1/4 section corner of sections 30 and 31.

From the 1/4 section corner of sections 31 and 32.

S. 89° 28.7' W., on the E - W centerline of section 31.

40.041 The center 1/4 section corner of section 31.

80.154 The 1/4 section corner of sections 31 and 36 on the west boundary of the township, hereinbefore described.

From the center S-S-N-N 1/1024 section corner of section 31.

S. 89° 34.3' W., on the E - W centerline of the S 1/2 of the S 1/2 of the N 1/2 of the NW 1/4 of section 31.

40.109 The S-S-N-N 1/1024 section corner of sections 31 and 36 on the west boundary of the township, hereinbefore described.

The Subdivision of Section 33,
T. 12 N., R. 12 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 4 and 33 on the south boundary of the township, hereinbefore described.

N. 0° 31.7' W., on the N - S centerline of section 33.

THE SUBDIVISION OF SECTION 33,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

20.306 Point for the center S 1/16 section corner of section 33, not monumented.

40.612 Point for the center 1/4 section corner of section 33, at intersection with the E - W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T 12 N R 12 W
C 1/4
S 33
2006

80.936 The 1/4 section corner of sections 28 and 33.

From the 1/4 section corner of sections 33 and 34.

N. 89° 45.6' W., on the E - W centerline of section 33.

20.094 Point for the center E 1/16 section corner of section 33.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T 12 N R 12 W
E 1/16
C ——— C
S 33
2006

40.188 The center 1/4 section corner of section 33.

80.148 The 1/4 section corner of sections 32 and 33.

From the point for the E 1/16 section corner of sections 4 and 33 on the south boundary of the township, hereinbefore described.

N. 0° 38.9' W., on the N - S centerline of the SE 1/4 of section 33.

20.239 Point for the SE 1/16 section corner of section 33, at intersection with the E - W centerline of the SE 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

THE SUBDIVISION OF SECTION 33,
T. 12 N., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T 12 N R 12 W
SE 1/16
S 33
2006

40.478 The center E 1/16 section corner of section 33.

From the S 1/16 section corner of sections 33 and 34.

N. 89° 57.2' W., on the E - W centerline of the SE 1/4 of section 33.

20.137 The SE 1/16 section corner of section 33.

40.274 The point for the center S 1/16 section corner of section 33.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
M. Ross Workman Glen B. Hatch	Supervisory Cadastral Surveyor Cadastral Surveyor

CERTIFICATE OF SURVEY

I, *Ronald K. Baugh*, *Supervisory Cadastral Surveyor*, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing the date of the *3rd day of October, 2005*, have *dependently resurveyed the south boundary, a portion of the east and west boundaries, a portion of the subdivisional lines, and subdivided sections 30, 31 and 33, in Township 12 North, Range 12 West*, of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions of the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Nov. 30, 2009

Date

Ronald K. Baugh
(Supervisory Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of the south boundary, a portion of east and west boundaries, portion of the subdivisional lines, and the subdivision of sections 30, 31 and 33, in Township 12 North, Range 12 West, Salt Lake Meridian, Utah*, executed by *Ronald K. Baugh*, *Supervisory Cadastral Surveyor*, having been critically examined and found correct, are hereby approved.

December 15, 2009

Date

Daniel W. Webb

(Chief Cadastral Surveyor for Utah)