

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE WEST BOUNDARY OF

TOWNSHIP 31 SOUTH RANGE 6 WEST,

A PORTION OF THE SOUTH AND WEST BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES,

AND THE SUBDIVISION OF SECTIONS 11, 12, AND 31

IN

TOWNSHIP 31 SOUTH, RANGE 7 WEST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

C. Scott Bishop
Cadastral Surveyor

Under special instructions dated **October 31, 2005**, approved **October 31, 2005**, which provided for the surveys included under Group Number **1013**, and assignment instructions dated **October 31, 2005**.

Survey commenced **November 15, 2005**
Survey completed **May 13, 2006**

INDEX DIAGRAM

Township 31 South, Range 7 West

6	5	4	3 23	2 18	1 14	9
7	8	9 28	22 10 21	17 11 17	13 12 11	7
18	17	28 16 27	21 15 20	16 14	13	
19	20 32	26 21 26	20 22	23	24	
10 30 30	31 29 30	25 28 24	19 27	26	25	
9 31 5	28 32 4	23 33 3	18 34	35	36	

The subdivision of section 11..... 32
 The subdivision of section 12..... 34
 The subdivision of section 31..... 37

TOWNSHIP 31 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

The following field notes are those of the dependent resurvey of a portion of the west boundary of T. 31 S., R. 6 W., a portion of the south and west boundaries, a portion of the subdivisional lines, and the subdivision of sections 11, 12, and 31, in T. 31 S., R. 7 W., Salt Lake Meridian, Utah.

History of Surveys

	Surveyed by		Retr. or Resurveyed by	
SOUTH BOUNDARY				
Portion	J. Gorlinski	1871		
Portion	J.R. & Q. Stewart	1910	J.R. & Q. Stewart	1910
Portion			L.V. Judd	1997
EAST BOUNDARY				
All	J.R. & Q. Stewart	1910		
WEST BOUNDARY				
Portion	J. Gorlinski	1871		
All	T.C. Bailey	1881	T.C. Bailey	1881
Portion			J.R. & Q. Stewart	1910
NORTH BOUNDARY (Sixth Standard Parallel South)				
Portion	J. Bausman	1869		
All	T.C. Bailey	1881	T.C. Bailey	1881
All			J.R. & Q. Stewart	1910
Portion			R.C. Yundt	1950
Portion			L.V. Judd	2003
SUBDIVISION				
Portion	J. Gorlinski	1871		
Portion	J.R. & Q. Stewart	1910	J.R. & Q. Stewart	1910

PRIVATE SURVEYS

A survey was executed by Jay Adams in sections 31 and 32, with plat dated July 22, 2005.

A survey was executed by Ralph Watson in section 31, with plat dated March 23 1990.

CHAINS

This survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1013, dated October 31, 2005.

The direction of the lines was determined by references to true meridians, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards and Guidelines for Cadastral Surveys Using GPS Methods*, dated May 9, 2001, Version 1.0. Trimble model 5700 GPS receivers were used for field collection. Cadastral Measurement Management (CMM) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and their calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic Control was derived from National Geodetic Survey Cooperative Base Network Control Station "EXTRA", with the published data as follows:

Latitude: 38°00'25.30326" N. Longitude: 112°30'57.87475 W.
NAD 1983 (1994) Elev. 7114 Feet N.A.V.D. 88

The geographic position of the corner of sections 3, 4, 33, and 34, Townships 31 and 32 South, Range 7 West, determined by using RTK methods from National Geodetic Survey Cooperative Base Network Control Station "EXTRA" is as follows:

Latitude: 38°03'29.810" N. Longitude: 112°38'43.664" W. NAD 83
Elev. 6396 Feet

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the South Boundary,
T. 31 S., R. 7 W., Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by
J. Gorlinski in 1871.

Beginning at the corner of sections 3, 4, 33, and 34,
monumented with an iron post, 3 inches diameter, firmly set in
a mound of stone 3 ft. base, to the top, with brass cap marked
as described in the official record of the survey executed by
J.R. & Q. Stewart in 1910.

from which the 1910 bearing trees

A cedar, 12 ins. diam., bears N. 60° E., 69 links distance,
with a healed blaze.

A cedar, 14 ins. diam., bears N. 80° W., 77 links distance,
with a mostly healed blaze.

Corner falls on top of ridge bearing northwest and southeast
in piñon and juniper growth.

N. 89°52.1' W., between sections 4 and 33.

40.399

The 1/4 section corner of sections 4 and 33, monumented with a
granite stone, 12x10x8 inches, loosely set, clearly marked 1/4
on north face.

At the corner point

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 28
inches in the ground, with aluminum cap marked:

T31SR7W
S33
1/4 —
S4
T32S
2006

Deposited the marked stone alongside the aluminum post.

Deposited a magnet enclosed in a clear plastic case at the
base of the aluminum post.

Raised a mound of stone 3 ft. by 3 ft. base, by 3 ft. high,
north of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground in scattering piñon and juniper
growth, and 32 ft. east of the east edge of a dirt road bears

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 66° W. and S. 46° W., and 29 ft. west of the centerline of dirt road bears N. 10° E. and S. 10° W.

N. 89°54.5' W., beginning new measurement.

- 40.007** The corner of sections 4, 5, 32, and 33, monumented with a trachyte stone, 16x8x6 inches, clearly marked with 4 notches on two edges, lying loose with marks up. (Record; 4 notches on east and 2 notches on west edges)

At the corner point

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T31SR7W
S32 S33
S5 S4
T32S
2006

Deposited the marked stone alongside the aluminum post.

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raised a mound of stone 3 ft. by 3 ft. base, by 2 ft. high, north of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on rolling ground in sagebrush.

S. 89°13.5' W., between sections 5 and 32.

- 40.078** The 1/4 section corner of sections 5 and 32, monumented with a trachyte stone, 24x18x14 inches, firmly set, clearly marked 1/4 on north face, with a steel fence post alongside.

At the corner point

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T31SR7W
S32
1/4 —
S5
T32S
2006

Deposited the marked stone alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raised a mound of stone 3 ft. by 2 ft. base, by 2 ft. high, north of the aluminum post.

Corner falls at the base of a gentle north slope.

S. 89°51.1' W., beginning new measurement.

40.017

The corner of sections 5, 6, 31, and 32, monumented with a blue sandstone, 9x9x9 inches, lying loose, clearly marked 3 notches, with no other marks visible, alongside a 3/4 inch diameter rebar, 26 inches long, with no cap attached, in a small mound of stone, with a steel fence post alongside. This monument is faithfully accepted as a careful determination of the original corner position.

At the corner point

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

T31SR7W
S31|S32
S6|S5
T32S
2006

Deposited the marked stone alongside and rebar inside the aluminum post.

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raised a small mound of stone north of the aluminum post.

Corner falls on flat ground.

S. 89°47.6' W., between sections 6 and 31.

20.100

Point for the E 1/16 section corner of sections 6 and 31.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

S31
E 1/16 —
S6
2006

Deposited a magnet enclosed in an orange case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner falls on flat ground in sagebrush.

- 40.200** The 1/4 section corner of sections 6 and 31, monumented with a trachyte stone, 18x10x6 inches, firmly set, clearly marked 1/4 on north face, with a steel fence post and rotted off cedar post alongside.

At the corner point

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 30 inches in the ground, with aluminum cap marked:

T31SR7W
S31
1/4 —
S6
T32S
2006

Deposited the marked stone alongside the aluminum post.

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Corner falls in flat pasture land.

S. 89°43.9' W., beginning new measurement.

- 40.278** The corner of Townships 31 and 32 South, Ranges 7 and 8 West, monumented with an aluminum post, 2 1/2 inches diameter, projecting 2 inches above ground, with aluminum cap marked as described in the official record of the resurvey executed by L.V. Judd in 1997, with a small mound of stone to the west.

Corner falls on flat ground.

From this corner, a rebar, 5/8 inch diameter, with no cap attached, bears east, 0.55 ft. distance.

Dependent Resurvey of a Portion of the West Boundary
T. 31 S., R. 6 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
J.R. & Q. Stewart in 1910.

From the corner of sections 7 and 18, monumented with an iron post, 2 inches diameter, firmly set in a mound of stone 3 ft. base, with the brass cap incorrectly marked common for sections 7, 12, 13, and 18. Removed the marks pertaining to sections 12 and 13, and add the date 2006 to the brass cap.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY
T. 31 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

from which the 1910 bearing trees

A juniper, 20 ins. diam., bears N. 58° E., 96 links distance, scribed T31S R6W S17 BT, on a partially healed blaze.

A juniper, 12 ins. diam., bears S. 41° E., 42 links distance, scribed T31S R6W S18 BT, on a partially healed blaze. (Record; S. 51° E.)

Corner falls on a gradual east slope in piñon and juniper.

N. 0°21.2' E., on the west boundary of section 7 Township 31 South, Range 6 West.

- 10.357** True point for the closing corner of sections 12 and 13 only, Township 31 South, Range 7 West, hereinafter described.
- 30.287** Point for the S 1/16 section corner of section 12 only, Township 31 South, Range 7 West, not monumented.
- 39.999** The 1/4 corner of section 7 only, monumented with a iron post, 1 inch diameter, firmly set in a mound of stone 3 ft. base, to top, with the brass cap incorrectly marked common for sections 7 and 12, Removed the marks S12 and add the date 2006 to the brass cap.

from which the 1910 bearing tree

A piñon, scribed 1/4 S7 BT, was found down and dead, not remeasured.

A piñon, 10 ins. diam., not of record, with faint scribe marks on a mostly healed blaze, was found down and dead, not remeasured.

Corner falls on flat ground in piñon and juniper growth, and 20 ft. east of a wood road bears north and south.

N. 0°31.8' W., beginning new measurement.

- 10.217** Point for the 1/4 section corner of section 12 only, Township 31 South, Range 7 West.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to solid rock, in a mound of stone 5 ft. base, to top, with aluminum cap marked:

T31S
R7W R6W
1/4 |
S12 |
2006

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY
T. 31 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside aluminum post.

Corner falls on a steep east slope in piñon and juniper growth.

20.026 Point for the N 1/16 section corner of section 7 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, in a mound of stone 3 ft. base, to top, with aluminum cap marked:

| N 1/16
| S7
2006

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Corner falls on a steep rocky east slope in piñon and juniper.

30.147 Point for the N 1/16 section corner of section 12 only, Township 31 South, Range 7 West.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

N 1/16 |
S12 |
2006

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

A steel fence post bears west, 3 ft. from the aluminum post.

Raised a small mound of stone west of the aluminum post.

Corner falls on a gradual slope in sagebrush and scattering piñon and juniper growth, 9 ft. west of drainage drains N. 30° W.

39.694 The monumented witness corner of sections 6 and 7 only, monumented with an iron post, 3 inches diameter, firmly set in a mound of stone 3 ft. base, to top, with the brass cap incorrectly marked common for sections 1, 6, 7, and 12. Removed the marks S7 and S12, and add the date 2006 to the brass cap.

from which the 1910 bearing tree

A piñon, 20 ins. diam., bears N. 14° E., 159 links distance, dead and standing, scribed WC T31S R BT visible. (Record; N. 3° E., 163 links)

Set a steel fence post alongside the iron post.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY
T. 31 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner falls 35 ft. south of Fremont Wash 20 ft. wide by 5 ft. deep, drains northwest.

N. 0°35.5' E., beginning new measurement.

0.359 True point for the corner of sections 6 and 7 only, not monumented.

N. 0°35.5' E., on the west boundary of section 6 Township 31 South, Range 6 West.

8.328 True point for the closing corner of sections 1 and 12 only, Township 31 South, Range 7 West, hereinafter described.

39.931 The 1/4 section corner of section 6 only, monumented with an iron post, 1 inch diameter, firmly set in a mound of stone 3 ft. base, to top, with the brass cap incorrectly marked common for sections 1 and 6. Removed the marks S1 and add the date 2006 to the brass cap.

from which the 1910 bearing tree

A piñon, 12 ins. diam., bears N. 64° W., 58 links distance, scribed 1/4 S1 BT. (Record 46 links)

Dependent Resurvey of a Portion of the West Boundary,
T. 31 S., R. 7 W., Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by
J. Gorlinski in 1871, and the Resurvey
Executed by T.C. Bailey in 1881.

From the corner Townships 31 and 32 South, Ranges 7 and 8 West, hereinbefore described.

N. 0°08.5' W., between sections 31 and 36.

40.281 The 1/4 section corner of sections 31 and 36, monumented with a granite stone, 15x9x6 inches, firmly set, plainly marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T31S
R8W R7W
1/4
S36|S31
2006

Deposited the marked stone alongside the aluminum post.

Corner falls in a sagebrush flat, in a fence corner projecting north, east, and south.

N. 0°12.7' W., beginning new measurement.

20.368 Point for the N 1/16 section corner of sections 31 and 36, not monumented.

40.736 Point for the corner of sections 25, 30, 31, and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T31S
R8W R7W
S25|S30
S36|S31
2006

Deposited a magnet enclosed in an orange case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls in sagebrush and on the east edge of a dirt road, 9 ft. wide bears north and south, and 1.5 ft. west of a fence line bears north and south.

N. 0°12.7' W., between sections 25 and 30.

40.736 The 1/4 section corner of sections 25 and 30, monumented with a lava stone 12x9x5 inches, firmly set, plainly marked 1/4 on west face, in a small mound of stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, on top of solid rock, in a mound of stone 3 foot base, to top, with aluminum cap marked:

T31S
R8W R7W
1/4
S25|S30
2006

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposited the marked stone alongside the aluminum post.

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Corner is located on top of ridge bears north and south.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 31 S., R. 7 W., Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by
J.R. & Q. Stewart in 1910.

From the corner of sections 11, 12, 13, and 14, monumented with an iron post, 2 inches diameter, firmly set in a mound of stone 4 ft. base, to top, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910.

from which the 1910 bearing trees

A juniper, 12 ins. diam., bears N. 17° E., 18 links distance, scribed T31S R7W S12 BT, on a partially healed blaze. (Record; N. 23° E.)

A piñon, 10 ins. diam., bears S. 10° W., 12 links distance, with no visible scribe marks on a partially healed blaze. (Record; S. 3°30' W., 22 links)

A juniper, 12 ins. diam., bears N. 50° W., 47 links distance, scribed T31S R7W S11 BT, on a partially healed blaze.

No remaining evidence of the SE bearing tree was found.

Found a granite stone, 16x8x6 inches, lying loose 3 ft. east of the iron post, clearly marked 4 notches and 1 notch. I deposit marked stone alongside the iron post.

Corner falls on a gradual east slope in piñon and juniper, at bottom of drainage, drains north.

S. 89°50.5' E, between sections 12 and 13.

39.959

The 1/4 section corner of sections 12 and 13, monumented with an iron post, 1 inch diameter, firmly set in a mound of stone 4 ft. base, to top, with brass cap marked as described in the official record of the survey executed by J.R. & Q. Stewart in 1910.

from which the 1910 bearing trees

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

A piñon, 10 ins. diam., bears S. 12° E., 52 links distance, scribed 1/4 S13 BT, on a partially healed blaze. (Record; S. 20° E., 20 links)

A piñon, 12 ins. diam., bears N. 20° W., 20 links distance, with visible scribe marks on a mostly healed blaze. (Record; N. 11° W., 48 links)

Corner falls on a gradual north slope in piñon and juniper growth.

S. 89°50.2' E., beginning new measurement.

19.934 Point for the E 1/16 section corner of sections 12 and 13, not monumented.

43.398 True point for the closing corner of sections 12 and 13 only, at intersection with the west boundary of section 7.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground to solid rock, in a collar of stone, with aluminum cap marked:

	T31S
	R7W R6W
S12 C	
S13 C	
	2006

from which the 1910 bearing trees

A piñon, 12 ins. diam., bears S. 20° E., 5 links distance, with scribe marks visible through a partially healed blaze.

A juniper, 16 ins. diam., bears N. 26° W., 80 links distance, with scribe marks visible through a mostly healed blaze.

Deposited a magnet enclosed in an orange plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground in piñon and juniper.

The original closing corner of sections 12 and 13, monumented with a iron post 2 inches diameter, firmly set in a mound of stone 3 ft. base, to top, with the brass cap marked as described in the official record of the survey executed by J.R. & Q. Stewart in 1910, bears S. 89°50.2' E., 0.139 chains distance

from which the 1910 bearing trees

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

A piñon, 12 ins. diam., bears S. 70° W., 13 links distance, with scribe marks visible through a partially healed blaze. (Record; S. 62°30'W.)

A juniper, 16 ins. diam., bears N. 34° W., 87 links distance, with scribe marks visible through a mostly healed blaze.

Add the marks AM 2006 to the brass cap.

Corner falls on flat ground in piñon and juniper.

Reestablishment of the Survey Executed by
J. Gorkinski in 1871, and the Resurvey
Executed by J.R. & Q. Stewart in 1910.

From the corner of sections 11, 12, 13, and 14.

N. 0°38.0' W., between sections 11 and 12.

19.933 Point for the S 1/16 section corner of sections 11 and 12.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

S 1/16
S11|S12
2006

Deposited a magnet enclosed in an orange case at the base of the aluminum post.

Raised a small mound of stone west of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground in sagebrush.

39.866 The 1/4 section corner of sections 11 and 12, monumented with an iron post, 1 inch diameter, firmly set in a mound of stone 3 ft. base, to top, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910.

from which the 1910 bearing trees

A juniper, 10 ins. diam., bears N. 20° E., 109 links distance, with no scribe marks visible on an open blaze. (Record; N. 16° E.)

A juniper, 12 ins. diam., bears N. 10° W., 134 links distance, scribed 1/4 S, on an open blaze. (Record; N. 20° W., 102 links)

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner falls on flat ground in piñon and juniper.

N. 2°19.9' W., beginning new measurement.

- 38.471** The corner of sections 1, 2, 11, and 12, monumented with an iron post, 2 inches diameter, firmly set in a mound of stone 3 ft. base, to top, with brass cap incorrectly marked. I remark the cap to read:

T31SR7W
S2 | S1
S11 | S12
2006

Set a steel fence post alongside the iron post.

Corner falls on a steep west slope.

Reestablishment of the Survey Executed by
J.R. & Q. Stewart in 1910.

N. 89°43.4' E., between sections 1 and 12.

- 40.337** The 1/4 section corner of section 1 only, monumented with an iron post, 1 inch diameter, firmly set in a mound of stone 3 ft. base, to top, with the brass cap incorrectly marked common for sections 1 and 12. Removed the marks S12 and add the date 2006 to the brass cap.

There is no remaining evidence of either bearing tree.

Set a steel fence post alongside the iron post.

Corner falls on flat ground, in a fence corner projecting N. 70° E., and south.

S. 89°05.5' E., beginning new measurement.

- 1.734** Point for the 1/4 section corner of section 12 only.

Set an aluminum post, 30 inches long, 2 1/12 inches diameter, 24 inches in the ground, in a mound of stone 3 ft. base, to top, with aluminum cap marked:

T31SR7W
1/4 S12
2006

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Set a cedar post 6 ins. diam., alongside aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner falls on flat ground in sagebrush, and 2 ft. south of a fence line bears east and west.

21.440 Point for the E 1/16 section corner of section 12 only, not monumented.

44.772 The monumented closing corner of sections 1 and 12 only, monumented with a brown lava stone, 14x10x8 inches, loosely set, in a mound of stone, clearly marked 4 notches on south and 1 notch on north edges, with CC on west face. (Record; 2 inches diameter iron post.)

from which the bearing trees not of record

A juniper limb, 8 ins. diam., bears S. 14° W., 10 links distance, scribed T31S R7W S12 BT, on a partially healed blaze.

A piñon, 6 ins. diam., with no visible scribe marks on a partially healed blaze, down and dead, not remeasured.

I add the marks AM to the marked stone and bury in place.

44.922 True point for the closing corner of sections 1 and 12 only, at intersection of the west boundary of section 6.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground to solid rock, in a mound of stone 3 ft. base, to top, with aluminum cap marked:

	T31S
	R7W R6W
S1	C
S12	C
	2006

from which a bearing tree not of record

A juniper limb, 8 ins. diam., bears S. 36° W., 20 links distance, scribed T31S R7W S12 BT, on a partially healed blaze.

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on a gradual southwest slope, 28 ft. west of wash, drains S. 30° E.

Reestablishment of the Survey Executed by
J. Gorkinski in 1871, and the Resurvey
Executed by J.R. & Q. Stewart in 1910.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 14, 15, 22, and 23, monumented with an iron post, 2 inches diameter, firmly set in a small mound of stone, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910.

from which the 1910 bearing trees

A juniper, 12 ins. diam., bears N. 48° E., 93 links distance, with a healed blaze. (Record; N. 42° E.)

A juniper, 12 ins. diam., bears S. 8° E., 132 links distance, with a healed blaze.

A juniper, 12 ins. diam., bears S. 73° W., 92 links distance, with a healed blaze. (Record; S. 70° W.)

A juniper, 10 ins. diam., bears N. 32° W., 263 links distance, with visible scribe marks on a partially healed blaze.

Set a steel fence post alongside the iron post.

Corner falls in piñon and juniper growth.

From this corner, National Geodetic Survey Cooperative Base Network Station "EXTRA" monumented with a standard disk stamped EXTRA 1938, cemented in a rock, bears, S. 43°04.0' E. (FWD), N. 42°59.9' W. (REV), 716.502 chains distance.

N. 0°00.8' W., between sections 14 and 15.

40.039

The 1/4 section corner of sections 14 and 15, monumented with an iron post, 1 inch diameter, firmly set in a mound of stone 3 ft. base, to top, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910.

Set a steel fence post alongside the iron post.

Corner falls in sagebrush flat.

N. 0°01.7' W., beginning new measurement.

43.805

The corner of sections 10, 11, 14, and 15, monumented with an iron post, 2 inches diameter, firmly set, projecting 14 inches above ground, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910.

Set a steel fence post alongside the iron post.

Corner falls in sagebrush flat.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 11, 12, 13, and 14.

S. 87°21.7' W., between sections 11 and 14.

21.462 The E 1/16 section corner of sections 11 and 12, not monumented.

42.924 The 1/4 section corner of sections 11 and 14, monumented with an iron post, 1 inch diameter, firmly set, projecting 16 inches above ground, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910.

from which the 1910 bearing trees

A piñon, 10 ins. diam., bears N. 17° W., 32 links distance, scribed 1/4 S11 BT. (Record; N. 20° W.)

A piñon, dead and standing, 8 ins. diam., bears S. 23° W., 19 links distance, scribed 1/4 S14 BT. (Record; juniper, S. 20° E.)

Set a steel fence post alongside the iron post.

Corner falls on an east slope in piñon and juniper growth.

WEST, beginning new measurement.

40.104 The corner of sections 10, 11, 14, and 15.

Reestablishment of the Survey Executed
by J. Gorlinski in 1871.

N. 0°59.0' W., between sections 10 and 11.

40.112 The 1/4 section corner of sections 10 and 11, monumented with a trachyte stone, 12x12x10 inches, firmly set, plainly marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

T31SR7W
1/4
S10|S11
2006

Deposited the marked stone alongside the aluminum post.

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Raised a mound of stone 3 ft. by 2 ft. base, by 1 ft. high, west of the aluminum post.

From this corner a 5/8 inch diameter rebar, firmly set, projecting 4 inches above ground, bears N. 21°37' W., 29.1 feet distance.

N. 1°25.5' W., beginning new measurement.

- 40.930** The corner of sections 2, 3, 10, and 11, monumented with an iron post, 2 inches diameter, firmly set in a mound of stone 2 ft. base, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910.

Set a steel fence post alongside the iron post.

Reestablishment of the Survey Executed by
J. Gorkinski in 1871, and the Resurvey
Executed by J.R. & Q. Stewart in 1910.

From the corner of sections 1, 2, 11, and 12.

N. 89°17.0' W., between sections 2 and 11.

- 40.838** The 1/4 section corner of sections 2 and 11, monumented with an iron post, 1 inch diameter, firmly set in a mound of stone 3 ft. base, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910.

from which a bearing tree not of record

A piñon limb, 10 ins. diam., bears S. 80° W., 22 links distance, with an open blaze.

Set a steel fence post alongside the iron post.

Corner falls on flat ground in sagebrush and piñon and juniper growth.

N. 89°40.8' W., beginning new measurement.

- 41.832** The corner of sections 2, 3, 10, and 11.

From the corner of sections 3, 4, 33, and 34, on the south boundary of the township, hereinbefore described.

N. 0°20.2' W., between sections 33 and 34.

- 39.847** The 1/4 section corner of sections 33 and 34, monumented with an iron post, 1 inch diameter, firmly set in a mound of stone 2 ft. base, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Found a trachyte stone, 16x10x6 inches, lying loose alongside the iron post, plainly marked 1/4 on one face, deposited the marked stone in the mound of stone alongside the iron post.

No remaining evidence of the original bearing trees was found.

Corner falls in piñon and juniper growth.

N. 0°32.7' W., beginning new measurement.

- 40.439** The corner of sections 27, 28, 33, and 34, monumented with an iron post, 2 inches diameter, firmly set in a mound of stone 2 ft. base, at the base of a juniper tree, with the north fork 12 inches diameter, with two blazes with illegible scribe marks visible, and the south fork 10 inches diameter scribed BT T3 S3 BT visible, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910. (The 1910 resurvey record states that the tree was destroyed and the iron post was set in its place.)

from which the 1910 bearing trees

A piñon, 18 ins. diam., bears N. 73° E., 43 links distance, with a healed blaze. (Record; N. 77° E., 36 links)

A juniper, 12 ins. diam., bears S. 52° E., 36 links distance, with a mostly healed blaze. (Record; 42 links)

No remaining evidence of the SW or NW bearing trees was found.

N. 0°08.2' W., between sections 27 and 28.

- 39.989** The 1/4 section corner of sections 27 and 28, monumented with an iron post, 1 inch diameter, firmly set in a mound of stone 3 ft. base, to top, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910.

from which the 1910 bearing tree

A juniper, 12 ins. diam., bears N. 79° W., 58 links distance, scribed 1/4 S28 BT on a partially healed blaze. (Record; N. 86° W.)

A piñon, 10 ins. diam., scribed 1/4 S27 BT, was found dead and standing, not remeasured.

Corner falls on top of a hill with a gradual east slope on rocky ground in piñon and juniper.

N. 0°14.5' W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.055

The corner of sections 21, 22, 27, and 28, monumented with an iron post, 2 inches diameter, firmly set in a mound of stone 3 ft. base, to top, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910

Corner falls in a steep north slope in conglomerate rock ledges.

N. $0^{\circ}40.4'$ E., between sections 21 and 22.

40.049

The 1/4 section corner of sections 21 and 22, monumented with an iron post, 1 inch diameter, firmly set in a mound of stone 3 ft. base, to top, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910.

from which the 1910 bearing trees

A piñon, 10 ins. diam., bears S. 59° E., 81 links distance, scribed 1/4 S22 BT.

A piñon, 10 ins. diam., was found down and dead, not remeasured.

Corner falls on a north slope in piñon and juniper growth.

N. $0^{\circ}09.4'$ W., beginning new measurement.

40.040

The corner of sections 15, 16, 21, and 22, monumented with an iron post, 2 inches diameter, loosely set in a mound of stone 3 ft. base, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910

Corner falls on an east slope in the corner of fences projecting north, west, and S. 40° E.

From the corner of sections 14, 15, 22, and 23.

S. $89^{\circ}26.8'$ W., between sections 15 and 22.

39.169

The 1/4 section corner of sections 15 and 22, monumented with an iron post, 1 inch diameter, projecting 14 inches above a scattered mound of stone, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910.

Set a steel fence post alongside the iron post.

Corner falls in sagebrush flat.

S. $89^{\circ}54.3'$ W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

37.029

The corner of sections 15, 16, 21, and 22.

Reestablishment of the Survey Executed
by J. Gorlinski in 1871.

N. 1°38.0' W., between sections 15 and 16.

44.457

The 1/4 section corner of sections 15 and 16 monumented with a granite stone, 14x8x6 inches, firmly set, clearly marked 1/4 on west face. (Record; iron stone)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with the aluminum cap marked:

T31SR7W
1/4
S16|S15
2006

Deposited the marked stone alongside the aluminum post.

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground in sagebrush.

N. 1°35.0' W., beginning new measurement.

39.597

The corner of sections 9, 10, 15, and 16, monumented with an iron post, 2 inches diameter, firmly set, projecting 16 inches above ground, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910.

Corner falls at the top of a northwest slope in piñon and juniper growth, and in the corner of fences projecting south and west.

From the corner of sections 10, 11, 14, and 15.

S. 89°48.5' W., between sections 10 and 15.

39.256

Point for the 1/4 section corner of sections 10 and 15 at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T31SR7W
S10
1/4—
S15
2006

Deposited a magnet enclosed in an orange plastic case at the base of the aluminum post.

Corner falls on barren ground, and 3.6 ft. north of a fence line bearing east and west.

78.512 The corner of sections 9, 10, 15, and 16.

Reestablishment of the Survey Executed by
J. Gorkinski in 1871, and the Resurvey
Executed by J.R. & Q. Stewart in 1910.

N. 4°38.8' W., between sections 9 and 10.

40.693 The 1/4 section corner of sections 9 and 10, monumented with an iron post, 1 inch diameter, firmly set in a mound of stone 3 ft. base, to top, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910.

from which the 1910 bearing trees

A piñon, 16 ins. diam., bears N. 33° E., 11 links distance, with a healed blaze. (Record; N. 20° E.)

A juniper, 20 ins. diam., bears S. 81° W., 54 links distance, with a mostly healed blaze.

Set a steel fence post alongside the iron post.

Corner falls on a gentle northeast slope in piñon and juniper growth.

N. 0°04.8' E., beginning new measurement.

40.093 The corner of sections 3, 4, 9, and 10, monumented with an iron post, 2 inches diameter, firmly set in a mound of stone 3 ft. base, to top, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910.

from which the 1910 bearing tree

A piñon, dead and standing, 10 ins. diam., bears S. 32° E., 25 links distance, scribed T31S R7W S10 BT.
(Record; S. 41° E.)

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

A piñon, 8 ins. diam., was found down and dead, not remeasured.

Set a steel fence post alongside the iron post.

Corner falls in piñon and juniper.

From the corner of sections 2, 3, 10, and 11.

S. 89°25.1' W., between sections 3 and 10.

- 40.009** The 1/4 section corner of sections 3 and 10, monumented with an iron post, 2 inches diameter, firmly set in a mound of stone 3 ft. base, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910.

from which

A piñon, 18 ins. diam., bears S. 65° E., 41 links distance, with a healed blaze. (Record; S. 72° E.)

A piñon, 18 ins. diam., bears N. 14° W., 73 links distance, with a healed blaze.

Corner falls in piñon and juniper growth.

S. 89°40.3' W., beginning new measurement.

- 40.023** The corner of sections 3, 4, 9, and 10.
-

Reestablishment of the Survey Executed
by J. Gorlinski in 1871.

From the corner of sections 4, 5, 32, and 33, on the south boundary of the township, hereinbefore described.

N. 0°34.1' W., between sections 32 and 33.

- 39.762** Point for the 1/4 section corner of sections 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T31SR7W
1/4
S32|S33
2006

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Raised a small mound of stone west of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground in sagebrush.

From this corner, a 5/8 inch diameter rebar, with a yellow cap attached, marked ADAMS SUR PLS 167230, bears N. 9°29'38" E., 17.64 feet distance.

79.524 Point for the corner of sections 28, 29, 32, and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 5 inches in the ground to solid rock, in a mound of stone 4 ft. base, to top, with aluminum cap marked:

T31SR7W
<u>S29</u> <u>S28</u>
S32 S33
2006

Deposited a magnet enclosed in an orange plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on a gradual rocky south slope in scattering juniper.

From this corner a 5/8 inch diameter rebar, with a yellow cap attached, marked ADAMS SUR PLS 167230, bears N. 0°10'20" W., 61.87 feet distance.

From the corner of sections 27, 28, 33, and 34.

S. 89°19.4 'W., between sections 28 and 33.

40.602 The 1/4 section corner of sections 28 and 33, monumented with a lava rock, 12x8x8 inches, firmly set, clearly marked 1/4 on north face. (Record; conglomerate)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T31SR7W
S28
1/4 —
S33
2006

Deposited the marked stone alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Raised a mound of stone 3 ft. by 3 ft. base, by 2 ft. high, north of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground in scattering piñon and juniper growth.

S. 89°49.1' W., beginning new measurement.

39.962 The corner of sections 28, 29, 32, and 33.

N. 2°03.9' E., between sections 28 and 29.

39.786 The 1/4 section corner of sections 28 and 29, monumented with an iron stone, 24x18x18 inches, loosely set, clearly marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, in a mound of stone 3 ft. base, to top, with aluminum cap marked:

T31SR7W
1/4
S29|S28
2006

Deposited the marked stone alongside the aluminum post.

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on a steep rocky west slope.

N. 0°16.2' W., beginning new measurement.

40.406 The corner of sections 20, 21, 28, and 29, monumented with a stationary iron rock, 24x20x20 inches, dimly marked 4 grooves on east and 2 grooves on south faces.

At the corner point on top of rock

Set a 3/4 inch diameter rebar, 10 inches long into drill hole, with attached 3 1/4 inch diameter aluminum cap marked:

T31SR7W
S20|S21
S29|S28
2006

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a mound of stone 4 ft. base around bottom of rock.

Corner falls on a gradual barren rocky west slope in scattering piñon and juniper growth.

From the corner of sections 21, 22, 27, and 28.

S. 89°31.7' W., between sections 21 and 28.

39.701 The 1/4 section corner of sections 21 and 28, monumented with a conglomerate stone, 16x10x6 inches, loosely set, clearly marked 1/4 on north face. (Record; iron stone)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 4 inches in the ground to solid rock, in a mound of stone 6 ft. base, to top, with aluminum cap marked:

T31SR7W
S21
1/4 —
S28
2006

Deposited the marked stone alongside the aluminum post.

Deposited a magnet enclosed in an orange plastic case at the base of the aluminum post.

Corner falls on a gradual rocky east slope in piñon and juniper growth.

S. 89°46.2' W., beginning new measurement.

39.336 The corner of sections 20, 21, 28, and 29.

N. 1°23.3' W., between sections 20 and 21.

41.270 The 1/4 section corner of sections 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with aluminum cap marked:

T31SR7W
1/4
S20|S21
2006

Deposited a magnet enclosed in an orange plastic case at the base of the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post 0.5 ft. east, and a wood post alongside the aluminum post.

Corner falls in the I-15 R.O.W. and 32.2 ft west of I-15 R.O.W. fence, bears N. 50° E., and S. 50° W.

- 82.540** The corner of sections 16, 17, 20, and 21, monumented with an iron post, 2 inches diameter, firmly set in a small mound of stone, projecting 4 inches above mound, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910.

Corner falls on flat ground in sagebrush at the corner of fences projecting north and east.

From the corner of sections 15, 16, 21, and 22.

N. 88°37.9' W., between sections 16 and 21.

- 40.702** Point for the 1/4 section corner of sections 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T31SR7W
S16
1/4 ———
S21
2006

Deposited a magnet enclosed in an orange plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground in sagebrush, and 15 ft. north of a fence line, bears east and west.

From this corner, a Right-of-Way marker, a 2 inch diameter iron post, firmly set in concrete, marked C/L 264.69 sta. 2917+42.16 elev. 6066.73 1981, bears east, 16 inches distance.

- 81.404** The corner of sections 16, 17, 20, and 21.

Reestablishment of the Survey Executed by
J. Gorkinski in 1871, and the Resurvey
Executed by J.R. & Q. Stewart in 1910.

N. 1°03.0' W., between sections 16 and 17.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

41.408

The 1/4 section corner of sections 16 and 17, monumented with an iron post, 1 inch diameter, firmly set in a mound of stone 4 ft. base, to top, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910.

Corner falls on a gentle southwest slope in sagebrush, and in a fence line bears north and south.

N. 0°27.3' W., beginning new measurement.

40.113

The corner of sections 8, 9, 16, and 17, monumented with an iron post, 2 inches diameter, firmly set, projecting 16 inches above ground, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910, with a mound of stone to the north.

from which the 1910 bearing tree

A juniper, 8 ins. diam., bears N. 48° W., 110 links distance, with a healed blaze. (Record; N. 60° W.)

No remaining evidence of the NE, SE, or SW, bearing trees were found.

Corner falls on a steep north slope in piñon and juniper.

From the corner of sections 9, 10, 15, and 16.

S. 89°20.7' W., between sections 9 and 16.

40.061

The 1/4 section corner of sections 9 and 16, monumented with an iron post, 1 inch diameter, firmly set in a small mound of stone, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910.

Corner falls on flat rolling ground in sagebrush.

S. 89°50.9' W., beginning new measurement.

40.023

The corner of sections 8, 9, 16, and 17.

Reestablishment of the Survey Executed
by J. Gorkinski in 1871.

From the corner of sections 5, 6, 31, and 32, on the south boundary of the township, hereinbefore described.

N. 0°05.2' W., between sections 31 and 32.

40.365

The 1/4 section corner of sections 31 and 32, monumented with a 5/8 inch diameter rebar, with a yellow cap attached, marked

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

ADAMS SUR PLS 167230, in a small mound of stone. This is faithfully accepted as best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T31SR7W

1/4

S31|S32

2006

Deposited rebar with cap and a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raised a small mound of stone west of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat open ground with scattering sagebrush.

N. 0°20.4' W., beginning new measurement.

20.054 Point for the N 1/16 section corner of sections 31 and 32, not monumented.

40.108 The corner of sections 29, 30, 31, and 32, monumented with a 5/8 inch diameter rebar, with a yellow cap attached, marked Adams Sur PLS 167230, in a mound of stone. This is faithfully accepted as best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

T31SR7W

S30|S29

S31|S32

2006

Deposited rebar with cap and a magnet enclosed in an orange plastic case at the base of the aluminum post.

Raised a small mound of stone west of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground.

From the corner of sections 28, 29, 32, and 33.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89°46.8' W., between sections 29 and 32.

39.793

Point for the 1/4 section corner of sections 29 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T31SR7W
S29
1/4 —
S32
2006

Deposited a magnet enclosed in an orange plastic case at the base of the aluminum post.

Raised a small mound of stone north of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on a gradual south slope in sagebrush.

From this corner a 5/8 inch diameter rebar, with a yellow cap attached, marked ADAMS SUR PLS 167230, bears N. 0°14'04" W., 31.12 feet distance.

79.586

The corner of sections 29, 30, 31, and 32.

N. 89°51.0' W., between sections 30 and 31.

20.053

Point for the E 1/16 section corner of sections 30 and 31, not monumented.

40.106

Point for the 1/4 section corner of sections 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 30 inches in the ground, with aluminum cap marked:

T31SR7W
S30
1/4 —
S31
2006

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls in a large gravel pit.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

60.159 Point for the W 1/16 section corner of sections 30 and 31, not monumented.

80.413 The corner of sections 25, 30, 31, and 36, on the west boundary of the township, hereinbefore described.

From the corner of sections 29, 30, 31, and 32.

N. 0°02.5' W., between sections 29 and 30.

40.311 True point for the 1/4 section corner of sections 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.

True point falls in the I-15 corridor, not suitable for monumentation. Not monumented.

42.820 Point selected for the witness 1/4 section corner of sections 29 and 30.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with aluminum cap marked:

WC
T31SR7W
1/4
S30 | S29
↓
2006

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Corner falls in the westerly I-15 Right-of-Way fence, bears N. 68° W., and S. 68° E.

80.622 The corner of sections 19, 20, 29, and 30, monumented with an iron post, 2 inches diameter, firmly set in a mound of stone 3 ft. base, to top, with brass cap marked as described in the official record of the resurvey executed by J.R. & Q. Stewart in 1910.

Found a lava stone, 14x8x6 inches, lying loose alongside the iron post, clearly marked 5 notches and 2 notches. I deposit marked stone alongside iron post in the mound of stone.

Set a steel fence post alongside the aluminum post.

Corner falls on a gentle east slope in sagebrush.

From the corner of sections 20, 21, 28, and 29.

N. 89°27.5' W., between sections 20 and 29.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS**40.438**

True point for the 1/4 section corner of sections 20 and 29, at proportionate distance; there is no remaining evidence of the original corner.

True point falls in the I-15 corridor, not suitable for monumentation. Not monumented.

46.424

Point selected for the witness 1/4 section corner of sections 20 and 29.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

WC
T31SR7W
S20
1/4 →
S29
2006

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Corner falls in the westerly I-15 Right-of-Way fence, bears N. 68° W., and S. 68° E.

From this corner, an I-15 Right-of-Way marker, an iron post, 2 inches diameter, firmly set in concrete, marked C/L DOT 150ML sta. 2840 elev., bears east, 1.2 ft. distance.

80.876

The corner of sections 19, 20, 29 and 30.

The Subdivision of Section 11
T. 31 S., R. 7 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 11 and 14.

N. 0°01.3' E., on the N - S centerline of section 11

20.478

Point for the center S 1/16 section corner of section 11, not monumented.

40.956

Point for the center 1/4 section corner, at intersection with the E - W centerline of section 11.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T31SR7W
C 1/4
S11
2006

THE SUBDIVISION OF SECTION 11
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposited a magnet enclosed in an orange case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on east edge of dirt road 12 ft. wide bears north and south.

80.790 The 1/4 section corner of sections 2 and 11.

From the 1/4 section corner of sections 11 and 12.

S. 88°48.4' W., on the E - W centerline of section 11.

21.214 Point for the center E 1/16 section corner of section 11.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, in a small mound of stone, with aluminum cap marked:

E 1/16
C — C
S11
2006

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls, on a gradual south slope in scattering piñon growth, and at the base of a piñon 12 inches diameter.

42.428 The center 1/4 of section 11.

83.240 The 1/4 section corner of sections 10 and 11.

From the point for the E 1/16 section corner of sections 11 and 14.

N. 0°18.1' W., on the N - S centerline of the SE 1/4 of section 11.

20.205 Point for the SE 1/16 section corner, at intersection with the E - W centerline of the SE 1/4 of section 11.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

SE 1/16
S11
2006

Deposited a magnet enclosed in an orange plastic case at the base of the aluminum post.

THE SUBDIVISION OF SECTION 11
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a small mound of stone north of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on the edge of a wash drains west.

40.410 The center E 1/16 section corner of section 11.

From the S 1/16 section corner of sections 11 and 12.

S. 88°04.8' W., on the E - W centerline of the SE 1/4 of section 11.

21.336 The SE 1/16 section corner of section 11.

42.672 The point for the center S 1/16 section corner of section 11.

The Subdivision of Section 12
T. 31 S., R. 7 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 12 and 13.

N. 0°04.9' E., on the N - S centerline of section 12.

19.929 Point for the center S 1/16 section corner of section 12.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a small mound of stone, with aluminum cap marked:

C
S 1/16 | S12
C
2006

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Corner falls on a gradual north slope in piñon and juniper growth, and 20.5 ft. east of wood road, bears north and south.

39.858 Point for the center 1/4 section corner, at intersection with the E - W centerline of section 12.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

T31SR7W
C 1/4
S12
2006

THE SUBDIVISION OF SECTION 12
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Corner falls on flat ground in sagebrush.

60.138 Point for the center N 1/16 section corner of section 12, not monumented.

78.581 The 1/4 section corner of section 12 only.

From the 1/4 section corner of section 12 only, on the east boundary of the township, hereinbefore described.

N. 89°50.2' W., on the E - W centerline of section 12.

23.542 Point for the center E 1/16 section corner of section 12.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, in a small mound of stone, with aluminum cap marked:

E 1/16
C — C
S12
2006

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on a gradual south slope in piñon growth.

43.425 The center 1/4 of section 12.

83.879 The 1/4 section corner of sections 11 and 12.

From the center E 1/16 section corner of section 12.

N. 0°10.9' W., on the N- S centerline of the NE 1/4 of section 12.

20.119 Point for the NE 1/16 section corner, at intersection with the E - W centerline of the NE 1/4 of section 12.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

NE 1/16
S12
2006

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

THE SUBDIVISION OF SECTION 12
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground in scattering sagebrush.

38.467 The point for the E 1/16 of section 12 only.

From the N 1/16 section corner of section 12 only, on the east boundary of the township, hereinbefore described.

N. 89°22.2' W., on the E - W centerline of the NE 1/4 of section 12.

23.422 The NE 1/16 section corner of section 12.

43.212 The point for the center N 1/16 section corner of section 12.

From the point for the E 1/16 section corner of sections 12 and 13.

N. 0°00.8' E., on the N - S centerline of the SE 1/4 of section 12.

19.929 Point for the SE 1/16 section corner, at intersection with the E - W centerline of the SE 1/4 of section 12.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

SE 1/16
S12
2006

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on a gradual north slope in piñon and juniper growth, and 19 ft. south of wash drains east.

39.858 The center E 1/16 of section 12.

From the point for the S 1/16 of section 12 only, on the east boundary of the township, hereinbefore described.

N. 89°50.2' W., on the E - W centerline of the SE 1/4 of section 12.

23.581 The SE 1/16 section corner of section 12.

43.490 The center S 1/16 of section 12.

From the center S 1/16 section corner of section 12.

THE SUBDIVISION OF SECTION 12
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89°50.4' W., on the E - W center line of the SW 1/4 of section 12.

40.206 The S 1/16 section corner of sections 11 and 12.

The Subdivision of Section 31
T. 31 S., R. 7 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 6 and 31, on the south boundary of the township, hereinbefore described.

N. 0°09.1' W., on the N - S centerline of section 31.

40.302 Point for the center 1/4 section corner, at intersection with the E - W centerline of section 31.

True point falls within the I-15 corridor, not suitable for monumentation.

The monumented witness center 1/4 section corner bears N. 89°40.8' E., 0.538 chains distance, monumented with a 5/8 inch diameter rebar, with a yellow plastic cap attached, marked ADAMS SUR PLS 167230.

At the witness point

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

WC
T31SR7W
C 1/4
←
S31
2006

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Deposit the rebar with cap inside the aluminum post.

Corner falls on flat open ground, 1 ft. east of the easterly I-15 Right-of-Way fence, bears N. 50° E., and S. 50° W., and N. 62° E., from an A-frame brace on the easterly Right-of-Way fence of I-15.

60.512 Point for the center N 1/16 section corner of section 31.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 31
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

C
N 1/16|S31
C
2006

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground, and 3.7 ft. south of a fence line, bears east and west.

80.722 The 1/4 section corner of sections 30 and 31.

From the 1/4 section corner of sections 31 and 32.

S. 89°42.2' W., on the E - W centerline of section 31.

20.121 The center E 1/16 section corner of section 31, monumented with a 5/8 inch diameter rebar, with a yellow plastic cap attached, marked ADAMS SUR PLS 167230. This monument is accepted as a careful determination of the center E 1/16 section corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 30 inches in the ground, with aluminum cap marked:

E 1/16
C — C
S31
2006

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Deposit the rebar with cap inside the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat open ground.

40.242 The true point for the center 1/4 section corner of section 31.

60.326 Point for the center W 1/16 section corner of section 31.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked.

THE SUBDIVISION OF SECTION 31
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

W 1/16
C — C
S31
2006

Deposited a magnet enclosed in an orange plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat open ground.

- 80.510** The 1/4 section corner of sections 31 and 36, on the west boundary of the township, hereinbefore described.

From the center E 1/16 section corner of section 31.

N. 0°14.8' W., on the N - S centerline of the NE 1/4 of section 31.

- 20.132** The NE 1/16 section corner, at intersection with the E - W centerline of the NE 1/4 of section 31, monumented with a 5/8 inch diameter rebar, with a yellow plastic cap attached, marked ADAMS SUR PLS 167230. This monument is accepted as a careful determination of the NE 1/16 section corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

NE 1/16
S31
2006

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Deposit the rebar with cap inside the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat open ground.

- 40.264** The point for the E 1/16 section corner of sections 30 and 31.

From the point for the N 1/16 section corner of sections 31 and 32.

S. 89°55.6' W., on the E - W center line of the NE 1/4 of section 31.

- 20.087** The NE 1/16 section corner of section 31.

THE SUBDIVISION OF SECTION 31
T. 31 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS
40.174

The center N 1/16 section corner of section 31.

From the E 1/16 section corner of sections 6 and 31, on the south boundary of the township, hereinbefore described.

N. 0°07.2' W., on the N - S centerline of the SE 1/4 of section 31.

40.334 The center E 1/16 section corner of section 31.

From the center W 1/16 section corner of section 31.

N. 0°06.7' W., on the N - S centerline of the NW 1/4 of section 31.

20.289 Point for the NW 1/16 section corner of section 31.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

NW 1/16
S31
2006

Deposited a magnet enclosed in an orange plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat open ground.

40.578 The point for the W 1/16 section corner of section 30 and 31.

From the center N 1/16 section corner of section 31.

S. 89°55.6' W., on the E - W center line of the NW 1/4 of section 31.

20.069 The NW 1/16 section corner of section 31.

40.288 The N 1/16 section corner of sections 31 and 36, on the west boundary of the township, hereinbefore described.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Jeremy Davis	Survey Technician
Michael Mortensen	Survey Aid
Donald Johnson	Survey Aid

CERTIFICATE OF SURVEY

I, *C. Scott Bishop*, Cadastral Surveyor, hereby certify upon honor that, in pursuance of special instructions bearing the date *31st day of October, 2005*, have executed a *dependent resurvey of a portion of the west boundary of Township 31 South, Range 6 West, a portion of the south and west boundaries, a portion of the subdivisional lines, and the subdivision of sections 11, 12, and 31, in Township 31 South, Range 7 West,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

APRIL 25, 2007

Date

C. Scott Bishop

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the west boundary of Township 31 South, Range 6 West, a portion of the south and west boundaries, a portion of the subdivisional lines, and the subdivision of sections 11, 12, and 31, in Township 31 South, Range 7 West, Salt Lake Meridian, Utah,*

executed by *C. Scott Bishop*, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

May 1, 2007

Date

Daniel W. Webb

(Chief Cadastral Surveyor for Utah)