

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

**FIELD NOTES**

OF

THE DEPENDENT RESURVEY OF THE SOUTH BOUNDARY  
(EIGHTH STANDARD PARALLEL SOUTH),  
OF TOWNSHIP 40 SOUTH, RANGE 24 EAST,  
THE DEPENDENT RESURVEY OF THE SOUTH AND WEST BOUNDARIES,  
A PORTION OF THE EAST BOUNDARY, THE CORRECTIVE RESURVEY OF A  
PORTION OF THE EAST BOUNDARY, THE DEPENDENT RESURVEY OF A PORTION OF THE  
SUBDIVISIONAL LINE, THE SURVEY OF A PORTION  
OF THE SUBDIVISIONAL LINES, THE SUBDIVISION OF ALL SECTIONS,  
AND THE SURVEY OF THE MEANDER OF THE LEFT AND RIGHT BANKS  
OF THE SAN JUAN RIVER, IN  
TOWNSHIP 41 SOUTH, RANGE 24 EAST,  
OF THE SALT LAKE MERIDIAN,  
IN THE STATE OF UTAH

EXECUTED BY

**SCOTT A. BURKHARDT**  
**CADASTRAL SURVEYOR**

Under special instructions dated April 12, 2006, approved **April 12, 2006**,  
which provided for the surveys included under Group Number **1014**, Utah, and  
assignment instructions dated **April 12, 2006**.

Survey commenced **April 24, 2006**  
Survey completed **June 28, 2006**

### INDEX DIAGRAM

Township 41 South, Range 24 East, Salt Lake Meridian, Utah

26	10 6 71	72	8 5 71	62	7 4 62	54	5 3 54	48	4 2 47	40	2 1 39
25	7 69	70	8 69	61	9 60	53	10 53	46	11 45	38	12 37
23	18 67	68	17 67	59	16 59	52	15 51	44	14 44	36	13 36 18
22	19 65	66	20 66	57	21 57	50	22 49	43	23 42	35	24 35 17
21	30 32	64	29 31	56	28 31	49	27 30	41	26 29	34	25 28
20	31 15	63	32 15	55	33 14	48	34 13	41	35 13	33	36 12 16

Subdivision of Section 1 .....	Page-72
Subdivision of Section 2 .....	Page-73
Subdivision of Section 3 .....	Page-74
Subdivision of Section 4 .....	Page-75
Subdivision of Section 5 .....	Page-76
Subdivision of Section 6 .....	Page 77
Subdivision of Section 7 .....	Page-78
Subdivision of Section 8 .....	Page-79
Subdivision of Section 9 .....	Page-79
Subdivision of Section 10 .....	Page-80
Subdivision of Section 11 .....	Page-81
Subdivision of Section 12 .....	Page-82
Subdivision of Section 13 .....	Page-83
Subdivision of Section 14 .....	Page-84
Subdivision of Section 15 .....	Page 85
Subdivision of Section 16 .....	Page-86
Subdivision of Section 17 .....	Page-87
Subdivision of Section 18 .....	Page-87
Subdivision of Section 19 .....	Page 88
Subdivision of Section 20 .....	Page-89
Subdivision of Section 21 .....	Page-90
Subdivision of Section 22 .....	Page-91
Subdivision of Section 23 .....	Page-91
Subdivision of Section 24 .....	Page 92
Subdivision of Section 25 .....	Page-93
Subdivision of Section 26 .....	Page-94
Subdivision of Section 27 .....	Page-94
Subdivision of Section 28 .....	Page 95
Subdivision of Section 29 .....	Page-96
Subdivision of Section 30 .....	Page-97
Subdivision of Section 31 .....	Page-98
Subdivision of Section 32 .....	Page-99
Subdivision of Section 33 .....	Page-99
Subdivision of Section 34 .....	Page-100
Subdivision of Section 35 .....	Page-101
Subdivision of Section 36 .....	Page-102
Meanders, Right Bank of the San Juan River.....	Pages-102-106
Meanders, Left Bank of the San Juan River.....	Pages-106-110

## T. 40 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

The following field notes describe the dependent resurvey of the South boundary (Eighth Standard Parallel South), of Township 40 South, Range 24 East, the dependent resurvey of the South and West boundaries, a portion of the East boundary, the corrective resurvey of a portion of the East boundary, the dependent resurvey of a portion of the subdivisional lines, the survey of a portion of the subdivisional lines, the subdivision of all sections, and the survey of the meanders of the right and left banks of the San Juan River of Township 41 South, Range 24 East, Salt Lake Meridian, Utah.

**History of Surveys**

<b>Surveyed by</b>	<b>Retr. or Rsurveyed by</b>
<b>SOUTH BOUNDARY</b>	
All A. Nelson & R.C. Yundt	1953
<b>EAST BOUNDARY</b>	
Portion H.D. Page & J.M. Lentz	1899
Portion A. Nelson & R.C. Yundt	1953
All	A.Nelson & R.C. Yundt 1953 J.F. Carroll 2004
<b>WEST BOUNDARY</b>	
All A. Nelson & R.C. Yundt	1953
<b>NORTH BOUNDARY (Eighth Standard Parallel)</b>	
All A.D. Ferron	1884
Portion	H.D. Page & J.M. Lentz 1899
Portion	A. Nelson & R.C. Yundt 1953
Portion	M.D. Cazier 2003
Portion	J.F.Carroll 2004
<b>SUBDIVISION</b>	
Portion H.D. Page & J.M. Lentz	1899

Meanders of the right bank of the San Juan River by H.D. Page & Lentz in 1899.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated April 12, 2006, for Group No. 1014, Utah.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 4700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

T. 40 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

CHAINS

All monuments set in this survey and resurvey bear the Navajo seal, unless otherwise noted.

Geodetic control was derived from Global Positioning System (GPS) static post observations processed by National Geodetic Survey, Online Positioning User Service (OPUS).

The geographic positions, in NAD83 (CORS96), epoch date 2002.00 for the corners listed below were determined by Global Positioning System (GPS) observations to a Network Accuracy of less than 0.10 meter, 95 percent confidence circle, as defined in *Standards and Guidelines for Cadastral Surveys Using Global Positioning Systems Methods, May 9, 2001, Version 1.0.*

The northwest township corner of Township 41 South, Range 24 East, Salt Lake Meridian, Utah is as follows:

Latitude 37° 15' 30.837" N., Longitude 109° 19' 56.257" W.,  
4512.7 ft. height above the ellipsoid. N.A.V.D. 1983, 4581.2  
FT.

The southeast township corner of Township 41 South, Range 24 East, Salt Lake Meridian, Utah is as follows:

Latitude 37° 10' 23.861" N., Longitude 109° 13' 25.847" W.,  
4540.2 ft. height above the ellipsoid. N.A.V.D. 1983, 4608.4  
FT.

---

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY  
(EIGHTH STANDARD PARALLEL SOUTH)  
T. 40 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

---

Reestablishment of the Survey Executed by  
A.D. Ferron in 1884, and the Resurveys Executed by H.D. Page and  
J.M. Lentz in 1899, A. Nelson and R.C. Yundt in 1953, M.D.  
Cazier in 2003, and J.F. Carroll in 2004

---

Beginning at the standard township cor. of T. 40 S., Rs. 24 and 25 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap (Navajo seal) mkd. as described in the official record of the 2003 resurvey.

S. 89°56.1' W., on the south boundary of sec. 36.

5.438

The closing cor. of secs. 1 and 6, T. 41 S., Rs. 24 and 25 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush with the ground, with brass cap (Navajo seal) mkd. as described in the official record of the 2004 resurvey.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY  
 (EIGHTH STANDARD PARALLEL SOUTH)  
 T. 40 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

From this cor., a rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, bears S. 1°07' E., 0.280 ch. dist. Not utilized in this resurvey.

- 39.916 The standard 1/4 sec. cor. of sec. 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a collar of stones, 3 ft. diam. base, 8 ins. above ground, with brass cap (Navajo seal) mkd. as described in the official record of the 2003 resurvey.

---

N. 89°54.3' W., beginning new measurement.

- 5.502 Point for the 1/4 sec. cor. of sec. 1, T. 41 S., R. 24 E., at midpoint between closing cors.

Cement a brass tablet, 2 1/2 ins. stem, 3 1/4 ins. face, in a hole drilled in the sandstone outcrop, with brass face mkd.:

T 40 S R 24 E

1/4 S 1

T 41 S R 24 E

2006

Deposit a magnet at the base of the brass tablet.

Set a steel fence post northeast of brass tablet as a witness post.

Cor. is located on a horizontal sandstone bench. From cor., the edge of the bench bears West, 0.450 ch. dist.

- 40.034 The standard cor. of secs. 35 and 36 only, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush in a mound of stones, 6 ft. diam. base, 3 ft. above ground, with brass cap (Navajo seal) mkd. as described in the official record of the 2003 resurvey, witnessed by fiberglass rod, 1/2 in. diam., projecting 3 ft. above ground.

Add T41S to brass cap.

Cor. is located on the west face of a moderately steep ridge trending north and south.

---

N. 89°59.0' W., on the south boundary of sec. 35.

- 5.448 Point for the closing cor. of secs. 1 and 2, T. 41 S., R. 24 E. on the Eighth Standard Parallel South, original closing cor. found off line, hereinafter described.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY  
 (EIGHTH STANDARD PARALLEL SOUTH)  
 T. 40 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stones, 3 ft. diam., with brass cap mkd.:

T 40 S R 24 E  
 S 35  
 S 2 | S 1  
 T 41 S R 24 E  
 CC  
 2006

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Set a steel fence post east of stainless steel post as a witness post.

Cor. is located on a gentle, west-facing slope, with scattered grass and rocky ground.

39.931

The standard 1/4 sec. cor. of sec. 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap (Navajo seal) mkd. as described in the official record of the 2003 resurvey.

Set steel fence post north of stainless steel post as witness post.

---

N. 89°59.0' W., bet. secs. 2 and 35, beginning new measurement.

5.444

Point for the 1/4 sec. cor. of sec. 2, T. 41 S., R. 24 E., at midpoint between closing cors., on the Eighth Standard Parallel South.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.:

T 40 S R 24 E  
 1/4 S 2  
 T 41 S R 24 E  
 2006

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Set a steel fence post east of stainless steel post as a witness post.

Cor. is located on the east edge of a dry pond, surrounded by short tamarisk.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY  
 (EIGHTH STANDARD PARALLEL SOUTH)  
 T. 40 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

39.931 The standard cor. of secs. 34 and 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stones, 4 ft. diam. base, 3 ft. above side of hill, with brass cap (Navajo seal) mkd. as described in the official record of the 2003 resurvey.

---

N. 89°59.0' W., on the south boundary of sec. 34.

5.440 Point for the closing cor. of secs. 2 and 3, T. 41 S., R. 24 E., at proportionate distance on the Eighth Standard Parallel South; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, with a supporting mound of stones below, 6 ft. by 3 ft. by 4 ft. high, with brass cap mkd.:

T	40	S		R	24	E
			S		34	
		S	3		S	2
T	41	S		R	24	E
			CC			
			2006			

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Set a steel fence post northeast of stainless steel post as a witness post.

Cor. is located near the base of a steep cliff, in heavily eroded terrain with large boulders, in a drainage, course S. 40° W.

36.366 The centerline of Utah State Highway 162, a paved road, 25 ft. wide, that bears N. 78° W. and S. 73° E.

39.931 The standard 1/4 sec. cor. of sec. 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap (Navajo seal) mkd. as described in the official record of the 2003 resurvey.

---

N. 89°59.0' W., beginning new measurement.

5.576 Point for the 1/4 sec. cor. of sec. 3, T. 41 S., R. 24 E., at midpoint between closing cors., on the Eighth Standard Parallel South.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY  
 (EIGHTH STANDARD PARALLEL SOUTH)  
 T. 40 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

T 40 S R 24 E  
 \_\_\_\_\_  
 1/4 S 3  
 T 41 S R 24 E  
 2006

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Set a steel fence post north of stainless steel post as a witness post.

Cor. is located below the south shoulder of a paved highway. From cor., the centerline of Utah State Highway 162, 25 ft. wide, extending N. 89° W./S. 89° E., bears North, 0.803 ch. dist.

- 29.690 The centerline of Utah State Highway 162, a paved road, 25 ft. wide, that bears S. 80° W. and N. 80° E.
- 39.754 The witness cor. to the standard cor. of secs. 33 and 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush in a mound of stones, 4 ft. diam. base, 2 ft. above ground, with brass cap (Navajo seal) mkd. as described in the official record of the 2003 resurvey.
- 39.931 True point for the standard cor. of secs. 33 and 34; point falls on the face of a ledge, impracticable to establish a monument here.

---

N. 89°59.0' W., on the south boundary of sec. 33.

- 5.714 Point for the closing cor. of secs. 3 and 4, T. 41 S., R. 24 E., on the Eighth Standard Parallel South, original closing cor. found off line, hereinafter described.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground, in a supporting mound of stones, 4 ft. diam., 5 ft. above ground on the side of a hill, with brass cap mkd.:

T 40 S R 24 E  
 S 33  
 \_\_\_\_\_  
 S 4 | S 3  
 T 41 S R 24 E  
 CC  
 2006

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY  
 (EIGHTH STANDARD PARALLEL SOUTH)  
 T. 40 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Set a steel fence post east of stainless steel post as a witness post.

Cor. located on a steep, west-facing slope, in loose, unconsolidated rocks and boulders.

39.931 True point for the standard 1/4 sec. cor. of sec. 33; point falls on a south-facing cliff where it is impracticable to establish a monument.

---

N. 89°59.0' W., beginning new measurement.

2.971 The witness cor. to the standard 1/4 sec. cor. of secs. 33, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap (Navajo seal) mkd. as described in the official record of the 2003 resurvey.

5.656 Point for the 1/4 sec. cor. of sec. 4, T. 41 S., R. 24 E., at midpoint between closing cors., on the Eighth Standard Parallel South.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a collar of stones, 4 ft. diam., with brass cap mkd.:

T 40 S R 24 E

---

1/4 S 4

T 41 S R 24 E

2006

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Set a steel fence post south of stainless steel post as a witness post.

Cor. located on a moderately steep, northwest-facing slope, in river stones and scant vegetation, above a steep drainage, course S. 45° W.

39.931 The standard cor. of secs. 32 and 33, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush in a mound of stones, 3 ft. diam. base, 16 ins. above ground, with brass cap (Navajo seal) mkd. as described in the official record of the 2003 resurvey.

---

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY  
 (EIGHTH STANDARD PARALLEL SOUTH)  
 T. 40 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

- N. 89°56.8' W., on the south boundary of sec. 32.
- 5.597 Point for the closing cor. of secs. 4 and 5, T. 41 S., R. 24 E., at proportionate distance on the Eighth Standard Parallel South; there is no remaining evidence of the original cor.
- Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, with brass cap mkd.:
- |   |    |    |      |    |    |
|---|----|----|------|----|----|
| T | 40 | S  | R    | 24 | E  |
|   |    | S  | 32   |    |    |
|   | S  | 5  | S    | 4  |    |
|   | T  | 41 | S    | R  | 24 |
|   |    |    | E    |    |    |
|   |    |    | CC   |    |    |
|   |    |    | 2006 |    |    |
- Deposit a magnet in a white plastic case at the base of the stainless steel post.
- Set a steel fence post west of stainless steel post as a witness post.
- From cor., the centerline of Utah State Highway 162, 25 ft. wide, extending N. 75° W./S. 71° E., bears South, 0.273 chs. dist.
- 6.428 The centerline of Utah State Highway 162, a paved road, 25 ft. wide, that bears N. 72° W. and S. 72° E.
- 20.543 The standard E 1/16 sec. cor. of sec. 32, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush with ground, with brass cap (Navajo seal) mkd. as described in the official record of the 2003 resurvey.
- Cor. falls 0.030 ch. north of E-W fence, and bears S. 24° W., 0.197 ch. dist. from SW cor. of a house.
- 
- N. 89°56.8' W., beginning new measurement.
- 20.543 The standard 1/4 sec. cor. of sec. 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap (BLM) mkd. as described in the official record of the 2003 resurvey.
- 
- S. 89°57.3' W., beginning new measurement.
- 4.669 Point for the 1/4 sec. cor. of sec. 5, T. 41 S., R. 24 E., at midpoint between closing cors., on the Eighth Standard Parallel South.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY  
 (EIGHTH STANDARD PARALLEL SOUTH)  
 T. 40 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stones, 3 ft. diam., 14 ins. above ground, with brass cap mkd.:

T 40 S R 24 E

1/4 S 5

T 41 S R 24 E

2006

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Cor. located on a level, gravel bench, above the San Juan River, south of a chain link fence.

From cor., a chain link fence, 6 ft. high, with 3 strands of barbed wire on top, extending East and West, bears North, 0.0173 ch. dist.

- 13.650 The witness meander cor. of secs. 5 and 32, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stones, 3 ft. diam. base, 12 ins. above ground, with brass cap (Navajo seal) mkd. as described in the official record of the 2003 resurvey.
- 19.377 The centerline of San Juan County road 450, a paved road, 25 ft. wide, that bears N. 39° E. and S. 39° W.
- 24.750 Point for the original meander cor. of secs. 5 and 32, falls in San Juan River flood area, not monumented.
- 24.944 Right bank of the San Juan River, point for the meander cor. of secs. 5 and 32. Not monumented.
- 26.545 Left bank of the San Juan River, point for the meander cor. of secs. 5 and 32. Not monumented.
- 40.000 Point for the standard cor. of secs. 31 and 32, falls in San Juan River flood area, not monumented.
- 
- S. 89°57.3' W., on the south boundary of sec. 31.
- 4.829 Point for the closing cor. of secs. 5 and 6, T. 41 S., R. 24 E., on the Eighth Standard Parallel South. Note: this cor. was never set before and is not a part of the Dependent Resurvey.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY  
 (EIGHTH STANDARD PARALLEL SOUTH)  
 T. 40 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T 40 S R 24 E  
 S 31  
 S 6 | S 5  
 T 41 S R 24 E  
 CC  
 2006

Deposit three (3) 60D nails at the base of the stainless steel post as a memorial.

Set a steel fence post east of stainless steel post as a witness post.

Cor. is located in the San Juan River floodplain, in high cottonwood, willow, and Russian olive trees, and thick tamarisk bushes.

10.400 The reference point for the 1953 resurvey, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap (Navajo seal) mkd. as described in the official record of the 2003 resurvey.

40.000 The standard 1/4 sec. cor. of sec. 31, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap (BLM) mkd. as described in the official record of the 2003 resurvey, witnessed by a steel fence post west of cor.

---

S. 89°57.0' W., beginning new measurement.

4.829 Point for the 1/4 sec. cor. of sec. 6, T. 41 S., R. 24 E., at 40.000 chains West from the closing cor. of secs. 5 and 6, and on the Eighth Standard Parallel South.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

T 40 S R 24 E  
 1/4 S 6  
 T 41 S R 24 E  
 2006

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Set a steel fence post north of stainless steel post as a witness post.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY  
 (EIGHTH STANDARD PARALLEL SOUTH)  
 T. 40 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Cor. located in a level, sandy area, north of an oil and gas processing plant.

From cor., an enclosure fence, 3 ft. high, with barbed wire, 3 strands, extending East and West, bears South, 0.024 ch. dist.

38.702

The standard cor. of T. 40 S., Rs. 23 and 24 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap (BLM) mkd. as described in the official record of the 2003 resurvey.

Set an angle iron as witness post east of iron post.

---

N. 89°58.6' W., on the south boundary of sec. 36, T. 40 S., R, 23 E.

4.559

The closing cor. of T. 41 S., Rs. 23 and 24 E., monumented with an iron post, 2 1/2 ins. diam., buried 11 ins. below ground, with brass cap (BLM) mkd. as described in the official record of the 1953 survey. Found broken glass around post (record memorial).

Remove dirt from around iron post.

From iron post, a rebar, 3/4 ins. diam., firmly set flush with ground, with aluminum cap, 3 ins. diam., mkd.:

161297  
 S 36  
 \_\_\_\_\_  
 S 1 | S 6 T41  
 R 23 E | R 24 E  
 SLM  
 MANOS

bears S. 61° W., 0.035 ch. dist. Not utilized in this resurvey. Rebar set at cor. of fences, 3 ft. enclosure fence with 3 strand barbed wire, extending North and East.

From the closing cor., the standard 1/4 sec. cor. of sec. 36, T. 40 S., R. 23 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap (BLM) mkd. as described in the official record of the 1953 survey, bears N. 89°58.6' W., 35.467 chs. dist.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

CHAINS

---

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

---

Reestablishment of the Survey Executed by  
A. Nelson and R.C. Yundt in 1953

---

From the cor. of Ts. 41 and 42 S., R. 24 E., on the W. bdy. of T. 41 S., R. 25 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap (BLM) mkd. as described in the official record of the 1953 survey. Mound of stones set west of iron post.

Set a steel fence post south of iron post as a witness post; add a collar of stones, 2 ft. diam., around iron post.

From cor., the centerline of a maintained gravel road, 15 ft. wide, extending North and South, bears East, 0.197 ch. dist.

From cor., the center of a shallow wash, 8 ft. deep, 10 ft. wide, course North, bears West, 0.333 ch. dist.

S. 89°59.3' W., bet. secs. 1 and 36, on the S. bdy. of the township.

40.022 The 1/4 sec. cor. of secs. 1 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above an embedded mound of stones, 2 ft. diam., with brass cap (BLM) mkd. as described in the official record of the 1953 survey.

Set a steel fence post east of iron post as a witness post; rehabilitate collar of stones.

Cor. is located in gently rolling sand dunes, south of an oilfield tank battery.

---

S. 89°57.4' W., beginning new measurement.

40.019 The cor. of secs. 1, 2, 35, and 36, monumented with an embedded mound of stones, 4 ft. diam.; there is no remaining evidence of the 1953 post.

At the cor. point (center of mound of stones)

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, in a mound of stones, 4 ft. diam., 20 ins. above ground, with brass cap mkd.:

T 41 S	R 24 E
S 35	S 36
S 2	S 1
T 42 S	
2006	

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located at the base of a sandstone mesa, in an open wash, course N. 40° E.

N. 89°57.9' W., bet. secs. 2 and 35, on the S. bdy. of the township.

39.995

The 1/4 sec. cor. of secs. 2 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above an embedded mound of stones, 3 ft. diam., with brass cap (BLM) mkd. as described in the official record of the 1953 survey.

Set a steel fence post east of iron post as a witness post; rehabilitate collar of stones.

Cor. is located at the base of a steep cliff to the northwest, in a fairly level valley bottom.

S. 89°59.0' W., beginning new measurement.

40.003

The cor. of secs. 2, 3, 34, and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap (BLM) mkd. as described in the official record of the 1953 survey.

Set a steel fence post west of iron post as a witness post; build a mound of stones, 3 ft. diam, 12 ins. above ground, around iron post.

Cor. is located on a steep, north-facing slope of hardened clay, no rocks or vegetation.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

S. 89°59.9' W., bet. secs. 3 and 34, on the S. bdy. of the township.

40.013 The 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap (BLM) mkd. as described in the official record of the 1953 survey.

Set a steel fence post south of iron post as a witness post; build a mound of stones, 3 ft. diam., around iron post.

Cor. is located in a steep, northwest-facing slope, rocky and eroded.

From cor., a rebar, 1/2 in. diam., firmly set flush with ground, with plastic cap mkd. San Juan County, bears S. 7° W., 2.318 chs. dist. Not utilized in this resurvey.

---

S. 89°59.8' W., beginning new measurement.

21.473 The centerline of San Juan County road 444, a curving gravel road, 25 ft. wide, that bears N. 35° E. and S. 28° E.

40.006 The cor. of secs. 3, 4, 33, and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above a mound of stones, 4 ft. diam., 18 ins. above ground, with brass cap (BLM) mkd. as described in the official record of the 1953 survey.

Set a steel fence post west of iron post as a witness post; rehabilitate the mound of stones around the iron post.

Cor. is located in a drainage, course S. 70° W., rocky with few trees.

From cor., a rebar, 1/2 in. diam., firmly set, projecting 11 ins. above ground, bears N. 54° W., 0.505 ch. dist. Not utilized in this resurvey.

---

S. 89°59.0' W., bet. secs. 4 and 33, on the S. bdy. of the township.

39.935 The 1/4 sec. cor. of secs. 4 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above a mound of stones, 5 ft. diam., 18 ins. above ground, with brass cap (BLM) mkd. as described in the official record of the 1953 survey.

Set a steel fence post southwest of iron post as a witness post; rehabilitate mound of stones around post.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Cor. is located on the edge of a mesa top, on east sloping bedrock, with very little soil.

---

S. 89°59.6' W., beginning new measurement.

40.017 The cor. of secs. 4, 5, 32, and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above a mound of stones, 4 ft. diam., 18 ins. above ground, with brass cap (BLM) mkd. as described in the official record of the 1953 survey.

Set a steel fence post northeast of iron post as a witness post; rehabilitate the mound of stones around the iron post.

Cor. is located on a gentle, southwest-sloping mesa top, with sandstone outcroppings, in little soil with scattered juniper shrubs.

---

S. 89°59.8' W., bet. secs. 5 and 32, on the S. bdy. of the township.

39.979 The 1/4 sec. cor. of secs. 5 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap (BLM) mkd. as described in the official record of the 1953 survey.

Set a steel fence post north of iron post as a witness post; rehabilitate mound of stones around post.

Cor. is located on a steep, southeast-facing hill, at the base of a 10 ft. cliff, below mesa top, overlooking a large, open valley trending northeast/southwest.

---

S. 89°59.2' W., beginning new measurement.

40.047 The cor. of secs. 5, 6, 31, and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above a mound of stones, 3 ft. diam., 12 ins. above ground, with brass cap (BLM) mkd. as described in the official record of the 1953 survey.

Set a steel fence post south of iron post as a witness post; rehabilitate the mound of stones around the iron post.

Cor. is located on the steep, south bank of a narrow drainage, 10 ft. wide, 10 ft. deep, course N. 60° E.

---

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

S. 89°59.7' W., bet. secs. 6 and 31, on the S. bdy. of the township.

39.975 The 1/4 sec. cor. of secs. 6 and 31, monumented with an iron post, 2 1/2 ins. diam., firmly set flush in a mound of stones, 2 ft. diam. base, 10 ins. above ground, with brass cap (BLM) mkd. as described in the official record of the 1953 survey.

Set a steel fence post west of iron post as a witness post.

Cor. is located in gently rolling terrain, with scant grass and no trees.

---

S. 89°59.2' W., beginning new measurement.

19.362 The centerline of San Juan County road 406, a paved road, 25 ft. wide, that bears N. 17° E. and S. 17° W.

38.879 The cor. of Ts. 41 and 42 S., Rs. 23 and 24 E., monumented with an iron post, 2 1/2 ins. diam., buried 4 ins. below ground, below a scattered mound of stones, 2 ft. diam., with brass cap (BLM) mkd. as described in the official record of the 1953 survey.

Set a steel fence post northeast of iron post as a witness post; remove dirt from and build collar of stones around post.

Cor. is located in an eroded area, above a winding arroyo.

---

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

Reestablishment of the Survey Executed by H.D. Page and J.M. Lentz in 1899, the Resurvey Executed by A. Nelson and R.C. Yundt in 1953, and the Resurvey Executed by J.F. Carroll in 2004

---

From the cor. of Ts. 41 and 42 S., R. 24 E., on the W. bdy. of T. 41 S., R. 25 E., hereinbefore described.

N. 0°00.9' E., bet. secs. 31 and 36, on the E. bdy. of the township.

29.450 The witness cor. to the 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, in an embedded mound of stones, 3 ft. diam. base, with brass cap (BLM) mkd. as described in the official record of the 2004 resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a steel fence post west of iron post as a witness post.

Cor. is located in eroded badlands.

---

N. 0°00.6' W., beginning new measurement.

1.000 True point for the 1/4 sec. cor. of secs. 31 and 36.

41.002 The cor. of secs. 25, 30, 31, and 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap (Navajo Seal) mkd. as described in the official record of the 2004 resurvey, witnessed by steel fence post to the northeast, from which the bearing object mkd. in the 1953 resurvey

An "X", chiseled on a sandstone boulder, 4 x 4 x 1 ft., bears N. 35°25' E., 1.24 chs. dist.

Cor. is located on a west facing sand dune.

---

CORRECTIVE RESURVEY OF A PORTION OF THE EAST BOUNDARY  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

---

Reestablishment of the Survey Executed by H.D. Page and J.M. Lentz in 1899, the Resurvey Executed by A. Nelson and R.C. Yundt in 1953, and the Resurvey Executed by J.F. Carroll in 2004

---

From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., monumented with a PK nail, firmly driven in the sandstone, no remains of an "X", from which the bearing object mkd. by J.F. Carroll, in 2004:

An "X", mkd. on a vertical sandstone face, bears N. 52°22.5' E., 0.128 ch. dist. (Rec: N. 52°31.6' E., 0.127 ch. dist.).

At the cor. point

Cement a brass tablet, 2 1/2 ins. stem, 3 1/4 ins. face, in a hole drilled in the sandstone outcrop, with brass face mkd.:

CORRECTIVE RESURVEY OF A PORTION OF THE EAST BOUNDARY  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T 41 S  
1/4  
R 24 E | R 25 E  
S 24 | S 19  
2006

Place PK nail at the base of the brass tablet.

Set a steel fence post southeast of brass tablet as a witness post.

N. 0°00.6' W., bet. secs. 19 and 24.

40.012 The cor. of secs. 13, 18, 19, and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, in a mound of stones, 3 ft. diam., 8 ins. above ground, with brass cap (BLM) mkd. as described in the official record of the 2004 resurvey, from which the bearing object mkd. by J.F. Carroll, in 2004:

An "X", mkd. on a sandstone outcrop, bears S. 74°14' E., 0.755 ch. dist. (Rec: S. 74 1/2° E.)

Set a steel fence post north of iron post as a witness post.

Cor. is located in sandy, open terrain, surrounded by sandstone outcrops.

---

N. 0°02.3' E., bet. secs. 13 and 18, on the E. bdy. of the township.

40.022 The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap (BLM) mkd. as described in the official record of the 2004 resurvey.

Set a steel fence post north of iron post as a witness post.

Cor. is located on a level flood plain, with tamarisk and cottonwood trees.

---

N. 0°00.3' W., beginning new measurement.

15.709 Angle point for the original meander cor. of secs. 13 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, 2 ins. below ground, with brass cap (BLM) mkd. as described in the official record of the 2004 resurvey.

Set a steel fence post west of iron post as a witness post.

CORRECTIVE RESURVEY OF A PORTION OF THE EAST BOUNDARY  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Cor. is located on a muddy flood plain of the San Juan River, with tamarisk trees.

---

N. 0°01.2' W., beginning new measurement.

6.567 The witness cor. to the meander cor. for secs. 13 and 18, left bank of the San Juan River, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap (Navajo seal) mkd. as described in the official record of the 2004 resurvey.

Set a steel fence post east of stainless steel post as a witness post.

Cor. is located on the flood plain of the San Juan River, with tamarisk trees. From cor., the centerline of an improved dirt road, 20 ft. wide, extending N. 70° W./ S. 70° E., bears South, 0.303 ch.

---

N. 0°00.6' W., beginning new measurement.

7.401 True point for the meander cor. of secs. 13 and 18, left bank of the San Juan River.

12.777 True point for the meander cor. of secs. 13 and 18, right bank of the San Juan River.

12.904 The witness cor. to the meander cor. for secs. 13 and 18, right bank of the San Juan River, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap (Navajo Seal) mkd. as described in the official record of the 2004 resurvey.

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on a sandy bank above the San Juan River, with tamarisk and Russian olive trees.

---

N. 0°00.7' W., beginning new measurement.

4.836 The cor. of secs. 7, 12, 13, and 18, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap (Navajo Seal) mkd. as described in the official record of the 2004 resurvey, witnessed by steel fence post to the west.

Add a collar of stones, 2 ft. diam., around stainless steel post.

CORRECTIVE RESURVEY OF A PORTION OF THE EAST BOUNDARY  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Cor. is located on the fairly level flood plain of the San Juan River, in low tamarisk.

---

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

---

Reestablishment of the Survey Executed by  
A. Nelson and R.C. Yundt in 1953

---

From the cor. of Ts. 41 and 42 S., Rs. 23 and 24 E., hereinbefore described.

North, along the W. bdy. of sec. 31, on the W. bdy. of the township.

30.552

The 1/4 sec. cor. of sec. 31 only, T. 41 S., R. 24 E., monumented with an iron post, 2 1/2 ins. diam., buried 6 ins. below ground, with brass cap (BLM) mkd. as described in the official record of the 1953 survey.

Set a steel fence post west of iron post as a witness post; remove dirt from around post.

Cor. is located on an east-sloping hill, with scattered grass.

---

N. 0°01.1' E., beginning new measurement.

9.443

The 1/4 sec. cor. of sec. 36 only, T. 41 S., R. 23 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap (BLM) mkd. as described in the official record of the 1953 survey. Witnessed by mound of stones, 3 ft. diam., 2 ft. above ground west of post.

Set a steel fence post north of iron post as a witness post.

Cor. is located on a sandy hill, above an arroyo winding around the cor.

---

N. 0°00.5' W., beginning new measurement.

30.550

Point for the cor. of secs. 30 and 31, T. 41 S., R. 24 E., at proportionate distance; there is no remaining evidence of the original cor.

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a collar of stones, 2 ft. diam., with brass cap mkd.:

T 41 S	
R 23 E	R 24 E
	S 30
S 36	S 31
2006	

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on a sandy ridge, above a drainage, course East.

---

N. 0°00.5' W., along the W. bdy of sec. 30, on the W. bdy. of the township.

9.450 The cor. of secs. 25 and 36, T. 41 S., R. 23 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above an embedded mound of stones, 3 ft. diam., with brass cap (BLM) mkd. as described in the official record of the 1953 survey. Witnessed by mound of stones, 3 ft. diam., 2 ft. above ground west of post.

Set a steel fence post north of iron post as a witness post.

Cor. is located on a south-sloping hill, with sandstone outcrops, above a drainage, course N. 40° E.

---

N. 0°00.4' E., beginning new measurement.

30.548 The 1/4 sec. cor. of sec. 30 only, T. 41 S., R. 24 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap (BLM) mkd. as described in the official record of the 1953 survey.

Set a steel fence post west of iron post as a witness post.

Cor. is located on a gently-rolling, sandy hill.

---

N. 0°01.7' E., beginning new measurement.

9.451 The 1/4 sec. cor. of sec. 25 only, T. 41 S., R. 23 E., monumented with an iron post, 2 1/2 ins. diam., firmly set,

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

projecting 10 ins. above ground, with brass cap (BLM) mkd. as described in the official record of the 1953 survey.

Set a steel fence post west of iron post as a witness post.

Cor. is located in fairly level, open terrain, west of a windmill.

---

N. 0°00.1' E., beginning new measurement.

30.565 The cor. of secs. 19 and 30, T. 41 S., R. 24 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above an embedded mound of stones, 3 ft. diam., with brass cap (BLM) mkd. as described in the official record of the 1953 survey. Witnessed by steel fence post set south of post.

Cor. is located on a level bench, in sandy soil.

---

N. 0°00.2' W., along the W. bdy of sec. 19, on the W. bdy. of the township.

9.453 Point for the cor. of secs. 24 and 25, T. 41 S., R. 23 E., at proportionate distance; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. below ground, in a graded dirt road, with brass cap mkd.:

T 41 S	
R 23 E	R 24 E
S 24	S 19
S 25	
2006	

from which

A stainless steel post, for a reference monument, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, with brass cap mkd. RM T41S R24E S19 35.4 FT. TO COR 2006, with an arrow pointing toward cor., bears S. 77°51' E., 0.537 ch. dist. Deposit a magnet and broken glass at the base of stainless steel post. Set a steel fence post north of stainless steel post as a witness post.

A stainless steel post, for a reference monument, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, with brass cap mkd. RM T41S R23E S25 40.7 FT. TO COR 2006, with an arrow pointing toward cor., bears S. 2°13' W., 0.617 ch. dist. Deposit a magnet and broken glass at the base of stainless steel post. Set a steel fence post north of stainless steel post as a witness post.

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Deposit a magnet and broken glass at the base of the stainless steel post.

Cor. is located 3 ft. southeast of the centerline of a graded dirt road, 20 ft. wide, extending N. 48° E./ S. 48° W.

From cor., a rebar, 1/2 in. diam., buried 5 ins. below ground, bears S. 0°02' E., 0.411 ch. dist. Not utilized in this resurvey.

23.229 The centerline of San Juan County road 410, a gravel road, 30 ft. wide, that bears N. 46° W. and S. 46° E.

40.013 The 1/4 sec. cor. of sec. 19 only, T. 41 S., R. 24 E., monumented with an iron post, 2 1/2 ins. diam., firmly set flush with the ground, with brass cap (BLM) mkd. as described in the official record of the 1953 survey.

Set a steel fence post west of iron post as a witness post.

Cor. is located on a gently-rolling, sandy hill.

---

N. 0°01.1' E., beginning new measurement.

9.454 The 1/4 sec. cor. of sec. 24 only, T. 41 S., R. 23 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap (BLM) mkd. as described in the official record of the 1953 survey.

Set a steel fence post west of iron post as a witness post.

Cor. is located in gently-rolling, sandy hills, with scattered desert plants.

---

N. 0°00.2' W., beginning new measurement.

30.557 The cor. of secs. 18 and 19, T. 41 S., R. 24 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap (BLM) mkd. as described in the official record of the 1953 survey. Witnessed by a steel fence post set northwest of post.

Cor. is located in rolling, sandy hills.

---

N. 0°00.1' E., along the W. bdy of sec. 18, on the W. bdy. of the township.

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

9.449

Point for the cor. of secs. 13 and 24, T. 41 S., R. 23 E., at proportionate distance; the original iron post, mkd. as described in the official record of the 1953 survey, was found loosely placed on top of a steel fence post. There was no method to determine the original location of the post.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a collar of stones, 3 ft. diam., with brass cap mkd.:

	T 41 S	
R 23 E		R 24 E
S 13		S 18
S 24		
	2006	

Deposit broken glass and a magnet in a white plastic case at the base of the stainless steel post; bury original iron post south of stainless steel post.

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on a sandy hill, above an arroyo trending northwest and southeast.

From cor., a rebar, 1/2 in. diam., buried 5 ins. below ground, bears S. 19°13' E., 0.013 ch. dist. Not utilized in this resurvey.

From cor., a telephone pole, 10 ins. diam., bears N. 60° E., 0.041 ch. dist.

39.997

Point for the 1/4 sec. cor. of sec. 18 only, T. 41 S., R. 24 E., at proportionate distance; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.:

	T 41 S	
R 23 E		R 24 E
		1/4 S 18
	2006	

Deposit broken glass and a magnet in a white plastic case at the base of the stainless steel post.

Set a steel fence post northeast of stainless steel post as a witness post.

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Cor. is located in rolling, eroded terrain, southwest of a large mesa.

From cor., a rebar, 3/4 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap, 3 ins., mkd. Maness Colo LS 19612 T41S R24E 1996 W 1/4 S18, bears N. 84°47' E., 0.017 ch. dist. Not of record, not utilized in this resurvey.

49.446 The 1/4 sec. cor. of sec. 13 only, T. 41 S., R. 23 E., monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stones, 3 ft. diam., 24 ins. above ground, with brass cap (BLM) mkd. as described in the official record of the 1953 survey. Witnessed by a steel fence post set south of post.

Cor. is located at the base of the west face of Flat Top Mountain, in rocky and barren terrain.

---

N. 0°00.8' W., beginning new measurement.

30.550 The cor. of secs. 7 and 18, T. 41 S., R. 24 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, in a collar of stones, 4 ft. diam., with brass cap (BLM) mkd. as described in the official record of the 1953 survey.

Set a steel fence post east of iron post as a witness post.

Cor. is located on a moderately steep, west-facing, and rocky slope.

---

N. 0°02.1' E., along the W. bdy of sec. 7, on the W. bdy. of the township.

9.452 The cor. of secs. 12 and 13, T. 41 S., R. 23 E., monumented with an iron post, 2 1/2 ins. diam., firmly set flush in a mound of stones, 3 ft. diam., 24 ins. above the ground, with brass cap (BLM) mkd. as described in the official record of the 1953 survey.

Set a steel fence post south of iron post as a witness post.

Cor. is located on a moderately steep, northwest-facing hillside, in scattered grass.

---

N. 0°00.4' E., beginning new measurement.

30.546 Point for 1/4 sec. cor. of sec. 7 only, T. 41 S., R. 24 E., at proportionate distance; there is no remaining evidence of the original cor.

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.:

T 41 S  
R 23 E | R 24 E  
          | 1/4 S 7  
          2006

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located in an open field, west of a house, on gentle, north-sloping ground.

39.995 The 1/4 sec. cor. of sec. 12 only, T. 41 S., R. 23 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap (BLM) mkd. as described in the official record of the 1953 survey. Witnessed by a steel fence post set west of post.

Cor. is located in gently rolling, sandy terrain, with scattered grass.

From cor., the centerline of a maintained, gravel road, 30 ft. wide, extending N. 12° E. / S. 12° W., bears West, 1.424 chs. dist.

---

N. 0°00.1' E., beginning new measurement.

30.557 The cor. of secs. 6 and 7, T. 41 S., R. 24 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap (BLM) mkd. as described in the official record of the 1953 survey.

Set a steel fence post west of iron post as a witness post.

Cor. is located in gently rolling terrain, sloping west.

---

N. 0°00.1' W., along the W. bdy of sec. 6, on the W. bdy. of the township.

9.454 The cor. of secs. 1 and 12, T. 41 S., R. 23 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap (BLM) mkd. as described in the official record of the 1953 survey. Witnessed by a steel fence post set southwest of post.

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Cor. is located in open terrain, with scattered grass and yucca plants, sloping west.

N. 0°00.3' E., beginning new measurement.

30.559 Point for 1/4 sec. cor. of sec. 6 only, T. 41 S., R. 24 E., at proportionate distance; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stones, 3 ft. diam. base, 6 ins. above ground, with brass cap mkd.:

T 41 S  
R 23 E | R 24 E  
          | 1/4 S 6  
          2006

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Set a steel fence post southwest of stainless steel post as a witness post.

From cor., a fence brace bears N. 35° E., 0.051 ch. dist.

From cor., the centerline of a dirt road, 15 ft. wide, extending N. 60° W. / S. 80° E., bears South, 0.500 ch. dist.

From cor., an aluminum post, 2 1/2 ins. diam., firmly set in cement, bent over and projecting 8 ins. above ground, with aluminum cap mkd. T41S / Sec 1 R23E / S 1/16 Sec 6 R24E / 1991 LS 4346, bears S. 61°19' W., 0.038 ch. dist. Not of record, not utilized in this resurvey.

40.012 The 1/4 sec. cor. of sec. 1 only, T. 41 S., R. 23 E., monumented with a broken wine bottle, 18 ins. below ground (1953 record: broken glass at the base of the iron post).

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a collar of stones, 2 ft. diam., with brass cap mkd.:

T 41 S  
R 23 E | R 24 E  
1/4 S 1 |  
          2006

Deposit broken glass and a magnet in a white plastic case at the base of the stainless steel post.

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located in gentle, north-sloping terrain, open, with little vegetation.

From cor., an aluminum post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap, 3 ins., mkd. 1991 LS 4346 / T 41S / S1 NE4 SE4 / S6 / R23E / R24E / SLPM, bears S. 63°10' W., 0.035 ch. dist. Not of record, not utilized in this resurvey.

From cor., an enclosure fence, 4 ft. high, with 2 strands of barbed wire, extending north and south, bears East, 0.030 ch. dist.

---

N. 0°00.2' E., beginning new measurement.

30.562 The closing cor. of T. 41 S., Rs. 23 and 24 E., hereinbefore described.

---

SURVEY OF THE GOVERNING SECTION LINE  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

---

From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the township, hereinbefore described.

N. 89°59.9' W, bet. secs. 25 and 36.

40.000 Point for the 1/4 sec. cor. of secs. 25 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stones, 3 ft. diam. base, 22 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E

S 25

1/4 ———

S 36

2006

Set a steel fence post northwest of stainless steel post as a witness post.

Cor. is located in a shallow, sandy area, overlying bedrock.

80.000 Point for the cor. of secs. 25, 26, 35, and 36.

SURVEY OF THE GOVERNING SECTION LINE  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stones, 3 ft. diam. base, 8 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E	
S 26	S 25
S 35	S 36
2006	

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on a steep, east-facing slope, 60 ft. above a wash below, course N. 30° E.

N. 89°59.9' W, bet. secs. 26 and 35.

40.000 Point for the 1/4 sec. cor. of secs. 26 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a supporting mound of stones on the side of a hill, 3 ft. diam., 3 ft. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E	
	S 26
1/4	—
	S 35
2006	

Set a steel fence post south of stainless steel post as a witness post.

Cor. is located on a moderately steep, west-facing hillside, rocky with no vegetation.

80.000 Point for the cor. of secs. 26, 27, 34, and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a supporting mound of stones on the side of a hill, 3 ft. diam., 3 ft. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E	
S 27	S 26
S 34	S 35
2006	

Set a steel fence post north of stainless steel post as a witness post.

SURVEY OF THE GOVERNING SECTION LINE  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Cor. is located on a steep, west-facing slope, 150 ft. above the valley below.

N. 89°59.9' W, bet. secs. 27 and 34.

40.000 Point for the 1/4 sec. cor. of secs. 27 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a supporting mound of stones, 3 ft. diam., 18 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 27  
1/4 ———  
S 34  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on the southwest side of a narrow arroyo, with no vegetation.

From cor., the center of an arroyo, 15 ft. wide, course N. 35° W., bears East, 0.273 ch. dist.

From cor., the centerline of a dirt road, 15 ft. wide, extending North and South, bears East, 0.864 ch. dist.

80.000 Point for the cor. of secs. 27, 28, 33, and 34.

Cement a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a hole drilled in a sandstone outcrop, with brass face mkd.:

T 41 S R 24 E  
S 28 | S 27  
S 33 | S 34  
2006

Magnet incorporated in the stem of the brass tablet.

Set a steel fence post north of the brass tablet, on top of a ridge, as a witness post.

Cor. is located near the top of a steep, south-facing sandstone ridge, approximately 20 feet below the crest, and 300 feet above the valley floor.

N. 89°59.9' W, bet. secs. 28 and 33.

SURVEY OF THE GOVERNING SECTION LINE  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

22.123 The centerline of San Juan County road 444, a gravel road, 25 ft. wide, that bears N. 28° E. and S. 23° W.

40.000 Point for the 1/4 sec. cor. of secs. 28 and 33.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stones, 3 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 28  
1/4 ———  
S 33  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on the south side of a low mesa, in rocky ground, with no vegetation.

From cor., the centerline of a dirt road, 15 ft. wide, extending N. 25° E. / S. 25° W., bears East, 3.439 chs. dist.

80.000 Point for the cor. of secs. 28, 29, 32, and 33.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a supporting mound of stones on the side of a hill, 3 ft. diam., 3 ft. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 29 | S 28  
S 32 | S 33  
2006

Set a steel fence post east of stainless steel post as a witness post.

Cor. is located on a steep, north-sloping hillside, rocky, with scattered grass.

From cor., an aluminum post, 2 1/2 ins. diam., loosely set in a collar of stones, 2 ft. diam., projecting 14 ins. above the ground, with aluminum cap, 3 ins., mkd. 1991 LS 4346 / T41S / R24E / SLM / S29 / S28 / S32 / S33, bears N. 89°26' W., 0.144 ch. dist. Witnessed by a steel fence post. Not of record, not utilized in this resurvey.

---

N. 89°59.9' W, bet. secs. 29 and 32.

40.000 Point for the 1/4 sec. cor. of secs. 29 and 32.

SURVEY OF THE GOVERNING SECTION LINE  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with supporting mound of stones on the side of a hill, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 29  
1/4 ———  
S 32  
2006

Set a steel fence post northeast of stainless steel post as a witness post.

Cor. is located on the rocky, moderately steep, south-facing slope of White Mesa Mountain.

80.000 Point for the cor. of secs. 29, 30, 31, and 32.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, in a mound of stones, 4 ft. diam., 8 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 30 | S 29  
S 31 | S 32  
2006

From which

A juniper, 12 ins. diam., bears S. 69° W., 0.923 ch. dist., marked X BT.

A juniper, 24 ins. diam., bears N. 13° W., 0.611 ch. dist., marked X BT.

Set a steel fence post east of stainless steel post as a witness post.

Cor. is located on a fairly level bench, in eroded terrain.

N. 89°59.9' W, bet. secs. 30 and 31.

40.000 Point for the 1/4 sec. cor. of secs. 30 and 31.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with magnet at base, with brass cap mkd.:

SURVEY OF THE GOVERNING SECTION LINE  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T 41 S R 24 E  
S 30  
1/4 ———  
S 31  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located in gently rolling sand dunes, with scattered desert grasses.

From cor., an aluminum post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. 1991 LS 4346 / T41S / R24E / SLM / SEC30 / 1/14 / SEC31, bears S. 82°39' W., 0.088 ch. dist. Not of record, not utilized in this resurvey.

49.141 The centerline of San Juan County road 406, a paved road, 25 ft. wide, that bears North and South.

78.813 The cor. of secs. 30 and 31, on the W. bdy of township, hereinbefore described.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

From the cor. of secs. 25, 26, 35, and 36, on the Governing Section Line of the township, hereinbefore described.

S. 0°01.4' W, bet. secs. 35 and 36.

40.000 Point for the 1/4 sec. cor. of secs. 35 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, in a mound of stones, 3 ft. diam. base, 14 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
1/4  
S 35 | S 36  
2006

Cor. is located in open, rocky badlands, eroded with no vegetation.

70.496 The cor. of secs. 1, 2, 35, and 36, on the S. bdy of the township, hereinbefore described.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

From the cor. of secs. 25, 26, 35, and 36.

N. 0°00.2' E, bet. secs. 25 and 26.

40.000 Point for the 1/4 sec. cor. of secs. 25 and 26.

Cement a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a hole drilled in a sandstone boulder, 12 x 12 x 4 ft., with brass face mkd.:

T 41 S	R 24 E
1/4	
S 26	S 25
2006	

Magnet incorporated in the stem of the brass tablet.

Set a steel fence post and raise a mound of stones, 2 ft. diam., 24 ins. above ground, south of cor.

Cor. is located on a moderate, north-facing, slope, 30 feet below the north edge of a mesa top, surrounded by large sandstone boulders. Valley floor approximately 300 feet below cor.

80.000 Point for the cor. of secs. 23, 24, 25, and 26.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stones, 2 ft. diam., 6 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S	R 24 E
S 23	S 24
S 26	S 25
2006	

Set a steel fence post north of stainless steel post as a witness post.

Cor. is located on the east side of a wide drainage, course N. 34° W., in desert brush and scattered boulders.

From cor., a galvanized iron pipe, 1 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, mkd. T41S R24E / 23 / 24 / 26 / 25 / COC, bears N. 21°30' W., 0.023 ch. dist. Not of record, not utilized in this resurvey.

---

From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the township, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap (Navajo seal) mkd. as described in the official record of the 2004 resurvey, witnessed by a steel fence post on north side.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

S. 89°58.4' W., bet. secs. 24 and 25.

39.996 Point for the 1/4 sec. cor. of secs. 24 and 25.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a supporting mound of stones on a hillside, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 24  
1/4 ———  
S 25  
2006

Set a steel fence post south of stainless steel post as a witness post.

Cor. is located on a moderately steep, northeast-facing hillside, on rocky ground with large boulders.

79.992 The cor. of secs. 23, 24, 25, and 26.

N. 0°00.2' E, bet. secs. 23 and 24.

40.000 Point for the 1/4 sec. cor. of secs. 23 and 24.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stones, 4 ft. diam. base, 16 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
1/4  
S 23 | S 24  
2006

Set a steel fence post north of stainless steel post as a witness post.

Cor. is located on a fairly level mesa top, in desert brush.

80.000 Point for the cor. of secs. 13, 14, 23, and 24.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stones, 4 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 14 | S 13  
S 23 | S 24  
2006

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on a west-facing slope, in rocky ground, in an eroded area with many small washes.

From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the township, hereinbefore described.

S.  $89^{\circ}57.3'$  W., bet. secs. 13 and 24.

39.989 True point for 1/4 sec. cor. of secs. 13 and 24; it is impracticable to establish a permanent monument here. Point falls in an arroyo, at the base of a steep cliff, in an area of significant sloughing.

43.489 Point selected for the witness 1/4 sec. cor. of secs. 13 and 24, on a flat bench above an arroyo.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stones, 4 ft. diam. base, 8 ins. above ground, with magnet at base, with brass cap mkd.:

WC  
T 41 S R 24 E  
S 13  
1/4 →  
S 24  
2006

Set a steel fence post north of stainless steel post as a witness post.

The witness cor. is located on a fairly level bench, above an arroyo, 85 ft. wide, 60 ft. deep, course N.  $45^{\circ}$  E.

79.978 The cor. of secs. 13, 14, 23, and 24.

N.  $0^{\circ}00.2'$  E, bet. secs. 13 and 14.

40.000 Point for the 1/4 sec. cor. of secs. 13 and 14.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
1/4  
S 14 | S 13  
2006

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a steel fence post east of stainless steel post as a witness post.

Cor. is located on a fairly level mesa top, in sandy soil, with desert brush.

67.440 The centerline of San Juan County road 457, a gravel road, 24 ft. wide, that bears N. 44° W. and S. 47° E.

80.000 Point for the cor. of secs. 11, 12, 13, and 14.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a collar of stones, 3 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S	R 24 E
S 11	S 12
S 14	S 13
2006	

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on a fairly level, rocky bench, above the San Juan River floodplain to the north.

From cor., a power pole, 10 ins. diam., bears N. 80° E., 0.415 ch. dist.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

Reestablishment of the Resurvey Executed  
by H.D. Page and J.M. Lentz in 1899

From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the township, hereinbefore described.

S. 89°55.7' W., bet. secs. 12 and 13.

25.780 Right bank of the San Juan River, point for the meander cor. of secs. 12 and 13. Not monumented.

28.355 Left bank of the San Juan River, point for the meander cor. of secs. 12 and 13. Not monumented.

39.989 Point for 1/4 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original cor.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stones, 2 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 12  
1/4 ———  
S 13  
2006

Set a steel fence post south of stainless steel post as a witness post.

Cor. is located in the floodplain of the San Juan River, in sand and gravel, with short tamarisk bushes.

58.984 Point for the original meander cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original cor. Not monumented.

79.978 The cor. of secs. 11, 12, 13, and 14.

N. 0°00.2' E, bet. secs. 11 and 12.

31.150 Point for the original meander cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original cor. Not monumented.

38.000 Point selected for the witness 1/4 sec. cor. of secs. 11 and 12, on the floodplain of the San Juan River.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at base, with brass cap mkd.:

WC  
T 41 S R 24 E  
1/4  
↑  
S 11 S 12  
2006

Set a steel fence post north of stainless steel post as a witness post.

Cor. is located on the floodplain of the San Juan River, in short tamarisk bushes, in sand and gravel.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

- 39.448 Left bank of the San Juan River, point for the meander cor. of secs. 11 and 12. Not monumented.
- 40.000 True point for 1/4 sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original cor. Point falls in the San Juan River; it is impracticable to establish a permanent monument here.
- 42.367 Right bank of the San Juan River, point for the meander cor. of secs. 11 and 12. Not monumented.
- 60.208 The centerline of Utah State Highway 162, a paved road, 25 ft. wide, that bears N. 65° W. and S. 65° E.
- 80.000 Point for the cor. of secs. 1, 2, 11, and 12. There is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a collar of stones, 2 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S	R 24 E
S 2	S 1
S 11	S 12
2006	

Set a steel fence post east of stainless steel post as a witness post.

Cor. is located on the northwest edge of a wide open wash, 80 ft. wide, course West.

---

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the township, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush in a mound of stones, 4 ft. diam., 6 ins. above ground, with brass cap (Navajo seal) mkd. as described in the official record of the 2004 resurvey.

Set a steel fence post south of the stainless steel post as a witness post.

From cor., a rebar, 1/2 in. diam., firmly set, projecting 4 ins. above ground, bears N. 32°38' W., 0.165 ch. Not utilized in the course of this resurvey.

S. 89°51.8' W., bet. secs. 1 and 12.

- 39.983 Point for 1/4 sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original cor.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stones, 2 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 1  
1/4 —  
S 12  
2006

Set a steel fence post southeast of stainless steel post as a witness post.

Cor. is located on gentle, west-sloping terrain, with sandstone outcrops and desert brush.

79.966 The cor. of secs. 1, 2, 11, and 12.

---

N. 0°02.4' E, bet. secs. 1 and 2.

40.034 Point for 1/4 sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
1/4  
S 2 | S 1  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on gentle, south-sloping terrain, sandy with scattered desert brush.

80.006 The closing cor. of secs. 1 and 2, T. 41 S., R. 24 E., monumented with a sandstone, 18 x 13 x 6 ins., firmly set, projecting 9 ins. above ground, mkd. CC on northwest face, 5 grooves on northeast edge, 1 groove on southwest edge, in embedded mound of stones, 3 ft. diam., 2 ft. above ground, witnessed by a rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, and fiberglass rod (Record: 15 x 10 x 6 ins., CC on south, 5 grooves on west, 1 groove on east).

Add the marks AM to original stone, bury stone in place.

80.068 The closing cor. of secs. 1 and 2, at intersection with the south bdy. of T. 40 S., R. 24 E., the Eighth Standard Parallel South, hereinbefore described.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

---

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

---

From the cor. of secs. 26, 27, 34, and 35, on the Governing  
Section Line of the township, hereinbefore described.

S. 0°00.7' W, bet. secs. 34 and 35.

40.000 Point for the 1/4 sec. cor. of secs. 34 and 35.

Cement a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a  
hole drilled in a sandstone outcrop, with brass face mkd.:

T 41 S R 24 E  
1/4  
S 34 | S 35  
2006

From which

A juniper, 5 ins. diam., bears N. 27° W., 0.473 ch. dist.,  
marked X BT.

Magnet incorporated in the stem of the brass tablet.

Set a steel fence post south of brass tablet as a witness post.

Raise a mound of stones east of cor.

Cor. is located on a fairly level sandstone face, surrounded by  
low mesas, with scattered desert brush.

70.487 The cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the  
township, hereinbefore described.

---

From the cor. of secs. 26, 27, 34, and 35, on the Governing  
Section Line of the township, hereinbefore described.

N. 0°00.5' W, bet. secs. 26 and 27.

40.000 Point for the 1/4 sec. cor. of secs. 26 and 27.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27  
ins. in the ground, with magnet at base, with brass cap mkd.:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T 41 S R 24 E  
1/4  
S 27 | S 26  
2006

Set a steel fence post north of stainless steel post as a witness post.

Cor. is located in rolling, sandy hills.

From cor., a galvanized iron pipe, 1 1/4 ins. diam., firmly set, projecting 4 ins. above the ground, mkd. 1/4 27/26 COC, bears N. 23°06' W., 0.124 ch. dist. Not of record, not utilized in this resurvey.

80.000 Point for the cor. of secs. 22, 23, 26, and 27.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stones, 4 ft. diam., 10 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 22 | S 23  
S 27 | S 26  
2006

Set a steel fence post northwest of stainless steel post as a witness post.

Cor. is located in a broad and shallow wash, course N. 21° W.

From cor., an iron pipe, 1 in. diam., firmly set, projecting 10 ins. above the ground, mkd. T41S R24 22/23/27/26, bears N. 81° E., 0.145 ch. dist. Not of record, not utilized in this resurvey.

From cor., the centerline of a dirt road, 10 ft. wide, extending N. 40° E. / S. 40° W., bears West, 1.439 chs. dist.

---

From the cor. of secs. 23, 24, 25, and 26.

N. 89°59.9' W., bet. secs. 23 and 26.

40.000 Point for the 1/4 sec. cor. of secs. 23 and 26.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stones, 4 ft. diam. base, 16 ins. above ground, with magnet at base, with brass cap mkd.:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T 41 S R 24 E  
S 23  
1/4 ———  
S 26  
2006

Set a steel fence post north of stainless steel post as a witness post.

Cor. is located on fairly level terrain, surrounded by mesas, in rocky and barren ground.

80.000 The cor. of secs. 22, 23, 26, and 27.

---

N. 0°00.5' W, bet. secs. 22 and 23.

40.000 Point for the 1/4 sec. cor. of secs. 22 and 23.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stones, 4 ft. diam. base, 12 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
1/4  
S 22 | S 23  
2006

Set a steel fence post northeast of stainless steel post as a witness post.

Cor. is located on a gently rolling plain, with no vegetation.

80.000 Point for the cor. of secs. 14, 15, 22, and 23.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, in a mound of stones, 3 ft. diam., 9 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 15 | S 14  
S 22 | S 23  
2006

Set a steel fence post east of stainless steel post as a witness post.

Cor. is located on fairly level terrain, with no vegetation.

From cor., an aluminum post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, mkd. T41S R24E SLM

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

15/14/22/23, bears N. 53°54' E., 0.228 ch. dist. Not of record, not utilized in this resurvey.

From cor., the centerline of a dirt road, 15 ft. wide, extending N. 10° W. / S. 10° E., bears East, 0.682 ch. dist.

---

From the cor. of secs. 13, 14, 23, and 24.

N. 89°59.9' W., bet. secs. 14 and 23.

40.000 Point for the 1/4 sec. cor. of secs. 14 and 23.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 14  
1/4 ———  
S 23  
2006

Set a steel fence post southwest of stainless steel post as a witness post.

Cor. is located in rolling, sandy hills, on a gentle, west-facing slope.

From cor., an aluminum post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, mkd. T41S R24E SLM 1/4 14/23 1992 LS4346, bears N. 71°42' E., 0.222 ch. dist. Not of record, not utilized in this resurvey.

80.000 The cor. of secs. 14, 15, 22, and 23.

---

N. 0°00.5' W, bet. secs. 14 and 15.

40.000 Point for the 1/4 sec. cor. of secs. 14 and 15.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stones, 3 ft. diam. base, 12 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
1/4  
S 15 | S 14  
2006

Set a steel fence post southwest of stainless steel post as a witness post.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Cor. is located on a small knoll, above eroded terrain, with sandstone outcrops and scattered desert grasses.

From cor., a galvanized iron pipe, 1 1/2 ins. diam., firmly set, projecting 17 ins. above the ground, mkd. 1/4 S15 S14, bears N. 79°20' E., 0.226 ch. dist. Not of record, not utilized in this resurvey.

80.000

Point for the cor. of secs. 10, 11, 14, and 15.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a collar of stones, 3 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S R 24 E	
S 10	S 11
S 15	S 14
2006	

Set a steel fence post east of stainless steel post as a witness post.

Cor. is located in rolling, sandy hills, on the northwest face of a dune, with scattered desert brush.

From cor., a galvanized iron pipe, 1 3/4 ins. diam., firmly set, projecting 23 ins. above the ground, mkd. T41S R24E 10/11/15/14, bears N. 69°21' E., 0.279 ch. dist. Not of record, not utilized in this resurvey.

From the cor. of secs. 11, 12, 13, and 14.  
N. 89°59.9' W., bet. secs. 11 and 14.

9.704

The centerline of San Juan County road 457, a gravel road, 24 ft. wide, that bears N. 47° W. and S. 41° E.

40.000

Point for the 1/4 sec. cor. of secs. 11 and 14.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a collar of stones, 2 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S R 24 E	
	S 11
1/4	—
	S 14
2006	

Set a steel fence post east of stainless steel post as a witness post.

Cor. is located on the rocky, east-facing slope of a drainage.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

From the cor., an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, with an aluminum cap mkd. Maness Colo T41S R24E 1/4 S11 S14 1996 LS19612, bears N. 79°43' E., 0.309 ch. dist. Not of record, not utilized in this resurvey.

From the cor., the center of a rocky drainage, course N. 23° E., bears East, 0.758 ch. dist.

80.000 The cor. of secs. 10, 11, 14, and 15.

---

N. 0°00.5' W, bet. secs. 10 and 11.

40.000 Point for the 1/4 sec. cor. of secs. 10 and 11.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
1/4  
S 10 | S 11  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on gentle, north-sloping ground, near the base of low mesas to the south.

From cor., an aluminum post, 2 1/2 ins. diam., firmly set, projecting 17 ins. above the ground, mkd. T41S R24E SLM 1/4 10/11 1992 LS4346, bears N. 74°47' E., 0.266 ch. dist. Witnessed by steel fence post and iron pipe. Not of record, not utilized in this resurvey.

42.195 The centerline of San Juan County road 457, a gravel road, 24 ft. wide, that bears N. 79° W. and S. 79° E.

80.000 Point for the cor. of secs. 2, 3, 10, and 11.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 3 | S 2  
S 10 | S 11  
2006

Set a steel fence post west of stainless steel post as a witness post.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Cor. is located on the San Juan River floodplain, in thick tamarisk.

From cor., an aluminum post, 2 1/2 ins. diam., firmly set, projecting 13 ins. above the ground, mkd. T41S R24E SLM S3/S2/S10/S11 1991 LS4346, bears N. 68°13' E., 0.248 ch. dist. Not of record, not utilized in this resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

Reestablishment of the Resurvey Executed  
by H.D. Page and J.M. Lentz in 1899

From the cor. of secs. 1, 2, 11, and 12.

N. 89°59.9' W., bet. secs. 2 and 11.

40.000 Point for 1/4 sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 2  
1/4 ———  
S 11  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on the north shoulder of paved highway 162.

41.198 The centerline of Utah State Highway 162, a paved road, 25 ft. wide, that bears N. 55° W. and S. 58° E.

55.042 Right bank of the San Juan River, point for the meander cor. of secs. 2 and 11. Not monumented.

66.656 Left bank of the San Juan River, point for the meander cor. of secs. 2 and 11. Not monumented.

67.450 Point for the original meander cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original cor. Not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

- 80.000 The cor. of secs. 2, 3, 10, and 11.
- 
- N. 0°08.0' E, bet. secs. 2 and 3.
- 14.706 Point for the original meander cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original cor. Not monumented.
- 26.828 Left bank of the San Juan River, point for the meander cor. of secs. 2 and 3. Not monumented.
- 30.394 Right bank of the San Juan River, point for the meander cor. of secs. 2 and 3. Not monumented.
- 40.044 Point for 1/4 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original cor.
- Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with magnet at base, with brass cap mkd.:
- T 41 S R 24 E  
1/4  
S 3 | S 2  
2006
- Set a steel fence post east of stainless steel post as a witness post.
- Cor. is located on the floodplain of the San Juan River, in sandy soil, surrounded by short tamarisk.
- 59.078 The centerline of Utah State Highway 162, a paved road, 25 ft. wide, that bears N. 53° W. and S. 53° E.
- 80.088 The closing cor. of secs. 2 and 3, at intersection with the south bdy. of T. 40 S., R. 24 E., the Eighth Standard Parallel South, hereinbefore described.

---

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

---

- From the cor. of secs. 27, 28, 33, and 34, on the Governing Section Line of the township, hereinbefore described.
- S. 0°01.0' W, bet. secs. 33 and 34.
- 40.000 Point for the 1/4 sec. cor. of secs. 33 and 34.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stones, 3 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
1/4  
S 33 | S 34  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on the east shoulder of a primitive dirt road, gently sloping southwest.

From cor., the centerline of a primitive dirt road, 8 ft. wide, extending N. 24° E. / S. 24° W., bears West, 0.152 ch. dist.

54.246 The centerline of San Juan County road 444, a gravel road, 25 ft. wide, that bears N. 53° W. and S. 63° E.

70.494 The cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the township, hereinbefore described.

---

From the cor. of secs. 27, 28, 33, and 34, on the Governing Section Line of the township, hereinbefore described.

N. 0°01.2' W, bet. secs. 27 and 28.

40.000 Point for the 1/4 sec. cor. of secs. 27 and 28.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
1/4  
S 28 | S 27  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located in rolling sand dunes.

80.000 Point for the cor. of secs. 21, 22, 27, and 28.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stones, 3 ft. diam., with magnet at base, with brass cap mkd.:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T 41 S	R 24 E
S 21	S 22
S 28	S 27
2006	

Set a steel fence post south of stainless steel post as a witness post.

Cor. is located in a wash, 70 ft. wide, course N. 15° E., surrounded by short tamarisk.

From the cor. of secs. 22, 23, 26, and 27.

N. 89°59.9' W., bet. secs. 22 and 27.

40.000 Point for the 1/4 sec. cor. of secs. 22 and 27.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., on a bedrock shelf, in a mound of stones, 4 ft. diam. base, 28 ins. above ground, with brass cap mkd.:

T 41 S	R 24 E
	S 22
	1/4 ———
	S 27
2006	

Cement a magnet in a drilled hole at the base of the stainless steel post.

Set a steel fence post and raise a mound of stones northeast of stainless steel post as a witness post.

Cor. is located in an open valley, level terrain, in a north / south power line corridor, with exposed sandstone outcrops.

80.000 The cor. of secs. 21, 22, 27, and 28.

N. 0°01.2' W, bet. secs. 21 and 22.

40.000 Point for the 1/4 sec. cor. of secs. 21 and 22.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S	R 24 E
	1/4
S 21	S 22
2006	

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a steel fence post east of stainless steel post as a witness post.

Cor. is located on a sand dune, on a bank above Sahgzie Wash, course N. 30° E.

80.000 Point for the cor. of secs. 15, 16, 21, and 22.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S	R 24 E
S 16	S 15
S 21	S 22
2006	

Set a steel fence post east of stainless steel post as a witness post.

Cor. is located in gently rolling sand dunes, with desert brush.

---

From the cor. of secs. 14, 15, 22, and 23.

N. 89°59.9' W., bet. secs. 15 and 22.

40.000 Point for the 1/4 sec. cor. of secs. 15 and 22.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stones, 4 ft. diam. base, 22 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S	R 24 E
S 15	
1/4	—
S 22	
2006	

Set a steel fence post southeast of stainless steel post as a witness post.

Cor. is located in fairly level terrain, surrounded by low, eroded mesas.

From cor., an aluminum post, 2 1/2 ins. diam., loosely set in a mound of stones, 3 ft. base, 2 ft. above the ground, mkd. T41S R24E SLM 1/4 15/22 1992 LS4346, bears N. 51°25' E., 0.326 ch. dist. Not of record, not utilized in this resurvey.

80.000 The cor. of secs. 15, 16, 21, and 22.

---

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

N. 0°01.2' W, bet. secs. 15 and 16.

40.000 Point for the 1/4 sec. cor. of secs. 15 and 16.

Cement a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a hole drilled in a sandstone outcrop, with brass face mkd.:

T 41 S R 24 E  
1/4  
S 16 | S 15  
2006

From which

A steel fence post, in a mound of stones, bears N. 80° W., 0.127 ch. dist.

Cor. is located on an east-facing sandstone slope, moderately steep, 25 ft. below a mesa top.

80.000 Point for the cor. of secs. 9, 10, 15, and 16.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stones, 3 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 9 | S 10  
S 16 | S 15  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located in gently rolling sandy hills, northeast of a ranch house.

From cor., an iron pipe, 1 1/2 ins. diam., firmly set, projecting 11 ins. above ground, mkd. T41 R24E 9/10/16/15 PPC, bears N. 62°33' E., 0.169 ch. dist. Not of record, not utilized in this resurvey.

From the cor. of secs. 10, 11, 14, and 15.

N. 89°59.9' W., bet. secs. 10 and 15.

40.000 Point for the 1/4 sec. cor. of secs. 10 and 15.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, in a mound of stones, 3 ft. diam.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

base, 8 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 10  
1/4 ———  
S 15  
2006

Set a steel fence post east of stainless steel post as a witness post.

Cor. is located east of eroded sandstone cliffs, in a sandy wash.

80.000 The cor. of secs. 9, 10, 15, and 16.

---

N. 0°01.2' W, bet. secs. 9 and 10.

40.000 Point for the 1/4 sec. cor. of secs. 9 and 10.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
1/4  
S 9 | S 10  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located in gently rolling sand dunes, northwest of an oilfield tank batter.

From cor., an iron pipe, 1 1/2 ins. diam., firmly set, projecting 7 ins. above ground, bears N. 81°53' E., 0.142 ch. dist. Not of record, not utilized in this resurvey.

44.859 The centerline of San Juan County road 457, a gravel road, 24 ft. wide, that bears N. 60° E. and S. 60° W.

80.000 Point for the cor. of secs. 3, 4, 9, and 10.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a collar of stones, 2 ft. diam., with magnet at base, with brass cap mkd.:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T 41 S	R 24 E
S 4	S 3
S 9	S 10
2006	

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on a fairly level plain, in sandy soil.

---

From the cor. of secs. 2, 3, 10, and 11.

N. 89°59.9' W., bet. secs. 3 and 10.

40.000 Point for the 1/4 sec. cor. of secs. 3 and 10.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S	R 24 E
S 3	
1/4	—
S 10	
2006	

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on a level, sandy plain, with no vegetation.

80.000 The cor. of secs. 3, 4, 9, and 10.

---

N. 0°01.5' E., bet. secs. 3 and 4.

40.053 Point for the 1/4 sec. cor. of secs. 3 and 4.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a collar of stones, 2 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S	R 24 E
S 4	S 3
2006	

Set a steel fence post north of stainless steel post as a witness post.

Cor. is located on a level plain, with no vegetation.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

---

Reestablishment of the Resurvey Executed  
by H.D. Page and J.M. Lentz in 1899

---

From the 1/4 sec. cor. of secs. 3 and 4.

N. 0°01.5' E., bet. secs. 3 and 4.

- 24.507 Left bank of the San Juan River, point for the meander cor. of secs. 3 and 4. Not monumented.
- 26.806 Right bank of the San Juan River, point for the meander cor. of secs. 3 and 4. Not monumented.
- 27.086 Point for the original meander cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original cor. Not monumented.
- 35.691 The centerline of Utah State Highway 162, a paved road, 25 ft. wide, that bears S. 80° W. and N. 80° E.
- 39.996 The closing cor. of secs. 3 and 4, T. 41 S., R. 24 E., monumented with a sandstone, 18 x 12 x 7 ins., laying loose on a mound of stones, mkd. CC on one face, 3 grooves on one perpendicular face, 3 grooves on other perpendicular face (Record: 12 x 10 x 6 ins., CC on south, 3 grooves on east & west faces, mound of stones south).
- Add the marks AM to original stone, bury stone in place.
- 40.053 The closing cor. of secs. 3 and 4, at intersection with the south bdy. of T. 40 S., R. 24 E., the Eighth Standard Parallel South, hereinbefore described.

---

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

---

From the cor. of secs. 28, 29, 32, and 33, on the Governing Section Line of the township, hereinbefore described.

S. 0°02.0' E., bet. secs. 32 and 33.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

36.561 The centerline of a dirt road, 25 ft. wide, extending N. 56° E. and S. 56° W.

40.000 Point for the 1/4 sec. cor. of secs. 32 and 33.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
1/4  
S 32 | S 33  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on gentle, south-sloping terrain.

From cor., an aluminum post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, mkd. T41S R24E SLM Sec32/Sec33 1/4 1991 LS4346, bears S. 88°49' W., 0.090 ch. dist. Not of record, not utilized in this resurvey.

70.515 The cor. of secs. 4, 5, 32, and 33, on the S. bdy. of township, hereinbefore described.

---

From the cor. of secs. 28, 29, 32, and 33, on the Governing Section Line of the township, hereinbefore described.

N. 0°01.8' W, bet. secs. 28 and 29.

40.000 Point for the 1/4 sec. cor. of secs. 28 and 29.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stones, 4 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
1/4  
S 29 | S 28  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on a barren ridge, between two washes trending east / west.

80.000 Point for the cor. of secs. 20, 21, 28, and 29.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stones, 2 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S	R 24 E
S 20	S 21
S 29	S 28
2006	

Set a steel fence post north of stainless steel post as a witness post.

Cor. is located on a rocky, moderately steep, west-facing slope, with large boulders.

From cor., a galvanized iron post, 1 1/2 ins. diam., firmly set, projecting 20 ins. above ground, mkd. T41S R24E 20/21/29/28, bears N. 86°15' W., 0.331 ch. dist. Not of record, not utilized in this survey.

From the cor. of secs. 21, 22, 27, and 28.

N. 89°59.9' W., bet. secs. 21 and 28.

17.606 The centerline of San Juan County road 444, a curving gravel road, 25 ft. wide, that bears N. 15° W. and S. 8° W.

40.000 Point for the 1/4 sec. cor. of secs. 21 and 28.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a collar of stones, 3 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S	R 24 E
	S 21
	1/4 ———
	S 28
2006	

Set a steel fence post south of stainless steel post as a witness post.

Cor. is located on the northwest face of a sand dune, in scattered grass, above a drainage, course N. 51° E.

80.000 The cor. of secs. 20, 21, 28, and 29.

N. 0°01.8' W, bet. secs. 20 and 21.

40.000 Point for the 1/4 sec. cor. of secs. 20 and 21.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a collar of stones, 2 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
1/4  
S 20 | S 21  
2006

Set a steel fence post north of stainless steel post as a witness post.

Cor. is located on a fairly level, barren plain, near a housing subdivision, south of White Rock Curve Village.

From cor., the center of a power line, extending North and South, bears West, 0.303 ch. dist.

77.500

Point selected for the witness 1/4 sec. cor. of secs. 16, 17, 20, and 21, on a sandy dune south of an oil and gas processing facility.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at base, with brass cap mkd.:

WC  
T 41 S R 24 E  
↑  
S 17 | S 16  
S 20 | S 21  
2006

Set a steel fence post north of stainless steel post as a witness post.

Cor. is located on a sandy dune, south of a gated and locked oil and gas processing facility.

From cor., the centerline of a dirt road, 25 ft. wide, extending North and South, bears West, 1.485 chs. dist.

From cor., the southwest corner of a chain link enclosure fence for the oil and gas processing facility bears N. 21°30' W, 1.122 chs. dist.

80.000

True point for the cor. of secs. 16, 17, 20, and 21; it is impossible to establish a monument here. Point falls inside of a fenced and locked oil and gas processing facility.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

From the cor. of secs. 15, 16, 21, and 22.

N. 89°59.9' W., bet. secs. 16 and 21.

36.023 The centerline of San Juan County road 444, a gravel road, 25 ft. wide, that bears North and South.

40.000 Point for the 1/4 sec. cor. of secs. 16 and 21.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stones, 2 ft. diam., 6 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 16  
1/4 ———  
S 21  
2006

Set a steel fence post northeast of stainless steel post as a witness post.

Cor. is located on a gentle, east-sloping hill.

From cor., the center of a power line, extending North and South, bears East, 0.152 ch. dist.

80.000 The true point for the cor. of secs. 16, 17, 20, and 21.

N. 0°01.8' W, bet. secs. 16 and 17.

27.049 The centerline of San Juan County road 444, a gravel road, 25 ft. wide, that bears N. 81° W. and S. 81° E.

40.000 Point for the 1/4 sec. cor. of secs. 16 and 17.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
1/4  
S 17 | S 16  
2006

Set a steel fence post north of stainless steel post as a witness post.

Cor. is located on a gentle, north-sloping plain, south of a housing subdivision.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

From cor., the center of a power line, extending North and South, bears West, 0.182 ch. dist.

From cor., a galvanized iron pipe, 1 1/2 ins. diam., firmly set, projecting 19 ins. above ground, mkd. 1/4 S16/S17, bears N. 65°16' W., 0.288 ch. dist. Not of record, not utilized in this survey.

47.703 The centerline of San Juan County road 4251, a gravel road, 24 ft. wide, that bears N. 48° E. and S. 40° W.

80.000 Point for the cor. of secs. 8, 9, 16, and 17.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stones, 3 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S	R 24 E
S 8	S 9
S 17	S 16
2006	

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located in rolling, sandy hills.

From cor., an iron pipe, 1 3/4 ins. diam., firmly set, projecting 22 ins. above ground, mkd. T41S R24E 8/9/17/16, bears N. 76° W., 0.211 ch. dist. Not of record, not utilized in this survey.

From cor., a rebar, 1/2 in. diam., firmly set flush with ground, mkd. Huddleston LS 161297, bears N. 59° W., 1.303 chs. dist. Not of record, not utilized in this survey.

From cor., a rebar, 1/2 in. diam., firmly set flush with ground, bears N. 42° W., 1.417 chs. dist. Witnessed by steel fence post. Not of record, not utilized in this survey.

From the cor. of secs. 9, 10, 15, and 16.

N. 89°59.9' W., bet. secs. 9 and 16.

40.000 Point for the 1/4 sec. cor. of secs. 9 and 16.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, in a collar of stones, 2 ft. diam., with magnet at base, with brass cap mkd.:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T 41 S R 24 E  
S 9  
1/4 ———  
S 16  
2006

Set a steel fence post northwest of stainless steel post as a witness post.

Cor. is located in the southeast shoulder of a dirt road.

40.334 The centerline of San Juan County road 4251, a gravel road, 24 ft. wide, that bears N. 43° E. and S. 43° W.

80.000 The cor. of secs. 8, 9, 16, and 17.

---

N. 0°01.8' W, bet. secs. 8 and 9.

40.000 Point for the 1/4 sec. cor. of secs. 8 and 9.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stones, 2 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
1/4  
S 8 | S 9  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located in a rolling, sandy hills, with scattered desert brush.

From cor., an iron pipe, 1 1/4 ins. diam., firmly set, projecting 9 ins. above ground, bears N. 68° W., 0.184 ch. dist. Not of record, not utilized in this survey.

52.227 The centerline of San Juan County road 457, a gravel road, 24 ft. wide, that bears N. 64° W. and S. 64° E.

80.000 Point for the cor. of secs. 4, 5, 8, and 9.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stones, 2 ft. diam., with magnet at base, with brass cap mkd.:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T 41 S	R 24 E
S 5	S 4
S 8	S 9
2006	

Set a steel fence post northwest of stainless steel post as a witness post.

Cor. is located in rolling, sandy hills.

From cor., the centerline of a dirt road, 15 ft. wide, extending N. 43° E. / S. 32° W., bears West, 0.955 chs. dist.

From the cor. of secs. 3, 4, 9, and 10.

N. 89°59.9' W., bet. secs. 4 and 9.

40.000 Point for the 1/4 sec. cor. of secs. 4 and 9.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stones, 1 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S	R 24 E
	S 4
	1/4 ———
	S 9
2006	

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on a fairly level plain, with scattered brush.

80.000 The cor. of secs. 4, 5, 8, and 9.

N. 0°11.7' E, bet. secs. 4 and 5.

40.066 Point for the 1/4 sec. cor. of secs. 4 and 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stones, 2 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S	R 24 E
	1/4
S 5	S 4
2006	

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on a level bench above the San Juan River, with scant grass and sandy soil, northeast of a water tank.

From cor., a galvanized iron pipe, 1 1/2 ins. diam., set flush with the ground, mkd. 1/4 5/4, bears N. 6°18' E., 0.045 ch. dist. Not of record, not utilized in this survey.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

---

Reestablishment of the Resurvey Executed  
by H.D. Page and J.M. Lentz in 1899

---

From the 1/4 sec. cor. of secs. 4 and 5.

N. 0°11.7' E, bet. secs. 4 and 5.

- 13.272 Point for the original meander cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original cor. Not monumented.
- 30.470 Left bank of the San Juan River, point for the meander cor. of secs. 4 and 5. Not monumented.
- 36.382 Right bank of the San Juan River, point for the meander cor. of secs. 4 and 5. Not monumented.
- 39.797 The centerline of Utah State Highway 162, a paved road, 25 ft. wide, that bears N. 72° W. and S. 72° E.
- 40.066 The closing cor. of secs. 4 and 5, at intersection with the south bdy. of T. 40 S., R. 24 E., the Eighth Standard Parallel South, hereinbefore described.

---

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

---

From the cor. of secs. 29, 30, 31, and 32, on the Governing Section Line of the township, hereinbefore described.

S. 0°01.4' E., bet. secs. 31 and 32.

- 40.000 Point for the 1/4 sec. cor. of secs. 31 and 32.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
1/4  
S 31 | S 32  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on northeast-sloping ground, sandy, with scattered desert grasses, below a mesa to the northwest.

70.529 The cor. of secs. 5, 6, 31, and 32, on the S. bdy. of township, hereinbefore described.

---

From the cor. of secs. 29, 30, 31, and 32, on the Governing Section Line of the township, hereinbefore described.

N. 0°02.5' W, bet. secs. 29 and 30.

40.000 Point for the 1/4 sec. cor. of secs. 29 and 30.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
1/4  
S 30 | S 29  
2006

Set a steel fence post south of stainless steel post as a witness post.

Cor. is located on a gentle, northwest-sloping, sandy hill, in scattered desert brush.

80.000 Point for the cor. of secs. 19, 20, 29, and 30.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stones, 3 ft. diam., 10 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 19 | S 20  
S 30 | S 29  
2006

Set a steel fence post south of stainless steel post as a witness post.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Cor. is located in rolling hills, southeast of a paved highway.

---

From the cor. of secs. 20, 21, 28, and 29.

N. 89°59.9' W., bet. secs. 20 and 29.

40.000 Point for the 1/4 sec. cor. of secs. 20 and 29.

Cement a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a hole drilled in a sandstone outcrop, with brass face mkd.:

T 41 S R 24 E  
S 20  
1/4 ———  
S 29  
2006

From which

A steel fence post, in a mound of stones, 3 ft. diam., 24 ins. above ground, bears N. 37°09' E., 0.032 ch. dist.

Magnet incorporated in the stem of the tablet.

Cor. is located on a rocky bench, on the north side of White Mesa Mtn.

80.000 The cor. of secs. 19, 20, 29, and 30.

---

N. 89°59.2' W., bet. secs. 19 and 30.

5.063 The centerline of San Juan County road 406, a paved road, 25 ft. wide, that bears N. 49° E. and S. 49° W.

40.000 Point for the 1/4 sec. cor. of secs. 19 and 30.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 19  
1/4 ———  
S 30  
2006

Set a steel fence post east of stainless steel post as a witness post.

Cor. is located on the southwest face of a sand dune.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

- 71.284 The centerline of San Juan County road 410, a gravel road, 30 ft. wide, that bears N. 16° W. and S. 19° E.
- 78.732 The cor. of secs. 19 and 30, T. 41 S., R. 24 E., on the W. bdy. of the township, hereinbefore described.

---

From the cor. of secs. 19, 20, 29, and 30.

N. 0°02.5' W, bet. secs. 19 and 20.

- 4.447 The centerline of San Juan County road 406, a paved road, 25 ft. wide, that bears N. 49° E. and S. 49° W.

- 40.000 Point for the 1/4 sec. cor. of secs. 19 and 20.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
1/4  
S 19 | S 20  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on the east edge of a well pad, Exxon Mobil Well #19-97, Ratherford Unit.

- 80.000 Point for the cor. of secs. 17, 18, 19, and 20.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a collar of stones, 2 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 18 | S 17  
S 19 | S 20  
2006

Set a steel fence post northeast of stainless steel post as a witness post.

Cor. is located in rolling sand dunes, with scattered desert plants.

From cor., the centerline of a dirt road, 18 ft. wide, extending N. 10° W. / S. 10° E., bears East, 1.909 chs. dist.

From cor., a galvanized iron pipe, 1 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, mkd. T41S R24E 18/17/19/20,

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

bears N. 79°41' W., 0.587 ch. dist. Not of record, not utilized in this survey.

---

From the cor. of secs. 16, 17, 20, and 21.

N. 89°59.9' W., bet. secs. 17 and 20.

27.523 The centerline of San Juan County road 406, a paved road, 25 ft. wide, that bears N. 24° E. and S. 24° W.

40.000 Point for the 1/4 sec. cor. of secs. 17 and 20.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 17  
1/4 ———  
S 20  
2006

Set a steel fence post north of stainless steel post as a witness post.

Cor. is located in a broad, sandy wash, course N. 30° E.

From cor., a power line, extending North and South, bears West, 1.394 chs. dist.

80.000 The cor. of secs. 17, 18, 19, and 20.

---

N. 89°58.1' W., bet. secs. 18 and 19.

40.000 Point for the 1/4 sec. cor. of secs. 18 and 19.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stones, 4 ft. diam., 14 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 18  
1/4 ———  
S 19  
2006

Set a steel fence post south of stainless steel post as a witness post.

Cor. is located on a fairly level mesa top, surrounded by eroded gullies.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

From cor., a power line, extending North and South, bears West, 1.076 chs. dist.

From cor., a galvanized iron pipe, 1 in. diam., firmly set, projecting 15 ins. above the ground, mkd. 1/4 18/19 PPC, bears N. 86°02' W., 0.631 ch. dist. Not of record, not utilized in this survey.

78.661 The cor. of secs. 18 and 19, T. 41 S., R. 24 E., on the W. bdy. of the township, hereinbefore described.

---

From the cor. of secs. 17, 18, 19, and 20.

N. 0°02.5' W, bet. secs. 17 and 18.

40.000 Point for the 1/4 sec. cor. of secs. 17 and 18.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stones, 3 ft. diam., 8 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
1/4  
S 18 | S 17  
2006

Set a steel fence post northwest of stainless steel post as a witness post.

Cor. is located on a small knoll, in gently rolling terrain, south of Flat Top Mountain.

From cor., a power line, extending N. 20° W. and S. 20° E., bears West, 0.189 ch. dist

80.000 Point for the cor. of secs. 7, 8, 17, and 18.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stones, 4 ft. diam., 10 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 7 | S 8  
S 18 | S 17  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on the east edge of Flat Top Mountain, on a gentle, east-sloping face, in rocky terrain.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

From cor., an iron pipe, 1 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, bears N. 85°47' W., 0.607 ch. dist. Not of record, not utilized in this survey.

From the cor. of secs. 8, 9, 16, and 17.

N. 89°59.9' W., bet. secs. 8 and 17.

2.028 The centerline of San Juan County road 406, a paved road, 25 ft. wide, that bears North and South.

40.000 Point for the 1/4 sec. cor. of secs. 8 and 17.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stones, 5 ft. diam., 10 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 8  
1/4 ———  
S 17  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located in rolling hills, in soft sandstone below sandy ground.

From cor., a rebar, 5/8 ins. diam., firmly set, projecting 10 ins. above ground, bears N. 85°18' W., 0.405 ch. dist.

80.000 The cor. of secs. 7, 8, 17, and 18.

N. 89°58.3' W., bet. secs. 7 and 18.

40.000 Point for the 1/4 sec. cor. of secs. 7 and 18.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground to bedrock, in a mound of stones, 3 ft. diam., 6 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 7  
1/4 ———  
S 18  
2006

Set a steel fence post southwest of stainless steel post as a witness post.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Cor. is located on the fairly level top of Flat Top Mountain, in rocky ground.

From cor., an iron pipe, 1 1/2 ins. diam., firmly set, projecting 20 ins. above the ground, bears N. 88°24' W., 0.716 ch. dist. Not of record, not utilized in this survey.

78.594 The cor. of secs. 7 and 18, T. 41 S., R. 24 E., on the W. bdy. of the township, hereinbefore described.

---

From the cor. of secs. 7, 8, 17, and 18.

N. 0°02.5' W, bet. secs. 7 and 8.

40.000 Point for the 1/4 sec. cor. of secs. 7 and 8.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, in a mound of stones, 4 ft. diam., 24 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
1/4  
S 7 | S 8  
2006

Cor. is located on a rocky bench on the northeast edge of Flat Top Mountain.

From cor., a telephone pole, 10 ins. diam., bears N. 17° W., 0.254 ch. dist.

80.000 Point for the cor. of secs. 5, 6, 7, and 8.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stones, 4 ft. diam., 18 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 6 | S 5  
S 7 | S 8  
2006

Cor. is located in eroded badlands, in sandy soil on top of bedrock.

From cor., an aluminum post, 2 1/2 ins. diam., firmly set, projecting 13 ins. above the ground, mkd. T41S R23E SLM 6/5/7/8 1991 LS 4346, bears N. 58° E., 0.124 ch. dist. Not of record, not utilized in this survey.

---

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

From the cor. of secs. 4, 5, 8, and 9.

N. 89°59.9' W., bet. secs. 5 and 8.

37.417 The centerline of San Juan County road 406, a paved road, 25 ft. wide, that bears N. 48° W. and S. 48° E.

40.000 Point for the 1/4 sec. cor. of secs. 5 and 8.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 5  
1/4 ———  
S 8  
2006

Set a steel fence post north of stainless steel post as a witness post.

Cor. is located in a low lying, sandy area, south of a paved highway.

80.000 The cor. of secs. 5, 6, 7, and 8.

N. 89°58.1' W., bet. secs. 6 and 7.

40.000 Point for the 1/4 sec. cor. of secs. 6 and 7.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, in a mound of stones, 3 ft. diam., 13 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
S 6  
1/4 ———  
S 7  
2006

Cor. is located on the fairly level top of Flat Top Mountain, in rocky ground atop bedrock.

From cor., the centerline of a maintained gravel road, 17 feet wide, extending N. 33° E. / S. 33° W., bears West, 1.455 chs. dist.

From cor., an aluminum post, 2 1/2 ins. diam., firmly set, projecting 13 ins. above the ground, mkd. T41S R24E SLM 1/4 SEC 6/SEC 7 1992 LS 4346, witnessed by a fence post, bears

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

N.  $76^{\circ}32'$  W., 0.152 ch. dist. Not of record, not utilized in this survey.

78.509 The cor. of secs. 6 and 7, T. 41 S., R. 24 E., on the W. bdy. of the township, hereinbefore described.

---

From the cor. of secs. 5, 6, 7, and 8.

N.  $0^{\circ}02.5'$  W., bet. secs. 5 and 6.

40.062 Point for the 1/4 sec. cor. of secs. 5 and 6.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
1/4  
S 6 | S 5  
2006

Set a steel fence post north of stainless steel post as a witness post.

Cor. is located northeast of Flat Top Mountain, on a gentle, northeast-sloping ground.

From cor., an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, mkd. T41S R23E SLM 1/4 6/5 1991 LS 4346, witnessed by a fence post, bears N.  $88^{\circ}19'$  E., 0.468 ch. dist. Not of record, not utilized in this survey.

80.124 Point for the closing cor. of secs. 5 and 6, at intersection with the south bdy. of T. 40 S., R. 24 E., the Eighth Standard Parallel South, hereinbefore described.

---

Subdivision of Section 1,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 1 and 12.

N.  $0^{\circ}02.7'$  E., on the N-S centerline of sec 1.

39.941 Point for the center 1/4 sec. cor. of sec. 1, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with magnet at base, with brass cap mkd.:

SUBDIVISION OF SECTION 1  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T 41 S R 24 E  
C 1/4 S 1  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located in rolling, sandy hills, with scattered desert brush.

79.915 The 1/4 sec. cor. of sec. 1 only, at intersection with the south bdy. of T. 40 S., R. 24 E., the Eighth Standard Parallel South, hereinbefore described.

---

From the 1/4 sec. cor. of secs. 1 and 6, on the E. bdy. of township, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush in a mound of stones, 4 ft. diam. base, 18 ins. above ground, with brass cap (Navajo seal) mkd. correctly. The official record of the 2004 resurvey shows the cap was incorrectly marked.

Set a steel fence post south of the stainless steel post as a witness post.

S. 89°59.8' W., on the E-W centerline of sec 1.

39.886 The center 1/4 sec. cor. of sec. 1.

79.867 The 1/4 sec. cor. of secs. 1 and 2.

---

Subdivision of Section 2,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 2 and 11.

N. 0°05.2' E., on the N-S centerline of sec 2.

40.039 Point for the center 1/4 sec. cor. of sec. 2, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 2  
2006

Set a steel fence post southwest of stainless steel post as a witness post.

SUBDIVISION OF SECTION 2  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Cor. is located on a fairly level plain, with scattered desert brush.

80.078 The 1/4 sec. cor. of sec. 2 only, at intersection with the south bdy. of T. 40 S., R. 24 E., the Eighth Standard Parallel South, hereinbefore described.

---

From the 1/4 sec. cor. of secs. 1 and 2.

N. 89°59.4' W., on the E-W centerline of sec 2.

39.964 The center 1/4 sec. cor. of sec. 2.

64.964 The centerline of Utah State Highway 162, a paved road, 25 ft. wide, that bears N. 23° W. and S. 21° E.

79.928 The 1/4 sec. cor. of secs. 2 and 3.

---

Subdivision of Section 3,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 3 and 10.

N. 0°04.8' E., on the N-S centerline of sec 3.

40.049 Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 3  
2006

Set a steel fence post south of stainless steel post as a witness post.

Cor. is located on a gentle, north-sloping plain.

From cor., a power line, extending North and South, bears West, 0.636 ch. dist.

55.264 Left bank of the San Juan River, point for the meander cor. Not monumented.

59.982 Right bank of the San Juan River, point for the meander cor. Not monumented.

SUBDIVISION OF SECTION 3  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

80.098 The 1/4 sec. cor. of sec. 3 only, at intersection with the south bdy. of T. 40 S., R. 24 E., the Eighth Standard Parallel South, hereinbefore described.

---

From the 1/4 sec. cor. of secs. 2 and 3.

N. 89°59.5' W., on the E-W centerline of sec 3.

11.258 Right bank of the San Juan River, point for the meander cor. Not monumented.

14.928 Left bank of the San Juan River, point for the meander cor. Not monumented.

40.034 The center 1/4 sec. cor. of sec. 3.

80.068 The 1/4 sec. cor. of secs. 3 and 4.

---

Subdivision of Section 4,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 4 and 9.

N. 0°06.6' E., on the N-S centerline of sec 4.

40.059 Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, in a mound of stones, 3 ft. diam., 13 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 4  
2006

Set a steel fence post east of stainless steel post as a witness post.

Cor. is located in gently rolling hills, with sand overlying large river stones.

From cor., a galvanized iron pipe, 1 1/4 ins. diam., firmly set, projecting 6 ins. above the ground, bears S. 36°10' E., 0.099 ch. dist. Not of record, not utilized in this survey.

69.602 Left bank of the San Juan River, point for the meander cor. Not monumented.

SUBDIVISION OF SECTION 4  
T. 42 S., R. 17 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

- 72.449 Right bank of the San Juan River, point for the meander cor. Not monumented.
- 73.583 The centerline of Utah State Highway 162, a paved road, 25 ft. wide, that bears S. 89° W. and N. 89° E.
- 80.117 The 1/4 sec. cor. of sec. 4 only, at intersection with the south bdy. of T. 40 S., R. 24 E., the Eighth Standard Parallel South, hereinbefore described.

---

From the 1/4 sec. cor. of secs. 3 and 4.

N. 89°59.3' W., on the E-W centerline of sec 4.

- 39.937 The center 1/4 sec. cor. of sec. 4.

- 79.874 The 1/4 sec. cor. of secs. 4 and 5.

---

Subdivision of Section 5,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 5 and 8.

N. 0°04.6' E., on the N-S centerline of sec 5.

- 2.355 The centerline of San Juan County road 406, a paved road, 25 ft. wide, that bears N. 47° W. and S. 47° E.

- 40.064 Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 5  
2006

Set a steel fence post south of stainless steel post as a witness post.

Cor. is located on a steep, unconsolidated hill of sand and gravel, facing northeast, 70 ft. above the valley floor.

From cor., an aluminum post, 2 1/2 ins. diam., firmly set flush with the ground, mkd. T41S R23E SLM C1/4 SEC5 WC 50WEST 1991 LS4346, witnessed by a steel fence post, bears N. 85°37' W., 0.497 ch. dist. Not of record, not utilized in this survey.

SUBDIVISION OF SECTION 5  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

- 73.567 Left bank of the San Juan River, point for the meander cor.  
Not monumented.
- 76.861 Right bank of the San Juan River, point for the meander cor.  
Not monumented.
- 80.158 The 1/4 sec. cor. of sec. 5 only, at intersection with the south  
bdy. of T. 40 S., R. 24 E., the Eighth Standard Parallel South,  
hereinbefore described.
- 
- From the 1/4 sec. cor. of secs. 4 and 5.  
West, on the E-W centerline of sec 5.
- 40.079 The center 1/4 sec. cor. of sec. 5.
- 70.150 The curving centerline of San Juan County road 406, a paved  
road, 25 ft. wide, that bears N. 43° W. and S. 49° E.
- 80.158 The 1/4 sec. cor. of secs. 5 and 6.

Subdivision of Section 6,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

- 
- From the 1/4 sec. cor. of secs. 6 and 7.  
N. 0°02.8' W., on the N-S centerline of sec 6.
- 40.037 Point for the center 1/4 sec. cor. of sec. 6, at intersection  
with the E-W centerline.
- Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25  
ins. in the ground, in a collar of stones, 2 ft. diam., with  
magnet at base, with brass cap mkd.:
- T 41 S R 24 E  
C 1/4 S 6  
2006
- Set a steel fence post north of stainless steel post as a  
witness post.
- Cor. is located on a gently rolling, west-sloping hill.
- 80.071 The 1/4 sec. cor. of sec. 6 only, at intersection with the south  
bdy. of T. 40 S., R. 24 E., the Eighth Standard Parallel South,  
hereinbefore described.

---

From the 1/4 sec. cor. of secs. 5 and 6.

SUBDIVISION OF SECTION 6  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

S. 89°59.7' W., on the E-W centerline of sec 6.

40.000 The center 1/4 sec. cor. of sec. 6.

78.470 The 1/4 sec. cor. of sec. 6 only, on the W. bdy. of the township, hereinbefore described.

Subdivision of Section 7,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 7 and 18.

N. 0°02.8' W., on the N-S centerline of sec 7.

39.999 Point for the center 1/4 sec. cor. of sec. 7, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stones, 5 ft. diam., 18 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 7  
2006

Set a steel fence post southeast of stainless steel post as a witness post.

Cor. is located at the base of the west face of Flat Top Mountain, at the head of a drainage, course S. 30° W., in a boulder field.

80.002 The 1/4 sec. cor. of secs. 6 and 7.

From the 1/4 sec. cor. of secs. 7 and 8.

N. 89°58.4' W., on the E-W centerline of sec 7.

40.000 The center 1/4 sec. cor. of sec. 7.

78.548 The 1/4 sec. cor. of sec. 7 only, on the W. bdy. of the township, hereinbefore described.

Subdivision of Section 8,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

SUBDIVISION OF SECTION 8  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

- From the 1/4 sec. cor. of secs. 8 and 17.
- N. 0°2.2' W., on the N-S centerline of sec 8.
- 40.000 Point for the center 1/4 sec. cor. of sec. 8, at intersection with the E-W centerline.
- Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., on a bedrock outcrop, in a mound of stones, 4 ft. diam. base, 28 ins. above ground, with magnet at base, with brass cap mkd.:
- T 41 S R 24 E  
C 1/4 S 8  
2006
- Set a steel fence post west of stainless steel post as a witness post.
- Cor. is located in a drainage, course N. 10° W., in rocky soil, with little vegetation.
- 80.000 The 1/4 sec. cor. of secs. 5 and 8.
- 
- From the 1/4 sec. cor. of secs. 8 and 9.
- N. 89°59.9' W., on the E-W centerline of sec 8.
- 3.215 The centerline of San Juan County road 406, a paved road, 25 ft. wide, that bears N. 4° W. and S. 4° E.
- 40.000 The center 1/4 sec. cor. of sec. 8.
- 80.000 The 1/4 sec. cor. of secs. 7 and 8.

Subdivision of Section 9,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

- 
- From the 1/4 sec. cor. of secs. 9 and 16.
- N. 0°01.5' W., on the N-S centerline of sec 9.
- 0.358 The centerline of San Juan County road 4251, a gravel road, 24 ft. wide, that bears N. 43° E. and S. 43° W.
- 40.000 Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E-W centerline.
- Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. below ground, in an improved gravel road, with magnet at base, with brass cap mkd.:

SUBDIVISION OF SECTION 9  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T 41 S R 24 E  
C 1/4 S 9  
2006

from which

A stainless steel post, for a reference monument, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, with brass cap mkd. RM T41S R24E C 1/4 S9 23.5 FT. TO COR 2006, with an arrow pointing toward cor., bears S. 45°27' W., 0.356 ch. dist. Deposit a magnet at the base of stainless steel post. Set a steel fence post west of stainless steel post as a witness post.

A stainless steel post, for a reference monument, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, with brass cap mkd. RM T41S R24E C 1/4 S9 30.0 FT. TO COR 2006, with an arrow pointing toward cor., bears N. 53°45' W., 0.454 ch. dist. Deposit a magnet at the base of stainless steel post. Set a steel fence post north of stainless steel post as a witness post.

Cor. is located in a gravel road, 12 ft. wide, extending North and South.

- 40.724 The centerline of San Juan County road 457, a gravel road, 24 ft. wide, that bears N. 74° W. and S. 74° E.
- 80.000 The 1/4 sec. cor. of secs. 4 and 9.

---

From the 1/4 sec. cor. of secs. 9 and 10.

N. 89°59.9' W., on the E-W centerline of sec 9.

- 6.271 The centerline of San Juan County road 457, a gravel road, 24 ft. wide, that bears N. 46° E. and S. 46° W.
- 37.460 The centerline of San Juan County road 457, a gravel road, 24 ft. wide, that bears N. 74° W. and S. 74° E.
- 40.000 The center 1/4 sec. cor. of sec. 9.
- 80.000 The 1/4 sec. cor. of secs. 8 and 9.

---

Subdivision of Section 10,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 10 and 15.

N. 0°00.8' W., on the N-S centerline of sec 10.

SUBDIVISION OF SECTION 10  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

- 40.000 Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E-W centerline.
- Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at base, with brass cap mkd.:
- T 41 S R 24 E  
C 1/4 S 10  
2006
- Set a steel fence post north of stainless steel post as a witness post.
- Cor. is located in a broad drainage, course N. 5° W.
- From cor., a galvanized iron pipe, 1 3/4 ins. diam., firmly set, projecting 4 ins. above the ground, bears N. 82°29' E., 0.308 ch. dist. Not of record, not utilized in this survey.
- 63.844 The centerline of San Juan County road 457, a gravel road, 24 ft. wide, that bears N. 82° W. and S. 84° E.
- 80.000 The 1/4 sec. cor. of secs. 3 and 10.
- 
- From the 1/4 sec. cor. of secs. 10 and 11.
- N. 89°59.9' W., on the E-W centerline of sec 10.
- 40.000 The center 1/4 sec. cor. of sec. 10.
- 80.000 The 1/4 sec. cor. of secs. 9 and 10.

Subdivision of Section 11,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

- 
- From the 1/4 sec. cor. of secs. 11 and 14.
- N. 0°00.2' W., on the N-S centerline of sec 11.
- 23.221 The centerline of San Juan County road 457, a gravel road, 24 ft. wide, that bears N. 58° W. and S. 58° E.
- 40.000 Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E-W centerline.
- Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at base, with brass cap mkd.:

SUBDIVISION OF SECTION 11  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T 41 S R 24 E

C 1/4 S 11

2006

Set a steel fence post north of stainless steel post as a witness post.

Cor. is located on a fairly level floodplain of the San Juan River, in short tamarisk and sandy soil.

- 66.427 Left bank of the San Juan River, point for the meander cor. Not monumented.
- 68.695 Right bank of the San Juan River, point for the meander cor. Not monumented.
- 79.229 The centerline of Utah State Highway 162, a paved road, 25 ft. wide, that bears N. 57° W. and S. 60° E.
- 80.000 The 1/4 sec. cor. of secs. 2 and 11.

From the true point for the 1/4 sec. cor. of secs. 11 and 12.

N. 89°59.9' W., on the E-W centerline of sec 11.

- 1.809 Left bank of the San Juan River, point for the meander cor. Not monumented.
- 40.000 The center 1/4 sec. cor. of sec. 11.
- 70.679 The centerline of San Juan County road 457, a gravel road, 24 ft. wide, that bears N. 72° W. and S. 71° E.
- 80.000 The 1/4 sec. cor. of secs. 10 and 11.

Subdivision of Section 12,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 12 and 13.

N. 0°00.2' E., on the N-S centerline of sec 12.

- 17.347 Left bank of the San Juan River, point for the meander cor. Not monumented.
- 22.040 Right bank of the San Juan River, point for the meander cor. Not monumented.
- 40.006 Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E-W centerline.

SUBDIVISION OF SECTION 12  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 12  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on a fairly level floodplain of the San Juan River, in short tamarisk and sandy soil.

46.805 The centerline of Utah State Highway 162, a paved road, 25 ft. wide, that bears N. 85° W. and S. 85° E.

80.045 The 1/4 sec. cor. of secs. 1 and 12.

From the 1/4 sec. cor. of secs. 7 and 12, on the E. bdy. of the township, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above a collar of stones, 4 ft. diam. base, with brass cap (Navajo seal) mkd. as described in the official record of the 2004 resurvey.

Set a steel fence post north of the stainless steel post as a witness post.

S. 89°55.2' W., on the E-W centerline of sec 12.

13.497 The centerline of Utah State Highway 162, a paved road, 25 ft. wide, that bears N. 60° W. and S. 60° E.

39.974 The center 1/4 sec. cor. of sec. 12.

45.102 Right bank of the San Juan River, point for the meander cor. Not monumented.

60.306 Right bank of the San Juan River, point for the meander cor. Not monumented.

71.596 Right bank of the San Juan River, point for the meander cor. Not monumented.

79.960 The true point for the 1/4 sec. cor. of secs. 11 and 12.

Subdivision of Section 13,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

From the true point for the 1/4 sec. cor. of secs. 13 and 24.

SUBDIVISION OF SECTION 13  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

- N. 0°00.5' E., on the N-S centerline of sec 13.
- 38.093 The centerline of San Juan County road 457, a gravel road, 24 ft. wide, that bears N. 63° W. and S. 63° E.
- 40.011 Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E-W centerline.
- Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at base, with brass cap mkd.:
- T 41 S R 24 E  
C 1/4 S 13  
2006
- Set a steel fence post north of stainless steel post as a witness post.
- Cor. is located on a fairly level floodplain of the San Juan River, in short tamarisk and sandy soil, at the base of steep cliffs to the south.
- 80.019 The 1/4 sec. cor. of secs. 12 and 13.
- 
- From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the township, hereinbefore described.
- S. 89°56.4' W., on the E-W centerline of sec 13.
- 40.006 The center 1/4 sec. cor. of sec. 13.
- 44.366 The centerline of San Juan County road 457, a gravel road, 24 ft. wide, that bears N. 68° W. and S. 68° E.
- 79.995 The 1/4 sec. cor. of secs. 13 and 14.

Subdivision of Section 14,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

- 
- From the 1/4 sec. cor. of secs. 14 and 23.
- N. 0°00.2' W., on the N-S centerline of sec 14.
- 40.000 Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E-W centerline.

SUBDIVISION OF SECTION 14  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a collar of stones, 4 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 14  
2006

Set a steel fence post east of stainless steel post as a witness post.

Cor. is located on a gentle, north-sloping hill, in eroded terrain.

80.000 The 1/4 sec. cor. of secs. 11 and 14.

---

From the 1/4 sec. cor. of secs. 13 and 14.

N. 89°59.9' W., on the E-W centerline of sec 14.

40.000 The center 1/4 sec. cor. of sec. 14.

80.000 The 1/4 sec. cor. of secs. 14 and 15.

---

Subdivision of Section 15,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 15 and 22.

N. 0°00.8' W., on the N-S centerline of sec 15.

40.000 Point for the center 1/4 sec. cor. of sec. 15, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 15  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located in gently rolling sand dunes, in scattered grass.

80.000 The 1/4 sec. cor. of secs. 10 and 15.

---

SUBDIVISION OF SECTION 15  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

From the 1/4 sec. cor. of secs. 14 and 15.

N. 89°59.9' W., on the E-W centerline of sec 15.

40.000 The center 1/4 sec. cor. of sec. 15.

80.000 The 1/4 sec. cor. of secs. 15 and 16.

Subdivision of Section 16,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 16 and 21.

N. 0°01.5' W., on the N-S centerline of sec 16.

17.177 The centerline of San Juan County road 444, a gravel road, 25 ft. wide, that bears N. 66° W. and S. 61° E.

40.000 Point for the center 1/4 sec. cor. of sec. 16, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 16  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on the northwest shoulder of a gravel road.

From cor., the centerline of a gravel road, 20 ft. wide, extending N. 45° E./ S. 45° W., bears East, 0.470 ch. dist.

80.000 The 1/4 sec. cor. of secs. 9 and 16.

From the 1/4 sec. cor. of secs. 15 and 16.

N. 89°59.9' W., on the E-W centerline of sec 16.

40.000 The center 1/4 sec. cor. of sec. 16.

80.000 The 1/4 sec. cor. of secs. 16 and 17.

Subdivision of Section 17,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

SUBDIVISION OF SECTION 17  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

From the 1/4 sec. cor. of secs. 17 and 20.

N. 0°02.2' W., on the N-S centerline of sec 17.

40.000 Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, in a mound of stones, 4 ft. diam. base, 9 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 17  
2006

Set a steel fence post northeast of stainless steel post as a witness post.

Cor. is located in rolling hills, in scattered dessert grass.

From cor., a power line, extending North and South, bears West, 0.303 ch. dist.

80.000 The 1/4 sec. cor. of secs. 8 and 17.

From the 1/4 sec. cor. of secs. 16 and 17.

N. 89°59.9' W., on the E-W centerline of sec 17.

9.768 The centerline of San Juan County road 406, a paved road, 25 ft. wide, that bears N. 24° E. and S. 24° W.

40.000 The center 1/4 sec. cor. of sec. 17.

80.000 The 1/4 sec. cor. of secs. 17 and 18.

Subdivision of Section 18,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 18 and 19.

N. 0°02.8' W., on the N-S centerline of sec 18.

39.998 Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground to bedrock, in a mound of stones, 4 ft. diam.

SUBDIVISION OF SECTION 18  
T. 42 S., R. 17 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

base, 6 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 18  
2006

Set a steel fence post east of stainless steel post as a witness post.

Cor. is located in eroded badlands, south of Flat Top Mountain, northwest of an oil and gas production facility.

79.997 The 1/4 sec. cor. of secs. 7 and 18.

---

From the 1/4 sec. cor. of secs. 17 and 18.

N. 89°58.3' W., on the E-W centerline of sec 18.

40.000 The center 1/4 sec. cor. of sec. 18.

78.624 The 1/4 sec. cor. of sec. 18 only, on the W. bdy. of the township, hereinbefore described.

---

Subdivision of Section 19,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 19 and 30.

N. 0°02.8' W., on the N-S centerline of sec 19.

40.007 Point for the center 1/4 sec. cor. of sec. 19, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 19  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on a gentle, west-sloping hill, west of an oil and gas tank battery.

From cor., an iron pipe, 1 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with an aluminum tag mkd.

SUBDIVISION OF SECTION 19  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Center Sec 19 Phillips Pet Co, bears S. 79°13' W., 0.788 ch. dist. Not of record, not utilized in this survey.

80.013 The 1/4 sec. cor. of secs. 18 and 19.

---

From the 1/4 sec. cor. of secs. 19 and 20.

N. 89°58.6' W., on the E-W centerline of sec 19.

40.000 The center 1/4 sec. cor. of sec. 19.

78.699 The 1/4 sec. cor. of sec. 19 only, on the W. bdy. of the township, hereinbefore described.

---

Subdivision of Section 20,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 20 and 29.

N. 0°02.2' W., on the N-S centerline of sec 20.

40.000 Point for the center 1/4 sec. cor. of sec. 20, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 20  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on a fairly level plain, east of an oil and gas tank battery.

From cor., an iron pipe, 1 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, bears N. 57°30' W., 0.367 ch. dist. Not of record, not utilized in this survey.

52.512 The centerline of San Juan County road 406, a paved road, 25 ft. wide, that bears N. 28° E. and S. 32° W.

80.000 The 1/4 sec. cor. of secs. 17 and 20.

---

From the 1/4 sec. cor. of secs. 20 and 21.

N. 89°59.9' W., on the E-W centerline of sec 20.

SUBDIVISION OF SECTION 20  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

- 40.000 The center 1/4 sec. cor. of sec. 20.
- 47.818 The centerline of San Juan County road 406, a paved road, 25 ft. wide, that bears N. 29° E. and S. 29° W.
- 80.000 The 1/4 sec. cor. of secs. 19 and 20.

Subdivision of Section 21,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

- From the 1/4 sec. cor. of secs. 21 and 28.
- N. 0°01.5' W., on the N-S centerline of sec 21.
- 40.000 Point for the center 1/4 sec. cor. of sec. 21, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 11 ins. in the ground to bedrock, in a mound of stones, 4 ft. diam. base, 17 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 21  
2006

- Set a steel fence post south of stainless steel post as a witness post.
- Cor. is located in eroded, rocky, and barren ground, northwest of an oil production facility.
- 80.000 The 1/4 sec. cor. of secs. 16 and 21.

- From the 1/4 sec. cor. of secs. 21 and 22.
- N. 89°59.9' W., on the E-W centerline of sec 21.
- 33.781 The centerline of San Juan County road 444, a gravel road, 25 ft. wide, that bears N. 10° W. and S. 7° E.
- 40.000 The center 1/4 sec. cor. of sec. 21.
- 80.000 The 1/4 sec. cor. of secs. 20 and 21.

Subdivision of Section 22,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

SUBDIVISION OF SECTION 22  
T. 42 S., R. 17 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

From the 1/4 sec. cor. of secs. 22 and 27.

N. 0°00.8' W., on the N-S centerline of sec 22.

40.000 Point for the center 1/4 sec. cor. of sec. 22, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stones, 3 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 22  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located in an open drainage, course N. 40° E., west of a small knoll.

From cor., an aluminum post, 2 1/2 ins. diam., firmly set, projecting 14 ins. above the ground, mkd. T41S R24E SLM C1/4 SEC22 1992 LS4346, witnessed by a steel fence post, bears N. 60°56' E., 0.190 ch. dist. Not of record, not utilized in this survey.

80.000 The 1/4 sec. cor. of secs. 15 and 22.

---

From the 1/4 sec. cor. of secs. 22 and 23.

N. 89°59.9' W., on the E-W centerline of sec 22.

40.000 The center 1/4 sec. cor. of sec. 22.

80.000 The 1/4 sec. cor. of secs. 21 and 22.

---

Subdivision of Section 23,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 23 and 26.

N. 0°00.2' W., on the N-S centerline of sec 23.

40.000 Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a supporting mound of stones on a hillside, 4 ft. diam., with magnet at base, with brass cap mkd.:

SUBDIVISION OF SECTION 23  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T 41 S R 24 E  
C 1/4 S 23  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on a rocky, moderately steep, east-facing hillside.

80.000 The 1/4 sec. cor. of secs. 14 and 23.

---

From the 1/4 sec. cor. of secs. 23 and 24.

N. 89°59.9' W., on the E-W centerline of sec 23.

40.000 The center 1/4 sec. cor. of sec. 23.

80.000 The 1/4 sec. cor. of secs. 22 and 23.

---

Subdivision of Section 24,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 24 and 25.

N. 0°00.2' E., on the N-S centerline of sec 24.

40.006 Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a supporting mound of stones on a hillside, 3 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 24  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on a rocky, moderately steep, northwest-facing hillside.

80.012 The true point for the 1/4 sec. cor. of secs. 13 and 24.

---

From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the township, hereinbefore described.

SUBDIVISION OF SECTION 24  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

S. 89°57.8' W., on the E-W centerline of sec 24.

- 40.001 The center 1/4 sec. cor. of sec. 24.  
79.994 The 1/4 sec. cor. of secs. 23 and 24.

Subdivision of Section 25,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 25 and 36.

N. 0°00.3' E., on the N-S centerline of sec 25.

- 40.014 Point for the center 1/4 sec. cor. of sec. 25, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 25  
2006

Set a steel fence post north of stainless steel post as a witness post.

Cor. is located on a gently rolling sand dune, east of White Mesa.

- 80.021 The 1/4 sec. cor. of secs. 24 and 25.

From the true point for the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the township. From this point, the witness cor. to the 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 2 1/2 ins. diam., buried 24 ins. below ground, with brass cap (BLM seal) mkd. as described in the official record of the 2004 resurvey, bears North, 6.004 chs. dist.

Set a steel fence post north of the iron post as a witness post.

S. 89°59.0' W., on the E-W centerline of sec 25.

- 39.992 The center 1/4 sec. cor. of sec. 25.  
79.990 The 1/4 sec. cor. of secs. 25 and 26.

SUBDIVISION OF SECTION 25  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

---

Subdivision of Section 26,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 26 and 35.

N. 0°00.2' W., on the N-S centerline of sec 26.

40.000 Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in the ground to bedrock, in a mound of stones, 4 ft. diam. base, 26 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 26  
2006

Set a steel fence post northeast of stainless steel post as a witness post.

Cor. is located on a steep, northeast-facing hillside, on the west side of White Mesa, approximately 200 ft. above the valley floor below.

80.000 The 1/4 sec. cor. of secs. 23 and 26.

---

From the 1/4 sec. cor. of secs. 25 and 26.

N. 89°59.9' W., on the E-W centerline of sec. 26.

40.000 The center 1/4 sec. cor. of sec. 26.

80.000 The 1/4 sec. cor. of secs. 26 and 27.

---

Subdivision of Section 27,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 27 and 34.

N. 0°00.8' W., on the N-S centerline of sec 27.

40.000 Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, in a mound of stones, 5 ft. diam.

SUBDIVISION OF SECTION 27  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

base, 20 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 27  
2006

Set a steel fence post south of stainless steel post as a witness post.

Cor. is located in eroded badlands.

From cor., the centerline of a gravel road, 15 ft. wide, extending N. 38° E. / S. 43° W., bears West, 1.955 chs. dist.

80.000 The 1/4 sec. cor. of secs. 22 and 27.

---

From the 1/4 sec. cor. of secs. 26 and 27.

N. 89°59.9' W., on the E-W centerline of sec 27.

40.000 The center 1/4 sec. cor. of sec. 27.

80.000 The 1/4 sec. cor. of secs. 27 and 28.

---

Subdivision of Section 28,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 28 and 33.

N. 0°01.5' W., on the N-S centerline of sec 28.

40.000 Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stones, 3 ft. diam. base, 18 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 28  
2006

Cor. is located on a gentle, southeast-sloping hillside.

From cor., an aluminum post, 2 1/2 ins. diam., firmly set, projecting 16 ins. above the ground, mkd. T41S R24E SLM C1/4 S28 1992 LS4346, witnessed by a steel fence post, bears N. 71°04' W., 0.133 ch. dist. Not of record, not utilized in this survey.

SUBDIVISION OF SECTION 28  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

- 80.000 The 1/4 sec. cor. of secs. 21 and 28.
- 
- From the 1/4 sec. cor. of secs. 27 and 28.
- N. 89°59.9' W., on the E-W centerline of sec 28.
- 27.010 The centerline of San Juan County road 444, a curving gravel road, 25 ft. wide, that bears N. 12° E. and S. 2° E.
- 40.000 The center 1/4 sec. cor. of sec. 28.
- 80.000 The 1/4 sec. cor. of secs. 28 and 29.

Subdivision of Section 29,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

- 
- From the 1/4 sec. cor. of secs. 29 and 32.
- N. 0°02.2' W., on the N-S centerline of sec 29.
- 40.000 True point for center 1/4 sec. cor. of sec. 29, at intersection with the E-W centerline. It is impracticable to establish a permanent monument here. Point falls on the steep, unstable southeast slope of White Mesa Mountain.
- 80.000 The 1/4 sec. cor. of secs. 20 and 29.
- 
- From the 1/4 sec. cor. of secs. 28 and 29.
- N. 89°59.9' W., on the E-W centerline of sec 29.
- 34.000 Point selected for the witness center 1/4 sec. cor. of sec. 29.
- Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a supporting mound of stones on a hillside, with magnet at base, with brass cap mkd.:

WC



T 41 S R 24 E  
C 1/4 S 29  
2006

Set a steel fence post northeast of stainless steel post as a witness post.

SUBDIVISION OF SECTION 29  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Witness cor. is located on an unconsolidated, south-facing, moderately steep slope.

40.000 True point for center 1/4 sec. cor. of sec. 29.

80.000 The 1/4 sec. cor. of secs. 29 and 30.

Subdivision of Section 30,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 30 and 31.

N. 0°02.8' W., on the N-S centerline of sec 30.

39.999 Point for the center 1/4 sec. cor. of sec. 30, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a collar of stones, 2 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 30  
2006

Set a steel fence post east of stainless steel post as a witness post.

Cor. is located on the east side of a shallow drainage, course N. 40° W.

From cor., an aluminum post, 2 1/2 ins. diam., firmly set, projecting 13 ins. above the ground, mkd. T41S R24E SLM SEC30 C1/4 1991 LS4346, bears N. 87°34' W., 0.144 ch. dist. Not of record, not utilized in this survey.

52.357 The centerline of San Juan County road 406, a paved road, 25 ft. wide, that bears N. 52° E. and S. 47° W.

80.007 The 1/4 sec. cor. of secs. 19 and 30.

From the 1/4 sec. cor. of secs. 29 and 30.

N. 89°59.9' W., on the E-W centerline of sec 30.

40.000 The center 1/4 sec. cor. of sec. 30.

48.566 The centerline of San Juan County road 406, a paved road, 25 ft. wide, that bears N. 23° E. and S. 19° W.

SUBDIVISION OF SECTION 30  
T. 42 S., R. 17 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

- 51.411 The centerline of San Juan County road 410, a gravel road, 30 ft. wide, that bears N. 16° E. and South.
- 78.774 The 1/4 sec. cor. of sec. 30 only, on the W. bdy. of the township, hereinbefore described.

Subdivision of Section 31,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 6 and 31, on the S. bdy. of the township, hereinbefore described.

N. 0°03.0' W., on the N-S centerline of sec 31.

- 30.538 Point for the center 1/4 sec. cor. of sec. 31, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 31  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on a gentle northwest-sloping sand dune.

- 70.535 The 1/4 sec. cor. of secs. 30 and 31.

From the 1/4 sec. cor. of secs. 31 and 32.

N. 89°59.6' W., on the E-W centerline of sec 31.

- 39.986 The center 1/4 sec. cor. of sec. 31.
- 49.988 The centerline of San Juan County road 406, a paved road, 25 ft. wide, that bears N. 14° E. and S. 17° W.
- 78.836 The 1/4 sec. cor. of sec. 31 only, on the W. bdy. of the township, hereinbefore described.

Subdivision of Section 32,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

SUBDIVISION OF SECTION 32  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

From the 1/4 sec. cor. of secs. 5 and 32, on the S. bdy. of the township, hereinbefore described.

N. 0°03.4' W., on the N-S centerline of sec 32.

30.519 Point for the center 1/4 sec. cor. of sec. 32, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stones, 4 ft. diam., with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 32  
2006

Set a steel fence post south of stainless steel post as a witness post.

Cor. is located in a shallow drainage, course N. 30° E.

70.519 The 1/4 sec. cor. of secs. 29 and 32.

From the 1/4 sec. cor. of secs. 32 and 33.

N. 89°59.9' W., on the E-W centerline of sec 32.

39.988 The center 1/4 sec. cor. of sec. 32.

80.015 The 1/4 sec. cor. of secs. 31 and 32.

Subdivision of Section 33,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 4 and 33, on the S. bdy. of the township, hereinbefore described.

N. 0°02.5' W., on the N-S centerline of sec 33.

30.508 Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a collar of stones, 3 ft. diam., with magnet at base, with brass cap mkd.:

SUBDIVISION OF SECTION 33  
T. 42 S., R. 17 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T 41 S R 24 E  
C 1/4 S 33  
2006

Set a steel fence post west of stainless steel post as a witness post.

Cor. is located on a gentle, north-sloping bench, above a small housing subdivision to the northeast.

70.508 The 1/4 sec. cor. of secs. 28 and 33.

---

From the 1/4 sec. cor. of secs. 33 and 34.

N. 89°59.9' W., on the E-W centerline of sec 33.

23.073 The centerline of San Juan County road 444, a curving gravel road, 25 ft. wide, that bears North and S. 26° E.

39.963 The center 1/4 sec. cor. of sec. 33.

79.973 The 1/4 sec. cor. of secs. 32 and 33.

---

Subdivision of Section 34,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of township, hereinbefore described.

N. 0°01.0' E., on the N-S centerline of sec 34.

30.490 Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., on a bedrock outcropping, in a mound of stones, 4 ft. diam. base, 28 ins. above ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 34  
2006

Set a steel fence post east of stainless steel post as a witness post.

Cor. is located at the top of a drainage, course S. 80° W., 10 ft. below the mesa top, on rocky ground.

70.490 The 1/4 sec. cor. of secs. 27 and 34.

SUBDIVISION OF SECTION 34  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

---

From the 1/4 sec. cor. of secs. 34 and 35.

N. 89°59.9' W., on the E-W centerline of sec 34.

40.008 The center 1/4 sec. cor. of sec. 34.

80.012 The 1/4 sec. cor. of secs. 33 and 34.

---

Subdivision of Section 35,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of township, hereinbefore described.

N. 0°00.8' E., on the N-S centerline of sec 35.

30.474 Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a supporting mound of stones on a hillside, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 35  
2006

Set a steel fence post southeast of stainless steel post as a witness post.

Cor. is located on a moderate, northeast-facing slope, rocky with sandstone outcrops.

70.474 The 1/4 sec. cor. of secs. 26 and 35.

---

From the 1/4 sec. cor. of secs. 35 and 36.

N. 89°59.9' W., on the E-W centerline of sec 35.

39.997 The center 1/4 sec. cor. of sec. 35.

79.999 The 1/4 sec. cor. of secs. 34 and 35.

---

Subdivision of Section 36,  
T. 41 S., R. 24 E., Salt Lake Meridian, Utah

---

SUBDIVISION OF SECTION 36  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

From the 1/4 sec. cor. of secs. 1 and 36, on the S. bdy. of township, hereinbefore described.

N. 0°00.8' E., on the N-S centerline of sec 36.

30.462 Point for the center 1/4 sec. cor. of sec. 36, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with magnet at base, with brass cap mkd.:

T 41 S R 24 E  
C 1/4 S 36  
2006

Set a steel fence post north of stainless steel post as a witness post.

Cor. is located on a gently rolling sand dune, in scattered desert brush.

70.464 The 1/4 sec. cor. of secs. 25 and 36.

---

From the true point for the 1/4 sec. cor. of secs. 31 and 36, on the E. bdy. of the township, hereinbefore described.

N. 89°59.7' W., on the E-W centerline of sec 36.

40.020 The center 1/4 sec. cor. of sec. 36.

80.031 The 1/4 sec. cor. of secs. 35 and 36.

---

SURVEY OF THE MEANDERS OF THE RIGHT BANK OF THE SAN JUAN RIVER,  
THROUGH T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

---

From the point for the meander cor. of secs. 5 and 32, on the N. bdy. of the township, on the right bank of the San Juan River, hereinbefore described. Not monumented.

Thence, with the meanders of the present right bank of the San Juan River through sec. 5.

S. 16°16.1' E., 1.021 chs.

S. 51°39.0' E., 6.562 chs.

N. 84°06.2' E., 6.570 chs.

SURVEY OF THE MEANDERS OF THE RIGHT BANK OF THE SAN JUAN RIVER,  
THROUGH T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

N. 88°11.3' E., 5.614 chs.  
 N. 71°09.9' E., 2.844 chs. The point for the meander cor. of  
 the N-S center line of sec. 5. Not  
 monumented.  
 S. 89°05.2' E., 4.319 chs.  
 N. 78°52.9' E., 2.6000 chs.  
 S. 79°05.4' E., 4.816 chs.  
 N. 81°06.0' E., 5.882 chs.  
 S. 78°41.4' E., 4.939 chs.  
 N. 82°25.3' E., 4.311 chs.  
 S. 88°07.5' E., 13.631 chs. The point for the meander cor. of  
 secs. 4 and 5. Not monumented.

---

Thence in sec. 4

S. 82°14.8' E., 4.176 chs.  
 S 72°42.8' E., 12.364 chs.  
 N. 88°31.2' E., 8.154 chs.  
 S. 79°53.5' E., 5.881 chs.  
 N. 73°56.3' E., 4.108 chs.  
 S. 89°15.7' E., 6.040 chs. The point for the meander cor. of the  
 N-S center line of sec. 4. Not  
 monumented.  
 S. 89°15.6' E., 5.998 chs.  
 N. 85°42.4' E., 3.933 chs.  
 S. 83°32.7' E., 3.462 chs.  
 N. 86°05.0' E., 7.841 chs.  
 S. 86°27.9' E., 3.313 chs.  
 N. 77°00.6' E., 3.033 chs.  
 S. 79°8.4' E., 1.740 chs.

SURVEY OF THE MEANDERS OF THE RIGHT BANK OF THE SAN JUAN RIVER,  
THROUGH T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 63°35.3' E., 3.896 chs.

S. 51°24.8' E., 4.148 chs.

S. 65°56.5' E., 4.379 chs. The point for the meander cor. of  
secs. 3 and 4. Not monumented.

---

Thence in sec. 3

S. 65°56.5' E., 0.756 ch.

S. 75°34.1' E., 2.873 chs.

S. 59°49.0' E., 4.180 chs.

S. 80°41.3' E., 4.454 chs.

S. 54°37.5' E., 1.778 chs.

S. 84°54.1' E., 8.791 chs.

S. 88°05.0' E., 5.194 chs.

S. 85°27.2' E., 13.210 chs. The point for the meander cor. of  
the N-S center line of sec. 3. Not  
monumented.

S. 85°27.1' E., 4.413 chs.

S. 59°07.6' E., 12.065 chs.

S. 48°41.6' E., 3.073 chs.

S. 45°47.2' E., 16.302 chs. The point for the meander cor. of  
the E-W center line of sec. 3. Not  
monumented.

S. 45°47.2' E., 0.918 chs.

S. 60°23.1' E., 6.274 chs.

S. 36°42.0' E., 3.443 chs.

S. 44°12.2' E., 4.396 chs. The point for the meander cor. of  
secs. 2 and 3. Not monumented.

---

Thence in sec. 2

S. 44°12.2' E., 2.365 chs.

S. 56°37.9' E., 17.104 chs.

SURVEY OF THE MEANDERS OF THE RIGHT BANK OF THE SAN JUAN RIVER,  
THROUGH T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 24°24.2' E., 20.549 chs.

S. 38°38.5' E., 0.741 chs. The point for the meander cor. of  
secs. 2 and 11. Not monumented.

---

Thence in sec. 11

S. 38°38.5' E., 10.596 chs.

S. 70°13.2' E., 8.955 chs. The point for the meander cor. of  
the N-S center line of sec. 11. Not  
monumented.

S. 70°13.1' E., 10.159 chs.

S. 49°27.9' E., 10.361 chs.

S. 52°44.9' E., 16.275 chs.

S. 28°02.8' E., 2.467 chs.

S. 56°17.2' E., 5.408 chs.

S. 76°10.6' E., 3.316 chs.

S. 65°25.6' E., 0.807 chs. The point for the meander cor. of  
secs. 11 and 12. Not monumented.

---

Thence in sec. 12

S. 65°25.6' E., 4.607 chs.

S. 84°00.1' E., 4.197 chs. The point for the meander cor. of  
the E-W center line of sec. 12. Not  
monumented.

S. 84°00.0' E., 8.944 chs.

N. 68°20.8' E., 2.577 chs. The point for the meander cor. of  
the E-W center line of sec. 12. Not  
monumented.

N. 68°20.8' E., 3.223 chs.

S. 81°49.7' E., 8.066 chs.

N. 87°45.0' E., 4.153 chs.

S. 21°53.4' E., 0.199 ch. The point for the meander cor. of

SURVEY OF THE MEANDERS OF THE RIGHT BANK OF THE SAN JUAN RIVER,  
THROUGH T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

the E-W center line of sec.12. Not  
monumented.

S. 21°53.4' E., 5.907 chs.

S. 8°40.8' E., 8.242 chs.

S. 21°13.0' E., 4.646 chs. The point for the meander cor. of  
the N-S center line of sec. 12.  
Not monumented.

S. 21°13.0' E., 1.547 chs.

S. 37°46.9' E., 5.303 chs.

S. 31°30.7' E., 14.937 chs.

S. 15°46.4' E., 1.551 chs.

S. 45°7.01' E., 3.062 chs. The point for the meander cor. of  
secs. 12 and 13. Not monumented.

Thence in sec. 13

S. 55°58.8' E., 3.814 chs.

S. 73°59.7' E., 6.802 chs.

S. 69°22.1' E., 4.317 chs.

N. 69°56.1' E., 1.856 chs.

N. 88°31.7' E., 4.359 chs.

S. 67°10.0' E., 2.892 chs.

N. 83°20.6' E., 1.544 chs.

N. 65°31.0' E., 1.915 chs. The point for the meander cor. of  
secs. 13 and 18, on the E. bdy of the  
township, on the right bank of the  
San Juan River, hereinbefore  
described. Not monumented.

SURVEY OF THE MEANDERS OF THE LEFT BANK OF THE SAN JUAN RIVER,  
THROUGH T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

From the point for the meander cor. of secs. 13 and 18, on the  
E. bdy. of the township, on the left bank of the San Juan River,  
hereinbefore described. Not monumented.

SURVEY OF THE MEANDERS OF THE LEFT BANK OF THE SAN JUAN RIVER,  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Thence, with the meanders of the present left bank of the San Juan River through sec. 13.

S. 65°04.2' W., 3.388 chs.

N. 86°50.4' W., 3.531 chs.

N. 62°03.8' W., 10.272 chs.

N. 51°11.1' W., 2.480 chs.

N. 79°26.2' W., 3.442 chs.

N. 71°37.7' W., 5.461 chs.

N. 37°49.3' W., 3.566 chs. The point for the meander cor. of  
secs. 12 and 13. Not monumented.

---

Thence in sec. 12

N. 37°49.3' W., 8.965 chs.

N. 21°37.2' W., 7.170 chs.

N. 44°15.9' W., 5.006 chs. The point for the meander cor. of  
the N-S center line of sec. 12.  
Not monumented.

N. 44°15.9' W., 9.753 chs.

N. 60°00.1' W., 7.753 chs.

N. 39°13.6' W., 5.993 chs.

N. 47°42.0' W., 5.830 chs.

N. 85°04.6' W., 13.649 chs.

N. 73°02.4' W., 4.979 chs. The point for the meander cor. of  
secs. 11 and 12. Not monumented.

---

Thence in sec. 11

N. 73°02.4' W., 1.892 chs. The point for the meander cor. of  
the E-W center line of sec. 11.  
Not monumented.

N. 73°02.4' W., 4.436 chs.

N. 49°41.8' W., 35.071 chs.

SURVEY OF THE MEANDERS OF THE LEFT BANK OF THE SAN JUAN RIVER,  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

N. 71°12.9' W., 7.608 chs. The point for the meander cor. of  
the N-S center line of sec. 11.  
Not monumented.

N. 71°13.0' W., 14.329 chs.

N. 84°48.9' W., 6.468 chs.

N. 58°54.3' W., 5.280 chs.

N. 20°39.2' W., 6.037 chs. The point for the meander cor. of  
secs. 2 and 11. Not monumented.

---

Thence in sec. 2

N. 20°39.2' W., 0.977 ch.

N. 6°06.9' W., 4.047 chs.

N. 51°14.5' W., 6.432 chs.

N. 13°00.7' W., 9.636 chs.

N. 28°00.1' W., 7.645 chs.

N. 45°06.4' W., 2.444 chs. The point for the meander cor. of  
secs. 2 and 3. Not monumented.

---

Thence in sec. 3

N. 45°06.4' W., 12.868 chs.

N. 56°38.9' W., 5.635 chs.

N. 45°58.2' W., 1.495 chs. The point for the meander cor. of  
the E-W center line of sec. 3.  
Not monumented.

N. 45°58.3' W., 16.549 chs.

N. 78°17.4' W., 9.173 chs.

N. 66°11.6' W., 4.594 chs. The point for the meander cor. of  
the N-S center line of sec. 3.  
Not monumented.

N. 66°11.6' W., 4.004 chs.

N. 89°53.1' W., 19.801 chs.

SURVEY OF THE MEANDERS OF THE LEFT BANK OF THE SAN JUAN RIVER,  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

N. 67°48.1' W., 10.169 chs.

N. 62°03.4' W., 8.109 chs. The point for the meander cor. of  
secs. 3 and 4. Not monumented.

---

Thence in sec. 4

N. 62°03.4' W., 13.515 chs.

S. 88°05.6' W., 4.931 chs.

S. 85°51.1' W., 6.355 chs.

S. 81°51.6' W., 9.295 chs.

N. 83°22.4' W., 6.201 chs.

S. 87°11.3' W., 1.323 chs. The point for the meander cor. of  
the N-S center line of sec. 4. Not  
monumented.

S. 87°11.3' W., 6.648 chs.

S. 70°53.0' W., 3.333 chs.

S. 82°21.8' W., 8.483 chs.

N. 89°59.2' W., 18.279 chs.

N. 44°27.9' W., 4.870 chs. The point for the meander cor. of  
secs. 4 and 5. Not monumented.

---

Thence in sec. 5

N. 44°27.9' W., 6.059 chs.

S. 88°32.0' W., 6.434 chs.

S. 78°42.5' W., 4.739 chs.

S. 87°55.5' W., 7.106 chs.

N. 84°58.9' W., 6.220 chs.

S. 86°06.9' W., 9.843 chs.

N. 89°13.2' W., 1.693 chs. The point for the meander cor. of  
the N-S center line of sec. 5. Not  
monumented.

N. 89°13.2' W., 3.700 chs.

SURVEY OF THE MEANDERS OF THE LEFT BANK OF THE SAN JUAN RIVER,  
T. 41 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- S. 81°47.5' W., 5.958 chs.
- N. 84°44.6' W., 4.805 chs.
- N. 57°48.0' W., 6.752 chs.
- N. 26°53.1' W., 3.918 chs. The point for the meander cor. of  
secs. 5 and 32, on the N. bdy. of  
township, hereinbefore described. Not  
monumented.

---

GENERAL DESCRIPTION

---

Township 41 South, Range 24 East is located entirely within the Navajo Reservation, in southeastern Utah. The nearest town is Montezuma Creek, which is located immediately northwest of the north boundary. A large part of the Aneth oil field, discovered in 1956, is located within this township, as are several small communities, including White Rock Village. The average elevation of the township is 5000 feet above sea level.

The San Juan River flows through the northeast area of the township, where there is a large floodplain and considerable tamarisk growth. The northeast end of White Mesa, trending southwest/northeast, terminates within the township, and Flat Top Mountain and White Mesa Mountain are two other prominent projections. The terrain has great variety, from the riparian area surrounding the river to high, rocky mesa tops, with open desert in between. The soil ranges from soft and sandy to solid sandstone outcrops.

Utah State Highway 162 crosses the northeast tip; the paved county road 406 runs north and south through the western half of the township, and numerous gravel and dirt roads lie within the interior. Isolated Navajo housing is scattered throughout the project, and there are no individual Navajo allotments.

---



## CERTIFICATE OF SURVEY

I, **Scott A. Burkhardt, Cadastral Surveyor**, hereby certify upon honor that, in pursuance of special instructions bearing the date of the **12th day of April, 2006**, I have executed the **dependent resurvey of the South boundary (Eighth Standard Parallel South), of Township 40 South, Range 24 East, the dependent resurvey of the South and West boundaries, a portion of the East boundary, the corrective resurvey of a portion of the East boundary, the dependent resurvey of a portion of the subdivisional lines, the survey of a portion of the subdivisional lines, the subdivision of all sections, and the survey of the meanders of the right and left banks of the San Juan River in Township 41 South, Range 24 East, of the Salt Lake Meridian, in the state of Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

9/23/07

Date

Scott A. Burkhardt

(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the of the **dependent resurvey of the South boundary (Eighth Standard Parallel South), of Township 40 South, Range 24 East, the dependent resurvey of the South and West boundaries, a portion of the East boundary, the corrective resurvey of a portion of the East boundary, the dependent resurvey of a portion of the subdivisional lines, the survey of a portion of the subdivisional lines, the subdivision of all sections, and the survey of the meanders of the right and left banks of the San Juan River in Township 41 South, Range 24 East, of the Salt Lake Meridian, in the state of Utah**, executed by Scott A. Burkhardt, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

September 28, 2007

Date

Daniel W. Wall

(Chief Cadastral Surveyor for Utah)