

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 15, 22, AND 23

IN

**TOWNSHIP 14 NORTH, RANGE 15 WEST**

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

**Ronald K. Baugh**  
**Supervisory Cadastral Surveyor**

Under Special Instructions dated **June 9, 2006**, approved **June 9, 2006**, which provided for the surveys included under Group Number **1020**, and assignment instructions dated **June 9, 2006**.

Survey commenced **June 20, 2006**  
Survey completed **July 12, 2006**

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 15, 22, AND 23

IN

**TOWNSHIP 14 NORTH, RANGE 15 WEST**

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

**Ronald K. Baugh**  
**Supervisory Cadastral Surveyor**

Under Special Instructions dated **June 9, 2006**, approved **June 9, 2006**, which provided for the surveys included under Group Number **1020**, and assignment instructions dated **June 9, 2006**.

Survey commenced **June 20, 2006**  
Survey completed **July 12, 2006**

# INDEX DIAGRAM

Township 14 North, Range 15 West

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	8 15	14	13
19	20	21	6 22	2 23	24
30	29	28	5 27	26	25
31	32	33	34	35	36

The Subdivision of Section 15.....Page 9  
The Subdivision of Section 22.....Page 11  
The Subdivision of Section 23.....Page 13



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 14 NORTH, RANGE 15 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

Cadastral Control Network was derived from GPS static observations, post processed by the National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS): HNSLYALLY, HILL72, and CNRSFRNGS.

The geographic position of the corner of sections 23 and 26 only, Township 14 North, Range 15 West, as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: 41°54'57.355" N.                      Longitude: 113°32'32.810" W.  
N.A.D. 1983, Network Accuracy = 0.200 meter at 95% confidence.  
N.A.V.D. 1988 Elevation: 7386.54 ft.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
Township 14 North, Range 15 West, Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
N.P. Anderson in 1902

---

From the corner of sections 23 and 26, on the east boundary of section 27, monumented with a shale stone, 15x7x6 inches, firmly set, clearly marked 2 notches on south and east edges, and witnessed with a mound of stone to the west.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

	T14N
	S23
S27	———
	S26
	R15W
	2006

Deposit marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls on a northwest slope, 1 ft. west of the corner of fences bearing east and north.

N. 0°22.8' E., along the west boundary of section 23.

**4.046** The closing corner of sections 22 and 27, monumented with a limestone, 15x11x8 inches, firmly set, clearly marked 2 notches

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 14 NORTH, RANGE 15 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

on the south and east edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground to bedrock, with aluminum cap marked:

```

      T14N
      S22 |
CC ——— | S23
      S27 |
          |
          R15W
          2006
  
```

Deposit marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls on a northwest slope, 1 ft. east of the corner of fences bearing west and south.

- 39.542** The 1/4 section corner of section 23 only, monumented with a quartz stone, 14x9x7 inches, firmly set, clearly marked 1/4 on west face, witnessed with a mound of stone to the west.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, in a mound of stone 3 ft. base to top of aluminum cap marked:

```

      T14NR15W
          | 1/4
          | S 23
          |
          2006
  
```

Deposit marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls on a northeast slope.

---

N. 0°15.4' E., beginning new measurement.

- 4.930** Point for the 1/4 section corner of section 22 only, at midpoint between the corner of sections 14, 15, 22, and 23, and the closing corner of sections 22 and 27.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, in a mound of stone 3 ft. base to top of

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 14 NORTH, RANGE 15 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

aluminum cap marked:

T14NR15W  
1/4 |  
S22 |  
2006

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls on a northeast slope.

**45.356** The corner of sections 14, 15, 22, and 23, monumented with a quartzite stone 18x13x5 inches, firmly set, clearly marked 2 notches on east and 3 notches on south edges, and witnessed with a mound of stone to the west.

from which

A root hole, bears N 32° E., 71 links distance, alongside of which is lying a piñon 15 ins. diam., with visible scribe marks on an open blaze. (Record: N. 27 1/2° E., 70 links)

A root hole, bears S 76° W., 11 links distance, alongside of which is lying a piñon 6 ins. diam., with visible scribe marks on an open blaze. (Record: S. 79 1/2° W., 12 links)

A root hole, bears N 47° W., 57 links distance, alongside of which is lying a piñon 12 ins. diam., with visible scribe marks on an open blaze. (Record: N. 45 1/4° W., 58 links)

No remaining evidence of the southeast bearing tree was found.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to solid rock, in a mound of stone 6 ft. base to top of aluminum cap marked:

T14NR15W  
S15 | S14  
S22 | S23  
2006

Deposit marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls on a northeast slope.

From the 1/4 section corner of sections 14 and 23, monumented

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 14 NORTH, RANGE 15 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

with a quartz stone, 24x13x5 inches, firmly set, clearly marked 1/4 on north face, and witnessed with an embedded mound of stone to the north.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14NR15W  
S14  
1/4—  
S23  
2006

Deposit marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Raise a mound of stone to the north of the aluminum post.

Corner falls at the intersection of fence lines projecting north, south, east and west.

N. 89°33.7' W., between sections 14 and 23

**39.756** The corner of sections 14, 15, 22, and 23.

---

From the corner of sections 21, 22, 27, and 28, monumented with an iron post, 2 1/2 inches diameter, firmly set in a mound of stone 3 ft. base to top of brass cap marked as described in the official record of the 1965 remonumentation.

Corner falls 3 ft. west of intersection of fence lines projecting east, west and north.

N. 89°53.2' E., between sections 22 and 27.

**40.170** Point for the 1/4 section corner of sections 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a mound of stone 3 ft. base to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 14 NORTH, RANGE 15 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

T14NR15W  
S22  
1/4—  
S27  
2006

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls on a south slope in dense juniper growth, and 15.5 ft. south of an east-west fence line.

**60.255** Point for the E 1/16 section corner of sections 22 and 27.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a mound of stone 3 ft. base to top of aluminum cap marked:

T14NR15W  
S22  
E 1/16—  
S27  
2006

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls on a southeast slope in piñon and juniper growth, and 1.5 ft. south of an east-west fence line, and 40 ft. west of a drainage, draining southwest.

**80.340** The closing corner of sections 22 and 27, hereinbefore described.

From the corner of sections 21, 22, 27, and 28.

N. 0°08.6' W., between sections 21 and 22.

**40.138** The 1/4 section corner of sections 21 and 22, monumented with a quartzite stone, 17x10x5 inches, firmly set in a mound of stone 3 ft. base, clearly marked 1/4 on west face.

from which

A piñon stump, 2 ft. high, 18 ins, diam., bears N. 46° W., 70 links distance, with visible scribe marks on an open blaze.  
(Record: N. 44°10' W., 71 links)

No remaining evidence of the southeast bearing tree was found.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 14 NORTH, RANGE 15 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

inches in the ground, in a mound of stone 3 ft. base to top of aluminum cap marked:

T14NR15W  
1/4  
S21|S22  
2006

Deposit marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls 3 ft. east of a north-south fence line.

---

N. 0°01.1' E., beginning new measurement.

**20.214** Point for the N 1/16 section corner of sections 21 and 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14NR15W  
N 1/16  
S21|S22  
2006

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls 3 ft. west of a north-south fence line.

**40.428** The corner of sections 15, 16, 21, and 22, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1965 remonumentation.

Corner falls in the intersection of fence lines projecting north, south, and west.

---

From the 1/4 section corner of sections 15 and 22, monumented with a limestone, 24x12x9 inches, firmly set in a mound of stone 3 ft. base, clearly marked 1/4 on west face.

from which

A cedar, 20 ins. diam., bears N 16° E., 36 links distance, with visible scribe marks on an open blaze. (Record: N. 15 1/2° E.)

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 14 NORTH, RANGE 15 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

A piñon, 20 ins. diam., bears S 53° E., 49 links distance, with visible scribe marks on an open blaze. (Record: S. 52 1/2° E., 48 links)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to solid rock, in a mound of stone 4 ft. base to top of aluminum cap marked:

T14NR15W  
S15  
1/4 —  
S22  
2006

Deposit marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls on a northwest slope.

S. 89°57.9' W., between sections 15 and 22

**19.891** Point for the W 1/16 section corner of sections 15 and 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14NR15W  
S15  
W 1/16 —  
S22  
2006

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls on a southwest slope in piñon and juniper growth, and 23 ft. east of a north-south fence line.

**39.782** The corner of sections 15, 16, 21, and 22.

---

N. 0°07.2' E., between sections 15 and 16.

**20.192** Point for the S 1/16 section corner of sections 15 and 16, not monumented.

**40.384** The 1/4 section corner of sections 15 and 16, monumented with a quartz stone, 22x14x4 inches, firmly set, clearly marked 1/4 on west face.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 14 NORTH, RANGE 15 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14NR15W  
1/4  
S16|S15  
2006

Deposit marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls in an ancient north-south fence line.

The Subdivision of Section 15,  
Township 14 North, Range 15 West, Salt Lake Meridian, Utah

From the 1/4 section corner of sections 15 and 22

N. 0°15.9' E., on the N - S center line of section 15.

**20.238** Point for the center S 1/16 section corner of section 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14NR15W  
C  
S 1/16 | S15  
C  
2006

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls alongside a piñon stump, on a gentle northwest slope in dense piñon and juniper growth, and 3.4 ft. west of a north-south fence line.

**40.476** Point for the center 1/4 section corner, at intersection with the E - W center line of section 15.

Set a rebar, 15 inches long, 3/4 inch diameter, driven 6 inches below road surface, with a 1 1/2 inch diameter aluminum cap attached and marked:

THE SUBDIVISION OF SECTION 15,  
TOWNSHIP 14 NORTH, RANGE 15 WEST, SALT LAKE MERIDIAN UTAH

## CHAINS

T14NR15W  
C 1/4  
S15  
2006

Corner falls N. 13°27' E., 165.24 ft. from the corner of fences projecting north, south, and east. Corner falls on easterly edge of gravel road projecting north and southwesterly.

**80.717** Point for the 1/4 section corner of sections 10 and 15, determined longitudinally by an old fence bearing north and south, and latitudinally by the extension of a fence from the east. There is no remaining evidence of the original monument.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a mound of stone 3 ft. base to top of aluminum cap marked:

T14NR15W  
S10  
1/4 —  
S15  
2006

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

---

From the 1/4 section corner of sections 14 and 15, monumented with a quartz stone, 16x10x8 inches, firmly set, no marks visible, and witnessed with a mound of stone to the east.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14NR15W  
1/4  
S15|S14  
2006

Deposit quartz stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Raise a mound of stone 3 ft. base by 1.5 ft. high, west of the aluminum post.

Corner falls on a south slope in piñon and juniper growth, and in an ancient dilapidated north-south fence line, and 2 ft.

THE SUBDIVISION OF SECTION 15,  
TOWNSHIP 14 NORTH, RANGE 15 WEST, SALT LAKE MERIDIAN UTAH

CHAINS

west of an north-south fence line.

S. 89°50.2' W., on the E - W center line of section 15.

- 40.897** The center 1/4 section corner of section 15.
- 60.837** Point for the center W 1/16 section corner of section 15, not monumented.
- 80.777** The 1/4 section corner of sections 15 and 16.
- 

From the W 1/16 section corner of sections 15 and 22.

N. 0°11.6' E., on the N - S center line of the SW 1/4 of section 15.

- 20.215** Point for the SW 1/16 section corner, at intersection with the E - W center line of the SW 1/4 of section 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14NR15W  
SW 1/16  
S15  
2006

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls west of a county road.

- 40.430** The point for the center W 1/16 section corner of section 15.
- 

From the center S 1/16 section corner of section 15.

S. 89°54.1' W., on the E - W center line of the SW 1/4 of section 15.

- 19.916** The SW 1/16 section corner of section 15.
- 39.832** The point for the S 1/16 section corner of sections 15 and 16, not monumented.

THE SUBDIVISION OF SECTION 15,  
TOWNSHIP 14 NORTH, RANGE 15 WEST, SALT LAKE MERIDIAN UTAH

CHAINS

---

The Subdivision of Section 22,  
Township 14 North, Range 15 West, Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 22 and 27.

N. 0°20.0' W., on the N - S center line of section 22.

- 40.280** Point for the center 1/4 section corner, at intersection with the E - W center line of section 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14NR15W  
C 1/4  
S22  
2006

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls on the northwest edge of a tailings pile.

- 60.397** Point for the center N 1/16 section corner of section 22, not monumented.

- 80.514** The 1/4 section corner of sections 15 and 22.
- 

From the 1/4 section corner of section 22 only.

S. 89°41.1' W., on the E - W center line of section 22.

- 20.331** Point for the center E 1/16 section corner of section 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a mound of stone 3 ft. base to top of aluminum cap marked:

T14NR15W  
E 1/16  
C — C  
S22  
2006

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls on a steep southwest slope in dense piñon and juniper growth.

THE SUBDIVISION OF SECTION 22,  
TOWNSHIP 14 NORTH, RANGE 15 WEST, SALT LAKE MERIDIAN UTAH

## CHAINS

- 40.662** The center 1/4 section corner of section 22.
- 60.679** Point for the center W 1/16 section corner of section 22, not monumented.
- 80.696** The 1/4 section corner of sections 21 and 22.

---

From the E 1/16 section corner of sections 22 and 27.

N. 0°01.2' E., on the N - S center line of the SE 1/4 of section 22.

- 40.352** The center E 1/16 section corner of section 22.

---

From the point for the center W 1/16 section corner of section 22.

N. 0°09.4' W., on the N - S center line of the NW 1/4 of section 22.

- 20.166** Point for the NW 1/16 section corner, at intersection with the E - W center line of the NW 1/4 of section 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14NR15W  
NW 1/16  
S22  
2006

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls on gentle rolling land in dense piñon and juniper growth, and 100 ft. east of a north-south fence line.

- 40.332** The W 1/16 section corner of sections 15 and 22.

---

From the point for the center N 1/16 section corner of section 22.

S. 89°49.5' W., on the E - W centerline of the NW 1/4 of section 22.

- 19.954** The NW 1/16 section corner of section 22.

- 39.908** The N 1/16 section corner of sections 21 and 22.

THE SUBDIVISION OF SECTION 22,  
TOWNSHIP 14 NORTH, RANGE 15 WEST, SALT LAKE MERIDIAN UTAH

CHAINS

The Subdivision of Section 23,  
Township 14 North, Range 15 West, Salt Lake Meridian, Utah

From the 1/4 section corner of sections 23 and 26, monumented with a quartzite stone, 20x12x9 inches, firmly set, clearly marked 1/4 on north face, and witnessed with a mound of stone to the north.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a mound of stone 3 ft. base to top of aluminum cap marked:

T14NR15W  
S23  
1/4 —  
S26  
2006

Deposit marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls 38 ft. north of an east-west fence line.

N. 0°43.5' E., on the N - S center line of section 23.

**39.584** Point for the center 1/4 section corner, at intersection with the E - W center line of section 23.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14NR15W  
C 1/4  
S23  
2006

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls N. 15°41' E., 101 ft. distance, of an intersection of fence lines projecting north, east, and west.

**83.612** The 1/4 section corner of sections 14 and 23

THE SUBDIVISION OF SECTION 23,  
TOWNSHIP 14 NORTH, RANGE 15 WEST, SALT LAKE MERIDIAN UTAH

CHAINS

---

From the 1/4 section corner of sections 23 and 24, monumented with a limestone, 14x7x6 inches, firmly set, dimly marked 1/4 on west face, and witnessed with a mound of stone to the west.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground, in a mound of stone 3 ft. base to top of aluminum cap marked:

T14NR15W  
1/4  
S23| S24  
2006

Deposit marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls on a steep southwest slope, and 75 ft. south of an east-west ridge line.

S. 88°30.6' W., on the E - W center line of section 23.

**39.647** The center 1/4 section corner of section 23.

**79.067** The 1/4 section corner of section 23 only.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Glen Hatch	Cadastral Surveyor
Travis Hanks	Survey Technician

---

## CERTIFICATE OF SURVEY

I, **Ronald K. Baugh**, *Supervisory Cadastral Surveyor*, hereby certify upon honor, that in pursuance of special instructions bearing the date of the **9th day of June, 2006**, I have **dependently resurveyed a portion of the subdivisional lines, and the subdivision of sections 15, 22, and 23, in Township 14 North, Range 15 West,**

of the **Salt Lake** Meridian, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions of the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

July 29, 2008  
Date

Ronald K. Baugh  
Supervisory Cadastral Surveyor

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The following field notes of the **dependent resurvey of a portion of the subdivisional lines, and the subdivision of sections 15, 22, and 23, in Township 14 North, Range 15 West, Salt Lake Meridian, Utah,**

Executed by **Ronald K. Baugh**, *Supervisory Cadastral Surveyor*, having been **critically examined and found correct, are hereby approved.**

September 12, 2008  
Date

David W. Webb  
(Chief Cadastral Surveyor for Utah)