

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 21, 22, 27, 28, AND 29,

IN

TOWNSHIP 28 SOUTH, RANGE 9 EAST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Ronald K. Baugh
Supervisory Cadastral Surveyor

and

Ronald K. Batty
Survey Technician

Under Special Instructions dated and approved **December 8, 2006**, which provided for the surveys included under Group Number 1033, and Assignment Instructions dated **December 8, 2006**.

Survey Commenced, **December 19, 2006**
Survey Completed, **July 19, 2007**

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 21, 22, 27, 28, AND 29,

IN

TOWNSHIP 28 SOUTH, RANGE 9 EAST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Ronald K. Baugh
Supervisory Cadastral Surveyor

and

Ronald K. Batty
Survey Technician

Under Special Instructions dated and approved **December 8, 2006**, which provided for the surveys included under Group Number 1033, and Assignment Instructions dated **December 8, 2006**.

Survey Commenced, **December 19, 2006**
Survey Completed, **July 19, 2007**

INDEX DIAGRAM

Township 28 South, Range 9 East.

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	7 6 21	5 4 22 3	23	24
30	8 7 29	6 5 28	4 3 27 3	26	25
31	7 32	5 33	3 34	35	36

The Subdivision of Section 21.....	Page 8
The Subdivision of Section 22.....	Page 11
The Subdivision of Section 27.....	Page 11
The Subdivision of Section 28.....	Page 13
The Subdivision of Section 29.....	Page 14

TOWNSHIP 28 SOUTH, RANGE 9 EAST, SALT LAKE MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, and the subdivision of sections 21, 22, 27, 28, and 29, in T. 28 S., R. 9 E., Salt Lake Meridian, Utah.

HISTORY OF SURVEYS

Surveyed by		Retr. or Resurveyed by	
SOUTH BOUNDARY			
All	A.D. Ferron	1883	
Portion		E. Bird	1919
Portion		C.P. Sylvester	1964
EAST BOUNDARY			
All	A.D. Ferron	1883	
All		C.P. Sylvester	1964
WEST BOUNDARY			
All	A.D. Ferron	1883	
All	Moore & Clark	1932-34	
Portion		R.C. Yundt	1949
NORTH BOUNDARY			
Portion	A.D. Ferron	1883	
Portion	Moore & Clark	1832-34	
Portion		E. Bird	1940
SUBDIVISION			
Portion	A.D. Ferron	1883	
Portion	Moore & Clark	1932-34	
Portion		Moore & Clark	1932-34
Portion		R.C. Yundt	1949
Portion		C.P. Sylvester	1964

TOWNSHIP 28 SOUTH, RANGE 9 EAST, SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1033, dated December 8, 2006.

The directions of the lines were determined by references to true meridians, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods*, dated May 9, 2001, Version 1.0. Trimble model 5800 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Cadastral Control Network was derived from GPS static observations, post processed by the National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS): MARYSVALE_UT2006, CARBON COUNTY COU, and MONTICELLO_UT2006.

The geographic position of the corner of sections 15, 16, 21, and 22, T. 28 S., R. 9 E., as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: **38°22'04.041" N.**,
Longitude: **110°56'05.010" W.**, N.A.D. 83,
Network Accuracy = 0.200 meter at 95% confidence

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 28 SOUTH, RANGE 9 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 9 E., Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by A.D. Ferron in 1883,
and the Resurvey Executed by C.P. Sylvester in 1964.

Beginning at the 1/4 section corner of sections 26 and 27,
monumented with an iron post, 2 1/2 inches diameter, firmly set,
marked as described in the official record of the 1964 resurvey.

N. 0°33.6' E., between sections 26 and 27.

- 39.533 The corner of sections 22, 23, 26, and 27, monumented with an
iron post, 2 1/2 inches diameter, firmly set, marked as described
in the official record of the 1964 resurvey.

N. 0°17.9' E., between sections 22 and 23.

- 40.335 The 1/4 section corner of sections 22 and 23, monumented with an
iron post, 2 1/2 inches diameter, firmly set, marked as described
in the official record of the 1964 resurvey.

From the 1/4 section corner of sections 27 and 34, monumented
with an iron post, 2 1/2 inches diameter, firmly set, marked as
described in the official record of 1964 resurvey.

N. 89°46.4' W., between sections 27 and 34.

- 40.509 The corner of sections 27, 28, 33, and 34, monumented with an
iron post, 2 1/2 inches diameter, firmly set, marked as described
in the official record of the 1964 resurvey.

N. 0°04.5' W., between sections 27 and 28.

- 39.663 The 1/4 section corner of sections 27 and 28, monumented with an
iron post, 2 1/2 inches diameter, firmly set, marked as described
in the official record of the 1964 resurvey.

N. 0°01.6' E., beginning new measurement.

- 20.129 Point for the N 1/16 section corner of sections 27 and 28.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over
a magnet, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 28 SOUTH, RANGE 9 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

N 1/16
S28 | S27
2007

Corner is located on a steep, south facing slope.

- 40.258 Point for the corner of sections 21, 22, 27, and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 26 inches in the ground, with aluminum cap marked:

T28S R9E
S21 | S22
S28 | S27
2006

Corner is located in a swampy river bottom surrounded by sparse cottonwood trees and brush.

From the corner of sections 22, 23, 26, and 27.

N. 89°50.6' W., between sections 22 and 27.

- 40.015 The 1/4 section corner of sections 22 and 27, monumented with an iron post, 2 1/2 inches diameter, firmly set, marked as described in the official record of the 1964 resurvey.

N. 89°55.8' W., beginning new measurement.

- 20.111 Point for the W 1/16 section corner of sections 22 and 27.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 26 inches in the ground, with aluminum cap marked:

S22
W 1/16 ———
S27
2007

Corner is located in a river bottom with sandy soil surrounded by thick tamarack.

- 40.222 The corner of sections 21, 22, 27, and 28.

N. 0°13.2' E., between sections 21 and 22.

- 20.129 Point for the S 1/16 section corner of sections 21 and 22, not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 28 SOUTH, RANGE 9 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.258 The 1/4 section corner of sections 21 and 22, monumented with an iron post, 2 1/2 inches diameter, firmly set, marked as described in the official record of the 1964 resurvey.

N. 0°12.7' E., beginning new measurement.

- 40.266 The corner of sections 15, 16, 21, and 22, monumented with an iron post, 2 inches diameter, firmly set, marked as described in the official record of the 1932-34 resurvey.

From the 1/4 section corner of sections 15 and 22, monumented with an iron post, 2 1/2 inches diameter, firmly set, marked as described in the official record of the 1964 resurvey.

N. 89°44.5' W., between sections 15 and 22.

- 39.955 The corner of sections 15, 16, 21, and 22.

From the corner of sections 27, 28, 33, and 34.

S. 89°42.0' W., between sections 28 and 33.

- 39.888 The 1/4 section corner of sections 28 and 33, monumented with an iron post, 2 1/2 inches diameter, firmly set, marked as described in the official record of the 1964 resurvey.

S. 89°50.6' W., beginning new measurement.

- 41.049 The corner of sections 28, 29, 32, and 33, monumented with an iron post, 2 1/2 inches diameter, firmly set, marked as described in the official record of the 1964 resurvey.

N. 0°24.8' E., between sections 28 and 29.

- 40.146 The 1/4 section corner of sections 28 and 29, monumented with an iron post, 2 1/2 inches diameter, firmly set, marked as described in the official record of the 1964 resurvey.

N. 0°25.3' E., beginning new measurement.

- 38.163 The witness corner for the corner of sections 20, 21, 28, and 29, monumented with an iron post, 2 inches diameter, firmly set, marked as described in official record of the 1932-34 resurvey.

- 40.763 True point for the corner of sections 20, 21, 28, and 29, not monumented.
-

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 28 SOUTH, RANGE 9 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

From the corner of sections 21, 22, 27, and 28.

N. 89°32.0' W., between sections 21 and 28.

20.016 Point for the E 1/16 section corner of sections 21 and 28, not monumented.

40.032 The 1/4 section corner of sections 21 and 28, monumented with an iron post, 2 1/2 inches diameter, firmly set, marked as described in the official record of the 1964 resurvey.

N. 89°31.1' W., beginning new measurement.

20.134 Point for the W 1/16 section corner of sections 21 and 28.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 31 inches in the ground, with aluminum cap marked:

	S21
W 1/16	—————
	S28
	2007

Corner is located on the northern edge of Highway 24.

40.268 The true point for the corner of sections 20, 21, 28, and 29.

Reestablishment of the Survey Executed by A.D. Ferron
in 1883, and the Resurvey Executed by C.F. Moore and
J.C. Clark in 1932-1934.

N. 0°09.5' W., between sections 20 and 21.

20.010 Point for the S 1/16 section corner of section 21 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 21 inches in the ground, with aluminum cap marked:

	S 1/16
	S 21
	2007

Corner is located on a steep, east facing hillside.

40.020 The W 1/4 section corner of section 21 only, monumented with an iron post, 1 inch diameter, firmly set, marked as described in the official record of the 1932-34 resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 28 SOUTH, RANGE 9 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

From the corner of sections 15, 16, 21, and 22.

N. 89°50.6' W., between sections 16 and 21.

- 40.398 True point for the 1/4 corner of sections 16 and 21, not monumented.

From this point, the witness corner for the 1/4 section corner of sections 16 and 21, bears S. 0°03.1' E., 2.620 chains distance, monumented with an iron post, 1 inch diameter, firmly set, projecting 10 inches from the ground, to the top of brass cap marked as described in the official record of the 1932-34 resurvey.

Reestablishment of the Survey Executed by A.D. Ferron in 1883,
and the Resurvey Executed by C.P. Sylvester in 1964.

From the corner of sections 28, 29, 32, and 33.

S. 89°58.6' W., between sections 29 and 32.

- 39.943 The 1/4 corner of sections 29 and 32, monumented with an iron post, 2 1/2 inches diameter, firmly set, marked as described in the official record of the 1964 resurvey.

N. 89°46.8' W., beginning new measurement.

- 40.246 The corner of sections 29, 30, 31, and 32, monumented with an iron post, 2 1/2 inches diameter, firmly set, marked as described in the official record of the 1949 resurvey.

Reestablishment of the Survey Executed by A.D. Ferron in 1883,
and the Resurvey Executed by R.C. Yundt in 1949.

N. 0°02.4' W., between sections 29 and 30.

- 40.004 Point for the 1/4 section corner of sections 29 and 30, at proportionate distance. There is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 26 inches in the ground, with aluminum cap marked:

T28S R9E
1/4
S30 | S29
2006

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 28 SOUTH, RANGE 9 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

Corner is located at the edge of a grassy field. A fence extending north and south is located approximately 40 feet east of the aluminum post.

- 60.006 The N 1/16 section corner of sections 29 and 30, monumented with an iron post, 2 inches diameter, firmly set, marked as described in the official record of the 1949 resurvey.

N. 0°08.2' W., beginning new measurement.

- 19.986 True point for the corner of sections 29 and 30 only.

From this point, the witness corner for the corner of sections 29 and 30 only, bears N. 0°08.2' W., 0.420 chains distance, monumented with an iron post, 2 inch diameter, firmly set, projecting 4 inches from the ground, to the top of brass cap marked as described in the official record in the 1932-34 resurvey.

Reestablishment of the Survey Executed by A.D. Ferron
in 1883, and the Resurvey Executed by C.F. Moore and
J.C. Clark in 1932-1934.

From the true point for the corner of sections 20, 21, 28, and 29.

S. 89°28.3' W., between sections 20 and 29.

- 39.713 The south 1/4 section corner of section 20 only, monumented with an iron post, 1 inch diameter, firmly set, marked as described in the official record of the 1932-34 resurvey.

- 40.074 The north 1/4 section corner of section 29 only, monumented with an iron post, 1 inch diameter, firmly set, marked as described in the official record of the 1932-34 resurvey.

S. 89°25.8' W., beginning new measurement.

- 40.419 The true point for the corner of sections 29 and 30.

The Subdivision of Section 21,
T. 28 S., R. 9 E., Salt Lake Meridian, Utah.

From the 1/4 corner of sections 21 and 28.

N. 0°03.1' W., on the N-S centerline of section 21.

- 20.073 Point for the center S 1/16 section corner of section 21.

THE SUBDIVISION OF SECTION 21,
TOWNSHIP 28 SOUTH, RANGE 9 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 27 inches in the ground, with aluminum cap marked:

C
S 1/16 | S 21
C
2007

40.146 Point for the center 1/4 section corner of section 21.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 27 inches in the ground, with aluminum cap marked:

T28S R9E
C1/4 S21
2007

77.687 The witness corner for the 1/4 section corner of sections 16 and 21.

80.307 The true point for the 1/4 section corner of sections 16 and 21.

From the 1/4 section corner of sections 21 and 22.

N. 89°41.9' W., on the E-W centerline of section 21.

20.109 Point for the center E 1/16 section corner of section 21.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 27 inches in the ground, with aluminum cap marked:

E 1/16 S21
C—C
2007

Raised a mound of stone, 2 feet base, 1 1/2 feet high, west of the aluminum post.

40.218 The point for the center 1/4 corner of section 21.

60.387 Point for the center W 1/16 section corner of section 21.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 26 inches in the ground, with aluminum cap marked:

W 1/16 S21
C—C
2007

Corner is located in level area between hills to west and east.

80.556 The west 1/4 section corner of section 21 only.

THE SUBDIVISION OF SECTION 21,
TOWNSHIP 28 SOUTH, RANGE 9 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the point for the E 1/16 section corner of sections 21 and 28.

N. 0°05.1' E., on the N-S centerline of the SE 1/4 of section 21.

20.101 Point for the SE 1/16 section corner of section 21.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 27 inches in the ground, with aluminum cap marked:

S21 SE 1/16
2007

40.202 The center E 1/16 section corner of section 21.

From the point for the S 1/16 section corner of section 21 and 22.

N. 89°36.8' W., on the E-W centerline of the SE 1/4 of section 21.

20.063 The SE 1/16 section corner of section 21.

40.126 The center S 1/16 section corner of section 21.

From the W 1/16 section corner of section 21.

N. 0°06.3' W., on the N-S centerline of the SW 1/4 of section 21.

20.042 Point for the SW 1/16 section corner of section 21.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

SW 1/16 S21
2007

Corner is located on the southern edge of a small ridge.

40.084 The center W 1/16 section corner of section 21.

From the center S 1/16 section corner of section 21.

N. 89°36.5' W., on the E-W centerline of the SW 1/4 of section 21.

20.151 The SW 1/16 section corner of section 21.

40.302 The S 1/16 section corner on the west boundary of section 21 only.

THE SUBDIVISION OF SECTION 22,
TOWNSHIP 28 SOUTH, RANGE 9 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 22,
T. 28 S., R. 9 E., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 22 and 27.

N. 0°01.9' E., on the N-S centerline of section 22.

40.268 Point for the center 1/4 section corner of section 22, at
intersection with E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over
a magnet, 27 inches in the ground, with aluminum cap marked:

T28S R9E
C1/4 S22
2007

80.392 The 1/4 section corner of sections 15 and 22.

From the 1/4 section corner of sections 22 and 23.

N. 89°56.5' W., on the E-W centerline of section 22.

40.199 The center 1/4 section corner of section 22.

60.242 Point for the center W 1/16 section corner of section 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over
a magnet, 27 inches in the ground, with aluminum cap marked:

W 1/16 S22
C—C
2007

80.285 The 1/4 section corner of sections 21 and 22.

From the W 1/16 section corner of sections 22 and 27.

N. 0°07.5' W., on the N-S centerline of the SW 1/4 of section 22.

40.263 Point for the W 1/16 section corner of section 22.

The Subdivision of Section 27,
T. 28 S., R. 9 E., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 27 and 34.

N. 0°13.4' W., on the N-S centerline of section 27.

THE SUBDIVISION OF SECTION 27,
TOWNSHIP 28 SOUTH, RANGE 9 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

40.113 Point for the center 1/4 section corner of section 27.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 26 inches in the ground, with aluminum cap marked:

T28S R9E
C1/4 S27
2007

Corner is located on flat sandy area at top of a plateau.

60.073 Point for the center N 1/16 section corner of section 27.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 26 inches in the ground, with aluminum cap marked:

C
N 1/16 | S 27
C
2007

Corner is located on flat ground on a north facing bench.

80.033 The 1/4 section corner of section 22 and 27.

From the 1/4 section corner of section 26 and 27.

S. 89°35.6' W., on the E-W centerline of section 27.

39.479 Point for the center 1/4 section corner of section 27.

59.680 Point for the center W 1/16 section corner of section 27.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 26 inches in the ground with aluminum cap marked:

W 1/16
C—C
S27
2007

Corner is located on a gentle west facing slope, and the bottom of a wash is approximately 20 feet west of corner.

79.881 The 1/4 section corner of section 27 and 28.

From the center W 1/16 section corner of section 27.

N. 0°05.8' W., on the N-S centerline of the NW 1/4 of section 27.

20.044 Point for the NW 1/16 section corner of section 27,

THE SUBDIVISION OF SECTION 27,
TOWNSHIP 28 SOUTH, RANGE 9 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 26 inches in the ground, with aluminum cap marked:

NW 1/16 S27
2007

Corner is located at the bottom of drainage.

40.088 The W 1/16 section corner of section 22 and 27.

From the center N 1/16 section corner of section 27.

S. 89°49.8' W., on the E-W centerline of the NW 1/4 of section 27.

20.156 Point for the NW 1/16 section corner of section 27.

40.312 Point for the N 1/16 section corner of section 27 and 28.

The Subdivision of Section 28,
T. 28 S., R. 9 E., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 28 and 33.

N. 0°07.9' W., on the N-S centerline of section 28.

39.953 Point for the center 1/4 section corner of section 28.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 28 inches in the ground, with aluminum cap marked:

T28S R9E
C1/4 S28
2007

Corner is located in flat area surrounded by sandy hills.

60.204 Point for the center N 1/16 section corner of section 28.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 26 inches in the ground, with aluminum cap marked:

C
N 1/16 | S 28
C
2007

Corner is located in swampy area north of the Fremont River.

80.455 The 1/4 section corner of section 21 and 28.

THE SUBDIVISION OF SECTION 28,
TOWNSHIP 28 SOUTH, RANGE 9 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of section 27 and 28.

N. 89°53.0' W., on the E-W centerline of section 28.

39.923 The center 1/4 section corner of section 28.

80.586 The 1/4 section corner of section 28 and 29.

From the N 1/16 section corner of sections 27 and 28.

N. 89°42.5' W., on the E-W centerline of the NE 1/4 of section 28.

39.978 The center N 1/16 section corner of section 28.

The Subdivision of Section 29,
T. 28 S., R. 9 E., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 29 and 32.

N. 0°03.8' E., on the N-S centerline of section 29.

40.162 Point for the center 1/4 section corner of section 29, at intersection with the E-W centerline, falls in the river bottom of the Fremont River; where it is impractical to monument, not monumented.

60.355 Point for the center N 1/16 section corner of section 29.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 27 inches in the ground, with aluminum cap marked:

C
N 1/16 | S 29
C
2007

Corner is located on east bank of a small canal. Center of the canal is 9.7 feet west of the corner. The center line of a power line bearing E-W is located 26 feet south. Highway 24 is located approximately 400 feet south of the corner.

80.548 The N 1/4 section corner of section 29.

From the 1/4 section corner of sections 28 and 29.

S. 89°59.9' W., on the E-W centerline of section 29.

40.183 The point for the center 1/4 corner of section 29.

THE SUBDIVISION OF SECTION 29,
TOWNSHIP 28 SOUTH, RANGE 9 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

80.497 The 1/4 section corner of sections 29 and 30.

From the center N 1/16 section corner of section 29.

S. 89°43.4' W., on the E-W centerline of the NW 1/4 of section
29.

40.349 The N 1/16 section corner of section 30.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Adrian M. Kurip	Survey Technician
Daniel T. Gillins	Survey Technician
Calvert C. Norton	Survey Technician

CERTIFICATE OF SURVEY

We, **Ronald K. Baugh, Cadastral Surveyor**, and **Ronald K. Batty, Survey Technician**, hereby certify upon honor that, in pursuance of special instructions bearing the date of the **8th day of December, 2006**, we have executed a **dependent resurvey of a portion of the subdivisional lines, and the subdivision of sections 21, 22, 27, 28, and 29, in T. 28 S., R 9 E.,**

of the **Salt Lake Meridian**, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Aug. 23, 2010
Name

Ronald K. Baugh
(Cadastral Surveyor)

Aug 23, 2010
Name

[Signature]
(Survey Technician)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt lake City, Utah

The foregoing field notes of the **dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 21, 22, 27, 28, and 29 of Township 28 South, Range 9 East, Salt Lake Meridian, Utah.**

executed by **Ronald K. Baugh, Cadastral Surveyor** and **Ronald K. Batty, Survey Technician**, having been critically examined and found correct, are hereby approved.

August 25, 2010
Date

Daniel W. Webb
Chief Cadastral Surveyor for Utah

~~CERTIFICATE OF TRANSCRIPT~~

~~I certify that the foregoing transcript of the field notes of the above described surveys in **T. 28 S., R. 9 E., Salt Lake Meridian, Utah**, is a true copy of the original field notes.~~

~~_____~~
~~Date~~

~~_____~~
~~(Cadastral Surveyor)~~