

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
THE CORRECTIVE RESURVEY OF A PORTION OF THE NORTH BOUNDARY,

OF

TOWNSHIP 40 SOUTH, RANGE 23 EAST,

THE DEPENDENT RESURVEY OF THE WEST BOUNDARY
(COLORADO GUIDE MERIDIAN)

THE DEPENDENT RESURVEY OF THE NORTH BOUNDARY,

THE SUBDIVISIONAL LINES,

AND THE SURVEY OF THE
SUBDIVISION OF SECTIONS 5, 8, 23, AND 33,

AND

THE SURVEY OF THE MEANDERS OF THE LEFT BANK OF
RECAPTURE CREEK IN SECTION 19,

IN

TOWNSHIP 39 SOUTH, RANGE 23 EAST,

OF THE SALT LAKE MERIDIAN,
IN THE STATE OF UTAH.

EXECUTED BY

Scott A. Burkhardt
Cadastral Surveyor

Under Special Instructions Dated **June 27, 2007**, approved **June 27, 2007**, which provided for the surveys included under **Group Number 1037**, and Assignment Instructions Dated **June 27, 2007**

Survey commenced **July 17, 2007**
Survey completed **September 20, 2007**

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
THE CORRECTIVE RESURVEY OF A PORTION OF THE NORTH BOUNDARY,

OF

TOWNSHIP 40 SOUTH, RANGE 23 EAST,

THE DEPENDENT RESURVEY OF THE WEST BOUNDARY
(COLORADO GUIDE MERIDIAN)

THE DEPENDENT RESURVEY OF THE NORTH BOUNDARY,

THE SUBDIVISIONAL LINES,

AND THE SURVEY OF THE
SUBDIVISION OF SECTIONS 5, 8, 23, AND 33,

AND

THE SURVEY OF THE MEANDERS OF THE LEFT BANK OF
RECAPTURE CREEK IN SECTION 19,

IN

TOWNSHIP 39 SOUTH, RANGE 23 EAST,

OF THE SALT LAKE MERIDIAN,
IN THE STATE OF UTAH.

EXECUTED BY

Scott A. Burkhardt
Cadastral Surveyor

Under Special Instructions Dated **June 27, 2007**, approved **June 27, 2007**, which provided for the surveys included under **Group Number 1037**, and Assignment Instructions Dated **June 27, 2007**

Survey commenced **July 17, 2007**
Survey completed **September 20, 2007**

INDEX DIAGRAM

Township 39 South, Range 23 East

16	20	20	20	19	19	18	18	18	17	17	17	17
16	6	64	5	52	4	44	3	37	2	30	1	
15	63	62	63	51	51	43	44	36	37	29	29	29
14	7	61	8	50	9	43	10	36	11	28	12	
14	61	59	60	49	50	43	42	35	36	27	28	28
13	18	59	17	49	16	42	15	35	14	27	13	
13	58	57	57	48	48	41	41	34	34	26	26	26
13	19	56	20	48	21	40	22	34	23	26	24	
12	56	55	55	46	47	39	40	32	33	24	25	24
11	30	55	29	46	28	39	27	32	26	23	25	
11	54	53	53	45	46	38	38	31	31	22	23	22
10	31	52	32	45	33	37	34	31	35	21	36	
10	9	8	8	7	6	6	5	5	4	3	3	3

The Subdivision of Section 5.....Page 65
 The Subdivision of Section 8.....Page 66
 The Subdivision of Section 23.....Page 66
 The Subdivision of Section 33.....Page 68
 The Meanders of the Left Bank of Recapture Creek.....Page 70

TOWNSHIP 39 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

The following field notes describe the dependent resurvey of a portion of the north boundary and the corrective resurvey of a portion of the north boundary of Township 40 South, Range 23 East, the dependent resurvey of the west boundary (Colorado Guide Meridian), the north boundary, and the subdivisional lines, the survey of the subdivision of sections 5, 8, 23, and 33, and the survey of the meanders of the left bank of Recapture Creek in section 19 of Township 39 South, Range 23 East, Salt Lake Meridian, Utah.

History of Surveys

Surveyed by	Retr. or Resurveyed by
SOUTH BOUNDARY	
All A.D. Ferron 1884	
All	H.D. Page & J.M. Lentz 1899
All	H.B. Miller & J.C. Thoma 1912
Portion	D.A. Buhler 1980
EAST BOUNDARY	
All H.B. Miller & J.C. Thoma 1912	
All	M.R. Workman & C.S. Bishop 2003
WEST BOUNDARY (Colorado Guide Meridian)	
All F. Dickert 1878	
All	A.P. Hanson 1907
All	H.B. Miller & J.C. Thoma 1912
NORTH BOUNDARY	
All H.B. Miller & J.C. Thoma 1912	
Portion	R.A. Zaninovich 1984
SUBDIVISION	
All H.B. Miller & J.C. Thoma 1912	

TOWNSHIP 39 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated June 27, 2007, for Group No. 1037, Utah.

The direction of the lines was determined by references to true meridians, established by Global Positioning Systems (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. Trimble model 4800 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) and Trimble Geomatics Office software's were utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

All monuments set in this survey and resurvey, bear the Navajo seal, unless otherwise noted.

Geodetic control was derived from Global Positioning System (GPS) static post observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS); Monticello UT 2006, Aztec, and Chaco CNHP_NM 2005.

The geographic positions, in NAD83 (CORS96), epoch date 2002.00 for the corners listed below were determined by Global Positioning System (GPS) observations to a Network Accuracy of less than 0.20 meter, 95 percent confidence circle, as defined in *Standards and Guidelines for Cadastral Surveys Using Global Positioning Systems Methods, May 9, 2001, Version 1.0*.

The geographic position of the corner of Townships 38 and 39 South, Ranges 22 and 23 East, Salt Lake Meridian, Utah, as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude 37° 25' 56.894" N.,
 Longitude 109° 26' 23.582" W.,
 N.A.D. 1983 (CORS96)
 N.A.V.D. 1988, Elevation 4844 ft.

The geographic position of the corner of Townships 38 and 39 South, Ranges 23 and 24 East, Salt Lake Meridian, Utah, as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude 37° 25' 57.179" N.,
 Longitude 109° 19' 51.732" W.,
 N.A.D. 1983 (CORS96)
 N.A.V.D. 1988, Elevation 5258 ft.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY
T. 40 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the North Boundary,
T. 40 S., R. 23 E., Salt Lake Meridian, Utah

Reestablishing the Survey executed by A.D. Ferron in 1884, the
Dependent Resurveys by H.D. Page and J.M. Lentz in 1899,
and D.B. Miller and J.C. Thoma, in 1912

Beginning at the cor. of Tps. 39 and 40 S., Rs. 23 and 24 E.,
monumented with a stainless steel post, 2 1/2 ins. diam., firmly
set flush with ground, with brass cap (Navajo seal) mkd. as
described in the official record of the 2003 resurvey of the W.
bdy. of T. 39 S., R. 24 E., witnessed by a mound of stone, 4 ft.
diam. base, 1 1/2 ft. high, southeast of cor. Set a steel fence
post north of cor.

N. 89°54.7' W., bet. secs. 1 and 36, on the N. bdy. of the Tp.

40.054

The 1/4 sec. cor. of secs. 1 and 36, monumented with a
sandstone, 19 x 7 x 7 ins., no marks, projecting 10 ins. above
an embedded mound of stone, 2 1/2 ft. diam.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20
ins. in the ground with magnet at base, in a mound of stone,
2 1/2 ft. base to top of Navajo brass cap mkd.:

T39S R23E
S 36
1/4 ———
S 1
T40S
2007

Bury original stone in mound of stone.

Set a steel fence post north of cor.

Cor. is located on the northwest side of a wash, course
northeast.

N. 89°54.9' W., beginning new measurement.

35.130

The centerline of Utah State Highway 262, a paved road, 25 ft.
wide, extending N. 09° E. and S. 09° W.

40.048

The cor. of secs. 1, 2, 35, and 36, monumented with a sandstone,
10 x 7 x 3 ins., firmly set, no marks, projecting 7 ins. above
an embedded mound of stone, 3 ft. base, 6 ins. high.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY
T. 40 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground with magnet at base, in a collar of stone, 3 ft. diam., with Navajo brass cap mkd.:

T39S	R23E
S 35	S 36
S 2	S 1
T40S	
2007	

Bury original stone in mound of stone.

Set a steel fence post north of cor.

from which

A rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, bears S. 81°59.4' E., 0.063 ch. dist. not of record, not utilized in this resurvey.

Cor. is located in open prairie, with desert vegetation.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 736+00, ELEV 5200.10, 1960, on the west side of Utah State Highway 262, bears N. 44°39.6' E., 5.649 chs. dist.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 4 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 736+00, ELEV 5193.31, 1960, on the east side of Utah State Highway 262, bears N. 62°58.8' E., 7.812 chs. dist.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 4 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 745+00, ELEV 5197.74, 1960, on the east side of Utah State Highway 262, bears S. 26°05.5' E., 11.041 chs. dist.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 5 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 745+00, ELEV 5198.30, on the west side of Utah State Highway 262, bears S. 11°10.4' E., 9.622 chs. dist.

S. 89°54.4' W., bet. secs. 2 and 35, on the N. bdy. of the Tp.

39.855

The 1/4 sec. cor. of secs. 2 and 35, monumented with a sandstone, 25 x 15 x 5 ins., mkd. 1/4 on north face, projecting 16 ins. above an embedded mound of stone, 3 ft. base, 1 ft.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY
T. 40 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

high, witnessed by a mound of stone, 2 1/2 ft. diam. base, 2 ft. high, north of cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground to bedrock, with magnet at base, in a mound of stone, 4 ft. base to top of Navajo brass cap mkd.

T39S R23E
S 35
1/4 ———
S 2
T40S
2007

Bury original stone in mound of stone.

Set a steel fence post north of cor.

Cor. is located on the south edge of a mesa top, with a 300 foot drop to the south.

N. 89°50.7' W., beginning new measurement.

39.987

The cor. of secs. 2, 3, 34, and 35, determined from an embedded mound of stone, 5 ft. base, 2 ft. high. Accept the center of the mound of stone as the best available evidence.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, in supporting mound of stone on a hillside, 5 ft. base, with magnet at base, with Navajo brass cap mkd.

T39S R23E
S 34 | S 35
S 3 | S 2
T40S R23E
2007

Set a steel fence post west of cor.

Cor. is located on a rocky, moderately steep, west facing slope.

S. 89°57.4' W., bet. secs. 3 and 34, on the N. bdy. of the Tp.

40.030

Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with magnet at base, in a mound of stone, 4 ft. base to top of Navajo brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY
T. 40 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T39S R23E
S 34
1/4 ———
S 3
T40S
2007

Set a steel fence post north of cor.

Cor. is located on a moderately steep, south facing slope, east of a drainage, course south.

- 80.060** The cor. of secs. 3, 4, 33, and 34, monumented with an iron post, 2 1/2 ins. diam., set flush in a mound of stone, 5 ft. base, 2 ft. high to top of brass cap (BLM DOI) mkd. as described in the official record of the 1980 resurvey by D.A. Buhler.

Corrective Resurvey of a Portion of the North Boundary,
T. 40 S., R. 23 E., Salt Lake Meridian, Utah

Reestablishment of the Survey executed by A.D. Ferron in 1884, the Dependent Resurveys by H.D. Page and J.M. Lentz in 1899, H.B. Miller and J.C. Thoma in 1912, and the Corrective Resurvey of D.A. Buhler in 1980.

From the cor. of secs. 3, 4, 33, and 34, on the north boundary of Township 40 South, Range 23 East, hereinbefore described.

S. 89°52.3' W., bet. secs. 4 and 33, on the N. bdy. of the Tp.

- 39.568** The 1/4 sec. cor. of sec. 4 only, T. 40 S., R. 23 E., monumented with a galvanized iron post, 2 1/2 ins. diam., firmly set, projecting 14 ins. above ground, mkd. as described in the official record of the 1980 resurvey, with mound of stone, 2 ft. base, 1 ft. high, north of cor. Build mound of stone around pipe, 3 ft. base, to top of brass cap. Remove S33 from cap, add 2007 to cap. Monument previously functioned as the 1/4 sec. cor. of secs. 4 and 33.

Set a steel fence post northwest of cor.

N. 89°59.0' W., beginning new measurement.

- 0.411** Point for the 1/4 sec. cor. of sec. 33 only, T. 39 S., R. 23 E., at proportionate distance.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with magnet at the base, in a collar of stone, 2 1/2 ft. diam., with Navajo brass cap mkd.

CORRECTIVE RESURVEY OF A PORTION OF THE NORTH BOUNDARY
T. 40 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T39S R23E
1/4 S 33

2007

Set a steel fence post north of stainless steel post.

Cor. is located in rolling, sandy hills, with sandstone outcrops.

- 19.881** The W 1/16 sec. cor. of sec. 4 only, T. 40 S., R. 23 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above a mound of stone, 4 ft. base, 2 ft. high, with brass cap (BLM DOI) mkd. as described in the official record of the 1980 resurvey.

Set a steel fence post north of stainless steel post.

- 20.401** Point for the W 1/16 sec. cor. of sec. 33 only, T. 39 S., R. 23 E., at proportionate distance.

Set a brass tablet, 3 1/4 ins. diam., with a 3 1/2 ins. stem, flush with sandstone, in cement bond, into a drill hole on a sandstone outcrop, with brass face (Navajo seal) mkd.

T39S R23E
W 1/16 S 33

2007

Set a steel fence post northeast of stainless steel post.

Cor. is located on a sandstone outcrop, above a small drainage, with little vegetation present.

- 39.764** The cor. of secs. 4 and 5 only, T. 40 S., R. 23 E., monumented with an iron post, 1 in. diam., firmly set in a sandstone outcrop, projecting 5 ins. above ground, with brass cap (US GLO) mkd. as described in the official record of the 1980 resurvey, with a mound of stone, 2 ft. base, 1 ft. high, east of cor.

Set a steel fence post north of cor.

S. 89°56.0' W., bet. secs. 5 and 33, on the N. bdy. of the Tp.

- 0.627** The cor. of secs. 32 and 33 only, T. 39 S., R. 23 E., monumented with an iron post, 2 1/2 ins. diam., in a mound of stone, 4 ft. base, 2 ft. high, to top of iron cap mkd. as described in the official record of the 1980 resurvey.

Set a steel fence post northwest of cor.

CORRECTIVE RESURVEY OF A PORTION OF THE NORTH BOUNDARY
T. 40 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on a moderately steep, west facing slope.

39.865

True point for the 1/4 sec. cor. of sec. 5 only, T. 40 S., R. 23 E., at proportionate distance, located in the bottom of an arroyo, 20 ft. wide, course S. 45° E., impracticable to establish a permanent monument.

From which an offline witness cor. for the 1/4 sec. cor of sec. 5 only, T. 40 S., R. 23 E., bears N. 51°02.4' W., 0.371 chs. dist. The monument used for this offline witness cor. previously functioned as the online witness cor. to the 1/4 sec. cor. of sec. 5 only, monumented with an aluminum post, 2 1/2 ins. diam., firmly set in a mound of stone, 5 ft. base to cap, with aluminum cap (BLM DOI) mkd. as described in the official record of the 1980 resurvey (Note: record iron post and brass cap). Restamp the aluminum cap with a new arrow and the year 2007. Set a steel fence post west of aluminum post. Witness cor. located on the west side of a steep drain, course S. 45° E.

40.612

True point for the 1/4 sec. cor. of sec. 32 only, T. 39 S., R. 23 E., at proportionate distance, located on a very steep and shaley slope, impracticable to establish a permanent monument.

From which an offline witness cor. for the 1/4 sec. cor of sec. 32 only, T. 39 S., R. 23 E., bears N. 60°40.4' W., 0.455 chs. dist. The monument used for this offline witness cor. previously functioned as the 1/4 sec. cor. of sec. 32 only, monumented with an aluminum post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. base to top of aluminum cap (BLM DOI) mkd. as described in the official record of the 1980 resurvey (Note: record iron post and brass cap). Restamp the aluminum cap with a WC, an arrow, and the year 2007. Set a steel fence post southwest of aluminum post. Witness cor. located on the edge of a steep ridge, trending N. 20° W. and S. 20° E.

79.729

The cor. of secs. 5 and 6 only, T. 40 S., R. 23 E., monumented with an iron post, 2 1/2 ins. diam., firmly set flush in a mound of stone, 4 ft. base, 2 ft. high to top of brass cap (BLM DOI) mkd. as described in the official record of the 1980 resurvey (Note: record aluminum post and aluminum cap).

Set a steel fence post south of cor.

Cor. located on steep east facing slope.

N. 89°52.6' W., bet. secs. 6 and 32, on the N. bdy. of the Tp.

0.868

Point for the cor. of secs. 31 and 32 only, T. 39 S., R. 23 E., at intersection with the north boundary of section 6.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, flush with sandstone, in cement bond, into a drill hole on a sandstone

CORRECTIVE RESURVEY OF A PORTION OF THE NORTH BOUNDARY
T. 40 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

outcrop, with a magnet at the base of stem, with brass face (BLM DOI) mkd.

T39S R23E
S 31 | S 32

2007

Set a steel fence post northeast of brass tablet.

Cor. is located on a moderately steep, east sloping sandstone outcrop, at the base of a vertical cliff to the west, approximately 100 feet high.

From this cor., an iron post, 2 1/2 ins. diam., firmly set, in a mound of stone, 4 ft. base, 3 ft. high to top of brass cap mkd. as described in the official record of the 1980 resurvey, bears S. 0°06.7' W., 0.089 chs. dist. This monument previously functioned as the cor. of secs. 31 and 32 only. Amend this monument by adding AM 2007 to the brass cap. From this cor., a juniper, 5 ins. diam., bears N. 11° E., 0.237 chs. dist., mkd. T39S R23E S32 BT (no record of this tree in any official records).

40.293 Point for the 1/4 sec. cor. of sec. 6 only, T. 40 S., R. 23 E., at proportionate distance.

From this point, the 1/4 sec. cor of sec. 6 only, T. 40 S., R. 23 E., as described in the official record of the 1980 resurvey, bears N. 2°25.5' E., 0.271 chs. dist.

This monument was removed and reset at this point for the 1/4 sec. cor. of sec. 6 only, T. 40 S., R. 23 E., with the aluminum post, 30 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, with a magnet at the base, in a mound of stone, 4 ft. base to top of aluminum cap (BLM DOI) remarked

1/4 S 6
T40S R23E
2007

Set a steel fence post northeast of stainless steel post.

Cor. is located near the top of a steep and rocky, southwest facing slope.

40.779 Point for the 1/4 sec. cor. of sec. 31 only, T. 39 S., R. 23 E., at proportionate distance.

From this point, the 1/4 sec. cor of sec. 31 only, T. 39 S., R. 23 E., as described in the official record of the 1980 resurvey, bears N. 57°12.3' W., 0.481 chs. dist.

DEPENDENT RESURVEY OF THE WEST BOUNDARY
(COLORADO GUIDE MERIDIAN)
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

This monument was removed and reset at this point for the 1/4 sec. cor. of sec. 31 only, T. 39 S., R. 23 E., with the iron post, 30 ins. long, 2 1/2 ins. diam., set 21 ins. in the ground, with a magnet at the base, in a mound of stone, 4 ft. base to top of brass cap (BLM DOI) remarked

T39S R23E
1/4 S 31

2007

Set a steel fence post south of stainless steel post.

Cor. is located near the top of a steep and rocky, southwest facing slope.

80.032

The cor. of Tps. 39 and 40 S., Rs. 22 and 23 E., monumented with an aluminum post, 2 1/2 ins. diam., firmly set flush in a mound of stone, 6 ft. base, 2 1/2 ft. high to top of aluminum cap (BLM DOI) mkd. as described in the official record of the 1980 resurvey of the E. bdy. of T. 40 S., R. 22 E. Set a steel fence post east of cor.

Cor. located near head of large drainage, course south.

Dependent Resurvey of the West Boundary
(Colorado Guide Meridian),
T. 39 S., R. 23 E., Salt Lake Meridian, Utah

Reestablishment of the Survey by F. Dickert in 1878, the
Dependent Resurveys by A.P. Hanson in 1907 and
J.C. Thoma, in April, 1912

From the cor. of Tps. 39 and 40 S., Rs. 22 and 23 E., hereinbefore described.

N. 0°01.6' E., bet. secs. 31 and 36, on the W. bdy. of the Tp.

39.895

Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate distance, there is no remaining evidence of the original cor.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with magnet at the base, in a collar of stone, 2 ft. diam., with aluminum cap (BLM DOI) mkd.

DEPENDENT RESURVEY OF THE WEST BOUNDARY
(COLORADO GUIDE MERIDIAN)
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T39S
1/4
R22E | R23E
S 36 | S 31
CGM
2007

Set a steel fence post north of aluminum post.

Cor. is located in rolling, sandy hills, west of McCracken Mesa.

79.790

The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 3 ins. diam., firmly set, projecting 21 ins. above ground, with brass cap mkd. as described in the official record of the 1912 resurvey.

Iron post located in a 6 strand barbed wire fence, extending E and W.

Build a mound of stone 2 ft. base around iron post, to top of brass cap.

Cor. located in broken badland country, with desert vegetation.

N. 0°27.1' E., bet. secs. 25 and 30, on the W. bdy. of the Tp.

40.008

The 1/4 sec. cor. of secs. 25 and 30, determined from an accessory mound of stone, embedded, 2 1/2 ft. diam., 1 ft. high; there is no remaining evidence of the 1912 iron post.

At the corner point (immediately east of the mound of stone)

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with a magnet at the base, in a mound of stone, 2 ft. base to top of Navajo brass cap mkd.

T39S
1/4
R22E | R23E
S 25 | S 30
CGM
2007

Set a steel fence post north of stainless steel post.

Cor. is located in rolling, sandy hills, with scattered desert brush.

N. 0°17.2' W., beginning new measurement.

DEPENDENT RESURVEY OF THE WEST BOUNDARY
(COLORADO GUIDE MERIDIAN)
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.002 Point for the cor. of secs. 19, 24, 25, and 30, at proportionate distance. The iron pipe, mkd. as described in the official record of the 1912 resurvey, was found laying loose on the ground. There was no evidence to determine the location of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, with a magnet at the base, in a mound of stone, 3 ft. base to top of Navajo brass cap mkd.

T39S	
R22E	R23E
S 24	S 19
S 25	S 30
CGM	
2007	

Bury original iron post north of stainless steel post in mound of stone.

Set a steel fence post south of stainless steel post.

From cor., a fence line, 6 strand barbed wire, extending N. 87° E. and S. 87° W., bears South, 0.379 ch. dist.

Cor. is located on a bluff, 30 feet above Recapture Creek.

N. 0°17.2' W., bet. secs. 19 and 24, on the W. bdy. of the Tp.

0.061 Point selected for the witness cor. to the meander cor. for secs. 19 and 24, left bank of Recapture Creek.

Set a brass tablet, 3 1/4 ins. diam., with a 3 1/2 ins. stem, flush with sandstone in cement bond, into drill hole on a sandstone outcrop, with a magnet at base of stem, with brass face (Navajo seal) mkd.

WC	
MC	
↑	
S 24	S 19
R22E	R23E
T39S	
2007	

Witness cor. is located on the south side (left bank) of Recapture Creek, 30 feet above the river bed, on a sandstone bluff.

DEPENDENT RESURVEY OF THE WEST BOUNDARY
(COLORADO GUIDE MERIDIAN)
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- 0.365** True point for the meander cor. for secs. 19 and 24, left bank of Recapture Creek, course S. 81° W., falls at base of vertical cliff, unable to monument.
- 40.002** The 1/4 sec. cor. of secs. 19 and 24, determined from an embedded collar of stone, witnessed by a mound of stone, 2 ft. base 6 ins. high west of collar; there is no remaining evidence of the 1912 iron post.

At the corner point (center of the collar of stone)

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with a magnet at the base, in a collar of stone, 2 1/2 ft. diam., with aluminum cap (BLM DOI) mkd

T39S	
1/4	
R22E	R23E
S 24	S 19
CGM	
2007	

Set a steel fence post north of aluminum post.

Cor. is located on a mesa top, above Horse Canyon.

N. 0°18.9' E., beginning new measurement.

- 39.929** The cor. of secs. 13, 18, 19, and 24, monumented with an iron post, 3 ins. diam., firmly set, projecting 16 ins. above ground, in a collar of stone, 3 ft. diam., with brass cap mkd. as described in the official record of the 1912 resurvey. Witnessed by an embedded mound of stone, 2 1/2 ft. base west of iron post.

Set steel fence post north of iron post.

N. 0°00.7' W., bet. secs. 13 and 18, on the W. bdy. of the Tp.

- 40.099** Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate distance, there is no remaining evidence of the original cor. from the 1912 resurvey. Note: a sandstone, 18 x 11 x 6 ins., mkd. 1/4 on west face, firmly set, projecting 8 ins. above ground, witnessed by a mound of stone, 2 ft. base, west of marked stone, bears S. 56°0' E., 0.850 chs. dist. This stone was set in the 1907 resurvey of the W. bdy., and was superseded by the 1912 resurvey. Bury stone in place and scatter mound.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at the base, in a collar of stone, 2 ft. diam., with aluminum cap (BLM DOI) mkd.

DEPENDENT RESURVEY OF THE WEST BOUNDARY
(COLORADO GUIDE MERIDIAN)
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T39S
1/4
R22E | R23E
S 13 | S 18
CGM
2007

Set a steel fence post north of aluminum post.

Cor. is located in the floodplain of Recapture Creek, at the base of the east bank.

80.198

Point for the cor. of secs. 7, 12, 13 and 18, at proportionate distance, there is no remaining evidence of the original cor. from the 1912 resurvey. Note: a sandstone, 16 x 10 x 8 ins., mkd. with 4 grooves on one face, 2 grooves on opposite face, laying loose in an embedded mound of stone, witnessed by a mound of stone, 2 ft. base, west of marked stone, bears S. 17°22' E., 0.183 chs. dist. This stone was set in the 1907 resurvey of the W. bdy., and was superseded by the 1912 resurvey. Bury stone in place and scatter mound.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, with magnet at the base, in a mound of stone, 3 ft. base to top of aluminum cap (BLM DOI) mkd.

T39S
R22E | R23E
S 12 | S 7
S 13 | S 18
CGM
2007

Set a steel fence post north of aluminum post.

from which

A rebar, 3/8 in. diam., firmly set, flush with ground, bears N. 41°32' W., 0.413 ch. dist. Not of record, not utilized in this resurvey.

Cor. is located in the middle of an open north and south valley.

N. 0°00.7' W., bet. secs. 7 and 12, on the W. bdy. of the Tp.

40.099

The 1/4 sec. cor. of secs. 7 and 12, monumented with a bent iron pipe, 1 in. diam., loosely set, projecting 20 ins. above ground, rusted out at the base, with brass cap mkd. as described in the official record of the 1912 resurvey. Witnessed by an embedded mound of stone, 2 ft. base, 1 ft. high found west of monument.

DEPENDENT RESURVEY OF THE WEST BOUNDARY
(COLORADO GUIDE MERIDIAN)
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, with magnet at the base, in a mound of stone, 4 ft. diam. base to top of aluminum cap (BLM DOI) mkd.

T39S		
1/4		
R22E		R23E
S 12		S 7
CGM		
2007		

Bury the original iron pipe west of the aluminum post in the mound of stone.

Set a steel fence post north of aluminum post.

Cor. is located on a gentle, west facing boulder field, on the east side of Recapture Creek.

N. 0°01.7' E., beginning new measurement.

39.849

Point for the cor. of secs. 1, 6, 7, and 12, at proportionate distance, there is no remaining evidence of the original cor. Significant dirt work has been done in the area.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at the base, in a collar of stone, 2 ft. diam., with aluminum cap (BLM DOI) mkd.

T39S		
R22E		R23E
S 1		S 6
S 12		S 7
CGM		
2007		

Set a steel fence post south of aluminum post (on top of a mound of dirt).

Cor. is located on a flat, bulldozed area, amongst large cobble stones.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 4 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 116+23.3, ELEV 4843.62, 1962, on the south side of Utah State Highway 262, bears N. 73°14.6' E., 18.612 chs. dist.

DEPENDENT RESURVEY OF THE WEST BOUNDARY
(COLORADO GUIDE MERIDIAN)
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 6 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 138+51.9, ELEV 4856.43, 1959, on the south side of Utah State Highway 262, bears N. 88°19.7' E., 24.934 chs. dist.

N. 0°01.7' E., bet. secs. 1 and 6, on the W. bdy. of the Tp.

- 9.252 The centerline of Utah State Highway 262, a paved road, 25 ft. wide, extending N. 79° E. and S. 79° W.
- 39.850 Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate distance, there is no remaining evidence of the original cor. Significant dirt work has been done in the area.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with magnet at the base, in a collar of stone, 2 ft. diam., with aluminum cap (BLM DOI) mkd.

T39S
1/4
R22E | R23E
S 1 | S 6
CGM
2007

Set a steel fence post north of aluminum post.

Cor. is located on top of a fairly level, gravel and dirt hill, where considerable dirt work has been done; probable location for source of road building material for Utah State Highway 262.

- 79.700 The cor. of Tps. 38 and 39 S., Rs. 22 and 23 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1984 resurvey of the S. bdy. of T. 38 S., R. 23 E. witnessed by a mound of stone, 3 ft. base, 2 ft. high south of iron post.

Set a steel fence post south of iron post.

Dependent Resurvey of the North Boundary T. 39 S., R. 23 E.,
Salt Lake Meridian, Utah

Reestablishment of the Survey executed by
D.B. Miller & J.C. Thoma, in 1912

DEPENDENT RESURVEY OF THE NORTH BOUNDARY
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the cor. of Tps. 38 and 39 S., Rs. 23 and 24 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 17 ins. above ground, with brass cap mkd. as described in the official record of the 2003 resurvey of the W. bdy. of T. 39 S., R. 24 E. Set a steel fence post north of cor.

Cor. located east of primary gravel road.

S. 89°57.6' W., bet. secs. 1 and 36, on the N. bdy. of the Tp.

3.631 Centerline of San Juan County Road 408, gravel, 24 ft. wide, extending N. 2° E. and S. 2° W.

39.995 The 1/4 sec. cor. of secs. 1 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. as described in the official record of the 1912 survey of the N. bdy. of T.39 S., R. 23 E.

Set a steel fence post south of iron post.

S. 89°57.4' W., beginning new measurement.

40.021 The cor. of secs. 1, 2, 35, and 36, monumented with an iron post, 3 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. as described in the official record of the 1912 survey of the N. bdy. of T. 39 S., R. 23 E.

Set a steel fence post north of iron post.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 418+00, ELEV 5214.53, 1959, on the north side of Utah State Highway 262, bears S. 07°08.6' E., 37.314 chs. dist.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 408+00, ELEV 5196.53, 1959, on the north side of Utah State Highway 262, bears S. 16°36.8' W., 32.350 chs. dist.

S. 89°58.5' W., bet. secs. 2 and 35, on the N. bdy. of the Tp.

40.044 The 1/4 sec. cor. of secs. 2 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1912 survey of the N. bdy. of T.39 S., R. 23 E.

Build a mound of stone around iron post, 2 ft. base to top of brass cap; set a steel fence post north of iron post.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 89°58.4' W., beginning new measurement.

- 40.027 The cor. of secs. 2, 3, 34, and 35, monumented with an iron post, 3 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. as described in the official record of the 1912 survey of the N. bdy. of T. 39 S., R. 23 E.

Set a steel fence post north of iron post.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 357+00, ELEV 5240.36, 1959, on the north side of Utah State Highway 262, bears S. 12°42.4' W., 0.511 ch. dist.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 349+04.3, ELEV 5248.94, 1959, on the south side of Utah State Highway 262, bears N. 83°12.4' W., 12.490 ch. dist.

S. 89°58.5' W., bet. secs. 3 and 34, on the N. bdy. of the Tp.

- 5.099 The centerline of Utah State Highway 262, a paved road, 25 ft. wide, extending N. 67° W. and S. 67° E.
- 10.332 Centerline of San Juan County Road 411, gravel, 16 ft. wide, extending N. 10° E. and S. 10° W.
- 40.047 The 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. as described in the official record of the 1912 survey of the N. bdy. of T.39 S., R. 23 E., witnessed by a mound of stone, north of cor.

Set a steel fence post north of iron post.

S. 89°53.2' W., beginning new measurement.

- 39.927 The cor. of secs. 3, 4, 33, and 34, determined at the center of an embedded mound of stone, 3 ft. diam. base, 6 ins. high, with the original iron post, 36 ins. long, 3 ins. diam., cement filled, with brass cap mkd. as described in the official record of the 1912 survey of the N. bdy. of T.39 S., R. 23 E., laying loose on top of the mound.

At the corner point (center of mound of stone)

Reset the original iron post, 36 ins. long, 3 ins. diam., 24 ins. in the ground, with magnet at base, in a mound of stone, 2 ft. base to top of brass cap mkd. as described in the official record of the 1912 survey of the N. bdy. of T.39 S., R. 23 E.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post north of iron post.

Cor. is located on fairly level ground, south of Utah State Highway 262.

N. 89°59.7' W., bet. secs. 4 and 33, on the N. bdy. of the Tp.

40.001 The 1/4 sec. cor. of secs. 4 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. as described in the official record of the 1912 survey of the N. bdy. of T.39 S., R. 23 E., witnessed by a mound of stone, 2 ft. diam, 1 1/2 ft. high, north of cor.

Set a steel fence post east of iron post.

S. 89°55.7' W., beginning new measurement.

39.987 Point for the cor. of secs. 4, 5, 32, and 33, at proportionate distance, there is no remaining evidence of the original cor. True point for the proportionate position falls in Utah State Highway 262.

Set a PK nail, 2 ins. long, with a BLM Cadastral Survey brass washer, 1 1/2 ins. diam., flush in the paved surface of Utah State Highway 262.

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground, with magnet at base, in a collar of stone, 1 1/2 ft. diam., for a reference monument, bears S. 71°16' E., 0.722 ch. dist., with brass cap (Navajo seal) mkd. RM T39S R23E S4 47.7 FT TO COR 2007 and an arrow pointing to the true point. Set steel fence post north of reference monument.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground, with magnet at base, in a collar of stone, 1 1/2 ft. diam., for a reference monument, bears S. 20°07' W., 1.460 chs. dist., with brass cap (Navajo seal) mkd. RM T39S R23E S5 96.3 FT TO COR 2007 and an arrow pointing to the true point. Set steel fence post north of reference monument.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 249+71.3, ELEV 4977.72, 1959, on the south side of Utah State Highway 262, bears N. 57°56.9' E., 7.309 chs. dist.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 240+00, ELEV 4944.54, 1959, on the north side of Utah State Highway 262, bears S. 58°55.4' W., 7.889 chs. dist.

S. 89°55.7' W., bet. secs. 5 and 32, on the N. bdy. of the Tp.

0.244 The centerline of Utah State Highway 262, a paved road, 25 ft. wide, extending N. 47° E. and S. 47° W.

38.988 The witness 1/4 sec. cor. of secs. 5 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. as described in the official record of the 1912 survey of the N. bdy. of T.39 S., R. 23 E., witnessed by a mound of stone, 2 ft. base, north of cor.

Build a mound of stone around iron post.

Cor. located in 6 strand barbed wire fence, extending E-W.

S. 89°57.4' W., beginning new measurement.

0.999 True point for the 1/4 sec. cor. of secs. 5 and 32. This point still lies in the middle of Horse Creek, as described in the official record of the 1912 survey of the N. bdy. of T.39 S., R. 23 E. Impracticable to establish monument here.

40.946 The cor. of secs. 5, 6, 31, and 32, monumented with an iron post, 3 ins. diam., loosely set, projecting 15 ins. above ground, in an embedded mound of stone, with brass cap mkd. as described in the official record of the 1912 survey of the N. bdy. of T. 39 S., R. 23 E., with witness mound of stone, 2 ft. diam., 1 ft. high, west of iron post. Reset iron post at original location due to loose condition. Place 60D nail at base of iron post. Rebuild mound of stone around post, 3 ft. base, 2 ft. high to top of brass cap.

Set a steel fence post northwest of iron post.

S. 89°46.4' W., bet. secs. 6 and 31, on the N. bdy. of the Tp.

39.916 The 1/4 sec. cor. of secs. 6 and 31, monumented with the rusted, cement-filled stem of an iron pipe, 8 ins. long, 1 in. diam., in an embedded mound of stone, 2 ft. diam. The rest of the iron post, 1 in. diam., 28 ins. long, with brass cap mkd. as described in the official record of the 1984 resurvey of the S. bdy. of T. 38 S., R. 23 E., was loosely set in the mound of stone.

At the corner point

DEPENDENT RESURVEY OF THE NORTH BOUNDARY
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, with a magnet at base, in a mound of stone, 3 ft. base to top of aluminum cap (BLM DOI) mkd.

T38S R23E
S 31
1/4 ———
S 6
T39S
2007

Place original iron post inside aluminum post.

Cor. is located on east edge of mesa top, at the cor. of fences, 4 strand barbed wire, extending north and west.

N. 89°56.9' W., beginning new measurement.

39.095 The cor. of Tps. 38 and 39 S., Rs. 22 and 23 E., hereinbefore described.

Dependent Resurvey of the Subdivisional Lines
T. 39 S., R. 23 E., Salt Lake Meridian, Utah

Reestablishment of the Survey executed by
D.B. Miller and J.C. Thoma in 1912

From the cor. of secs. 1, 2, 35, and 36, on the N. bdy of Tp. 40 S., R. 23 E., hereinbefore described.

N. 0°05.0' E., bet. secs. 35 and 36.

40.022 Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at the base, with brass cap (Navajo seal) mkd.

T39S R23E
1/4
S 35 | S 36
2007

Set a steel fence post north of stainless steel post.

Cor. is located on a fairly level, grassy plain.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins. above ground, with brass cap mkd. State Road

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Right of Way Marker, STA 708+00, ELEV 5196.26, 1960, on the west side of Utah State Highway 262, bears N. 60°49.2' E., 11.988 chs. dist.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 708+00, ELEV 5194.70, 1960, on the east side of Utah State Highway 262, bears N. 68°13.1' E., 14.505 chs. dist.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 721+00, ELEV 5197.11, 1960, on the east side of Utah State Highway 262, bears S. 36°34.4' E., 17.485 chs. dist.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 1 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 721+00, ELEV 5199.10, 1960, on the west side of Utah State Highway 262, bears S. 28°41.4' E., 15.467 chs. dist.

80.044

The cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 2 ins. diam. above ground, firmly set, projecting 15 ins. above ground, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E.

Build a mound of stone around iron post, 2 ft. base to top of brass cap.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 2 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 684+00, ELEV 5184.75, 1960, on the west side of Utah State Highway 262, bears N. 83°48.4' E., 16.120 chs. dist.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, flush with ground, with brass cap mkd. State Road Right of Way Marker, STA 684+00, ELEV 5182.17, 1960, on the east side of Utah State Highway 262, bears N. 86°10.5' E., 19.068 chs. dist.

From the cor. of secs. 25, 30, 31, and 36, on the E. bdy of the Tp., monumented with an iron post, 3 ins. diam., firmly set, in a mound of stone, 5 ft. base, 2 1/2 ft. high, projecting 10 ins. above mound, with brass cap (GLO) mkd. as described in the official record of the 2003 dependent resurvey of the W. bdy. of T. 39 S., R. 24 E. No accessory mound of stone present.

N. 89°58.6' W., bet. secs. 25 and 36.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.053 Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at the base, with brass cap (Navajo seal) mkd.

T39S R23E
S 25
1/4 ———
S 36
2007

Set a steel fence post north of stainless steel post.

Cor. is located on a gently rolling plain, with sage brush and desert plants.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, flush with ground, with brass cap mkd. State Road Right of Way Marker, STA 684+00, ELEV 5182.17, 1960, on the east side of Utah State Highway 262, bears N. 86°29.7' W., 21.067 chs. dist.

62.773 The centerline of Utah State Highway 262, a paved road, 25 ft. wide, extending N. 9° E. and S. 9° W.

80.106 The cor. of secs. 25, 26, 35, and 36.

N. 0°01.8' E., bet. secs. 25 and 26.

40.015 The 1/4 sec. cor. of secs. 25 and 26, determined at the center of an embedded mound of stone, 5 ft. base, 6 ins. above ground; there is no remaining evidence of the 1912 iron post.

from which the original bearing trees

A juniper stump, 15 ins. diam., bears N. 15°08' E., 1.694 chs. dist., not mkd. (Record: 15 ins. diam., bears N. 20°30' E., 170 lks. dist., mkd. 1/4 S25 BT).

A juniper, 12 ins. diam., bears N. 68°39' W., 0.631 ch. dist., undecipherable scribing (Record: 6 ins. diam., bears N. 65° W., 48 lks. dist., mkd. 1/4 S26 BT).

At the corner point (center of mound of stone)

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, with a magnet at the base, in a mound of stone, 4 ft. base to top of brass cap (Navajo seal) mkd.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T39S R23E
1/4
S 26 | S 25
2007

Set a steel fence post southeast of stainless steel post.

Cor. is located in rolling, desert terrain, on a sandstone bedrock outcrop with little soil. Scattered juniper in area.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 648+00, ELEV 5165.80, 1960, on the west side of Utah State Highway 262, bears N. 57°27.7' E., 28.991 chs. dist.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 2 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 666+00, ELEV 5167.67, 1960, on the west side of Utah State Highway 262, bears S. 60°44.4' E., 23.180 chs. dist.

N. 0°02.1' E., beginning new measurement.

40.062

The cor. of secs. 23, 24, 25, and 26, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E.

Set a steel fence post north of iron post.

Cor. is located on fairly level mesa top, grassy, little vegetation.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins., with brass cap mkd. State Road Right of Way Marker, STA 628+00, ELEV 5169.79, 1960, on the west side of Utah State Highway 262, bears N. 79°25.2' E., 29.592 chs. dist.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins., with brass cap mkd. State Road Right of Way Marker, STA 639+00, ELEV 5164.35, 1960, on the west side of Utah State Highway 262, bears S. 67°29.1' E., 28.711 chs. dist.

From the cor. of secs. 19, 24, 25, and 30, on the E. bdy of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 17 ins. above mound, with brass cap (GLO) mkd. as described in the official record of the 2003 dependent resurvey of the W. bdy. of T. 39 S., R. 24 E.

Set steel fence post north of iron post.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89°54.5' W., bet. secs. 24 and 25.

40.067 Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with magnet at the base, with brass cap (Navajo seal) mkd.

T39S R23E
S 24
1/4 ———
S 25
2007

Set a steel fence post north of stainless steel post.

Cor. is located on a gentle, east sloping plain, in a grassy area that had been burned in the recent past.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 639+00, ELEV 65.79 (incorrectly mkd.), 1960, on the east side of Utah State Highway 262, bears S. 42°47.8' W., 15.534 chs. dist.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 628+00, ELEV 5169.83, 1960, on the east side of Utah State Highway 262, bears N. 57°46.4' W., 9.441 chs. dist.

50.332 The centerline of Utah State Highway 262, a paved road, 25 ft. wide, extending N. 9° E. and S. 9° W.

80.134 The cor. of secs. 23, 24, 25, and 26.

N. 0°00.3' W., bet. secs. 23 and 24.

20.015 Point for the S 1/16 sec. cor. of secs. 23 and 24.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with magnet at the base, in a collar of stone, 3 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
S 1/16
S 23 | S 24
2007

Set a steel fence post north of stainless steel post.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on gentle, northwest sloping terrain, in scattered junipers and sage brush.

- 40.030** The 1/4 sec. cor. of secs. 23 and 24, determined immediately east of an embedded mound of stone, 3 ft. base, 2 ft. high (Record: accessory mound of stone raised west of cor., 2 ft. diam. base, 1 1/2 ft. high; there is no remaining evidence of the 1912 iron post).

At the corner point (east of mound of stone)

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, with a magnet at the base, in a mound of stone, 4 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
1/4
S 23 | S 24
2007

Set a steel fence post north of stainless steel post.

Cor. is located in gently rolling hills, with cactus and sage brush.

N. 0°28.1' E., beginning new measurement.

- 39.318** The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E.

Set a steel fence post north of iron post.

From the cor. of secs. 13, 18, 19, and 24, on the E. bdy of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 14 ins. above mound, with brass cap (GLO) mkd. as described in the official record of the 2003 dependent resurvey of the W. bdy. of T. 39 S., R. 24 E.

Set steel fence post north of iron post.

N. 89°53.6' W., bet. secs. 13 and 24.

- 37.906** The centerline of Utah State Highway 262, a paved road, 25 ft. wide, extending N. 9° E. and S. 9° W.

- 40.068** The 1/4 sec. cor. of secs. 13 and 24, monumented with an iron post, 1 in. diam. above ground, firmly set, projecting 16 ins. above ground, with brass cap mkd. as described in the official

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

record of the 1912 survey of the subdivision of T. 39 S., R. 23 E.

Set a steel fence post north of iron post.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 567+00, ELEV 5187.29, 1960, on the west side of Utah State Highway 262, bears N. 10°50.7' E., 16.999 chs. dist.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 582+00, ELEV 5185.05, 1960, on the west side of Utah State Highway 262, bears S. 3°04.5' W., 5.739 chs. dist.

S. 89°05.2' W., beginning new measurement.

39.843 The cor. of secs. 13, 14, 23, and 24.

N. 0°12.8' W., bet. secs. 13 and 14.

40.382 Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with magnet at the base, with brass cap (Navajo seal) mkd.

T39S R23E
1/4
S 14 | S 13
2007

Set a steel fence post north of stainless steel post.

Cor. is located in gently rolling hills covered with sage brush.

80.764 The cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E. Witnessed by an embedded mound of stone, 4 ft. base, 1 ft. high west of post.

Build a mound of stone around iron post, 3 ft. base to top of brass cap.

Set a steel fence post northeast of iron post.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the cor. of secs. 7, 12, 13, and 18, on the E. bdy of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap (GLO) mkd. as described in the official record of the 2003 dependent resurvey of the W. bdy. of T. 39 S., R. 24 E. Witnessed by a wooden post, 5 ft. high, southeast of cor.

N. 89°48.2' W., bet. secs. 12 and 13.

25.468 The centerline of Utah State Highway 262, a paved road, 25 ft. wide, extending N. 9° E. and S. 9° W.

40.128 Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at the base, with brass cap (Navajo seal) mkd.

T39S R23E
S 12
1/4 ———
S 13
2007

Set a steel fence post north of stainless steel post.

Cor. is located on a gentle, west sloping prairie.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 519+00, ELEV 5190.81, 1960, on the west side of Utah State Highway 262, bears N. 59°25.3' E., 16.749 chs. dist.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins., with brass cap mkd. State Road Right of Way Marker, STA "no stamping", ELEV "no stamping", on the west side of Utah State Highway 262, bears S. 50°54.9' E., 14.963 chs. dist. ROW surveyor forgot to stamp this monument.

80.256 The cor. of secs. 11, 12, 13, and 14.

N. 0°06.5' E., bet. secs. 11 and 12.

40.050 The 1/4 sec. cor. of secs. 11 and 12, determined immediately east of an embedded mound of stone, 4 ft. base, 6 ins. high (Record: accessory mound of stone raised west of cor., 2 ft. diam. base, 1 1/2 ft. high; there is no remaining evidence of the 1912 iron post).

At the corner point (east of mound of stone)

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with a magnet at the base, in a mound of stone, 4 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
1/4
S 11 | S 12
2007

Set a steel fence post north of stainless steel post.

Cor. is located on a gentle northwest slope, with scattered juniper trees.

N. 0°01.9' E., beginning new measurement.

40.024 The cor. of secs. 1, 2, 11, and 12, monumented with an iron post, 2 ins. diam., firmly set, in an embedded collar of stone, 2 ft. diam., projecting 15 ins. above ground, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E. Witnessed by a mound of stone, 2 ft. base, 1 ft. high west of post.

Build a mound of stone around iron post, 2 ft. base to top of brass cap.

Set a steel fence post north of iron post.

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap (Navajo seal) mkd. as described in the official record of the 2003 dependent resurvey of the W. bdy. of T. 39 S., R. 24 E.

N. 89°44.9' W., bet. secs. 1 and 12.

13.125 The centerline of Utah State Highway 262, a paved road, 25 ft. wide, extending N. 9° E. and S. 9° W.

40.134 Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate distance; the original iron post, 1 in. diam., 36 ins. long, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E, was found laying loose in the brush nearby. There was no evidence to determine the original location of the iron post.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with magnet at the base, with brass cap (Navajo seal) mkd.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T39S R23E
S 1
1/4 ———
S 12
2007

Bury original iron post north of cor.

Set a steel fence post north of stainless steel post.

Cor. is located on a gentle, north sloping prairie.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 455+71.5, ELEV 5221.14, 1959, on the south side of Utah State Highway 262, bears N. 42°44.2' E., 23.831 chs. dist.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 477+00, ELEV 5209.55, 1960, on the west side of Utah State Highway 262, bears S. 70°09.2' E., 25.642 chs. dist.

80.268 The cor. of secs. 1, 2, 11, and 12.

N. 0°14.8' E., bet. secs. 1 and 2.

40.053 The 1/4 sec. cor. of secs. 1 and 2, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E.

Build a mound of stone around iron post, 2 ft. base to top of brass cap.

Set a steel fence post north of iron post.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 418+00, ELEV 5209.77, 1959, on the south side of Utah State Highway 262, bears S. 87°11.5' E., 3.666 chs. dist.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 408+00, ELEV 5206.67, 1959, on the south side of Utah State Highway 262, bears N. 60°30.2' W., 11.773 chs. dist.

N. 0°17.1' E., beginning new measurement.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- 3.058** The centerline of Utah State Highway 262, a paved road, 25 ft. wide, extending N. 67° W. and S. 67° E.
- 39.577** The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of Tp., hereinbefore described.

From the cor. of secs. 2, 3, 34, and 35, on the N. bdy of T. 40 S., R. 23 E., hereinbefore described.

N. 0°01.0' W., bet. secs. 34 and 35.

- 39.992** The 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 17 ins. above ground, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E., with accessory mound of stone west of cor. (Record: accessory mound to the north of corner).

Build a mound of stone around iron post, 2 1/2 ft. base to top of brass cap, place magnet next to post at the base of the mound of stone.

Set a steel fence post south of iron post.

Cor. located near north edge of mesa top.

N. 0°01.1' E., beginning new measurement.

- 40.120** The cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 17 ins. above a mound of stone, 2 ft. diam., 1 ft. high, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E.

Rebuild mound of stone around iron post, 4 ft. base to top of brass cap.

Set a steel fence post south of iron post.

From the cor. of secs. 25, 26, 35, and 36.

N. 89°56.9' W., bet. secs. 26 and 35.

- 40.017** The 1/4 sec. cor. of secs. 26 and 35, monumented with the rusted, cement-filled stem of an iron pipe, 6 ins. long, 2 ins. diam., in a mound of stone, 2 ft. base, 1 ft. high, with the rest of the iron post and brass cap, mkd. as described in the official record of the 1912 survey of the subdivision of

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T. 39 S., R. 23 E, loosely set in the mound of stone. Witness by a mound of stone, 3 ft. base, 2 ft. high north of cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, with magnet at base, in a mound of stone, 4 ft. base to top of brass cap mkd.

T39S R23E
S 26
1/4 ———
S 35
2007

Place original iron post inside stainless steel post.

Set a steel fence post north of stainless steel post.

Cor. is located in eroded, badlands country with numerous washes, near the base of a steep mesa to the east.

N. 89°53.7' W., beginning new measurement.

39.925 The cor. of secs. 26, 27, 34, and 35.

N. 0°01.9' E., bet. secs. 26 and 27.

40.021 Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance. Note: the 1912 survey was unable to set a corner at this point, and a witness cor. was set 1.0 chain north; there is no remaining evidence of the witness cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, with magnet at the base, in a mound of stone, 5 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
1/4
S 27 | S 26
2007

Set a steel fence post northeast of stainless steel post.

Cor. is located on the northeast bank of a drainage, 10 ft. wide, course S. 70° E., 10 ft. wide.

80.042 The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2 ins. diam., loosely set, projecting 20 ins. above a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. as

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E.

Rebuild mound of stone around iron post, 3 ft. base to top of brass cap, add magnet at the base of the iron post.

Set a steel fence post east of iron post.

From the cor. of secs. 23, 24, 25, and 26.

N. 89°55.4' W., bet. secs. 23 and 26.

19.966 Point for the E 1/16 sec. cor. of secs. 23 and 26.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, with magnet at the base, in a mound of stone, 4 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
S 23
E 1/16 ———
S 26
2007

Set a steel fence post southeast of stainless steel post.

Cor. is located on a mesa top, with scattered junipers and desert brush.

39.932 The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E.

Build a mound of stone around iron post, 4 ft. base to top of brass cap.

Set a steel fence post south of iron post.

Cor. falls on southwest sloping terrain south of sandstone cliffs, 30 ft. high.

N. 89°58.1' W., beginning new measurement.

39.996 The cor. of secs. 22, 23, 26, and 27.

N. 0°07.5' E., bet. secs. 22 and 23.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.030

Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with magnet at the base, in a mound of stone, 3 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
1/4
S 22 | S 23
2007

Set a steel fence post north of stainless steel post.

Cor. is located on a mesa top, with minimal vegetation.

80.060

The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E, witnessed by a mound of stone, 4 ft. base, 2 1/2 ft. high, west of post.

from which

A juniper stump, 10 ins. diam., no mkg., bears S. 35°41' W., 0.166 ch. dist. (Record: cedar, 10 ins. diam., bears S. 45° W., 15 lks. dist., mkd. T39S R23E S22 BT).

Set a steel fence post west of iron post.

Cor. located beneath large sandstone cliff.

From the cor. of secs. 13, 14, 23, and 24.

N. 88°51.9' W., bet. secs. 14 and 23.

40.238

The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above a mound of stone, 2 1/2 ft. base, 20 ins. high, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E.

Rebuild a mound of stone around iron post.

Set a steel fence post north of iron post.

S. 89°59.2' W., beginning new measurement.

39.825

The cor. of secs. 14, 15, 22, and 23.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0°02.3' E., bet. secs. 14 and 15.

40.024

The 1/4 sec. cor. of secs. 14 and 15, determined from an accessory mound of stone, embedded, 3 ft. diam., 6 ins. high; there is no remaining evidence of the 1912 iron post.

At the corner point (immediately east of the mound of stone)

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 3 ins. in the ground to bedrock, with a magnet at the base, in a mound of stone, 4 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
1/4
S 15 | S 14
2007

from which

A juniper, 8 ins. diam., bears N. 24° W., 0.078 ch. dist., mkd. X BT (scribe 4 ft. above ground).

Cor. is located on a sandstone outcrop, with a gentle east slope.

N. 0°03.0' W., beginning new measurement.

40.042

The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E.

from which

A juniper, 9 ins. diam., no visible marks (probable healed over blaze), bears S. 14° W., 0.568 ch. dist. (Record: cedar, 6 ins. diam., bears S. 14°30' W., 56 lks. dist., mkd. T39S R23E S15 BT).

Build a mound of stone around iron post, 2 ft. base to top of brass cap.

Set a steel fence post north of iron post.

Cor. located on rolling desert terrain, with scattered junipers and sage.

From the cor. of secs. 11, 12, 13, and 14.

N. 89°52.9' W., bet. secs. 11 and 14.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

39.775 The 1/4 sec. cor. of secs. 11 and 14, determined from an accessory mound of stone, embedded, 3 ft. diam., 6 ins. high; there is no remaining evidence of the 1912 iron post.

At the corner point (immediately south of the mound of stone)

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with a magnet at the base, in a mound of stone, 5 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
S 11
1/4 ———
S 14
2007

Set a steel fence post northwest of stainless steel post.

Cor. is located on the west side of a drainage, on a southeast sloping bench.

N. 89°59.3' W., beginning new measurement.

39.972 The cor. of secs. 10, 11, 14, and 15.

N. 0°00.4' W., bet. secs. 10 and 11.

40.013 The 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E.

Set a steel fence post north of iron post.

Cor. located on gentle south sloping terrain.

N. 0°01.0' W., beginning new measurement.

40.050 The cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E.

Set a steel fence post northwest of iron post.

Cor. located on level terrain covered with sage brush.

From the cor. of secs. 1, 2, 11, and 12.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89°54.5' W., bet. secs. 2 and 11.

39.868 The 1/4 sec. cor. of secs. 2 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E.

Set a steel fence post north of iron post.

Cor. located on gently rolling prairie with sage brush and grass.

N. 89°58.6' W., beginning new measurement.

39.977 The cor. of secs. 2, 3, 10, and 11.

N. 0°05.6' E., bet. secs. 2 and 3.

39.937 Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with magnet at the base, with brass cap (Navajo seal) mkd.

T39S R23E
1/4
S 3 | S 2
2007

Set a steel fence post north of stainless steel post.

Cor. is located on a gently rolling plain, with sagebrush and desert grasses.

77.326 The centerline of Utah State Highway 262, a paved road, 25 ft. wide, extending N. 67° W. and S. 67° E.

79.514 The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of Tp., hereinbefore described.

From the cor. of secs. 3, 4, 33, and 34, on the N. bdy of Tp. 40 S., R. 23 E., hereinbefore described.

N. 0°03.2' W., bet. secs. 33 and 34.

40.032 The 1/4 sec. cor. of secs. 33 and 34, determined from an accessory mound of stone, embedded, 2 ft. base, 6 ins. high; there is no remaining evidence of the 1912 iron post.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point (immediately east of the mound of stone)

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with a magnet at the base, in a mound of stone, 2 1/2 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
1/4
S 33 | S 34
2007

Set a steel fence post north of stainless steel post.

Cor. is located in eroded terrain, in McCracken Canyon.

N. 0°03.1' W., beginning new measurement.

39.940

The cor. of secs. 27, 28, 33, and 34, determined from an accessory mound of stone, embedded, 4 ft. base, 6 ins. high; there is no remaining evidence of the 1912 iron post.

At the corner point (immediately east of the mound of stone)

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, with a magnet at the base, in a mound of stone, 3 ft. base to top of brass cap (Navajo seal) mkd.

T 39 S R 23 E
S 28 | S 27
S 33 | S 34
2007

Set a steel fence post north of stainless steel post.

Cor. is located in eroded badlands, above McCracken Canyon.

From the cor. of secs. 26, 27, 34, and 35.

S. 89°51.4' W., bet. secs. 27 and 34.

40.060

Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, with magnet at the base, in a mound of stone, 4 ft. base to top of brass cap (Navajo seal) mkd.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T39S R23E
S 27
1/4 ———
S 34
2007

Set a steel fence post south of stainless steel post.

Cor. is located on the northwest edge of a primitive road, in rocky terrain.

80.120 The cor. of secs. 27, 28, 33, and 34.

N. 0°04.9' W., bet. secs. 27 and 28.

40.062 The 1/4 sec. cor. of secs. 27 and 28, determined from an accessory mound of stone, embedded, 3 ft. base, 1 ft. high; there is no remaining evidence of the 1912 iron post.

At the corner point (immediately east of the mound of stone)

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, with a magnet at the base, in a mound of stone, 3 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
1/4
S 28 | S 27
2007

Set a steel fence post north of stainless steel post.

Cor. is located on a fairly level mesa top.

N. 0°00.6' E., beginning new measurement.

40.040 The cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 2 ins. diam., 27 ins. long, loosely set in a mound of stone, 4 ft. base, 2 ft. high, rusted out 9 ins. above the flanges, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E. Witnessed by an embedded mound of stone, 2 ft. base, 1 ft. high, west of monument.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, with a magnet at the base, in a mound of stone, 2 1/2 ft. base to top of brass cap (Navajo seal) mkd.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T 39 S	R 23 E
S 21	S 22
S 28	S 27
2007	

Place original iron post and cap inside stainless steel post.

Cor. is located in gently rolling hills, in an open valley.

From the cor. of secs. 22, 23, 26, and 27.

S. 89°53.8' W., bet. secs. 22 and 27.

40.064

The 1/4 sec. cor. of secs. 22 and 27, determined from an accessory mound of stone, embedded, 4 ft. base, 3 ft. high; there is no remaining evidence of the 1912 iron post.

At the corner point (immediately south of the mound of stone)

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, with a magnet at the base, in a mound of stone, 3 ft. base to top of brass cap (Navajo seal) mkd.

T39S	R23E
	S 22
	1/4 ———
	S 27
2007	

Set a steel fence post north of stainless steel post.

Cor. is located in rolling hills with rocky ground.

S. 89°54.2' W., beginning new measurement.

40.136

The cor. of secs. 21, 22, 27, and 28.

N. 0°00.4' W., bet. secs. 21 and 22.

40.007

The 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 1 in. diam., loosely set in a mound of stone, 2 ft. base, 1 1/2 ft. high, projecting 16 ins. above mound, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E.

Reset iron post 15 ins. in the ground, with a magnet at base, rebuild mound of stone, 3 ft. base to top of brass cap.

Set a steel fence post west of iron post.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0°07.9' E., beginning new measurement.

40.037 Point for the cor. of secs. 15, 16, 21, and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set a brass tablet, 3 1/4 ins. diam., with a 3 1/2 ins. stem, flush with sandstone in cement bond, into drill hole on a sandstone outcrop, with a magnet at base of stem, with brass face (Navajo seal) mkd.

T39S R23E	
S 16	S 15
S 21	S 22
2007	

from which a bearing tree (not of record)

A juniper, 20 ins. diam., bears N. 75°34' W., 0.454 ch. dist., mkd. S16. Re-mark tree X BT.

Cor. located on a sandstone outcrop, gently sloping east, with scattered juniper trees.

From the cor. of secs. 14, 15, 22, and 23.

N. 89°55.6' W., bet. secs. 15 and 22.

40.086 The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above an embedded collar of stone, 3 ft. diam., with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E.

Rebuild mound of stone around post, 3 ft. base, 1 ft. high.

Set a steel fence post northwest of iron post.

S. 89°42.3' W., beginning new measurement.

40.187 The cor. of secs. 15, 16, 21, and 22.

N. 0°04.4' W., bet. secs. 15 and 16.

31.697 Centerline of San Juan County Road 411, gravel, 16 ft. wide, extending N. 28° E. and S. 28° W.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.036

Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with magnet at the base, with brass cap (Navajo seal) mkd.

T39S	R23E
1/4	
S 16	S 15
2007	

Set a steel fence post north of stainless steel post.

Cor. is located on a gently rolling prairie, with desert grasses.

80.072

The cor. of secs. 9, 10, 15, and 16, determined at the center of a mound of stone, embedded, 3 ft. base, 1 ft. high; there is no remaining evidence of the 1912 iron post. Witnessed by a mound of stone, 2 ft. base, 1 ft. high, west of cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, with a magnet at the base, in a mound of stone, 4 ft. base to top of brass cap (Navajo seal) mkd.

T39S	R23E
S 9	S 10
S 16	S 15
2007	

Set a steel fence post west of stainless steel post, in a mound of stone, 1 1/2 ft. base, 1 ft. high.

Cor. is located on a gentle, northwest slope.

From the cor. of secs. 10, 11, 14, and 15.

S. 89°52.1' W., bet. secs. 10 and 15.

40.216

The 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E.

S. 89°55.1' W., beginning new measurement.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

18.915 Centerline of San Juan County Road 411, gravel, 16 ft. wide, extending N. 9° E. and S. 9° W.

40.136 The cor. of secs. 9, 10, 15, and 16.

N. 0°02.9' W., bet. secs. 9 and 10.

39.951 The 1/4 sec. cor. of secs. 9 and 10, determined at the center of a mound of stone, embedded, 3 ft. base, 6 ins. high; there is no remaining evidence of the 1912 iron post. Witnessed by a mound of stone, 3 ft. base, 6 ins. high, west of cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 3 ins. in the ground to bedrock, with a magnet at the base, in a mound of stone, 3 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
1/4
S 9 | S 10
2007

from which

A juniper, 8 ins. diam., bears N. 46° W., 0.102 ch. dist., mkd. X BT.

Set a steel fence post north of stainless steel post.

Cor. is located on a sandstone outcrop, gently sloping west, with scattered junipers.

N. 0°00.3' E., beginning new measurement.

39.947 The cor. of secs. 3, 4, 9, and 10, monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above ground, in a scattered collar of stone, 6 ft. diam., with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E.

Build a mound of stone around iron post, 3 ft. base, 6 ins. high.

Set a steel fence post north of iron post.

Cor. located in level grassy prairie.

From the cor. of secs. 2, 3, 10, and 11.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 89°46.6' W., bet. secs. 3 and 10.

31.832 Centerline of San Juan County Road 411, gravel, 16 ft. wide, extending N. 23° E. and S. 23° W.

40.175 Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with magnet at the base, with brass cap (Navajo seal) mkd.

T39S R23E
S 3
1/4 ———
S 10
2007

Set a steel fence post north of stainless steel post.

Cor. is located on a rolling, grassy prairie, with scattered juniper bushes.

80.350 The cor. of secs. 3, 4, 9, and 10.

N. 0°17.0' E., bet. secs. 3 and 4.

39.887 The 1/4 sec. cor. of secs. 3 and 4, determined at the center of a mound of stone, embedded, 3 ft. base, 6 ins. high; there is no remaining evidence of the 1912 iron post.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with a magnet at the base, in a mound of stone, 3 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
1/4
S 4 | S 3
2007

Set a steel fence post north of stainless steel post.

Cor. is rolling, sandy hills, with scattered junipers.

N. 0°25.3' E., beginning new measurement.

39.846 The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of Tp., hereinbefore described.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the cor. of secs. 32 and 33 only, on the N. bdy of
Tp. 40 S., R. 23 E., hereinbefore described.

N. 0°05.7' E., bet. secs. 32 and 33.

19.966 Point for the S 1/16 sec. cor. of secs. 32 and 33. Not
monumented.

39.932 The 1/4 sec. cor. of secs. 32 and 33, monumented with the
rusted, cement-filled stem of an iron pipe, 7 ins. long, 1 in.
diam. The rest of the iron post, 1 in. diam., 29 ins. long, with
brass cap mkd. as described in the official record of the 1912
survey of the subdivision of T. 39 S., R. 23 E., was laying
loose on the hillside below.

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in
the ground, with a magnet at base, in a mound of stone, 4 ft.
base, to top of aluminum cap (BLM DOI) mkd.

T39S R23E
1/4
S 32 | S 33
2007

Bury original iron post west of cor.

Set a steel fence post north of aluminum post.

Cor. is located on a moderately steep, west facing hillside.

N. 0°00.3' W., beginning new measurement.

39.939 The cor. of secs. 28, 29, 32, and 33, monumented with an iron
post, 2 ins. diam., firmly set, projecting 16 ins. above ground,
in a collar of stone, 2 ft. diam., with brass cap mkd. as
described in the official record of the 1912 survey of the
subdivision of T. 39 S., R. 23 E.

Rebuild mound of stone around iron post, 3 ft. base to top of
brass cap.

Set a steel fence post north of iron post.

Cor. located in a fence, 6 strand barbed wire, extending
N. 80° W. and S. 80° E.

From the cor. of secs. 27, 28, 33, and 34.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 89°59.7' W., bet. secs. 28 and 33.

- 40.017 The 1/4 sec. cor. of secs. 28 and 33, monumented with an iron post, 1 in. diam., loosely set in a mound of stone, 3 ft. base, 1 1/2 ft. high, projecting 14 ins. above mound, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E.

Straighten iron post, place magnet at base, rebuild mound of stone, 5 ft. base, 3 ft. high to top of brass cap.

Set a steel fence post southeast of iron post.

S. 89°44.5' W., beginning new measurement.

- 39.791 The cor. of secs. 28, 29, 32, and 33.

N. 0°02.3' W., bet. secs. 28 and 29.

- 40.026 Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with magnet at the base, in a mound of stone, 3 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
1/4
S 29 | S 28
2007

Set a steel fence post north of stainless steel post.

Cor. is located on a rocky, northeast sloping hillside.

- 80.052 The cor. of secs. 20, 21, 28, and 29, monumented with the rusted, cement-filled stem of an iron pipe, 6 ins. long, 2 ins. diam., in a mound of stone, 3 ft. base, 1 ft. high. The remainder of the iron post, 2 in. diam., 18 ins. long, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E., was loosely set in the mound of stone. Witnessed by a mound of stone, 2 ft. base, 1 ft. high, west of cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, with a magnet at the base, in a mound of stone, 5 ft. base to top of brass cap (Navajo seal) mkd.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T39S	R23E
S 20	S 21
S 29	S 28
2007	

from which

A bearing object, + B0, marked on a piece of sandstone which flaked off of a vertical face, was found face down in the dirt. The original location of this bearing object was determined to bear N. 60° E., 0.121 ch. dist. (Record: N. 34° E., 18 lks. dist.) This bearing object is no longer functional.

Bury original iron post northwest of stainless steel post.

Set a steel fence post north of stainless steel post.

Cor. is located at the base of a sandstone mesa to the northwest.

From the cor. of secs. 21, 22, 27, and 28.

S. 89°40.3' W., bet. secs. 21 and 28.

39.885

The 1/4 sec. cor. of secs. 21 and 28, determined at the center of a mound of stone, embedded, 3 ft. base, 1 ft. high; there is no remaining evidence of the 1912 iron post. Witnessed by a mound of stone, 2 ft. base, 1 ft. high, north of cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 11 ins. in the ground to bedrock, with a magnet at the base, in a mound of stone, 4 ft. base to top of brass cap (Navajo seal) mkd.

T39S	R23E
	S 21
	1/4 ———
	S 28
2007	

Set a steel fence post south of stainless steel post.

Cor. is located in eroded badlands, no vegetation.

S. 89°59.8' W., beginning new measurement.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

39.910 The cor. of secs. 20, 21, 28, and 29.

N. 0°00.8' W., bet. secs. 20 and 21.

18.972 Centerline of San Juan County Road 411, gravel, 16 ft. wide, extending N. 49° E. and S. 49° W.

39.949 Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at the base, with brass cap (Navajo seal) mkd.

T39S R23E
1/4
S 20 | S 21
2007

Set a steel fence post north of stainless steel post.

Cor. is located on a level mesa top.

79.898 The cor. of secs. 16, 17, 20, and 21, monumented with an iron post, 2 ins. diam., firmly set, projecting 17 ins. above ground, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E., witnessed by a mound of stone, 3 ft. base, 6 ins. high, west of cor.

Build a mound of stone around iron post, 3 ft. base to top of brass cap.

Set a steel fence post north of iron post.

Cor. is located on a rocky, southwest sloping hill.

From the cor. of secs. 15, 16, 21, and 22.

S. 89°43.8' W., bet. secs. 16 and 21.

38.792 Centerline of San Juan County Road 411, gravel, 16 ft. wide, extending N. 25° E. and S. 25° W.

39.942 Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at the base, with brass cap (Navajo seal) mkd.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T39S R23E
S 16
1/4 ———
S 21
2007

Set a steel fence post north of stainless steel post.

Cor. is located on a gentle, south sloping mesa top.

79.884 The cor. of secs. 16, 17, 20, and 21.

N. 0°07.2' W., bet. secs. 16 and 17.

39.994 The 1/4 sec. cor. of secs. 16 and 17, determined at the center of a collar of stone, embedded, 2 ft. diam., 6 ins. high; there is no remaining evidence of the 1912 iron post or cross marked on sandstone face. Witnessed by a mound of stone, 2 ft. base, 2 ft. high, west of cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., on bedrock slab, with a magnet at the base, in a mound of stone, 3 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
1/4
S 17 | S 16
2007

from which

A bearing object bears N. 17°49' E., 0.158 ch. dist., mkd. BXO, on a moderate slope sandstone outcropping.

Set a steel fence post southwest of stainless steel post.

Cor. is located on an exposed sandstone face, fairly level, at the edge of a mesa, 20 ft. above a wash below, course N. 10° W.

N. 0°06.9' E., beginning new measurement.

40.176 The cor. of secs. 8, 9, 16, and 17, determined from an accessory mound of stone, embedded, 3 ft. base, 1 ft. high; there is no remaining evidence of the 1912 iron post.

At the corner point (immediately east of the mound of stone)

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, with a magnet at the base, in a

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

mound of stone, 3 ft. base to top of brass cap (Navajo seal) mkd.

T39S	R23E
S 8	S 9
S 17	S 16
2007	

Set a steel fence post east of stainless steel post, in a mound of stone, 1 1/2 ft. base, 1 ft. high.

Cor. is located in broken ground, with no vegetation.

From the cor. of secs. 9, 10, 15, and 16.

S. 89°47.9' W., bet. secs. 9 and 16.

39.884

Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with magnet at the base, in a collar of stone, 2 ft. base to top of brass cap (Navajo seal) mkd.

T39S	R23E
	S 9
1/4	—
	S 16
2007	

Set a steel fence post north of stainless steel post.

Cor. is located in a wide drainage, course N. 40° W., 30 ft. wide.

79.768

The cor. of secs. 8, 9, 16, and 17.

N. 0°04.2' W., bet. secs. 8 and 9.

40.065

The 1/4 sec. cor. of secs. 8 and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E. Cap oriented southwest, witnessed by a mound of stone west of cor., 3 ft. base, 1 ft. high.

Build a mound of stone around post, 3 ft. base to top of brass cap.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0°02.0' E., beginning new measurement.

40.013 Point for the cor. of secs. 4, 5, 8, and 9, at proportionate distance; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with a magnet at the base, with brass cap (Navajo seal) mkd.

T39S	R23E
S 5	S 4
S 8	S 9
2007	

from which

A juniper, 7 ins. diam., bears S. 23° W., 0.052 ch. dist., mkd. X BT.

Set a steel fence post east of stainless steel post.

Cor. located on a steep and rocky slope, facing southeast.

From the cor. of secs. 3, 4, 9, and 10.

S. 89°54.9' W., bet. secs. 4 and 9.

39.790 The 1/4 sec. cor. of secs. 4 and 9, determined at the center of a collar of stone, embedded, 3 ft. diam.; there is no remaining evidence of the 1912 iron post. Witnessed by a mound of stone, 2 ft. base, 1 ft. high, north of cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. in the ground to bedrock, with a magnet at the base, in a mound of stone, 3 ft. base to top of brass cap (Navajo seal) mkd.

T39S	R23E
	S 4
1/4	S 9
2007	

Set a steel fence post north of stainless steel post.

Cor. is located in rolling hills, with desert brush.

S. 89°56.3' W., beginning new measurement.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

39.959 The cor. of secs. 4, 5, 8, and 9.

N. 0°02.5' W., bet. secs. 4 and 5.

40.013 The 1/4 sec. cor. of secs. 4 and 5, determined from an accessory mound of stone, 2 1/2 ft. base, 2 1/2 ft. high; there is no remaining evidence of the 1912 iron post.

At the corner point (immediately east of the mound of stone)

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, with a magnet at the base, in a mound of stone, 3 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
1/4
S 5 | S 4
2007

Set a steel fence post west of stainless steel post, in a mound of stone, 3 ft. base, 2 ft. high.

Cor. is at the foot of a rocky, moderate west slope.

N. 0°22.8' E., beginning new measurement.

39.775 The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of Tp., hereinbefore described.

From the cor. of secs. 31 and 32 only, on the N. bdy of Tp. 40 S., R. 23 E., hereinbefore described.

N. 0°06.7' E., bet. secs. 31 and 32.

39.929 The 1/4 sec. cor. of secs. 31 and 32, determined at the center of a mound of stone, embedded, 3 ft. base, 6 ins. high; the 1912 iron post was found laying loose nearby. Witnessed by a mound of stone, 2 ft. base, 1 ft. high, west of cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, with a magnet at the base, in a mound of stone, 2 1/2 ft. base to top of brass cap (Navajo seal) mkd.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T39S R23E
1/4
S 31 | S 32
2007

Bury original iron post south of cor.

Set a steel fence post south of stainless steel post.

Cor. is located on the west edge of McCracken Mesa.

N. 0°01.3' W., beginning new measurement.

39.960 The cor. of secs. 29, 30, 31, and 32, determined from an accessory mound of stone, embedded, 4 ft. base, 6 ins. high; there is no remaining evidence of the 1912 iron post.

At the corner point (immediately east of the mound of stone)

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground, with a magnet at the base, in a mound of stone, 3 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
S 30 | S 29
S 31 | S 32
2007

The accessory mound of stones was used to build the mound around the stainless steel post.

Set a steel fence post west of stainless steel post.

Cor. is located in badlands, northwest of oilfield production pad.

From the cor. of secs. 28, 29, 32, and 33.

S. 89°57.2' W., bet. secs. 29 and 32.

30.582 Centerline of San Juan County Road 411, gravel, 16 ft. wide, extending N. 33° E. and S. 33° W.

39.853 The 1/4 sec. cor. of secs. 29 and 32, determined at the center of a mound of stone, embedded, 4 ft. base, 6 ins. high; there was no remains of 1912 iron post. Witnessed by a scattered mound of stone north of cor.

At the corner point

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground to bedrock, with a magnet at the base, in a mound of stone, 4 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
S 29
1/4 ———
S 32
2007

Cor. is located near the west edge of McCracken Mesa.

S. 89°56.9' W., beginning new measurement.

40.103 The cor. of secs. 29, 30, 31, and 32.

N. 89°56.9' W., bet. secs. 30 and 31.

39.971 True point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner. Point falls in a highly eroded area subject to future erosion; poor location to monument.

40.279 Point selected for on-line witness 1/4 sec. cor. of secs. 30 and 31.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with magnet at base, in a mound of stone, 3 ft. base to top of brass cap (Navajo seal) mkd.

WC
T39S R23E
S 30
1/4 ———>
S 31
2007

Set a steel fence post west of stainless steel post.

Witness cor. located in eroded badlands, at the base of a 15 ft. high bank of clay and mudstone.

79.173 The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of Tp., hereinbefore described.

From the cor. of secs. 29, 30, 31, and 32.

N. 0°06.5' W., bet. secs. 29 and 30.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

39.950 Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with magnet at the base, in a collar of stone, 4 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
1/4
S 30 | S 29
2007

Set a steel fence post north of stainless steel post.

Cor. is located on the southeast side of a drainage, 40 ft. wide, course S. 50° W.

79.900 True point for the cor. of secs. 19, 20, 29, and 30, at proportionate distance; there is no remaining evidence of the original corner. Point falls in a moderately steep boulder field, subject to future movement.

From the cor. of secs. 20, 21, 28, and 29.

S. 89°50.5' W., bet. secs. 20 and 29.

18.871 Centerline of San Juan County Road 411, gravel, 16 ft. wide, extending N. 33° E. and S. 33° W.

40.019 Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with magnet at the base, in a mound of stone, 3 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
S 20
1/4 ———
S 29
2007

Set a steel fence post west of stainless steel post.

Cor. is located on a moderately steep, northwest facing hillside.

80.038 True point for the cor. of secs. 19, 20, 29, and 30.

N. 89°44.5' W., bet. secs. 19 and 30.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

39.924 The 1/4 sec. cor. of secs. 19 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, in a collar of stone, 2 ft. diam., with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E.

Straighten iron post, rebuild mound of stone around iron post, 3 ft. diam. to cap.

Set a steel fence post north of iron post.

S. 89°59.9' W., beginning new measurement.

38.968 The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of Tp., hereinbefore described.

From the cor. of secs. 19, 20, 29, and 30.

N. 0°02.4' E., bet. secs. 19 and 20.

0.314 Point selected for on-line witness cor. of secs. 19, 20, 29, and 30. Unable to monument at true point. Found iron post laying loose nearby; impossible to determine original location of iron post.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at base, in a mound of stone, 4 ft. base to top of brass cap (Navajo seal) mkd.

WC	
T39S	R23E
S 19	S 20
S 30	S 29
2007	

Bury original iron post west of cor.

Set a steel fence post north of stainless steel post.

Witness cor. is located on a moderately steep, rocky, west facing hillside, with little vegetation.

39.950 The 1/4 sec. cor. of secs. 19 and 20, monumented with an iron post, 1 in. diam., loosely set in a mound of stone, 3 ft. base, 2 ft. high, projecting 6 ins. above mound, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E. Witnessed by a mound of stone, 3 ft. base, 2 ft. high, west of cor.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Straighten iron post, place magnet at base, rebuild mound of stone, 3 ft. base, 2 ft. high to top of brass cap.

Set a steel fence post west of iron post, in accessory mound of stone.

N. 0°01.9' W., beginning new measurement.

40.001 Point for the cor. of secs. 17, 18, 19, and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with a magnet at the base, in a collar of stone, 3 ft. base to top of brass cap (Navajo seal) mkd.

T39S	R23E
S 18	S 17
S 19	S 20
2007	

Set a steel fence post north of stainless steel post.

Cor. is located on the northeast side of a shallow wash, 15 ft. wide, course N. 20° W.

From the cor. of secs. 16, 17, 20, and 21.

S. 89°46.2' W., bet. secs. 17 and 20.

39.989 The 1/4 sec. cor. of secs. 17 and 20, monumented with the rusted flanges from an iron post, in an embedded mound of stone, 4 ft. base, 1 ft. high. No remains of the rest of the 1912 iron post.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, with magnet at the base, in a mound of stone, 4 ft. base to top of brass cap (Navajo seal) mkd.

T39S	R23E
	S 17
1/4	—
	S 20
2007	

from which the original bearing trees

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

A juniper, 20 ins. diam., bears N. 74°25' E., 1.159 chs. dist., mkd. 1/4 S17 BT (Record: 8 ins. diam., N. 74° E., 117 lks.).

A juniper, 18 ins. diam., bears S. 35°43' W., 1.181 chs. dist., mkd. 1/4 S20 BT (Record: 14 ins. diam., S. 45° W., 120 lks.).

Bury rusted flanges at base of stainless steel post.

Set a steel fence post east of stainless steel post.

Cor. is located near the south edge of a mesa top, fairly flat, with scattered juniper trees.

S. 89°59.3' W., beginning new measurement.

40.011 The cor. of secs. 17, 18, 19, and 20.

S. 89°57.0' W., bet. secs. 18 and 19.

40.051 The 1/4 sec. cor. of secs. 18 and 19, determined at the center of a mound of stone, embedded, 4 ft. base, 1 ft. high; there was no remains of 1912 iron post. Witnessed by a mound of stone, 2 ft. base, embedded, north of cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, with a magnet at the base, in a mound of stone, 4 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
S 18
1/4 ———
S 19
2007

Set a steel fence post north of stainless steel post.

Cor. is located on a fairly level bench, no vegetation.


N. 89°42.9' W., beginning new measurement.

25.659 Point selected for the witness cor. to the meander cor. for secs. 18 and 19, left bank of Recapture Creek.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with magnet at base, in a collar of stone, 2 ft. base to top of brass cap (Navajo seal) mkd.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS



Set a steel fence post north of stainless steel post.

Witness cor. is located on the left bank of Recapture Creek, on a level bank, 15 ft. above creek.

26.114 True point for the meander cor. for secs. 18 and 19, left bank of Recapture Creek. Unable to monument due to erosion of steep bank.

38.812 The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of Tp., hereinbefore described.

From the cor. of secs. 17, 18, 19, and 20.

N. 0°04.5' E., bet. secs. 17 and 18.

40.001 The 1/4 sec. cor. of secs. 17 and 18, determined at the center of a mound of stone, embedded, 3 ft. base, 1 ft. high; there was no remains of 1912 iron post. Witnessed by a mound of stone, 2 ft. base, embedded, west of cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground to bedrock, with a magnet at the base, in a mound of stone, 4 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
1/4
S 18 | S 17
2007

Cor. is located on a north/south spur.

N. 0°05.7' W., beginning new measurement.

40.061 The cor. of secs. 7, 8, 17, and 18, determined at the center of a collar of stone, embedded, 2 ft. diam., 6 ins. high; there was

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

no remains of 1912 iron post. Witnessed by a mound of stone, 4 ft. base, 3 ft. high, west of cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with a magnet at the base, in a mound of stone, 2 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E	
S 7	S 8
S 18	S 17
2007	

Set a steel fence post west of stainless steel post.

Cor. is located on the edge of a mesa, above Horse Canyon.

From the cor. of secs. 8, 9, 16, and 17.

S. 89°47.9' W., bet. secs. 8 and 17.

39.945 True point for the 1/4 sec. cor. of secs. 8 and 17. Point falls in a wash, 30 ft. wide, course South; poor location for monument. 1912 survey found similar conditions and was not set.

43.240 The witness cor. to the 1/4 sec. cor. of secs. 8 and 17, determined at the center of a mound of stone, embedded, 2 ft. base, 1 1/2 ft. high; there was no remains of 1912 iron post. Witnessed by a mound of stone, 3 ft. base, 2 ft. high, north of cor.

At the witness corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground to bedrock, with magnet at base, in a mound of stone, 4 ft. base to top of brass cap (Navajo seal) mkd.

WC	
T39S R23E	
	S 8
1/4	→
	S 17
2007	

Set a steel fence post north of stainless steel post, in a mound of stone, 2 ft. base, 2 ft. high.

Witness cor. located on the edge of a mesa top, above a deep wash, course south.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 89°48.4' W., beginning new measurement.

- 5.161** Centerline of San Juan County Road 474, gravel, 16 ft. wide, extending N. 29° W. and S. 29° E.
- 36.755** The cor. of secs. 7, 8, 17, and 18.

N. 89°35.1' W., bet. secs. 7 and 18.

- 40.081** The 1/4 sec. cor. of secs. 7 and 18, determined from an accessory mound of stone, embedded, 3 ft. base, 2 ft. high; there is no remaining evidence of the 1912 iron post.

At the corner point (immediately south of the mound of stone)

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground, with a magnet at the base, in a mound of stone, 3 ft. base to top of aluminum cap (BLM DOI seal) mkd.

T39S R23E
S 7
1/4 ———
S 18
2007

Set a steel fence post north of aluminum post, in a mound of stone, 3 ft. base, 2 ft. high.

Cor. is located in rocky, broken ground.

N. 89°59.8' W., beginning new measurement.

- 38.770** The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of Tp., hereinbefore described.

From the cor. of secs. 7, 8, 17, and 18.

N. 0°02.4' E., bet. secs. 7 and 8.

- 40.038** The 1/4 sec. cor. of secs. 7 and 8, determined at the center of a collar of stone, embedded, 2 1/2 ft. diam.; there was no remains of 1912 iron post. Witnessed by a mound of stone, 2 ft. base, 1 ft. high, embedded, west of cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, with a magnet at the base, in a mound of

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

stone, 3 ft. base to top of brass cap (Navajo seal) mkd.

T39S		R23E	
1/4			
S	7	S	8
2007			

Cor. is located at the cor. of fences, 6 strand barbed wire, extending South and N. 28° E.

N. 0°02.2' W., beginning new measurement.

40.064

The cor. of secs. 5, 6, 7, and 8, determined at the center of a mound of stone, embedded, 4 ft. base, 1 ft. high; there was no remains of 1912 iron post.

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, with a magnet at the base, in a mound of stone, 4 ft. base to top of aluminum cap (BLM DOI) mkd.

T39S		R23E	
S	6	S	5
S	7	S	8
2007			

Set a steel fence post north of aluminum post.

Cor. is located on the gentle, north facing slope of a small knoll.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 6 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 177+59.5, ELEV 4856.31, 1959, on the southeast side of Utah State Highway 262, bears N. 16°56.2' E., 13.584 chs. dist.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 5 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 172+36.5, ELEV 4863.49, 1959, on the south side of Utah State Highway 262, bears N. 21°33.5' W., 9.455 chs. dist.

From the cor. of secs. 4, 5, 8, and 9.

S. 89°59.4' W., bet. secs. 5 and 8.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- 6.769** Centerline of San Juan County Road 474, gravel, 16 ft. wide, extending N. 10° E. and S. 5° W.
- 40.018** The 1/4 sec. cor. of secs. 5 and 8, determined at the center of a collar of stone, embedded, 3 ft. diam.; there was no remains of 1912 iron post. Witnessed by a mound of stone, 2 ft. base, 1 ft. high, north of cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, with a magnet at the base, in a mound of stone, 3 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
S 5
1/4 ———
S 8
2007

Set a steel fence post west of stainless steel post.

Cor. is located in rolling hills, on rocky, barren ground.

S. 89°38.9' W., beginning new measurement.

- 39.934** The cor. of secs. 5, 6, 7, and 8.

N. 89°54.0' W., bet. secs. 6 and 7.

- 38.565** The centerline of Utah State Highway 262, a paved road, 25 ft. wide, extending N. 74° E. and S. 78° W.

- 39.983** Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground to bedrock, with magnet at the base, in a collar of stone, 3 ft. base to top of aluminum cap (BLM DOI) mkd.

T39S R23E
S 6
1/4 ———
S 7
2007

Set a steel fence post east of aluminum post.

Cor. is located in the north shoulder of Utah State Highway 262.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From cor., the centerline of Utah State Highway 262, 24 ft. wide, extending N. 75° E. and S. 75° W., bears South, 0.371 ch. dist.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 4 ins., with brass cap mkd. State Road Right of Way Marker, STA 148+43.9, ELEV 4880.38, 1959, on the north side of Utah State Highway 262, bears N. 33°15.8' E., 1.660 chs. dist.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 4 ins., with brass cap mkd. State Road Right of Way Marker, STA 148+43.9, ELEV 4866.98, 1959, on the south side of Utah State Highway 262, bears S. 49°46.3' E., 2.339 chs. dist.

48.754 The centerline of Utah State Highway 262, a paved road, 25 ft. wide, extending N. 66° W. and S. 79° E.

78.826 The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of Tp., hereinbefore described.

From the cor. of secs. 5, 6, 7, and 8.

N. 0°13.6' E., bet. secs. 5 and 6.

12.036 The centerline of Utah State Highway 262, a paved road, 25 ft. wide, extending N. 55° E. and S. 69° W.

40.027 The 1/4 sec. cor. of secs. 5 and 6, monumented with an iron post, 1 in. diam., loosely set in a mound of stone, 3 ft. base, 2 ft. high, projecting 14 ins. above mound, with brass cap mkd. as described in the official record of the 1912 survey of the subdivision of T. 39 S., R. 23 E.

Reset iron post 15 ins. in the ground, place magnet at base, rebuild mound of stone, 3 ft. base to top of brass cap.

Set a steel fence post north of iron post.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 6 ins., with brass cap mkd. State Road Right of Way Marker, STA 177+59.5, ELEV 4866.96, 1959, on the northwest side of Utah State Highway 262, bears S. 4°02.1' E., 24.861 chs. dist.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 5 ins., with brass cap mkd. State Road Right of Way Marker, STA 172+36.5, ELEV 4864.51, 1959, on the north side of Utah State Highway 262, bears S. 9°00.3' W., 28.680 chs. dist.

N. 0°06.9' E., beginning new measurement.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

39.933 The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of Tp., hereinbefore described.

Subdivision of Section 5,
T. 39 S., R. 23 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 5 and 8, hereinbefore described.

N. 0°11.2' E., on the N-S centerline of sec 5.

39.901 Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, with magnet at base, in a mound of stone, 2 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
C 1/4 S 5
2007

Cor. is located in open, gently rolling terrain, in a fence, 6 strand barbed wire, extending north and south.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 200+00, ELEV 4868.99, 1959, on the southeast side of Utah State Highway 262, bears S. 69°22.1' W., 11.824 chs. dist.

From cor., an iron pipe, 2 ins. diam., firmly set in concrete, projecting 3 ins. above ground, with brass cap mkd. State Road Right of Way Marker, STA 210+00, ELEV 4883.14, 1959, on the southeast side of Utah State Highway 262, bears N. 0°49.5' E., 6.040 chs. dist.

79.745 The true point for 1/4 sec. cor. of secs. 5 and 32, on the N. bdy. of Tp., hereinbefore described.

From the 1/4 sec. cor. of secs. 4 and 5, hereinbefore described.

S. 89°49.8' W., on the E-W centerline of sec 5.

16.604 Centerline of San Juan County Road 474, gravel, 16 ft. wide, extending N. 61° W. and S. 61° E.

39.856 The center 1/4 sec. cor. of sec. 5.

79.757 The 1/4 sec. cor. of secs. 5 and 6, hereinbefore described.

THE SUBDIVISION OF SECTION 8,
T. 42 S., R. 17 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Subdivision of Section 8,
T. 39 S., R. 23 E., Salt Lake Meridian, Utah

From the true point for the 1/4 sec. cor. of secs. 8 and 17, hereinbefore described.

N. 0°04.6' W., on the N-S centerline of sec 8.

12.919 Centerline of San Juan County Road 474, gravel, 16 ft. wide, extending N. 52° E. and S. 52° W.

40.054 Point for the center 1/4 sec. cor. of sec. 8, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground to bedrock, with magnet at base, in a mound of stone, 4 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
C 1/4 S 8
2007

Cor. is located in rolling badlands, rocky with no vegetation.

80.212 The 1/4 sec. cor. of secs. 5 and 8, hereinbefore described.

From the 1/4 sec. cor. of secs. 8 and 9, hereinbefore described.

S. 89°47.0' W., on the E-W centerline of sec 8.

5.706 Centerline of San Juan County Road 474, gravel, 16 ft. wide, extending N. 15° E. and S. 23° W.

39.945 The center 1/4 sec. cor. of sec. 8.

79.910 The 1/4 sec. cor. of secs. 7 and 8, hereinbefore described.

Subdivision of Section 23,
T. 39 S., R. 23 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 23 and 26, hereinbefore described.

N. 0°00.5' E., on the N-S centerline of sec 23.

20.007 Point for the center S 1/16 sec. cor. of sec. 23, not monumented.

THE SUBDIVISION OF SECTION 23
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.014 Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E-W centerline.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at base, with brass cap (Navajo seal) mkd.

T39S R23E
C 1/4 S 23
2007

Set a steel fence post north of stainless steel post.

Cor. is located on a fairly level prairie, with desert vegetation.

80.090 The 1/4 sec. cor. of secs. 14 and 23, hereinbefore described.

From the 1/4 sec. cor. of secs. 23 and 24, hereinbefore described.

N. 89°56.8' W., on the E-W centerline of sec 23.

19.959 Point for the center E 1/16 sec. cor. of sec. 23, not monumented.

39.918 The center 1/4 sec. cor. of sec. 23.

79.828 The 1/4 sec. cor. of secs. 22 and 23, hereinbefore described.

From the E 1/16 sec. cor. of secs. 23 and 26, hereinbefore described.

N. 0°00.1' E., on the N-S centerline of the SE 1/4 of sec 23.

20.011 Point for the SE 1/16 sec. cor. of sec. 23, at intersection with the E-W centerline of the SE 1/4 of sec. 23.

Set a brass tablet, 3 1/4 ins. diam., with a 3 1/2 ins. stem, flush with sandstone, in cement bond, into a drill hole on a sandstone outcrop, with magnet at base of stem, with brass face (Navajo seal) mkd.

T39S R23E
SE 1/16 S 23
2007

from which

THE SUBDIVISION OF SECTION 23
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

A juniper, 12 ins. diam., bears S. 17°29' E., 0.666 ch. dist., marked X BT.

Set a steel fence post north of brass tablet, in a mound of stone, 2 ft. base, 2 ft. high.

Cor. is located on a gentle, west sloping sandstone outcrop, in scattered juniper trees.

40.022 Point for the center E 1/16 sec. cor. of sec. 23, not monumented.

From the S 1/16 sec. cor. of secs. 23 and 24, hereinbefore described.

N. 89°56.1' W., on the E-W centerline of the SE 1/4 of sec 23.

19.963 The SE 1/16 sec. cor. of sec. 23.

39.926 The point for the center S 1/16 sec. cor. of sec. 23, not monumented.

Subdivision of Section 33,
T. 39 S., R. 23 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of sec. 33 only, T. 39 S., R. 23 E., on the N. bdy. of Tp. 40 S., R. 23 E., hereinbefore described.

N. 0°05.1' W., on the N-S centerline of sec 33.

20.015 Point for the center S 1/16 sec. cor. of sec. 33.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, with magnet at base, in a mound of stone, 4 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
C
S 1/16 | S 33
C
2007

Set a steel fence post north of stainless steel post.

Cor. is located between 2 large boulders, on the north side of a small knoll.

40.030 Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E-W centerline.

THE SUBDIVISION OF SECTION 33
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with magnet at base, in a mound of stone, 3 ft. base to top of brass cap (Navajo seal) mkd.

T39S R23E
C 1/4 S 33
2007

Set a steel fence post north of stainless steel post.

Cor. is located on a moderately steep, east facing slope, just below mesa top, high above McCracken Canyon.

80.057 The 1/4 sec. cor. of secs. 28 and 33, hereinbefore described.

From the 1/4 sec. cor. of secs. 33 and 34, hereinbefore described.

S. 89°52.2' W., on the E-W centerline of sec 33.

39.998 The center 1/4 sec. cor. of sec. 33.

59.923 The center W 1/16 sec. cor. of sec. 33, not monumented.

79.848 The 1/4 sec. cor. of secs. 32 and 33, hereinbefore described.

From the W 1/16 sec. cor. of sec. 33 only, T. 39 S., R. 23 E., on the N. bdy. of Tp. 40 S., R. 23 E., hereinbefore described.

N. 0°00.3' E., on the N-S centerline of the SW 1/4 of sec 33.

19.988 Point for the SW 1/16 sec. cor. of sec. 33, at intersection with the E-W centerline of the SW 1/4 of sec. 33.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at base, with brass cap (Navajo seal) mkd.

T39S R23E
SW 1/16 S 33
2007

Set a steel fence post north of stainless steel post.

Cor. is located in rolling, sandy hills.

From cor., a fence, 4 strand barbed wire, extending north and south, bears East, 0.409 ch. dist.

39.979 Point for the center W 1/16 sec. cor. of sec. 33, not monumented.

THE SUBDIVISION OF SECTION 33
T. 39 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the center S 1/16 sec. cor. of sec. 33.

S. 89°56.4' W., on the E-W centerline of the SW 1/4 of sec 33.

19.958 The SW 1/16 sec. cor. of sec. 33.

39.916 The point for the S 1/16 sec. cor. of secs. 32 and 33, not monumented.

Survey of the Meanders of the left bank of Recapture Creek in
Section 19, T. 39 S., R. 23 E., Salt Lake Meridian, Utah

From the true point for the meander cor. of secs. 18 and 19,
T. 39 S., R. 23 E., on the left bank of Recapture Creek,
hereinbefore described.

Thence, with the meanders of the present left bank of Recapture
Creek through section 19.

S. 19°04.6' W., 9.232 chs.

S. 26°46.5' E., 13.257 chs.

S. 56°12.2' E., 10.638 chs.

S. 13°38.3' E., 2.979 chs.

S. 19°00.1' W., 17.097 chs.

S. 73°04.7' W., 10.982 chs.

S. 42°00.4' W., 3.294 chs.

S. 12°52.1' E., 6.532 chs.

S. 21°44.7' W., 5.736 chs.

S. 3°08.4' W., 16.103 chs.

S. 84°13.9' W., 5.417 chs.

The true point for the meander cor. of
secs. 19 and 24, on the W. bdy. of
T. 39 S., R. 23 E., on the left bank of
Recapture Creek, hereinbefore described.

TOWNSHIP 39 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

GENERAL DESCRIPTION

This project, Township 39 South, Range 23 East, contains a large part of McCracken Mesa, which is a high desert mesa, approximately 5000 feet above sea level. Except for several sections on the western side, the township is located within the Navajo Reservation, of the Aneth Chapter House. The nearest town is Montezuma Creek, several miles to the south. Utah State Highway 262 travels along the eastern and northern boundaries of the township, and several well maintained San Juan County roads are located within.

The climate varies from hot in the summer (100 degrees plus) to well below freezing in the winter. The terrain is open desert, with scattered sage brush and other common desert plants. The soil ranges from soft and sandy to solid sandstone outcrops. Recapture Creek intermittently flows along the western boundary, and McCracken Canyon originates in the northeast sector and cuts southwest. Several oil wells actively produce in the township, with many plugged and abandoned exploration wells present.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Phil Freiberg	Survey Technician

CERTIFICATE OF SURVEY

I, *Scott A. Burkhardt*, Cadastral Surveyor, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *27th day of June, 2007*, I have *dependently resurveyed a portion of the North boundary and correctively resurveyed a portion of the North boundary, of Township 40 South, Range 23 East, dependently resurveyed the West (Colorado Guide Meridian) and the North boundaries, and the subdivisional lines, and surveyed the subdivision of sections 5, 8, 23, and 33, and the survey of the meander of the left bank of Recapture Creek in section 19, in Township 39 South, Range 23 East, of the Salt Lake Meridian, in the State of Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 24, 2008

Date

Scott A. Burkhardt

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the North boundary, and the corrective resurvey of a portion of the North boundary, of Township 40 South, Range 23 East, the dependent resurvey of the West (Colorado Guide Meridian) and North boundaries, and the subdivisional lines, and the survey of the subdivision of sections 5, 8, 23, and 33, and the survey of the meander of the left bank of Recapture Creek in section 19, in Township 39 South, Range 23 East, of the Salt Lake Meridian, in the State of Utah*, executed by *Scott A. Burkhardt, Cadastral Surveyor*, having been critically examined and found correct, are hereby approved.

September 29, 2008

Date

Daniel W. Webb

(Chief Cadastral Surveyor for Utah)