

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,

AND

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTION 18,

THE METES AND BOUNDS SURVEY IN THE SW 1/4 OF THE NE 1/4,

AND

THE CEMETERY IN THE SW 1/4 OF THE SE 1/4 OF SECTION 18,

IN

TOWNSHIP 14 NORTH, RANGE 3 WEST,

OF THE SALT LAKE MERIDIAN, UTAH,
IN THE STATE OF UTAH

EXECUTED BY

Ronald K. Baugh, Supervisory Cadastral Surveyor

Under special instruction dated and approved *July 10, 2007*, which provided for the surveys included under Group Number *1044*, and the assignment instructions dated *July 10, 2007*, and reassignment instructions dated *September 10, 2007*

Survey commenced *August 15, 2007*
Survey completed *August 22, 2007*

INDEX DIAGRAM

Township 14 North, Range 3 West

6	5	4	3	2	1
7	8	9	10	11	12
9 8					
4 18 8 3 6 5	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

The Subdivision of Section 18.....Page 9

The Metes and Bounds Survey in the SW 1/4 of the NE 1/4.....Page 15

The Cemetery in the SW 1/4 of the SE 1/4.....Page 16

TOWNSHIP 14 NORTH, RANGE 3 WEST, SALT LAKE MERIDIAN

The following field notes are those of the dependent resurvey of a portion of the west boundary, and a portion of the subdivisional lines, and the subdivision of section 18, the metes and bounds survey in the SW 1/4 of the NE 1/4, and the Cemetery in the SW 1/4 of the SE 1/4 of section 18, in Township 14 North, Range 3 West, Salt Lake Meridian, Utah.

History of Surveys

Surveyed by	Retr. or Resurveyed by		
SOUTH BOUNDARY			
Portion J. Trokolawski	1856		
Portion A. J. Stewart Sr.	1875-76	A. J. Stewart Sr.	1875-76
Portion		H. Fitzhugh	1887
EAST BOUNDARY			
Portion A.J. Stewart Sr.	1875		
Portion H. P. Hanson	1896		
WEST BOUNDARY			
All J. Trokolawski	1856		
All		H. Fitzhugh	1887
NORTH BOUNDARY			
Portion J. Trokolawski	1856		
Portion A. P. Hanson	1896		
SUBDIVISION			
Portion J. Trokolawski	1856		
Portion A. P. Hanson	1896	A.P. Hanson	1896

A private survey was preformed by Harper-Leavitt Engineering, INC. in 1985 for the Northwestern Band of the Shoshone Nation of the Cemetery and a Metes and Bounds survey located in the SW 1/4 of the NE 1/4 of section 18.

This survey is to establish the Trust lands for the Northwestern Band of Shoshone, Parcel 1, Parcel 2 and Parcel 3, based on Warranty Deed 195-63, Book 382 Page 520, recorded in Box Elder County, Utah.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1044, Utah, dated July 10, 2007.

The direction of the lines was determined by references to the meridians, established by Global Positioning Systems (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards and Guidelines for Cadastral Surveys Using Global Positioning Methods*, dated May 9, 2001, Version 1.0. Trimble model 5700 GPS receivers were used for field collection.

TOWNSHIP 14 NORTH, RANGE 3 WEST, SALT LAKE MERIDIAN

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geodetic control was derived from U. S. Geological Survey Triangulation Station "PORTAGE", as published by National Geodetic Survey, is as follows:

Latitude: $41^{\circ} 57' 01.12634''$ N., Longitude: $112^{\circ} 14' 41.28487''$ W.,
N.A.D. 1983 (1994), N.A.V.D. 1988, Elevation: 4660 Ft.

The geographic positions of the 1/4 section corner of sections 13 and 18, on the west boundary of the township, in N.A.D. 1983 (CORS96), determined by a tie made to U.S. Geological Survey Triangulation Station "PORTAGE" with Global Positioning System (GPS) observations to a Network Accuracy of less than 0.20 meter, 95 percent confidence circle, is as follows:

Latitude: $41^{\circ} 57' 00.541''$ N., Longitude: $112^{\circ} 14' 46.256''$ W.
N.A.V.D. 1988, Elevation: 4674 Ft.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 14 N., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the West Boundary,
T. 14 N., R. 3 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by J. Troskolawski
in 1856, and Dependent Resurvey by H. Fitzhugh in 1887

Beginning at the corner of sections 13, 18, 19, and 24, on
the west boundary of the township, monumented with a 1/2
inch rebar, projecting 3 inches above ground, with a steel
fence post along side. This monument is accepted as the
best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches
diameter, 22 inches in the ground to bedrock, with a magnet
at base, with aluminum cap marked:

T14N	
R4W	R3W
S13	S18
S24	S19
2007	

Deposit the rebar inside the aluminum post.

Reset the steel fence post alongside the aluminum post.

From this corner, a capped water well bears N. 1° 07.1' E.,
8.704 chains distance.

N. 2° 25.8' W., between sections 13 and 18.

0.969 Intersect a fence, projecting easterly and westerly; west,
1.7 links distance to the corner of fences projecting
easterly, westerly and northerly.

19.877 The S 1/16 section corner of sections 13 and 18, monumented
with a 1/2 inch rebar, projecting 3 inches above ground.
This monument is accepted as a careful and faithful
determination of the corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches
diameter, 26 inches in the ground, with a magnet at base,
with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 14 N., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T14N
R4W R3W
S 1/16
S13 | S18
2007

Deposit the rebar inside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 2° 26.8' W., beginning new measurement.

1.201 Intersect a fence, projecting easterly and westerly; west,
72.6 links distance to the corner of fences projecting
easterly, westerly and southerly.

19.872 The 1/4 section corner of sections 13 and 18, monumented
with a 1/2 inch rebar, flush with the ground and bent over.
This monument is accepted as the best available evidence of
the original corner position.

At the center base of the bent rebar

Set an aluminum post, 30 inches long, 2 1/2 inches
diameter, 24 inches in the ground, with a magnet at base,
with aluminum cap marked:

T14N
R4W R3W
1/4
S13 | S18
2007

Deposit the bent rebar inside the aluminum post.

Set a steel fence post alongside the aluminum post.

From this corner, National Geodetic Survey Control Station
"PORTAGE", monumented with a standard disk set in the top
of a cylindrical concrete post, 12 inches in diameter,
projecting 8 inches above the ground, with disk stamped:
"PORTAGE 1960", bears N. 81° 02.3' E., 5.763 chains
distance.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 14 N., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 14 N., R. 3 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by J. Troskolawski
in 1856

From the corner of sections 17, 18, 19, and 20, monumented with a 1/2 inch rebar, flush with the ground and bent over. This monument is accepted as the best available evidence of the original corner position.

At the center base of the bent rebar.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with a magnet at base, with aluminum cap marked:

T14N	R3W
S18	S17
S19	S20
2007	

Deposit the bent rebar inside the aluminum post.

Set steel fence post alongside the aluminum post.

S. 88° 30.5' W., between sections 18 and 19.

19.589 Intersect the approximate center of a gravel road projecting northerly and southerly; south, 12.8 links distance to an intersection of roads projecting westerly, northerly and southerly.

20.012 Point for the E 1/16 section corner of sections 18 and 19.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 2 inches below ground, with a magnet at base, with aluminum cap marked:

T14N	R3W
	S 18
E 1/16	—————
	S 19
	2007

Set a steel fence post alongside the aluminum post.

28.866 Point on line at proportionate distance based on the Harper-Leavitt 1985 survey of the Cemetery.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 14 N., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, flush with the ground, with magnet at base, with aluminum cap marked:

T14N R3W
POL
S18
S19
2007

Set a steel fence post alongside the aluminum post.

Corner is located on the north edge of a gravel road.

From this monument, the southwest corner of the Air Quality Station fence enclosure, bears N. 13° 19.1' E., 4.657 chains distance. The enclosure is approximately 50 ft, square.

From this same monument, the point for Angle Point 1 on the Cemetery boundary line, at a record angle from the Harper-Leavitt 1985 survey, bears N. 1° 57.2' W., 5.808 chains at record distance.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground to bedrock, with a magnet at base, with aluminum cap marked:

T14N R3W
CEM | S 18
AP 1 | IRB
2007

Raise a mound of stone, 3 ft. base to top of aluminum cap.

Set a steel fence post alongside the aluminum post.

Corner is located on the east side of a barb wire fence corner projecting north and east.

33.936

Intersect the approximate center of a gravel road, projecting northerly and southerly; south, 5.3 links distance to an intersection, with roads projecting easterly and westerly.

40.024

The 1/4 section corner of sections 18 and 19, monumented with a 1/2 inch rebar, flush with the ground and bent over. This monument is accepted as the best available evidence of the original corner position.

At the center base of the bent rebar

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 14 N., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 2 inches below ground, with a magnet at base, with aluminum cap marked:

T14N R3W
S 18
1/4 ———
S 19
2007

Deposit the bent rebar inside the aluminum post.

Set a steel fence post North, 5 ft. distance from the aluminum post.

Corner is located in a 2 track gravel road.

S. 88° 30.6' W., beginning new measurement.

40.089 The corner of sections 13, 18, 19, and 24, on the west boundary of the township, hereinbefore described.

From the corner of sections 17, 18, 19, and 20.

N. 1° 48.8' W., between sections 17 and 18.

0.610 Intersect a fence, projecting easterly and westerly.

1.111 Intersect the approximate center of a gravel road projecting easterly and westerly.

19.906 Point for the S 1/16 section corner of sections 17 and 18.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with a magnet at base, with aluminum cap marked:

T14N R3W
S 1/16
S18 | S17
2007

Set a steel fence post alongside the aluminum post.

Corner is located in a fence line projecting northerly and southerly.

39.620 Intersect a fence, projecting westerly and easterly; east, 2.1 links distance to the corner of fences projecting westerly, northerly and southerly.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 14 N., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS
39.812

The 1/4 section corner of sections 17 and 18, monumented with a 1/2 inch rebar, flush with the ground. This monument is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T14N R3W
1/4
S18 | S17
2007

Deposit the rebar inside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 1° 48.8' W., beginning new measurement.

19.905

Point for the N 1/16 section corner of sections 17 and 18, not monumented.

39.810

The corner of sections 7, 8, 17, and 18, monumented with a 1/2 inch rebar, with a yellow plastic cap marked, "BOX ELDER COUNTY", flush with the ground. This monument is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with a magnet at base, with aluminum cap marked:

T14N R3W
S7 | S8
S18 | S17
2007

Deposit the rebar and cap inside the aluminum post.

Set a steel fence post alongside the aluminum post.

S. 88° 25.9' W., between sections 7 and 18.

5.081

Intersect a fence, projecting easterly and westerly.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 14 N., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

19.920

Intersect a fence, projecting northerly and southerly;
south, 6.6 links to the corner of fences projecting
northerly, easterly and westerly.

20.212

Point for the E 1/16 section corner of sections 7 and 18,
not monumented.

40.340

Intersect a fence, projecting northerly and southerly;
south, 60.9 links distance to the corner of fences,
projecting northerly, southerly and easterly.

40.424

The 1/4 section corner of sections 7 and 18, monumented
with a 1/2 inch rebar, flush with ground. This monument is
accepted as the best available evidence of the original
corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches
diameter, 28 inches in the ground, with a magnet at base,
with aluminum cap marked:

	T14N	R3W
		S7
1/4		
		S18
		2007

Deposit the rebar inside the aluminum post.

Set a steel fence post alongside the aluminum post.

A road bears west, 32 links distance, bears northerly and
southerly.

The Subdivision of Section 18
T. 14 N., R. 3 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 18 and 19.

N. 2° 07.2' W., on the N - S centerline of section 18.

0.323

Intersect a fence, projecting easterly and westerly.

19.897

The center S 1/16 section corner of section 18, monumented
with a 1/2 inch rebar, flush with the ground. This monument
is accepted as a careful and faithful determination of the
corner position.

At the corner point

THE SUBDIVISION OF SECTION 18,
T. 14 N., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T14N R3W
C
S 1/16 | S18
C
2007

Deposit the rebar inside the aluminum post.

A steel fence post found at the corner was reset alongside the aluminum post.

From this corner, the corner of fences projection westerly and northerly, bears N. 89 3/4° W., 51.8 links distance.

N. 2° 05.9' W., beginning new measurement.

19.884 Point for the center 1/4 section corner of section 18, at intersection with the E - W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T14N R3W
C 1/4
S18
2007

Set a steel fence post alongside the aluminum post.

26.728 Intersect a fence, projecting easterly and westerly; west, 41.5 links distance to the corner of fences projecting easterly and southerly.

26.734 Angle Point 1, on the Northwestern Band of Shoshone Indian Reservation boundary line, monumented with a 1/2 inch rebar, projecting 2 inches above ground. This monument is accepted as a careful and faithful determination of the corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

THE SUBDIVISION OF SECTION 18,
T. 14 N., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T14N R3W
S18 | AP 1
IRB
2007

Deposit the rebar inside the aluminum post.

A steel fence post was found at the corner and was reset alongside the aluminum post.

A 1/2 inch rebar was also found west of the aluminum post, not used in the course of this survey.

N. 2° 06.6' W., beginning new measurement.

13.047 Point for the center N 1/16 section corner of section 18.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T14N R3W
C
N 1/16 | S18
C
2007

Set a steel fence post alongside the aluminum post.

14.019 Intersect the approximate center of a gravel road on a curve that projects northerly and easterly.

32.944 The 1/4 section corner of sections 7 and 18.

From the 1/4 section corner of sections 17 and 18.

S. 88° 27.6' W., on the E - W centerline of section 18.

19.726 Intersect the approximate center of a gravel road projecting northerly and southerly.

20.112 Point for the center E 1/16 section corner of section 18.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with a magnet at base, with aluminum cap marked:

THE SUBDIVISION OF SECTION 18,
T. 14 N., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T14N R3W
E 1/16
C ————— C
S18
2007

Set a steel fence post alongside the aluminum post.

A 1/2 by 24 inch rebar is located approximately 10 ft. west of corner, not used in the course of this survey.

- 20.131 Intersect a fence, projecting northerly and southerly; south, 35 links distance to the corner of fences projecting northerly, southerly and easterly.
- 40.224 The center 1/4 section corner of section 18.
- 40.675 Intersect a fence, projecting northerly and southerly.
- 80.537 The 1/4 section corner of sections 13 and 18, on the west boundary of the township, hereinbefore described.

From the center E 1/16 section corner of section 18.

N. 1° 57.7' W., on the N - S centerline of the NE 1/4 of section 18.

- 19.644 Intersect the approximate center of a gravel road on a curve that projects southerly and easterly.
- 19.904 Point for the NE 1/16 section corner of section 18, at intersection with the E - W centerline of the of the NE 1/4.
- Set a rebar, 18 inches long, 3/4 inch diameter, 12 inches below the surface of a gravel road, with a 3 inch aluminum cap marked:

T14N R3W
NE 1/16 S18
2007

Set a steel fence post, 55 ft. West of the rebar.

Set a steel fence post, 100 ft. South of the rebar.

- 39.729 Intersect a fence, projecting westerly and easterly; east, 29.2 links distance to the corner of fences projecting northerly and easterly and westerly.
- 39.802 The point for the E 1/16 section corner of sections 7 and 18.

THE SUBDIVISION OF SECTION 18,
T. 14 N., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the point for the N 1/16 section corner of sections 17 and 18.

S. 88° 27.2' W., on the E - W centerline of the NE 1/4 of section 18.

- 20.162 The NE 1/16 section corner of section 18.
- 20.398 Intersect the approximate center of a gravel road on a curve that projects southerly and westerly.
- 20.837 Intersect a fence, projecting northwesterly and southeasterly; northeasterly, 9.3 links distance, to the corner of fences projecting westerly, and southeasterly; southeasterly, 75.9 links distance, to the corner of fences projecting southerly and northwesterly.
- 29.187 Angle Point 5, on the Northwestern Band of Shoshone Indian Reservation boundary line, monumented with a 1/2 inch rebar, projecting 2 inches above ground, in a fence projecting northerly and southerly. This monument is accepted as a careful and faithful determination of the corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T14N	R3W
S 18	AP 5
	IRB
	2007

Deposit the rebar inside the aluminum post.

Set a steel fence post alongside the aluminum post.

From this corner, the corner of fences projecting southerly and easterly, bears north, 3 links distance.

From this same corner, a gravel road projecting easterly and westerly, bears north, 60 links distance.

S. 88° 25.6' W., beginning new measurement.

- 11.137 The center N 1/16 section corner of section 18.
-

THE SUBDIVISION OF SECTION 18,
T. 14 N., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the E 1/16 section corner of sections 18 and 19.

N. 1° 57.7' W., on the N - S centerline of the SE 1/4 of section 18.

0.062 Intersect a fence, projecting westerly and easterly; east, 1.3 links distance to the corner a fence projecting westerly and northerly.

19.901 The SE 1/16 section corner of section 18, at intersection with the E - W centerline of the SE 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with a magnet at base, with aluminum cap marked:

T14N R3W
SE 1/16 S18
2007

Set a steel fence post alongside the aluminum post.

39.446 Intersect a fence, projecting easterly and westerly; west, 1.5 links distance to the corner of fences projecting easterly, westerly, northerly and southerly.

39.796 The center E 1/16 section corner of section 18.

From the S 1/16 section corner of sections 17 and 18.

S. 88° 29.5' W., on the E - W centerline of the SE 1/4 of section 18.

19.566 Intersect the approximate center of a gravel road projecting northerly and southerly.

20.032 Intersect a fence, projecting northerly and southerly.

20.062 The SE 1/16 section corner of section 18.

40.128 The center S 1/16 section corner of section 18.

From the center S 1/16 section corner of section 18.

S. 88° 28.8' W., on the E - W centerline of the SW 1/4 of section 18.

40.194 The S 1/16 section corner of sections 13 and 18, on the west boundary of the township, hereinbefore described.

THE METES AND BOUNDS SURVEY IN THE SW 1/4 OF THE NE 1/4,
SECTION 18, T. 14 N., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The Metes and Bounds Survey in the SW 1/4 of the NE 1/4,
section 18, T. 14 N., R. 3 W., Salt Lake Meridian, Utah

From Angle Point 1, on the N - S centerline of section 18.

N. 87° 30.0' E., on the Northwestern Band of Shoshone
Indian Reservation boundary line, along a fence.

5.580

Angle Point 2, monumented with a 1/2 inch rebar, projecting
3 inches above the ground. This monument is accepted as a
careful and faithful determination of the corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches
diameter, 24 inches in the ground, with a magnet at base,
with aluminum cap marked:

T14N	R3W	
S 18		
		AP 2
		IRB
		2007

Deposit the rebar inside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 1° 32.2' W., beginning new measurement.

0.006

Intersect a fence, projecting westerly and easterly; east,
0.4 links distance to the corner of fences projecting
westerly and northerly.

8.895

Angle Point 3, monumented with a 1/2 inch rebar, projecting
3 inches above ground. This monument is accepted as a
careful and faithful determination of the corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches
diameter, 26 inches in the ground, with a magnet at base,
with aluminum cap marked:

T14N	R3W	
S 18		
		AP 3
		IRB
		2007

Deposit the rebar inside the aluminum post.

THE METES AND BOUNDS SURVEY IN THE SW 1/4 OF THE NE 1/4,
SECTION 18, T. 14 N., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the aluminum post.

From this corner, the corner of fences projecting southerly
and easterly, bears N. 17° W., 1.4 links distance.

N. 88° 08.0' E., beginning new measurement.

5.453

Angle Point 4, monumented with a 1/2 inch rebar, projecting
4 inches above ground. This monument is accepted as a
careful and faithful determination of the corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches
diameter, 24 inches in the ground, with a magnet at base,
with aluminum cap marked:

```

      T14N   R3W
      S 18   |
      _____| AP 4
                | IRB
                |
                | 2007
  
```

Deposit the rebar inside the aluminum post.

Set a steel fence post alongside the aluminum post.

From this corner, the corner of fences projecting northerly
and westerly, bears N. 16 1/2° W., 2.1 links distance.

N. 1° 53.9' W., beginning new measurement.

4.033

Angle Point 5 on the E - W center line of the NE 1/4 of
section 18.

The Cemetery in the SW 1/4 of the SE 1/4 of section 18, T.
14 N., R. 3 W., Salt Lake Meridian, Utah

From Angle Point 1 at the southeast corner of the Cemetery,
hereinbefore described.

S. 89° 37.1' W., on a record angle from the Harper-Leavitt
1985 survey on the south boundary of the Cemetery.

5.020

Intersect the approximate center of a gravel road,
projecting, southerly and northerly; north, 5.6 links
distance to the opening in the east and west fence line
into the Cemetery.

5.183

Point for Angle Point 2 at record distance.

THE CEMETERY IN THE SW 1/4 OF THE SE 1/4 OF SECTION 18,
T. 14 N., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with a magnet at base, with aluminum cap marked:

T14N	R3W
S 18	CEM
IRB	AP 2

2007

Set a steel fence post alongside the aluminum post.

From this corner, the corner of fences projecting northerly and easterly, bears N. 37 1/2° E., 7.3 links distance.

N. 1° 57.3' W., on the west boundary of the Cemetery, on a record angle from the Harper-Leavitt 1985 survey.

9.093

Point for Angle Point 3 at record distance.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with a magnet at base, with aluminum cap marked:

T14N	R3W
S 18	AP 3
IRB	CEM

2007

Set a steel fence post alongside the aluminum post.

From this corner the corner of fences projecting southerly and easterly, bears N. 48° W., 5.6 links distance.

From this same corner, the southeast corner of a well house, bears N. 55° 04.5' W., 79.2 links distance. This building is oriented N - S and E - W, approximately 8 ft. square and 8 ft. high.

N. 89° 37.1' E., on the north boundary of the Cemetery, on a record angle from the Harper-Leavitt 1985 survey.

5.183

Point for Angle Point 4 at record distance.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

THE CEMETERY IN THE SW 1/4 OF THE SE 1/4 OF SECTION 18,
T. 14 N., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T14N	R3W
AP 4	S 18
CEM	IRB
2007	

Set a steel fence post alongside the aluminum post.

From this corner, the corner of fences projecting westerly and southerly, bears S. 3 3/4° W., 3.3 links distance.

S. 1° 57.2' E., on the east boundary of the Cemetery, on a record angle from the Harper-Leavitt 1985 survey.

9.093

Angle Point 1 at record distance, and point of beginning.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

T. 14 N., R. 3 W., SALT LAKE MERIDIAN, UTAH

FIELD ASSISTANTS

Name	Capacity
Glen B. Hatch	Cadastral Surveyor
Adrian Kurip	Survey Technician
Travis R. Hanks	Cadastral Surveyor

CERTIFICATE OF SURVEY

I, **Ronald K. Baugh**, Supervisory Cadastral Surveyor, hereby certify upon honor that in pursuance of special instructions bearing the date of the 10th day of July, 2007, I have executed a dependent resurvey of a portion of the west boundary, and a portion of the subdivisional lines, and the subdivision of section 18, the metes and bounds survey in the SW 1/4 of the NE 1/4, and the Cemetery in the SW 1/4 of the SE 1/4 of section 18, in Township 14 North, Range 3 West, of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Jan. 28, 2008
Date

Ronald K. Baugh
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the west boundary, and a portion of the subdivisional lines, and the subdivision of section 18, the metes and bounds survey in the SW 1/4 of the NE 1/4, and the Cemetery in the SW 1/4 of the SE 1/4 of section 18, in Township 14 North, Range 3 West, Salt Lake Meridian, Utah*, executed by **Ronald K. Baugh**, Supervisory Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

January 28, 2008
Date

Daniel W. Webb
(Chief Cadastral Surveyor for Utah)