

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH BOUNDARY (FIRST STANDARD PARALLEL SOUTH) OF

TOWNSHIP 5 SOUTH, RANGE 8 WEST,

AND

PORTIONS OF THE SOUTH AND EAST BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES,

THE SUBDIVISION OF SECTIONS 10, 12, 14, 15, 22, 24, 25, AND 34,

AND

THE SURVEY OF PORTIONS OF THE RIGHT-OF-WAY LINES OF UTAH STATE ROAD NOS.  
196 AND 199,

IN

TOWNSHIP 6 SOUTH, RANGE 8 WEST,

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Daniel T. Gillins*  
*Survey Technician*

*Under the Supervision of*  
*Ronald K. Baugh*  
*Cadastral Surveyor*

Under Special Instructions dated *September 12, 2007*, approved *September 12, 2007*, which provided for the surveys included under Group Number *1054*, and assignment instructions dated *September 12, 2007*.

Survey Commenced, *September 14, 2007*  
Survey Completed, *September 13, 2008*

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH BOUNDARY (FIRST STANDARD PARALLEL SOUTH) OF

TOWNSHIP 5 SOUTH, RANGE 8 WEST,

AND

PORTIONS OF THE SOUTH AND EAST BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES,

THE SUBDIVISION OF SECTIONS 10, 12, 14, 15, 22, 24, 25, AND 34,

AND

THE SURVEY OF PORTIONS OF THE RIGHT-OF-WAY LINES OF UTAH STATE ROAD NOS.  
196 AND 199,

IN

TOWNSHIP 6 SOUTH, RANGE 8 WEST,

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Daniel T. Gillins*  
*Survey Technician*

*Under the Supervision of*  
*Ronald K. Baugh*  
*Cadastral Surveyor*

Under Special Instructions dated *September 12, 2007*, approved *September 12, 2007*, which provided for the surveys included under Group Number *1054*, and assignment instructions dated *September 12, 2007*.

Survey Commenced, *September 14, 2007*  
Survey Completed, *September 13, 2008*

## INDEX DIAGRAM

Township 6 South, Range 8 West.

6	5	4 5 36	3 3 30 35	2 29	1 13 23
7	8	9 35	10 29 34	11 22 28	12 12 22
18	17	16 34	15 27 33	14 21 26	13 11 21
19	20	21 32	22 25 31	23 19	24 10 19
30	29	28 31	27 24 31	26 18	25 8 16
31	32	33 30	34 24 6	35 15	36 7 6

The Subdivision of Section 10.....Page 36  
 The Subdivision of Section 12.....Page 37  
 The Subdivision of Section 14.....Page 38  
 The Subdivision of Section 15.....Page 40  
 The Subdivision of Section 22.....Page 41  
 The Subdivision of Section 24.....Page 42  
 The Subdivision of Section 25.....Page 43  
 The Subdivision of Section 34.....Page 44

The Survey of a portion of the  
 Right-of-Way lines of Utah State Road No. 196.....Page 45

The Survey of a portion of the  
 Right-of-Way lines of Utah State Road No. 199.....Page 52

## TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

The following field notes are those of the dependent resurvey of a portion of the south boundary (First Standard Parallel South) of T. 5 S., R. 8 W.; and portions of the south and east boundaries, a portion of the subdivisional lines, the subdivision of sections 10, 12, 14, 15, 22, 24, 25, and 34, and the survey of portions of the right-of-way lines of Utah State Roads nos. 196 and 199, in T. 6 S., R. 8 W., Salt Lake Meridian, Utah.

## HISTORY OF SURVEYS

	Surveyed by		Retr. Or Resurveyed by	
<b>NORTH BOUNDARY (First Standard Parallel South)</b>				
All	A.D. Ferron	1871		
Portion			E. Bird	1950-51
<b>SOUTH BOUNDARY</b>				
Portion	A.J. Stewart Sr.	1875		
Portion	J. Gorlinski	1876		
All			E. Bird	1950-51
<b>EAST BOUNDARY</b>				
All	A.J. Stewart Sr.	1875		
<b>WEST BOUNDARY</b>				
Portion	A.J. Stewart Sr.	1875		
All	E. Bird	1950-51	E. Bird	1950-51
<b>SUBDIVISION</b>				
Portion	A.J. Stewart Sr.	1875		
Portion	E. Bird	1950-51	E. Bird	1950-51
<b>RIGHT-OF-WAY SURVEY</b>				
State Road 196	State of Utah	1951		
State Road 199	State of Utah	1942		

## TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

This survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1054, dated September 12, 2007.

The direction of the lines was determined by references to true meridians, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods, dated May 9, 2001, Version 1.0. Trimble model 5800 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for the project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic Control was derived from GPS static observations, post processed by the National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS): KENNECOTT1UT2005 CORS ARP, MIDVALE CORS ARP, and RED BUTTE CORS ARP.

The geographic position of the corner of sections 19, 24, 25, and 30, Township 6 South, Ranges 7 and 8 West, as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: 40°16'25.970" N.  
Longitude: 112°41'14.235" W., N.A.D. 1983,  
Network Accuracy = 0.200 meter at 95% confidence.

THE DEPENDENT RESURVEY A PORTION OF THE SOUTH BOUNDARY  
(FIRST STANDARD PARALLEL SOUTH),  
TOWNSHIP 5 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

---

Dependent Resurvey of a Portion of the South Boundary  
(First Standard Parallel South),  
Township 5 South, Range 8 West, Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
A.D. Ferron in 1871

---

Beginning at the standard corner of sections 2, 3, 34, and 35, on the south boundary of the township, monumented with a limestone, 13 x 8 x 4 inches, lying on its north face, plainly marked with 2 notches on east edge, and 4 notches on west edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

S C			
T 5 S		R 8 W	
S 34		S 35	
S 3		S 2	
T 6 S			
2007			

Bury the marked stone, inverted, alongside the aluminum post.

This corner is located under an old barbed wire fence, bears east and west, and is 2 ft. west of a fence corner with fences extending north and west.

From this corner, the standard corner of sections 1, 2, 35, and 36, bears N. 89°52.4' E., 80.404 chains distance; monumented with a limestone, 16 x 7 x 5 inches, firmly set, 12 inches below a layer of blow sand, plainly marked with 1 notch on east edge, 5 notches on west edge.

At this corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

S C			
T 5 S		R 8 W	
S 35		S 36	
S 2		S 1	
T 6 S			
2007			

Bury the marked stone, inverted, alongside the aluminum post.

THE DEPENDENT RESURVEY A PORTION OF THE SOUTH BOUNDARY  
(FIRST STANDARD PARALLEL SOUTH),  
TOWNSHIP 5 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

S. 89°53.0' W., along the south boundary of section 34.

- 39.838 Point for the 1/4 section corner of section 3 only, T. 6 S., R. 8 W., at midpoint between the closing corner of sections 3 and 4, T. 6 S., R. 8 W., and the standard corner of sections 2, 3, 34, and 35.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

T 5 S R 8 W

-----  
1/4 S 3  
T 6 S R 8 W

2007

Set a steel fence post along the west side of the aluminum post.

This corner is located 20 ft. north of the center line of a dirt road, bears east and west.

- 40.178 The standard 1/4 section corner of section 34 only, monumented with an iron post, 3 inches in diameter, firmly set, projecting 16 inches above ground, with brass cap incorrectly marked 1/4 SC S34 S3 1950. Found the 1875 stone corner monument, a limestone, 4 x 6 x 9 inches above ground, set alongside the iron post as described in the official record of the 1950-51 resurvey.

Remove the marks "S3" from the brass cap and set a steel fence post along the west side of the iron post.

This corner is located 20 ft. north of a dirt road, bears east and west. A spring trough is northwest of the corner.

---

Reestablishment of the Survey Executed by  
A.D. Ferron in 1871, and the Resurvey  
Executed by E. Bird in 1950-51.

---

N. 89°36.8' W., beginning new measurement.

- 38.687 Intersect the center line of Utah State Road No. 196, bears northwest and southeast.
- 39.498 The closing corner of sections 3 and 4, T. 6 S., R. 8 W., monumented with a damaged iron post, 2 1/2 inches in diameter, firmly set, broken at the ground surface. Found the brass cap lying alongside the corner, marked as described in the

THE DEPENDENT RESURVEY A PORTION OF THE SOUTH BOUNDARY  
(FIRST STANDARD PARALLEL SOUTH),  
TOWNSHIP 5 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

official record of the 1950-51 resurvey.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

T	5	S	R	8	W
S 34					
S	4		S	3	
T	6	S	R	8	W
C			C		
2007					

Bury the broken iron post alongside the aluminum post.

Set a steel fence post along the northeast side of the aluminum post.

This corner is located 43 ft. north of the center line of a gravel road, bears east and west.

- 39.989** Point for the standard corner of sections 33 and 34, at proportionate distance, falls in a cleared area where there is no remaining evidence of the 1950 iron post monument.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 29 inches in the ground, with aluminum cap marked:

S C						
T	5	S		R	8	W
S 33				S 34		
2007						

Set a steel fence post along the west side of the aluminum post.

This corner is located 43 ft. north of the center line of a gravel road, bears east and west.

**N. 89°36.8' W.**, along the south boundary of section 33.

- 39.989** The standard 1/4 section corner of section 33 only, monumented with an iron post, 1 inch diameter, projecting 12 inches above the ground, with brass cap marked as described in the official record of the 1950-51 resurvey.

Dependent Resurvey of a Portion of the South Boundary,  
Township 6 South, Range 8 West, Salt Lake Meridian, Utah

THE DEPENDENT RESURVEY A PORTION OF THE SOUTH BOUNDARY,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

Reestablishment of the Survey Executed by  
A.J. Stewart Sr. in 1875 and the Resurvey  
Executed by E. Bird in 1950-51

---

From the corner of Township 6 South, Ranges 7 and 8 West, monumented with an iron post, 3 inches diameter, firmly set, projecting 14 inches above the ground, with brass cap marked as described in the official record of the 1950-51 survey. Found the 1875 stone corner monument, a limestone, 14 x 7 x 9 inches above the ground, set alongside the iron post.

Found an L-shape post set along north side of the iron post.

S. 89°47.9' W., along the south boundary of section 36.

- 40.419 The 1/4 section corner of section 36 only, monumented with an iron post, 3 inches diameter, firmly set, projecting 13 inches above ground, with brass cap marked as described in the official record of the 1950-51 resurvey. Found the 1875 stone corner monument, a decayed limestone, 7 x 8 x 3 inches above ground, with no visible marks, set alongside the iron post.
- 

S. 89°00.5' W., beginning new measurement.

- 30.783 The closing corner of sections 1 and 2, T. 7 S., R. 8 W., bears South, 0.059 chains distance, monumented with an iron post, 3 inches diameter, firmly set, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1950-51 resurvey. Found the 1875 stone corner monument, a limestone, 15 x 10 x 4 inches, with no visible marks, loosely set alongside the iron post.
- 40.281 The corner of sections 35 and 36 only, monumented with an iron post, 3 inches diameter, firmly set, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1950-51 resurvey. Found the 1875 stone corner monument, a decayed limestone, 13 x 12 x 6 inches, with no visible marks, set flush with ground alongside the iron post.
- 

From the corner of sections 34 and 35 only, on the south boundary of the township, monumented with an iron post, 3 inches diameter, firmly set, projecting 5 inches above ground, with brass cap marked as described in the official record of the 1950-51 resurvey. Found the 1875 stone corner monument set along the west side of the iron post.

S. 89°48.5' W., along the south boundary of section 34.

THE DEPENDENT RESURVEY A PORTION OF THE SOUTH BOUNDARY,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

- 40.295 The 1/4 section corner of section 34 only, monumented with an iron post, 3 inches diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1950-51 resurvey.

This corner is located under a fence, bears east and west.

---

N. 89°51.8' W., beginning new measurement.

- 31.263 The closing corner of sections 3 and 4, T. 7 S., R. 8 W., bears South, 0.017 chains distance, monumented with an iron post, 3 inches diameter, firmly set, projecting 1 inch above ground, with brass cap marked as described in the official record of the 1950-51 resurvey.

This corner is located under a fence, bears east and west, and 13.2 ft. south of the center line of a dirt road.

- 40.208 The corner of sections 33 and 34 only, monumented with an iron post, 3 inches diameter, firmly set, projecting 9 inches above ground, with brass cap marked as described in the official record of the 1950-51 survey.

This corner is located under a fence, bears east and west, and 6.8 ft. south of the center of a dirt road, bears east and west.

---

Dependent Resurvey of the East Boundary,  
Township 6 South, Range 8 West, Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
A.J. Stewart Sr. in 1875

---

From the corner of Township 6 South, Ranges 7 and 8 West, hereinbefore described.

N. 0°19.8' W., between sections 31 and 36.

- 40.542 The 1/4 section corner of sections 31 and 36, monumented with a limestone, 11 x 9 x 5 inches, lying on its east face, plainly marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

THE DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 6 S	
R 8 W	R 7 W
1/4	
S 36	S 31
2007	

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the east side of the aluminum post.

---

N. 0°18.3' W., beginning new measurement.

**40.601** The corner of sections 25, 30, 31, and 36, monumented with a limestone, 16 x 11 x 6 inches, firmly set, projecting 4 inches above ground, marked with 1 notch on south edge and 5 notches on north edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with aluminum cap marked:

T 6 S	
R 8 W	R 7 W
S 25	S 30
S 36	S 31
2007	

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the northeast side of the aluminum post.

---

N. 0°16.2' W., between sections 25 and 30.

**32.885** Intersect the apparent center line of Utah State Road No. 199, bears northeast and southwest.

**37.593** Intersect the northwesterly right-of-way line of Utah State Road No. 199, hereinafter surveyed. This point of intersection is determined 200 feet distance from and at right angle to the apparent centerline of Utah State Road No. 199.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:



THE DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the north side of the aluminum post.

This corner is located 22 ft. east of the remnants of an old barbed wire fence, bears north and south.

N. 0°17.2' W., between sections 19 and 24.

40.196 The 1/4 section corner of sections 19 and 24, monumented with a limestone, 14 x 8 x 6 inches, firmly set, projecting 1 inch above ground, plainly marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T 6 S	
R 8 W	R 7 W
1/4	
S 24	S 19
2007	

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the northwest side of the aluminum post.

N. 0°22.8' W., beginning new measurement.

40.173 The corner of sections 13, 18, 19, and 24, monumented with a limestone, 15 x 13 x 4 inches, firmly set, projecting 8 inches above ground, plainly marked with 3 notches on south edge and 3 notches on north edge. Found an old cedar post, 5 ft. long, 6 inches diameter, set north of the corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 30 inches in the ground, with aluminum cap marked:

T 6 S	
R 8 W	R 7 W
S 13	S 18
S 24	S 19

2007

THE DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Bury the marked stone, inverted, alongside the aluminum post.

---

N. 0°20.2' W., between sections 13 and 18.

- 40.023 The 1/4 section corner of sections 13 and 18, monumented with a blue limestone, 14 x 8 x 5 inches, lying on its east face, plainly marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

```

T 6 S
R 8 W R 7 W
  1/4
  |
S 13 | S 18
  |
  2007

```

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the north side of the aluminum post.

---

N. 0°16.6' W., beginning new measurement.

- 20.054 Point for the N 1/16 section corner of sections 13 and 18. Found decayed wooden stakes lying nearby the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

```

N 1/16
  |
S 13 | S 18
  |
  2007

```

Set a steel fence post along the west side of the aluminum post.

- 40.108 The corner of sections 7, 12, 13, and 18, monumented with a decayed cedar post, 4 inches diameter, firmly set, projecting 12 inches above ground. This cedar post is similar to a cedar post set alongside the section corner 1 mile to the south, is harmoniously related to existing original corners, and is accepted as the best available evidence of the original corner position. Found 2 rusted steel fence posts set alongside the corner.

THE DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

T 6 S	
R 8 W R 7 W	
S 12	S 7
S 13	S 18

2007

Set a steel fence post along the west side of the aluminum post.

Re-set the cedar post alongside the aluminum post.

N. 0°17.5' W., between sections 7 and 12.

**20.066** Point for the S 1/16 section corner of sections 7 and 12.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

S 1/16	
S 12	S 7
2007	

Set a steel fence post along the east side of the aluminum post.

This corner is located 12 ft. south of the south edge of pavement of an asphalt road, bears east and west.

**40.132** The 1/4 section corner of sections 7 and 12, monumented with a blue limestone, 13 x 8 x 5 inches, firmly set, projecting 6 inches above the ground, plainly marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

THE DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

	T 6 S	
R 8 W		R 7 W
	1/4	
S 12		S 7
	2007	

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the north side of the aluminum post.

---

N. 0°39.0' W., beginning new measurement.

**40.046** The corner of sections 1, 6, 7, and 12, monumented with a limestone, 15 x 10 x 5 inches, firmly set, projecting 7 inches above ground, plainly marked with 5 notches on south edge and 1 notch on north edge. Found a steel fence post set along the southwest side of the corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

	T 6 S	
R 8 W		R 7 W
S 1		S 6
S 12		S 7
	2007	

Bury the marked stone, inverted, alongside the aluminum post.

This corner is located 21 ft. north of the center line of a dirt road, bears east and west, and 15 ft. south of a power line, bears east and west.

---

N. 0°01.7' E., between sections 1 and 6.

**40.042** The 1/4 section corner of sections 1 and 6, monumented with a gray sandstone, 14 x 8 x 5 inches, firmly set, projecting 5 inches above the ground, plainly marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

THE DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

	T 6 S	
R 8 W		R 7 W
	1/4	
S 1		S 6
	2007	

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the north side of the aluminum post.

---

N. 0°12.5' W., beginning new measurement.

20.028 Point for the N 1/16 section corner of sections 1 and 6.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

	T 6 S	
R 8 W		R 7 W
	N 1/16	
S 1		S 6
	2007	

Set a steel fence post along the southeast side of the aluminum post.

From this corner, a corner of barbed wire fences extending west, east, and north bears N. 14° W., 36.5 ft. distance.

40.056 The standard corner of Townships 5 and 6 South, Ranges 7 and 8 West, monumented with a limestone, 20 x 9 x 5 inches, firmly set, projecting 10 inches above ground, plainly marked with 6 notches on the north, south, east, and west edges. Found a steel fence post set along the northeast side of the corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

	SC	
	T 5 S	
R 8 W		R 7 W
S 36		S 31
S 1		S 6
	T 6 S	
	2007	

THE DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Bury the marked stone, inverted, alongside the aluminum post.

This corner is located 5 ft. east of a barbed wire fence line, bears north and south.

From this corner, the standard corner of sections 1, 2, 35 and 36, on the north boundary of the township, bears  $S.89^{\circ}56.1'W.$ , 80.305 chains distance, hereinbefore described.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
Township 6 South, Range 8 West, Salt Lake Meridian, Utah


Reestablishment of the Survey Executed by  
A.J. Stewart Sr. in 1875

From the corner of sections 35 and 36 only, on the south boundary of the township, hereinbefore described.

N.  $0^{\circ}42.8'$  W., between sections 35 and 36.

17.269 Intersect the southeasterly right-of-way line of Utah State Road No. 199, hereinafter surveyed. This point of intersection is determined 50 feet distance from and at right angle to the apparent centerline of Utah State Road No. 199.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:



2008

Bury a magnet beneath and set a steel fence post alongside the aluminum post.

This corner is located 1 ft. north of a barbed wire fence, bears northeast and southwest.

18.436 Intersect the apparent center line of Utah State Road No. 199, bears northeast and southwest.

40.906 The 1/4 section corner of sections 35 and 36, at a fence corner with barbed wire fences extending north, east, and west. This fence corner is harmoniously related to existing original corners and is accepted as the best available evidence of the original corner position.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,  
26 inches in the ground, with aluminum cap marked:

T 6 S R 8 W	
1/4	
S 35	S 36
2008	

---

N. 0°29.3' W., beginning new measurement.

- 40.360** The corner of sections 25, 26, 35, and 36, monumented with a decayed and fragmented limestone. The largest fragment is 18 x 8 x 6 inches, marked with 1 notch.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,  
28 inches in the ground, with aluminum cap marked:

T 6 S R 8 W	
S 26	S 25
S 35	S 36
2007	

Bury the fragmented stone alongside the aluminum post.

This corner is located under a barbed wire fence, bears north and south.

---


From the corner of sections 25, 30, 31, and 36, on the east boundary of the township, hereinbefore described.

S. 89°28.2' W., between sections 25 and 36.

- 26.766** Intersect the southeasterly right-of-way line of Utah State Road No. 199, hereinafter surveyed. This point of intersection is determined 50 feet distance from and at right angle to the apparent centerline of Utah State Road No. 199.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,  
26 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS



2007

Bury a magnet beneath and set a steel fence post alongside the aluminum post.


This corner is located alongside a barbed wire fence, bears northeast and southwest.

**27.759** Intersect the apparent center line of Utah State Road No. 199, bears northeast and southwest.

**31.734** Intersect the northwesterly right-of-way line of Utah State Road No. 199, hereinafter surveyed. This point of intersection is determined 200 feet distance from and at right angle to the apparent centerline of Utah State Road No. 199.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T 6 S R 8 W



S 36  
2007

Bury a magnet beneath and set a steel fence post alongside the aluminum post.

**40.473** The 1/4 section corner of sections 25 and 36, monumented with a limestone, 15 x 12 x 7 inches, firmly set, projecting 6 inches above the ground, marked 1/4 on north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

T 6 S R 8 W  
          S 25  
1/4 ———  
          S 36  
          2007

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the west side of the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

---

S. 89°30.7' W., beginning new measurement.

40.609 The corner of sections 25, 26, 35, and 36.

---

N. 0°27.2' W., between sections 25 and 26.

40.358 Point for the 1/4 section corner of sections 25 and 26, determined latitudinally by proportionate distance, and longitudinally by an ancient barbed wire fence line extending north and south; there is no remaining evidence of the 1875 cedar post monument.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{T 6 S R 8 W} \\ \quad \quad \quad 1/4 \\ \quad \quad \quad | \\ \text{S 26} \quad | \quad \text{S 25} \\ \quad \quad \quad | \\ \quad \quad \quad 2007 \end{array}$$

This corner is located in a swampy area.

---

N. 0°16.1' W., beginning new measurement.

20.180 Point for the N 1/16 section corner of sections 25 and 26.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{N 1/16} \\ \quad \quad \quad | \\ \text{S 26} \quad | \quad \text{S 25} \\ \quad \quad \quad | \\ \quad \quad \quad 2007 \end{array}$$

From this corner, a fence corner with barbed wire fences extending east and south bears N. 59° W., 4 ft. distance.

40.360 The corner of sections 23, 24, 25, and 26, monumented with an old cedar post, 6 inches diameter, firmly set, projecting 4 ft. above ground. This cedar post is harmoniously related to existing original corners, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

T 6 S R 8 W	
S 23	S 24
S 26	S 25

2007

Re-set the cedar post along the north side of the aluminum post.

From the corner of sections 19, 24, 25, and 30, on the east boundary of the township, hereinbefore described.

S. 89°14.9' W., between sections 24 and 25.

**40.778** The 1/4 section corner of sections 24 and 25, monumented with a decayed limestone, 12 x 9 x 7 inches, firmly set, projecting 6 inches above the ground, under a barbed wire fence, bears north and south. The stone is too decayed to read any marks. Found a steel fence post set southeast of this corner, 1 ft. distance.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T 6 S R 8 W	
S 24	
1/4	S 25
2007	

Bury the decayed stone alongside the aluminum post.

S. 89°54.7' W., beginning new measurement.

**40.346** The corner of sections 23, 24, 25, and 26.

N. 0°07.1' E., between sections 23 and 24.

**20.146** Point for the S 1/16 section corner of sections 23 and 24.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

S 1/16	
S 23	S 24
2007	

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

This corner is located 2 ft. west of a barbed wire fence,  
bears north and south.

- 40.292 The 1/4 section corner of sections 23 and 24, monumented with  
a decayed limestone, 16 x 13 x 6 inches, firmly set,  
projecting 8 inches above the ground, marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,  
26 inches in the ground, with aluminum cap marked:

T 6 S R 8 W	
1/4	
S 23	S 24
2007	

Bury the marked stone, inverted, alongside the aluminum post.

This corner is located under a barbed wire fence, bears north  
and south.

---

N. 0°06.6' E., beginning new measurement.

- 40.035 The corner of sections 13, 14, 23, and 24, monumented with a  
limestone, 16 x 14 x 6 inches, firmly set, projecting 6 inches  
above ground, plainly marked with 3 notches on south edge and  
1 notch on east edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,  
28 inches in the ground, with aluminum cap marked:

T 6 S R 8 W	
S 14	S 13
S 23	S 24
2007	

Bury the marked stone, inverted, alongside the aluminum post.

This corner is located 2 ft. south of a fence corner, with  
barbed wire fences extending west and south.

---

From the corner of sections 13, 18, 19, and 24, on the east  
boundary of the township, hereinbefore described.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

S. 89°35.7' W., between sections 13 and 24.

- 40.064 The 1/4 section corner of sections 13 and 24, monumented with a decayed and fragmented limestone. The fragments make up a stone, 11 x 10 x 4 inches. The stone is too decayed to read any marks. Found remains of old wood posts alongside the stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

```

      T 6 S R 8 W
        S 13
1/4 —————
        S 24
        2007

```

Bury the fragmented stone, alongside the aluminum post.

Set a steel fence post, along the east side of the aluminum post.

---

S. 89°29.8' W., beginning new measurement.

- 40.414 The corner of sections 13, 14, 23, and 24.

---

N. 0°07.8' W., between sections 13 and 14.

- 40.084 Point for the 1/4 section corner of sections 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with aluminum cap marked:

```

      T 6 S R 8 W
        1/4
      S 14 | S 13
        2007

```

Set a steel fence post along the east side of the aluminum post.

- 80.168 The corner of sections 11, 12, 13, and 14, monumented by person(s) unknown, with a rebar, 1/2 inch in diameter, firmly set, projecting 1 inch above ground. This rebar is at a fence corner to barbed wire fences extending west and north, is harmoniously related to existing original corners, and is

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

T 6 S R 8 W	
S 11	S 12
S 14	S 13

2007

Bury the rebar inside the aluminum post.

---

From the corner of sections 7, 12, 13, and 18, on the east boundary of the township, hereinbefore described.

N. 89°48.9' W., between sections 12 and 13.

40.002 The 1/4 section corner of sections 12 and 13, monumented with a limestone, 13 x 9 x 5 inches, lying on its south face, marked 1/4 on north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T 6 S R 8 W	
S 12	
1/4	—————
S 13	
2007	

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the east side of the aluminum post.

---

S. 88°57.6' W., beginning new measurement.

40.215 The corner of sections 11, 12, 13, and 14.

---

N. 0°22.9' W., between sections 11 and 12.

40.861 The 1/4 section corner of sections 11 and 12, monumented with a decayed limestone, 14 x 10 x 5 inches, lying on west face, marked 1/4 on west face.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,  
27 inches in the ground, with aluminum cap marked:

T 6 S	R 8 W
1/4	
S 11	S 12
2007	

Bury the marked stone, inverted, alongside the aluminum post.

This corner is located 2 ft. west of a barbed wire fence,  
bears north and south, and under a powerline, bears north and  
south.

---

N. 0°17.8' W., beginning new measurement.

- 40.325 The corner of sections 1, 2, 11, and 12, at an 8 ft. tall  
cedar fence post with fences extending east, west, and south.  
This fence corner is harmoniously related to existing original  
corners and is accepted as the best available evidence of the  
original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,  
27 inches in the ground, with aluminum cap marked:

T 6 S		R 8 W	
S 2		S 1	
S 11		S 12	
2007			

In an effort to verify this corner's position, we find the  
standard corner of sections 1, 2, 35, and 36, on the north  
boundary of the township bears N. 0°18.7' W., 79.598 chains  
distance; hereinbefore described.

---

From the corner of sections 1, 6, 7, and 12, on the east  
boundary of the township, hereinbefore described.

N. 89°42.4' W., between sections 1 and 12.

- 40.008 Point for the 1/4 section corner of sections 1 and 12, at  
proportionate distance, falls in a dirt road, bears east and  
west; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

30 inches in the ground, with aluminum cap marked:

T 6 S R 8 W  
S 1  
1/4 —————  
S 12  
2007

80.016 The corner of sections 1, 2, 11, and 12.

From the corner of sections 34 and 35 only, on the south boundary of the township, hereinbefore described.

N. 0°17.6' W., between sections 34 and 35.

40.152 The 1/4 section corner of sections 34 and 35, at a fence corner with old barbed wire fences extending north and east. This fence corner is harmoniously related to existing original corners and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

T 6 S R 8 W  
1/4  
S 34 | S 35  
2007

This corner is located 16 ft. north of the center line of a dirt road.

N. 0°17.1' W., beginning new measurement.

40.286 The corner of sections 26, 27, 34, and 35, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1950-51 resurvey. Found the 1875 stone corner monument, a limestone, 10 x 6 x 10 inches above ground, set along the east side of the iron post.

This corner is located 1.3 ft. east of a fence corner with fences extending north and east.

N. 0°20.6' W., between sections 26 and 27.

40.339 The 1/4 section corner of sections 26 and 27, monumented with


DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

a limestone, 15 x 10 x 8 inches, firmly set, projecting 3 inches above ground, marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:



Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the north side of the aluminum post.

This corner is located 3 ft. east of a new barbed wire fence (with steel posts), bears north and south, and under the remains of an ancient barbed wire fence (with cedar posts), bears north and south.

N. 0°07.7' W., beginning new measurement.

- 40.331** The corner of sections 22, 23, 26, and 27, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1950-51 resurvey. Found the 1875 stone corner monument, a limestone, 10 x 3 x 6 inches above ground, set along the west side of the iron post.

This corner is located 2 ft. east of a new barbed wire fence (with steel posts), bears north and south, and under the remains of an ancient barbed wire fence (with cedar posts), bears north and south.

N. 0°06.5' E., between sections 22 and 23.

- 40.026** The 1/4 section corner of sections 22 and 23, monumented with a limestone, 10 x 8 x 6 inches, lying on west face, marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

T 6 S R 8 W	
1/4	
S 22	S 23
2007	

Bury the marked stone, inverted, alongside the aluminum post.

This corner is located 2.3 ft. northeast of a new fence corner with fences extending south and west, and under the remains of an ancient barbed wire fence (with cedar posts), bears north and south.

---

N. 0°04.6' E., beginning new measurement.

**40.249** The corner of sections 14, 15, 22, and 23, monumented with a decayed limestone, 17 x 12 x 8 inches, firmly set, projecting 6 inches above ground. The stone is too decayed to read any marks.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with aluminum cap marked:

T 6 S R 8 W	
S 15	S 14
S 22	S 23
2007	

Bury the stone, inverted, alongside the aluminum post.

This corner is located under a barbed wire fence, bears east and west.

---

From the corner of sections 13, 14, 23, and 24.

S. 88°46.4' W., between section 14 and 23.

**20.003** Point for the E 1/16 section corner of sections 14 and 23.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

E 1/16	S 14
	S 23
	2007

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

This corner is located 1 ft. south of a barbed wire fence,  
bears east and west.

- 40.006 Point for the 1/4 section corner of sections 14 and 23, at  
proportionate distance; there is no remaining evidence of the  
original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,  
26 inches in the ground, with aluminum cap marked:

```

      T 6 S R 8 W
        S 14
1/4 —————
        S 23
        2007
    
```

This corner is located under a barbed wire fence, bears east  
and west.

- 80.012 The corner of sections 14, 15, 22, and 23.

N. 1°21.2' W., between sections 14 and 15.

- 40.521 The 1/4 section corner of sections 14 and 15, monumented with  
a limestone, 12 x 11 x 7 inches, firmly set, projecting 5  
inches above ground, plainly marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,  
28 inches in the ground, with aluminum cap marked:

```

      T 6 S R 8 W
        1/4
      S 15 | S 14
        2007
    
```

Bury the marked stone, inverted, alongside the aluminum post.

N. 0°11.4' W., beginning new measurement.

- 40.415 The corner of sections 10, 11, 14, and 15, monumented with a  
decayed limestone, 20 x 14 x 6 inches, firmly set, projecting  
6 inches above ground, marked with 2 visible notches.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,  
28 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

T 6 S R 8 W  

S 10	S 11
S 15	S 14

2007

Bury the marked stone, inverted, alongside the aluminum post.

This corner is located 2 ft. west of an old fence post with a barbed wire fence extending east, at the south end of a cultivated field.

From the corner of sections 11, 12, 13, and 14.

S. 89°22.2' W., between sections 11 and 14.

20.122 Point for the E 1/16 section corner of sections 11 and 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 30 inches in the ground, with aluminum cap marked:

E 1/16	S 11
	S 14
	2007

This corner is located 2 ft. south of a barbed wire fence, bears east and west.

40.244 The 1/4 section corner of sections 11 and 14, monumented with a limestone, 12 x 11 x 5 inches, firmly set, projecting 4 inches above ground, plainly marked 1/4 on north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with aluminum cap marked:

T 6 S R 8 W	
	S 11
1/4	
	S 14
	2007

Bury the marked stone, inverted, alongside the aluminum post.

This corner is located 1 ft. west of a fence, bears north and south and 1.5 ft. east of a cedar stump.

S. 89°16.5' W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

40.648 The corner of sections 10, 11, 14, and 15.

---

N. 0°21.2' W., between sections 10 and 11.

40.530 The 1/4 section corner of sections 10 and 11, monumented with a decayed limestone, 14 x 8 x 4 inches, firmly set, projecting 4 inches above ground, marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

T 6 S R 8 W	
1/4	
S 10	S 11
2007	

Bury the marked stone, inverted, alongside the aluminum post.

This corner is located along the west side of a tall cedar post in a barbed wire fence, bears north and south.

---

N. 0°11.2' W., beginning new measurement.

40.311 Point for the corner of sections 2, 3, 10, and 11, determined latitudinally by proportionate measurement and longitudinally by a barbed wire fence line extending north and south; there is no remaining evidence of the original monument.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

T 6 S R 8 W	
S 3	S 2
S 10	S 11
2007	

---

From the corner of sections 1, 2, 11, and 12.

N. 89°50.5' W., between sections 2 and 11.

40.159 The 1/4 section corner of sections 2 and 11, at a fence corner with barbed wire fences extending north, south, and east. This fence corner is harmoniously related to existing original corners and is accepted as the best available evidence of the original corner position.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,  
27 inches in the ground, with aluminum cap marked:

T 6 S R 8 W  
S 2  
1/4 —————  
S 11  
2007

---

S. 88°00.5' W., beginning new measurement.

40.636 The corner of sections 2, 3, 10, and 11.

---

N. 0°03.6' W., between sections 2 and 3.

40.310 Point for the 1/4 section corner of sections 2 and 3, at  
proportionate distance; there is no remaining evidence of the  
original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,  
27 inches in the ground, with aluminum cap marked:

T 6 S R 8 W  
1/4  
S 3 | S 2  
2007

This corner is located under a barbed wire fence, bears north  
and south, and 61.2 ft. south of a corner of fences extending  
north, south, and east.

80.721 The standard corner of sections 2, 3, 34, and 35, on the north  
boundary of the township, hereinbefore described.

---

Reestablishment of the Survey Executed by  
A.J. Stewart Sr. in 1875 and  
the Resurvey Executed by E. Bird in 1950-51

---

From the corner of sections 33 and 34 only, on the south  
boundary of the township, hereinbefore described.

N. 0°06.9' E., between sections 33 and 34.

40.143 The 1/4 section corner of sections 33 and 34, monumented with  
an iron post, 2 1/2 inches diameter, firmly set, projecting 5

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

inches above ground, with brass cap marked as described in the official record of the 1950-51 resurvey.

---

N. 0°07.4' E., beginning new measurement.

- 40.132 The corner of sections 27, 28, 33, and 34, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above a collar of stone, 3 ft. base, with brass cap marked as described in the official record of the 1950-51 resurvey.

---

From the corner of sections 26, 27, 34, and 35.

S. 89°51.3' W., between sections 27 and 34.

- 39.944 The 1/4 section corner of sections 27 and 34, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1950-51 resurvey.

---

S. 89°51.4' W., beginning new measurement.

- 23.530 Point of intersection with the easterly right-of-way line of Utah State Road No. 196, hereinafter described.

- 25.042 Intersect the center line of Utah State Road No. 196, bears northwest and southeast.

- 39.970 The corner of sections 27, 28, 33, and 34.

---

N. 0°08.1' W., between sections 27 and 28.

- 40.175 The 1/4 section corner of sections 27 and 28, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1950-51 resurvey.

---

N. 0°08.3' W., beginning new measurement.

- 40.154 The corner of sections 21, 22, 27, and 28, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 16 inches above the ground with brass cap marked as described in the official record of the 1950-51 resurvey.

---

From the corner of sections 22, 23, 26, and 27.

S. 89°37.4' W., between sections 22 and 27.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

39.877 The 1/4 section corner of sections 22 and 27, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1950-51 resurvey.

---

S. 89°35.9' W., beginning new measurement.

26.370 Point of intersection with the easterly right-of-way line of Utah State Road No. 196, hereinafter described.

27.886 Intersect the center line of Utah State Road No. 196, bears northwest and southeast.

39.880 The corner of sections 21, 22, 27, and 28.

---

N. 0°03.5' E., between sections 21 and 22.

40.152 The 1/4 section corner of sections 21 and 22, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1950-51 resurvey.

---

N. 0°01.6' E., beginning new measurement.

40.156 The corner of sections 15, 16, 21, and 22, monumented with an iron post, 2 1/2 inches diameter, projecting 12 inches above the ground with brass cap marked as described in the official record of the 1950-51 resurvey. Found the 1875 stone corner monument, a white limestone, set along the west side of the iron post.

From this corner, the United States Coast and Geodetic Survey Benchmark "X 62", set in 1934, bears N. 88°21.2' E., 4.786 chains distance, monumented with a standard brass disk, 3 1/2 inches diameter, seated in a concrete monument, 14 inches square, projecting 5 inches above the ground, marked X 62 1934.

---

Reestablishment of the Survey Executed by  
A.J. Stewart Sr. in 1875

---

From the corner of sections 14, 15, 22, and 23.

S. 89°40.0' W., between sections 15 and 22.

20.004 Point for the E 1/16 section corner of sections 15 and 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

S 15  
E 1/16 —————  
S 22  
2007

Set a steel fence post along the east side of the aluminum post.

This corner is located 21 ft. north of a barbed wire fence, bears east and west.

- 40.008 The 1/4 section corner of sections 15 and 22, monumented with a gray limestone, 14 x 12 x 5 inches, lying on its east side, plainly marked 1/4 on north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

T 6 S R 8 W  
S 15  
1/4 —————  
S 22  
2007

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the west side of the aluminum post.

This corner is located 42.7 ft. north of a barbed wire fence, bears east and west.

---

S. 89°36.1' W., beginning new measurement.

- 29.475 The easterly right-of-way line marker (at an offset of 100 ft. from the center line) of Utah State Road No. 196, hereinafter described.
- 30.987 Intersect the center line of Utah State Road No. 196, bears northwest and southeast.
- 31.746 The westerly right-of-way line marker (at an offset of 50 ft. from the center line) of Utah State Road No. 196, hereinafter described.
- 39.801 The corner of sections 15, 16, 21, and 22.

---

Reestablishment of the Survey Executed by  
A.J. Stewart Sr. in 1875 and  
the Resurvey Executed by E. Bird in 1950-51

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

---

N. 0°23.3' W., between sections 15 and 16.

- 40.256 The 1/4 section corner of sections 15 and 16, monumented with an iron post, 3 inches diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1950-51 resurvey. Found the 1875 stone corner monument, a limestone, 7 x 7 x 3 inches above ground, set along the north side of the iron post.

---

N. 0°25.0' W., beginning new measurement.

- 20.243 Point for the N 1/16 section corner of sections 15 and 16.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

	N 1/16	
S 16		S 15
	2007	

Set a steel fence post along the west side of the aluminum post.

- 40.486 The corner of sections 9, 10, 15, and 16, monumented with an iron post, 3 inches diameter, firmly set, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1950-51 resurvey.

---

Reestablishment of the Survey Executed by  
A.J. Stewart Sr. in 1875

---

From the corner of sections 10, 11, 14, and 15.

S. 89°29.9' W., between sections 10 and 15.

- 39.635 Point for the 1/4 section corner of sections 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

	T 6 S R 8 W
	S 10
1/4	-----
	S 15
	2007

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

Set a steel fence post along the SW side of the aluminum post.

This corner is located 3 ft. west of a barbed wire fence, bears NW and SE, and 13 ft. east of the center line of a gravel road, bears NW and SE.

- 71.522 Point of intersection with the easterly right-of-way line of Utah State Road No. 196, hereinafter described.
- 73.037 Intersect the center line of Utah State Road No. 196, bears northwest and southeast.
- 79.270 The corner of sections 9, 10, 15, and 16.

Reestablishment of the Survey Executed by  
A.J. Stewart Sr. in 1875 and  
the Resurvey Executed by E. Bird in 1950-51

N. 0°19.8' W., between sections 9 and 10.

- 40.490 The 1/4 section corner of sections 9 and 10, monumented with an iron post, 3 inches diameter, firmly set, projecting 11 inches above ground, with brass cap marked as described in the official record of the 1950-51 resurvey. Found the 1875 stone corner monument, a limestone, 4 x 4 x 3 inches above ground, set along the north side of the iron post.

N. 0°32.3' W., beginning new measurement.

- 40.456 The corner of sections 3, 4, 9, and 10, monumented with an iron post, 3 inches diameter, firmly set, projecting 10 inches above ground, with brass cap marked as described in the official record of the 1950-51 resurvey. Found the 1875 stone corner monument, a limestone, 6 x 6 x 5 inches above ground, set along the NW side of the iron post.

Reestablishment of the Survey Executed by  
A.J. Stewart Sr. in 1875

From the corner of sections 2, 3, 10, and 11.

N. 89°58.4' W., between sections 3 and 10.

- 39.244 The 1/4 section corner of sections 3 and 10, at a fence post with an ancient barbed wire fence line extending south. A land document is inside of an old, rusted can attached to the fence post. This fence post is harmoniously related to existing original corners, and is accepted as the best available

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,  
27 inches in the ground, with aluminum cap marked:

T 6 S R 8 W  
S 3  
1/4 —————  
S 10  
2007

This corner is located 3 ft. east of the east edge of a gravel  
road, bears NE and south.

---

S. 89°07.8' W., beginning new measurement.

36.551 Intersect the center line of Utah State Road No. 196, bears  
northwest and southeast.

40.240 The corner of sections 3, 4, 9, and 10.

---

Reestablishment of the Survey Executed by  
A.J. Stewart Sr. in 1875 and  
the Resurvey Executed by E. Bird in 1950-51

---

N. 0°17.7' W., between sections 3 and 4.

40.034 The 1/4 section corner of sections 3 and 4, monumented with an  
iron post, 3 inches diameter, firmly set, projecting 10 inches  
above ground, with brass cap marked as described in the  
official record of the 1950-51 resurvey. Found the 1875 stone  
corner monument, a limestone, 7 x 4 x 9 inches above ground,  
set along the south side of the iron post.

---

N. 0°07.4' W., beginning new measurement.

41.466 The closing corner of sections 3 and 4, on the north boundary  
of the township, hereinbefore described.

---

The Subdivision of Section 10,  
Township 6 South, Range 8 West, Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 10 and 15.

N. 0°00.1' W., on the N-S center line of section 10.

THE SUBDIVISION OF SECTION 10,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.514 Point for the center 1/4 section corner of section 10 at the intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

T 6 S R 8 W

C 1/4 S 10

2007

Set a steel fence post along the SW side of the aluminum post.

This corner is located 13 ft. east of the east edge of a gravel road, bears north and south, and 12 ft. west of a barbed wire fence, bears north and south.

- 81.206 The 1/4 section corner of sections 3 and 10.

---

From the 1/4 section corner of sections 10 and 11.

S. 89°28.1' W., on the E-W center line of section 10.

- 39.381 The center 1/4 section corner of section 10.

- 72.837 Point of intersection with the easterly right-of-way line of Utah State Road No. 196, hereinafter described.

- 74.354 Intersect the center line of Utah State Road No. 196, bears northwest and southeast.

- 79.243 The 1/4 section corner of sections 9 and 10.

---

The Subdivision of Section 12,  
Township 6 South, Range 8 West, Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 12 and 13.


N. 0°28.9' W., on the N-S center line of section 12.

- 20.035 Point for the center S 1/16 section corner of section 12.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 12,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS



This corner is located 3 ft. north of the north edge of pavement of an asphalt road, bears east and west.

40.070 Point for the center 1/4 section corner of section 12 at the intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

T 6 S R 8 W

C 1/4 S 12

2007

Set a steel fence post along the west side of the aluminum post.

80.254 The 1/4 section corner of sections 1 and 12.

From the 1/4 section corner of sections 7 and 12, on the east boundary of the township, hereinbefore described.

N. 89°54.5' W., on the E-W center line of section 12.

40.129 The center 1/4 section corner of section 12.

80.269 The 1/4 section corner of sections 11 and 12.

From the S 1/16 section corner of sections 7 and 12, on the east boundary of the township.

N. 89°51.6' W., on the E-W center line of the SE 1/4 of section 12.

40.066 The center S 1/16 section corner of section 12.

The Subdivision of Section 14,  
Township 6 South, Range 8 West, Salt Lake Meridian, Utah

From the 1/4 section corner of sections 14 and 23.

N. 0°18.5' W., on the N-S center line of section 14.

THE SUBDIVISION OF SECTION 14,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

40.304 Point for the center 1/4 section corner of section 14 at the intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

T 6 S R 8 W

C 1/4 S 14

2007

80.582 The 1/4 section corner of sections 11 and 14.

---

From the 1/4 section corner of sections 13 and 14.

S. 89°05.3' W., on the E-W center line of section 14.

20.062 Point for the center E 1/16 section corner of section 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

E 1/16  
C ————— C

S 14

2007

This corner is located 4 ft. west of a barbed wire fence, bears north and south.

40.124 The center 1/4 section corner of section 14.

80.862 The 1/4 section corner of sections 14 and 15.

---

From the center E 1/16 section corner of section 14.

N. 0°13.2' W., on the N-S center line of the NE 1/4 of section 14.

40.181 The E 1/16 section corner of sections 11 and 14.

---

From the E 1/16 section corner of sections 14 and 23.

N. 0°13.2 W., on the N-S center line of the SE 1/4 of section 14.

40.194 The center E 1/16 section corner of section 14.

---

THE SUBDIVISION OF SECTION 15,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 15,  
Township 6 South, Range 8 West, Salt Lake Meridian, Utah


---

From the 1/4 section corner of sections 15 and 22.

N. 0°30.8' W., on the N-S center line of section 15.

- 40.365 Point for the center 1/4 section corner of section 15 at the intersection with the E-W center line, not monumented.
- 60.589 Point for the center N 1/16 section corner of section 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:



Set a steel fence post on the south side of the aluminum post.

This corner is located 32 ft. south of a barbed wire fence, bears east and west.

- 80.813 The 1/4 section corner of sections 10 and 15.
- 

From the 1/4 section corner of sections 14 and 15.

S. 89°26.8' W., on the E-W center line of section 15.

- 39.410 Point for the center 1/4 section corner of section 15.
- 71.602 Intersect the center line of Utah State Road No. 196, bears northwest and southeast.
- 72.362 Point of intersection with the westerly right-of-way line of Utah State Road No. 196, hereinafter described.
- 79.118 The 1/4 section corner of sections 15 and 16.
- 

From the center N 1/16 section corner of section 15.

S. 89°28.3' W., on the E-W center line of the NW 1/4 of section 15.

- 31.283 Point of intersection with the easterly right-of-way line (at an offset of 100 ft. from the center line) of Utah State Road No. 196, hereinafter described.

THE SUBDIVISION OF SECTION 15,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

- 32.797 Intersect the center line of Utah State Road No. 196, bears northwest and southeast.
- 33.557 Point of intersection with the westerly right-of-way line (at an offset of 50 ft. from the center line) of Utah State Road No. 196, hereinafter described.
- 39.671 The N 1/16 section corner of sections 15 and 16.

The Subdivision of Section 22,  
Township 6 South, Range 8 West, Salt Lake Meridian, Utah

- From the 1/4 section corner of sections 22 and 27.
- N. 0°00.4' W., on the N-S center line of section 22.
- 40.082 Point for the center 1/4 section corner of section 22 at the intersection with the E-W center line.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:
- T 6 S R 8 W  
C 1/4 S 22  
2007
- Set a steel fence post along the east side of the aluminum post.
- 80.304 The 1/4 section corner of sections 15 and 22.

- From the 1/4 section corner of sections 22 and 23.
- S. 89°42.1' W., on the E-W center line of section 22.
- 19.977 Point for the center E 1/16 section corner of section 22.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

E 1/16  
C ————— C  
S 22  
2007

Set a steel fence post along the west side of the aluminum post.

THE SUBDIVISION OF SECTION 22,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

This corner is located 17 ft. east of a barbed wire fence, bears north and south.

- 39.954 The center 1/4 section corner of section 22.
- 67.878 Point of intersection with the easterly right-of-way line of Utah State Road No. 196, hereinafter described.
- 69.396 Intersect the center line of State Road No. 196, bears northwest and southeast.
- 79.782 The 1/4 section corner of sections 21 and 22.

From the center E 1/16 section corner of section 22.

N. 0°02.1' E., on the N-S center line of the NE 1/4 of section 22.

- 40.236 The E 1/16 section corner of sections 15 and 22.

The Subdivision of Section 24,  
Township 6 South, Range 8 West, Salt Lake Meridian, Utah

From the 1/4 section corner of sections 24 and 25.

N. 0°10.0' E., on the N-S center line of section 24.

- 20.241 Point for the center S 1/16 section corner of section 24.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{C} \\ | \\ \text{S } 1/16 \quad | \quad \text{S } 24 \\ | \\ \text{C} \\ 2007 \end{array}$$

Set a steel fence post along the west side of the aluminum post.

This corner is located 10 ft. north of a fence corner, with fences extending south and west.

- 40.482 Point for the center 1/4 section corner of section 24 at the intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 24,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

T 6 S R 8 W

C 1/4 S 24

2007

Set a steel fence post along the east side of the aluminum post.

80.620 The 1/4 section corner of sections 13 and 24.

---

From the 1/4 section corner of sections 19 and 24, on the east boundary of the township, hereinbefore described.

S. 89°38.7' W., on the E-W center line of section 24.

40.452 The center 1/4 section corner of section 24.

80.829 The 1/4 section corner of sections 23 and 24.

---

From the center S 1/16 section corner of section 24.

S. 89°46.6' W., on the E-W center line of the SW 1/4 of section 24.

40.362 The S 1/16 section corner of sections 23 and 24.

---

The Subdivision of Section 25,  
Township 6 South, Range 8 West, Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 25 and 36.

N. 0°32.6' W., on the N-S center line of section 25.

40.420 Point for the center 1/4 section corner of section 25 at the intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

T 6 S R 8 W

C 1/4 S 25

2007


Set a steel fence post along the west side of the aluminum post.

60.428 Point for the center N 1/16 section corner of section 25.

THE SUBDIVISION OF SECTION 25,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:



Set a steel fence post along the east side of the aluminum post.

A fence corner with fences extending north and west bears S. 65° W., 21 ft. distance.

80.436 The 1/4 section corner of sections 24 and 25.

---

From the 1/4 section corner of sections 25 and 30, on the east boundary of the township, hereinbefore described.

S. 89°25.7' W., on the E-W center line of section 25.

40.662 Point for the center 1/4 section corner of section 25.

81.205 The 1/4 section corner of sections 25 and 26.

---

From the center N 1/16 section corner of section 25.

S. 89°40.0' W., on the E-W center line of the NW 1/4 of section 25.

40.444 The N 1/16 section corner of sections 25 and 26.

---

The Subdivision of Section 34,  
Township 6 South, Range 8 West, Salt Lake Meridian, Utah

---

From the 1/4 section corner of section 34 only, on the south boundary of the township.

N. 0°02.7' W., on the N-S center line of section 34.

40.265 Point for the center 1/4 section corner of section 34 at the intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 34,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

T 6 S R 8 W

C 1/4 S 34

2007

Set a steel fence post along the NE side of the aluminum post.

- 41.985 Intersect the center line of Utah State Road No. 196, bears northwest and southeast.
- 80.471 The 1/4 section corner of sections 27 and 34.

From the 1/4 section corner of sections 34 and 35.

S. 89°58.0' W., on the E-W center line of section 34.

- 37.245 Intersect the center line of Utah State Road No. 196, bears northwest and southeast.
- 40.116 The center 1/4 section corner of section 34.
- 80.208 The 1/4 section corner of sections 33 and 34.

The Survey of a Portion of the Right-of-Way Lines of Utah  
State Road No. 196,  
Township 6 South, Range 8 West, Salt Lake Meridian, Utah

**Note:** The right-of-way lines of Utah State Road No. 196 (SR 196) are determined from existing survey markers set in 1951 by the Utah Department of Transportation (UDOT), Project AD-1. All stations cited herein refer to stationing labels on the 1951 official drawing sheets of Project AD-1, on file at UDOT.

From the easterly right-of-way line marker at a point of circular tangency, Station No. 146+16.3, monumented with an iron post, 2 inches diameter, firmly set, projecting 7 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY.

There is no evidence of a westerly right-of-way line marker at this station.

N. 2°13.0' W., on the easterly right-of-way line of SR 196.

- 0.420 The point at the intersection with the section line between sections 27 and 34.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

THE SURVEY OF A PORTION OF THE RIGHT-OF-WAY LINES OF UTAH  
STATE ROAD NO. 196,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

	T 6 S
ROW	S 27
SR196	S 34
	R 8 W

2007

Bury a magnet beneath and set a steel fence post alongside the aluminum post.

- 20.950** The easterly right-of-way line marker at Station No. 160+00 of SR 196, monumented with an iron post, 2 inches diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY,

From which

the westerly right-of-way line marker bears S. 87°48.8' W., 3.030 chains distance, monumented with an iron post, 2 inches diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY.

---

N. 2°13.3' W., beginning new measurement.

- 15.145** Point for the easterly right-of-way line marker at Station No. 170+00 of SR 196, there is no evidence of an easterly right-of-way line marker at this station,

From which

the westerly right-of-way line marker bears S. 87°46.7' W., 3.035 chains distance, monumented with an iron post, 2 inches diameter, firmly set, projecting 8 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY.

- 30.280** The easterly right-of-way line marker at Station No. 180+00 of SR 196, monumented with an iron post, 2 inches diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY,

From which

the westerly right-of-way line marker bears S. 87°52.5' W., 3.032 chains distance, monumented with an iron post, 2 inches diameter, firmly set, projecting 7 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY.

THE SURVEY OF A PORTION OF THE RIGHT-OF-WAY LINES OF UTAH  
STATE ROAD NO. 196,  
CHAINS TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

---

N. 2°12.9' W., beginning new measurement.

- 15.143 The easterly right-of-way line marker at Station No. 190+00 of SR 196, monumented with an iron post, 2 inches diameter, firmly set, projecting 9 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY,

From which

the westerly right-of-way line marker bears S. 87°40.5' W., 3.032 chains distance, monumented with an iron post, 2 inches diameter, firmly set, projecting 7 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY.

---

N. 2°13.8' W., beginning new measurement.

- 14.490 The point at the intersection with the section line between sections 22 and 27, not monumented.
- 15.147 The easterly right-of-way line marker at Station No. 200+00 of SR 196, monumented with an iron post, 2 inches diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY,

From which

the westerly right-of-way line marker bears S. 87°54.4' W., 3.032 chains distance, monumented with an iron post, 2 inches diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY.

---

N. 2°13.5' W., beginning new measurement.

- 15.149 The easterly right-of-way line marker at Station No. 210+00 of SR 196, monumented with an iron post, 2 inches diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY,

From which

the westerly right-of-way line marker bears S. 87°37.1' W., 3.030 chains distance, monumented with an iron post, 2 inches diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY.

THE SURVEY OF A PORTION OF THE RIGHT-OF-WAY LINES OF UTAH  
STATE ROAD No. 196,  
CHAINS            TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

---

N. 2°13.9' W., beginning new measurement.

- 15.143    The easterly right-of-way line marker at Station No. 220+00 of SR 196, monumented with an iron post, 2 inches diameter, firmly set, projecting 7 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY,

There is no evidence of a westerly right-of-way line marker at this station.

---

N. 2°14.6' W., beginning new measurement.

- 9.201    The point at the intersection with the E-W center line of section 22, not monumented.
- 15.144    The easterly right-of-way line marker at Station No. 230+00 of SR 196, monumented with an iron post, 2 inches diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY,

From which

the westerly right-of-way line marker bears S. 87°44.7' W., 3.033 chains distance, monumented with an iron post, 2 inches diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY.

---

N. 2°11.6' W., beginning new measurement.

- 15.148    The easterly right-of-way line marker at Station No. 240+00 of SR 196, monumented with an iron post, 2 inches diameter, firmly set, projecting 5 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY,

From which

the westerly right-of-way line marker bears S. 87°38.8' W., 3.027 chains distance, monumented with an iron post, 2 inches diameter, firmly set, projecting 7 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY.

---

N. 2°14.4' W., beginning new measurement.

- 19.104    The easterly right-of-way line marker (at an offset of 100 ft.

THE SURVEY OF A PORTION OF THE RIGHT-OF-WAY LINES OF UTAH  
STATE ROAD No. 196,  
CHAINS TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

from the center line) of SR 196, on the section line between sections 15 and 22, monumented with an iron post, 2 inches diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY.

There is no evidence of the second easterly right-of-way line marker (at an offset of 50 ft. from the center line) of SR 196, on the section line between sections 15 and 22.

---

From the westerly right-of-way line marker (at an offset of 50 ft. from the center line) of SR 196, on the section line between sections 15 and 22, monumented with a damaged iron post, 2 inches diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches diameter, without a brass cap,

From which

the second westerly right-of-way line marker (at an offset of 100 ft. from the center line) of SR 196, on the section line between sections 15 and 22, bears S. 89°36.1' W., 0.762 chains distance, monumented with an iron post, 2 inches diameter, firmly set, projecting 8 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY.

N. 2°14.0' W., on the westerly right-of-way line of SR 196.

26.251 Search for the westerly right-of-way line marker at Station No. 270+00 of SR 196. Find a rusted iron post, 2 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY, lying entirely out of the ground in a broken concrete pillar. The original position of this monument could not be determined.

There is no evidence of an easterly right-of-way line marker at this station.

40.295 The point at the intersection with the E-W center line of section 15, not monumented.

41.402 The westerly right-of-way line marker at Station No. 280+00 of SR 196, at a hole drilled in sandstone, 2 inches diameter, 8 inches deep, stained with rust; there is no remaining evidence of the 2 inches diameter iron post.


There is no evidence of an easterly right-of-way line marker at this station.

60.543 The point at the intersection with the E-W center line of the NW 1/4 of section 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,

THE SURVEY OF A PORTION OF THE RIGHT-OF-WAY LINES OF UTAH  
 STATE ROAD NO. 196,  
 CHAINS TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

26 inches in the ground, with aluminum cap marked:



Bury a magnet beneath and set a steel fence post alongside the aluminum post.


From which

nearby this point the westerly right-of-way line marker (at an offset of 50 ft. from the center line) of SR 196, is lying entirely out of the ground, a rusted iron post, 2 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY, encircled with concrete. The original position of this monument could not be determined.

The second westerly right-of-way line marker (at an offset of 100 ft. from the center line) of SR 196, bears S. 86°06.6' W., 0.758 chains distance, monumented with an iron post, 2 inches diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY. UDOT intended to set this marker on the E-W center line of the NW 1/4 of section 15, but I find it off line.

From the point at the intersection of the easterly right-of-way line (at an offset of 100 ft. from the center line) of SR 196, with the E-W center line of the NW 1/4 of section 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:



From which

the easterly right-of-way line marker (at an offset of 100 ft. from the center line) of SR 196, bears S. 2°13.6' E., 0.079 chains distance, monumented with an iron post, 2 inches

THE SURVEY OF A PORTION OF THE RIGHT-OF-WAY LINES OF UTAH  
STATE ROAD NO. 196,  
CHAINS TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

diameter, loosely set, projecting 6 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY. UDOT intended to set this marker on the E-W center line of the NW 1/4 of section 15, but I find it off line.

N. 2°13.6' W., on the easterly right-of-way line of SR 196.

20.248 The point at the intersection with the section line between sections 10 and 15, not monumented.

26.372 The easterly right-of-way line marker at Station No. 310+00 of SR 196, monumented with an iron post, 2 inches diameter, firmly set, projecting 7 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY,

From which

the westerly right-of-way line marker bears S. 87°44.1' W., 3.031 chains distance, monumented with an iron post, 2 inches diameter, firmly set, projecting 7 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY.

---

N. 2°13.6' W., beginning new measurement.

15.155 Point for the easterly right-of-way line marker at Station No. 320+00 of SR 196, there is no evidence of an easterly right-of-way line marker at this station,

From which,

the westerly right-of-way line marker bears S. 87°46.4' W., 3.033 chains distance, monumented with an iron post, 2 inches diameter, firmly set, projecting 7 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY.

30.307 The easterly right-of-way line marker at Station No. 330+00 of SR 196, monumented with an iron post, 2 inches diameter, firmly set, projecting 7 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY,

From which

the westerly right-of-way line marker bears S. 87°38.7' W., 3.029 chains distance, monumented with an iron post, 2 inches diameter, firmly set, projecting 7 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY.


---

CHAINS THE SURVEY OF A PORTION OF THE RIGHT-OF-WAY LINES OF UTAH  
STATE ROAD NO. 196,  
TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

N. 2°14.5' W., beginning new measurement.

- 4.080 The point at the intersection with the E-W center line of section 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:



Bury a magnet beneath aluminum post.

A fence corner with barbed wire fences extending north and east bears S. 69°32' W., 51.5 ft. distance.

- 15.140 The easterly right-of-way line marker at Station No. 340+00 of SR 196, monumented with an iron post, 2 inches diameter, firmly set, projecting 4 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY,

From which

the westerly right-of-way line marker bears S. 88°13.8' W., 3.035 distance, monumented with an iron post, 2 inches diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches diameter, with brass cap, 3 inches diameter, marked: STATE ROAD RIGHT OF WAY.

---

The Survey of a Portion of the Right-of-Way Lines of Utah  
State Road No. 199,  
Township 6 South, Range 8 West, Salt Lake Meridian, Utah

---

**Note:** The location of Utah State Road No. 199 in sections 25 and 36, according to drawing sheets nos. 4 and 5 of Utah State Road Commission Plans of Proposed State Road, Project D.A. - W.R. No. 19(1), approved October 1942, and on file at the Utah Department of Transportation (UDOT), was only tied to then existing fences; there is no indication of a monumented right-of-way. After verifying this in the field, a diligent search was made for the fences in an attempt to locate the right-of-way based upon the 1942 ties. The apparent (or present as-built) centerline of State Road No. 199, a paved road, was then surveyed through sections 25 and 36 as a reference line;

THE DEPENDENT RESURVEY OF A PORTION OF THE RIGHT-OF-WAY LINES  
OF UTAH STATE ROAD NO. 199,  
*CHAINS*            TOWNSHIP 6 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

this reference line could not be made to fit the existing fences with the 1942 ties and evidence of road realignment could not be found. Therefore, the reference line is used as the best available evidence of the original 1942 centerline of State Road No. 199 in sections 25 and 36 to control the right-of-way location. The northwesterly right-of-way line of State Road No. 199 in section 25 is established parallel with and 200 feet distance from the reference line. The southeasterly right-of-way line of State Road No. 199 in section 36 is established parallel with and 50 feet distance from the reference line.

From the point on the northwesterly right-of-way line (at an offset of 200 ft. from the existing center line) of SR 199, on the section line between sections 25 and 30 on the east boundary of township, hereinbefore described.

S. 39°47.6' W., on the northwesterly right-of-way line of SR 199.

**49.305**      Point of intersection with the section line between sections 25 and 36, hereinbefore described.

---

From the point on the southeasterly right-of-way line (at an offset of 50 ft. from the existing center line) of SR 199, on the section line between sections 25 and 36, hereinbefore described.

S. 39°47.6' W., on the southeasterly right-of-way line of SR 199.

**83.891**      Point of intersection with the section line between sections 35 and 36, hereinbefore described.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Calvert C. Norton	Survey Technician
Adrian M. Kurip	Survey Technician

---

## CERTIFICATE OF SURVEY

We, *Ronald K. Baugh, Supervisory Cadastral Surveyor, and Daniel T. Gillins, Survey Technician*, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing the date of the *12<sup>th</sup> day of September, 2007*, we have *dependently resurveyed a portion of the south boundary (First Standard Parallel South) of Township 5 South, Range 8 West; and portions of the south and east boundaries, a portion of the subdivisional lines, subdivided sections 10, 12, 14, 15, 22, 24, 25, and 34, and surveyed portions of the right-of-way lines of Utah State Roads nos. 196 and 199, in Township 6 South, Range 8 West, of the Salt Lake Meridian, in the State of Utah*, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions of the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 09, 2011

Date

Ronald K. Baugh  
Supervisory Cadastral Surveyor

January 28, 2011

Date

Daniel T. Gillins  
Survey Technician

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The following field notes of the *dependent resurvey of a portion of the south boundary (First Standard Parallel South) of Township 5 South, Range 8 West; and a portions of the south and east boundaries, a portion of the subdivisional lines, the subdivision of sections 10, 12, 14, 15, 22, 24, 25, and 34, and the survey of portions of the right-of-way lines of Utah State Roads nos. 196 and 199, in Township 6 South, Range 8 West*, executed by *Ronald K. Baugh, Supervisory Cadastral Surveyor, and Daniel T. Gillins, Survey Technician*, having been critically examined and found correct, are hereby approved.

May 9, 2011

Date

Daniel W. Webb

Chief Cadastral Surveyor for Utah