

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

THE EAST AND THE NORTH BOUNDARIES,

A PORTION OF THE SOUTH BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES

AND

THE SUBDIVISION OF SECTIONS 3 AND 4,

IN

**TOWNSHIP 24 SOUTH, RANGE 9 WEST**

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Daniel T. Gillins*  
*Cadastral Surveyor*

*Under the Supervision of*

*Ronald K. Baugh*  
*Supervisory Cadastral Surveyor*

Under Special Instructions dated **August 30, 2007**, approved **August 30, 2007**, which provided for the surveys included under Group Number **1055**, and assignment instructions dated **August 30, 2007**, with reassignment instructions dated **January 14, 2008**.

Survey commenced **September 6, 2007**  
Survey completed **April 12, 2008**

# INDEX DIAGRAM

Township 24 South, Range 9 West

15	14	13	13	12	11
6	5	45 4 44	37 3 36	30 2 29	23 1 10 22
7	8	43 9 43	35 10 35	28 11 28	22 12 9 21
18	17	42 16 42	34 15 33	27 14 27	20 13 9 20
19	20	41 21 40	33 22 32	26 23 25	19 24 8 18
30	29	40 28 39	31 27 31	25 26 24	18 25 7 17
31	32	38 33 5	30 34 5	23 35 4	16 36 6 4

The Subdivision of Section 3.....Page 45  
 The Subdivision of Section 4.....Page 48

## TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of the east and north boundaries, a portion of the south boundary, a portion of the subdivisional lines, and the subdivision of sections 3 and 4 in Township 24 South, Range 9 West, Salt Lake Meridian, Utah.

**History of Surveys**

Surveyed by		Retr. Or Resurveyed by	
<b>SOUTH BOUNDARY</b>			
All	A.J. Stewart Jr.	1882	
Portion			F.D. Reynolds 1993-94
<b>EAST BOUNDARY</b>			
All	A.J. Stewart Jr.	1882	
All			A.D. Griffin 1959
<b>WEST BOUNDARY</b>			
All	J. Bausman	1870	
All			A.J. Stewart Jr. 1882
<b>NORTH BOUNDARY</b>			
Portion	J. Bausman	1870	
All	A.J. Stewart Jr.	1882	A.J. Stewart Jr. 1882
Portion			R. Gentry 1925
<b>SUBDIVISION</b>			
All	A.J. Stewart Jr.	1882	

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1055, dated August 30, 2007.

The direction of the lines was determined by references to true meridians, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods, dated May 9, 2001, Version 1.0. Trimble model 5800 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for the project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

## TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

Geodetic control was derived from GPS static observations of the 1/4 section corner of section 19 only, T. 24 S., R. 8 W., post processed by the National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS): ECHO\_BRGN\_NV1999 CORS ARP, DELTAMUNI\_UT2004 CORS ARP, and MARYSVALE\_UT2006 CORS ARP. The geographic position of the said corner is as follows:

Latitude: 38°42'38.022" N.      Longitude: 112°48'21.810" W.    N.A.D. 1983,  
Network Accuracy = 0.100 meter at 95% confidence.

## CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY OF  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

---

Dependent Resurvey of a Portion of the South Boundary of  
Township 24 South, Range 9 West, Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
A.J. Stewart Jr. in 1882, and  
the Resurvey Executed by F.D. Reynolds in 1993-94

---

Beginning at the corner of Townships 24 and 25 South, Ranges 8 and 9 West, monumented with iron post, 2 1/2 inches in diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1959 resurvey, with a sandstone, 14X8X4 inches, lying alongside the iron post, poorly marked, with a steel fence post alongside.

Corner is located in open sand flat.

S. 89° 55.9' W., between sections 1 and 36.

- 40.190 The 1/4 section corner of sections 1 and 36, monumented with an aluminum post, 2 1/2 inches in diameter, firmly set, in a mound of stone, 3 ft. base, 2 inches high, to top of aluminum cap marked as described in the official record of the 1993-94 resurvey; with a steel fence post set alongside.

Corner is located along easterly edge of sage brush.

---

S. 89° 52.5' W., beginning new measurement.

- 40.119 The corner of sections 1, 2, 35, and 36, monumented with an aluminum post, 2 1/2 inches in diameter, projecting 3 inches above mound of stone, 4 ft. base, 2 ft. high, with aluminum cap marked as described in the official record of the 1993-94 resurvey; with a steel fence post set alongside.
- 

N. 83° 56.3' W., between sections 2 and 35.

- 36.778 The 1/4 section corner of sections 2 and 35, monumented with an aluminum post, 2 1/2 inches in diameter, projecting 2 inches above ground, in a collar of stone, with aluminum cap marked as described in the official record of the 1993-94 resurvey; with a steel fence post set alongside.
- 

S. 89° 26.2' W., beginning new measurement.

- 40.366 The corner of sections 2, 3, 34, and 35, monumented with an aluminum post, 2 1/2 inches in diameter, projecting 10 inches

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY OF  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

above ground, in a collar of stone, with aluminum cap marked as described in the official record of the 1993-94 resurvey; with a steel fence post set alongside.

---

S. 89° 37.9' W., between sections 3 and 34.

- 40.407 The 1/4 section corner of sections 3 and 34, monumented with an aluminum post, 2 1/2 inches in diameter, projecting 1 inch above the ground, in a collar of stone, with aluminum cap marked as described in the official record of the 1993-94 resurvey; with a steel fence post set alongside.

Corner is located 75 links E. of a wash, drains southerly.

---

S. 89° 45.5' W., beginning new measurement.

- 40.391 The corner of sections 3, 4, 33, and 34, monumented with an aluminum post, 2 1/2 inches in diameter, projecting 4 inches above ground, in a collar of stone, with aluminum cap marked as described in the official record of the 1993-94 resurvey; with a steel fence post set alongside.
- 

Reestablishment of the Survey Executed by A.J. Stewart Jr.  
in 1882

---

S. 89° 41.8' W., between sections 4 and 33.

- 38.853 The 1/4 section corner of sections 4 and 33, monumented with a lava stone, 12X10X6 inches, firmly set, plainly marked 1/4, with an iron pipe, 2 1/2 inches diameter, projecting 6 inches above ground, without cap, set alongside.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 25 inches in the ground, with magnet at base, and aluminum cap marked:

	T24S R9W
	S33
1/4	_____
	S4
	T25S
	2007

Bury the marked stone and iron pipe alongside aluminum post.

Set steel fence post alongside aluminum post.

---

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY OF  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

S. 89° 42.2' W., beginning new measurement.

- 40.082 The corner of sections 4, 5, 32, and 33, monumented with a granite stone, 18X12X5 inches, firmly set, marked with 4 notches on E. edge and 2 notches on W. edge, in a mound of stone, with an iron pipe, 2 inches in diameter, projecting 18 inches above the ground, without cap, set alongside.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 15 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T24S R9W	
S32	S33
S5	S4
T25S	
2007	

Bury the marked stone and iron pipe alongside aluminum post.

Set steel fence post alongside aluminum post.

---

Dependent Resurvey of the East Boundary of  
Township 24 South, Range 9 West, Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
A.J. Stewart Jr. in 1882, and  
the Resurvey Executed by A.D. Griffin in 1959

---

From the corner of Townships 24 and 25 South, Ranges 8 and 9 West, hereinbefore described.

N. 0° 04.6' W., along the east boundary of section 36.

- 40.240 The 1/4 section corner of section 36 only, monumented with an iron post, 2 1/2 inches in diameter, firmly set, in a mound of stone, 3 ft. base, 12 inches high, to top of brass cap marked as described in the official record of the 1959 resurvey.

A wash bears westerly, 1 chain distance, drains southerly.

Set steel fence post alongside iron post.

---

N. 0° 03.8' E., beginning new measurement.

- 3.743 The 1/4 section corner of section 31 only, Township 24 South, Range 8 West, monumented with an iron post, 2 1/2 inches in

DEPENDENT RESURVEY OF THE EAST BOUNDARY OF  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

diameter, firmly set, projecting 6 inches above a mound of stone, 4 ft. base, 1 ft. high, with brass cap marked as described in the official record of the 1959 resurvey.

A wash bears westerly, 50 links distance, drains southerly.

Set steel fence post alongside iron post.

- 40.147 The corner of sections 25 and 36 only, monumented with an iron post, 2 1/2 inches in diameter, firmly set, projecting 10 inches above ground, with brass cap marked as described in the official record of the 1959 resurvey, with a poorly marked lava stone, 6x5x4 inches, lying loose alongside.

Corner is located in sagebrush.

Set steel fence post alongside iron post.

---

N. 0° 04.0' W., along the east boundary of section 25.

- 3.576 The corner of sections 30 and 31 only, Township 24 South, Range 8 West, bears West, 0.024 chains distance, monumented with an iron post, 2 1/2 inches in diameter, firmly set, projecting 6 inches above a mound of stone, 3 ft. base, 8 inches high, with brass cap marked as described in the official record of the 1959 resurvey.

Corner is located in sagebrush.

Set steel fence post alongside iron post.

- 40.265 The 1/4 section corner of section 25 only, monumented with an iron post, 2 1/2 inches in diameter, firmly set, in a mound of stone, 3 ft. base, 1 ft. high, to top of brass cap marked as described in the official record of the 1959 resurvey, with a lava stone, 14x8x6 inches, plainly marked 1/4, set alongside.

Corner is located among lava stones.

Set steel fence post alongside iron post.

---

N. 0° 02.7' E., beginning new measurement.

- 3.385 The 1/4 section corner of section 30 only, Township 24 South, Range 8 West, bears West, 0.013 chains distance, monumented with an iron post, 2 1/2 inches in diameter, firmly set, projecting 12 inches above ground, in a collar of stone, 2 ft. base, with brass cap marked as described in the official record of the 1959 resurvey.

Corner is located in open land.

Set steel fence post alongside iron post.

DEPENDENT RESURVEY OF THE EAST BOUNDARY OF  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.178** The corner of sections 24 and 25 only, monumented with an iron post, 2 1/2 inches in diameter, firmly set, projecting 10 inches above ground, in a collar of stone, with brass cap marked as described in the official record of the 1959 resurvey.

Corner is located on S. edge of sage brush.

Set steel fence post alongside iron post.

---

**N. 0° 02.2' W.**, along the east boundary of section 24.

- 3.197** The corner of sections 19 and 30 only, Township 24 South, Range 8 West, bears West, 0.052 chains distance, monumented with an iron post, 2 1/2 inches in diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1959 resurvey.

Corner is located in sagebrush.

Set steel fence post alongside iron post.

- 40.402** The 1/4 section corner of section 24 only, monumented with an iron post, 2 1/2 inches in diameter, firmly set, projecting 12 inches above ground, in a collar of stone, with brass cap marked as described in the official record of the 1959 resurvey, with a lava stone, 7x6x5 inches, faintly marked 1/4, set alongside.

Corner is located southerly of intersections of roads.

Set steel fence post alongside iron post.

---

**N. 0° 06.5' E.**, beginning new measurement.

- 2.757** The 1/4 section corner of section 19 only, Township 24 South, Range 8 West, bears West, 0.009 chains distance, monumented with an iron post, 2 1/2 inches in diameter, firmly set, projecting 12 inches above ground, in a collar of stone, with brass cap marked as described in the official record of the 1959 resurvey.

Corner is located 3 chains S. of road, 20 ft. wide, bears N. 20° E. - S. 20° W.

Set steel fence post alongside iron post.

- 40.184** The corner of sections 13 and 24 only, monumented with an iron post, 2 1/2 inches in diameter, projecting 16 inches above ground, with brass cap marked as described in the official record of the 1959 resurvey.

Corner is located in sandy flat rolling hills.

DEPENDENT RESURVEY OF THE EAST BOUNDARY OF  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set steel fence post alongside iron post.

---

N. 0° 19.2' E., along the east boundary of section 13.

- 2.590 The corner of sections 18 and 19, Township 24 South, Range 8 West, bears West, 0.017 chains distance, monumented with an iron post, 2 1/2 inches in diameter, projecting 16 inches above ground, with brass cap marked as described in the official record of the 1959 resurvey.

Corner is located in rolling sand hills.

Set steel fence post alongside iron post.

- 40.200 The 1/4 section corner of section 13 only, monumented with an iron post, 2 1/2 inches in diameter, projecting 8 inches above ground, in a scattered mound of stone, with brass cap marked as described in the official record of the 1959 resurvey.

Set steel fence post alongside iron post.

---

N. 0° 01.1' E., beginning new measurement.

- 2.369 The 1/4 section corner of section 18 only, Township 24 South, Range 8 West, bears East, 0.017 chains distance, monumented with an iron post, 2 1/2 inches in diameter, projecting 12 inches above ground, in a mound of stone, with brass cap marked as described in the official record of the 1959 resurvey.

Set steel fence post alongside iron post.

- 40.592 The corner of sections 12 and 13 only, monumented with an iron post, 2 1/2 inches in diameter, projecting 15 inches above ground, in a mound of stone, with brass cap marked as described in the official record of the 1959 resurvey.

Set steel fence post alongside iron post.

---

N. 2° 42.5' E., along the east boundary of section 12.

- 1.789 The corner of sections 7 and 18 only, Township 24 South, Range 8 West, monumented with an iron post, 2 1/2 inches in diameter, projecting 16 inches above ground, in a mound of stone, with brass cap marked as described in the official record of the 1959 resurvey.

Set steel fence post alongside iron post.

---

N. 2° 38.1' E., beginning new measurement.

DEPENDENT RESURVEY OF THE EAST BOUNDARY OF  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

39.983 The 1/4 section corner of sections 7 and 12, monumented with an iron post, 2 1/2 inches in diameter, projecting 15 inches above ground, with brass cap marked as described in the official record of the 1959 resurvey.

Set steel fence post alongside iron post.

---

N. 2° 38.7' E., beginning new measurement.

40.100 The corner of sections 6 and 7 only, Township 24 South, Range 8 West, monumented with an iron post, 2 1/2 inches in diameter, projecting 15 inches above ground, with brass cap marked as described in the official record of the 1959 resurvey, with a mound of stone west of corner.

Set steel fence post alongside iron post.

---

N. 2° 45.7' E., beginning new measurement.

1.684 The corner of sections 1 and 12 only, monumented with an iron post, 2 1/2 inches in diameter, projecting 12 inches above ground, with a brass cap marked as described in the official record of the 1959 resurvey, with a mound of stone west of corner.

Set steel fence post alongside iron post.

---

N. 2° 38.3' E., along the east boundary of section 1.

38.368 The 1/4 section corner of section 6 only, Township 24 South, Range 8 West, monumented with an iron post, 2 1/2 inches in diameter, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1959 resurvey.

Set steel fence post alongside iron post.

---

N. 2° 38.9' E., beginning new measurement.

3.410 The 1/4 section corner of section 1 only, monumented with an iron post, 2 1/2 inches in diameter, projecting 10 inches above ground, in a scattered mound of stone, with brass cap marked as described in the official record of the 1959 resurvey.

Set steel fence post alongside iron post.

---

N. 2° 38.4' E., beginning new measurement.

36.639 An unrecorded 1/16 section corner of section 6 only, Township 24 South, Range 8 West, monumented with a General Land Office iron

DEPENDENT RESURVEY OF THE EAST BOUNDARY OF  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

post, 2 1/2 inches in diameter, projecting 5 inches above ground, with a steel fence post set alongside, with brass cap marked:

T24S  
1/16 | R8W  
      | S6  
      |  
      80  
      1959

- 41.702 The corner of Townships 23 and 24 South, Ranges 8 and 9 West, monumented with an iron post, 3 inches diam., firmly set 12 inches above ground with brass cap marked as described in the official record of the 1915 resurvey of the south boundary of Township 23 South, Range 8 West.

---

Dependent Resurvey of the North Boundary of  
Township 24 South, Range 9 West, Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed  
by A.J. Stewart Jr. in 1882 and  
the Resurvey Executed by R. Gentry in 1925

---

N. 89° 43.6' W., along the north boundary of section 1.

- 39.975 The 1/4 section corner of section 36 only, Township 23 South, Range 9 West, monumented with an iron post, 1 inch in diameter, projecting 15 inches above ground, with brass cap marked as described in the official record of the 1925 resurvey, with a mound of stone north of corner.

Corner is located under an E-W barbed wire fence.

---

S. 89° 09.4' W., beginning new measurement.

- 0.319 The 1/4 section corner of section 1 only, monumented with an iron post, 1 inch in diameter, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1925 resurvey, with a mound of stone south of corner.

Corner is located under an E-W barbed wire fence.

---

N. 89° 45.2' W., beginning new measurement.

- 39.632 The corner of sections 35 and 36 only, Township 23 South, Range 9 West, monumented with an iron post, 2 inches in diameter, projecting 9 inches above ground, in mound of stone, 3 ft. base, 2 ft. high, with brass cap marked as described in the official record of the 1925 resurvey.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY OF  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located on rocky, south facing slope.

Set steel fence post alongside iron post.

---

S. 89° 31.7' W., beginning new measurement.

- 0.649 The corner of sections 1 and 2 only, monumented with an iron post, 2 inches in diameter, projecting 12 inches above ground, in a mound of stone, with brass cap marked as described in the official record of the 1925 resurvey.

Corner is located on rocky, south facing slope.

---

N. 89° 44.5' W., along the north boundary of section 2.

- 39.298 The 1/4 section corner of section 35 only, Township 23 South, Range 9 West, monumented with an iron post, 1 inch diameter, set in a mound of stone, 4 ft. base, 2 ft. high to top of brass cap marked as described in the official record of the 1925 resurvey.

Corner is located on small N-S ridge.

Set steel fence post alongside iron post.

---

S. 89° 36.1' W., beginning new measurement.

- 0.959 The 1/4 section corner of section 2 only, monumented with an iron post, 1 inch diameter, projecting 8 inches above ground, in a mound of stone, 3 ft. base to top of brass cap marked as described in the official record of the 1925 resurvey.

Corner is located on westerly facing slope.

Set steel fence post alongside iron post.

---

N. 89° 45.8' W., beginning new measurement.

- 40.249 The corner of sections 2, 3, 34, and 35, monumented with an iron post, 2 inches in diameter, set in a mound of stone, 3 ft. base, 9 inches high to top of brass cap marked as described in the official record of the 1925 resurvey.

Set steel fence post alongside iron post.

---

Reestablishment of the Survey Executed  
by J. Bausman in 1870 and  
the Resurvey Executed by A.J. Stewart Jr. in 1882

---

DEPENDENT RESURVEY OF THE NORTH BOUNDARY OF  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89° 56.2' W., between sections 3 and 34.

20.177 Point for the E 1/16 section corner for sections 3 and 34, not monumented.

40.354 The 1/4 section corner of sections 3 and 34, monumented with a sandstone, 15x12x9 inches, firmly set, in a mound of stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 24 inches in the ground, with magnet at base, in a mound of stone, 4 ft. base to top of aluminum cap marked:

	T23S R9W
	S34
1/4	-----
	S3
	T24S
	2007

Bury the marked stone alongside aluminum post.

Set steel fence post alongside aluminum post.

---

N. 89° 54.8' W., beginning new measurement.

40.328 The corner of sections 3, 4, 33, and 34, monumented with a granite stone, 18x12x6 inches, firmly set, marked with 6 grooves on S. face and 3 notches on E. and W. edges, with a steel fence post alongside.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with magnet at base, in a mound of stone, 2 1/2 ft. base to top of aluminum cap marked:

	T23S R9W
	S33   S34
	S4   S3
	T24S
	2007

Bury the marked stone alongside aluminum post.

---

S. 89° 59.7' W., between sections 4 and 33.

40.528 Point for the 1/4 section corner of sections 4 and 33, at proportionate distance, there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY OF  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 25 inches in the ground, with magnet at base, and aluminum cap marked:

T23S R9W  
S33  
1/4 —————  
S4  
T24S  
2007

Corner is located at N. end of spring in thick brush.

Set steel fence post alongside aluminum post.

60.792 Point for the W 1/16 section corner of sections 4 and 33.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with magnet at base, and aluminum cap marked:

S33  
W 1/16 —————  
S4  
2007

Set steel fence post 1 ft. south of corner.

81.056 The corner of sections 4, 5, 32, and 33, determined at a cedar post, 4 inches diameter, in the center of a scattered mound of stone, with a steel fence post set alongside. This is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with magnet at base, and aluminum cap marked:

T23S R9W  
S32 | S33  
S5 | S4  
T24S  
2007

Raise a mound of stone, 3 ft. base, 2 ft. high, west of corner.

---

S. 89° 54.4' W., between sections 5 and 32.

40.301 The 1/4 section corner of sections 5 and 32, monumented with a lava stone, 15x12x8 inches, lying on top of a mound of stone, 4

DEPENDENT RESURVEY OF THE NORTH BOUNDARY OF  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

ft. base, 2 ft. high, with defaced marks on one side.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with magnet at base, and aluminum cap marked:

	T23S R9W
	S32
1/4	-----
	S5
	T24S
	2007

Bury the marked stone alongside aluminum post.

Raise a mound of stone, 2 ft. base, 2 ft. high, west of corner.

Set steel fence post alongside aluminum post.

N. 89° 53.9' W., beginning new measurement.

40.175 The corner of sections 5, 6, 31, and 32; identical with corner no. 1 of the Beaver No. 32 lode, corner no. 1 of the Beaver No. 33 lode, and corner no. 1 of the Beaver No. 36 lode, Mineral Survey No. 7382, monumented with a gray sandstone, 18x12x10 inches, firmly set, marked with 1 notch on W. edge, 5 notches on E. edge, 6 grooves on N. face, "USMS 7382" on S. face, and "B33-1, B36-1" on W. face, with a steel fence post set alongside.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with magnet at base, and aluminum cap marked:

	T23S R9W
	S31   S32
	-----
	S6   S5
	T24S
	2007

Bury the marked stone alongside aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, west of corner.

S. 88° 58.3' W., between sections 6 and 31.

40.028 The 1/4 section corner of sections 6 and 31, monumented with a lava stone, 18x12x10 inches, firmly set, marked 1/4 on north

DEPENDENT RESURVEY OF THE NORTH BOUNDARY OF  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with magnet at base, and aluminum cap marked:

	T23S R9W
	S31
1/4	—————
	S6
	T24S
	2007

Bury the marked stone alongside aluminum post.

Set steel fence post alongside aluminum post.

---

N. 89° 54.3' W., beginning new measurement.

- 40.138 The corner of Townships 23 and 24 South, Ranges 9 and 10 West, monumented with an iron post, 3 inches in diameter, projecting 12 inches above ground, in a mound of stone, with brass cap marked as described in the official record of the 1925 resurvey.

Set steel fence post alongside iron post.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
Township 24 South, Range 9 West, Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by A.J. Stewart Jr.  
in 1882

---

From the corner of sections 1, 2, 35, and 36, on the south boundary of the township, hereinbefore described.

N. 0° 30.0' W., between sections 35 and 36.

- 40.435 The 1/4 section corner of sections 35 and 36, monumented with a lava stone, 10x8x3 inches, firmly set, in scattered mound of stone, marked 1/4 on W. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 25 inches in the ground, with magnet at base, in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T24S R9W  
1/4  
S35 | S36  
2007

Bury the marked stone alongside aluminum post.

Set steel fence post alongside aluminum post.

---

N. 0° 05.8' W., beginning new measurement.

- 40.365 The corner of sections 25, 26, 35, and 36, monumented with a lava stone, 8x8x6 inches, plainly marked with 1 notch on S. edge and 1 notch on E. edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with magnet at base, and aluminum cap marked:

T24S R9W  
S26 | S25  
S35 | S36  
2007

Bury the marked stone alongside aluminum post.

Set steel fence post alongside aluminum post.

---

From the corner of sections 25 and 36 only, on the east boundary of the township, hereinbefore described.

N. 89° 48.2' W., between section 25 and 36.

- 40.352 The 1/4 section corner of sections 25 and 36, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 15 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T24S R9W  
S25  
1/4 —————  
S36  
2007

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set steel fence post alongside aluminum post.

80.704 The corner of sections 25, 26, 35, and 36.

---

N. 1° 19.5' E., between sections 25 and 26.

39.763 Point for the 1/4 section corner of sections 25 and 26, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 24 inches in the ground, with magnet at base, in a mound of stone, 2 ft. base, to top of aluminum cap marked:

T24S R9W  
1/4  
S26 | S25  
2007

Set steel fence post alongside aluminum post.

79.526 The corner of sections 23, 24, 25, and 26, monumented with a gray granite stone, 16x8x6 inches, loosely set, marked with 2 notches on S. edge and 1 notch on E. edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 24 inches in the ground, with magnet at base, and aluminum cap marked:

T24S R9W  
S23 | S24  
S26 | S25  
2007

Bury the marked stone along S. side of aluminum post.

Corner is located on gentle S. facing slope.

Raise a mound of stone west of corner.

Set steel fence post alongside aluminum post.

---

From the corner of sections 24 and 25 only, on the east boundary of the township, hereinbefore described.

S. 89° 31.1' W., between section 24 and 25.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 39.418 Point for the 1/4 section corner of sections 24 and 25, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with magnet at base, and aluminum cap marked:

T24S R9W  
S24  
1/4 —————  
S25  
2007

Corner is located 1.35 chains W. of N-S dirt road.

Set steel fence post alongside aluminum post.

- 78.836 The corner of sections 23, 24, 25, and 26.

N. 0° 55.2' W., between sections 23 and 24.

- 40.672 Point for the 1/4 section corner of sections 23 and 24, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 10 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T24S R9W  
1/4  
S23 | S24  
2007

Corner is located on southerly facing slope, in a drainage, course S.

Set steel fence post alongside aluminum post.

- 81.344 The corner of sections 13, 14, 23, and 24, monumented with a bismuth stone, 18x12x8 inches, firmly set, plainly marked with 3 notches on S. edge and 1 notch on E. edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 18 inches in the ground to solid rock, with magnet at base, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T24S R9W	
S14	S13
S23	S24
2007	

Bury the marked stone alongside aluminum post.

Corner is located on steep, rocky, northerly facing slope.

Set steel fence post alongside aluminum post.

---

From the corner of sections 13 and 24 only, on the east boundary of the township, hereinbefore described.

**N. 89° 57.3' W.**, between sections 13 and 24.

**40.176** The 1/4 section corner of sections 13 and 24, monumented with a lava stone, 18x8x6 inches, firmly set, plainly marked 1/4.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with magnet at base, and aluminum cap marked:

	T24S R9W
	S13
1/4	-----
	S24
	2007

Bury the marked stone alongside aluminum post.

Set steel fence post alongside aluminum post.

---

**N. 89° 55.5' W.**, beginning new measurement.

**39.998** The corner of sections 13, 14, 23, and 24.

---

**N. 0° 17.1' E.**, between sections 13 and 14.

**40.419** Point for the 1/4 section corner of sections 13 and 14, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 12 inches in the ground to solid rock, with magnet at base, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T24S R9W  
1/4  
S14 | S13  
2007

Corner is located on steep, rocky, southerly facing slope.

Set steel fence post alongside aluminum post.

- 80.838** The corner of sections 11, 12, 13, and 14, monumented with a granite stone, 14x12x6 inches, firmly set, plainly marked with 4 notches on S. edge and 1 notch on E. edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 5 inches in the ground to solid rock, with magnet at base, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T24S R9W  
S11 | S12  
S14 | S13  
2007

Bury the marked stone alongside aluminum post.

Corner is located on steep, rocky, southeasterly facing slope.

Set steel fence post alongside aluminum post.

From the corner of sections 12 and 13 only, on the east boundary of the township, hereinbefore described.

**N. 89° 54.5' W.**, between sections 12 and 13.

- 39.997** Point for the 1/4 section corner of sections 12 and 13, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 25 inches in the ground, with magnet at base, and aluminum cap marked:

T24S R9W  
S12  
1/4 —————  
S13  
2007

Set steel fence post alongside aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

79.994 The corner of sections 11, 12, 13, and 14.

---

N. 2° 31.0' E., between sections 11 and 12.

41.614 Point for the 1/4 section corner of sections 11 and 12, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with magnet at base, and aluminum cap marked:

T24S R9W  
1/4  
S11 | S12  
2007

Raise a mound of stone, 3 ft. base, 2 ft. high, west of corner.

Set steel fence post alongside aluminum post.

83.228 Point for the corner of sections 1, 2, 11, and 12, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with magnet at base, and aluminum cap marked:

T24S R9W  
S2 | S1  
S11 | S12  
2007

Raise a mound of stone, 3 ft. base, 2 ft. high, west of corner.

Set steel fence post alongside aluminum post.

---

From the corner of sections 1 and 12 only, on the east boundary of the township, hereinbefore described.

S. 89° 51.7' W., between sections 1 and 12.

40.088 Point for the 1/4 section corner of sections 1 and 12, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with magnet at base, in a collar of

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

stone, with aluminum cap marked:

T24S R9W  
S1  
1/4 —————  
S12  
2007

Set steel fence post alongside aluminum post.

80.176 The corner of sections 1, 2, 11, and 12.

---

N. 2° 20.3' E., between sections 1 and 2.

41.608 Point for the 1/4 section corner of sections 1 and 2, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 16 inches in the ground to solid rock, with magnet at base, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T24S R9W  
1/4  
S2 | S1  
2007

Corner is located on steep, westerly facing slope.

Set steel fence post alongside aluminum post.

84.007 The corner of sections 1 and 2 only, on the north boundary of the township, hereinbefore described.

---

From the corner of sections 2, 3, 34, and 35, on the south boundary of the township, hereinbefore described.

N. 2° 41.2' W., between sections 34 and 35.

38.677 Point for the 1/4 section corner of sections 34 and 35, at proportionate distance, there is no remaining evidence of the original corner. Point falls in a N-S dirt road, 20 ft. wide, where it is unsuitable to establish a permanent monument.

From which

An aluminum post, 30 inches long, 2 1/2 inches in diameter, set 24 inches in the ground, for a reference monument, bears N. 87° 40.1' E., 0.647 chains distance, with aluminum cap marked: T24S R9W 1/4 S34 S35 RM 2007 42.68 FT and an arrow pointing to the

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

corner.

An aluminum post, 30 inches long, 2 1/2 inches in diameter, set 24 inches in the ground, with magnet at base, for a reference monument, bears S. 1° 02.0' W., 0.549 chains distance, with aluminum cap marked: T24S R9W 1/4 S34 S35 RM 2007 36.25 FT and an arrow pointing to the corner.

Set steel fence post alongside both reference monuments.

- 77.354 The corner of sections 26, 27, 34, and 35, monumented with a lava stone, 15x12x8 inches, firmly set, in a mound of stone, 2 ft. base, 10 inches high, marked with 1 notch on S. edge and 2 notches on E. edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 15 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T24S R9W	
S27	S26
S34	S35
2007	

Bury the marked stone alongside aluminum post.

Set steel fence post alongside aluminum post.

From the corner of sections 25, 26, 35, and 36.

S. 89° 58.2' W., between sections 26 and 35.

- 40.063 Point for the 1/4 section corner of sections 26 and 35, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 10 inches in the ground, with magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T24S R9W	
S26	
1/4	_____
S35	
2007	

Corner is located on N. end of dry lake bed.

Set steel fence post alongside aluminum post.

- 80.126 The corner of sections 26, 27, 34, and 35.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

N. 1° 37.6' E., between sections 26 and 27.

- 41.021 Point for the 1/4 section corner of sections 26 and 27, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 20 inches in the ground, with magnet at base, in a mound of stone, 2 ft. base, to top of aluminum cap marked:

T24S R9W  
1/4  
S27 | S26  
2007

Set steel fence post alongside aluminum post.

- 82.042 The corner of sections 22, 23, 26, and 27, monumented with granite stone, 10x7x4 inches, firmly set, plainly marked with 2 grooves on S. face and 2 grooves on E. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with magnet at base, and aluminum cap marked:

T24S R9W  
S22 | S23  
S27 | S26  
2007

Bury the marked stone alongside aluminum post.

Corner is located in flat, sandy area, with scattered junipers.

Set steel fence post alongside aluminum post.

From the corner of sections 23, 24, 25, and 26.

N. 88° 10.1' W., between section 23 and 26.

- 39.957 The 1/4 section corner of section 23 and 26, monumented with a lava stone, 8x6x5 inches, firmly set and plainly marked 1/4 on N face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter,

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

20 inches in the ground, with magnet at base, in a collar of stone, with aluminum cap marked:

	T24S R9W
	S23
1/4	-----
	S26
	2007

Bury the marked stone alongside aluminum post.

Corner is located 1.15 chains S. of an E-W dirt road.

Set steel fence post alongside aluminum post.

---

N. 88° 17.3' W., beginning new measurement.

39.701 The corner of sections 22, 23, 26, and 27.

---

N. 0° 13.8' W., between sections 22 and 23.

40.777 Point for the 1/4 section corner of sections 22 and 23, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 6 inches in the ground to solid rock, with magnet at base, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

	T24S R9W
	1/4
	S22   S23
	2007

Set steel fence post alongside aluminum post.

81.554 Point for the corner of sections 14, 15, 22, and 23, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, on top of bedrock, with magnet at base, in a mound of stone, 5 ft. base, to top of aluminum cap marked:

	T24S R9W
	S15   S14
	-----
	S22   S23
	2007

Corner is located in drainage, course westerly.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set steel fence post alongside aluminum post.

---

From the corner of sections 13, 14, 23, and 24.

N. 88° 02.7' W., between sections 14 and 23.

- 39.337 Point for the 1/4 section corner of sections 14 and 23, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with magnet at base, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

	T24S R9W
	S14
1/4	—————
	S23
	2007

Corner is located on northeasterly facing slope.

Set steel fence post alongside aluminum post.

- 78.674 The corner of sections 14, 15, 22, and 23.
- 

N. 0° 43.7' E., between sections 14 and 15.

- 40.780 Point for the 1/4 section corner of sections 14 and 15, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches in diameter, 15 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 ft. base, to top of brass cap marked:

	T24S R9W
	1/4
	S15   S14
	2007

Set steel fence post alongside stainless steel post.

- 81.560 Point for the corner of sections 10, 11, 14, and 15, at proportionate distance, there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with magnet at base, and brass cap marked:

T24S R9W	
S10	S11
S15	S14
2007	

Raise a mound of stone, 4 ft. base, 3 ft. high, west of corner.

Set steel fence post alongside stainless steel post.

---

From the corner of sections 11, 12, 13, and 14.

N. 87° 30.1' W., between sections 11 and 14.

39.025 Point for the 1/4 section corner of sections 11 and 14, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with magnet at base, in a mound of stone, 3 ft. base, 2 ft. high, with aluminum cap marked:

T24S R9W	
S11	
1/4	—————
S14	
2007	

Corner is located on westerly facing slope.

Set steel fence post alongside aluminum post.

78.050 The corner of sections 10, 11, 14, and 15.

---

N. 1° 08.9' E., between sections 10 and 11.

40.785 Point for the 1/4 section corner of sections 10 and 11, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with magnet at base, and aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T24S R9W  
1/4  
S10 | S11  
2007

Raise a mound of stone, 3 ft. base, 2 ft. high, west of corner.

Set steel fence post alongside aluminum post.

- 81.570 Point for the corner of sections 2, 3, 10, and 11, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 29 inches in the ground, with magnet at base, and aluminum cap marked:

T24S R9W  
S3 | S2  
S10 | S11  
2007

Raise a mound of stone, 3 ft. base, 3 ft. high, west of corner.

Set steel fence post alongside aluminum post.

---

From the corner of sections 1, 2, 11, and 12.

N. 88° 42.4' W., between sections 2 and 11.

- 39.999 Point for the 1/4 section corner of sections 2 and 11, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with magnet at base, and aluminum cap marked:

1/4 T24S R9W  
S2  
S11  
2007

Raise a mound of stone, 3 ft. base, 2 ft. high, north of corner.

Set steel fence post alongside aluminum post.

- 79.998 The corner of sections 2, 3, 10, and 11.
-

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

N. 2° 00.2' E., between sections 2 and 3.

- 40.800 Point for the 1/4 section corner of sections 2 and 3, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with magnet at base, and aluminum cap marked:

T24S R9W  
1/4  
S3 | S2  
2007

Set steel fence post alongside steel post.

- 61.200 Point for the N 1/16 section corner of sections 2 and 3, not monumented.
- 82.518 The corner of sections 2, 3, 34, and 35, on the north boundary of the township, hereinbefore described.

From the corner of sections 3, 4, 33, and 34, on the south boundary of the township, hereinbefore described.

N. 2° 47.0' W., between sections 33 and 34.

- 40.419 Point for the 1/4 section corner of sections 33 and 34, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 20 inches in the ground, with magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T24S R9W  
1/4  
S33 | S34  
2007

Set steel fence post alongside aluminum post.

- 80.838 Point for the corner of sections 27, 28, 33, and 34, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 25 inches in the ground, with magnet at base, in a mound of

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

stone, 3 ft. base, to top of aluminum cap marked:

T24S R9W	
S28	S27
S33	S34
2007	

Set steel fence post alongside aluminum post.

---

From the corner of sections 26, 27, 34, and 35.

S. 89° 49.7' W., between sections 27 and 34.

- 40.405 The 1/4 section corner of sections 27 and 34, monumented with a lava stone, 14x12x10 inches, firmly set, plainly marked 1/4, with a mound of stone, 4 ft. base, 3 ft. high, north of corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with magnet at base, and aluminum cap marked:

	T24S R9W
	S27
1/4	-----
	S34
	2007

Bury the marked stone alongside aluminum post.

Set steel fence post alongside aluminum post.

---

N. 85° 32.9' W., beginning new measurement.

- 40.797 The corner of sections 27, 28, 33, and 34.
- 

N. 2° 31.2' E., between sections 27 and 28.

- 40.411 Point for the 1/4 section corner of sections 27 and 28, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 25 inches in the ground, with magnet at base, and aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T24S R9W  
1/4  
S28 | S27  
2007

Set steel fence post alongside aluminum post.

- 80.822 The corner of sections 21, 22, 27, and 28, monumented with a lava stone, 16x12x8 inches, lying on its side, marked with 2 notches on S. edge and 3 notches on E. edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 24 inches in the ground, with magnet at base, and aluminum cap marked:

T24S R9W  
S21 | S22  
S28 | S27  
2007

Bury the marked stone along S. side of aluminum post.

Corner is located in sage brush. A N-S road bears E., 1 chain distance.

From the corner of sections 22, 23, 26, and 27.

N. 88° 43.4' W., between sections 22 and 27.

- 39.930 Point for the 1/4 section corner of sections 22 and 27, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 24 inches in the ground, with magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T24S R9W  
S22  
1/4 —————  
S27  
2007

Set steel fence post alongside aluminum post.

- 79.860 The corner of sections 21, 22, 27, and 28.

N. 0° 47.5' E., between sections 21 and 22.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 41.981** Point for the 1/4 section corner of sections 21 and 22, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with magnet at base, and aluminum cap marked:

T24S R9W  
1/4  
S21 | S22  
2007

Set steel fence post alongside aluminum post.

- 83.962** The corner of sections 15, 16, 21, and 22, monumented with a granite stone, 15x12x6 inches, firmly set, marked with 3 notches on S. edge and 3 notches on E. edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T24S R9W  
S16 | S15  
S21 | S22  
2007

Bury the marked stone alongside aluminum post.

Corner is located on W. edge of wash, drains S.

Set steel fence post alongside aluminum post.

From the corner of sections 14, 15, 22, and 23.

**N. 86° 56.7' W.**, between sections 15 and 22.

- 39.223** Point for the 1/4 section corner of sections 15 and 22, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 2 inches in the ground to solid rock, with magnet at base, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T24S R9W  
S15  
1/4 

---

 S22  
2007

Corner is located on westerly facing slope.

Set steel fence post alongside aluminum post.

78.446 The corner of sections 15, 16, 21, and 22.

---

N. 0° 31.5' W., between sections 15 and 16.

40.257 The 1/4 section corner of sections 15 and 16, monumented with a granite boulder, 30x20x14 inches, firmly set, marked 1/4 on W. face, in a scattered mound of stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with magnet at base, and aluminum cap marked:

T24S R9W  
1/4  
S16 | S15  
2007

Bury the marked stone along W. side of aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, west of corner.

Corner is located on westerly facing slope.

Set steel fence post alongside aluminum post.

---

N. 0° 11.8' W., beginning new measurement.

40.051 The corner of sections 9, 10, 15, and 16, determined at the center of a scattered mound of stone. This is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 4 inches in the ground to solid rock, with magnet at base, in a mound of stone, 5 ft. base, to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T24S R9W	
S9	S10
S16	S15
2007	

Corner is located 1.20 chains distance, N. of wash, drains westerly.

Set steel fence post alongside aluminum post.

---

From the corner of sections 10, 11, 14, and 15.

N. 85° 30.4' W., between sections 10 and 15.

- 39.471 The 1/4 section corner of section 10 and 15, monumented with a limestone, 13x10x6 inches, firmly set, marked 1/4 on N. face, in a scattered mound of stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 6 inches in the ground to solid rock, with magnet at base, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

	T24S R9W
	S10
1/4	—————
	S15
	2007

Bury the marked stone alongside aluminum post.

Corner is located on easterly facing slope.

Set steel fence post alongside aluminum post.

---

S. 89° 46.4' W., beginning new measurement.

- 40.514 The corner of sections 9, 10, 15, and 16.
- 

N. 0° 51.5' E., between sections 9 and 10.

- 40.178 Point for the 1/4 section corner of sections 9 and 10, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 10 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T24S R9W  
1/4  
S9 | S10  
2007

Corner is located on NW facing slope.

Set steel fence post alongside aluminum post.

- 80.356 True point for the corner of sections 3, 4, 9, and 10, at proportionate distance, there is no remaining evidence of the original corner. Point falls on edge of rock outcropping where it is unsuitable for monumentation.

From which

Point selected for the off line witness corner of sections 3, 4, 9, and 10, bears S. 0°07.4' E., 0.389 chains distance. Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 2 inches in the ground to solid rock, with magnet at base, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T24S R9W  
WC  
S4 ↑ S3  
S9 | S10  
2007

Corner is located on rocky, NE facing slope.

Set steel fence post alongside aluminum post.

---

From the corner of sections 2, 3, 10, and 11.

N. 88° 46.1' W., between sections 3 and 10.

- 20.074 Point for the E 1/16 section corner of sections 3 and 10.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with magnet at base, and aluminum cap marked:

S3  
E 1/16 —————  
S10  
2007

Set steel fence post alongside aluminum post.

- 40.148 Point for the 1/4 section corner of sections 3 and 10, at proportionate distance, there is no remaining evidence of the

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 20 inches in the ground, with magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

	T24S R9W
	S3
1/4	—————
	S10
	2007

Set steel fence post alongside aluminum post.

60.222 Point for the W 1/16 section corner for sections 3 and 10.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 3 inches in the ground to solid rock, with magnet at base, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

	S3
W 1/16	—————
	S10
	2007

Corner is located on steep, SE facing slope.

Set steel fence post alongside aluminum post.

80.296 The corner of sections 3, 4, 9, and 10.

---

N. 1° 44.6' E., between sections 3 and 4.

20.096 Point for the S 1/16 section corner for sections 3 and 4.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 2 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

	S 1/16
	S4   S3
	2007

Set steel fence post alongside aluminum post.

40.192 Point for the 1/4 section corner of sections 3 and 4, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter,

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

18 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T24S R9W  
1/4  
S4 | S3  
2007

Set steel fence post alongside aluminum post.

60.288 Point for the N 1/16 section corner for sections 3 and 4.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 20 inches in the ground to solid rock, with magnet at base, in a mound of stone, 2 1/2 ft. base, to top of aluminum cap marked:

N 1/16  
S4 | S3  
2007

Set steel fence post alongside aluminum post.

80.886 The corner of sections 3, 4, 33, and 34, on the north boundary of the township, hereinbefore described.

From the corner of sections 4, 5, 32, and 33, on the south boundary of the township, hereinbefore described.

N. 1° 20.5' E., between sections 32 and 33.

40.153 Point for the 1/4 section corner of sections 32 and 33, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 24 inches in the ground, with magnet at base, and aluminum cap marked:

T24S R9W  
1/4  
S32 | S33  
2007

Set steel fence post alongside aluminum post.

80.306 The corner of sections 28, 29, 32, and 33, determined at an iron post, 2 inches in diameter, projecting 15 inches above the

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

ground, without a cap, in a collar of stone, with a 4 inch square wood post set alongside. This iron post, is similar to iron posts found along the south boundary of the township at the corner of sections 4, 5, 32, and 33, and the 1/4 section corner of sections 4 and 33, hereinbefore described. Therefore, this point is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T24S R9W	
S29	S28
S32	S33
2007	

Bury the iron post and wood post alongside aluminum post.

Set steel fence post alongside aluminum post.

---

From the corner of sections 27, 28, 33, and 34.

S. 85° 14.4' W., between sections 28 and 33.

40.907 The 1/4 section corner of section 28 and 33, monumented with a lava stone, 15x12x10 inches, firmly set and dimly marked 1/4 on N face, in a mound of stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 20 inches in the ground, with magnet at base, in a mound of stone, 2 ft. base, to top of aluminum cap marked:

T24S R9W	
S28	
1/4	
S33	
2007	

Bury the marked stone alongside aluminum post.

Set steel fence post alongside aluminum post.

---

N. 85° 32.6' W., beginning new measurement.

32.447 The corner of sections 28, 29, 32, and 33.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

N. 2° 40.0' W., between sections 28 and 29.

- 41.108 Point for the 1/4 section corner of sections 28 and 29, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with magnet at base, in a collar of stone, with aluminum cap marked:

T24S R9W
1/4
S29   S28
2007

Set steel fence post alongside aluminum post.

- 82.216 The corner of sections 20, 21, 28, and 29, monumented with granite stone, 22x11x10 inches, firmly set, projecting 11 inches above the ground, marked with 2 notches on S. edge and 4 notches on E. edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with magnet at base, in a collar of stone, with aluminum cap marked:

T24S R9W
S20   S21
S29   S28
2007

Bury the marked stone along S. side of aluminum post.

Corner is located in sage brush.

Set steel fence post alongside aluminum post.

From the corner of sections 21, 22, 27, and 28.

N. 89° 38.2' W., between sections 21 and 28.

- 40.239 Point for the 1/4 section corner of sections 21 and 28, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 20 inches in the ground, with magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T24S R9W  
S21  
1/4 —————  
S28  
2007

Set steel fence post alongside aluminum post.

80.478 The corner of sections 20, 21, 28, and 29.

---

N. 1° 02.5' E., between sections 20 and 21.

41.774 Point for the 1/4 section corner of sections 20 and 21, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 24 inches in the ground, with magnet at base, and aluminum cap marked:

T24S R9W  
1/4  
S20 | S21  
2007

Corner is located in sage and grasses.

Set steel fence post alongside aluminum post.

83.548 The corner of sections 16, 17, 20, and 21, monumented with a lava stone, 14x10x6 inches, firmly set, projecting 6 inches above the ground, marked with 3 notches on S. edge and 4 notches on E. edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with magnet at base, in a collar of stone, with aluminum cap marked:

T24S R9W  
S17 | S16  
S20 | S21  
2007

Bury the marked stone along S. side of aluminum post.

Corner is located in open sage and grasses.

Set steel fence post alongside aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 15, 16, 21, and 22.

N. 89° 56.1' W., between sections 16 and 21.

- 40.051 Point for the 1/4 section corner of sections 16 and 21, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with magnet at base, and aluminum cap marked:

	T24S R9W
	S16
1/4	—————
	S21
	2007

Raise a mound of stone, 2 ft. base, 1 ft. high, north of corner.

Set steel fence post along E. side of aluminum post.

- 80.102 The corner of sections 16, 17, 20, and 21.

N. 0° 09.3' E., between sections 16 and 17.

- 39.951 Point for the 1/4 section corner of sections 16 and 17, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 25 inches in the ground, with magnet at base, and aluminum cap marked:

	T24S R9W
	1/4
	S17   S16
	2007

Set steel fence post alongside aluminum post.

- 79.902 The corner of sections 8, 9, 16, and 17, monumented with a granite stone, 8x6x4 inches, firmly set, marked with 4 notches on S. edge and 4 notches on E. edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 18 inches in the ground to solid rock, with magnet at base, and

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

aluminum cap marked:

T24S R9W	
S8	S9
S17	S16
2007	

Bury the marked stone alongside aluminum post.

Corner is surrounded by junipers.

---

From the corner of sections 9, 10, 15, and 16.

S. 88° 57.5 W., between sections 9 and 16.

- 39.529 The 1/4 section corner of section 9 and 16, monumented with a granite stone, 18x12x8 inches, firmly set, dimly marked 1/4 on N. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 20 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

	T24S R9W	
	S9	
1/4		
	S16	
	2007	

Bury the marked stone alongside aluminum post.

Corner is located on southerly facing slope.

Set steel fence post alongside aluminum post.

---

N. 89° 25.0' W., beginning new measurement.

- 39.843 The corner of sections 8, 9, 16, and 17.
- 

N. 0° 24.6' E., between sections 8 and 9.

- 40.071 Point for the 1/4 section corner of sections 8 and 9, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 24 inches in the ground, with magnet at base, and aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T24S R9W  
1/4  
S8 | S9  
2007

Set steel fence post along E. side of aluminum post.

- 80.142 The corner of sections 4, 5, 8, and 9, monumented with a granite stone, 17x12x10 inches, firmly set, plainly marked with 5 notches on S. edge and 4 notches on E. edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 20 inches in the ground to solid rock, with magnet at base, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T24S R9W  
S5 | S4  
S8 | S9  
2007

Bury the marked stone alongside the aluminum post.

Corner is located on E. edge of wash, drains northerly.

Set steel fence post alongside aluminum post.

From the true point for the corner of sections 3, 4, 9, and 10.

S. 89° 37.7' W., between sections 4 and 9.

- 39.989 Point for the 1/4 section corner of sections 4 and 9, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with magnet at base, and aluminum cap marked:

T24S R9W  
S4  
1/4 —————  
S9  
2007

Corner is located on SE facing slope.

Set steel fence post alongside aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

79.978 The corner of sections 4, 5, 8, and 9.

---

N. 0° 56.8' E., between sections 4 and 5.

39.985 The 1/4 section corner of sections 4 and 5, monumented with a granite stone, firmly set, and plainly marked 1/4 on W. face, with a mound of stone, 4 ft. base, 2 ft. high, west of corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 24 inches in the ground, with magnet at base, and aluminum cap marked:

T24S R9W  
1/4  
S5 | S4  
2007

Bury the marked stone alongside aluminum post.

Set steel fence post alongside aluminum post.

---

N. 0° 58.4' E., beginning new measurement.

20.337 Point for the N 1/16 section corner for sections 4 and 5, not monumented.

41.385 The corner of sections 4, 5, 32, and 33, on the north boundary of the township, hereinbefore described.

---

The Subdivision of Section 3,  
Township 24 South, Range 9 West, Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 3 and 10.

N. 1° 51.9' E., on the N-S centerline of section 3.

20.249 Point for the center S 1/16 section corner of section 3, not monumented.

40.498 Point for the center 1/4 section corner of section 3 at the intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with magnet at base, and aluminum cap marked:

THE SUBDIVISION OF SECTION 3,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

T24S R9W

C 1/4 S3

2007

Set steel fence post alongside aluminum post.

60.741 Point for the center N 1/16 section corner of section 3.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with magnet at base, and aluminum cap marked:

$$\begin{array}{c} \text{C} \\ | \\ \text{N } 1/16 \quad | \quad \text{S3} \\ | \\ \text{C} \\ 2007 \end{array}$$

Set steel fence post alongside aluminum post.

81.693 The 1/4 section corner of sections 3 and 34, on the north boundary of the township.

---

From the 1/4 section corner of sections 2 and 3.

N. 89°12.0' W., on the E-W centerline of section 3.

20.123 Point for the center E 1/16 section corner of section 3.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with magnet at base, and aluminum cap marked:

$$\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{ --- } \text{C} \\ \text{S3} \\ 2007 \end{array}$$

Set steel fence post alongside aluminum post.

40.246 The center 1/4 section corner of section 3.

60.363 Point for the center W 1/16 section corner of section 3, not monumented.

80.480 The 1/4 section corner of sections 3 and 4.

---

From the center E 1/16 section corner of section 3.

THE SUBDIVISION OF SECTION 3,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

N. 1°56.1' E., on the N-S centerline of the NE 1/4 of section 3.

- 20.322 Point for the NE 1/16 section corner of section 3, at the intersection with the E-W centerline of the NE 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with magnet at base, and aluminum cap marked:

NE 1/16 S3

2007

Set steel fence post alongside aluminum post.

- 41.456 The point for the E 1/16 section corner of sections 3 and 34, on the north boundary of the township.

From the point for the N 1/16 section corner of sections 2 and 3.

N. 89°25.1' W., on the E-W centerline of the NE 1/4 of section 3.

- 20.148 The NE 1/16 section corner of section 3.

- 40.296 The center N 1/16 section corner of section 3.

From the E 1/16 section corner of sections 3 and 10.

N. 1°56.0' E., on the N-S centerline of the SE 1/4 of section 3.

- 40.648 The center E 1/16 section corner of section 3.

From the W 1/16 section corner of sections 3 and 10.

N. 1°48.2' E., on the N-S centerline of the SW 1/4 of section 3.

- 20.172 Point for the SW 1/16 section corner of section 3, at the intersection with the E-W centerline of the SW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 22 inches in the ground, with magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

SW 1/16 S3

2007

Corner is located on steep, NE facing slope.

Set steel fence post alongside aluminum post.

THE SUBDIVISION OF SECTION 3,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

40.344 The point for the center W 1/16 section corner of section 3.

---

From the point for the center S 1/16 section corner of section 3.  
N. 88°59.2' W., on the E-W centerline of the SW 1/4 of section 3.

20.095 The SW 1/16 section corner of section 3.

40.190 The S 1/16 section corner of sections 3 and 4.

---

From the center N 1/16 of section 3.  
N. 89°24.7' W., on the E-W centerline of the NW 1/4 of section 3.

40.277 The N 1/16 of sections 3 and 4.

---

The Subdivision of Section 4,  
Township 24 South, Range 9 West, Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 4 and 9.  
N. 1°21.0' E., on the N-S centerline of section 4.

40.089 Point for the center 1/4 section corner of section 4 at the intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 8 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T24S R9W

C 1/4 S4

2007

Set steel fence post alongside aluminum post.

60.304 Point for the center N 1/16 section corner of section 4.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 18 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

C  
|  
N 1/16 | S4  
|  
C  
2007

THE SUBDIVISION OF SECTION 4,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located at toe of NE facing slope.

Set steel fence post alongside aluminum post.

- 81.125 The 1/4 section corner of sections 4 and 33, on the north boundary of the township.

From the 1/4 section corner of sections 3 and 4.

S. 89°29.6' W., on the E-W centerline of section 4.

- 40.264 The center 1/4 section corner of section 4.

- 60.399 Point for the center W 1/16 section corner of section 4, not monumented.

- 80.534 The 1/4 section corner of sections 4 and 5.

From the point for the center W 1/16 section corner of section 4.

N. 1°09.6' E., on the N-S centerline of the NW 1/4 of section 4.

- 20.276 Point for the NW 1/16 section corner of section 4, at the intersection with the E-W centerline of the NW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 24 inches in the ground, with magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

NW 1/16 S4

2007

Set steel fence post alongside aluminum post.

- 41.210 The W 1/16 section corner of sections 4 and 33, on the north boundary of the township.

From the center N 1/16 section corner of section 4.

THE SUBDIVISION OF SECTION 4,  
TOWNSHIP 24 SOUTH, RANGE 9 WEST, SALT LAKE MERIDIAN, UTAH

*CHAINS*

S. 89°40.0' W., on the E-W centerline of the NW 1/4 of section 4.

20.199 The NW 1/16 section corner of section 4.

40.398 The point for the N 1/16 section corner of sections 4 and 5.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Tyler Trujillo	Cadastral Surveyor
Calvert C. Norton	Survey Technician
Adrian M. Kurip	Survey Technician
Leland Parazoo	Survey Aid

---

## CERTIFICATE OF SURVEY

I, *Daniel T. Gillins*, Cadastral Surveyor, under the supervision of *Ronald K. Baugh*, Supervisory Cadastral Surveyor, and hereby certify upon honor, that in pursuance of special instructions bearing the date of the *30th day of August, 2007*, have *dependently resurveyed the east and north boundaries, a portion of the south boundary, and a portion of the subdivisional lines, and subdivided sections 3 and 4, in Township 24 South, Range 9 West*, of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions of the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Jan. 13, 2010  
(Date)

*Ronald K. Baugh*  
(Supervisory Cadastral Surveyor)

Jan. 13, 2010  
(Date)

*Daniel T. Gillins*  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of the east and north boundaries, a portion of the south boundary, and a portion of the subdivisional lines, and the subdivision of sections 3 and 4, in Township 24 South, Range 9 West, Salt Lake Meridian, Utah*, Executed by *Daniel T. Gillins*, Cadastral Surveyor, under the supervision of *Ronald K. Baugh*, Supervisory Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

February 3, 2010  
(Date)

*Daniel W. Webb*  
(Chief Cadastral Surveyor for Utah)