

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,

AND

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SURVEY OF THE SOUTH AND EAST BOUNDARIES,

A PORTION OF THE NORTH BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

THE MEANDERS OF THE PRESENT LEFT BANK, AND AN INFORMATIVE TRAVERSE

OF THE PRESENT RIGHT BANK OF THE SAN JUAN RIVER

THROUGH SECTIONS 4, 5, 7, AND 8

IN

**TOWNSHIP 42 SOUTH, RANGE 19 EAST**

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Jeremy D. Davis, Cadastral Surveyor*

Under Special Instructions dated **January 9, 2009**, approved **January 9, 2009**, which provided for the surveys included under Group Number **1095**, and assignment instructions dated **January 9, 2009**.

Survey Commenced, **January 12, 2009**  
Survey Completed, **March 12, 2009**

## INDEX DIAGRAM

Township 42 South, Range 19 East

3	3	16	16	15	15
6	5	4	35 3	29 2	23 1 14
4	4	41			
4	49	40	34	29	23
7	8	40 9	34 10	28 11	22 12 14
49					
48	48	39	33	28	22
18	47 17	39 16	33 15	27 14	21 13 13
46	46	38	33	27	20
19	45 20	37 21	32 22	26 23	20 24 12
44	44	37	32	26	19
30	43 29	36 28	31 27	25 26	19 25 11
43	42	36	30	24	18
31	41 32	35 33	30 34	24 35	17 36 11
10	9	9	8	7	6

Meanders of the left bank of the San Juan River.....Page 50  
 An informative traverse of the right bank of the San Juan River...Page 53

## TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of a portion of the north boundary, and a portion of the subdivisional lines, and the survey of the south and east boundaries, a portion of the north boundary, a portion of the subdivisional lines, and the meanders of the present left bank, and an informative traverse of the present right bank of the San Juan River through sections 4, 5, 7, and 8, in Township 42 South, Range 19 East, Salt Lake Meridian, Utah.

**History of Surveys**

		<b>Surveyed by</b>	<b>Retr. Or Resurveyed by</b>	
<b>SOUTH BOUNDARY</b>				
All		Unsurveyed		
<b>EAST BOUNDARY</b>				
All		Unsurveyed		
<b>WEST BOUNDARY</b>				
Portion	E.E. Miller		1909	
Portion				J.L. Thomas
All	S.A. Burkhardt		2008	2000
<b>NORTH BOUNDARY</b>				
Portion	E.E. Miller		1909	
<b>SUBDIVISION</b>				
Portion	E.E. Miller		1909	
Portion				J.L. Thomas
				2000

Note: There are several U.S. Mineral Surveys in sections 5, 6, 7, and 8.

## TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 1095, dated January 9, 2009.

The direction of the lines was determined by references to true meridians, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods*, dated May 9, 2001, Version 1.0. Trimble Model 5800 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic Control was derived from GPS static observations, post processed by the National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS): **MONTICELLO\_UT2006, AZTEC, and CHACOCNHP\_NM2005.**

The geographic position of the corner of Townships 42 and 43 South, Ranges 19 and 20 East, as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

**Latitude: 37°05'04.978" N., Longitude: 109°45'52.082" W.,**  
N.A.D. 1983, Network Accuracy = 0.200 meter at 95% confidence.

All stainless steel monuments set in this survey bear the Navajo seal.

**CHAINS**

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

Dependent Resurvey of a Portion of the North Boundary in  
Township 42 South, Range 19 East, Salt Lake Meridian, Utah

Reestablishment of the Survey Executed  
by E.E. Miller in 1909

Beginning at the 1/4 section corner of sections 6 and 31, on the north boundary of the township, monumented with an iron post, 1 inch diameter, firmly set, projecting 6 inches above the ground with brass cap marked as described in the official record of the 1909 survey.

Corner is located on level open ground.

**S. 89°58.1' E.**, between sections 6 and 31.

**40.138** The corner of sections 5, 6, 31, and 32, monumented with an iron post, 3 inches diameter, firmly set, projecting 16 inches above the ground, with brass cap marked as described in the official record of the 1909 survey.

Corner is located on level open ground, on north edge of two track road, bears southwest and northeast.

**EAST**, between sections 5 and 32.

**40.000** Point for the 1/4 section corner of sections 5 and 32. There is no remaining evidence of the iron post.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, and brass cap marked:

T41S  
S32  
1/4 ———  
S5  
T42SR19E  
2009

Set a steel fence post 1.5 links north of the stainless steel post.

Corner is located on gentle rolling land.

**77.136** Point for the meander corner of sections 5 and 32, on the right bank of San Juan River.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, and brass cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

T41S  
S32  
-----/ MC  
S5  
T42SR19E  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

80.000 Point for the corner of sections 4, 5, 32, and 33, falls in the San Juan River; not monumented.

Dependent Resurvey of a Portion of the Subdivisional Lines in  
Township 42 South, Range 19 East, Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by E.E. Miller  
in 1909, and the Resurvey Executed by J.L. Thomas in 2000

From the corner of sections 5, 6, 7, and 8, monumented with an iron post, 2 inches diameter, firmly set, projecting 12 inches above a small mound of stone, with brass cap marked as described in the official record of the 1909 survey.

Corner is located on level open ground.

**EAST**, between sections 5 and 8.

29.480 Record distance for the 1909 meander corner of sections 5 and 8. There is no remaining evidence of the iron post.

31.459 Point for the present meander corner of sections 5 and 8, on the right bank of San Juan River.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, and aluminum cap marked:

T42SR19E  
S5  
-----/ MC  
S8  
2009

Raise a small mound of stone east of the aluminum post.

From the corner of sections 5, 6, 7, and 8.

**S. 0°02.1' E.**, between sections 7 and 8.

39.907 The 1/4 section corner of sections 7 and 8, monumented with

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

an aluminum post, 2 1/2 inches diameter, firmly set, projecting 4 inches above the ground, with aluminum cap marked as described in the official record of the 2000 resurvey.

---

**S. 0°01.3' E.**, beginning new measurement.

- 19.941** The meander corner of sections 7 and 8, monumented with a stainless steel post, 1 inch diameter, firmly set, projecting 5 inches above the ground, with brass cap marked as described in the official record of the 1909 survey. This corner will now function as the witness corner of sections 7 and 8. The right bank of the San Juan River has moved **SOUTH, 2.239 chains** from this point.

I add WC and 2009 to the brass cap.

Corner is located on level ground, north of the right bank of the San Juan River.

- 22.180** True point for the meander corner of sections 7 and 8, on the right bank of the San Juan River; not monumented.

---

Reestablishment of the Survey Executed by  
E.E. Miller in 1909

From the corner of sections, 4, 5, 32, and 33, on the north boundary of the township, hereinbefore described.

**S. 0°03.0' E.**, between sections 4 and 5.

- 3.908** True point for the meander corner of sections 4 and 5, falls in flood plain, where it is inaccessible and impractical to monument; not monumented.
- 4.930** Record distance for the 1909 meander corner of sections 4 and 5. There is no remaining evidence of the iron post; not monumented.
- 40.000** Point for the 1/4 section corner of sections 4 and 5, falls on steep ledges, where it is inaccessible and impractical to monument.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

- 46.587** Point for the witness meander corner of sections 4 and 5.  
Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with magnet at base, in a mound of stone, 2 feet base to top of aluminum cap marked:

T42SR19E  
S5 ↓ S4  
WCMC  
2009

Set a steel fence post alongside the aluminum post.

Corner is located at base of tall ledges on level ground.

- 46.660** Record distance for the meander corner of sections 4 and 5. There is no remaining evidence of the iron post.
- 47.391** True point for meander corner of sections 4 and 5, falls in flood plain, where it is inaccessible and impractical to monument; not monumented.

Survey of the South Boundary in  
Township 42 South, Range 19 East, Salt Lake Meridian, Utah

From the point for the corner of Townships 42 and 43 South, Ranges 19 and 20 East, determined at a point 480.000 chains **South** from the corner of Townships 41 and 42 South, Ranges 19 and 20 East.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 5 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42S  
R19E R20E  
S36 | S31  
S1 | S6  
T43S  
2009

Set a steel fence post 13.7 links northwest of the stainless steel post.

Corner is located on a gradual southeast slope with outcrops of sandstone.

**N. 89°50.0' W.**, between sections 1 and 36.

- 40.000** Point for the 1/4 section corner of sections 1 and 36.

SURVEY OF THE SOUTH BOUNDARY IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, and brass cap marked:

T42SR19E  
S36  
1/4 ———  
S1  
2009

Set a steel fence post 2.3 links north of the stainless steel post.

Corner is located on level sandy ground.

**80.000** Point for the corner of sections 1, 2, 35, and 36.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground to solid rock, with magnet at base, and brass cap marked:

T42SR19E  
S35 | S36  
S2 | S1  
T43S  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on level sandy ground.

**N. 89°50.0' W.,** between sections 2 and 35.

**40.000** Point for the 1/4 section corner of sections 2 and 35.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, and brass cap marked:

T42SR19E  
S35  
1/4 ———  
S2  
T43S  
2009

Set a steel fence post 2.3 links north of the stainless steel post.

Corner is located on level sandy ground.

**80.000** Point for the corner of sections 2, 3, 34, and 35.

SURVEY OF THE SOUTH BOUNDARY IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42SR19E  
S34 | S35  
S3 | S2  
T43S  
2009

Set a steel fence post 4.6 links north of the stainless steel post.

Corner is located on gradual northwest slope.

---

**N. 89°50.0' W.**, between sections 3 and 34.

**40.000** Point for the 1/4 section corner of sections 3 and 34.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42SR19E  
S34  
1/4           
S3  
T43S  
2009

Set a steel fence post 3.1 links north of the stainless steel post.

Corner is located on gradual southeast slope.

**80.000** Point for the corner of sections 3, 4, 33, and 34.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, and brass cap marked:

T42SR19E  
S33 | S34  
S4 | S3  
T43S  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

SURVEY OF THE SOUTH BOUNDARY IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located on level sandy ground.

---

**N. 89°50.0' W.**, between sections 4 and 33.

- 40.000** Point for the 1/4 section corner of sections 4 and 33.  
Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, in a mound of stone, 2 feet base to top of brass cap marked:

T42SR19E  
S33  
1/4 —————  
S4  
T43S  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on gradual southwest slope.

- 80.000** Point for the corner of sections 4, 5, 32, and 33.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, and brass cap marked:

T42SR19E  
S32|S33  
S5|S4  
T43S  
2009

Raise a mound of stone, 3 feet base, 2 feet high, west of the stainless steel post.

Set a steel fence post 4.6 links north of the stainless steel post.

Corner is located on a gradual southwest slope.

---

**N. 89°50.0' W.**, between sections 5 and 32.

- 40.000** Point for the 1/4 section corner of sections 5 and 32.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, and brass cap marked:

SURVEY OF THE SOUTH BOUNDARY IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

T42SR19E  
S32  
1/4 —————  
S5  
T43S  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on level sandy ground.

**80.000** Point for the corner of sections 5, 6, 31, and 32.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, and brass cap marked:

T42SR19E  
S31|S32  
S6|S5  
T43S  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on a gradual north facing slope.

---

**N. 89°50.0' W.**, between sections 6 and 31.

**40.000** Point for the 1/4 section corner of sections 6 and 31.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, and brass cap marked:

T42SR19E  
S31  
1/4 —————  
S6  
T43S  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on gradual north facing slope.

---

**77.752** The corner of Townships 42 and 43 South, Ranges 18 and 19 East, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set in a mound of stone, 3 feet base to top

SURVEY OF THE EAST BOUNDARY IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

of brass cap marked as described in the official record of the 2008 survey. From which a steel fence post bears north, 1.6 links distance.

Survey of the East Boundary in  
Township 42 South, Range 19 East, Salt Lake Meridian, Utah

From the corner of Townships 42 and 43 South, Ranges 19 and 20 East, hereinbefore described.

**NORTH**, between sections 31 and 36.

- 40.000** Point for the 1/4 section corner of sections 31 and 36. Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42S  
R19E R20E  
1/4  
S36 | S31  
2009

Set a steel fence post 3.1 links north of the stainless steel post.

Corner is located on level sandy ground.

- 80.000** Point for the corner of sections 25, 30, 31, and 36. Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42S  
R19E R20E  
S25 | S30  
S36 | S31  
2009

Set a steel fence post 3.1 links north of the stainless steel post.

Corner is located on level sandy ground.

**NORTH**, between sections 25 and 30.

- 40.000** Point for the 1/4 section corner of sections 25 and 30.

SURVEY OF THE EAST BOUNDARY IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, on solid rock, with magnet at base, in a mound of stone, 4 feet base to top of brass cap marked:

T42S  
R19ER20E  
1/4  
S25 | S30  
2009

Set a steel fence post 2.3 links north of the stainless steel post.

Corner is located in wash, course north.

**80.000** Point for the corner of sections 19, 24, 25, and 30.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with magnet at base, and brass cap marked:

T42S  
R19ER20E  
S24 | S19  
S25 | S30  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on a gradual southeast slope in loose sandy soil.

**NORTH**, between sections 19 and 24.

**40.000** Point for the 1/4 section corner of sections 19 and 24.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, and brass cap marked:

T42S  
R19ER20E  
1/4  
S24 | S19  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located in small drainage, course northwest.

SURVEY OF THE EAST BOUNDARY IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

**80.000** True point for the corner of sections 13, 18, 19, and 24, falls in deep wash, where it is inaccessible and impractical to monument.

From this point

Point selected for the off line witness corner of sections 13, 18, 19, and 24, bears **N. 49°57.3' W., 0.373 chains** distance.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42S
R19ER20E
S13   S18
S24   S19
WC →
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on finger ridge, bears northwest and southeast.

**NORTH**, between sections 13 and 18.

**40.000** Point for the 1/4 section corner of sections 13 and 18.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42S
R19ER20E
1/4
S13   S18
2009

Set a steel fence post 6.1 links west of the stainless steel post.

Corner is located level ground.

**80.000** Point for the corner of sections 7, 12, 13, and 18.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

SURVEY OF THE EAST BOUNDARY IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

T42S  
R19ER20E  
S12 | S7  
S13 | S18  
2009

Set a steel fence post 3.1 links north of the stainless steel post.

Corner is located in large wash, course southeast.

---

**NORTH**, between sections 7 AND 12.

- 40.000** Point for the 1/4 section corner of sections 7 and 12.  
Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with magnet at base, in a mound of stone, 2 feet base to top of brass cap marked:

T42S  
R19ER20E  
1/4  
S12 | S7  
2009

Set a steel fence post 1.6 links north of the iron post.

Corner is located level ground.

- 80.000** Point for the corner of sections 1, 6, 7, and 12.  
Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42S  
R19ER20E  
S1 | S6  
S12 | S7  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on a gradual southeast slope, between an upper and middle rock band.

---

**NORTH**, between sections 1 and 6.

- 40.000** Point for the 1/4 section corner of sections 1 and 6.  
Set a stainless steel post, 30 inches long, 2 1/2 inches

SURVEY OF THE EAST BOUNDARY IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

diameter, 10 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42S  
R19ER20E  
1/4  
S1 | S6  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located level ground.

80.000 The corner of Townships 41 and 42 South, Ranges 19 and 20 East, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set in a mound of stone, 3 feet base to top of brass cap marked as described in the official record of the 2008 survey. From which a steel fence post bears north of stainless steel post.

Corner is located on level ground.

Survey of a Portion of the North Boundary in  
Township 42 South, Range 19 East, Salt Lake Meridian, Utah

From the corner of Townships 41 and 42 South, Ranges 19 and 20 East, hereinbefore described.

**WEST**, between sections 1 and 36.

40.000 Point for the 1/4 section corner of sections 1 and 36, falls at a location where it is inaccessible and impractical to monument; not monumented.

80.000 Point for the corner of sections 1, 2, 35, and 36, falls at a location where it is inaccessible and impractical to monument; not monumented.

**WEST**, between sections 2 and 35.

40.000 Point for the 1/4 section corner of sections 2 and 35, falls at a location where it is inaccessible and impractical to monument; not monumented.

80.000 True point for the corner of sections 2, 3, 34, and 35, falls on ledges, where it is inaccessible and impractical to monument.


SURVEY OF A PORTION OF THE NORTH BOUNDARY IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

From this point

Point selected for the off line witness corner of sections 2, 3, 34, and 35, bears **N. 60°25.4' E., 0.524 chains** distance.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with magnet at base, in a mound of stone, 2 feet base to top of aluminum cap marked:




Corner is located on steep southeast slope.

---

**WEST**, between sections 3 and 34.

**40.000** Point for the 1/4 section corner of sections 3 and 34.


Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of aluminum cap marked:



Corner is located on level ground.

**80.000** Point for the corner of sections 3, 4, 33, and 34.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of aluminum cap marked:



Corner is located on gradual southwest slope.

---

**WEST**, between sections 4 and 33.

**40.000** Point for the 1/4 section corner of sections 4 and 33.

SURVEY OF A PORTION OF THE NORTH BOUNDARY IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of aluminum cap marked:

T41SR19E  
S33  
1/4 —————  
S4  
T42S  
2009

Corner is located on steep east slope on west side of wash, course southwest.

**N. 88°37.7' W.**, beginning new measurement.

**37.617** Left bank of San Juan River, point for the meander corner of sections 4 and 33.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with magnet at base, in a mound of stone, 2 feet base to top of brass cap marked:

T41SR19E  
S33  
MC / —————  
S4  
T42S  
2009

Corner is located on the left bank of San Juan River.

**39.156** True point for the corner of sections 4, 5, 32, and 33, hereinbefore described.

Survey of a Portion of the Subdivisional Lines in  
Township 42 South, Range 19 East, Salt Lake Meridian, Utah

From the corner of sections 1, 2, 35, and 36, on the south boundary of the township, hereinbefore described.

**N. 0°00.7' W.**, between sections 35 and 36.

**40.000** Point for the 1/4 section corner of sections 35 and 36.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, and brass cap marked:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

T42SR19E  
1/4  
S35 | S36  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on level open ground.

80.000 Point for the corner of sections 25, 26, 35, and 36.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42SR19E  
S26 | S25  
S35 | S36  
2009

Set a steel fence post 3.1 links north of the stainless steel post.

Corner is located on level sandy ground.

From the corner of sections 25, 30, 31, and 36, on the east boundary of the township, hereinbefore described.

N. 89°50.0' W., between sections 25 and 36.

40.000 Point for the 1/4 section corner of sections 25 and 36.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, and brass cap marked:

T42SR19E  
S25  
1/4 ———  
S36  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on level rolling ground.

80.000 The corner of sections 25, 26, 35, and 36.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

**N. 0°00.7' W.**, between sections 25 and 26.

**40.000** Point for the 1/4 section corner of sections 25 and 26.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42SR19E  
1/4  
S26 | S25  
2009

Set a steel fence post 3.1 links north of the stainless steel post.

Corner is located on a gradual southeast slope.

**80.000** True point for the corner of sections 23, 24, 25, and 26, falls in a wash, where it is inaccessible and impractical to monument.

From this point

Point selected for the off line witness corner of sections 23, 24, 25, and 26, bears **S. 24°24.0' W.**, **0.389 chains** distance.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, and brass cap marked:

T42S  
R19E WC ↗  
S23 | S24  
S26 | S25  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on top of ridge on level ground.

From the corner of sections 19, 24, 25, and 30, on the east boundary of the township, hereinbefore described.

**N. 89°50.0' W.**, between sections 24 and 25.

**40.000** Point for the 1/4 section corner of sections 24 and 25.

Set a stainless steel post, 30 inches long, 2 1/2 inches

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

diameter, 26 inches in the ground, with magnet at base, and brass cap marked:

T42SR19E  
S24  
1/4 —————  
S25  
2009

Raise a small mound of stone north of the stainless steel post.

Corner is located on a gradual northeast slope.

80.000 True point for the corner of sections 23, 24, 25, and 26.

---

N. 0°00.7' W., between sections 23 and 24.

40.000 Point for the 1/4 section corner of sections 23 and 24.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42SR19E  
1/4  
S23 | S24  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located in small drainage, course west.

80.000 Point for the corner of sections 13, 14, 23, and 24.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, and brass cap marked:

T42SR19E  
S14 | S13  
S23 | S24  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on a gradual southeast slope.

---

From the true point for the corner of sections 13, 18, 19,

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

and 24, on the east boundary of the township, hereinbefore described.

**N. 89°50.0' W.**, between sections 13 and 24.

**40.000** Point for the 1/4 section corner of sections 13 and 24.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, on solid rock, with magnet at base, in a mound of stone, 5 feet base to top of brass cap marked:

T42SR19E  
S13  
1/4 —————  
S24  
2009

Set a steel fence post 3.1 links north of the stainless steel post.

Corner is located in wash, course southeast.

**80.000** The corner of sections 13, 14, 23, and 24.

---

**N. 0°00.7' W.**, between sections 13 and 14.

**40.000** Point for the 1/4 section corner of sections 13 and 14.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42SR19E  
1/4  
S14 | S13  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on rolling ground.

**80.000** Point for the corner of sections 11, 12, 13, and 14.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42SR19E  
S11 | S12  
S14 | S13  
2009

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on top of small finger ridge.

---

From the corner of sections 7, 12, 13, and 18, on the east boundary of the township, hereinbefore described.

**N. 89°50.0' W.**, between sections 12 and 13.

**40.000** Point for the 1/4 section corner of sections 12 and 13.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 5 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42SR19E  
S12  
1/4 ———  
S13  
2009

Set a steel fence post 3.1 links north of the stainless steel post.

Corner is located on a gradual southeast slope.

**80.000** The corner of sections 11, 12, 13, and 14.

---

**N. 0°00.7' W.**, between sections 11 and 12.

**40.000** Point for the 1/4 section corner of sections 11 and 12.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42SR19E  
1/4  
S11 | S12  
2009

Set a steel fence post 1.6 links east of the stainless steel post.

Corner is located on a gradual northwest slope.

**80.000** Point for the corner of sections 1, 2, 11, and 12.

Set a stainless steel post, 30 inches long, 2 1/2 inches

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

diameter, 22 inches in the ground, with magnet at base, in a mound of stone, 2 feet base to top of brass cap marked:

T42SR19E  
 $\frac{S2 | S1}{S11 | S12}$   
 2009

Set a steel fence post alongside the stainless steel post.  
Corner is located on a gradual southwest slope.

---

From the corner of sections 1, 6, 7, and 12, on the east boundary of the township, hereinbefore described.

**N. 89°50.0' W.**, between sections 1 and 12.

**40.000** Point for the 1/4 section corner of sections 1 and 12.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to solid rock, with magnet at base, in a mound of stone, 5 feet base, 2 feet high to top of brass cap marked:

T42SR19E  
 $\frac{S1}{1/4 \text{ ————}}$   
 $\frac{S12}{2009}$

Set a steel fence post 1.6 links east of the stainless steel post.

Corner is located on steep east slope in wash, course southeast.

**80.000** The corner of sections 1, 2, 11, and 12.

---

**N. 0°00.7' W.**, between sections 1 and 2.

**40.000** Point for the 1/4 section corner of sections 1 and 2.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, and brass cap marked:

T42SR19E  
 $\frac{1/4}{S2 | S1}$   
 2009

Set a steel fence post alongside the stainless steel post.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

Corner is located on level ground.

**79.766** The point for the corner of sections 1, 2, 35, and 36, on the north boundary of the township, hereinbefore described.

---

From the corner of sections 2, 3, 34, and 35, on the south boundary of the township, hereinbefore described.

**N. 0°01.3' W.**, between sections 34 and 35.

**40.000** Point for the 1/4 section corner of sections 34 and 35.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, and brass cap marked:

```
T42SR19E
  1/4
S34 | S35
  2009
```

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on a gradual northwest slope.

**80.000** Point for the corner of sections 26, 27, 34, and 35.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, and brass cap marked:

```
T42SR19E
  S27 | S26
  S34 | S35
  2009
```

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on a gradual west slope.

---

From the corner of sections 25, 26, 35, and 36.

**N. 89°50.0' W.**, between sections 26 and 35.

**40.000** True point for the 1/4 section corner of sections 26 and 35, falls in a wash, where it is inaccessible and impractical to monument.

From this point

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

Point selected for the off line witness 1/4 section corner of sections 26 and 35, bears **S. 48°37.8' W., 0.360 chains** distance.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, and brass cap marked:

WC  
T42S ↗  
R19E S26  
1/4 ———  
S35  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on level ground.

**80.000** The corner of sections 26, 27, 34, and 35.

---

**N. 0°01.3' W.,** between sections 26 and 27.

**40.000** Point for the 1/4 section corner of sections 26 and 27.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42SR19E  
1/4  
S27 | S26  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on a gradual northwest slope.

**80.000** Point for the corner of sections 22, 23, 26, and 27.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42SR19E  
S22 | S23  
S27 | S26  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

Corner is located in large wash, course northeast.

---

From the true point for the corner of sections 23, 24, 25, and 26.

**N. 89°50.0' W.**, between sections 23 and 26.

**40.000** Point for the 1/4 section corner of sections 23 and 26.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 6 inches in the ground to solid rock, with magnet at base, in a mound of stone, 4 feet base to top of brass cap marked:

T42SR19E  
S23  
1/4 ———  
S26  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on a gradual northwest slope, at head of a small wash, course northwest.

**80.000** The corner of sections 22, 23, 26, and 27.

---

**N. 0°01.3' W.**, between sections 22 and 23.

**40.000** Point for the 1/4 section corner of sections 22 and 23.

Cement a brass tablet, 3 1/4 inches diameter, with a 3 inch stem drilled into sandstone, marked:

T42SR19E  
1/4  
S22 | S23  
2009

Raise a mound of stone, 3 feet base, 2 feet high, west of the brass tablet.

Corner is located on level ground.

**80.000** Point for the corner of sections 14, 15, 22, and 23.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

T42SR19E  
S15 | S14  
S22 | S23  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on level ground.

---

From the corner of sections 13, 14, 23, and 24.

**N. 89°50.0' W.**, between sections 14 and 23.

**40.000** Point for the 1/4 section corner of sections 14 and 23.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground, with magnet at base, in a mound of stone, 2 feet base to top of brass cap marked:

T42SR19E  
S14  
1/4 ———  
S23  
2009

Set a steel fence post 3.1 links northwest of the stainless steel post.

Corner is located on left bank of large wash, course north.

**80.000** The corner of sections 14, 15, 22, and 23.

---

**N. 0°01.3' W.**, between sections 14 and 15.

**40.000** Point for the 1/4 section corner of sections 14 and 15.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42SR19E  
1/4  
S15 | S14  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on level ground.

**80.000** Point for the corner of sections 10, 11, 14, and 15.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42SR19E  
 $\frac{S10}{S15} | \frac{S11}{S14}$   
 2009

Corner is located on level ground.

---

From the corner of sections 11, 12, 13, and 14.

**N. 89°50.0' W.**, between sections 11 and 14.

40.000 Point for the 1/4 section corner of sections 11 and 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with magnet at base, in a mound of stone, 2 feet base to top of aluminum cap marked:

T42SR19E  
 S11  
 1/4  $\frac{\text{---}}{\text{---}}$   
 S14  
 2009

Corner is located on a gradual southwest slope.

80.000 The corner of sections 10, 11, 14, and 15.

---

**N. 0°01.3' W.**, between sections 10 and 11.

40.000 Point for the 1/4 section corner of sections 10 and 11.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42SR19E  
 1/4  
 $\frac{S10}{\text{---}} | \frac{S11}{\text{---}}$   
 2009

Set a steel fence post 3.1 links north of the stainless steel post.

Corner is located on level ground.

80.000 Point for the corner of sections 2, 3, 10, and 11.  
 Set a stainless steel post, 30 inches long, 2 1/2 inches

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

diameter, 24 inches in the ground, with magnet at base, in a small mound of stone to top of brass cap marked:

T42SR19E  
 $\frac{S3 | S2}{S10 | S11}$   
 2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on level ground.

---

From the corner of sections 1, 2, 11, and 12.

**N. 89°50.0' W.**, between sections 2 and 11.

**40.000** Point for the 1/4 section corner of sections 2 and 11.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, and brass cap marked:

T42SR19E  
 S2  
 1/4 ———  
 S11  
 2009

Set a steel fence post alongside the stainless steel post.

Corner is located on a gradual northeast slope.

**80.000** The corner of sections 2, 3, 10, and 11.

---

**N. 0°01.3' W.**, between sections 2 and 3.

**40.000** Point for the 1/4 section corner of sections 2 and 3.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 5 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 feet base to top of aluminum cap marked:

T42SR19E  
 1/4  
 $S3 | S2$   
 2009

Corner is located on level ground.

**79.532** The true point for the corner of sections 2, 3, 34, and 35,

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

on the north boundary of the township, hereinbefore described.

---

From the corner of sections 3, 4, 33, and 34, on the south boundary of the township, hereinbefore described.

**N. 0°02.0' W.**, between sections 33 and 34.

**40.000** Point for the 1/4 section corner of sections 33 and 34.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, and brass cap marked:

T42SR19E  
1/4  
S33 | S34  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on gentle rolling ground.

**80.000** Point for the corner of sections 27, 28, 33, and 34.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42SR19E  
S28 | S27  
S33 | S34  
2009

Set a steel fence post 8.1 links south of the stainless steel post.

Corner is located on a gradual northwest slope, between the upper and middle rock band.

---

From the corner of sections 26, 27, 34, and 35.

**N. 89°50.0' W.**, between sections 27 and 34.

**40.000** Point for the 1/4 section corner of sections 27 and 34.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 8 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 feet base to top of brass cap

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

marked:

T42SR19E  
S27  
1/4 —————  
S34  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on level ground.

80.000 The corner of sections 27, 28, 33, and 34.

---

N. 0°02.0' W., between sections 27 and 28.

40.000 Point for the 1/4 section corner of sections 27 and 28.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground, with magnet at base, in a mound of stone, 4 feet base to top of brass cap marked:

T42SR19E  
1/4  
S28 | S27  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on level ground.

80.000 Point for the corner of sections 21, 22, 27, and 28.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42SR19E  
S21 | S22  
S28 | S27  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on level ground atop a small ridge, bears northeast and southwest.

80.000 The corner of sections 21, 22, 27, and 28.

---

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 0°02.0' W., between sections 21 and 22.

40.000 Point for the 1/4 section corner of sections 21 and 22.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground, with magnet at base, in a mound of stone, 2 feet base to top of brass cap marked:

T42SR19E  
1/4  
S21 | S22  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on a gradual southwest slope.

80.000 Point for the corner of sections 15, 16, 21, and 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, and aluminum cap marked:

T42SR19E  
S16 | S15  
S21 | S22  
2009

Raise a mound of stone, 3 feet base by 1 foot high, west of the aluminum post.

Corner is located on a gradual southeast slope.

From the corner of sections 14, 15, 22, and 23.

N. 89°50.0' W., between sections 15 and 22.

40.000 Point for the 1/4 section corner of sections 15 and 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 5 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 feet base to top of aluminum cap marked:

T42SR19E  
S15  
1/4 ———  
S22  
2009

Corner is located on steep northwest slope.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

80.000 The corner of sections 15, 16, 21, and 22.

---

N. 0°02.0' W., between sections 15 and 16.

40.000 Point for the 1/4 section corner of sections 15 and 16.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of aluminum cap marked:

T42SR19E  
1/4  
S16 | S15  
2009

Corner is located on top of ridge, bears southwest and northeast.

80.000 Point for the corner of sections 9, 10, 15, and 16.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, and aluminum cap marked:

T42SR19E  
S9 | S10  
S16 | S15  
2009

Raise a mound of stone, 3 feet base by 1 foot high, west of the aluminum post.

Corner is located on a gradual southwest slope.

---

From the corner of sections 10, 11, 14, and 15.

N. 89°50.0' W., between sections 10 and 15.

40.000 Point for the 1/4 section corner of sections 10 and 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 5 inches in the ground to solid rock, with magnet at base, in a mound of stone, 3 feet base to top of aluminum cap marked:

T42SR19E  
S10  
1/4 ———  
S15  
2009

From which

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

A sandstone, 3 X 2 feet X 2 inches, set in the center of a mound of stone, bears **N. 18°35.2' E., 2.271 chains** distance, plainly marked COR 7 830542 on south face.

Corner is located on level ground.

80.000 The corner of sections 9, 10, 15, and 16.

---

**N. 0°02.0' W.**, between sections 9 and 10.

40.000 Point for the 1/4 section corner of sections 9 and 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of aluminum cap marked:

T42SR19E  
1/4  
S9 | S10  
2009

Corner is located on north side of large wash, course west.

80.000 Point for the corner of sections 3, 4, 9, and 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of aluminum cap marked:

T42SR19E  
S4 | S3  
S9 | S10  
2009

Corner is located on a gradual north slope.

---

From the corner of sections 2, 3, 10, and 11.

**N. 89°50.0' W.**, between sections 3 and 10.

40.000 Point for the 1/4 section corner of sections 3 and 10.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42SR19E  
S3  
1/4 ———  
S10  
2009

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

Corner is located on level ground.

80.000 The corner of sections 3, 4, 9, and 10.

---

N. 0°02.0' W., between sections 3 and 4.

40.000 Point for the 1/4 section corner of sections 3 and 4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with magnet at base, in a mound of stone, 2 feet base to top of aluminum cap marked:

T42SR19E  
1/4  
S4 | S3  
2009

Corner is located on north edge of wash in a large draw, bears west. Corner is difficult to access.

79.298 The corner of sections 3, 4, 33, and 34, on the north boundary of the township, hereinbefore described.

---

From the corner of sections 4, 5, 32, and 33, on the south boundary of the township, hereinbefore described.

N. 0°02.6' W., between sections 32 and 33.

40.000 Point for the 1/4 section corner of sections 32 and 33.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, with brass cap marked:

T42SR19E  
1/4  
S32 | S33  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on level open ground.

80.000 Point for the corner of sections 28, 29, 32, and 33.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, with brass cap marked:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

T42SR19E  
 $\frac{S29}{S32} | \frac{S28}{S33}$   
 2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on level open ground.

---

From the corner of sections 27, 28, 33, and 34.

**N. 89°50.0' W.**, between sections 28 and 33.

**40.000** Point for the 1/4 section corner of sections 28 and 33.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42SR19E  
 S28  
 1/4 ———  
 S33  
 2009

Set a steel fence post 7.6 links southeast of the stainless steel post.

Corner is located on gentle rolling ground at south edge of small wash, course southwest.

**80.000** The corner of sections 28, 29, 32, and 33.

---

**N. 0°02.6' W.**, between sections 28 and 29.

**40.000** Point for the 1/4 section corner of sections 28 and 29.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with magnet at base, with brass cap marked:

T42SR19E  
 1/4  
 $S29 | S28$   
 2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on last cliff band before drainage, on a

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

gradual northwest slope.

**80.000** Point for the corner of sections 20, 21, 28, and 29.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, with brass cap marked:

T42SR19E  
S20|S21  
S29|S28  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located in wash, drains northwest.

---

From the corner of sections 21, 22, 27, and 28.

**N. 89°50.0' W.**, between sections 21 and 28.

**40.000** True point for the 1/4 section corner of sections 21 and 28, falls in a wash, where it is inaccessible and impractical to monument.

From this point

Point selected for the off line witness 1/4 section corner of sections 21 and 28, bears **S. 3°04.8' E.**, **0.697 chains** distance.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

WC  
↑ T42S  
S21 R19E  
1/4 —————  
S28  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on a gradual northeast slope.

**80.000** The corner of sections 20, 21, 28, and 29.

---

**N. 0°02.6' W.**, between sections 20 and 21.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

40.000 True point for the 1/4 section corner of sections 20 and 21, falls in a deep wash, where it is inaccessible and impractical to monument.

From this point

Point selected for the off line witness 1/4 section corner of sections 20 and 21, bears **S. 7°57.0' E., 1.238 chains** distance.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, and brass cap marked:

```

T42S
R19E 1/4 ↑ WC
  S20 | S21
      |
      2009
  
```

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on a gradual northwest slope.

80.000 Point for the corner of sections 16, 17, 20, and 21.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, and aluminum cap marked:

```

T42SR19E
  S17 | S16
  S20 | S21
      |
      2009
  
```

Raise a mound of stone, 3 feet base by 1 foot high, west of the aluminum post.

Corner is located in small hollow, drains east.

From the corner of sections 15, 16, 21, and 22.

**N. 89°50.0' W.,** between sections 16 and 21.

40.000 Point for the 1/4 section corner of sections 16 and 21.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, and aluminum cap marked:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

T42SR19E  
S16  
1/4 ———  
S21  
2009

Corner is located in bottom of wash, course south.

80.000 The corner of sections 16, 17, 20, and 21.

---

N. 0°02.6' W., between sections 16 and 17.

40.000 Point for the 1/4 section corner of sections 16 and 17.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, and aluminum cap marked:

T42SR19E  
1/4  
S17 | S16  
2009

Corner is located on top of a ridge, bears north and south.

80.000 True point for the corner of sections 8, 9, 16, and 17, falls on edge of a steep bank, where it is inaccessible and impractical to monument.

From this point

Point selected for the off line witness corner of sections 8, 9, 16, and 17, bears **S. 72°40.4' E., 0.387 chains** distance.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, and aluminum cap marked:

▼ WC  
T42SR19E  
S8 | S9  
S17 | S16  
2009

Corner is located on the edge of small ridge, bears east and west.

---

From the corner of sections 9, 10, 15, and 16.

N. 89°50.0' W., between sections 9 and 16.

40.000 Point for the 1/4 section corner of sections 9 and 16, falls

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

at a location where it is inaccessible and impractical to monument.

80.000 The true point for the corner of sections 8, 9, 16, and 17.

---

N. 0°02.6' W., between sections 8 and 9.

40.000 Point for the 1/4 section corner of sections 8 and 9.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, and aluminum cap marked:

T42SR19E  
1/4  
S8 | S9  
2009

Corner is located on a shelf, bears north and southwest, in middle of small wash.

80.000 Point for the corner of sections 4, 5, 8, and 9.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, on sandstone marked with an X, with magnet at base, in a mound of stone, 4 feet base to top of aluminum cap marked:

T42SR19E  
S5 | S4  
S8 | S9  
2009

Corner is located on rock shelf, bears northeast and southwest.

---

From the corner of sections 3, 4, 9, and 10.

N. 89°50.0' W., between sections 4 and 9.


40.000 True point for the 1/4 section corner of sections 4 and 9, falls on steep rock face, where it is inaccessible and impractical to monument. I mark with an 'X'.

From this point

Point selected for a reference monument, bears S. 32°29.2' W., 0.753 chains distance.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, and aluminum cap marked:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

**80.000** The corner of sections 4, 5, 8, and 9.


---

From the corner of sections 4, 5, 8, and 9.

**N. 0°02.6' W.**, between sections 4 and 5.

**29.134** Point for the meander corner of sections 4 and 5, on the left bank of the San Juan River.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with magnet at base, in a mound of stone, 2 feet base to top of brass cap marked:



From this point

The true point for the meander corner of sections 4 and 5, on the right bank of the San Juan River bears **N. 13°53.1' E.**, **3.579 chains** distance.

---

From the corner of sections 5, 6, 31, and 32, on the south boundary of the township, hereinbefore described.

**N. 0°03.3' W.**, between sections 31 and 32.

**40.000** True point for the 1/4 section corner of sections 31 and 32, falls on precipitous ledges, where it is inaccessible and impractical to monument.

From this point

Point selected for the off line witness 1/4 section corner of sections 31 and 32, bears **N. 57°26.5' E.**, **0.886 chains** distance.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, and brass cap marked:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

T42SR19E  
WC 1/4  
↙ S31 | S32  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on top of ridge on level ground.

**80.000** Point for the corner of sections 29, 30, 31, and 32.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, and brass cap marked:

T42SR19E  
S30 | S29  
S31 | S32  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on level sandy ground.

From the corner of sections 28, 29, 32, and 33.

**N. 89°50.0' W.**, between sections 29 and 32.

**40.000** True point for the 1/4 section corner of sections 29 and 32, falls in wash, where it is inaccessible and impractical to monument.

From this point

Point selected for the off line witness 1/4 section corner of sections 29 and 32, bears **S. 75°18.5' E., 0.521 chains** distance.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, and brass cap marked:

← WC T42S  
S29 R19E  
1/4 ———  
S32  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

Corner is located on top of small ridge, bears northwest.

80.000 The corner of sections 29, 30, 31, and 32.

---

N. 89°50.0' W., between sections 30 and 31.

40.000 Point for the 1/4 section corner of sections 30 and 31.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42SR19E  
S30  
1/4 ———  
S31  
2009

Set a steel fence post 2.6 links north of the stainless steel post.

Corner is located on a gradual southeast slope.

77.660 The corner of sections 25, 30, 31, and 36, on the west boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set in a mound of stone, 3 feet base to top of brass cap marked as described in the official record of the 2008 survey. From which a steel fence post bears north of the stainless steel post.

Corner is located on a gradual northwest slope.

---

From the corner of sections 29, 30, 31, and 32.

N. 0°03.3' W., between sections 29 and 30.

40.000 Point for the 1/4 section corner of sections 29 and 30.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42SR19E  
1/4  
S30 | S29  
2009

Set a steel fence post 7 links north of the stainless steel post.

Corner is located on gentle rolling ground.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

**80.000** Point for the corner of sections 19, 20, 29, and 30.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, and brass cap marked:

T42SR19E
S19   S20
S30   S29
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on level ground.

---

From the corner of sections 20, 21, 28, and 29.

**N. 89°50.0' W.**, between sections 20 and 29.

**40.000** Point for the 1/4 section corner of sections 20 and 29.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42SR19E
S20
1/4 ———
S29
2009

Set a steel fence post 2.3 links north of the stainless steel post.

Corner is located on a gradual southeast slope.

**80.000** The corner of sections 19, 20, 29, and 30.

---

**N. 89°50.0' W.**, between sections 19 and 30.

**40.000** Point for the 1/4 section corner of sections 19 and 30.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 5 inches in the ground to solid rock, with magnet at base, in a mound of stone, 4 feet base to top of brass cap marked:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

T42SR19E  
S19  
1/4 —————  
S30  
2009

Corner is located on a gradual southeast slope.

- 77.570** The corner of sections 19, 24, 25, and 30, on the west boundary of the township, monumented with a brass tablet, 3 1/4 inches diameter, firmly set in concrete, marked as described in the official record of the 2008 survey. From which a steel fence post bears west of the brass tablet.

Corner is located on a red sandstone ledge.

---

From the corner of sections 19, 20, 29, and 30.

**N. 0°03.3' W.**, between sections 19 and 20.

- 40.000** Point for the 1/4 section corner of sections 19 and 20.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground, with magnet at base, in a mound of stone, 4 feet base to top of brass cap marked:

T42SR19E  
1/4  
S19 | S20  
2009

Set a steel fence post 7.6 links north of the stainless steel post.

Corner is located at base of ledges on steep southwest slope.

- 80.000** True point for the corner of sections 17, 18, 19, and 20, falls at a location where it is inaccessible and impractical to monument.


From this point

Point selected for the off line witness corner of sections 17, 18, 19, and 20, bears **S. 77°31.3' E., 0.200 chains** distance.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**



Set a steel fence post 2.3 links south of the stainless steel post.

Corner is located on gentle northwest slope.


---

From the corner of sections 16, 17, 20, and 21.

N. 89°50.0' W., between sections 17 and 20.

40.000 Point for the 1/4 section corner of sections 17 and 20.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, and aluminum cap marked:



Corner is located on steep west slope of small wash, course south.


80.000 The true point for the corner of sections 17, 18, 19, and 20.

---

N. 89°50.0' W., between sections 18 and 19.

40.000 Point for the 1/4 section corner of sections 18 and 19.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 5 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:



Set a steel fence post 6.1 links northeast of the stainless steel post.

Corner is located on a steep northeast slope.

77.478 The corner of sections 13, 18, 19, and 24, on the west

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 2 inches above the ground, with brass cap marked as described in the official record of the 2008 survey. From which a steel fence post bears east of corner.

Corner is located on top of small ridge, bears northeast and southwest.

From the true point for the corner of sections 17, 18, 19, and 20.

**N. 0°03.3' W.**, between sections 17 and 18.

**40.000** Point for the 1/4 section corner of sections 17 and 18.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with magnet at base, in a mound of stone, 4 feet base to top of brass cap marked:

T42SR19E  
1/4  
S18 | S17  
2009

Corner is located on east edge of small wash, course northeast.

**80.000** True point for the corner of sections 7, 8, 17, and 18, falls at a location where it is inaccessible and impractical to monument.

From this point

Point selected for the off line witness corner of sections 7, 8, 17, and 18, bears **N. 75°14.8' W.**, **0.670 chains** distance.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, in a mound of stone, 2 feet base to top of brass cap marked:

T42SR19E  
S7 | S8  
S18 | S17  
WC →  
2009

Set a steel fence post 1.6 links north of the stainless steel post.

Corner is located on a steep east slope.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the corner of sections 8, 9, 16, and 17.

**N. 89°50.0' W.**, between sections 8 and 17.

**40.000** Point for the 1/4 section corner of sections 8 and 17.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 8 inches in the ground to solid rock, with magnet at base, in a mound of stone, 4 feet base to top of aluminum cap marked:

T42SR19E  
S8  
1/4 ———  
S17  
2009

Corner is located on north facing slope on east side of small wash, course north.

**80.000** The true point for the corner of sections 7, 8, 17, and 18.

---

**N. 89°50.0' W.**, between sections 7 and 18.

**40.000** Point for the 1/4 section corner of sections 7 and 18.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground, with magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T42SR19E  
S7  
1/4 ———  
S18  
2009

Set a steel fence post 7.6 links southwest of the stainless steel post.

Corner is located on level ground.

**77.386** The corner of sections 7, 12, 13, and 18, on the west boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set in a mound of stone, 4 feet base to top of brass cap marked as described in the official record of the 2008 survey. From which a steel fence post bears east of the stainless steel post.

Corner is located on north edge of small wash, course southeast.

---

From the true point for the corner of sections 7, 8, 17, and 18.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN  
TOWNSHIP 42 SOUTH, RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 0°03.3' W., between sections 7 and 8.

11.559 Point for the meander corner of sections 7 and 8, on the left bank of the San Juan River.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with magnet at base, and brass cap marked:

T42SR19E  
MC  
S7 | S8  
2009

From this point

The true point for the meander corner of sections 7 and 8, on the right bank of the San Juan River, bears N. 7°38.9' E., 5.880 chains distance.

From the corner of sections 4, 5, 8, and 9.

N. 89°50.0' W., between sections 5 and 8.

40.000 Point for the 1/4 section corner of sections 5 and 8, near the left bank of the San Juan River.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with magnet at base, and aluminum cap marked:

T42SR19E  
S5  
1/4 ———  
S8  
2009

Raise a mound of stone, 3 feet base by 1 foot high, 1.6 links west of the aluminum post.

Corner is located in old river bed.

42.736 Point for the meander corner of sections 5 and 8, on the left bank of the San Juan River.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, and brass cap marked:

CHAINS

SURVEY OF THE MEANDERS OF THE LEFT BANK OF THE  
SAN JUAN RIVER THROUGH TOWNSHIP 42 SOUTH, RANGE 19 EAST,  
SALT LAKE MERIDIAN, UTAH

T42SR19E  
 MC / S5  
       S8  
       2009

From this point

The meander corner of sections 5 and 8, on the right bank of the San Juan River, bears **S. 85°13.6' W., 4.990 chains** distance.

Survey of the Meanders of the Left Bank of the  
San Juan River, through Township 42 South, Range 19 East,  
Salt Lake Meridian, Utah

From the meander corner of sections 4 and 33, on the north boundary of the township, hereinbefore described.

Thence, with the meanders of the left bank of the San Juan River through section 4. Unless otherwise stated, the meanders points are not monumented.

- S. 30°03.9' E., 4.630 chains.
- S. 45°30.8' E., 5.146 chains.
- S. 42°15.1' E., 5.099 chains.
- S. 60°27.3' E., 8.442 chains.
- S. 76°21.3' E., 0.887 chains.
- S. 74°29.6' E., 3.913 chains.
- S. 57°11.0' E., 1.610 chains.
- S. 64°11.4' E., 5.257 chains.
- S. 47°44.1' E., 1.809 chains.
- S. 25°49.5' E., 2.501 chains.
- S. 20°10.2' E., 2.448 chains.
- S. 22°44.0' E., 1.672 chains.
- S. 13°48.4' E., 1.413 chains.
- S. 2°07.6' E., 2.034 chains.
- S. 12°42.1' W., 2.250 chains.



SURVEY OF THE MEANDERS OF THE LEFT BANK OF THE  
SAN JUAN RIVER THROUGH TOWNSHIP 42 SOUTH, RANGE 19 EAST,  
SALT LAKE MERIDIAN, UTAH

CHAINS

S. 39°25.1' W., 3.290 chains.  
 S. 42°56.0' W., 4.903 chains.  
 S. 34°16.9' W., 5.729 chains.  
 S. 25°15.5' W., 4.381 chains.  
 S. 16°29.4' W., 4.232 chains.  
 S. 11°21.6' W., 7.241 chains.  
 S. 14°11.9' W., 4.553 chains.  
 S. 19°27.0' W., 2.083 chains.  
 S. 18°49.4' W., 4.798 chains.  
 S. 20°09.2' W., 4.036 chains.  
 S. 22°20.5' W., 7.164 chains.  
 S. 38°28.6' W., 17.635 chains. The meander corner of  
 sections 7 and 8.

---

Thence, in section 7.

S. 54°13.5' W., 1.356 chains.  
 S. 61°02.1' W., 3.995 chains.  
 S. 70°00.9' W., 2.508 chains.  
 S. 82°36.1' W., 1.480 chains.  
 N. 88°29.9' W., 5.277 chains.  
 N. 86°41.8' W., 7.677 chains.  
 N. 71°20.0' W., 11.796 chains.  
 N. 54°43.3' W., 1.794 chains.  
 N. 45°53.0' W., 6.673 chains.  
 N. 40°45.1' W., 3.214 chains.  
 N. 21°32.2' W., 4.396 chains.  
 N. 5°09.8' W., 4.076 chains.  
 N. 30°44.1' W., 2.758 chains.

SURVEY OF THE MEANDERS OF THE LEFT BANK OF THE  
SAN JUAN RIVER THROUGH TOWNSHIP 42 SOUTH, RANGE 19 EAST,  
SALT LAKE MERIDIAN, UTAH

CHAINS

- N. 31°23.9' W., 3.348 chains.
- N. 29°45.1' W., 3.761 chains.
- N. 38°30.8' W., 2.492 chains.
- N. 40°00.0' W., 2.817 chains.
- N. 53°27.0' W., 2.055 chains.
- N. 72°12.9' W., 1.364 chains.
- N. 67°11.8' W., 1.945 chains.      Intersect the center line of  
paved State Road 163, 25  
feet wide.
- N. 67°11.8' W., 1.278 chains.
- N. 71°51.4' W., 8.837 chains.
- N. 55°51.8' W., 4.650 chains.
- N. 66°11.8' W., 8.690 chains.      The meander corner of  
sections 7 and 12, on the  
west boundary of the  
township, not monumented.

An Informative Traverse of the Present Meanders of the  
Right Bank of the San Juan River, through Township 42  
South, Range 19 East, Salt Lake Meridian, Utah

From the meander corner of sections 5 and 32, on the north  
boundary of the township, hereinbefore described.

Thence, with the meanders of the right bank of the San Juan  
River through section 5. Unless otherwise stated, the  
meander points are not monumented.

- S. 36°15.8' E., 4.848 chains.      The meander corner of  
sections 4 and 5.

Thence, in section 4.

- S. 34°27.4' E., 0.967 chains.
- S. 34°38.7' E., 2.668 chains.
- S. 38°45.1' E., 2.500 chains.
- S. 48°27.2' E., 6.435 chains.

AN INFORMATIVE TRAVERSE OF THE MEANDERS OF THE RIGHT BANK  
OF THE SAN JUAN RIVER THROUGH TOWNSHIP 42 SOUTH,  
RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

*CHAINS*

S. 48°27.2' E., 6.435 chains.  
 S. 53°41.4' E., 2.880 chains.  
 S. 66°19.6' E., 2.780 chains.  
 S. 66°36.1' E., 2.841 chains.  
 S. 68°52.6' E., 1.963 chains.  
 S. 70°00.2' E., 1.762 chains.  
 S. 74°42.9' E., 1.382 chains.  
 S. 71°43.6' E., 3.307 chains.  
 S. 60°14.7' E., 2.361 chains.  
 S. 49°31.1' E., 2.963 chains.  
 S. 34°35.4' E., 2.749 chains.  
 S. 16°03.3' E., 4.336 chains.  
 S. 0°09.3' W., 2.559 chains.  
 S. 16°49.9' W., 1.710 chains.  
 S. 29°19.9' W., 2.715 chains.  
 S. 55°41.0' W., 2.714 chains.  
 S. 63°00.8' W., 5.793 chains.  
 S. 69°56.2' W., 2.864 chains.  
 S. 76°51.4' W., 3.827 chains.  
 S. 72°47.0' W., 2.383 chains.  
 S. 68°31.3' W., 2.937 chains.  
 S. 73°03.6' W., 4.086 chains.  
 S. 68°07.8' W., 6.827 chains.      The true point for the  
meander corner of sections 4  
and 5.

---

Thence, in section 5.

S. 68°07.8' W., 1.991 chains.  
 S. 62°05.2' W., 5.901 chains.

AN INFORMATIVE TRAVERSE OF THE MEANDERS OF THE RIGHT BANK  
OF THE SAN JUAN RIVER THROUGH TOWNSHIP 42 SOUTH,  
RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

S. 60°50.6' W., 9.809 chains.  
S. 52°31.1' W., 3.183 chains.  
S. 58°03.5' W., 0.952 chains.  
S. 68°43.0' W., 10.875 chains.  
S. 48°44.6' W., 3.228 chains.  
S. 40°29.6' W., 2.048 chains.  
S. 51°03.9' W., 1.692 chains.  
S. 55°15.7' W., 4.022 chains.  
S. 49°07.6' W., 2.467 chains.  
S. 42°05.5' W., 4.062 chains.  
S. 57°19.8' W., 1.900 chains.  
S. 41°32.3' W., 7.389 chains.

The meander corner of  
sections 5 and 8.

Thence, in section 8.

S. 37°16.4' W., 5.754 chains.  
S. 39°49.1' W., 8.180 chains.  
S. 26°05.1' W., 15.224 chains.  
S. 14°59.7' W., 12.924 chains.  
S. 16°13.3' W., 4.251 chains.  
S. 13°11.5' W., 5.765 chains.  
S. 20°38.6' W., 3.292 chains.  
S. 29°58.9' W., 5.790 chains.  
S. 32°58.9' W., 3.663 chains.  
S. 36°28.6' W., 2.706 chains.  
S. 51°00.5' W., 3.226 chains.

The true point for the  
meander corner of sections 7  
and 8.

Thence, in section 7.

AN INFORMATIVE TRAVERSE OF THE MEANDERS OF THE RIGHT BANK  
OF THE SAN JUAN RIVER THROUGH TOWNSHIP 42 SOUTH,  
RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

S. 51°00.4' W., 10.407 chains.  
 S. 75°19.5' W., 2.424 chains.  
 N. 85°33.1' W., 4.967 chains.  
 N. 69°50.9' W., 3.737 chains.  
 N. 74°49.8' W., 5.058 chains.  
 N. 72°22.7' W., 3.036 chains.  
 N. 58°11.7' W., 1.227 chains.  
 N. 46°07.4' W., 1.192 chains.  
 N. 44°06.6' W., 0.664 chains.  
 N. 67°55.7' W., 2.294 chains.  
 N. 60°29.1' W., 1.690 chains.  
 N. 54°36.6' W., 2.545 chains.  
 N. 65°25.9' W., 2.825 chains.  
 N. 44°14.5' W., 2.826 chains.  
 N. 30°00.4' W., 3.547 chains.  
 N. 14°43.4' W., 2.934 chains.  
 N. 15°58.1' W., 4.983 chains.  
 N. 44°00.8' W., 2.467 chains.  
 N. 35°16.2' W., 3.881 chains.  
 N. 47°33.2' W., 1.816 chains.  
 N. 57°51.1' W., 1.038 chains.  
 N. 47°19.5' W., 2.509 chains.  
 N. 34°45.8' W., 0.974 chains.  
 N. 63°26.7' W., 0.815 chains.  
 N. 52°33.0' W., 3.304 chains.  
 N. 62°04.0' W., 0.619 chains.

Intersect the center line of  
paved State Road 163, 25  
feet wide.

AN INFORMATIVE TRAVERSE OF THE MEANDERS OF THE RIGHT BANK  
OF THE SAN JUAN RIVER THROUGH TOWNSHIP 42 SOUTH,  
RANGE 19 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 62°04.0' W., 2.431 chains.  
 N. 75°46.9' W., 1.112 chains.  
 N. 62°23.0' W., 1.648 chains.  
 N. 59°01.7' W., 0.552 chains.  
 N. 78°45.5' W., 2.029 chains.  
 N. 62°47.7' W., 1.550 chains.  
 N. 73°59.1' W., 0.956 chains.  
 N. 59°47.8' W., 2.606 chains.  
 N. 82°54.6' W., 1.045 chains.  
 N. 45°48.4' W., 5.528 chains.  
 N. 57°23.8' W., 5.004 chains.  
 N. 28°19.0' W., 3.425 chains.

The section line of sections 7 and 12, on the west boundary of the township, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 3 inches above ground in a collar of stone, 4 feet diameter, with aluminum cap marked as described in the official record of the 2000 resurvey.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Ronald K. Baugh	Supervisory Cadastral Surveyor
R. Keith Batty	Cadastral Surveyor
Phil Freiberg	Survey Technician
Matt Gillins	Survey Technician

**CERTIFICATE OF SURVEY**

I, *Jeremy D. Davis, Cadastral Surveyor*, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing the date of the 9<sup>th</sup> day of *January, 2009*, I have *dependently resurveyed a portion of the north boundary, and a portion of the subdivisional lines, the survey of the south and east boundaries, a portion of the north boundary, a portion of the subdivisional lines, and the meanders of the present left bank and the informative traverse of the present right bank of the San Juan River through sections 4, 5, 7, and 8, in Township 42 South, Range 19 East, of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions of the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.*

*June 28, 2010*  
Date

  
(Cadastral Surveyor)

**CERTIFICATE OF APPROVAL**

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The following field notes of the *dependent resurvey a portion of the north boundary, and a portion of the subdivisional lines, and the survey of the south and east boundaries, a portion of the north boundary, a portion of the subdivisional lines, and the meanders of the present left bank and the informative traverse of the present right bank of the San Juan River through sections 4, 5, 7, and 8, Township 42 South, Range 19 East, Salt Lake Meridian, Utah, executed by Jeremy D. Davis, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.*

*July 1, 2010*  
Date

  
(Chief Cadastral Surveyor for Utah)

**CERTIFICATE OF TRANSCRIPT**

I certify that the foregoing transcript of the Field Notes of the above-described surveys in *T. 42 S., R. 19 E., Salt Lake Meridian, Utah*, is a true copy of the original Field Notes.

\_\_\_\_\_  
Date

\_\_\_\_\_  
(Authorizing Signature)