

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE RETRACEMENT OF THE UTAH-ARIZONA STATE BOUNDARY LINE,

FROM MILE POST 225 TO MILEPOST 236,

AND

THE SURVEY OF THE EAST BOUNDARY,

AND

THE SUBDIVISIONAL LINES,

IN

TOWNSHIP 43 SOUTH, RANGE 18 EAST

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Ronald K. Batty*  
*Cadastral Surveyor*

Under Special Instructions dated and approved *December 8, 2008*, which provided for the surveys included under Group No. *1096*, and Assignment Instructions dated *December 8, 2008*.

Survey Commenced, *December 9, 2008*  
Survey Completed, *March 17, 2009*

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE RETRACEMENT OF THE UTAH-ARIZONA STATE BOUNDARY LINE,

FROM MILE POST 225 TO MILEPOST 236,

AND

THE SURVEY OF THE EAST BOUNDARY,

AND

THE SUBDIVISIONAL LINES,

IN

TOWNSHIP 43 SOUTH, RANGE 18 EAST

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Ronald K. Batty*  
*Cadastral Surveyor*

Under Special Instructions dated and approved *December 8, 2008*, which provided for the surveys included under Group No. *1096*, and Assignment Instructions dated *December 8, 2008*.

Survey Commenced, *December 9, 2008*  
Survey Completed, *March 17, 2009*

# INDEX DIAGRAM

Township 43 South, Range 18 East.

<b>6</b>	36 <b>5</b>	30 <b>4</b>	24 <b>3</b>	17 <b>2</b>	11 <b>1</b> 7
38	37	31	24	18	12
<b>7</b>	38 <b>8</b>	31 <b>9</b>	25 <b>10</b>	19 <b>11</b>	12 <b>12</b> 7
39	39	32	25	19	13
<b>18</b>	40 <b>17</b>	32 <b>16</b>	26 <b>15</b>	20 <b>14</b>	13 <b>13</b> 8
41	40	33	26	20	14
<b>19</b>	41 <b>20</b>	33 <b>21</b>	27 <b>22</b>	21 <b>23</b>	14 <b>24</b> 9
42	42	34	27	21	15
<b>30</b>	43 <b>29</b>	34 <b>28</b>	28 <b>27</b>	22 <b>26</b>	15 <b>25</b> 9
44	43	35	28	22	16
<b>31</b>	44 <b>32</b>	35 <b>33</b>	29 <b>34</b>	23 <b>35</b>	16 <b>36</b> 10
45	45	36	29	23	17
3	3	4	4	5	6

## TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN

The following field notes are those of the retracement of the Utah-Arizona State Boundary Line, from Mile Post 225 to Mile Post 236, and the survey of the east boundary and the subdivisional lines, in T. 43 S., R. 18 E., Salt Lake Meridian, Utah.

**HISTORY OF SURVEYS**

<b>Surveyed by</b>		<b>Retr. or Resurveyed by</b>	
<b>SOUTH BOUNDARY</b> (Arizona-Utah State Boundary Line)			
All	H. B. Carpenter	1901	
Portion			C. F. Moore & W. W. Bandy 1924
Portion			R. K. Baugh 2005
<b>EAST BOUNDARY</b>			
All	Unsurveyed		
<b>WEST BOUNDARY</b>			
All	C. F. Moore & W. W. Bandy	1924	
All			R. K. Baugh 2005
<b>NORTH BOUNDARY</b>			
All	S. A. Burkhardt	2008	
<b>SUBDIVISION</b>			
All	Unsurveyed		

## TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1096, dated December 8, 2008.

The direction of the lines was determined by references to true meridians, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods*, dated May 9 2001, Version 1.0. Trimble Model 5800 global positioning system receivers were used for field collection. Cadastral Automated Plat Development (CAPD) was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from GPS static observations, post processed by National Geodetic Survey, Online Positioning User Service-Rapid Static, (OPUS-RS), utilizing Continuously Operating Reference Stations; **MONTICELLO UT 2006, AZTEC CORS, CHACOCNHP\_NM2005, FRED FREDONIA.**

The geographic position of Mile Post 226 on the Utah-Arizona State boundary, Township 43 South, Range 18 East, is as follows:

**Latitude: 36°59'54.309" N., Longitude: 109°58'02.631" W.**  
N.A.D. 83, Network Accuracy = 0.100 meter at 95% confidence

All stainless steel monuments in this township bear the Navajo seal.

RETRACEMENT OF THE UTAH-ARIZONA STATE BOUNDARY LINE,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

---

Retracement of the Utah-Arizona State Boundary Line

---

Reestablishment of the Survey Executed by H.B. Carpenter in 1901, the Dependent Resurvey Executed by C.F. Moore and W.W. Bandy in 1924, and the Dependent Resurvey Executed by R. K. Baugh in 2005.

---

Beginning at Mile Post 225, monumented with an iron post, 2 inches diameter, firmly set, projecting 16 above ground, with brass cap marked as described in the official record of the 1924 resurvey.

Corner is located 14 feet south of a cedar post, and 8 feet south of a wash, drains northwesterly.

**N. 89°54.1' E.**, on the 226th mile.

- 17.119** True point for the closing corner of T. 43 S., R.17 E. and T. 43 S., R.18 E., sections 31 and 36, on the west boundary of the township.

From this true point, the 1924 closing corner bears **S. 0° 00.1" E.**, **0.011** chains distance, monumented with an iron post, 3 inches diameter, firmly set, projecting 2 inches above ground, with brass cap marked as described in the official record of the 2005 resurvey.

- 60.171** Point for the 1/4 section corner of section 31 only, hereinafter described.

- 80.318** Mile Post 226, monumented with an iron post, 3 inches diameter, firmly set, projecting 6 inches above ground, in a collar of stone, with brass cap marked as described in the official record of the 1924 resurvey.
- 

Reestablishment of the Survey Executed by H.B. Carpenter in 1901, and the Dependent Resurvey Executed by C.F. Moore and W.W. Bandy in 1924.

---

**N. 89°58.4' E.**, on the 227th mile.

- 19.853** Point for the closing corner of sections 31 and 32, hereinafter described.
- 59.853** Point for the 1/4 section corner of section 32 only, hereinafter described.
- 80.091** Mile Post 227, monumented with an iron post, 2 inch diameter, firmly set, projecting 18 inches above ground, with brass cap marked as described in the official record of the 1901 survey.

RETRACEMENT OF THE UTAH-ARIZONA STATE BOUNDARY LINE,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

---

**N. 89°59.6' E.**, on the 228th mile.

- 19.762** Point for the closing corner of sections 32 and 33, hereinafter described.
- 59.762** Point for the 1/4 section corner of section 33 only, hereinafter described.
- 79.977** Mile Post 228, monumented with a sandstone, 36x13x3 inches, firmly set, 12 inches in the ground, in a mound of stone, 5 feet base, 2 feet high, is located on the east side of the sandstone, marked Utah on north face, 37 N on east face, Arizona on south face, and 228 on the west face.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to solid rock, with magnet at base, in a mound of stone, 5 feet base, 20 inches high, with brass cap marked:

UTAH  
—228M—  
ARIZONA  
2009

Deposit the marked sandstone alongside the stainless steel post.

Set a steel fence post alongside the stainless steel post.

Corner is located on south edge of a wash, drains west.

---

**S. 89°54.2' E.**, on the 229th mile.

- 19.785** Point for the closing corner of sections 33 and 34, hereinafter described.
- 59.785** Point for the 1/4 section corner of section 34 only, hereinafter described.
- 80.160** Mile Post 229, monumented with a scattered mound of stone, 4 feet base, 6 inches high.

At the corner point (in center of scattered mound of stone)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 14 inches in the ground to solid rock, in a mound of stone, 5 feet base, 2 feet high, with brass cap marked:

RETRACEMENT OF THE UTAH-ARIZONA STATE BOUNDARY LINE,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

UTAH  
—229M—  
ARIZONA  
2009

Corner is located at the top of a ridge, bears northwest and southeast.

---

S. 89°55.7' E., on the 230th mile.

- 19.625 Point for the closing corner of sections 34 and 35, hereinafter described.
- 59.625 Point for the 1/4 section corner of section 35 only, hereinafter described.
- 79.754 Mile Post 230, monumented with a scattered mound of stone, 5 feet base, 6 inches high.

At the corner point (in center of scattered mound of stone)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 20 inches in the ground to solid rock, in a collar of stone, 3 feet base, with brass cap marked:

UTAH  
—230M—  
ARIZONA  
2009

Set a steel fence post alongside the stainless steel post.

---

S. 89°56.0' E., on the 231st mile.

- 19.872 Point for the closing corner of sections 35 and 36, hereinafter described.
- 59.872 Point for the 1/4 section corner of section 36 only, hereinafter described.
- 79.869 Point for Mile Post 231, at proportionate distance, there is no remaining evidence of the original corner.

Not remonumented.

---

S. 89°56.0' E., on the 232nd mile.

- 20.003 Point for the closing corner of sections 31 and 36, the southeast corner of the township, hereinafter described.

RETRACEMENT OF THE UTAH-ARIZONA STATE BOUNDARY LINE,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

79.869 Point for Mile Post 232, at proportionate distance, there is no remaining evidence of the original corner.

Not remonumented.

---

S 89° 56.0' E., on the 233th mile of the Utah-Arizona Boundary Line,

79.869 Point for Mile Post 233, at proportionate distance, there is no remaining evidence of the original corner.

Not remonumented.

---

S 89° 56.0' E., on the 234th mile of the Utah-Arizona Boundary Line,

79.869 Point for Mile Post 234, at proportionate distance, there is no remaining evidence of the original corner.

Not remonumented.

---

S 89° 56.0' E., on the 235th mile of the Utah-Arizona Boundary Line,

79.869 Point for Mile Post 235, at proportionate distance, there is no remaining evidence of the original corner.

Not remonumented.

---

S. 89° 56.0' E., on the 236th mile of the Utah-Arizona Boundary Line.

79.869 Mile Post 236 monumented with a sandstone, 19x14x5 inches, firmly set, marked Utah on north face, 236M on west face, other marks illegible.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

UTAH  
—236M—  
ARIZONA  
2009

Deposit the marked sandstone alongside the stainless steel post.

Set a steel fence post alongside the stainless steel post.

SURVEY OF THE EAST BOUNDARY,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

---

The Survey of the East Boundary,  
T. 43 S., R. 18 E., Salt Lake Meridian, Utah

---

From the corner of Townships 42 and 43 South, Ranges 18 and 19 E., monumented with a stainless steel post, firmly set, projecting 2 inches above ground, in a collar of stone, 3 feet base, with brass cap marked as described in the official record of the 2008 survey.

A steel fence post is located north of the stainless steel post.

**SOUTH**, between sections 1 and 6.

**40.000** Point for the 1/4 section corner of sections 1 and 6.

Set an iron rebar, 12 inches long, 1/2 inch diameter, drilled into solid rock with cement bond, 4 inches in the ground, in a small mound of stone, 2 feet base, 8 inches high, with 1 inch diameter aluminum cap marked:

T43S  
1/4  
R18E | R19E  
S1 | S6  
2009

Raise a mound of stone, 3 feet base, 3 feet high, with a steel fence post in the center, on the south side of the corner.

**80.000** Point for the corner of sections 1, 6, 7, and 12.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, with brass cap marked:

T43S  
R18E | R19E  
S1 | S6  
S12 | S7  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on the north edge of a small knoll.

---

**SOUTH**, between sections 7 and 12.

**40.000** Point for the 1/4 section corner of sections 7 and 12.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 10 inches in the ground to solid

SURVEY OF THE EAST BOUNDARY,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

rock, in a mound of stone, 5 feet base, 1 1/2 feet high, with brass cap marked:

T43S  
R18E 1/4 R19E  
S12|S7  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located in a small hollow, drains east.

**80.000** Point for the corner of sections 7, 12, 13, and 18.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, in a collar of stone, 4 feet base, with brass cap marked:

T43S  
R18E | R19E  
S12 | S7  
S13 | S18  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located in a small wash, drains northeast.

**SOUTH**, between sections 13 and 18.

**40.000** Point for 1/4 section corner of sections 13 and 18.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, with brass cap marked:

T43S  
1/4  
R18E | R19E  
S13 | S18  
2009

Corner is located on the northern edge of a bluff.

**80.000** Point for the corner of sections 13, 18, 19, and 24.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 8 inches in the ground to solid rock, in a mound of stone, 4 feet base, 20 inches high, with brass cap marked:

SURVEY OF THE EAST BOUNDARY,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T43S  
R18E | R19E  
S13 | S18  
S24 | S19  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on southeast facing slope.

---

**SOUTH**, between sections 19 and 24.

**40.000** Point for the 1/4 section corner of sections 19 and 24.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 25 inches in the ground, with brass cap marked:

T43S  
R18E 1/4 R19E  
S24 | S19  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on the north side of a wash, drains southeast.

**80.000** Point for sections 19, 24, 25, and 30.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 23 inches in the ground, with brass cap marked:

T43S  
R18E | R19E  
S24 | S19  
S25 | S30  
2009

Set a steel fence post alongside the stainless steel post.

---

**SOUTH**, between sections 25 and 30.

**40.000** Point for the 1/4 section corner of sections 25 and 30.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 25 inches in the ground, in a mound of earth 2 1/2 feet base, 5 inches high, with brass cap marked:

SURVEY OF THE EAST BOUNDARY,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

T43S  
R18E R19E  
1/4 S25|S30  
2009

Set a steel fence post alongside the stainless steel post.

Raise a mound of earth around the stainless steel post.

**80.000** Point for the corner of sections 25, 30, 31, and 36.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, in a collar of stone, 2 feet base, with brass cap marked:

T43S  
R18E | R19E  
S25|S30  
S36|S31  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on a sandy, east facing slope. A deep narrow wash, drains north, and is located approximately 100 feet east of the corner.

---

**SOUTH**, between sections 31 and 36.

**40.000** Point for the 1/4 section corner of sections 31 and 36.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with brass cap marked:

T43S  
R18E 1/4 R19E  
S36|S31  
2009

Set a steel fence post alongside the stainless steel post.

**77.878** The closing corner of sections 31 and 36 on the Utah-Arizona state boundary.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with brass cap marked:

SURVEY OF THE EAST BOUNDARY,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

C C  
T43S  
R18E | R19E  
S36 | S31  
2009

Set a steel fence post alongside the stainless steel post.

Corner falls on the centerline of a dirt road.

The Survey of the Subdivisional Lines,  
T. 43 S., R. 18 E., Salt Lake Meridian, Utah

From the corner of sections 1, 2, 35, and 36, on the north boundary, monumented with a stainless steel post, firmly set, projecting 1 inch above ground, with brass cap marked as described in the official record of the 2008 survey.

A steel fence post is located north of the stainless steel post.

S. 0°00.7' E., between sections 1 and 2.

**40.000** Point for the 1/4 section corner of sections 1 and 2.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, in a mound of stone, 2 feet base, 26 inches high, with brass cap marked:

T43SR18E  
1/4  
S2 | S1  
2009

Set a steel fence post alongside the stainless steel post.  
Corner is located on the right bank of a wash, drains east.

**80.000** Point for corner of sections 1, 2, 11, and 12.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 10 inches in the ground to solid rock, in a mound of stone, 3 feet base, 18 inches high, with brass cap marked:

T43SR18E  
S2 | S1  
S11 | S12  
2009

Set a steel fence post alongside the stainless steel post.

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Corner is located in a wash, drains east.

---

From the corner of sections 1, 6, 7, and 12, on the east boundary, hereinbefore described.

**WEST**, between sections 1 and 12.

**40.000** Point for the 1/4 section corner of sections 1 and 12.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 16 inches in the ground to solid rock, in a mound of stone, 3 feet base, 10 inches high, with brass cap marked:

T43SR18E  
S1  
1/4———  
S12  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on a northwest facing slope.

**80.000** The corner of sections 1, 2, 11, and 12.

---

**S. 0°00.7' E.**, between sections 11 and 12.

**40.000** Point for the 1/4 section corner of sections 11 and 12.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 20 inches in the ground to solid rock, in a mound of stone, 3 feet base, 10 inches high, with brass cap marked:

T43SR18E  
1/4  
S11|S12  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located at the bottom of a drainage, descends northeast.

**80.000** Point for the corner of sections 11, 12, 13, and 14.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 22 inches in the ground, in a collar of stone, 2 feet base, with brass cap marked:

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

T43SR18E  
S11|S12  
S14|S13  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on gentle northeast facing slope.

---

From the corner of sections 7, 12, 13, and 18, on the east boundary, hereinbefore described.

**WEST**, between sections 12 and 13.

**40.000** Point for the 1/4 section corner of sections 12 and 13.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 4 inches in the ground to solid rock, in a mound of stone, 3 1/2 feet base, 2 feet high, with brass cap marked:

T43SR18E  
S12  
1/4———  
S13  
2009

Corner is located on north facing slope.

**80.000** The corner of sections 11, 12, 13, and 14.

---

**S. 0°00.7' E.**, between sections 13 and 14.

**40.000** Point for the 1/4 section corner of sections 13 and 14.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 18 inches in the ground to solid rock, in a mound of stone, 3 feet base, 10 inches high, with brass cap marked:

T43SR18E  
1/4  
S14|S13  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on south facing slope.

**80.000** Point for the corner of sections 13, 14, 23, and, 24.

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Set a brass tablet, buried 2 inches beneath ground, with cement bond, in a collar of stone, with brass tablet marked:

T43SR18E  
 $\frac{S14}{S23} | \frac{S13}{S24}$   
 2009

Raise a mound of stone, 4 feet base, 3 feet high, with a steel fence post in the center of the mound, alongside the brass tablet.

Corner is located on a gentle slope, drains east.

---

From the corner of sections 13, 18, 19, and 24, on the east boundary, hereinbefore described.

**WEST**, between sections 13 and 24.

**40.000** Point for the 1/4 section corner of sections 13 and 24.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
 S13  
 1/4—  
 S24  
 2009

Set a steel fence post alongside the stainless steel post.

Corner is located on the north edge of a large wash.

**80.000** The corner of sections 13, 14, 23, and 24.

---

**S. 0°00.7' E.**, between sections 23 and 24.

**40.000** Point for the 1/4 section corner of sections 23 and 24.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 16 inches in the ground, in a mound of stone, 3 feet base, 10 inches high, with brass cap marked:

T43SR18E  
 1/4  
 $\frac{S23}{S24}$   
 2009

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

Set a steel fence post alongside the stainless steel post.

Corner is located on the west edge of a wash, drains northeast.

80.000 Point for the corner of sections 23, 24, 25, and 26.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 13 inches in the ground to solid rock, in a mound of stone, 3 1/2 feet base, 15 inches high, with brass cap marked:

T43SR18E  
S23|S24  
S26|S25  
2009

Set a steel fence post alongside the corner.

---

From the corner of sections 19, 24, 25, and 30, on the east boundary, hereinbefore described.

**WEST**, between sections 24 and 25.

40.000 Point for the 1/4 section corner of sections 24 and 25.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 21 inches in the ground to solid rock, in a collar of stone, 3 1/2 feet base, with brass cap marked:

T43SR18E  
S24  
1/4———  
S25  
2009

Set a steel fence post alongside the stainless steel post.

80.000 The corner of sections 23, 24, 25, and 26.

---

**S. 0°00.7' E.**, between sections 25 and 26.

40.000 Point for the 1/4 section corner of sections 25 and 26.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 18 inches in the ground to solid rock, in a mound of stone, 3 1/2 feet base, 1 foot high, with brass cap marked:

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

T43SR18E  
1/4  
S26|S25  
2009

Set a steel fence post alongside the stainless steel post.

**80.000** Point for the corner of sections 25, 26, 35, and 36.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S26|S25  
S35|S36  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on the south side of a small hollow, drains northeast.

---

From the corner of sections 25, 30, 31, and 36, on the east boundary, hereinbefore described.

**WEST**, between sections 25 and 36.

**40.000** Point for the 1/4 section corner of sections 25 and 36.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, in a collar of stone, 2 1/2 feet base, with brass cap marked:

T43SR18E  
S25  
1/4—————  
S36  
2009

Set a steel fence post alongside the stainless steel post.

**80.000** The corner of sections 25, 26, 35, and 36.

---

**S. 0°00.7' E.**, between sections 35 and 36.

**40.000** Point for the 1/4 section corner of sections 35 and 36.

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

*CHAINS*

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 12 inches in the ground to solid rock, in a mound of stone, 3 feet base, to top of post, with brass cap marked:

T43SR12E  
1/4  
S35|S36  
2009

Set a steel fence post alongside the stainless steel post.

**77.786** The closing corner of sections 35 and 36 on the Utah-Arizona state boundary.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, with brass cap marked:

C C  
T43S R18E  
S35|S36  
2009

Set a steel fence post alongside the stainless steel post.

Raise a mound of stone, 2 feet base, 1 foot high, north of stainless steel post.

Point for the 1/4 section corner of section 36 only, at midpoint between closing corners.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, with brass cap marked:

T43S R18W  
1/4 S36  
            
2009

Set a steel fence post alongside the stainless steel post.

Raised a mound of stone, 4 feet base, 2 feet high, north of corner.

From the corner of sections 2, 3, 34, and 35, on the north boundary, monumented with a stainless steel post, firmly set, in a mound of stone, 3 feet base to top of cap, with brass cap marked as described in the official record of the 2008 survey.

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

A steel fence post is located northeast of the stainless steel post.

**S. 0°01.3' E.**, between sections 2 and 3.

**40.000** Point for the 1/4 section corner of sections 2 and 3.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
1/4  
S3|S2  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on a flat bench.

**80.000** Point for the corner of sections 2, 3, 10, and 11.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S3|S2  
S10|S11  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located in a gulch.

From the corner of sections 1, 2, 11, and 12.

**WEST**, between sections 2 and 11.

**40.000** Point for the 1/4 section corner of sections 2 and 11.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S2  
1/4———  
S11  
2009

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

Set a steel fence post alongside the stainless steel post.

80.000 The corner of sections 2, 3, 10, and 11.

---

S. 0°01.3' E., between sections 10 and 11.

40.000 Point for the 1/4 section corner of sections 10 and 11.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 5 inches in the ground to solid rock, in a mound of stone, 4 feet base, 21 inches high, with brass cap marked:

T43SR18E  
1/4  
S10|S11  
2009

80.000 Point for the corner of sections 10, 11, 14, and 15.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S10|S11  
S15|S14  
2009

Set a steel fence post alongside the stainless steel post.

---

From the corner of sections 11, 12, 13, and 14.

WEST, between sections 11 and 14.

40.000 Point for the 1/4 section corner of sections 11 and 14.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, in a collar of stone, 3 feet base, with brass cap marked:

T43SR18E  
S11  
1/4———  
S14  
2009

80.000 The corner of sections 10, 11, 14, and 15.

---

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

S. 0°01.3' E., between sections 14 and 15.

40.000 Point for the 1/4 section corner of sections 14 and 15.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 4 inches in the ground to solid rock, in a mound of stone, 4 feet base, 2 feet high, with brass cap marked:

T43SR18E  
1/4  
S15|S14  
2009

Corner is located in a wash, drains southeast.

80.000 Point for the corner of sections 14, 15, 22, and 23.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S15|S14  
S22|S23  
2009

Set a steel fence post alongside the stainless steel post.

---

From the corner of sections 13, 14, 23, and 24.

**WEST**, between sections 14 and 23.

40.000 Point for the 1/4 section corner of sections 14 and 23.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 6 inches in the ground to solid rock, in a mound of stone, 5 feet base, 2 feet high, with brass cap marked:

T43SR18E  
S14  
1/4———  
S23  
2009

80.000 The corner of sections 14, 15, 22, and 23.

---

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

S. 0°01.3' E., between sections 22 and 23.

40.000 Point for the 1/4 section corner of sections 22 and 23.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, in a collar of stone, 3 feet base, with brass cap marked:

T43SR18E  
1/4  
S22|S23  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located at the base of a 20 foot tall cliff on the north bank of a creek, drains southeast.

80.000 Point for the corner of sections 22, 23, 26, and 27.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S22|S23  
S27|S26  
2009

Set a steel fence post alongside the stainless steel post.

---

From the corner of sections 23, 24, 25, and 26.

**WEST**, between sections 23 and 26.

40.000 Point for the 1/4 section corner of sections 23 and 26.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, with brass cap marked:

T43SR18E  
S23  
1/4-----  
S26  
2009

80.000 The corner of sections 22, 23, 26, and 27.

---

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

**S. 0°01.3' E.**, between sections 26 and 27.

**40.000** Point for the 1/4 section corner of sections 26 and 27.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 10 inches in the ground, in a mound of stone, 4 feet base, 1 1/2 feet high, with brass cap marked:

T43SR18E  
1/4  
S27|S26  
2009

Set a steel fence post on the south side of the stainless steel post.

Corner is located in a small hollow, draining northwest.

**80.000** Point for the corner of sections 26, 27, 34, and 35.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 14 inches in the ground, in a mound of stone, 3 feet base, 14 inches high, with brass cap marked:

T43SR18E  
S27|S26  
S34|S35  
2009

Corner is located on the right bank of a wash, drains north.

---

From the corner of sections 25, 26, 35, and 36.

**WEST**, between sections 26 and 35.

**40.000** Point for the 1/4 section corner of sections 26 and 35.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 12 inches in the ground to solid rock, in a mound of stone, 3 feet base, to top of post, with aluminum cap marked:

T43SR18E  
S26  
1/4——  
S35  
2009

Set a steel fence post alongside the aluminum post.

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

80.000 The corner of sections 26, 27, 34, and 35.

---

S. 0°01.3' E., between sections 34 and 35.

40.000 Point for the 1/4 section corner of sections 34 and 35.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, with brass cap marked:

T43SR18E  
1/4  
S34|S35  
2009

Set a steel fence post on the south side of the stainless steel post.

Corner is located on gentle north facing slope.

77.691 The closing corner of sections 34 and 35, on the Utah-Arizona state boundary.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, over a 1 inch diameter divot in solid rock, with magnet at base of divot, in a mound of stone, 5 feet base, 2 1/2 feet high, with brass cap marked:

C C  
T43S R18E  
S34|S35  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on a southeast facing slope.

---

Point for the 1/4 section corner of sections 35 only, at midpoint between closing corners,

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, with brass cap marked:

T43S R18W  
1/4 S35  

---

2009

Set a steel fence post alongside the stainless steel post.

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Raised a mound of stone, 3 feet base, 1 foot high, north of the corner.

---

From the corner of sections 3, 4, 33, and 34, on the north boundary, monumented with a stainless steel post, firmly set, projecting 4 inches above ground, with brass cap marked as described in the official record of the 2008 survey.

A steel fence post is located northwest of the stainless steel post.

**S. 0°02.0' E.**, between sections 3 and 4.

**40.000** Point for the 1/4 section corner of sections 3 and 4.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
1/4  
S4|S3  
2009

Set a steel fence post alongside the stainless steel post.

**80.000** Point for the corner of sections 3, 4, 9, and 10.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S4|S3  
S9|S10  
2009

Set a steel fence post alongside the stainless steel post.

---

From the corner of sections 2, 3, 10, and 11.

**WEST**, between sections 3 and 10.

**40.000** Point for the 1/4 section corner of sections 3 and 10.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 15 inches in the ground to solid rock, in a mound of stone, 3 feet base, 1 foot high, with brass cap marked:

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T43SR18E  
S3  
1/4—  
S10  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located at the top of a sandy ridge, bears northeast and southwest.

80.000 The corner of sections 3, 4, 9, and 10.

---

S. 0°02.0' E., between sections 9 and 10.

40.000 Point for the 1/4 section corner of sections 9 and 10.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
1/4  
S9|S10  
2009

Set a steel fence post alongside the stainless steel post.

80.000 Point for the corner of sections 9, 10, 15, and 16.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S9|S10  
S16|S15  
2009

Set a steel fence post alongside the stainless steel post.

---

From the corner of sections 10, 11, 14, and 15.

WEST, between sections 10 and 15.

40.000 Point for the 1/4 section corner of sections 10 and 15.

Set a brass tablet, 3 1/4 inch diameter, with a 3 1/2 inch long stem, drilled flush into sandstone with cement bond, with brass tablet marked:

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

T43SR18E  
S10  
1/4—  
S15  
2009

Set a steel fence post in the center of a mound of stone, 4 feet base, 3 feet high, at the west side of the brass tablet.

Corner is located approximately 50 feet north of a dirt road, bears northwest and southeast.

80.000 The corner of sections 9, 10, 15, and 16.

---

**S. 0°02.0' E.**, between sections 15 and 16.

40.000 Point for the 1/4 section corner of sections 15 and 16.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
1/4  
S16|S15  
2009

Set a steel fence post alongside the stainless steel post.

80.000 Point for the corner of sections 15, 16, 21, and 22.  
Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S16|S15  
S21|S22  
2009

Set a steel fence post alongside the stainless steel post.

---

From the corner of sections 14, 15, 22, and 23.

**WEST**, between sections 15 and 22.

40.000 Point for the 1/4 section corner of sections 15 and 22.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

T43SR18E  
S15  
1/4—  
S22  
2009

Set a steel fence post alongside the stainless steel post.

80.000 The corner of sections 15, 16, 21, and 22.

---

**S. 0°02.0' E.**, between sections 21 and 22.

40.000 Point for the 1/4 section corner of sections 21 and 22.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
1/4  
S21|S22  
2009

Set a steel fence post alongside the stainless steel post.

80.000 Point for the corner of sections 21, 22, 27, and 28.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S21|S22  
S28|S27  
2009

Set a steel fence post alongside the stainless steel post.

---

From the corner of sections 22, 23, 26, and 27.

**WEST**, between sections 22 and 27.

40.000 Point for the 1/4 section corner of sections 22 and 27.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 12 inches in the ground to solid rock, in a mound of stone, 4 feet base, 16 inches high, with brass cap marked:

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

T43SR18E  
S22  
1/4-----  
S27  
2009

Set a steel fence post alongside the stainless steel post.

80.000 The corner of sections 21, 22, 27, and 28.

---

**S. 0°02.0' E.**, between sections 27 and 28.

40.000 Point for the 1/4 section corner of sections 27 and 28.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 4 inches in the ground to solid rock, in a mound of stone, 4 feet base, 2 feet high, with brass cap marked:

T43SR18E  
1/4  
S28|S27  
2009

Corner is located in the bottom of a small gulch, drains northeast.

80.000 Point for the corner of sections 27, 28, 33, and 34.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S28|S27  
S33|S34  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on a southeast facing slope.

---

From the corner of sections 26, 27, 34, and 35.

**WEST**, between sections 27 and 34.

40.000 Point for the 1/4 section corner of sections 27 and 34.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

brass cap marked:

T43SR18E  
S27  
1/4—  
S34  
2009

Set a steel fence post alongside the stainless steel post.

80.000 The corner of sections 27, 28, 33, and 34.

---

S. 0°02.0' E., between sections 33 and 34.

40.000 Point for the 1/4 section corner of sections 33 and 34.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 22 inches in the ground to solid rock, with brass cap marked:

T43SR18E  
1/4  
S33|S34  
2009

Set a steel fence post alongside the stainless steel post.

77.567 The closing corner of sections 33 and 34 on the Utah-Arizona state boundary.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 6 inches in the ground to solid rock, in mound of stone, 3 feet base, 20 inches high, with brass cap marked:

C C  
T43S R18E  
S33|S34  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on rolling sandy ground at the north bank of a small drainage.

---

Point for the 1/4 section corner of sections 34, at midpoint between closing corners.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 8 inches in the ground to solid

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

rock, in a mound of stone, 4 feet base, 2 feet high, with brass cap marked:

T43S R18W  
1/4 S34  

---

2009

Set a steel fence post alongside the stainless steel post.

Corner is located near the west edge of a wash, drains northwest.

---

From the corner of sections 4, 5, 32, and 33, on the north boundary, monumented with a stainless steel post, firmly set, projecting 18 inches above ground, in a mound of stone, 3 feet base to top of cap, with brass cap marked as described in the official record of the 2008 survey.

A steel fence post is located northwest of the stainless steel post.

S. 0°02.7' E., between sections 4 and 5.

**40.000** Point for the 1/4 section corner of sections 4 and 5.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 27 inches in the ground, with brass cap marked:

T43SR18E  
1/4  
S5|S4  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on a gentle, northwest facing slope.

**80.000** Point for the corner of sections 4, 5, 8, and 9.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 27 inches in the ground, with brass cap marked:

T43SR18S  
S5|S4  
S8|S9  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located in a small hollow, drains east.

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

---

From the corner of sections 3, 4, 9, and 10.

**WEST**, between sections 4 and 9.

**40.000** Point for the 1/4 section corner of sections 4 and 9.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S4  
1/4—  
S9  
2009

Set a steel fence post alongside the stainless steel post.

**80.000** The corner of sections 4, 5, 8, and 9.

---

**S. 0°02.7' E.**, between sections 8 and 9.

**40.000** Point for the 1/4 section corner of sections 8 and 9.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 25 inches in the ground, with brass cap marked:

T43SR18E  
1/4  
S8|S9  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on a gentle, southeast facing sandy slope.

**80.000** Point for the corner of sections 8, 9, 16, and 17.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 27 inches in the ground, with brass cap marked:

T43SR18E  
S8|S9  
S17|S16  
2009

Set a steel fence post alongside the stainless steel post.

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Corner is located on rolling, sandy terrain.

---

From the corner of sections 9, 10, 15, and 16.

**WEST**, between sections 9 and 16.

**40.000** The 1/4 section corner of sections 9 and 16.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with brass cap marked:

T43SR18E  
S9  
1/4———  
S16  
2009

Set a steel fence post alongside the stainless steel post.

**80.000** The corner of sections 8, 9, 16, and 17.

---

**S. 0°02.7' E.**, between sections 16 and 17.

**40.000** Point for the 1/4 section corner of sections 16 and 17.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
1/4  
S17|S16  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on sandy, rolling terrain.

**80.000** Point for the corner of sections 16, 17, 20, and 21.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 10 inches in the ground to solid rock, in a mound of stone, 3 feet base, 18 inches high, with brass cap marked:

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

T43SR18E  
S17|S16  
S20|S21  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on a gentle south facing slope. A wash, drains east, is located approximately 300 feet south of the corner.

---

From the corner of sections 15, 16, 21, and 22.

**WEST**, between sections 16 and 21.

**40.000** Point for the 1/4 section corner of sections 16 and 21.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S16  
1/4——  
S21  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on a gentle, east facing, sandy slope.

**80.000** The corner of sections 16, 17, 20, and 21.

---

**S. 0°02.7' E.**, between sections 20 and 21.

**40.000** Point for the 1/4 section corner of sections 20 and 21.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 18 inches in the ground to solid rock, in a mound of stone, 3 feet base, 10 inches high, with brass cap marked:

T43SR18E  
1/4  
S20|S21  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on a gentle, north facing slope. A wash, drains east, is located approximately 25 feet north of the corner.

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

**80.000** Point for the corner of sections 20, 21, 28, and 29.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S20|S21  
S29|S28  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on flat sandy ground. A faint 2-track is located approximately 20 feet south of the corner.

---

From the corner of sections 21, 22, 27, and 28.

**WEST**, between sections 21 and 28.

**40.000** Point for the 1/4 section corner of sections 21 and 28.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 25 inches in the ground, with brass cap marked:

T43SR18E  
S21  
1/4———  
S28  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on flat ground. The centerline of a 2-track road is located approximately 10 feet southeast of the corner.

**80.000** The corner of sections 20, 21, 28, and 29.

---

**S. 0°02.7' E.**, between sections 28 and 29.

**40.000** Point for the 1/4 section corner of sections 28 and 29.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

T43SR18E  
1/4  
S29|S28  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on flat ground. The centerline of a road is located approximately 25 feet north of corner.

**80.000** Point for the corner of sections 28, 29, 32, and 33.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 4 inches in the ground to solid rock, in a mound of stone, 3 feet base, 22 inches high, with brass cap marked:

T43SR18E  
S29|S28  
S32|S33  
2009

Corner is located on the north edge of a small wash, drains southeast.

---

From the corner of sections 27, 28, 33, and 34.

**WEST**, between sections 28 and 33.

**40.000** Point for the 1/4 section corner of sections 28 and 33.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S28  
1/4———  
S33  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on east facing slope.

**80.000** The corner of sections 28, 29, 32, and 33.

---

**S. 0°02.7' E.**, between sections 32 and 33.

**40.000** Point for the 1/4 section corner of sections 32 and 33.

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 6 inches in the ground to solid rock, in a mound of stone, 3 feet base, 22 inches high, with brass cap marked:

T43SR18E  
1/4  
S32|S33  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on rolling ground, on the east edge of a small wash, drains north.

- 77.542** The closing corner of sections 32 and 33, on the Utah-Arizona state boundary.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, with brass cap marked:

C C  
T43S R18E  
S32|S33  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on rolling sandy ground.

---

Point for the 1/4 section corner of section 33 only, at midpoint between closing corners.

Set an iron rebar, 12 inches long, 3/4 inches diameter, drilled and cemented 5 inches in the ground, with a 3 inch diameter aluminum cap marked:

T43S R18W  
1/4 S33  

---

2009

Set a steel fence post alongside the iron rebar.

Corner is located on a north facing slope.

---

From the corner of sections 5, 6, 31, and 32, on the north boundary, monumented with a stainless steel post, firmly set, projecting 2 inches above ground, with brass cap marked as described in the official record of the 2008 survey.

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

A steel fence post is located north of the stainless steel post.

**S. 0°03.3' E.**, between sections 5 and 6.

**40.000** Point for the 1/4 section corner of sections 5 and 6.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
1/4  
S6|S5  
2009

Set a steel fence post alongside the stainless steel post.

**80.000** Point for the corner of sections 5, 6, 7, and 8.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S6|S5  
S7|S8  
2009

Set a steel fence post alongside the stainless steel post.

---

From the corner of sections 4, 5, 8, and 9.

**WEST**, between sections 5 and 8.

**40.000** Point for the 1/4 section corner of sections 5 and 8.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S5  
1/4——  
S8  
2009

Set a steel fence post alongside the stainless steel post.

Raise a mound of stone, 2 feet base, 1 foot high, 1 foot west of the stainless steel post.

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

Corner is located on the south edge of a broad knoll. The centerline of a paved road, bears east and west, is located approximately 40 feet north of the corner.

80.000 The corner of sections 5, 6, 7, and 8.

---

N. 89°57.0' W., between sections 6 and 7.

40.000 Point for the 1/4 section corner of sections 6 and 7.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S6  
1/4——  
S7  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located approximately 50 feet south of the bottom of a wash, drains southwest.

82.501 The corner of sections 1, 6, 7, and 12, on the west boundary, monumented with a stainless steel post, firmly set, projecting 2 inches above ground, with brass cap marked as described in the official record of the 2005 survey.

---

From the corner of sections 5, 6, 7, and 8.

S. 0°03.3' E., between sections 7 and 8.

40.000 Point for the 1/4 section corner of sections 7 and 8.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
1/4  
S7|S8  
2009

Set a steel fence post alongside the stainless steel post.

80.000 Point for the corner of sections 7, 8, 17, and 18.

Set a stainless steel post, 30 inches long, 2 1/2 inches

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
 $\frac{S7}{S18} | \frac{S8}{S17}$   
 2009

Set a steel fence post alongside the stainless steel post.

---

From the corner of sections 8, 9, 16, and 17.

**WEST**, between sections 8 and 17.

**40.000** Point for the 1/4 section corner of sections 8 and 17.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
 S8  
 1/4———  
 S17  
 2009

Set a steel fence post alongside the stainless steel post.  
 Corner is located in a wash, drains southeast.

**80.000** The corner of sections 7, 8, 17, and 18.

---

**N. 89°55.6' W.**, between sections 7 and 18.

**40.000** Point for the 1/4 section corner of sections 7 and 18.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with brass cap marked:

T43SR18E  
 S7  
 1/4———  
 S18  
 2009

Set a steel fence post alongside the stainless steel post.

**82.640** The corner of sections 7, 12, 13, and 18, on the west boundary, monumented with a stainless steel post, firmly set, projecting 4 inches above ground, with brass cap marked as described in the

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

*CHAINS*

official record of the 2005 survey.

A mound of stone, 3 feet base, 2 feet high, is located west of the corner.

---

From the corner of sections 7, 8, 17, and 18.

**S. 0°03.3' E.**, between sections 17 and 18.

**40.000** Point for the 1/4 section corner of sections 17 and 18.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
1/4  
S18|S17  
2009

Set a steel fence post alongside the stainless steel post.

**80.000** Point for the corner of sections 17, 18, 19, and 20.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S18|S17  
S19|S20  
2009

Set a steel fence post alongside the stainless steel post.

---

From the corner of sections 16, 17, 20, and 21.

**WEST**, between sections 17 and 20.

**40.000** Point for the 1/4 section corner of sections 17 and 20.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 12 inches in the ground to solid rock, in a mound of stone, 2 1/2 feet base, 16 inches high, with brass cap marked:

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

T43SR18E  
S17  
1/4-----  
S20  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on north facing slope.

80.000 The corner of sections 17, 18, 19, and 20.

---

N. 89°55.4' W., between sections 18 and 19.

40.000 Point for the 1/4 section corner of sections 18 and 19.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S18  
1/4-----  
S19  
2009

Set a steel fence post alongside the stainless steel post.

82.710 The corner of sections 13, 18, 19, and 24, on the west boundary, monumented with a stainless steel post, firmly set, projecting 4 inches above ground, with brass cap marked as described in the official record of the 2005 survey.

A mound of stone, 3 feet base, 2 feet high, is located west of the corner.

---

From the corner of sections 17, 18, 19, and 20.

S. 0°03.3' E., between sections 19 and 20.

40.000 Point for the 1/4 section corner of sections 19 and 20.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
1/4  
S19|S20  
2009

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

Set a steel fence post alongside the stainless steel post.

80.000 Point for the corner of sections 19, 20, 29, and 30.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S19|S20  
S30|S29  
2009

Set a steel fence post alongside the stainless steel post.

---

From the corner of sections 20, 21, 28, and 29.

**WEST**, between sections 20 and 29.

40.000 Point for the 1/4 section corner of sections 20 and 29.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S20  
1/4———  
S29  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on flat, sandy ground.

80.000 The corner of sections 19, 20, 29, and 30.

---

**N. 89°54.0' W.**, between sections 19 and 30.

40.000 Point for the 1/4 section corner of sections 19 and 30.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

T43SR18E  
S19  
1/4—  
S30  
2009

Set a steel fence post alongside the stainless steel post.

- 82.802** The corner of sections 19, 24, 25, and 30, on the west boundary, monumented with an iron post, 2 inches diameter, firmly set, projecting 6 inches above ground, in a mound of stone, with brass cap marked as described in the official record of the 1924 survey.

A steel fence post is located alongside the iron post.

---

From the corner of sections 19, 20, 29, and 30.

**S. 0°03.3' E.**, between sections 29 and 30.

- 40.000** Point for the 1/4 section corner of sections 29 and 30.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
1/4  
S30|S29  
2009

Set a steel fence post alongside the stainless steel post.

- 80.000** Point for the corner of sections 29, 30, 31, and 32.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S30|S29  
S31|S32  
2009

Set a steel fence post alongside the stainless steel post.

---

From the corner of sections 28, 29, 32, and 33.

**WEST**, between sections 29 and 32.

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

**40.000** Point for the 1/4 section corner of sections 29 and 32.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43SR18E  
S29  
1/4—  
S32  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on flat, sandy ground.

**80.000** The corner of sections 29, 30, 31, and 32.

---

**N. 89°53.5' W.**, between sections 30 and 31.

**40.000** Point for the 1/4 section corner of sections 30 and 31.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 12 inches in the ground to solid rock, in a mound of stone, 3 feet base, 16 inches high, with brass cap marked:

T43SR18E  
S30  
1/4—  
S31  
2009

Set a steel fence post alongside the stainless steel post.

**82.934** The corner of sections 25, 30, 31, and 36, on the west boundary, monumented with an iron post, firmly set, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

A steel fence post is located alongside the corner.

---

From the corner of sections 29, 30, 31, and 32.

**S. 0°03.3' E.**, between sections 31 and 32.

**40.000** Point for the 1/4 section corner of sections 31 and 32.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 27 inches in the ground, with brass cap marked:

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

T43SR18E  
1/4  
S31|S32  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on flat, sandy ground.

- 77.575** The closing corner of sections 31 and 32 on the Utah-Arizona state boundary.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 27 inches in the ground, with brass cap marked:

C C  
T43S R18E  
S31|S32  
2009

Set a steel fence post alongside the stainless steel post.

Corner is located on the north edge of a wash, drains northeast.

---

Point for the 1/4 section corner of sections 32 only, determined at midpoint between closing corners,

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with brass cap marked:

T43S R18W  
1/4 S32  

---

2009

Set a steel fence post alongside the stainless steel post.

Corner is located on flat sandy ground. A small enclosure is located approximately 300 feet northeast of the corner.

---

Point for the 1/4 section corner of section 31 only, is at **40.000** chains distance from the closing corner of sections 31 and 32.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with brass cap marked:

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 43 SOUTH, RANGE 18 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T43S R18W  
1/4 S31  

---

2009

Set a steel fence post alongside the stainless steel post.

Corner is located on rolling, sandy ground.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**


---

<b>Name</b>	<b>Capacity</b>
Daniel W. Webb	Chief Cadastral Surveyor for Utah
Ronald K. Baugh	Supervisory Cadastral Surveyor
Jeremy D. Davis	Cadastral Surveyor
Daniel T. Gillins	Cadastral Surveyor
Dale A. Graff	Cadastral Surveyor
Steven L. Hope	Cadastral Surveyor
Michael L. Thompson	Cadastral Surveyor
M. Ross Workman	Cadastral Surveyor
Matthew Gillins	Survey Technician
Adrian M. Kurip	Survey Technician
Christopher J. May	Survey Technician
Gregg C. Ostergaard	Survey Technician

## CERTIFICATE OF SURVEY

I, *Ronald K. Batty, Cadastral Surveyor*, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing the date of the *8th day of December, 2008*, I have *retraced the Utah-Arizona State Boundary Line from Mile Post 225 to Mile Post 236, surveyed the east boundary, and surveyed the subdivisional lines, in Township 43 South, Range 18 East*, of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 30, 2010  
Date


  
Cadastral Surveyor

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt lake City, Utah

The foregoing field notes of the *retracement of the Utah-Arizona State Boundary Line from Mile Post 225 to Mile Post 236, and the survey of the east boundary, and the survey of the subdivisional lines, in T. 43 S., R 18 E., Salt Lake Meridian, Utah*, executed by *Ronald K. Batty, Cadastral Surveyor* having been critically examined and found correct, are hereby approved.

June 8, 2010  
Date

  
Chief Cadastral Surveyor for Utah