

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

**FIELD NOTES**

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH AND EAST BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 13, 14, 24, 25, 26, AND 35,

AND

THE DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 7271,

IN

**TOWNSHIP 31 SOUTH, RANGE 21 EAST,**

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Scott A. Burkhardt*

*Cadastral Surveyor*

Under Special Instructions dated *July 1, 2009*, and approved *July 1, 2009*,  
which provided for the surveys included under Group Number *1103*, Utah,  
and Assignment Instructions dated *July 1, 2009*

Survey Commenced, *July 2, 2009*  
Survey Completed, *August 5, 2009*

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

**FIELD NOTES**

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH AND EAST BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 13, 14, 24, 25, 26, AND 35,

AND

THE DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 7271,

IN

**TOWNSHIP 31 SOUTH, RANGE 21 EAST,**

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Scott A. Burkhardt*

*Cadastral Surveyor*

Under Special Instructions dated *July 1, 2009*, and approved *July 1, 2009*,  
which provided for the surveys included under Group Number *1103*, Utah,  
and Assignment Instructions dated *July 1, 2009*

Survey Commenced, *July 2, 2009*  
Survey Completed, *August 5, 2009*

# INDEX DIAGRAM

Township 31 South, Range 21 East.

6	5	4	3	2	1
7	8	9	10 21	22 11 20	12 13
18	17	16	15	19 14 18	11 13 5 10
19	20	21	22	17 23 17	10 24 8
30	29	28	27	16 26 15	7 25 6
31	32	33	34	13 35 4	6 36 3

The Subdivision of Section 13.....Page 22  
 The Subdivision of Section 14.....Page 25  
 The Subdivision of Section 24.....Page 27  
 The Subdivision of Section 25.....Page 30  
 The Subdivision of Section 26.....Page 32  
 The Subdivision of Section 35.....Page 34  
 Dependent Resurvey of Mineral Survey No. 7271.....Page 37

## TOWNSHIP 31 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH.

The following field notes describe the dependent resurvey of a portion of the south and east boundaries, a portion of the subdivisional lines, and the subdivision of sections 13, 14, 24, 25, 26, and 35, and the dependent resurvey of a portion of Mineral Survey 7271, in Township 31 South, Range 21 East, of the Salt Lake Meridian, in the State of Utah.

## HISTORY OF SURVEYS

Surveyed by		Retraced or Resurveyed by	
<b>SOUTH BOUNDARY</b>			
All	S.P. Stewart & E.H. Anderson	1911	
<b>EAST BOUNDARY</b>			
All	S.P. Stewart & E.H. Anderson	1911	
Portion		R.K. Baugh	2005
<b>WEST BOUNDARY</b>			
All	S.P. Stewart & E.H. Anderson	1911	
Portion		V.E. Lane	1957
<b>NORTH BOUNDARY</b>			
All	E. Buettner	1884	
All		S.P. Stewart & E.H. Anderson	1911
<b>SUBDIVISION</b>			
Portion	S.P. Stewart & E.H. Anderson	1911	
<b>MINERAL SURVEY NO. 7271</b>			
All	R.E. Brandon	1955	

## TOWNSHIP 31 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 1103, dated July 1, 2009.

The direction of the lines was determined by references to true meridians, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods*, dated May 9, 2001, Version 1.0. Trimble Model 5800 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic Control was derived from GPS static observations, post processed by the National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS); MONTICELLO UT2006, MESA CNTY 04 COOP, and CRAWFORD CORS ARP.

The geographic position of the section corner of sections 10, 11, 14, and 15, T. 31 S., R. 21 E., as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: 38° 05' 25.312" N.,  
Longitude: 109° 35' 28.694" W., N.A.D. 83,  
Network Accuracy = 0.200 meters at 95% confidence.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

CHAINS

---

Dependent Resurvey of a Portion of the South Boundary,  
T. 31 S., R. 21 E., Salt Lake Meridian, Utah.

---

Reestablishment of the Survey Executed by  
S.P. Stewart & E.H. Anderson in 1911.

---

Beginning at the witness corner to the corner of Townships 31 and 32 South, Ranges 21 and 22 East, monumented with an iron post, 3 inches diameter, flush in a mound of stone, 4 ft. base, 3 ft. high, with brass cap marked as described in the official record of the 1911 survey.

from which the remaining 1911 bearing trees

A juniper, 12 inches diameter, bears N. 10°12' E., 142 links distance, with illegible markings in an open blaze.  
(Record: Cedar)

A pinon, 14 inches diameter, bears S. 24°05' W., 102 links distance, with illegible markings in an open blaze.

No remains of the NW and SE bearing trees.

S. 89° 52.2' W., between sections 1 and 36, on the south boundary of the township.

**35.002** The 1/4 section corner of sections 1 and 36, monumented with an iron post, 1 inch diameter, firmly set, projecting 16 inches above a mound of stone, 2 ft. base, 6 inches high, with brass cap marked as described in the official record of the 1911 survey.

Rehabilitate mound of stone, 3 ft. base, to top of brass cap.

from which the 1911 bearing trees

A pinon snag, 5 inches diameter, bears N. 56° 38' W., 22.8 links distance, marked 1/4 S36 BT. (Record: N. 59° 30' W., 22 links distance.)

A pinon, 8 inches diameter, bears S. 9° 57' E., 7.7 links distance, marked 1/4 S1 BT. (Record: S. 14° 10' E., 7 links distance.)

Corner is located on a moderately steep, north-facing slope on top of Sundial Mesa, accessible by foot or helicopter only.

---

N. 89° 51.9' W., beginning new measurement.

**40.332** The corner of sections 1, 2, 35, and 36, monumented with an iron post, 3 inches diameter, firmly set, projecting 15 inches above a

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

CHAINS

mound of stone, 3 ft. base, 1 ft. high, with brass cap marked as described in the official record of the 1911 survey.

Rehabilitate mound of stone, 4 ft. base, to top of brass cap.

from which the remaining 1911 bearing trees

A pinon, 5 inches diameter, bears N. 27° 38' E., 20.1 links distance, with illegible markings (Record: N. 29° E., 21 links distance).

No remains of the SE bearing tree.

A pinon, 9 inches diameter, bears S. 52° 34' W., 57.7 links distance, with illegible markings (Record: S. 52° 30' W., 5 links distance).

A pinon, 6 inches diameter, bears N. 10° 25' W., 64.0 links distance, with illegible markings (Record: N. 80° 50' W., 62 links distance).

N. 89° 47.1' W., between sections 2 and 35.

39.599 The 1/4 section corner of sections 2 and 35, monumented with an iron post, 1 inch diameter, firmly set, projecting 15 inches above an embedded collar of stone, 2 ft. diameter, with brass cap marked as described in the official record of the 1911 survey.

There are no remains of the 1911 bearing trees.

Rehabilitate mound of stone, 3 ft. base, to top of brass cap.

Set a steel fence post west of iron post.

S. 89° 55.8' W., beginning new measurement.

20.009 Point for the W 1/16 section corner of sections 2 and 35.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked:

T31S R21E  
S 35  
W 1/16 ———  
S 2  
T32S  
2009

A fence, 4-strand barbed wire, extending east and west, bears north, 2 links distance.

Set a steel fence post north of the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

CHAINS

Corner is located on fairly level ground, east of Cottonwood Creek.

- 36.430 Intersect the centerline of San Juan County Road 107, a maintained gravel road, 20 ft. wide, extending N. 14° E. and S. 14° W.
- 40.018 The corner of sections 2, 3, 34, and 35, monumented with an iron post, 3 inches diameter, firmly set, projecting 11 inches above the ground, with brass cap marked as described in the official record of the 1911 survey.

Corner located in a fence, 4-strand barbed wire, extending east and west.

---

Dependent Resurvey of a Portion of the East Boundary,  
T. 31 S., R. 21 E., Salt Lake Meridian, Utah.

---

Reestablishment of the Survey Executed by S.P. Stewart  
& E.H. Anderson in 1911, and the Resurvey Executed  
by R.K. Baugh in 2005.

---

From the corner of sections 13, 18, 19, and 24, on the east boundary of the township, monumented with an iron post, 3 inches diameter, firmly set, flush in a mound of stone, 4 ft. base, 2 ft. high, with brass cap marked as described in the official record of the 2005 resurvey.

from which the remaining bearing objects

A sandstone boulder, 12x12x12 ft., bears N. 52° E., 308 links distance, marked + T31S R22E S18 BO.

A sandstone boulder, 12x12x10 ft., bears S. 67° E., 183 links distance, with dim, illegible markings.

No remains of the SW and NW bearing objects.

N. 0° 04.1' E., between sections 13 and 18.

- 19.961 Point for the S 1/16 section corner of sections 13 and 18, not monumented.
- 39.922 True point for the 1/4 section corner of sections 13 and 18, falls on top of an inaccessible mesa; impracticable to establish a monument at this location.
- 55.393 The witness corner to the 1/4 section corner of sections 13 and 18, monumented with an iron post, 1 inch diameter, firmly set, projecting 7 inches above a mound of stone, 3 ft. base, 2 ft. high, with brass cap marked as described in the official record of the 2005 resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

CHAINS

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 31 S., R. 21 E., Salt Lake Meridian, Utah.

---

Reestablishment of the Survey Executed by  
S.P. Stewart & E.H. Anderson in 1911.

---

From the corner of sections 1, 2, 35, and 36, on the south boundary of the township, hereinbefore described.

N. 0° 08.2' E., between sections 35 and 36.

- 39.697 The 1/4 section corner of sections 35 and 36, monumented with an iron post, 1 inch diameter, firmly set, projecting 15 inches above a mound of stone, 2 ft. base, 1 ft. high, with brass cap marked as described in the official record of the 1911 survey.

Rehabilitate mound of stone, 4 ft. base, to top of brass cap.

from which the 1911 bearing trees

A pinon, 9 inches diameter, bears N. 43° 47' W., 14.7 links distance, with illegible markings (Record: N. 47° W., 15 links distance, marked 1/4 S35 BT).

A pinon, 6 inches diameter, bears N. 66° 03' E., 29.4 links distance, with illegible markings (Record: N. 31° 20' E., 30 links distance, marked 1/4 S36 BT).

---

N. 0° 25.2' W., beginning new measurement.

- 40.170 True point for the corner of sections 25, 26, 35, and 36, at proportionate distance, falls on a steep sandstone bedrock slope, where it is impracticable to establish a permanent monument; there is no remaining evidence of the "+" on the bedrock, as described in the official record of the 1911 survey.

---

From the corner of sections 25, 30, 31, and 36, on the east boundary of the township, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 2 inches above the ground, with aluminum cap marked as described in the official record of the 2005 resurvey of the west boundary of T. 31 S., R. 22 E.

N. 89° 47.4' W., between sections 25 and 36.

- 19.987 Point for the E 1/16 section corner of sections 25 and 36.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in ground, magnet at base, in a mound of stone, 2 ft. base, to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

CHAINS

T31S R21E  
S 25  
E 1/16 ———  
S 36  
2009

Set a steel fence post northeast of the aluminum post.

Corner is located near the top of a steep, east-facing talus slope, at the base of a vertical sandstone cliff. Difficult GPS environment, confirm monument location with total station.

- 39.974 The 1/4 section corner of sections 25 and 36, monumented with an iron post, 1 inch diameter, firmly set, projecting 14 inches above a mound of stone, 2 ft. base, 1 ft. high, with brass cap marked as described in the official record of the 1911 survey.

Rehabilitate mound of stone, 4 ft. base, to top of brass cap.

from which the 1911 bearing trees

A pinon, 15 inches diameter, bears N. 10° 54' E., 66.9 links distance, marked 1/4 S25 BT (Record: N. 10° 30' E., 67 links distance).

A pinon snag, 6 inches diameter, bears S. 40° 19' W., 5.3 links distance, marked BT 1/4 S36 BT (Record: S. 43° 28' W., 6 links distance).

Corner is located on top of Sundial mesa, accessible by foot or helicopter only.

---

S. 89° 40.9' W., beginning new measurement.

- 39.985 True point for the corner of sections 25, 26, 35, and 36.

---

N. 0° 01.0' W., between sections 25 and 26.

- 6.240 The witness corner to the corner of sections 25, 26, 35, and 36, monumented with an iron post, 2 inches diameter, firmly set, projecting 11 inches above a mound of stone, 2 ft. base, 1 ft. high, with brass cap marked as described in the official record of the 1911 survey.

from which the remaining 1911 bearing trees

A pinon, 7 inches diameter, bears N. 46° 47' E., 121.7 links distance, marked S25 BT (Record: N. 46° 30' E., 123 links distance, marked WC T31S R21E S25 BT).

A pinon, 11 inches diameter, bears S. 27° 26' W., 54.7 links distance, marked WC T31S R21E S26 BT (Record: S. 27° 17' W., 54 links distance).

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

CHAINS

Rehabilitate mound of stone, 4 ft. base, to top of brass cap.

Corner is located on a moderately steep, north-facing slope on top of Sundial Mesa, accessible by foot or helicopter only.

---

N. 0° 10.4' E., beginning new measurement.

- 33.706 The 1/4 section corner of sections 25 and 26, monumented with an iron post, 1 inch diameter, firmly set, projecting 2 inches above the ground, with brass cap marked as described in the official record of the 1911 survey; there is no remaining evidence of the original bearing object.

Set a steel fence post north of the iron post.

---

N. 0° 02.5' E., beginning new measurement.

- 20.041 Point for the N 1/16 section corner of sections 25 and 26, not monumented.

- 40.082 The corner of sections 23, 24, 25, and 26, monumented with an iron post, 2 inches diameter, firmly set, projecting 16 inches above the ground, with brass cap marked as described in the official record of the 1911 survey; there is no remaining evidence of the original accessories.

Set a steel fence post north of the iron post.

---

From the corner of sections 19, 24, 25, and 30, on the east boundary of the township, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 2 inches above the ground, with aluminum cap marked as described in the official record of the 2005 resurvey of the west boundary of T. 31 S., R. 22 E, with a mound of stone, 2 ft. base, 1 ft. high, west of corner.

S. 89° 57.6' W., between sections 24 and 25.

- 20.172 Point for the E 1/16 section corner of sections 24 and 25.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked:

T31S R21E  
S 24  
E 1/16 ———  
S 25  
2009

Set a steel fence post southeast of the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

CHAINS

Corner is located on a moderately steep, east-facing, rocky slope.

- 28.271 The witness corner to the 1/4 section corner of sections 24 and 25, monumented with an iron post, 1 inch diameter, firmly set in bedrock, projecting 12 inches above the rock, with brass cap marked as described in the official record of the 1911 survey.

Raise a mound of stone around iron post, 2 1/2 ft. base, to top of brass cap.

from which the 1911 bearing trees

A juniper, 10 inches diameter, bears S. 50° 58' E., 37.4 links distance, with illegible markings in a partially healed blaze (Record: S. 41° 30' E., 36 links distance, marked WC 1/4 S25 BT).

A juniper, 10 inches diameter, bears N. 46° 27' E., 86.4 links distance, marked S24 BT. (Record: N. 42° W., 94 links distance, marked WC 1/4 S24 BT.)

from which

A "+", on vertical cliff face, 2 ft. above the ground, bears S. 73° W., 2.9 links distance, not of record.

Corner is located 3 links east of overhanging sandstone cliff, 150 ft. high. Difficult location to GPS, confirm location of monument with a total station.

---

S. 89° 57.4' W., beginning new measurement.

- 11.856 True point for the 1/4 section corner of sections 24 and 25, at proportionate distance, falls on vertical sandstone cliff, impracticable to establish a permanent monument.

- 31.666 Point for the W 1/16 section corner of sections 24 and 25.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, two 60d nails at the base as a memorial, with aluminum cap marked:

T31S R21E  
S 24  
W 1/16 ———  
S 25  
2009

Set a steel fence post north of the aluminum post.

Corner is located on a gentle west slope, with desert vegetation.

- 51.476 The corner of sections 23, 24, 25, and 26.
-

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

CHAINS

N. 0° 07.6' W., between sections 23 and 24.

- 40.019** Point for the 1/4 section corner of sections 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked:

T31S R21E	
1/4	
S 23	S 24
2009	

Set a steel fence post north of the aluminum post.

Corner is located on fairly level ground, in tamarisk bushes.

- 80.038** Point for the corner of sections 13, 14, 23, and 24, at proportionate distance; found an iron post, 2 inches diameter, 36 inches long, bent, laying horizontal, 8 inches below the ground, in a previously cultivated field, with brass cap marked as described in the official record of the 1911 survey; there is no remaining evidence of the original accessories.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked:

T31S R21E	
S 14	S 13
S 23	S 24
2009	

Bury iron post south of the aluminum post.

Set a steel fence post west of the aluminum post.

Corner is located in a fairly level field, with sparse vegetation.

From the corner of sections 13, 18, 19, and 24, on the east boundary of the township, hereinbefore described.

S. 89° 58.9' W., between sections 13 and 24.

- 19.908** Point for the E 1/16 section corner of sections 13 and 24.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

CHAINS

T31S R21E  
S 13  
E 1/16 ———  
S 24  
2009

Set a steel fence post north of the aluminum post.

Corner is located on fairly level ground, south of vertical, sandstone cliffs.

- 39.816 The 1/4 section corner of sections 13 and 24, monumented with an iron post, 1 inch diameter, firmly set, projecting 3 inches above the ground, with brass cap marked as described in the official record of the 1911 survey; there is no remaining evidence of the original accessories.

Set a steel fence post east of the iron post.

Corner is located in the northeast shoulder of paved Utah State Highway 211, in thick brush.

---

S. 89° 57.4' W., beginning new measurement.

- 0.630 Intersect the centerline of paved Utah State Highway 211, 29 ft. wide, extending N. 41° W. and S. 41° E.
- 20.009 Point for the W 1/16 section corner of sections 13 and 24, not monumented.
- 40.018 The corner of sections 13, 14, 23, and 24.

---

NORTH, between sections 13 and 14.

- 20.010 Point for the S 1/16 section corner of sections 13 and 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked:

T31S R21E  
S 1/16  
S 14 | S 13  
2009

Set a steel fence post north of the aluminum post.

Corner is located on fairly level, formerly cultivated ground, with sparse vegetation.

- 40.020 Point for the 1/4 section corner of sections 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked:

T31S R21E  
1/4  
S 14 | S 13  
2009

Set a steel fence post north of the aluminum post.

Corner is located on fairly level terrain, formerly cultivated ground, with no vegetation.

45.355 Intersect the centerline of San Juan County Road 107, a maintained gravel road, 20 ft. wide, extending N. 80° E. and S. 76° W.

60.030 Point for the N 1/16 section corner of sections 13 and 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, in a collar of stone, 2 ft. diameter, with aluminum cap marked:

T31S R21E  
N 1/16  
S 14 | S 13  
2009

Set a steel fence post north of the aluminum post.

Corner is located in rolling hills, with grass and sparse trees.

80.040 The corner of sections 11, 12, 13, and 14, monumented with an iron post, 2 inches diameter, firmly set, projecting 16 inches above a collar of stone, 3 ft. diameter, with brass cap marked as described in the official record of the 1911 survey.

from which the remaining 1911 bearing trees

A juniper, 15 inches diameter, bears S. 10° 08' E., 282.0 links distance, with hack marks in an open blaze (Record: marked T31S R21E S13 BT).

No remains of SW bearing tree of record.

A juniper, 15 inches diameter, bears N. 64° 20' W., 79.0 links distance, marked T31S R21E S11 BT.

Rehabilitate mound of stone.

Set a steel fence post north of the iron post.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

CHAINS

From the corner of sections 7, 12, 13, and 18, on the east boundary of the township, monumented with an iron post, 3 inches diameter, firmly set, projecting 13 inches above the ground, with brass cap marked as described in the official record of the 2005 resurvey of the west boundary of T. 31 S., R. 22 E.

from which

A 4x4 wooden post, not of record, projecting 3 ft., in the center of a mound of stone, 4 ft. base, 2 ft. high, bears N. 33° 57' E., 83.4 links distance, with no visible markings.

A 4x4 wooden post, not of record, projecting 2 1/2 ft., in the center of a mound of stone, 5 ft. base, 1 ft. high, bears S. 54° 11' E., 59.3 links distance, with no visible markings.

A 4x4 wooden post, not of record, sawed off flush, in the center of an embedded mound of stone, 4 ft. base, bears S. 39° 11' W., 82.3 links distance, with no visible markings.

S. 89° 55.2' W., between sections 12 and 13.

39.926 Point for the 1/4 section corner of sections 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground, magnet at base, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T31S R21E  
S 12  
1/4 ———  
S 13  
2009

Set a steel fence post east of the aluminum post.

Corner is located on a moderately steep, southeast-facing hillside.

79.310 Intersect the centerline of paved Utah State Highway 211, 29 ft. wide, extending N. 41° W. and S. 41° E.

79.852 The corner of sections 11, 12, 13, and 14.

From the corner of sections 2, 3, 34, and 35, on the south boundary of the township, hereinbefore described.

N. 0° 22.5' W., between sections 34 and 35.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

CHAINS  
20.038

Point for the S 1/16 section corner of sections 34 and 35.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in ground, magnet at base, with aluminum cap marked:

T31S R21E  
S 1/16  
S 34 | S 35  
2009

Set a steel fence post southwest of the aluminum post.

Corner is located on the west side of a north and south valley, on a gentle, easterly slope.

- 40.076 The 1/4 section corner of sections 34 and 35, monumented with an iron post, 1 inch diameter, firmly set, projecting 13 inches above the ground, with brass cap marked as described in the official record of the 1911 survey.

from which the remaining 1911 bearing tree

A juniper, 12 inches diameter, bears S. 36° 00' W., 119.6 links distance, marked 1/4 S34 BT (Record: S. 28° 00' W., 100 links distance).

Rehabilitate mound of stone, 3 ft. base, to top of brass cap.

Set a steel fence post northwest of the iron post.

Corner is located on a very steep talus slope, at the base of vertical sandstone cliffs to the west.

---

N. 0° 09.7' W., beginning new measurement.

- 39.927 The corner of sections 26, 27, 34, and 35, monumented with an iron post, 2 inches diameter, firmly set, projecting 15 inches above the ground, with brass cap marked as described in the official record of the 1911 survey.

from which the remaining 1911 bearing trees

A juniper, 6 inches diameter, bears S. 61° 54' E., 76.2 links distance, marked BT with other illegible markings (Record: S. 62° 30' E., 78 links distance, marked T31S R21E S35 BT).

No remains of the SW bearing tree.

A juniper, 20 inches diameter, bears N. 22° 32' W., 81.9 links distance, marked BT with other illegible markings (Record: N. 22° W., 80 links distance, marked T31S R21E S27 BT).

Rehabilitate mound of stone.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

## CHAINS

Set a steel fence post east of the iron post.

Corner is located on a moderately steep, north-facing slope.

---

From the corner of sections 25, 26, 35, and 36.

N. 89° 49.9' W., between sections 26 and 35.

19.722 Point for the E 1/16 section corner of sections 26 and 35.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 5 inches in the ground, to bedrock, magnet at base, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T31S R21E  
S 26  
E 1/16 ———  
S 35  
2009

Set a steel fence post southwest of the aluminum post.

Corner is located on a steep talus slope, at the base of sandstone ledges, with vertical sandstone cliffs to the east.

39.444 The 1/4 section corner of sections 26 and 35, monumented with an iron post, 1 inch diameter, firmly set, projecting 4 inches above the ground, with brass cap marked as described in the official record of the 1911 survey; there is no remaining evidence of the original accessories.

Set a steel fence post north of the iron post.

---

N. 89° 49.7' W., beginning new measurement.

19.445 Intersect the centerline of San Juan County Road 107, a maintained gravel road, 20 ft. wide, extending N. 6° E. and S. 6° W.

20.166 Point for the W 1/16 section corner of sections 26 and 35.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in ground, magnet at base, with aluminum cap marked:

T31S R21E  
S 26  
W 1/16 ———  
S 35  
2009

Set a steel fence post north of the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

CHAINS

Corner is located on a gentle, east slope, west of a maintained dirt road.

40.332 The corner of sections 26, 27, 34, and 35.

---

N. 0° 07.5' E., between sections 26 and 27.

40.091 The 1/4 section corner of sections 26 and 27, monumented with an iron post, 1 inch diameter, firmly set, projecting 12 inches above the ground, with brass cap marked as described in the official record of the 1911 survey.

Set a steel fence post north of the iron post.

---

N. 0° 33.6' W., beginning new measurement.

39.600 The corner of sections 22, 23, 26, and 27, monumented with an iron post, 2 inches diameter, firmly set, projecting 15 inches above the ground, in a mound of stone, 2 ft. base, 1 ft. high, with brass cap marked as described in the official record of the 1911 survey. Bottom flanges rusted off post, remonument to better perpetuate corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, magnet at base, in a mound of stone, 2 ft. base, to top of aluminum cap marked:

T31S R21E	
S 22	S 23
S 27	S 26
2009	

from which the remaining 1911 bearing trees

A juniper, 28 inches diameter, bears S. 7° 24' E., 81.0 links distance, marked T31S R21E S26 BT (Record: S. 6° 30' E., 80 links distance).

A juniper, 34 inches diameter, bears N. 41° 35' W., 46.8 links distance, marked T31S R21E S22 BT (Record: N. 40° W., 47 links distance).

No remains of the NE and SW bearing trees.

Bury iron post, 2 inches diameter, 24 inches long, north of the aluminum post.

Corner is located on a moderately steep, north-facing slope on top of Bridger Jack Mesa, accessible by foot or helicopter only.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

## CHAINS

From the corner of sections 23, 24, 25, and 26.

S. 89° 55.5' W., between sections 23 and 26.

20.047 Point for the E 1/16 section corner of sections 23 and 26.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked:

T31S R21E  
S 23  
E 1/16 ———  
S 26  
2009

Set a steel fence post north of the aluminum post.

Corner is located in rolling, sandy terrain, with grass and cactus.

24.510 Intersect the centerline of San Juan County Road 107, a maintained gravel road, 20 ft. wide, extending N. 21° E. and S. 21° W.

39.384 Point selected for the witness corner to the 1/4 section corner of sections 23 and 26; there is no remaining evidence of the original witness corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, in a collar of stone, 3 ft. base, with aluminum cap marked:

WC  
T31S R21E  
S 23  
1/4 ←————  
S 26  
2009

Set a steel fence post west of aluminum post.

40.094 True point for the 1/4 section corner of sections 23 and 26, falls in wash; location subject to erosion.

80.188 The corner of sections 22, 23, 26, and 27.

N. 0° 04.0' E., between sections 22 and 23.

39.729 The 1/4 section corner of sections 22 and 23, monumented with an iron post, 1 inch diameter, firmly set, projecting 16 inches above a collar of stone, 2 ft. base, with brass cap marked as described in the official record of the 1911 survey.

from which the 1911 bearing trees

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

CHAINS

A juniper, 4 inches diameter, bears N. 78° 23' E., 35.3 links distance, with illegible markings (Record: EAST, 50 links distance, marked 1/4 S23 BT).

A juniper, 9 inches diameter, bears S. 65° 50' W., 30.0 links distance, marked 1/4 S22 BT (Record: S. 37° 20' W., 18 links distance).

Rehabilitate mound of stone, 3 ft. base, to top of brass cap.

Corner is located on top of Bridger Jack Mesa, accessible by foot or helicopter only.

---

N. 0° 03.9' E., beginning new measurement.

40.306 The corner of sections 14, 15, 22, and 23, monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone, 2 ft. base, with brass cap marked as described in the official record of the 1911 survey. Iron post rusted out 14 inches from top; remonument to better perpetuate corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, magnet at base, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T31S	R21E
S 15	S 14
S 22	S 23
2009	

from which the remaining 1911 bearing tree

A juniper, 16 inches diameter, bears S. 63° 07' E., 166.5 links distance, marked T31S R21E S23 BT (Record: S. 60° 30' E., 165 links distance).

No remains of the NE bearing tree.

Bury remains of the iron post next to corner.

Set a steel fence post north of corner.

Corner is located in rolling terrain, with vertical sandstone cliffs to the west and south.

---

From the corner of sections 13, 14, 23, and 24.

S. 89° 37.4' W., between sections 14 and 23.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

## CHAINS

17.215 Intersect the centerline of San Juan County Road 107, a maintained gravel road, 20 ft. wide, extending N. 2° E. and S. 2° W.

20.007 Point for the E 1/16 section corner of sections 14 and 23.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground, to bedrock, magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T31S R21E  
S 14  
E 1/16 ———  
S 23  
2009

Set a steel fence post north of the aluminum post.

Corner is located on a south and east facing slope, with sandstone bedrock ledges, east of Bridger Jack Mesa.

40.014 The 1/4 section corner of sections 14 and 23, monumented with an iron post, 1 inch diameter, loosely set, in a collar of stone, 2 ft. diameter, with brass cap marked as described in the official record of the 1911 survey. Iron post rusted out 20 inches from the top, remonument to better perpetuate corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground, magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T31S R21E  
S 14  
1/4 ———  
S 23  
2009

Bury remains of the iron post next to the aluminum post.

Set a steel fence post north of the aluminum post.

Corner is located on a steep, north-facing, unconsolidated slope.

N. 89° 46.8' W., beginning new measurement.

39.889 The corner of sections 14, 15, 22, and 23.

N. 0° 00.4' E., between sections 14 and 15.

39.764 The witness corner to the 1/4 section corner of sections 14 and 15, monumented with an iron post, 1 inch diameter, firmly set, projecting 8 inches above an embedded mound of stone, 3 ft. base,

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

CHAINS

1 ft. high, with brass cap marked as described in the official record of the 1911 survey; there is no remaining evidence of the original accessories.

Rehabilitate mound of stone, 3 ft. base, to top of brass cap.

Set a steel fence post northeast of the iron post.

---

N. 0° 03.0' W., beginning new measurement.

0.250 True point for the 1/4 section corner of sections 14 and 15, at proportionate distance, located in wash, subject to erosion.

40.264 The corner of sections 10, 11, 14, and 15, at proportionate distance, laying loose on the ground, an iron post, 2 inches diameter, 36 inches long, with brass cap marked as described in the official record of the 1911 survey; there is no remaining evidence of the original accessory.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, in a collar of stone, 3 ft. diameter, with aluminum cap marked:

T31S R21E	
S 10	S 11
S 15	S 14
2009	

Bury iron post south of the aluminum post.

Set a steel fence post north of the aluminum post.

Corner is located in rolling terrain, west of a shallow wash.

---

From the corner of sections 11, 12, 13, and 14.

S. 89° 54.6' W., between sections 11 and 14.

19.962 Point for the E 1/16 section corner of sections 11 and 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, in a collar of stone, 2 ft. diameter, with aluminum cap marked:

T31S R21E	
	S 11
E 1/16	—
	S 14
2009	

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

CHAINS

Set a steel fence post north of the aluminum post.

Corner is located on a fairly level hilltop, with rocky soil and grasses.

- 39.924 The 1/4 section corner of sections 11 and 14, monumented with an iron post, 1 inch diameter, buried 8 inches below ground, bent, next to a buried mound of stone, with brass cap marked as described in the official record of the 1911 survey.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 13 inches below ground, magnet at base, with aluminum cap marked:

T31S R21E  
S 11  
1/4 ———  
S 14  
2009

Bury iron post next to the aluminum post.

From the corner, the center of an irrigation pivot, 4 inches diameter, flush with the ground, bears N. 76° 41' W., 0.327 chain distance.

Corner is located in an irrigated hay field. Bury the aluminum post for protection from farm activities; found no reasonable location for a steel fence post or reference monuments.

---

S. 89° 55.1' W., beginning new measurement.

- 39.991 The corner of sections 10, 11, 14, and 15.

---

S. 89° 56.5' W., between sections 10 and 15.

- 40.092 True point for the 1/4 section corner of sections 10 and 15, at proportionate distance, falls on inaccessible sandstone cliff, not monumented.

- 46.807 The witness corner to the 1/4 section corner of sections 10 and 15, monumented with an iron post, 1 inch diameter, firmly set, projecting 15 inches above a mound of stone, 3 ft. base, 2 ft. high, with brass cap marked as described in the 1911 survey.

Rehabilitate the mound of stone, 3 ft. base, to top of brass cap.

Corner is located on a steep, west facing talus slope, at the base of a vertical sandstone cliff to the east.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

## CHAINS

From the corner of sections 10, 11, 14, and 15.

N. 0° 00.5' W., between sections 10 and 11.

- 40.014 The 1/4 section corner of sections 10 and 11, monumented with the cement core and other remains of the 1911 iron post.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked:

T31S R21E  
1/4  
S10 | S11  
2009

Bury remains of iron post next to the aluminum post.

Set a steel fence post east of the aluminum post.

Corner is located in eroded dirt hills, west of a plowed field, and east of Indian Creek.

The Subdivision of Section 13,  
T. 31 S., R. 21 E., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 13 and 24.

N. 0° 03.7' W., on the N-S centerline of section 13.

- 19.981 True point for the center S 1/16 section corner of section 13, falls in a rocky ravine, subject to erosion; where it is impracticable to establish a permanent monument.

- 39.962 True point for the center 1/4 section corner of section 13, at intersection with the E-W centerline, falls on a steeply sloping sandstone face; where it is impracticable to establish a permanent monument.

Point selected for the offline witness corner to the center 1/4 section corner of section 13, bears S. 61° 24.2' E., 0.071 chains distance.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 8 inches in the ground, to bedrock, magnet at base, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

WC  
T31S R21E  
C 1/4 S13  
2009

THE SUBDIVISION OF SECTION 13,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

## CHAINS

Set a steel fence post north of the aluminum post.

Corner is located near the top of a steep, northwest-facing talus slope, at the foot of vertical sandstone cliffs to the southeast, difficult to access.

80.064 The 1/4 section corner of sections 12 and 13.

---

From the point for the 1/4 section corner of sections 13 and 18, on the east boundary of the township, hereinbefore described.

N. 89° 57.7' W., on the E-W centerline of section 13.

19.951 Point for the center E 1/16 section corner of section 13, not monumented.

39.902 The true point for the center 1/4 section corner of section 13.

58.487 Intersect the centerline of paved Utah State Highway 211, 29 ft. wide, extending N. 21° W. and S. 21° E.

59.888 Point for the center W 1/16 section corner of section 13.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked:

T31S R21E  
W 1/16  
C ——— C  
S 13  
2009

Set a steel fence post north of the aluminum post.

Corner is located in gently rolling terrain, west of paved Utah State Highway 211.

79.874 The 1/4 section corner of sections 13 and 14.

---

From the E 1/16 section corner of sections 13 and 24.

N. 0° 00.2' E., on the N-S centerline of the SE 1/4 of section 13.

19.971 Point for the SE 1/16 section corner of section 13, at intersection with the E-W centerline of the SE 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in ground, magnet at base, with aluminum cap marked:

T31S R21E  
SE 1/16 S 13  
2009

THE SUBDIVISION OF SECTION 13,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

## CHAINS

Set a steel fence post east of the aluminum post.

Corner is located on a very steep, unconsolidated south-facing slope, at the base of vertical sandstone cliffs to the north.

39.942 The point for the center E 1/16 section corner of section 13.


From the point for the S 1/16 section corner of sections 13 and 18, on the east boundary of the township, hereinbefore described.

N. 89° 59.4' W., on the E-W centerline of the SE 1/4 of section 13.

19.929 The SE 1/16 section corner of section 13.

39.432 Point selected for the witness corner to the center S 1/16 section corner of section 13.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 21 inches in the ground, to bedrock, magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:



Set a steel fence post north of the aluminum post.

Corner is located on a rocky hillside, east of a small reservoir.


39.858 True point for the center S 1/16 section corner of section 13.

From the point for the W 1/16 section corner of sections 13 and 24.

N. 0° 01.8' W., on the N-S centerline of the SW 1/4 of section 13.

19.995 Point for the SW 1/16 section corner of section 13, at intersection with the E-W centerline of the SW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in ground, magnet at base, with aluminum cap marked:



Set a steel fence post north of the aluminum post.

THE SUBDIVISION OF SECTION 13,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

## CHAINS

Corner is located on a north-sloping hill, south of an irrigation ditch.

39.990 The center W 1/16 section corner of section 13.

---

From the true point for the center S 1/16 section corner of section 13.

S. 89° 59.9' W., on the E-W centerline of the SW 1/4 of section 13.

11.010 Intersect the centerline of paved Utah State Highway 211, 29 ft. wide, extending N. 21° W. and S. 21° E.

19.998 The SW 1/16 section corner of section 13.

39.996 The S 1/16 section corner of sections 13 and 14.

---

The Subdivision of Section 14,  
T. 31 S., R. 21 E., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 14 and 23.

N. 0° 03.5' E., on the N-S centerline of section 14.

40.224 Point for the center 1/4 section corner of section 14, at intersection with the E-W centerline.

Set a brass tablet, 3 1/4 inches diameter, with a 2 1/2 inch stem, flush with sandstone, in cement bond into a drill hole on solid rock, 4 inches below ground, marked:

T31S R21E  
C 1/4 S 14  
2009

Set a steel fence post northeast of the brass tablet.

Corner is located on a gentle north slope, with exposed sandstone bedrock, in scattered juniper trees.

60.231 Point for the center N 1/16 section corner of section 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground, to bedrock, magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

THE SUBDIVISION OF SECTION 14,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

## CHAINS

T31S R21E  
C  
N 1/16 | S 14  
C  
2009

Set a steel fence post west of the aluminum post.

Corner is located on rolling ground, with exposed sandstone outcrops, south of Indian Creek.

80.238 The 1/4 section corner of sections 11 and 14.

---

From the 1/4 section corner of sections 13 and 14.

S. 89° 55.1' W., on the E-W centerline of section 14.

19.405 Intersect the centerline of San Juan County Road 107, a maintained gravel road, 20 ft. wide, extending N. 18° W. and S. 18° E.

19.984 Point for the center E 1/16 section corner of section 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, in a collar of stone, 2 ft. base, with aluminum cap marked:

T31S R21E  
E 1/16  
C ————— C  
S 14  
2009

Set a steel fence post north of the aluminum post.

21.188 Intersect line 2-3, Jean Fraction Lode, M.S. 7271, not monumented.

21.607 Intersect line 1-2, Jean Fraction Lode, M.S. 7271, not monumented.

39.968 The center 1/4 section corner of section 14.

79.888 True point for the 1/4 section corner of sections 14 and 15.

---

From the center E 1/16 section corner of section 14.

N. 0° 01.7' E., on the N-S centerline of the NE 1/4 of section 14.

1.710 Intersect the centerline of San Juan County Road 107, a maintained gravel road, 20 ft. wide, extending N. 19° W. and S. 19° E.

THE SUBDIVISION OF SECTION 14,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

## CHAINS

- 6.450** Intersect the centerline of San Juan County Road 107, a maintained gravel road, 20 ft. wide, extending N. 49° E. and S. 35° W.
- 20.008** Point for the NE 1/16 section corner of section 14, at intersection with the E-W centerline of the NE 1/4.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in ground, magnet at base, with aluminum cap marked:
- T31S R21E  
NE 1/16 S 14  
2009
- Set a steel fence post north of the aluminum post.
- Corner is located in rolling hills, with thick brush and scattered cottonwood trees.
- 40.016** The E 1/16 section corner of sections 11 and 14.
- 
- From the N 1/16 section corner of sections 13 and 14.
- S. 89° 54.8' W.**, on the E-W centerline of the NE 1/4 of section 14.
- 19.973** The NE 1/16 section corner of section 14.
- 39.946** The center N 1/16 section corner of section 14.
- 
- From the E 1/16 section corner of sections 14 and 23.
- N. 0° 01.7' E.**, on the N-S centerline of the SE 1/4 of section 14.
- 16.311** Intersect line 3-4, King Fraction Lode, M.S. 7271, not monumented.
- 39.029** Intersect line 1-2, King Fraction Lode, M.S. 7271, not monumented.
- 40.122** The center E 1/16 section corner of section 14.

The Subdivision of Section 24,  
T. 31 S., R. 21 E., Salt Lake Meridian, Utah.

---

From the true point for the 1/4 section corner of sections 24 and 25.

**N. 0° 09.9' E.**, on the N-S centerline of section 24.

THE SUBDIVISION OF SECTION 24,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

## CHAINS

- 40.015 Point for the center 1/4 section corner of section 24, at intersection with the E-W centerline.

Set a brass tablet, 3 1/4 inches diameter, with a 2 1/2 inch stem, flush with sandstone, in cement bond into a drill hole on sandstone boulder, 8x4x4 ft., marked:

T31S R21E  
C 1/4 S 24  
2009

Set a steel fence post northwest of the brass tablet.

Corner is located amongst large boulders, at the base of a talus slope, north of Sundial Mesa.

- 60.027 Point for the center N 1/16 section corner of section 24, not monumented.
- 79.320 Intersect the centerline of paved Utah State Highway 211, 29 ft. wide, extending N. 40° W. and S. 43° E.
- 80.039 The 1/4 section corner of sections 13 and 24.

From the 1/4 section corner of sections 19 and 24, on the east boundary of the township, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 2 inches above ground, with aluminum cap marked as described in the official field notes of the 2005 resurvey of the west boundary of Township 31 South, Range 22 East, with a mound of stone, 2 ft. base, 1 ft. high, west of corner.

S. 89° 57.8' W., on the E-W centerline of section 24.

- 4.345 Intersect the centerline of paved Utah State Highway 211, 29 ft. wide, extending N. 35° W. and S. 35° E.
- 19.986 Point for the center E 1/16 section corner of section 24.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked:

T31S R21E  
E 1/16  
C ——— C  
S 24  
2009

Set a steel fence post northeast of the aluminum post.

Corner is located on fairly level ground, in an open valley.

THE SUBDIVISION OF SECTION 24,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

## CHAINS

39.972 The center 1/4 section corner of section 24.

59.881 Point for the center W 1/16 section corner of section 24.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with two 60d nails at the base, as a memorial, with aluminum cap marked:

T31S R21E  
W 1/16  
C ————C  
S 24  
2009

Set a steel fence post north of the aluminum post.

Corner is located on fairly level ground in tamarisk trees.

79.790 The 1/4 section corner of sections 23 and 24.

---

From the center E 1/16 section corner of section 24.

N. 0° 03.4' E., on the N-S centerline of the NE 1/4 of section 24.

19.420 Intersect the centerline of paved Utah State Highway 211, 29 ft. wide, extending N. 45° W. and S. 45° E.

20.009 Point for the NE 1/16 section corner of section 24, at intersection with the E-W centerline of the NE 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in ground, magnet at base, with aluminum cap marked:

T31S R21E  
NE 1/16 S 24  
2009

Set a steel fence post south of the aluminum post.

Corner is located on the northeast shoulder of paved Utah State Highway 211.

40.018 The E 1/16 section corner of sections 13 and 24.

---

From the N 1/16 section corner of sections 19 and 24, on the east boundary of the township, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 4 inches above the ground, with aluminum cap marked as described in the official field notes of the 2005 resurvey of the west boundary of Township 31 South, Range 22 East; with a mound of stone, 3 ft. base, 1 1/2 ft. high, west of the aluminum post.

THE SUBDIVISION OF SECTION 24,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

## CHAINS

S. 89° 58.4' W., on the E-W centerline of the NE 1/4 of section 24.

- 19.947 The NW 1/16 section corner of section 24.
- 20.540 Intersect the centerline of paved Utah State Highway 211, 29 ft. wide, extending N. 44° W. and S. 44° E.
- 39.894 The point for the center N 1/16 section corner of section 24.

From the E 1/16 section corner of sections 24 and 25.

N. 0° 12.8' E., on the N-S centerline of the SE 1/4 of section 24.

- 40.014 The center E 1/16 section corner of section 24.

From the W 1/16 section corner of sections 24 and 25.

N. 0° 01.1' E., on the N-S centerline of the SW 1/4 of section 24.

- 40.017 The center W 1/16 section corner of section 24.

The Subdivision of Section 25,  
T. 31 S., R. 21 E., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 25 and 36.

N. 0° 09.8' W., on the N-S centerline of section 25.

- 39.789 Point for the center 1/4 section corner of section 25, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 23 inches in the ground, magnet at base, in a collar of stone, 3 ft. diameter, with aluminum cap marked:

T31S R21E  
C 1/4 S25  
2009

Corner is located on a gentle east slope, with towering, vertical sandstone cliffs to the north, south, and west.

- 59.813 Point for the center N 1/16 section corner of section 25, not monumented.
- 79.837 The true point for the 1/4 section corner of sections 24 and 25.

THE SUBDIVISION OF SECTION 25,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

## CHAINS

From the 1/4 section corner of sections 25 and 30, on the east boundary of the township, monumented with an iron post, 1 inch diameter, firmly set, projecting 2 inches above ground, with brass cap marked as described in the official record of the 1911 survey.

S. 89° 54.4' W., on the E-W centerline of section 25.

20.026 Point for the center E 1/16 section corner of section 25.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, in a collar of stone, 2 ft. diameter, with aluminum cap marked:

T31S R21E  
E 1/16  
C ————— C  
S 25  
2009

Set a steel fence post southwest of the aluminum post.

Corner is located on a small knoll, in a gravel deposit, of an open valley.

40.052 The center 1/4 section corner of section 25.

79.818 The 1/4 section corner of sections 25 and 26.

From the center E 1/16 section corner of section 25.

N. 0° 15.8' W., on the N-S centerline of the NE 1/4 of section 25, at intersection with the E-W centerline of the NE 1/4.

20.015 Point for the NE 1/16 section corner of section 25, at intersection with the E-W centerline of the NE 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked:

T31S R21E  
NE 1/16 S 25  
2009

Set a steel fence post north of the aluminum post.

Corner is located on a gentle east slope, near the base of a talus slope, with sandstone cliffs to the west.

40.029 The E 1/16 section corner of sections 24 and 25.

From the N 1/16 section corner of sections 25 and 30, on the east boundary of the township, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 3 inches above the ground, with aluminum cap marked as described in the official

THE SUBDIVISION OF SECTION 25,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

## CHAINS

field notes of the 2005 resurvey of the west boundary of Township 31 South, Range 22 East.

S. 89° 55.8' W., on the E-W centerline of the NE 1/4 of section 25.

20.099 The NE 1/16 section corner of section 25.

40.089 The point for the center N 1/16 section corner of section 25.

---

From the E 1/16 section corner of sections 25 and 36.

N. 0° 06.2' W., on the N-S centerline of the SE 1/4 of section 25.

39.895 The center E 1/16 section corner of section 25.

---

The Subdivision of Section 26,  
T. 31 S., R. 21 E., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 26 and 35.

N. 0° 22.8' W., on the N-S centerline of section 26.

40.021 Point for the C 1/4 section corner of section 26, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked:

T31S R21E  
C 1/4 S 26  
2009

Set a steel fence post north of the aluminum post.

Corner is located in gently rolling hills, east of a maintained gravel road.

49.100 Intersect the centerline of San Juan County Road 107, a maintained gravel road, 20 ft. wide, extending N. 32° E. and S. 32° W.

59.942 Point for the center N 1/16 section corner of section 26.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked:

THE SUBDIVISION OF SECTION 26,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

## CHAINS

T31S R21E  
C  
N 1/16 | S 26  
C  
2009

Set a steel fence post northeast of the aluminum post.

Corner is located on a moderately steep, east-facing, unconsolidated, rocky slope.

**79.863** The true point for the 1/4 section corner of sections 23 and 26.

---

From the 1/4 section corner of sections 25 and 26.

**N. 89° 43.6' W.**, on the E-W centerline.

**19.903** The center E 1/16 section corner of section 26.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked:

T31S R21E  
E 1/16  
C ————— C  
S 26  
2009

Set a steel fence post north of the aluminum post.

Corner is located on fairly level ground, on the right side of Cottonwood Creek, in tamarisk bushes.

**39.806** The center 1/4 section corner of section 26.

**45.575** Intersect the centerline of San Juan County Road 107, a maintained gravel road, 20 ft. wide, extending N. 32° E. and S. 32° W.

**79.781** The 1/4 section corner of sections 26 and 27.

---

From the center E 1/16 section corner of section 26.

**N. 0° 10.1' W.**, on the N-S centerline of the NE 1/4 of section 26.

**19.981** Point for the NE 1/16 section corner of section 26, at intersection with the E-W centerline of the NE 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked:

THE SUBDIVISION OF SECTION 26,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

## CHAINS

T31S R21E  
NE 1/16 S 26  
2009

Set a steel fence post north of the aluminum post.

Corner is located in a swampy area, in tamarisk and cottonwood trees.

39.962 The E 1/16 section corner of sections 23 and 26.

---

From the point for the N 1/16 section corner of sections 25 and 26.

N. 89° 54.1' W., on the E-W centerline of the NE 1/4 of section 26.

19.975 The NE 1/16 section corner of section 26.

33.080 Intersect the centerline of San Juan County Road 107, a maintained gravel road, 20 ft. wide, extending N. 31° E. and S. 32° W.

39.950 The center N 1/16 section corner of section 26.

---

From the E 1/16 section corner of sections 26 and 35.

N. 0° 07.1' W., on the N-S centerline of the SE 1/4 of section 26.

39.983 The center E 1/16 section corner of section 26.

---

The Subdivision of Section 35,  
T. 31 S., R. 21 E., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 2 and 35, on the south boundary of the township, hereinbefore described.

N. 0° 02.3' W., on the N-S centerline of section 35.

19.893 Point for the center S 1/16 section corner of section 35.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked:

THE SUBDIVISION OF SECTION 35,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

## CHAINS

T31S R21E  
C  
S 1/16 | S 35  
C  
2009

Set a steel fence post north of the aluminum post.

Corner is located on the southwest bank of a dry drainage, course N. 30° W.

- 38.786 Point selected for the witness corner to the center 1/4 section corner of section 35.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked:

WC  
T31S R21E ↑  
C 1/4 S 35 |  
2009

Set a steel fence post north of the aluminum post.

Corner is located on the left bank of Cottonwood Creek.

- 39.786 True point for the center 1/4 section corner of section 35, at intersection with the E-W centerline; falls in Cottonwood Creek, subject to erosion, not monumented.

- 79.833 The 1/4 section corner of sections 26 and 35.

From the 1/4 section corner of sections 35 and 36.

N. 89° 39.4' W., on the E-W centerline of section 35.

- 39.717 The true point for the center 1/4 section corner of section 35.

- 59.842 Point for the center W 1/16 section corner of section 35.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked:

T31S R21E  
W 1/16  
C ——— C  
S 35  
2009

Set a steel fence post north of the aluminum post.

Corner is located on fairly level terrain, near the middle of a valley, bears north and south.

THE SUBDIVISION OF SECTION 35,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

## CHAINS

**66.135** Intersect the centerline of San Juan County Road 107, a maintained gravel road, 20 ft. wide, extending N. 14° E. and S. 14° W.

**79.967** The 1/4 section corner of sections 34 and 35.

---

From the W 1/16 section corner of sections 2 and 35, on the south boundary of the township, hereinbefore described.

**N. 0° 12.5' W.**, on the N-S centerline of the SW 1/4 of section 35.

**19.966** The SW 1/16 section corner of section 35, at intersection with the E-W centerline of the SW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked:

T31S R21E  
SW 1/16 S35  
2009

Set a steel fence post north of the aluminum post.

Corner is located on a gentle east slope, near the middle of a valley, bears north and south.

**39.932** The center W 1/16 section corner of section 35.

---

From the center S 1/16 section corner of section 35.

**N. 89° 51.8' W.**, on the E-W centerline of the SW 1/4 of section 35.

**20.067** The SW 1/16 section corner of section 35.

**31.370** Intersect the centerline of San Juan County Road 107, a maintained gravel road, 20 ft. wide, extending N. 14° E. and S. 14° W.

**40.134** The S 1/16 section corner of sections 34 and 35.

---

From the center W 1/16 section corner of section 35.

**N. 0° 06.0' W.**, on the N-S centerline of the NW 1/4 of section 13.

**33.800** Intersect the centerline of San Juan County Road 107, a maintained gravel road, 20 ft. wide, extending N. 6° E. and S. 6° W.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 7271,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

CHAINS  
39.987

The W 1/16 section corner of sections 26 and 35.

Dependent Resurvey of a Portion of Mineral Survey No. 7271,  
T. 31 S., R. 21 E., Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by  
R.E. Brandon in 1955.

**THE JEAN NO. 1 LODE**

From corner 4, Jean No. 1 Lode, identical with corner 1, Jean No. 2 Lode, monumented with an iron post, 2 inches diameter, firmly set, projecting 16 inches above a mound of stone, 2 ft. base, 1 ft. high, with brass cap marked as described in the official record of the 1955 survey.

Thence, N. 0° 26.0' W., on line 4-1, Jean No. 1 Lode.

11.725

Corner 1, Jean No. 1 Lode, on line 4-1, Jean Fraction Lode, monumented with an iron post, 2 inches diameter, firmly set, projecting 8 inches above a mound of stone, 3 ft. base, 6 inches high, with brass cap marked as described in the official record of the 1955 survey.


From this corner, the center 1/4 section corner of section 14, bears N. 9° 15.7' W., 16.126 chains distance.

**THE JEAN NO. 2 LODE**

From corner 2, Jean No. 2 Lode, identical with corner 3, Jean No. 1 Lode, determined at the center of a mound of stone, 3 ft. base, 2 ft. high; there is no remaining evidence of the 1955 iron post.

At the corner point (center of mound)

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground, magnet at base, in a mound of stone, 3 ft. base, to top of aluminum cap marked:



Set a steel fence post east of the aluminum post.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 7271,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

CHAINS

Corner is located southeast of a wash.

Thence, **S. 0° 34.6' W.**, on line 2-3 Jean No. 2 Lode.

**11.101** Intersect line 3-4, King Fraction Lode of this resurvey.

**11.719** Corner 3, Jean No. 2 Lode, monumented with an iron post, 2 inches diameter, firmly set, projecting 8 inches above a mound of stone, 2 ft. base, 1 ft. high, with brass cap marked as described in the official record of the 1955 survey.

---

Thence, **S. 48° 34.2' W.**, on line 3-4, Jean No. 2 Lode.

**22.661** Corner 4, Jean No. 2 Lode, monumented with an iron post, 2 inches diameter, loosely set, projecting 18 inches above a mound of stone, 2 ft. base, 1 ft. high, with brass cap marked as described in the official record of the 1955 survey.

Rehabilitate mound of stone.

Corner is located on a moderately steep, north-facing hillside.

---

Thence, **N. 0° 23.8' W.**, on line 4-1, Jean No. 2 Lode.

**11.756** Corner 1, Jean No. 2 Lode, identical with Corner 4, Jean No. 1 Lode.

From this corner, the 1/4 section corner of sections 14 and 23, bears **S. 12° 13.0' W.**, **12.876** chains distance.

---

**THE JEAN FRACTION LODE**


From corner 4, of the Jean Fraction Lode, determined at the center of a mound of stone, 3 ft. base, 1 1/2 ft. high; there is no remaining evidence of the 1955 iron post.

At the corner point (center of mound)

Set a brass tablet, 3 1/4 inches diameter, with a 2 1/2 inch stem, flush with sandstone, in cement bond, magnet at base, into a drill hole on sandstone bedrock, marked:

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 7271,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

## CHAINS



Set a steel fence post, in a mound of stone, 2 ft. base, 2 ft. high, southwest of the brass tablet.

Corner is located in an area of exposed, sandstone bedrock.

Thence, **N. 41° 11.5' W.**, on line 4-1, Jean Fraction Lode.


1.457 Intersect corner 1, Jean No. 1 Lode.

---

Thence, **N. 41° 24.6' W.**, continuing on line 4-1, Jean Fraction Lode, beginning new measurement.

1.006 Point selected for the witness corner to Corner No. 1, Jean Fraction Lode.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked:



Set a steel fence post northwest of the aluminum post.

Corner is located in rolling hills, south of a wash.

1.568 The true point for Corner 1, Jean Fraction Lode, at proportionate distance (determined by grant boundary adjustment); there is no remaining evidence of the original 1955 corner. True point falls in a wash, location subject to erosion.

---

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 7271,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

## CHAINS

Thence, **N. 48° 41.7' E.**, on line 1-2, Jean Fraction Lode.


**22.370** Intersect the E-W centerline of section 14, not monumented.

**22.687** Corner 2, Jean Fraction Lode, monumented with an iron post, 2 inches diameter, loosely set, projecting 17 inches above a mound of stone, 3 ft. base, 2 ft. high, with brass cap marked as described in the official record of the 1955 survey.

Remonument to better perpetuate corner.

At the corner point

Set a brass tablet, 3 1/4 inches diameter, 2 1/2 inch stem, in cement bond, magnet at base, into a drill hole on sandstone bedrock, marked:



Raise a mound of stone, 2 ft. base, 2 ft. high, north of brass tablet.

Bury original iron post, 30 inches long, at base of the mound of stone.

Corner is located in rolling terrain, with exposed sandstone bedrock.

---

Thence, **S. 41° 07.6' E.**, on line 2-3, Jean Fraction Lode.

**0.276** Intersect the E-W centerline of section 14.

**1.581** Corner 2, Jean No. 1 Lode, monumented with an iron post, 2 inches diameter, firmly set, projecting 15 inches above an embedded collar of stone, 2 ft. base, with brass cap marked as described in the official record of the 1955 survey.

---

Thence, **S. 40° 56.9' E.**, continuing on line 2-3, Jean Fraction Lode, beginning new measurement.

**0.144** Intersect line 1-2, King Fraction Lode, not monumented.

**1.452** Corner 3, Jean Fraction Lode, monumented with an iron post, 2 inches diameter, firmly set, projecting 15 inches above an embedded collar of stone, 2 ft. base, with brass cap marked as described in the official record of the 1955 survey.

---

DEPENDENT RESURVEY OF MINERAL SURVEY No. 7271,  
T. 31 S., R. 21 E., SALT LAKE MERIDIAN, UTAH.

## CHAINS

## THE KING FRACTION LODE

From corner 1, King Fraction Lode, monumented with an iron post, 2 inches diameter, firmly set, projecting 14 inches above an embedded collar of stone, 2 ft. base, with brass cap marked as described in the official record of the 1955 survey.

From this corner, the center E 1/16 section corner of section 14, bears N. 58°03.2' E., 2.081 chains distance.

Thence, N. 89° 44.5' E., on line 1-2, King Fraction Lode.

- 1.514 Intersect line 2-3, Jean Fraction Lode of this resurvey, not monumented.
- 1.766 Intersect the N-S centerline of the SE 1/4 of section 14, not monumented.
- 3.033 Corner 2, King Fraction Lode, monumented with an iron post, 2 inches diameter, firmly set, projecting 11 inches above the ground, with brass cap marked as described in the official record of the 1955 survey.

Set a steel fence post northwest of the iron post.

Corner is located on the east shoulder of maintained gravel road.

From corner 3, King Fraction Lode, monumented with an iron post, 2 inches diameter, firmly set, projecting 16 inches above an embedded collar of stone, 2 ft. base, with brass cap marked as described in the official record of the 1955 survey.

Thence, S. 89° 42.8' W., on line 3-4, King Fraction Lode.

- 1.390 Intersect the N-S centerline of the SE 1/4 of section 14.
- 1.601 Intersect line 2-3, Jean No. 2 Lode.
- 3.032 Corner 4, King Fraction Lode, monumented with an iron post, 2 inches diameter, firmly set, projecting 15 inches above a mound of stone, 2 ft. base, 6 inches high, with brass cap marked as described in the official record of the 1955 survey.

---

## GENERAL DESCRIPTION

---

The portion of Township 31 South, Range 21 East included in this resurvey lies just east of Canyonlands National Park. Access to the area is by paved Utah State Highway 211, with vehicle access within the project area limited to maintained county and BLM roads that lie generally in the valleys. Access to the mesa tops is difficult due to the high, vertical cliffs that surround them. Indian Creek and Cottonwood Creek flow generally north to south through the resurvey area. The topography ranges from wide, flat valley bottoms, to flat topped mesas surrounded by vertical sandstone cliffs. Steep, talus covered shale and sandstone slopes form at the base of the cliffs.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Phil Freiberg	Survey Technician

---

CERTIFICATE OF SURVEY

I, **Scott A. Burkhardt, Cadastral Surveyor**, hereby certify upon honor that, in pursuance of Special Instructions bearing the date of the **1st day of July, 2009**, I have executed **the dependent resurvey of a portion of the south and east boundaries, a portion of the subdivisional lines, the subdivision of sections 13, 14, 24, 25, 26, and 35, and the dependent resurvey of Mineral Survey No. 7271, in Township 31 South, Range 21 East,**

of the **Salt Lake Meridian, in the State of Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

9/23/10

Date

Scott A. Burkhardt

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the **dependent resurvey of a portion of the south and east boundaries, the dependent resurvey of a portion of the subdivisional lines, the subdivision of sections 13, 14, 24, 25, 26, and 35, and the dependent resurvey of Mineral Survey 7271, in Township 31 South, Range 21 East, of the Salt Lake Meridian, in the state of Utah**, executed by Scott A. Burkhardt, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

December 13, 2010

Date

Daniel W. Webb

(Chief Cadastral Surveyor for Utah)