

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

THE UTAH-COLORADO STATE BOUNDARY LINE,  
FROM MILE POST 18 TO MILE POST 24,

THE

NORTH BOUNDARY, AND THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS

5, 6, 7, 8, 9, 10, 15, 17, 18, 19, 20, AND 21

IN

TOWNSHIP 40 SOUTH, RANGE 26 EAST,

OF THE SALT LAKE MERIDIAN,  
IN THE STATE OF UTAH

EXECUTED BY

*Scott A. Burkhardt*  
*Cadastral Surveyor*

Under Special Instructions dated *May 12, 2009*, approved *May 12, 2009*, which provided for the surveys included under Group Number *1104*, Utah, and Assignment Instructions dated *May 12, 2009*.

Survey commenced *May 13, 2009*  
Survey completed *June 17, 2009*

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

THE UTAH-COLORADO STATE BOUNDARY LINE,  
FROM MILE POST 18 TO MILE POST 24,

THE

NORTH BOUNDARY, AND THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS

5, 6, 7, 8, 9, 10, 15, 17, 18, 19, 20, AND 21

IN

TOWNSHIP 40 SOUTH, RANGE 26 EAST,

OF THE SALT LAKE MERIDIAN,  
IN THE STATE OF UTAH

EXECUTED BY

*Scott A. Burkhardt*  
*Cadastral Surveyor*

Under Special Instructions dated *May 12, 2009*, approved *May 12, 2009*, which provided for the surveys included under Group Number *1104*, Utah, and Assignment Instructions dated *May 12, 2009*.

Survey commenced *May 13, 2009*  
Survey completed *June 17, 2009*

# INDEX DIAGRAM

Township 40 South, Range 26 East, Salt Lake Meridian, Utah

9  <b>6</b>  46	11  47 <b>5</b>  45	12  33 <b>4</b>  32	13  24 <b>3</b> 8  23	MP24
7  43	44 <b>8</b>  42	31 <b>9</b>  31	22 <b>10</b> 7  21	MP23
<b>18</b>  40	41 <b>17</b>  40	30 <b>16</b>  29	20 <b>15</b> 6  19	MP22
<b>19</b>  38	39 <b>20</b>  37	28 <b>21</b>  27	18 <b>22</b> 5  17	MP21
<b>30</b>  36	36 <b>29</b>  35	26 <b>28</b>  26	16 <b>27</b> 4  16	MP20
<b>31</b>	34 <b>32</b>	25 <b>33</b>	14 <b>34</b> 3	MP19
				MP18

Subdivision of Section 5.....	Page 48
Subdivision of Section 6.....	Page 51
Subdivision of Section 7.....	Page 53
Subdivision of Section 8.....	Page 56
Subdivision of Section 9.....	Page 58
Subdivision of Section 10.....	Page 59
Subdivision of Section 15.....	Page 61
Subdivision of Section 17.....	Page 62
Subdivision of Section 18.....	Page 63
Subdivision of Section 19.....	Page 63
Subdivision of Section 20.....	Page 64
Subdivision of Section 21.....	Page 65

## T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

The following field notes describe the dependent resurvey of the Utah-Colorado State Boundary Line, from Mile Post 18 to Mile Post 24, the north boundary, and the subdivisional lines, and the subdivision of sections 5, 6, 7, 8, 9, 10, 15, 17, 18, 19, 20, and 21 in Township 40 South, Range 26 East, of the Salt Lake Meridian, Utah.

## HISTORY OF SURVEYS

Surveyed by		Retraced or Resurveyed by	
<b>UTAH-COLORADO STATE BOUNDARY LINE</b>			
All	R.J. Reeves	1878	
All			A.W. Wilson 1885
All			R.C. Yundt 1942-1944
Portion			R.K. Baugh 2005
<b>SOUTH BOUNDARY (Eighth Standard Parallel South)</b>			
Portion	A.D. Ferron	1884	
All	H.D. Page & J.M. Lentz	1899	H.D. Page & J.M. Lentz 1899
All			R.K. Baugh 2005
<b>WEST BOUNDARY</b>			
All	A.D. Ferron	1884	
All			H.D. Page & J.M. Lentz 1899
All			M.R. Workman 2004
<b>NORTH BOUNDARY</b>			
Portion	A.D. Ferron	1884	
All	H.D. Page & J.M. Lentz	1899	H.D. Page & J.M. Lentz 1899
All			D.B. Miller & J.C. Thoma 1912
<b>SUBDIVISION</b>			
All	H.D. Page & J.M. Lentz	1899	

## T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions for Group No. 1104, Utah, dated May 12, 2009.

The direction of the lines was determined by references to true meridians, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods, dated May 9, 2001, Version 1.0. Trimble model 5800 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for the project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions the based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from GPS static observations, post processed by the National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS): DI3419 p012 MONTICELLOUT2006 CORS ARP, DH6916 MC04 MESA CNTY 04 COOP CORS ARP, AI0265 AZCN AZTEC CORS ARP.

The geographic position of Mile Post 24, on the Utah-Colorado State Boundary Line, as determined by direct RTK methods from the National Geodetic Survey OPUS solutions is as follows:

**Latitude:** 37° 20' 46.202" N.,  
**Longitude:** 109° 02' 44.522" W., N.A.D. 1983,  
Network Accuracy = 0.20 meter, 95% confidence circle.

The geographic position of Mile Post 18, on the Utah-Colorado State Boundary Line, as determined by direct RTK methods from the National Geodetic Survey OPUS solutions is as follows:

**Latitude:** 37° 15' 35.127" N.,  
**Longitude:** 109° 02' 44.074" W., N.A.D. 1983,  
Network Accuracy = 0.20 meter, 95% confidence circle.

All monuments set in this survey and resurvey bear the Navajo Nation seal, unless otherwise noted.

DEPENDENT RESURVEY OF THE UTAH-COLORADO STATE BOUNDARY LINE,  
 FROM MILE POST 18 TO MILE POST 24,  
 T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

---

Dependent Resurvey of the Utah-Colorado State Boundary Line,  
 from Mile Post 18 to Mile Post 24,  
 T. 40 S., R. 26 E., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by R.J. Reeves in 1878,  
 the Resurvey Executed by A.W. Wilson in 1885, R.C. Yundt in  
 1942-1944, and R.K. Baugh in 2005

---

Beginning at Mile Post 18, on the Utah-Colorado State Boundary Line, in T. 40 S., R. 26 E., monumented with an iron post, 3 inches diameter, firmly set, flush with the top of a mound of stone, 4 feet base, 28 inches high, with brass cap marked as described in the official record of the 2005 retracement.

From this corner, the closing corner of Townships 40 South and 41 South, Range 26 East, on the Eighth Standard Parallel South, at intersection with the Utah-Colorado State Boundary Line, bears S. 0° 11.1' E, 6.864 chains distance, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 6 inches above the ground, witnessed by a mound of stone, 3 feet base, 2 feet high, west of corner, with brass cap marked as described in the official record of the 2005 resurvey.

N. 0° 15.4' W., on the 19th Mile.

**33.166** Point for the 1/4 section corner of section 34 only.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with magnet at the base, in a collar of stone, 2 feet diameter, with brass cap marked:

T40S R26E	
1/4 S 34	
2009	

Set a steel fence post north of stainless steel post.

Corner is located on gently west-sloping mesa top.

**46.905** Intersect the centerline of San Juan County Road 407, a gravel road, 20 feet wide, extending N. 40° E. and S. 40° W.

**73.196** True point for the closing corner of sections 27 and 34 only at proportionate distance; there is no remaining evidence of the original closing corner. Point is located on a steep, unconsolidated hillside, and is impracticable to establish a permanent monument.



DEPENDENT RESURVEY OF THE UTAH-COLORADO STATE BOUNDARY LINE,  
 FROM MILE POST 18 TO MILE POST 24,  
 T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

26.520 Intersect the centerline of San Juan County Road 407, a gravel road, 20 feet wide, extending N. 65° E. and S. 65° W.

33.854 Point for the 1/4 section corner of section 22 only.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 21 inches in the ground, to bedrock, with magnet at the base, in a mound of stone, 4 feet base, to brass cap marked:

T40S R26E	
1/4 S 22	
2009	

Set a steel fence post north of stainless steel post.

Corner is located on the edge of a mesa top, on fairly level, rocky ground.

73.843 Point for the closing corner of sections 15 and 22 only, at proportionate distance; nearby, a stone, 18x16x6 inches, faintly marked "CC", laying loose on the ground (Record: sandstone, 20x18x8, marked "CC" on west face, in a mound of stone.) There is no method to determine the original location of the corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at the base, in a mound of stone, 4 feet base, to brass cap marked:

T40S	
R26E	
S 15 C	
-----	
S 22 C	
2009	

Place original stone at the base of mound of stone.

Set a steel fence post north of stainless steel post.

From the corner, a barbed-wire fence, 6-strand, extending north-south, bears West, 5 links distance.

Corner is located on a gentle, west-sloping, rocky mesa top.

78.760 The 21st Mile Post, on the Utah-Colorado State Boundary Line, monumented with an iron post, 3 inches diameter, loosely set, projecting 15 inches above a mound of stone, 3 feet base, 12 inches high, with brass cap marked as described in the official record of the 1942-1944 resurvey.

DEPENDENT RESURVEY OF THE UTAH-COLORADO STATE BOUNDARY LINE,  
 FROM MILE POST 18 TO MILE POST 24,  
 T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Rebuild mound of stone, 3 feet base, to cap.

N. 0° 12.8' E., on the 22nd Mile.

35.227 Point for the 1/4 section corner of section 15 only.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, with brass cap marked:

T40S	
R26E	
1/4 S 15	
2009	

Set a steel fence post north of stainless steel post.

Corner is located on a fairly level mesa top, with desert grasses.

From the corner, a barbed-wire fence, 6-strand, extending north-south, bears East, 0.058 chain distance.

75.372 Point for the closing corner of sections 10 and 15 only, at intersection with the Utah-Colorado State Boundary Line.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with magnet at the base, in a collar of stone, 3 feet diameter, with brass cap marked:

T40S	
R26E	
S 10	C
S 15	C
2009	

Set a steel fence post north of stainless steel post.

Corner is located in rolling hills, sloping west toward McElmo Creek.

From which the original 1899 closing corner bears S. 89° 36.9' W., 0.141 chain distance, monumented with a sandstone, 19x11x7 inches, firmly set, projecting 15 inches above the ground, in an embedded collar of stone, 2 feet diameter, marked "E" on east face, undecipherable markings on west face, and 2 grooves on north edge (Record: a sandstone,

DEPENDENT RESURVEY OF THE UTAH-COLORADO STATE BOUNDARY LINE,  
 FROM MILE POST 18 TO MILE POST 24,  
 T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

16x8x6 inches, marked "CC U" on west face and "C" on east face, 4 grooves on south face and 2 grooves on north face). Add markings "AM" to stone and bury in place.

- 80.058 The 22nd Mile Post, on the Utah-Colorado State Boundary Line, monumented with an iron post, 3 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap marked as described in the official record of the 1942-1944 resurvey.

Rebuild mound of stone to 2 feet base, to cap.

---

N. 0° 01.3' E., on the 23rd Mile.

- 35.178 Point for the 1/4 section corner of section 10 only.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, with brass cap marked:

T40S |  
 R26E |  
 1/4 S 10 |  
 2009

Set a steel fence post north of stainless steel post.

Corner is located on the floodplain of McElmo Creek, with sage brush and tamarisk trees.

- 65.460 Intersect the centerline of San Juan County Road 402, a paved road, 30 feet wide, extending N. 84° E. and S. 84° W.

- 75.042 The closing corner of sections 3 and 10 only, at the intersection with the Utah-Colorado State Boundary Line, determined at the center of an embedded mound of stone, 2 feet base, 1 foot high, no marked stone found (Record: a sandstone, 18x7x6 inches, marked "CC U" on west face, "C" on east face, 5 grooves on south face, and 1 groove on north face, with a mound of stone, 2 feet base, 1 1/2 feet high, west of corner). The mound of stone is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 8 inches in the ground, to bedrock, with magnet at the base, in a mound of stone, 4 feet base, to brass cap marked:

DEPENDENT RESURVEY OF THE UTAH-COLORADO STATE BOUNDARY LINE,  
 FROM MILE POST 18 TO MILE POST 24,  
 T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T40S	R26E	
	S 3	
CC		
	S 10	

2009

Set a steel fence post northwest of stainless steel post.

Corner is located in rolling hills, with rocky ground.

- 79.625** The 23rd Mile Post, on the Utah-Colorado State Boundary Line, monumented with an iron post, 3 inches diameter, firmly set, projecting 13 inches above the ground, with brass cap marked as described in the official record of the 1942-1944 resurvey.

Rebuild mound of stone, 3 feet base, to cap.

**N. 0° 12.4' E.**, on the 24th Mile.

- 35.371** Point for the 1/4 section corner of section 3 only.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with magnet at the base, in a collar of stone, 3 feet diameter, to brass cap marked:

T40S	
R26E	
1/4	S 3

2009

Set a steel fence post north of stainless steel post.

Corner is located on east side of a saddle of a ridge, on an east-facing slope.

- 75.445** Point for the closing corner of Townships 39 South and 40 South, Range 26 East, at intersection of the Utah-Colorado State Boundary Line.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground, to bedrock, with magnet at the base, in a mound of stone, 3 feet base, to brass cap marked:

DEPENDENT RESURVEY OF THE UTAH-COLORADO STATE BOUNDARY LINE,  
 FROM MILE POST 18 TO MILE POST 24,  
 T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

	T39S	
	R26E	
	S 34	
CC	—	
	S 3	
	T40S	

2009

Corner is located on west edge of north-south trending mesa top.

From which the original 1899 closing corner bears  
 S. 89° 58.3' W., 0.461 chain distance, determined at the center  
 of an embedded mound of stone, 2 feet base, 1 1/2 feet high, no  
 marked stone found (Record: sandstone, 18x7x6 inches, marked "CC  
 U 26E" with 6 grooves on west face, "C" on east face, "40S" with  
 6 grooves on south face, and "39S" with 6 grooves on north face,  
 with a mound of stone, 2 feet base, 1 1/2 feet high, west of  
 corner). This mound is accepted as the best available evidence  
 of the original corner position. This point will now function as  
 an AM, not monumented.

79.026

The 24th Mile Post, on the Utah-Colorado State Boundary Line,  
 monumented with an iron post, 1 inch diameter, firmly set in  
 hole drilled in exposed sandstone bedrock, projecting 17 inches  
 above the rock, with brass cap marked as described in the  
 official record of the 1942-1944 resurvey.

---

Dependent Resurvey of the North Boundary,  
 T. 40 S., R. 26 E., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by A.D. Ferron in 1884,  
 the Survey and Resurvey Executed by H.D. Page & J.M. Lentz in  
 1899, D.B. Miller & J.C. Thoma in 1912, and M.R. Workman in 2004

---

From the corner of Townships 39 and 40 South, Ranges 25 and 26  
 East, monumented with a stainless steel post, 2 1/2 inches  
 diameter, flush with the ground, with a mound of stone, 3 feet  
 base, 1 foot high, west of corner, with brass cap marked as  
 described in the official record of the 2004 resurvey of the  
 East boundary of T. 40 S. R. 25 E.

Set a steel fence post north of stainless steel post.

**N. 89° 24.5' E.**, between sections 6 and 31, on the North  
 boundary of the township.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS  
40.114

The 1/4 section corner of sections 6 and 31, monumented with a sandstone, 16x9x3 inches, faintly marked 1/4 S, loosely set in an embedded collar of stone, 2 feet (Record: sandstone, 16x7x4 inches, marked 1/4 S 31 on north face, with a mound of stone, 2 feet base, 1 1/2 feet high, north of corner).

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, in a collar of stone, 2 feet diameter, with magnet at the base, with brass cap marked:

T39S R26E  
S 31  
1/4 ———  
S 6  
T40S  
2009

Bury marked stone next to corner.

Set a steel fence post north of stainless steel post.

From the corner, a barbed-wire fence, 5-strand, extending north-south, bears West, 0.115 chains distance.

Corner is located in rolling, sandy hills.

---

S. 89° 36.8' E., beginning new measurement.

19.994

Point for the east 1/16 section corner of sections 6 and 31.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, with brass cap marked:

T39S R26E  
S 31  
E 1/16 ———  
S 6  
T40S  
2009

Set a steel fence post north of stainless steel post.

Corner is located on fairly level ground, in a valley bottom..

39.988

The corner of sections 5, 6, 31, and 32, monumented with a sandstone, 19x9x6 inches, with 5 faint grooves on east face, loosely set in an embedded collar of stone, 2 feet diameter (Record: sandstone 16x10x4 inches, marked one notch on west edge, 5 notches on east edge, with a mound of stone, 2 feet

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

base, 1 1/2 feet high, west of corner), with old wooden juniper post east of corner.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at the base, in a mound of stone, 3 feet base, to brass cap marked:

T39S	R26E
S 31	S 32
S 6	S 5
T40S	
2009	

Bury marked stone next to stainless steel post.

Set a steel fence post north of stainless steel post.

Corner is located in broad drainage, on gentle northwest slope.

**N. 89° 59.0' E.**, between sections 5 and 32, on the North boundary of the township.

**24.260** Intersect the centerline of San Juan County Road 418, a gravel road, 20 feet wide, extending N. 12° E. and S. 12° W.

**39.855** The 1/4 section corner of sections 5 and 32, monumented with a sandstone, 14x11x6 inches, marked 1/4 on north face, loosely set, in a mound of stone, 2 feet base, 6 inches high (Record: sandstone, 18x8x3 inches, marked 1/4 S32 on north face, with a mound of stone, 2 feet base, 1 1/2 feet high, north of corner), with an old wooden juniper post east of corner.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with magnet at the base, in a collar of stone, 2 feet diameter, with brass cap marked:

T39S	R26E
	S 32
1/4	———
	S 5
T40S	
2009	

Bury marked stone next to corner.

Set a steel fence post north of stainless steel post.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located on fairly level mesa top, with sage brush and desert grasses.

---

N. 89° 58.4' E., beginning new measurement.

- 40.034 The corner of sections 4, 5, 32, and 33, determined at the center of an embedded collar of stone, 2 feet diameter; there is no remaining evidence of the 1899 marked stone (Record: sandstone 14x10x4 inches, marked two notches on west edge, 4 notches on east edge, with a mound of stone, 2 feet base, 1 1/2 feet high, west of corner). This collar of stone is accepted as the best available evidence of the original position of the corner.

At the corner point (center of collar)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with magnet at the base, in a collar of stone, 2 feet diameter, to brass cap marked:

T39S	R26E
S 32	S 33
S 5	S 4
T40S 2009	

Set a steel fence post north of stainless steel post.

Corner is located on a northeast-sloping mesa top, southwest of high-voltage transmission lines.

---

S. 89° 59.4' E., between sections 4 and 33, on the North boundary of the township.

- 40.061 The 1/4 section corner of sections 4 and 33, monumented with a sandstone, 26x10x3 inches, marked 1/4 on north face, loosely set, projecting 22 inches above the ground, in an embedded collar of stone, 2 feet base (Record: sandstone, 24x10x3 inches, marked 1/4 S33 on north face, with a mound of stone, 2 feet base, 1 1/2 feet high, north of corner).

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 19 inches in the ground, with magnet at the base, in a collar of stone, 2 feet diameter, with brass cap marked:

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T39S R26E  
S 33  
1/4 ———  
S 4  
T40S  
2009

Bury marked stone next to corner.

Set a steel fence post north of stainless steel post.

Corner is located on gentle south-sloping mesa top.


**N. 89° 56.6' E.**, beginning new measurement.

**39.871** The true point for the corner of sections 3, 4, 33, and 34, using record bearing & distance from the 1889 witness corner; point falls on the south edge of a wash, and is subject to erosion.

From which the 1889 witness corner to the corner of sections 3, 4, 33, and 34, bears South, 0.150 chains distance, monumented with a sandstone, 15x12x6 inches, marked "WC" on northeast face, 3 notches on east face, 2 notches on west edge, loosely set, projecting 12 inches above the ground, with an embedded mound of stone, 3 feet diameter, west of corner (Record: a sandstone, 14x12x4 inches, marked "WC" on northeast face, 3 notches on the east edge, 3 notches on the west edge, with a mound of stone, 2 feet base, 1 1/2 feet high west of corner).

At the witness corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground, with magnet at the base, in a mound of stone, 3 feet base, to brass cap marked:



Corner is located on the south edge of a wash, 0.018 chain wide, course S. 30° E.

**S. 89° 58.1' E.**, between sections 3 and 34, on the North boundary of the township.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

**39.976** The 1/4 section corner of sections 3 and 34, monumented with a sandstone, 18x11x10 inches, marked 1/4 on north face, firmly set, projecting 8 inches above the ground (Record: a sandstone, 16x6x6 inches, marked 1/4 S on north face, with a mound of stone, 2 feet base, 1 1/2 feet high north of corner).

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 8 inches in the ground, to bedrock, with magnet at the base, in a mound of stone, 3 feet base, to cap, with brass cap marked:

T39S R26E  
S 34  
1/4 ———  
S 3  
T40S  
2009

Bury marked stone next to corner.

Corner is located in an open valley, with sparse vegetation.

---

N. 89° 58.3' E., beginning new measurement.

**19.727** The point for the amended 1899 closing corner, hereinbefore described.

**20.188** The closing corner of sections 3 and 34 only, on the North boundary of the township, at intersection with the Utah-Colorado State Boundary Line, hereinbefore described.

---

Dependent Resurvey of the Subdivisional Lines,  
T. 40 S., R. 26 E., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
H.D. Page & J.M. Lentz in 1899

---

From the standard corner of sections 33 and 34 only, on the South boundary of the township (Eighth Standard Parallel South), monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, flush with the ground, with brass cap marked as described in the official record of the 2005 resurvey of T. 41 S., R. 26 E.

N. 0° 02.3' E., between sections 33 and 34.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

10.710

Intersect the centerline of San Juan County Road 407, a gravel road, 20 feet wide, extending N. 57° E. and S. 57° W.

39.917

The 1/4 section corner of sections 33 and 34, determined at a point immediately east of an embedded mound of stone, 3 feet base, 1 foot high, on a boulder, 16x12x6 feet, marked "1/4" on west face (Record: a boulder, 16x8x5 feet, marked "1/4 S 33" on west face, with a cross "+" on boulder at true point, with a mound of stone, 2 1/2 feet base, 1 1/2 feet high west of corner). There is no remaining evidence of the cross "+" on the boulder.

At the corner point (immediately east of the mound of stone and east of "1/4" on face of boulder)

Set a brass tablet, 3 1/4 inches diameter, 2 1/2 inch stem, flush with sandstone boulder, in cement bond, with magnet at the base, in a hole drilled in the sandstone boulder marked:

T40S	R26E
	1/4
S 33	S 34
	2009

Set a steel fence post west of brass tablet, in the original mound of stone, rebuilt to 2 feet base, 2 1/2 feet high.

Corner is located on top of the boulder, near the west edge.

N. 0° 06.3' W., beginning new measurement.

39.826

The corner of sections 27, 28, 33, and 34, monumented with a sandstone, 19x14x4 inches, marked with 3 notches on the east edge, 1 notch on south edge, firmly set, projecting 12 inches above ground (Record: a sandstone, 18x7x6 inches, with a mound of stone, 2 feet base, 1 1/2 feet high, west of corner).

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, to bedrock, in a collar of stone, 2 feet diameter, with magnet at the base, with brass cap marked:

T40S	R26E
S 28	S 27
S 33	S 34
	2009

Bury marked stone in collar.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a steel fence post north of stainless steel post.

Corner is located on a gently rolling valley floor, with sparse vegetation.

N. 89° 47.8' E., between sections 27 and 34.

40.168 Point for the 1/4 section corner of sections 27 and 34, at proportionate distance; there is no remaining evidence of the 1899 sandstone or mound of stone.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, in a collar of stone, 2 feet diameter, with magnet at the base, with brass cap marked:

T40S R26E  
S 27  
1/4 ———  
S 34  
2009

Set a steel fence post east of stainless steel post.

Corner is located in rolling terrain, in an open valley.

60.545 Point selected for the witness corner to the closing corner of sections 27 and 34 only.

Set a brass tablet, 3 1/4 inches diameter, 2 1/2 inch stem, flush with bedrock, in cement bond, in a hole drilled in the sandstone bedrock marked:

WC  
T40S R26E  
S 27 |  
CC ———> |  
S 34 |  
2009

Set a steel fence post northeast of brass tablet.

Corner is located on a sandstone outcrop, on a steep, southwest-facing slope.

60.784 The true point for the closing corner of sections 27 and 34 only, on the Utah-Colorado State Boundary Line, hereinbefore described.

From the corner of sections 27, 28, 33, and 34.


N. 0° 00.6' E., between sections 27 and 28.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS  
40.075

Point for the 1/4 section corner of sections 27 and 28, at proportionate distance; there is no remaining evidence of the 1899 corner.

Set a brass tablet, 3 1/4 inches diameter, 2 1/2 inch stem, flush with bedrock, in cement bond, in a hole drilled in the sandstone bedrock marked:



Raise a mound of stone, 2 feet base, 2 feet high.


Set a steel fence post, west of brass tablet.

Corner is located in a pipeline corridor, in highly disturbed ground, above a tank battery that lies to the southeast.

79.436

Point selected for the witness corner to the corner of sections 21, 22, 27, and 28.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with magnet at the base, with brass cap marked:



Set a steel fence post north of stainless steel post.

Corner is located on a moderately-steep, north-facing hillside, above a ravine extending east-west.

80.150

The true point for the corner of sections 21, 22, 27, and 28, at proportionate distance; there is no remaining evidence of the 1899 corner. The point is located on a steep, unconsolidated slope, and is impracticable to establish a permanent monument.

N. 89° 46.6' E., between sections 22 and 27.

39.944

The 1/4 section corner of sections 22 and 27, monumented with a cross "+" on a boulder, 15x4x2 feet, marked 1/4 S22 on north face; with an embedded mound of stone, 2 feet diameter, to the north.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

At the corner point (cross "+" on boulder)

Set a brass tablet, 3 1/4 inches diameter, 2 1/2 inch stem,  
flush with bedrock, in cement bond, with magnet at the base, in  
a hole drilled in the sandstone bedrock marked:

T40S R26E  
S 22  
1/4 ———  
S 27  
2009

Set a steel fence post south of brass tablet.

Corner is located on a moderately-steep, boulder-strewn, east-  
facing slope, above a drainage, course South.

S. 89° 50.5' E., beginning new measurement.

20.117 Point selected for the witness corner to the closing corner of  
sections 22 and 27 only.

Set a brass tablet, 3 1/4 inches diameter, 2 1/2 inch stem,  
flush with bedrock, in cement bond, with magnet at the base, in  
a hole drilled in the sandstone bedrock marked:

WC  
T40S  
R26E  
S 22  
CC → |  
S 27  
2009

Raise a mound of stone, 2 feet base, 2 feet high, north of  
corner.

Corner is located on a south-facing slope covered with large  
boulders.

20.344 The true point for the closing corner of sections 22 and 27  
only, on the Utah-Colorado State Boundary Line, hereinbefore  
described.

From the point for the corner of sections 21, 22, 27, and 28.

N. 0° 05.2' E., between sections 21 and 22.

40.075 The 1/4 section corner of sections 21 and 22, monumented with a  
sandstone, 16x13x6, firmly set, projecting 7 inches above the

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

ground, marked 1/4 on west face, with a mound of stone, 2 feet base, 1 foot high, west of corner (Record: a sandstone, 14x12x4 inches, marked 1/4 S on west face, with a mound of stone, 2 feet base, 1 1/2 feet high, west of corner).

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, in a mound of stone, 4 feet base, to cap, with magnet at the base, with brass cap marked:

T40S	R26E
1/4	
S 21	S 22
2009	

Bury marked stone at the base of mound of stone.

Set a steel fence post north of stainless steel post.

Corner is located in a drainage, course North, in rocky ground.

N. 0° 00.1' W., beginning new measurement.

**34.075** Intersect the centerline of San Juan County Road 407, a gravel road, 20 feet wide, extending N. 83° W. and S. 83° E.

**40.074** Point for the corner of sections 15, 16, 21, and 22, at proportionate distance; there is no remaining evidence of the 1899 corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, with brass cap marked:

T40S	R26E
S 16	S 15
S 21	S 22
2009	

Set a steel fence post north of stainless steel post.

Corner is located on the left bank of McElmo Creek, in thick tamarisk.

S. 89° 55.8' E., between sections 15 and 22.

**39.876** Point for the 1/4 section corner of sections 15 and 22, at proportionate distance; there is no remaining evidence of the 1899 corner.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground, to bedrock, with magnet at the base, in a mound of stone, 4 feet base, to brass cap marked:

T40S R26E  
S 15  
1/4 ———  
S 22  
2009

Set a steel fence post east of stainless steel post.

Corner is located on a steep, eroded hillside, with large, loose boulders.

- 59.873 The closing corner of sections 15 and 22 only, on the Utah-Colorado State Boundary Line, hereinbefore described.

From the corner of sections 15, 16, 21, and 22.

N. 0° 02.1' W., between sections 15 and 16.

- 40.074 The 1/4 section corner of sections 15 and 16, monumented with a sandstone, 16x15x5 inches, marked 1/4 on west face, loosely set, projecting 13 inches above a mound of stone, 3 feet base, 1 foot high (Record: a sandstone, 16x6x4 inches, marked 1/4 S on west face, with a mound of stone, 2 feet base, 1 1/2 feet high, west of corner).

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at the base, in a mound of stone, 3 feet base, to brass cap marked:

T40S R26E  
1/4  
S 16 | S 15  
2009

Bury marked stone at the base of mound of stone.

Set a steel fence post northwest of stainless steel post.

Corner is located near a mesa top, on a gentle, west-facing rocky slope, with no vegetation.

N. 0° 06.2' E., beginning new measurement.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

30.600

Intersect the centerline of San Juan County Road 402, a paved road, 30 feet wide, extending N. 72° E. and S. 72° W.

39.737

The corner of sections 9, 10, 15, and 16, monumented with a sandstone, 24x12x10 inches, marked with 4 notches on south edge, 3 notches on east edge, in a mound of stone, 3 feet base, 1 foot high (Record: a sandstone, 24x10x7 inches, with a mound of stone, 2 feet base, 1 1/2 feet high, west of corner).

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with magnet at the base, in a mound of stone, 4 feet base, to brass cap marked:

T40S	R26E
S 9	S 10
S 16	S 15
2009	

Bury marked stone at the base of mound of stone.

Set a steel fence post north of stainless steel post.

Corner is located on east-facing, moderately-steep, rocky slope.

N. 89° 36.9' E., between sections 10 and 15.

13.695

Intersect the centerline of San Juan County Road 402, a paved road, 30 feet wide, extending N. 23° E. and S. 23° W.

19.928

Point for the west 1/16 section corner of sections 10 and 15.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, with brass cap marked:

T40S	R26E
	S 10
W 1/16	_____
	S 15
2009	

Set a steel fence post north of stainless steel post.

Corner is located on the west side of a small drainage, course N. 40° E.

39.856

Point for the 1/4 section corner of sections 10 and 15, at proportionate distance. Laying loose on the ground, a sandstone, 26x15x3 inches, marked 1/4, no method to determine original location of stone (Record: a sandstone,

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

18x10x4 inches, marked 1/4 S, with a mound of stone, 2 feet base, 1 1/2 feet high, north of corner).

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at the base, in a mound of stone, 3 feet base, to brass cap marked:

T40S R26E  
S 10  
1/4 ———  
S 15  
2009

Bury marked stone in the base of mound of stone.

Set a steel fence post northeast of stainless steel post.

Corner is located in a shallow drainage, course S. 40° W.

59.934 The original closing corner of sections 10 and 15, from the 1899 survey. Amended monument, hereinbefore described.

60.075 The closing corner of sections 10 and 15 only, on the Utah-Colorado State Boundary Line, hereinbefore described.

From the corner of sections 9, 10, 15, and 16.

N. 0° 07.1' E., between sections 9 and 10.

40.132 The 1/4 section corner of sections 9 and 10, monumented with a cross "+" on sandstone bedrock, with the marking "1/4" to the west, and a collar of stone, 2 feet diameter, to the west (Record: the marking "1/4 S" and a mound of stone, 2 feet base, 1 1/2 feet high).

At the corner point (cross "+" on bedrock)

Set a brass tablet, 3 1/4 inches diameter, 2 1/2 inch stem, flush with bedrock, in cement bond, with magnet at the base, in a hole drilled in the sandstone bedrock marked:

T40S R26E  
1/4  
S 9 | S 10  
2009

Raise a mound of stone, 2 feet base, 1 foot high, west of corner.

Set a steel fence post northwest of brass tablet.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Corner is located on gentle, west-sloping, exposed sandstone bedrock.

---

N. 0° 03.8' E., beginning new measurement.

39.966

The corner of sections 3, 4, 9, and 10, monumented with a sandstone, 19x12x4 inches, marked with 2 notches on east edge, loosely set, projecting 16 inches above a collar of stone, 2 feet (Record: 14x12x5 inches, with 5 notches on the south edge and 3 notches on east edge, with a mound of stone, 2 feet base, 1 1/2 feet high to west of corner).

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 8 inches in the ground, to bedrock, in a mound of stone, 3 feet base, to cap, with magnet at the base, with brass cap marked:

T40S	R26E
S 4	S 3
S 9	S 10
2009	

from which the original bearing trees

A juniper, 12 inches diameter, bears S. 63° 58' E., 49.6 links distance, marked T40 R26 BT (Record: S. 63° 30' E., 50 links distance, marked BT T40S R26E S10).

A juniper, 24 inches diameter, bears N. 53° 06' E., 54.6 links distance, marked BT (Record: S. 2° 31' W., 0.55 chains distance, marked BT T40S R26E S9).

Set a steel fence post north of stainless steel post.

Corner is located on a rocky mesa top, with thin soil, with scattered juniper trees.

---

N. 89° 58.1' E., between sections 3 and 10.

19.992

Point for the west 1/16 section corner of sections 3 and 10.

Set a brass tablet, 3 1/4 inches diameter, 2 1/2 inch stem, flush with bedrock, in cement bond, with magnet at the base, in a hole drilled in the sandstone bedrock marked:

T40S	R26E
	S 3
W 1/16	_____
	S 10
2009	

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a steel fence post west of brass tablet.

Corner is located on a mesa top, immediately north of a multi-trunked juniper tree.

- 39.984 Point for the 1/4 section corner of sections 3 and 10, at proportionate distance; there is no remaining evidence of the 1899 corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 5 inches in the ground, to bedrock, with magnet at the base, in a mound of stone, 4 feet base, to brass cap marked:

T40S R26E  
S 3  
1/4 ———  
S 10  
2009

Set a steel fence post west of stainless steel post.

Corner is located on a bench, with a high mesa to the west and a drop-off to the east.

- 59.979 The closing corner of sections 3 and 10 only, on the Utah-Colorado State Boundary Line, hereinbefore described.

From the corner of sections 3, 4, 9, and 10.

N. 0° 07.6' E., between sections 3 and 4.

- 40.042 The 1/4 section corner of sections 3 and 4, monumented with a sandstone, 22x12x6 inches, marked 1/4 on west face, loosely set, projecting 15 inches above the ground (Record: a sandstone, 14x10x5 inches, marked 1/4 S, with a witness mound of stone, 2 feet base, 1 1/2 feet high, west of corner).

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground, to bedrock, with magnet at the base, in a mound of stone, 4 feet base, to brass cap marked:

T40S R26E  
1/4  
S 4 | S 3  
2009

Corner is located on the steep, south face of a ravine, course East.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

---

N. 0° 00.9' W., beginning new measurement.

- 39.882 The witness corner to the corner of sections 3, 4, 33, and 34, on the North boundary of the township, hereinbefore described.
- 40.032 The true point for the corner of sections 3, 4, 33, and 34, on the North boundary of the township, hereinbefore described.

---

From the standard corner of sections 32 and 33 only, on the South boundary of the township (Eighth Standard Parallel South), monumented with a stainless steel post, 2 1/2 inches diameter, flush with the ground, with brass cap marked as described in the official record of the 2005 resurvey of T. 41 S., R. 26 E.

N. 0° 00.8' W., between sections 32 and 33.

- 40.040 Point for the 1/4 section corner of sections 32 and 33, at proportionate distance; there is no remaining evidence of the 1899 corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with magnet at the base, in a mound of stone, 4 feet base, to brass cap marked:

T40S	R26E
	1/4
S 32	S 33
	2009

Set a steel fence post north of stainless steel post.

Corner is located on a moderately-steep, east-facing, rocky slope, with desert grasses.

- 80.080 The corner of sections 28, 29, 32, and 33, monumented with a sandstone, 14x10x3 inches, no visible markings, lying loose on an embedded mound of stone, 2 feet base, 1 foot high (Record: a sandstone, 16x10x5 inches, marked with 1 notch on the south edge, 4 notches on the east edge, with a mound of stone, 2 feet base, 1 1/2 feet high, west of corner). The center of the embedded mound of stone is accepted as the best available evidence of the original corner position.

At the corner point (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with magnet at the base, in a mound of stone, 2 feet base, to cap, with brass cap marked:

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T40S	R26E
S 29	S 28
S 32	S 33
2009	

Bury marked stone at the base of mound of stone.

Set a steel fence post north of stainless steel post.

Corner is located on a rocky, fairly level mesa top, with sparse vegetation.

From the corner of sections 27, 28, 33, and 34.

N. 89° 47.1' W., between sections 28 and 33.

**39.991** Point for the 1/4 section corner of sections 28 and 33, at proportionate distance; there is no remaining evidence of the 1899 corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground, to bedrock, with magnet at the base, in a mound of stone, 4 feet base, to brass cap marked:

T40S	R26E
	S 28
1/4	—
	S 33
2009	

Set a steel fence post north of stainless steel post.

Corner is located on the northwest side of a drainage, in rocky ground.

**79.982** The corner of sections 28, 29, 32, and 33.

N. 0° 03.0' E., between sections 28 and 29.


**39.891** The 1/4 section corner of sections 28 and 29, monumented with a sandstone, 22x9x6 inches, marked 1/4 on the west face, firmly set, projecting 15 inches above the ground, with an embedded accessory mound of stone, 2 feet diameter, west of corner (Record: a sandstone, 10x8x6 inches, marked 1/4 S, with a mound of stone, 2 feet base, 1 1/2 feet high, west of corner).

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground, with magnet at the base, in a mound of stone, 3 feet base, to brass cap marked:

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS



Bury marked stone at the base of mound of stone.

Set a steel fence post north of stainless steel post.

Corner is located on rocky ground, on a gentle, southwest-sloping hill.

---

N. 0° 02.7' W., beginning new measurement.

**40.507** True point for the corner of sections 20, 21, 28, and 29, at proportionate distance; there is no remaining evidence of the 1899 corner. Point falls in a deep arroyo, location subject to erosion; impracticable to set monument here.

From which the witness corner to the corner of sections 20, 21, 28, and 29 bears N.1°44.6'W., 0.751 chain distance, hereinafter described.


---

From the corner of sections 21, 22, 27, and 28.

N. 89° 36.4' W., between sections 21 and 28.

**39.990** Point for the 1/4 section corner of sections 21 and 28, at proportionate distance; there is no remaining evidence of the 1899 corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground, with magnet at the base, in a mound of stone, 3 feet base, to brass cap marked:



Set a steel fence post north of stainless steel post.

Corner is located on a moderately-steep, boulder-covered west-facing slope, above McElmo Creek.

**79.980** The true point for the corner of sections 20, 21, 28, and 29.

---


DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

N. 1° 44.6' W., between sections 20 and 21.

0.751 Point selected for the witness corner of sections 20, 21, 28, and 29.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, in a collar of stone, 2 feet diameter, with brass cap marked:




Set a steel fence post north of stainless steel post.

Corner is located on a sandy bench, on the right bank of McElmo Creek.

40.526 The 1/4 section corner of sections 20 and 21, monumented with a sandstone, 18x10x6 inches, marked 1/4 on west face, loosely set, projecting 14 inches above the ground, in a mound of stone, 2 feet base, 6 inches high (Record: marked 1/4 S, with a mound of stone, 2 feet base, 1 1/2 feet high, west of corner).

At the corner point (original marked stone)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 9 inches in the ground, to bedrock, with magnet at the base, in a mound of stone, 3 feet base, to brass cap marked:



Set a steel fence post north of stainless steel post.

Corner is located in rocky ground, in a shallow drainage, course S. 30° W.

---

N. 1° 58.9' E., beginning new measurement.

39.022 The corner of sections 16, 17, 20, and 21, monumented with a sandstone, 12x8x7 inches, marked with 4 notches on the east face, 2 notches on the south face, in a mound of stone, 2 feet base, 1 foot high (Record: a sandstone, 14x8x6 inches, marked

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

with 3 notches on the south edge, 4 notches on the east edge, with a mound of stone, 2 feet base, 1 1/2 feet high, west of corner).

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 17 inches in the ground, with magnet at the base, in a mound of stone, 3 feet base, to brass cap marked:

T40S	R26E
S 17	S 16
S 20	S 21
2009	

Bury marked stone at the base of the mound of stone.

Set a steel fence post north of stainless steel post.

Corner is located in rolling ground, south of a shallow drainage extending east-west, with desert brush.

From the corner of sections 15, 16, 21, and 22.

**S. 89° 44.6' W.**, between sections 16 and 21.

**33.025** Intersect the centerline of San Juan County Road 407, a gravel road, 20 feet wide, extending N. 6° E. and S. 6° W.

**39.876** Point for the 1/4 section corner of sections 16 and 21, monumented with a sandstone, 17x12x4 inches, marked 1/4 on the west face, loosely set, projecting 14 inches above the ground, in a mound of stone, 3 feet base, 1 foot high (Record: a sandstone, 15x11x9 inches, marked 1/4 S on the north face, with a mound of stone, 2 feet base, 1 1/2 feet high, north of corner).

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at the base, in a mound of stone, 4 feet base, to brass cap marked:

T40S	R26E
	S 16
1/4	—
	S 21
2009	

Bury marked stone at the base of the mound of stone.

Set a steel fence post north of stainless steel post.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Corner is located in rolling hills, with boulders and grasses.

N. 89° 52.6' W., beginning new measurement.

40.029 The corner of sections 16, 17, 20, and 21.

N. 0° 03.1' E., between sections 16 and 17.

10.300 Intersect the centerline of San Juan County Road 402, a paved road, 30 feet wide, extending N. 54° E. and S. 54° W.

39.975 Point for the 1/4 section corner of sections 16 and 17, at proportionate distance; there is no remaining evidence of the 1899 corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground, with magnet at the base, in a mound of stone, 4 feet base, to brass cap marked:

T40S	R26E
1/4	
S 17	S 16
2009	

Set a steel fence post northeast of stainless steel post.

Corner is located on a small bench, on a moderately-steep, south-facing, rocky hillside.

79.950 The corner of sections 8, 9, 16, and 17, monumented with a sandstone, 18x7x5 inches, marked with 4 notches on the south edge, 4 notches on the east edge, with an accessory mound of stone, 2 feet base, 1 foot high, west of corner (Record: a sandstone, 18x8x6 inches, marked with 4 notches on the south face, 4 notches on the east face, with a mound of stone, 2 feet base, 1 1/2 feet high, west of corner).

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 5 inches in the ground, to bedrock, with magnet at the base, in a mound of stone, 4 feet base, to brass cap marked:

T40S	R26E
S 8	S 9
S 17	S 16
2009	

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Bury marked stone at the base of the mound of stone.

Set a steel fence post east of stainless steel post.

Corner is located on a gentle, north-sloping bench, 150 feet above valley floor.

From the corner of sections 9, 10, 15, and 16.

N. 89° 58.0' W., between sections 9 and 16.

**39.445** Intersect the centerline of San Juan County Road 482, a gravel road, 18 feet wide, extending N. 4° E. and S. 1° W.

**39.932** Point for the 1/4 section corner of sections 9 and 16, at proportionate distance; there is no remaining evidence of the 1899 corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with magnet at the base, in a collar of stone, 2 feet diameter, with brass cap marked:

T40S R26E  
S 9  
1/4 ———  
S 16  
2009

Set a steel fence post west of stainless steel post.

Corner is located on the west side of an improved dirt road, in a sandy hill.

**79.864** The corner of sections 8, 9, 16, and 17.

N. 0° 01.7' E., between sections 8 and 9.


**39.928** The 1/4 section corner of sections 8 and 9, monumented with a sandstone, 16x12x7 inches, marked 1/4 on the west face, with a mound of stone, 3 feet base, 1 foot high, west of corner (Record: a sandstone, 15x19x8 inches, marked 1/4 S, with a mound of stone, 2 feet base, 1 1/2 feet high, west of corner).

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground, with magnet at the base, in a mound of stone, 3 feet base, to brass cap marked:

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS



Bury marked stone at the base of the mound of stone.

Set a steel fence post north of stainless steel post.

Corner is located on the gentle, west slope of a small hill.


**N. 0° 01.5' E.**, beginning new measurement.

**8.590** Intersect the centerline of San Juan County Road 482, a gravel road, 18 feet wide, extending N. 69° E. and S. 69° W.

**39.994** The corner of sections 4, 5, 8, and 9, monumented with a sandstone, 17x9x8 inches, marked with 5 notches on the south edge, 4 notches on the east edge, in a collar of stone, 2 feet (Record: a sandstone, 16x8x6 inches, with a mound of stone, 2 feet base, 1 1/2 feet high, west of corner).

At the corner point

Set a brass tablet, 3 1/4 inches diameter, 2 1/2 inch stem, flush with bedrock, in cement bond, with magnet at the base, in a hole drilled in the sandstone bedrock marked:



Raise a mound of stone, 2 feet base, 2 feet high,

Bury marked stone at the base of the mound of stone.

Set a steel fence post, north of brass tablet.

Corner is located at the base of a northwest slope, at the foot of a mesa.

From the corner of sections 3, 4, 9, and 10.

**S. 89° 54.4' W.**, between sections 4 and 9.

**39.970** Point for the 1/4 section corner of sections 4 and 9, at proportionate distance; there is no remaining evidence of the 1899 corner.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, in a collar of stone, 2 feet diameter, with brass cap marked:

T40S R26E  
S 4  
1/4 ———  
S 9  
2009

Set a steel fence post north of stainless steel post.

Corner is located on a fairly level mesa top, with desert grasses.

59.955 Point for the west 1/16 section corner of sections 4 and 9.

Set a brass tablet, 3 1/4 inches diameter, 2 1/2 inch stem, flush with bedrock, in cement bond, with magnet at the base, in a hole drilled in the sandstone bedrock marked:

T40S R26E  
S 4  
W 1/16 ———  
S 9  
2009

Set a steel fence post north of the brass tablet.

Corner is located on a gentle, northwest-sloping mesa top, with exposed sandstone bedrock.

79.940 The corner of sections 4, 5, 8, and 9.

N. 0° 01.0' E., between sections 4 and 5.

40.014 The 1/4 section corner of sections 4 and 5, determined at the center of an embedded mound of stone, 2 feet base, 1 foot high. There is no remaining evidence of the 1899 marked stone. This mound is accepted as the best available evidence of the original corner position.

At the corner point (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at the base, in a collar of stone, 3 feet diameter, with brass cap marked:

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T40S R26E  
1/4  
S 5 | S 4  
2009

Set a steel fence post north of stainless steel post.

Corner is located in an open valley.

---

N. 0° 05.0' E., beginning new measurement.

20.019 Point for the north 1/16 section corner of sections 4 and 5.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, with brass cap marked:

T40S R26E  
N 1/16  
S 5 | S 4  
2009

Set a steel fence post north of stainless steel post.

Corner is located on a gentle, south-sloping mesa top.

40.158 The corner of sections 4, 5, 32, and 33, on the North boundary of the township, hereinbefore described.

---

From the standard corner of sections 31 and 32 only, on the South boundary of the township (Eighth Standard Parallel South), monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 2 inches above the ground, with brass cap marked as described in the official record of the 2005 resurvey of T. 41 S., R. 26 E.


N. 0° 01.7' W., between sections 31 and 32.

39.641 Point for the 1/4 section corner of sections 31 and 32, at proportionate distance; there is no remaining evidence of the 1899 corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 6 inches below the ground, with magnet at the base, with brass cap marked:

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS




Corner is located in an agricultural field, near McElmo Creek.

79.282

The corner of sections 29, 30, 31, and 32, monumented with a sandstone, 16x11x5 inches, marked with 1 notch on the south edge, 5 notches on the east edge, firmly set, projecting 13 inches above the ground, with a mound of stone, 2 feet base, 1 foot high, west of corner (Record: a sandstone, 16x10x6 inches, with a mound of stone, 2 feet base, 1 1/2 feet high, west of corner).

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with magnet at the base, in a mound of stone, 3 feet base, to brass cap marked:



Bury marked stone at the base of the mound of stone.

Set a steel fence post north of stainless steel post.

Corner is located on a gentle, southeast-sloping hillside, with desert grasses.

From the corner of sections 28, 29, 32, and 33.

**S. 89° 56.7' W.**, between sections 29 and 32.

39.940

Point for the 1/4 section corner of sections 29 and 32, at proportionate distance; there is no remaining evidence of the 1899 corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with magnet at the base, in a collar of stone, 2 feet diameter, with brass cap marked:

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T40S R26E  
S 29  
1/4 ———  
S 32  
2009

Set a steel fence post north of stainless steel post.

Corner lies immediately north of a large boulder, in rolling, sandy terrain, south of McElmo Creek.

79.880 The corner of sections 29, 30, 31, and 32.

S. 89° 57.6' W., between sections 30 and 31.

39.985 Point for the 1/4 section corner of sections 30 and 31, at proportionate distance; there is no remaining evidence of the 1899 corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at the base, in a mound of stone, 3 feet base, to brass cap marked:

T40S R26E  
S 30  
1/4 ———  
S 31  
2009

Set a steel fence post north of stainless steel post.

Corner is located in gently-rolling, rock-covered hills, with sparse vegetation.

79.970 The corner of sections 25, 30, 31, and 36, on the West boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap marked as described in the official record of the 2004 resurvey of T. 40 S., R. 25 E, with a mound of stone, 4 feet base, 2 feet high, west of corner.

From the corner of sections 29, 30, 31, and 32.

N. 0° 01.7' E., between sections 29 and 30.

39.931 Point for the 1/4 section corner of sections 29 and 30, at proportionate distance; there is no remaining evidence of the 1899 corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with magnet at the base, in a mound of stone, 4 feet base, to brass cap marked:

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T40S	R26E
1/4	
S 30	S 29
2009	

Set a steel fence post northwest of stainless steel post.

Corner is located on a gentle south slope, on the north side of a drainage, course West.

79.862

The corner of sections 19, 20, 29, and 30, determined at the center of a mound of stone, 2 feet base, 1 foot high. There is no remaining evidence of the 1899 marked stone. This mound is accepted as the best available evidence of the original corner position.

At the corner point (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 23 inches in the ground, with magnet at the base, in a mound of stone, 3 feet base, to brass cap marked:

T40S	R26E
S 19	S 20
S 30	S 29
2009	

Set a steel fence post north of stainless steel post.

Corner is located on rocky ground, on a gentle, west-facing slope, with scattered desert grasses.

From the corner of sections 20, 21, 28, and 29.

**S. 89° 33.6' W.**, between sections 20 and 29.

39.915

Point for the 1/4 section corner of sections 20 and 29, at proportionate distance; nearby, a sandstone, 17x9x6 inches, marked 1/4 on one face, laying loose on the ground (Record: a sandstone, 16x8x6 inches, marked 1/4 S on west face, with a mound of stone, 2 feet base, 1 1/2 feet high). There is no method to determine the original location of the marked stone.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 30 inches in the ground, with magnet at the base, with brass cap marked:

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T40S R26E  
S 20  
1/4 ———  
S 29  
2009

Remove original stone from area.

Raise a mound of stone, 2 feet base, 2 feet high, west of corner.

Corner is located south of a housing area, in an area of disturbed ground.

79.830 The corner of sections 19, 20, 29, and 30.

---

S. 89° 33.0' W., between sections 19 and 30.

39.915 The 1/4 section corner of sections 19 and 30, monumented with a sandstone, 15x12x6 inches, marked 1/4 on north face, firmly set, projecting 11 inches above the ground (Record: a sandstone, 16x10x6 inches, marked 1/4 S, with a mound of stone, 2 feet base, 1 1/2 feet high, north of corner).

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with magnet at the base, in a collar of stone, 2 feet diameter, to brass cap marked:

T40S R26E  
S 19  
1/4 ———  
S 30  
2009

Bury marked stone in the collar of stone.

Set a steel fence post north of stainless steel post.

Corner is located on rocky ground, in rolling hills, with sparse vegetation.

---

N. 89° 30.2' W., beginning new measurement.

40.123 The corner of sections 19, 24, 25, and 30, on the West boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, flush with the ground, with brass cap marked as described in the official record of the 2004 resurvey of T. 40 S., R. 25 E.; with a mound of stone, 4 feet base, 2 feet high, west of corner.

---

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

From the corner of sections 19, 20, 29, and 30.

N. 0° 01.9' E., between sections 19 and 20.

40.163

The 1/4 section corner of sections 19 and 20, monumented with a sandstone, 16x10x5 inches, marked 1/4 on west face, firmly set, projecting 9 inches above the ground, in an embedded collar of stone, 2 feet diameter (Record: a sandstone, 14x10x7 inches, marked 1/4 S, with a mound of stone, 2 feet diameter base, 1 1/2 feet high, west of corner).

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, in a collar of stone, 2 feet diameter, with brass cap marked:

T40S	R26E
1/4	
S 19	S 20
2009	

Remove original stone from the area.

Set a steel fence post north of stainless steel post.

Corner is located southwest of a house, at the bottom of a shallow drainage, southeast of a corral.

---

N. 0° 16.1' W., beginning new measurement.

18.490

Intersect the centerline of San Juan County Road 402, a paved road, 30 feet wide, extending N. 82° W. and S. 82° E.

39.970

Point for the corner of sections 17, 18, 19, and 20, at proportionate distance; there is no remaining evidence of the 1899 corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with brass cap marked:

T40S	R26E
S 18	S 17
S 19	S 20
2009	

Bury a rebar, 5/8 inch diameter, 1 1/2 feet long, next to corner as a memorial.

Set a steel fence post north of stainless steel post.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Corner is located on the floodplain of a dry wash, in thick tamarisk trees.

---

From the corner of sections 16, 17, 20, and 21.

**S. 89° 56.1' W.**, between sections 17 and 20.

**9.150** Intersect the centerline of San Juan County Road 402, a paved road, 30 feet wide, extending N. 22° E. and S. 22° W.

**40.176** The 1/4 section corner of sections 17 and 20, monumented with a sandstone, 18x12x8 inches, marked 1/4 on north face, firmly set, projecting 12 inches above the ground, with an embedded accessory mound of stone, 2 feet base, 6 inches high, north of corner (Record: a sandstone, 18x10x6 inches, marked 1/4 S, with a mound of stone, 2 feet base, 1 1/2 feet high, north of corner).

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at the base, in a mound of stone, 4 feet base, to brass cap marked:

T40S R26E  
S 17  
1/4 ———  
S 20  
2009

Bury marked stone at the base of the mound of stone.

Set a steel fence post northwest of stainless steel post.

Corner is located on top of a spur, extending north-south, on rocky ground.

---

**N. 89° 54.9' W.**, beginning new measurement.

**22.970** Intersect the centerline of San Juan County Road 401, a paved road, 27 feet wide, extending N. 13° E. and S. 13° W.

**39.919** The corner of sections 17, 18, 19, and 20.

---

**S. 89° 58.0' W.**, between sections 18 and 19.

**39.919** Point for the 1/4 section corner of sections 18 and 19, at proportionate distance; there is no remaining evidence of the 1899 corner.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with magnet at the base, in a collar of stone, 2 feet diameter, with brass cap marked:

T40S R26E  
S 18  
1/4 ———  
S 19  
2009

Set a steel fence post north of stainless steel post.

Corner is located in rolling hills, on hard, rocky ground, with sparse vegetation.

- 79.838** The corner of sections 13, 18, 19, and 24, on the West boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 7 inches above the ground, with brass cap marked as described in the official record of the 2004 resurvey of T. 40 S., R. 25 E., with a mound of stone, 3 feet base, 1 1/2 feet high, west of corner.

Set a steel fence post north of stainless steel post.

From the corner of sections 17, 18, 19, and 20.

**N. 0° 17.8' E.**, between sections 17 and 18.

- 39.970** The 1/4 section corner of sections 17 and 18, monumented with a sandstone, 12x8x4 inches, marked 1/4 on the west face, firmly set, projecting 7 inches above the ground, in a collar of stone, 2 feet diameter (Record: a sandstone, 12x8x5 inches, marked 1/4 S, with a mound of stone, 2 feet base, 1 1/2 feet high, west of corner).

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with magnet at the base, in a collar of stone, 2 feet diameter, with brass cap marked:

T40S R26E  
1/4  
S 18 | S 17  
2009

Bury marked stone in the collar of stone.

Set a steel fence post north of stainless steel post.

Corner is located in gently rolling hills.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

---

N. 0° 01.3' E., beginning new measurement.

40.027 The corner of sections 7, 8, 17, and 18, determined at the center of an embedded mound of stone, 2 feet base, 6 inches high, with a sandstone, 16x10x4 inches, marked with 4 notches on one edge, 5 notches on another edge, broken and lying loose on the mound (Record: a sandstone, 18x14x3 inches, marked with 4 notches on south edge, 5 notches on east edge, with a mound of stone, 2 feet base, 1 1/2 feet high, west of corner).

At the corner point (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, in a collar of stone, 2 feet diameter, with brass cap marked:

T40S	R26E
S 7	S 8
S 18	S 17
2009	

Set a steel fence post north of stainless steel post.

Corner is located in gently rolling hills, with desert grasses.

---

From the corner of sections 8, 9, 16, and 17.

N. 89° 57.4' W., between sections 8 and 17.

39.965 Point for the 1/4 section corner of sections 8 and 17, at proportionate distance; there is no remaining evidence of the 1899 corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 30 inches in the ground, with magnet at the base, with brass cap marked:

T40S	R26E
	S 8
1/4	—————
	S 17
2009	

Corner is located south of a small housing subdivision, at the foot of a steep west-facing slope.

59.770 Intersect the centerline of San Juan County Road 401, a paved road, 27 feet wide, extending N. 8° W. and S. 8° E.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

59.947

Point for the west 1/16 section corner of sections 8 and 17.  
Point falls on a paved highway, 22 feet wide, extending N. 8° W.  
and S. 8° E.

Set a PK magnetic nail, 2 inches long, flush with pavement.

from which

A stainless steel post, 30 inches long, 2 1/2 inches  
diameter, 30 inches in the ground, with magnet at the  
base, for a reference monument, bears S. 31° 26' 09" W.,  
0.422 chain distance, with brass cap marked: T40S R26E  
S17 RM 2009, and an arrow pointing to corner with 27.9  
FT. TO COR. marked along it.

Set a steel fence post north of stainless steel post.

Falls in west shoulder of highway.

A stainless steel post, 30 inches long, 2 1/2 inches  
diameter, 30 inches in the ground, with magnet at the  
base, for a reference monument, bears N. 44° 28' 55" W.,  
0.448 chain distance, with brass cap marked: T40S R26E S8  
RM 2009, with an arrow pointing to corner with 29.6 FT.  
TO COR. marked along it.

Set a steel fence post north of stainless steel post.

Falls in west shoulder of highway.

79.929

The corner of sections 7, 8, 17, and 18.

---

S. 89° 58.1' W., between sections 7 and 18.

20.024

Point for the east 1/16 section corner of sections 7 and 18.

Set a stainless steel post, 30 inches long, 2 1/2 inches  
diameter, 29 inches in the ground, with magnet at the base, with  
brass cap marked:

T40S R26E  
S 7  
E 1/16 ———  
S 18  
2009

Set a steel fence post north of stainless steel post.

Corner is located on a gentle, east-sloping plain.

40.048

Point for the 1/4 section corner of sections 7 and 18, at  
proportionate distance; there is no remaining evidence of the  
1899 corner.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with magnet at the base, in a collar of stone, 2 feet diameter, with brass cap marked:

T40S R26E  
S 7  
1/4 ———  
S 18  
2009

Set a steel fence post west of stainless steel post.

Corner is located on fairly level ground, with scattered desert grasses.

- 80.096** Point for the corner of sections 7, 12, 13, and 18, on the West boundary of the township, monumented with an iron railroad spike, set flush with the surface of the dirt road, as described in the official record of the 2004 resurvey of T. 40 S., R. 25 E.

from which

A boulder, 5x5x2 feet, marked "XBO", bears N. 1° 02.8' W., 86.5 links distance (Record: N. 1° 04.7' W., 86.6 links distance).

from which (new accessory)

A Cadastral Survey washer, brass, 1 1/2 inches diameter, attached with a PK magnetic nail, in a power pole, 12 inches diameter, 5 feet above the ground, bears N. 33° 54.6' W., 94.8 links distance.

From the corner of sections 7, 8, 17, and 18.

N. 0° 03.4' E., between sections 7 and 8.

- 19.998** Point for the south 1/16 section corner of sections 7 and 8, not monumented.


- 39.996** The 1/4 section corner of sections 7 and 8, monumented with a sandstone, 14x13x4 inches, marked 1/4 on west face, firmly set, projecting 11 inches above the ground (Record: a sandstone, 18x16x3 inches, marked 1/4 S, with a mound of stone, 2 feet base, 1 1/2 feet high, west of corner).

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, in a collar of stone, 2 feet diameter, with brass cap marked:

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS



Bury marked stone in the collar of stone.


Set a steel fence post north of stainless steel post.

Corner is located on a fairly level plain, with sparse vegetation.

**N. 0° 00.6' E.**, beginning new measurement.

- 9.021** Intersect the centerline of San Juan County Road 401, a paved road, 27 feet wide, extending N. 70° W. and S. 70° E.
- 19.986** Point for the north 1/16 section corner of sections 7 and 8, not monumented.
- 39.972** Point for the corner of sections 5, 6, 7, and 8, at proportionate distance; there is no remaining evidence of the 1899 corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, with brass cap marked:



Set a steel fence post north of stainless steel post.

Corner is located on fairly level ground, in a large, open valley.

From the corner of sections 4, 5, 8, and 9.

**S. 89° 52.9' W.**, between sections 5 and 8.

- 39.846** The 1/4 section corner of sections 5 and 8, determined at the center of an embedded mound of stone, 2 feet base, 1 foot high. There is no remaining evidence of the 1899 marked stone. This mound is accepted as the best available evidence of the original corner position.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with magnet at the base, in a mound of stone, 3 feet base, to brass cap marked:

T40S R26E  
S 5  
1/4 ———  
S 8  
2009

Set a steel fence post north of the stainless steel post.

Corner is located on a gentle west slope, at the base of a mesa.

---

N. 89° 43.8' W., beginning new measurement.

20.030 Point for the west 1/16 section corner of sections 5 and 8.

Set a brass tablet, 3 1/4 inches diameter, 2 1/2 inch stem, flush with bedrock, in cement bond, in a hole drilled in a sandstone boulder, 6x5x2 feet, marked:

T40S R26E  
S 5  
W 1/16 ———  
S 8  
2009

Set a steel fence post southeast of brass tablet.

Corner is located on a moderately-steep, boulder-covered west-facing slope.

40.060 The corner of sections 5, 6, 7, and 8.

---

S. 89° 52.8' W., between sections 6 and 7.

4.780 Intersect the centerline of San Juan County Road 418, a gravel road, 20 feet wide, extending N. 22° E. and S. 22° W.

20.029 Point for the east 1/16 section corner of sections 6 and 7.

Set a brass tablet, 3 1/4 inches diameter, 2 1/2 inch stem, flush with bedrock, in cement bond, in a hole drilled in a sandstone bedrock, marked:

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T40S R26E  
S 6  
E 1/16 ———  
S 7  
2009

Set a steel fence post east of brass tablet.

Corner is located in rolling hills, with grass and occasional sandstone outcrops.

- 40.058 Point for the 1/4 section corner of sections 6 and 7, at proportionate distance; there is no remaining evidence of the 1899 corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, with brass cap marked:

T40S R26E  
S 6  
1/4 ———  
S 7  
2009

Set a steel fence post north of the stainless steel post.

Corner is located below an earthen dam, in a shallow basin.

- 80.116 The corner of sections 1, 6, 7, and 12, on the West boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, flush, in a collar of stone, 3 feet diameter, with brass cap marked as described in the official record of the 2004 resurvey.

Set a steel fence post south of stainless steel post.

Corner lies between two large boulders.

From the corner of sections 5, 6, 7, and 8.

N. 0° 03.0' E., between sections 5 and 6.

- 11.937 Intersect the centerline of San Juan County Road 418, a gravel road, 20 feet wide, extending N. 22° E. and S. 22° W.
- 19.986 Point for the south 1/16 section corner of sections 5 and 6, not monumented.
- 39.972 Point for the 1/4 section corner of sections 5 and 6, at proportionate distance; there is no remaining evidence of the 1899 corner.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, in a mound of stone, 4 feet base, to brass cap marked:

T40S R26E  
1/4  
S 6 | S 5  
2009

Set a steel fence post north of stainless steel post.

Corner is located on a gentle south slope, in an open valley, with desert grasses.

**59.958** Point for the north 1/16 section corner of sections 5 and 6.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, with brass cap marked:

T40S R26E  
N 1/16  
S 6 | S 5  
2009

Set a steel fence post north of stainless steel post.

Corner is located on the east side of a valley, on a gentle west slope.

**80.034** The corner of sections 5, 6, 31, and 32, on the North boundary of the township, hereinbefore described.

---

The Subdivision of Section 5,  
T. 40 S., R. 26 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 5 and 8.

**N. 0° 05.4' W.**, on the N-S centerline of section 5.

**20.064** Point for the center south 1/16 section corner of section 5.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, with brass cap marked:

THE SUBDIVISION OF SECTION 5,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T40S R26E  
C  
S 1/16 | S 5  
C  
2009

Set a steel fence post north of the stainless steel post.

Corner is located on a gentle, grassy north slope.

- 40.128** Point for the center 1/4 section corner of section 5, at intersection with E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 30 inches in the ground, with magnet at the base, in a collar of stone, 2 feet diameter, with brass cap marked:

T40S R26E  
C 1/4 S 5  
2009

Set a steel fence post north of stainless steel post.

Corner is located on a moderately-steep, boulder-covered, west-facing hillside, with a large boulder immediately east of the corner.

- 60.129** Point for the center north 1/16 section corner of section 5.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, with brass cap marked:

T40S R26E  
C  
N 1/16 | S 5  
C  
2009

Set a steel fence post north of the stainless steel post.

Corner is located in an open valley, on a gentle, west slope.

- 80.235** The 1/4 section corner of sections 5 and 32, on the North boundary of the township, hereinbefore described.

---

From the 1/4 section corner of sections 4 and 5.

THE SUBDIVISION OF SECTION 5,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

N. 89° 57.2' W., on the E-W centerline of section 5.

39.917 The center 1/4 section corner of section 5.

59.895 Point for the center west 1/16 section corner of section 5.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with magnet at the base, in a collar of stone, 3 feet diameter, with brass cap marked:

T40S R26E  
W 1/16  
C ————— C  
S 5  
2009

Set a steel fence post east of the stainless steel post.

Corner is located on the north side of, and near the top of, a spur, extending east-west.

68.795 Intersect the centerline of San Juan County Road 418, a gravel road, 20 feet wide, extending N. 22° E. and S. 22° W.

79.873 The 1/4 section corner of sections 5 and 6.

From the north 1/16 section corner of sections 4 and 5.

N. 89° 58.7' W., on the E-W centerline of the northeast 1/4 of section 5.

39.976 The center north 1/16 section corner of section 5.

From the west 1/16 section corner of sections 5 and 8.

N. 0° 01.2' W., on the N-S centerline of the southwest 1/4 of section 5.

20.025 Point for the southwest 1/16 section corner of section 5.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, with brass cap marked:

T40S R26E  
SW 1/16 S 5  
2009

Set a steel fence post north of the stainless steel post.

Corner is located behind an earthen dam, in a heavily eroded area.

THE SUBDIVISION OF SECTION 5,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

- 40.050 The center west 1/16 section corner of section 5.
- 
- From the center south 1/16 section corner of section 5.
- N. 89° 50.5' W.**, on the E-W centerline of the southwest 1/4 of section 5.
- 20.004 The southwest 1/16 section corner of section 5.
- 36.830 Intersect the centerline of San Juan County Road 418, a gravel road, 20 feet wide, extending N. 22° E. and S. 22° W.
- 40.008 The point for the south 1/16 section corner of sections 5 and 6.
- 
- From the center north 1/16 section corner of section 5.
- N. 89° 58.4' W.**, on the E-W centerline of the northwest 1/4 of section 5.
- 20.755 Intersect the centerline of San Juan County Road 418, a gravel road, 20 feet wide, extending N. 22° E. and S. 22° W.
- 39.906 The north 1/16 section corner of sections 5 and 6.

The Subdivision of Section 6,  
T. 40 S., R. 26 E., Salt Lake Meridian, Utah

- 
- From the 1/4 section corner of sections 6 and 7.
- N. 0° 05.8' E.**, on the N-S centerline of section 6.
- 39.986 Point for the center 1/4 section corner of section 6, at intersection with the E-W centerline.
- Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with magnet at the base, in a collar of stone, 2 feet diameter, with brass cap marked:

T40S R26E  
C 1/4 S 6  
2009

Set a steel fence post north of the stainless steel post.

Corner is located southwest of a rocky slope, in scattered juniper trees.

THE SUBDIVISION OF SECTION 6,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

80.389

The 1/4 section corner of sections 6 and 31, on the North boundary of the township, hereinbefore described.

---

From the 1/4 section corner of sections 5 and 6.

S. 89° 54.0' W., on the E-W centerline of section 6.

20.011

Point for the center east 1/16 section corner of section 6.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, with brass cap marked:

T40S R26E  
E 1/16  
C ————— C  
S 6  
2009

Set a steel fence post north of stainless steel post.

Corner is located on a fairly level mesa top, with desert grasses.

40.022

The center 1/4 section corner of section 6.

80.099

The 1/4 section corner of sections 1 and 6, on the West boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, flush with the top of a mound of stone, 4 feet base, 1 foot high, with brass cap marked as described in the official record of the 2004 resurvey of T. 40 S., R. 25 E.

Set a steel fence post south of stainless steel post.

---

From the center east 1/16 section corner of section 6.

N. 0° 04.4' E., on the N-S centerline of the northeast 1/4 of section 6.

40.232

The east 1/16 section corner of sections 6 and 31, on the North boundary of the township, hereinbefore described.

---

From the east 1/16 section corner of sections 6 and 7.

N. 0° 04.4' E., on the N-S centerline of the southeast 1/4 of section 6.

39.979

The center east 1/16 section corner of section 6.

THE SUBDIVISION OF SECTION 7,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 7,  
T. 40 S., R. 26 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 7 and 18.

N. 0° 01.2' E., on the N-S centerline of section 7.

**19.995** Point for the center south 1/16 section corner of section 7.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at the base, in a collar of stone, 2 feet diameter, with brass cap marked:

```

T40S  R26E
      C
S 1/16 | S 7
      C
      2009
    
```

Set a steel fence post north of stainless steel post.

Corner is located on a gentle, southeast slope, in rolling hills.

**39.990** Point for the center 1/4 section corner of section 7, at intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with magnet at the base, with brass cap marked:

```

T40S  R26E
C 1/4  S 7
      2009
    
```

Set a steel fence post northwest of stainless steel post.


Corner is located on fairly level ground, in a large, open valley.

**59.949** Point for the center north 1/16 section corner of section 7.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, with brass cap marked:

THE SUBDIVISION OF SECTION 7,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS



Set a steel fence post north of stainless steel post.

Corner is located south of a paved highway, in gently rolling ground.

**63.795** Intersect the centerline of San Juan County Road 401, a paved road, 27 feet wide, extending N. 70° W. and S. 70° E.

**79.908** The 1/4 section corner of sections 6 and 7.

From the 1/4 section corner of sections 7 and 8.

**S. 89° 57.5' W.**, on the E-W centerline of section 7.

**20.035** Point for the center east 1/16 section corner of section 7, not monumented.

**40.070** The center 1/4 section corner of section 7.

**80.145** The 1/4 section corner of sections 7 and 12, on the West boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 3 inches above the ground, with brass cap marked as described in the official record of the 2004 resurvey of T. 40 S., R. 25 E., with an embedded mound of stone, 2 feet base, 6 inches high, west of corner.

Set a steel fence post northwest of stainless steel post.

From the point for the center east 1/16 section corner of section 7.

**N. 0° 00.9' E.**, on the N-S centerline of the northeast 1/4 of section 7.

**16.405** Intersect the centerline of San Juan County Road 401, a paved road, 27 feet wide, extending N. 70° W. and S. 70° E.

**19.972** Point for the northeast 1/16 section corner of section 7.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with magnet at the base, with brass cap marked:

THE SUBDIVISION OF SECTION 7,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T40S R26E  
NE 1/16 S7  
2009

Set a steel fence post north of stainless steel post.

Corner is located north of a paved highway, on fairly level ground.

**39.944** The east 1/16 section corner of sections 6 and 7.

From the point for the north 1/16 section corner of sections 7 and 8.

**S. 89° 55.2' W.**, on the E-W centerline of the northeast 1/4 of section 7.

**12.770** Intersect the centerline of San Juan County Road 418, a gravel road, 27 feet wide, extending N. 22° E. and S. 22° W.

**20.032** The northeast 1/16 section corner of section 7.

**29.680** Intersect the centerline of San Juan County Road 401, a paved road, 27 feet wide, extending N. 70° W. and S. 70° E.

**40.064** The center north 1/16 section corner of section 7.

From the east 1/16 section corner of sections 7 and 18.

**N. 0° 02.3' E.**, on the N-S centerline of the southeast 1/4 of section 7.

**19.997** Point for the southeast 1/16 section corner of section 7.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with magnet at the base, in a collar of stone, 2 feet diameter, with brass cap marked:

T40S R26E  
SE 1/16 S7  
2009

Set a steel fence post north of stainless steel post.

Corner is located on fairly level ground.

**39.994** The point for the center east 1/16 section corner of section 7.

From the point for the south 1/16 section corner of sections 7 and 8.

THE SUBDIVISION OF SECTION 7,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 89° 57.8' W., on the E-W centerline of the southeast 1/4 of section 7.

20.029 The southeast 1/16 section corner of section 7.

40.058 The center south 1/16 section corner of section 7.

Subdivision of Section 8,  
T. 40 S., R. 26 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 8 and 17.

N. 0° 06.4' E., on the N-S centerline of section 8.

26.680 Intersect the centerline of San Juan County Road 482, a gravel road, 18 feet wide, extending N. 62° E. and S. 62° W.

39.962 Point for the center 1/4 section corner of section 8, at intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, with brass cap marked:

T40S R26E  
C 1/4 S 8  
2009

Set a steel fence post north of stainless steel post.

Corner is located on a gentle west slope, in a large, open valley.

59.886 Point for the center north 1/16 section corner of section 8.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, with brass cap marked:

T40S R26E  
C  
N 1/16 | S 8  
C  
2009

Set a steel fence post north of stainless steel post.

Corner is located on a gentle south slope, in an open valley, near the base of a low mesa.

THE SUBDIVISION OF SECTION 8,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

79.810

The 1/4 section corner of sections 5 and 8.

---

From the 1/4 section corner of sections 8 and 9.

**N. 89° 54.5' W.**, on the E-W centerline of section 8.

5.940

Intersect the centerline of San Juan County Road 482, a gravel road, 18 feet wide, extending N. 34° E. and S. 34° W.

39.906

The center 1/4 section corner of section 8.

59.904

Point for the center west 1/16 section corner of section 8.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, with brass cap marked:

T40S R26E  
W 1/16  
C ————— C  
S 8  
2009

Set a steel fence post north of stainless steel post

Corner is located on fairly level ground, in a large, open valley, with desert grasses.

64.310

Intersect the centerline of San Juan County Road 401, a paved road, 27 feet wide, extending N. 35° W. and S. 25° E.

79.902

The 1/4 section corner of sections 7 and 8.

---

From the west 1/16 section corner of sections 8 and 17.

**N. 0° 04.9' E.**, on the N-S centerline of the southwest 1/4 of section 8.

18.300

Intersect the centerline of San Juan County Road 482, a gravel road, 18 feet wide, extending N. 83° E. and S. 83° W.

39.980

The center west 1/16 section corner of section 8.

---

From the center west 1/16 section corner of section 8.

**N. 0° 03.5' E.**, on the N-S centerline of the northwest 1/4 of section 8.

19.955

Point for the northwest 1/16 section corner of section 8.

THE SUBDIVISION OF SECTION 8,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, with brass cap marked:

T40S R26E  
NW 1/16 S8  
2009

Set a steel fence post north of the stainless steel post.

Corner is located on gentle south-sloping ground, on the east edge of a large, open valley.

39.910 The west 1/16 section corner of sections 5 and 8.

---

From the center north 1/16 section corner of section 8.

N. 89° 49.1' W., on the E-W centerline of the northwest 1/4 of section 8.

20.014 The northwest 1/16 section corner of section 8.

40.028 The point for the north 1/16 section corner of sections 7 and 8.

---

The Subdivision of Section 9,  
T. 40 S., R. 26 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 9 and 16.

N. 0° 03.6' E., on the N-S centerline of section 9.

40.030 Point for the center 1/4 section corner of section 9, at intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, with brass cap marked:

T40S R26E  
C 1/4 S9  
2009

Set a steel fence post north of stainless steel post.

Corner is located on the west shoulder of a dirt road extending north-south, on fairly level ground.

57.430 Intersect the centerline of San Juan County Road 482, a gravel road, 18 feet wide, extending N. 29° W. and S. 29° E.

80.010 The 1/4 section corner of sections 4 and 9.

THE SUBDIVISION OF SECTION 9,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

---

From the 1/4 section corner of sections 9 and 10.

S. 89° 53.2' W., on the E-W centerline.

- 39.280 Intersect the centerline of San Juan County Road 482, a gravel road, 18 feet wide, extending North and South.
- 39.971 The center 1/4 section corner of section 9.
- 59.946 True point for the center west 1/16 section corner of section 9, falls on inaccessible cliff face. Impracticable to establish a monument at this location.
- 60.249 Point selected for the witness corner to the center west 1/16 section corner of section 9.

Set a brass tablet, 3 1/4 inches diameter, 2 1/2 inch stem, flush with sandstone bedrock, in cement bond with magnet at base, into a drill hole in bedrock marked:

WC  
T40S R26E  
W 1/16  
C → C  
S 9  
2009

Corner is located on a mesa top, on a sandstone bench.

- 79.921 The 1/4 section corner of sections 8 and 9.

---

From the true point for the center west 1/16 section corner of section 9.

N. 0° 02.5' E., on the N-S centerline of the northwest 1/4 of section 9.

- 15.690 Intersect the centerline of San Juan County Road 482, a gravel road, 18 feet wide, extending N. 57° E. and S. 57° W.
- 39.987 The west 1/16 section corner of sections 4 and 9.

---

The Subdivision of Section 10,  
T. 40 S., R. 26 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 10 and 15.

N. 0° 11.4' E., on the N-S centerline of section 10.

THE SUBDIVISION OF SECTION 10,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

39.955

Point for the center 1/4 section corner of section 10, at intersection with the E-W centerline. Point falls on a paved highway, 27 feet wide, extending N. 16° E., S. 20° W.

Set a PK magnetic nail, 2 inches long, flush with pavement.

from which

A stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, for a reference monument, bears N. 66° 11' 47" E., 29.4 links distance, with brass cap marked: T40S R26E S10 RM 2009, and an arrow pointing to corner with 19.4 FT. TO COR. marked along it.

Set a steel fence post next to the stainless steel post.

Reference monument falls in east shoulder of highway.

A stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, for a reference monument, bears S. 28° 39' 00" E., 26.8 links distance, with brass cap marked: T40S R26E S10 RM 2009, and an arrow point to the corner with 17.7 FT. TO COR. marked along it.

Set a steel fence post next to the stainless steel post.

Reference monument falls in east shoulder of highway.

40.525

Intersect the centerline of San Juan County Road 402, a paved road, 30 feet wide, extending N. 16° E. and S. 20° W.

79.854

The 1/4 section corner of sections 3 and 10.

From the 1/4 section corner of section 10 only, on the Utah-Colorado State Boundary Line, hereinbefore described.

S. 89° 52.2' W., on the E-W centerline of section 10.

20.115

The center 1/4 section corner of section 10.

20.270

Intersect the centerline of San Juan County Road 402, a paved road, 30 feet wide, extending N. 16° E. and S. 20° W.

40.066

Point for the center west 1/16 section corner of section 10.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground, with magnet at the base, in a mound of stone, 4 feet base, to brass cap marked:

THE SUBDIVISION OF SECTION 10,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T40S R26E  
W 1/16  
C ————— C  
S 10  
2009

Set a steel fence post south of stainless steel post.

Corner is located on rocky ground, on a steep, southeast-facing slope, surrounded by large boulders.

60.017 The 1/4 section corner of sections 9 and 10.

---

From the west 1/16 section corner of sections 10 and 15.

**N. 0° 09.3' E.**, on the N-S centerline of the southwest 1/4 of section 10.

13.840 Intersect the centerline of San Juan County Road 402, a paved road, 30 feet wide, extending N. 43° E. and S. 43° W.

40.043 The center west 1/16 section corner of section 10.

---

From the center west 1/16 section corner of section 10.

**N. 0° 07.6' E.**, on the N-S centerline of the northwest 1/4 of section 10.

39.932 The west 1/16 section corner of sections 3 and 10.

---

The Subdivision of Section 15,  
T. 40 S., R. 26 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 15 and 22.

**N. 0° 01.5' E.**, on the N-S centerline of section 15.

40.121 Point for the center 1/4 section corner of section 15, at intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, with brass cap marked:

T40S R26E  
C 1/4 S 15  
2009

Set a steel fence post north of the stainless steel post.

THE SUBDIVISION OF SECTION 11,  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Corner is located in rolling dirt hills, east of McElmo Creek.

80.129 The 1/4 section corner of sections 10 and 15.

---

From the 1/4 section corner of section 15 only, on the Utah-Colorado State Boundary Line, hereinbefore described.

N. 89° 59.8' W., on the E-W centerline of section 15.

20.088 The center 1/4 section corner of section 15.

60.002 The 1/4 section corner of sections 15 and 16.

---

The Subdivision of Section 17,  
T. 40 S., R. 26 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 17 and 20.

N. 0° 11.8' E., on the N-S centerline of section 17.

40.025 Point for the center 1/4 section corner of section 17, at intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 23 inches in the ground, with magnet at the base, in a mound of stone, 4 feet base, to brass cap marked:

T40S R26E  
C 1/4 S17  
2009

Set a steel fence post west of stainless steel post.

Corner is located on a bench, on the southwest side of a mesa, midway between top and bottom of the mesa.

80.026 The 1/4 section corner of sections 8 and 17.

---

From the 1/4 section corner of sections 16 and 17.

N. 89° 59.7' W., on the E-W centerline of section 17.

40.070 The center 1/4 section corner of section 17.

52.750 Intersect the centerline of San Juan County Road 401, a paved road, 27 feet wide, extending N. 5° W. and S. 5° E.

79.916 The 1/4 section corner of sections 17 and 18.

THE SUBDIVISION OF SECTION 18  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

---

The Subdivision of Section 18,  
T. 40 S., R. 26 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 18 and 19.

**N. 0° 03.7' E.**, on the N-S centerline of section 18.

**39.991** Point for the center 1/4 section corner of section 18, at intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with magnet at the base, in a collar of stone, 2 feet diameter, with brass cap marked:

T40S R26E  
C 1/4 S18  
2009

Set a steel fence post southeast of stainless steel post.

Corner is located on a gentle, east-facing slope, with sparse vegetation.

**79.997** The 1/4 section corner of sections 7 and 18.

---

From the 1/4 section corner of sections 17 and 18.

**S. 89° 59.9' W.**, on the E-W centerline of section 18.

**40.080** The center 1/4 section corner of section 18.

**80.072** The 1/4 section corner of sections 13 and 18, on the West boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, flush with the top of a mound of stone, 6 feet base, 1 1/2 feet high, with brass cap marked as described in the official record of the 2004 resurvey of T. 40 S., R. 25 E.

---

The Subdivision of Section 19,  
T. 40 S., R. 26 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 19 and 30.

**N. 0° 07.6' W.**, on the N-S centerline of section 19.

**40.426** Point for the center 1/4 section corner of section 19, at intersection with the E-W centerline.

THE SUBDIVISION OF SECTION 19  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at the base, with brass cap marked:

T40S R26E  
C 1/4 S19  
2009

Set a steel fence post north of the stainless steel post.

Corner is located on gently-rolling ground, with sparse vegetation.

64.440 Intersect the centerline of San Juan County Road 402, a paved road, 30 feet wide, extending N. 82° W. and S. 82° E.

80.423 The 1/4 section corner of sections 18 and 19.

---

From the 1/4 section corner of sections 19 and 20.

S. 89°55.7' W., on the E-W centerline of section 19.

40.022 The center 1/4 section corner of section 19.

80.042 The 1/4 section corner of sections 19 and 24, on the West boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, flush with the top of a mound of stone, 4 feet base, with brass cap marked as described in the official record of the 2004 resurvey of T. 40 S., R. 25 E.

---

The Subdivision of Section 20,  
T. 40 S., R. 26 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 20 and 29.

N. 0° 06.6' W., on the N-S centerline of section 20.

40.342 Point for the center 1/4 section corner of section 20, at intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with magnet at the base, in a collar of stone, 2 feet diameter, with brass cap marked:

T40S R26E  
C 1/4 S20  
2009

Set a steel fence post north of stainless steel post.

THE SUBDIVISION OF SECTION 20  
T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located in rolling, rocky ground, with scattered desert grasses.

50.390 Intersect the centerline of San Juan County Road 402, a paved road, 30 feet wide, extending N. 80° E. and S. 80° W.

79.768 The 1/4 section corner of sections 17 and 20.

---

From the 1/4 section corner of sections 20 and 21.

S. 89° 18.1' W., on the E-W centerline of section 20.

38.758 The center 1/4 section corner of section 20.

78.572 The 1/4 section corner of sections 19 and 20.

---

The Subdivision of Section 21,  
T. 40 S., R. 26 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 21 and 28.

N. 0° 07.1' E., on the N-S centerline of section 21.

40.283 Point for the center 1/4 section corner of section 21, at intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with magnet at the base, with brass cap marked:

T40S R26E  
C 1/4 S21  
2009

Set a steel fence post north of stainless steel post.

Corner is located on the floodplain of the right bank of McElmo Creek, in sandy soil, with tamarisk trees.

79.695 The 1/4 section corner of sections 16 and 21.

---

From the 1/4 section corner of sections 21 and 22.

N. 89° 18.5' W., on the E-W centerline of section 21.

39.965 The center 1/4 section corner of section 21.

81.269 The 1/4 section corner of sections 20 and 21.

---

## T. 40 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

GENERAL DESCRIPTION

---

Township 40 South, Range 26 East lies within the boundaries of the Navajo Reservation. Most land is tribal, with some privately owned lands in the northern half. There are no major settlements within the township, but residences are scattered throughout. The topography ranges from fairly level mesa tops capping steep to moderate slopes composed of low sandstone cliffs and ledges, with sand, clay, and bedrock talus on the more moderate slopes. These slopes drop down to broad, level valley bottoms formed in shale, clay, or deep sandy soils. McElmo Creek flows from the northeast corner of the township to the southwest corner, in a shallow sandstone canyon with a narrow sandy floodplain.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Names	Capacity
Phil Freiberg	Surveying Technician

---

## CERTIFICATE OF SURVEY

I, **Scott A. Burkhardt, Cadastral Surveyor**, hereby certify upon honor that, in pursuance of Special Instructions bearing the date of the 12th day of May, 2009, I have executed the dependent resurvey of a portion of the Utah-Colorado State Boundary Line, from Mile Post 18 to Mile Post 24, the north boundary, and the subdivisional lines, and the subdivision of sections 5, 6, 7, 8, 9, 10, 15, 17, 18, 19, 20, and 21 in Township 40 South, Range 26 East, of the Salt Lake Meridian, Utah, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 20, 2010

Date

Scott A. Burkhardt

(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the dependent resurvey of a portion of the Utah-Colorado State Boundary Line, from Mile Post 18 to Mile Post 24, the north boundary, and the subdivisional lines, and the subdivision of sections 5, 6, 7, 8, 9, 10, 15, 17, 18, 19, 20, and 21 in Township 40 South, Range 26 East, of the Salt Lake Meridian, Utah, executed by Scott A. Burkhardt, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

September 29, 2010

Date

Daniel W. Webb

(Chief Cadastral Surveyor for Utah)