

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH BOUNDARY,

AND

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 15, 21, 22, 27, 28, 33, AND 34,

IN

TOWNSHIP 9 SOUTH, RANGE 19 WEST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Ronald K. Batty
Cadastral Surveyor

Under Special Instructions dated *September 10, 2010*, approved *September 10, 2010*, which provided for the surveys included under Group Number *1136*, and Assignment Instructions dated *September 10, 2010*, and Reassignment Instructions dated *February 14, 2011*.

Survey Commenced, *September 16, 2010*
Survey Completed, *April 27, 2011*

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH BOUNDARY,

AND

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 15, 21, 22, 27, 28, 33, AND 34,

IN

TOWNSHIP 9 SOUTH, RANGE 19 WEST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Ronald K. Batty
Cadastral Surveyor

Under Special Instructions dated *September 10, 2010*, approved *September 10, 2010*, which provided for the surveys included under Group Number *1136*, and Assignment Instructions dated *September 10, 2010*, and Reassignment Instructions dated *February 14, 2011*.

Survey Commenced, *September 16, 2010*
Survey Completed, *April 27, 2011*

INDEX DIAGRAM

Township 9 South, Range 19 West.

6	5	4	3	2	1
7	8	9	10	11	12
		19	14		
18	17	19 16	13 15	7 14	13
		19	12		
19	20	18 21	11 22	6 23	24
	20	17	10		
30	29	16 28	9 27	5 26	25
		16	9		
31	32	15 33	8 34	5 35	36
		4	3		

The Subdivision of Section 15.....21
 The Subdivision of Section 21.....23
 The Subdivision of Section 22.....24
 The Subdivision of Section 27.....27
 The Subdivision of Section 28.....27
 The Subdivision of Section 33.....28
 The Subdivision of Section 34.....31

TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

The following field notes are those of the dependent resurvey of a portion of the south boundary, and a portion of the subdivisional lines, and the subdivision of sections 15, 21, 22, 27, 28, 33, and 34, in T. 9 S., R. 19 W., Salt Lake Meridian, Utah.

HISTORY OF SURVEYS

Surveyed by		Retr. or Resurveyed by	
DEEP CREEK INDIAN RESERVATION			
All	J. Clark	1865	
SOUTH BOUNDARY			
All	J. Gorlinski	1875	
EAST BOUNDARY			
All	J. Gorlinski	1875	
All		T. C. Bailey	1882
All		C. P. Sylvester	1962
WEST BOUNDARY			
All	J. Gorlinski	1875	
Portion		T. C. Bailey	1882
NORTH BOUNDARY			
Portion	J. Gorlinski	1875	
All	T. C. Bailey	1882	1882
Portion		L. V. Judd	1993
SUBDIVISION			
Portion	J. Gorlinski	1875	
Portion	T. C. Bailey	1882	1882

TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 1136, dated September 10, 2010.

The directions of the lines were determined by references to true meridian, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods*, dated Feb 23, 2009, Version 1.0. Trimble model 5800 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from GPS static observations, post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS); EGAN_BRGN_NV1996, GOSH_BRGN_UT1996, KNOLLSWESTUT2006.

The geographic position of the corner of sections 26, 27, 34, and 35, as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: 40°00'26.956" N.,
Longitude: 113°57'52.961" W., N.A.D. 83,
Network Accuracy = 0.200 meter at 95% confidence

The geographic position of the corner of sections 8, 9, 16, and 17, as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: 40°03'03.318" N.,
Longitude: 114°00'08.365" W., N.A.D. 83,
Network Accuracy = 0.200 meter at 95% confidence

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY OF
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Resurvey of a Portion of the South Boundary of
Township 9 South, Range 19 West, Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by J. Gorlinski in 1875.

Beginning at the section corner of sections 2, 3, 34, and 35, on the south boundary of the township, monumented with a limestone, 17x12x3 inches, firmly set, marked with 2 notches on the east and 4 notches on the west with a 1 1/2 inch pipe, 1 foot north, projecting 16 inches above the ground.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with the aluminum cap marked:

T9S R19W	
S34	S35
S3	S2
T10S	
2010	

Deposit marked stone on the west side of the corner.

N. 89°57.9' W., between sections 3 and 34 on the south boundary of the township.

- 40.148 The 1/4 section corner of sections 3 and 34, monumented with a limestone, 15x8x7 inches, firmly set, and marked 1/4 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with the aluminum cap marked:

T9S R19W	
S34	
1/4	-----
S3	
T10S	
2010	

Deposit the marked stone alongside the west side of the corner.

N. 89°55.8' W., beginning new measurement.

- 20.045 The W 1/16 section corner of sections 3 and 34, monumented with a 5/8 inch diameter rebar, set in concrete, with a steel fence post alongside. This position is accepted as a faithful establishment of the corner position.

S. 89°58.4' W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY OF
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

- 20.075 The corner of sections 3, 4, 33, and 34, monumented with a steel fence post. This position is harmoniously related to existing original corners, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with the aluminum cap marked:

T9S R19W	
S33	S34
S4	S3
T10S	
2010	

Reset the steel fence post alongside the corner.

Corner falls in a cow pasture.

N. 89°56.9' W., between sections 4 and 33, on the south boundary of the township.

- 40.116 The 1/4 section corner of sections 4 and 33, monumented with a 5/8 inch rebar with a steel fence post alongside, set in concrete. This position is harmoniously related to existing original corners, and is accepted as the best available evidence of the original corner position. No evidence remains of the original monumentation.

N. 89°56.8' W., beginning new measurement.

- 20.061 The W 1/16 section corner of sections 4 and 33, monumented with a 5/8 inch rebar, firmly set in concrete with a steel fence post set alongside. This position is accepted as a faithful establishment of the corner position.

Corner falls in a fence extending north and south. A fence corner extending north and west is 2 feet south of the corner.

N. 89°57.4' W., beginning new measurement.

- 20.058 The corner of sections 4, 5, 32, and 33, monumented with a basalt stone, 14x8x7 inches, loosely set, marked 2 notches on the west and 4 notches on the east edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY OF
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T9S R19W
S32 | S33
S5 | S4
2010

Deposit the marked stone along the northwest side of the corner.

Dependent Resurvey of a Portion of the Subdivisional Lines of
Township 9 South, Range 19 West, Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by J. Gorlinski in 1875.

From the corner of sections 2, 3, 34, and 35, on the south
boundary of the township, hereinbefore described.

N. 0°03.7' W., between sections 34 and 35.

- 40.042 The 1/4 section corner of sections 34 and 35, monumented with a
limestone, 13x8x4 inches, firmly set, marked 1/4 on the west
face, with a cedar post, 2 inches diameter, 4 1/4 feet long, with
a metal tag attached.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with
magnet at base, 28 inches in the ground, with the aluminum cap
marked:

T9S R19W
1/4
S34 | S35
2010

Deposit the marked stone along the west side of the corner.

N. 0°13.0' W., beginning new measurement.

- 40.035 The corner of sections 26, 27, 34, and 35, monumented with a
limestone, 16x14x6 inches, firmly set, marked with 2 notches on
the east side and 1 notch on the south edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with
magnet at base, 26 inches in the ground, with the aluminum cap
marked:

T9S R19W
S27 | S26
S34 | S35
2010

Deposit the marked stone along the west side of the corner.

N. 0°08.1' E., between sections 26 and 27.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

- 39.883 The 1/4 section corner of sections 26 and 27, monumented with a blue limestone 15x9x6 inches, firmly set, marked 1/4 on the west face, with an old cedar post, 5 inches diameter, set alongside with the metal tag attached at a point 6 feet above the ground. At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W
1/4
S27 | S26
2010

Deposit the marked stone alongside the corner.

N. 0°01.4' E., beginning new measurement.

- 39.896 The corner of sections 22, 23, 26, and 27, monumented with a limestone, 16x12x6 inches, firmly set, and marked 2 notches on the east and south edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 18 inches in the ground to solid rock, in a mound of stone, 3 feet base, 10 inches high, with the aluminum cap marked:

T9S R19W
S22 | S23
S27 | S26
2010

Deposit the marked stone alongside the corner.

N. 0°03.9' E., between sections 22 and 23.

- 39.970 The 1/4 section corner of sections 22 and 23, monumented with a limestone, 12x7x6 inches, firmly set in a small mound of stone, marked 1/4 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with the aluminum cap marked:

T9S R19W
1/4
S22 | S23
2010

Deposit the marked stone along the west side of the corner.

An electrical line, extending east and west, is 15 links north of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

N. 0°04.0' E., beginning a new measurement.

- 39.978 The corner of sections 14, 15, 22, and 23, monumented with a limestone, 14x12x6 inches, marked 3 notches on the south, and 2 notches on the east, firmly set, with a steel fence post 2 feet east of the corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with the aluminum cap marked:

T9S R19W	
S15	S14
S22	S23
2010	

Deposit the marked stone alongside the corner.

N. 0°05.8' E., between sections 14 and 15.

- 39.900 The 1/4 section corner of sections 14 and 15, monumented with a limestone, 14x10x5 inches, firmly set, projecting 8 inches above the ground, plainly marked 1/4 on the west face, with a steel fence post alongside.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W	
1/4	
S15	S14
2010	

Deposit the marked stone alongside the corner.

N. 0°05.6' E., beginning new measurement.

- 40.166 The corner of sections 10, 11, 14, and 15, monumented with a limestone, 13x8x7 inches, firmly set, projecting 5 inches above the ground, plainly marked with 4 notches on the south edge and 2 notches on the east edge, with the steel fence post alongside the corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T9S R19W
S10 | S11
S15 | S14
2010

Deposit the marked stone alongside the corner.

From the corner of sections 3, 4, 33, and 34, on the south boundary of the township, hereinbefore described.

N. 0°07.2' W., between sections 33 and 34.

19.965 Point for the S 1/16 section corner of sections 33 and 34. Not monumented.

39.930 The 1/4 section corner of sections 33 and 34, monumented with a granite stone, 9x8x6 inches, loosely set in a scattered mound of stone, dimly marked.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W
1/4
S33 | S34
2010

Deposit the marked stone alongside the corner.

N. 0°01.7' E., beginning new measurement.

19.982 Point for the N 1/16 section corner of sections 33 and 34.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W
N 1/16
S33 | S34
2010

Set a steel fence post alongside the corner.

39.964 The corner of sections 27, 28, 33, and 34, monumented with a limestone, 14x7x5 inches, firmly set, projecting 8 inches above the ground, plainly marked with 3 notches on the east edge and 1 notch on the south edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T9S R19W	
S28	S27
S33	S34
2010	

Deposit the marked stone alongside the corner. Set a steel fence post alongside the corner.

Corner is northeast of a power pole for three power lines extending northwest, southeast, and west.

From the corner of sections 26, 27, 34, and 35.

S. 89°40.7' W., between sections 27 and 34.

- 40.267 The 1/4 section corner of sections 27 and 34, monumented with a broken limestone, with 1 piece clearly marked 1/4, in a scattered mound of stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W	
S27	
1/4	_____
S34	
2010	

Deposit the marked stone alongside the corner. Set a steel fence post alongside the corner.

Corner is 5 feet west of a barbed wire fence extending north-northeast and south-southwest.

N. 89°52.8' W., beginning new measurement.

- 19.927 Point for the W 1/16 section corner of sections 27 and 34.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W	
S27	
W1/16	_____
S34	
2010	

Corner is 115 feet east of a barbed wire fence, bears northeast and southwest.

- 39.854 The corner of sections 27, 28, 33, and 34.
-

N. 2°32.6' E., between sections 27 and 28.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

- 40.142 The 1/4 section corner of sections 27 and 28, monumented with a limestone, 12x7x5 inches, loosely set, plainly marked 1/4, broken in 2 pieces.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W
1/4
S28 | S27
2010

Deposit the marked stone alongside the corner.

N. 2°25.1' W., beginning new measurement.

- 39.886 The corner of sections 21, 22, 27, and 28, monumented with a limestone, 16x8x6 inches, firmly set, marked with 3 notches on the east edge and 2 notches on the south edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W
S21 | S22
S28 | S27
2010

Deposit the marked stone along the west side of the corner.

From the corner of sections 22, 23, 26, and 27.

N. 89°58.6' W., between sections 22 and 27.

- 40.058 Point for the 1/4 section corner of sections 22 and 27, at proportionate distance. Point falls on the west edge of BIA Highway 1, there is no remaining evidence of the original corner.

Set a railroad spike.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 26 inches in the ground, over a magnet, for a reference monument, bears S. 41°28.5' W., 36.5 links distance, with aluminum cap marked, RM1 24.1 FT TO 1/4 COR S27 2010, and an arrow pointing to corner.

Corner is alongside a wood post for a highway R.O.W. fence, bears north and south.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 26 inches in the ground, over a magnet, for a reference monument, bears N. 49°13.0' W., 33.7 links distance, with aluminum cap marked, RM2 22.2 FT TO 1/4 COR S22 2010, and an arrow pointing to the corner.

Corner is alongside a wood post for a highway R.O.W. fence, bears north and south.

60.087 Point for the W 1/16 section corner of sections 22 and 27.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W
S22
W1/16 ———
S27
2010

Set a steel fence post alongside.

A fence post in a barbed wire fence extending north, south, east, and west, bears N. 65° E., 15 links distance.

80.116 The corner of sections 21, 22, 27, and 28.

N. 0°02.8' E., between sections 21 and 22.

20.045 Point for the S 1/16 section corner of sections 21 and 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 27 inches in the ground, with the aluminum cap marked:

T9S R19W
S 1/16
S21 | S22
2010

A barbed wire fence extending north and south is 3 links east of the corner.

40.090 Point for the 1/4 section corner of sections 21 and 22, determined at the corner of an ancient barbed wire fence, extending west and south. This position is harmoniously related to existing original corners, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 27 inches in the ground, in a collar of stone, with the aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T9S R19W
1/4
S21 | S22
2010

N. 0°06.6' W., beginning new measurement.

- 40.191 Point for the corner of sections 15, 16, 21, and 22, at proportionate distance. Point falls on the west edge of BIA Highway 1, there is no remaining evidence of the original corner.

At corner point

Set a 6 inch railroad spike.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 26 inches in the ground, over a magnet, for a reference monument, bears N. 32°33.3' E., 84.4 links distance, with an aluminum cap marked: RM T9S R19W S15 55.73 FT 2011, and an arrow pointing to the corner.

A USGS 4 inches diameter tablet, set in a granite stone, marked "BM P26 1924" bears N. 85°39.5' E., 66.7 links distance.

From the corner of sections 14, 15, 22, and 23.

N. 89°44.9' W., between sections 15 and 22.

- 40.137 The 1/4 section corner of sections 15 and 22, monumented with a limestone, 12x8x4 inches, marked 1/4 on the north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with the aluminum cap marked:

T9S R19W
S15
1/4 ———
S22
2010

Deposit the marked stone along the west side of corner. Set a steel fence post on the north side of the corner.

N. 89°43.5' W., beginning new measurement.

- 20.049 Point for the W 1/16 section corner of sections 15 and 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

marked:

T9S R19W
S15
W 1/16 —————
S22
2011

Set a steel fence post alongside the corner.

A fence post in a barbed wire fence extending north, south, east, and west bears N. 65° E., 15 links distance.

40.098 The corner of sections 15, 16, 21, and 22.

N. 0°07.6' E., between sections 15 and 16.

20.096 Point for the S 1/16 section corner of sections 15 and 16. Point falls on BIA Highway 1.

Set a 4 inch railroad spike.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 26 inches in the ground, over a magnet, for a reference monument, bears S. 44°38.3 W., 66.1 links distance, with an aluminum cap marked, RM T9S R19W 43.67 FT S16 2011, and an arrow pointing to the corner

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 26 inches in the ground, over a magnet, for a reference monument, bears N. 43°01.6' W., 69.4 links distance, with the aluminum cap marked, RM T9S R19W 45.89 FT S16 2011, and an arrow pointing to the corner.

Both reference monuments are situated in a right-of-way fence line which extends north and south and is situated on the west side of BIA Highway 1.

40.192 Point for the 1/4 section corner of sections 15 and 16, at proportionate measurement. There is no remaining evidence of the original corner. Point falls in the middle of BIA Highway 1.

Set a 6 inch railroad spike.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 26 inches in the ground, over a magnet, for a reference monument, bears S. 56°14.2' W., 60.5 links distance, with the aluminum cap marked, RM T9S R19W 39.94 FT S16 2011, and an arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 26 inches in the ground, over a magnet, for a reference

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

monument, bears N. 33°52.4 W., 90.2 links distance, with the aluminum cap marked, RM T9S R19W 59.55 FT S16 2011, and an arrow pointing to the corner.

Both reference monuments are located in a right-of-way fence which extends north and south and is situated on the west side of BIA Highway 1.

- 60.288 Point for the N 1/16 section corner of sections 15 and 16. Not monumented.
- 70.336 Point for the N-N 1/64 section corner of sections 15 and 16. Not monumented.
- 80.384 The corner of sections 9, 10, 15, and 16, determined at the corner of a barbed wire fence extending north, south and west. This position is harmoniously related to existing original corners, and is accepted as the best available evidence of the original corner position.

At corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W	
S9	S10
S16	S15
2011	

Corner is situated on the west edge of the BIA Highway 1.

From the corner of sections 10, 11, 14, and 15.

N. 89°52.5' W., between sections 10 and 15.

- 40.096 The 1/4 section corner of sections 10 and 15, monumented with a sandstone, 15x6x5 inches, firmly set, projecting 7 inches above the ground, marked 1/4 on the north face, with a steel fence post alongside.

At corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with the aluminum cap marked:

T9S R19W	
S10	
1/4	-----
S15	
2010	

Deposit the marked stone alongside the corner.

N. 89°08.3' W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

20.040 Point for the W 1/16 section corner of sections 10 and 15. Not monumented.

30.060 Point for the W-W 1/64 section corner of sections 10 and 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, with the aluminum cap marked:

T9S R19W
S10
W-W 1/64 —————
S15
2011

Set a T-post on the NE side of corner.

40.080 The corner of sections 9, 10, 15, and 16.

From the corner of sections 4, 5, 32, and 33 on the south boundary of the township, hereinbefore described.

N. 0°01.6' E., between sections 32 and 33.

19.965 Point for the S 1/16 section corner of sections 32 and 33. Not monumented.

39.930 The 1/4 section corner of sections 32 and 33, monumented with a basalt stone 13x7x5 inches, firmly set, and marked 1/4 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W
1/4
S32 | S33
2010

Deposit the marked stone along the west side of the corner.

N. 0°05.6' E., beginning new measurement.

20.004 Point for the N 1/16 section corner of sections 32 and 33. Not monumented.

40.008 The corner of sections 28, 29, 32, and 33, monumented with a basalt stone, 14x8x7 inches, firmly set, marked with 4 notches on the east edge and 1 notch on the south edge.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with the aluminum cap marked:

T9S R19W	
S29	S28
S32	S33
2010	

Deposit the marked stone along the west side of the corner.

From the corner of sections 27, 28, 33, and 34.

N. 89°55.2' W., between sections 28 and 33.

20.017 Point for the E 1/16 section corner of sections 28 and 33.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

	S28
E 1/16	—————
	S33
	2010

Set a steel fence post along side.

Corner is located under a barbed wire fence extending north and south.

40.034 Point for the 1/4 section corner of sections 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W	
	S28
1/4	—————
	S33
	2010

Set a steel fence post alongside the corner.

A new barbed wire fence extending north and south is 15 links west of the corner.

60.051 Point for the W 1/16 section corner of sections 28 and 33. Not monumented.

80.068 The corner of sections 28, 29, 32, and 33.

N. 0°02.9' E., between sections 28 and 29.

40.023 Point for the 1/4 section corner of sections 28 and 29,

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

monumented with a basalt stone, 15x7x6 inches, firmly set in a fence corner extending north, south and east, marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with the aluminum cap marked:

T9S R19W
1/4
S29 | S28
2010

Deposit the stone along the northwest side of the corner.

A power line extending north and south is 3 links east of the corner.

N. 0°01.5' W., beginning new measurement.

39.990 Point for the corner of sections 20, 21, 28, and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 25 inches in the ground, with the aluminum cap marked:

T9S R19W
S20 | S21
S29 | S28
2011

Corner is located in a flat open area. A fence extending east and west is approximately 6 links south of the corner.

From the corner of sections 21, 22, 27, and 28.

N. 89°52.6' W., between sections 21 and 28.

20.033 Point for the E 1/16 section corner of sections 21 and 28.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W
S21
E 1/16 ———
S28
2011

40.066 Point for the 1/4 section corner of sections 21 and 28, at proportionate distance; there is no remaining evidence of the original corner. Point falls in the middle of a hay field. Not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

80.132 The corner of sections 20, 21, 28, and 29.

N. 0°12.8' E., between sections 20 and 21.

19.996 The S 1/16 section corner of sections 20 and 21.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with the aluminum cap marked:

T9S R19W
S 1/16
S20 | S21
2011

Corner is located on the east edge of a 2-track road bearing north and south. A juniper post is approximately 3 links south of the corner.

39.992 The 1/4 section corner of sections 20 and 21, monumented with a basalt stone, 16x10x8 inches, firmly set in a small mound of stone, marked 1/4 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with the aluminum cap marked:

T9S R19W
1/4
S20 | S21
2010

Deposit the marked stone along the west side of the corner. Set a steel fence post alongside the corner.

N. 0°04.3' W., beginning new measurement.

39.850 The corner of sections 16, 17, 20, and 21, monumented with a basalt stone, 17x7x6 inches, marked 4 notches on the east edge and 3 notches on the south edge, in a four strand barbed wire fence extending north and south.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with the aluminum cap marked:

T9S R19W
S17 | S16
S20 | S21
2010

Deposit the marked stone along the northeast side of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

From the corner of sections 15, 16, 21, and 22.

S. 89°48.4' W., between sections 16 and 21.

39.987 Point for the 1/4 section corner of sections 16 and 21, at proportionate distance, there is no remaining evidence of the original corner. Point is located in the middle of a hay field. Not monumented at request of the land owner.

79.974 The corner of sections 16, 17, 20, and 21.

N 0°16.2' E., between sections 16 and 17.

40.068 The 1/4 section corner of section 16, monumented with a flint stone, 12x7x7 inches, loosely set, plainly marked 1/4 on the west face, in a barbed wire fence extending north and south.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with the aluminum cap marked:

T9S R19W
1/4
S17 | S16
2010

Deposit the marked stone alongside the corner.

N. 0°17.4' E., beginning new measurement.

39.903 The corner of sections 8, 9, 16, and 17, monumented with a flint stone, 17x7x7 inches, loosely set in a scattered mound of stone, plainly marked with 4 notches on east edge and 4 notches on the south edge.

At the corner point

Set an aluminum post, 30 inches long 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W
S8 | S9
S17 | S16
2010

Deposit the marked stone alongside the corner.

Corner is located at the intersection of fences extending north, south, and east.

From the corner of sections 9, 10, 15, and 16.

S. 89°30.3' W., between sections 9 and 16.

39.873 Point for the 1/4 section corner of sections 9 and 16, at

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 25 inches in the ground, with the aluminum cap marked:

T9S R19W
S9
1/4 —————
S16
2011

Corner is located on the south edge of a fence line extending east and west.

79.746 The corner of sections 8, 9, 16, and 17.

From the corner of sections 20, 21, 28, and 29.

N. 89°39.7' W., between sections 20 and 29.

20.039 Point for the E 1/16 section corner of sections 20 and 29.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, with the aluminum cap marked:

T9S R19W
S20
E 1/16 —————
S29
2011

Set a steel fence post on the northwest side of the corner.

40.078 The 1/4 section corner of sections 20 and 29, monumented with a lava stone, 12x10x6 inches, marked 1/4 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with the aluminum cap marked:

T9S R19W
S20
1/4 —————
S29
2010

Deposit the marked stone along the west side of the corner. Set a steel fence post 1 foot west of the corner.

THE SUBDIVISION OF SECTION 15,
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

The Subdivision of Section 15,
Township 9 South, Range 19 West, Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 15 and 22.

N. 0°07.1' E., along the N-S centerline of sections 15.

20.028 Point for the center S 1/16 section corner of section 15. Not monumented.

40.056 Point for the center 1/4 section corner, at the intersection with the E-W centerline of section 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W
C1/4 S15
2010

Corner is located on an elevated flat. A two track road is approximately 40 links east of the corner.

60.017 Point for the center N 1/16 section corner of sections 15. Not monumented.

79.978 The 1/4 section corner of sections 10 and 15.

From the 1/4 section corner of sections 14 and 15.

N. 89°31.6' W., along the E-W centerline of section 15.

40.118 The center 1/4 section corner of section 15.

60.162 Point for the center W 1/16 section corner of section 15. Not monumented.

80.206 The 1/4 section corner of sections 15 and 16.

From the W 1/16 section corner of sections 15 and 22.

N. 0°07.3' E., along the N-S centerline of the SW 1/4 of section 15.

20.062 Point for the SW 1/16 section corner, at the intersection with the E-W centerline of the SW 1/4 of section 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 27 inches in the ground, with the aluminum cap marked:

THE SUBDIVISION OF SECTION 15,
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T9S R19W
SW1/16 S15
2010

Set a steel fence post on the north side of the corner.

A dirt road bearing west and southeast, is 24 links south of the corner. A railroad tie set at the intersection of fences extending west and south is approximately 1 chain west of the corner.

40.124 The point for the center W 1/16 section corner of section 15.

From the point for the center S 1/16 section corner of section 15.

N. 89°37.6' W., along the E-W centerline of the SW 1/4 of section 15.

20.047 The SW 1/16 section corner of section 15.

40.094 The S 1/16 section corner of sections 15 and 16.

From the point for the center W 1/16 section corner of section 15.

N. 0°07.3' E., along the N-S centerline of the NW 1/4 of section 15.

20.029 Point for the NW 1/16 section corner, at the intersection with the E-W centerline of the NW 1/4 of section 15. Not monumented.

30.043 Point for the center N-NW 1/64 section corner of section 15. Not monumented.

40.057 The point for the W 1/16 section corner of sections 10 and 15.

From the point for the center N 1/16 section corner of section 15.

N. 89°19.9' W., along the E-W centerline of the NW 1/4 of section 15.

20.042 The point for the NW 1/16 section corner of section 15.

30.063 Point for the center W-NW 1/64 section corner of section 15. Not monumented.

40.084 The point for the N 1/16 section corner of sections 15 and 16.

From the point for the center W-NW 1/64 section corner of section 15.

THE SUBDIVISION OF SECTION 15,
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

N. 0°07.4' E., along the N-S centerline of the NW 1/4 of the NW 1/4 of section 15.

- 10.031 Point for the NW-NW 1/64 section corner, at the intersection with the E-W centerline of the NW 1/4 of the NW 1/4 of section 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W
NW-NW 1/64 S15
2011

Set a T-post on the southeast side of corner.

- 20.062 The W-W 1/64 section corner of sections 10 and 15.

From the point for the center N-NW 1/64 section corner of section 15.

N. 89°14.1' W., along the E-W centerline of the NW 1/4 of the NW 1/4 of section 15.

- 10.021 The NW-NW 1/64 section corner of section 15.

- 20.042 The point for the N-N 1/64 section corner of sections 15 and 16.

The Subdivision of Section 21,
Township 9 South, Range 19 West, Salt Lake Meridian, Utah.

From the point for the 1/4 section corner of sections 21 and 28.

N. 0°01.2' E., along the N-S centerline of section 21.

- 20.020 Point for the center S 1/16 section corner of section 21. Not monumented.

- 40.040 Point for the center 1/4 section corner, at the intersection with the E-W centerline of section 21.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W
C 1/4 S21
2011

Set a steel fence post on the south side.

- 80.062 The point for the 1/4 section corner of sections 16 and 21.

From the 1/4 section corner of sections 21 and 22.

THE SUBDIVISION OF SECTION 21,
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

N. 89°56.8' W., along the E-W centerline of section 21.

- 20.041 Point for the center E 1/16 section corner of section 21. Not monumented.
- 40.082 The center 1/4 section corner of section 21.
- 80.009 The 1/4 section corner of sections 20 and 21.

From the E 1/16 section corner of sections 21 and 28.

N. 0°02.0' E., along the N-S centerline of the SE 1/4 of section 21.

- 20.033 Point for the SE 1/16 section corner, at the intersection with the E-W centerline of the SE 1/4 of section 21.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 27 inches in the ground, with the aluminum cap marked:

T9S R19W
SE 1/16 S21
2011

Set a steel fence post alongside the corner.

Corner is located in an open field. An irrigations ditch is approximately 30 links east of the corner. An old barbed wire fence is approximately 2.5 chains east of the corner.

- 40.066 The point for the center E 1/16 section corner of section 21.

From the S 1/16 section corner of sections 21 and 22.

N. 89°54.7' W., along the E-W centerline of the SE 1/4 of section 21.

- 20.037 The SE 1/16 section corner of sections 21.
- 40.074 The point for the center S 1/16 section corner of section 21.

The Subdivision of Section 22,
Township 9 South, Range 19 West, Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 22 and 27.

N. 0°00.2' E., along the N-S centerline of section 22.

- 20.015 Point for the center S 1/16 section corner of section 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with the aluminum cap marked:

THE SUBDIVISION OF SECTION 22,
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T9S R19W
C
S 1/16 | S22
C
2010

Set a steel fence post alongside the corner.

Corner is located at the bottom of a fill slope for the highway.

- 40.030** Point for the center 1/4 section corner of section 22, at the intersection with the E-W centerline of section 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W
C 1/4 S22
2010

Set a steel fence post alongside the corner.

A trailer pad is 60.6 links west of the corner.

- 80.107** The 1/4 section corner of sections 15 and 22.
-

From the 1/4 section corner of sections 22 and 23.

N. 89°53.5' W., along the E-W centerline of section 22.

- 40.097** The center 1/4 section corner of section 22.

- 60.108** Point for the center W 1/16 section corner of section 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 27 inches in the ground, with the aluminum cap marked:

W 1/16
C ————— C
S22
2010

Corner is located in a barbed wire fence extending east and west. A fence intersection extending north, south, and east, is 1.21 chains east of the corner.

- 80.119** The 1/4 section corner of sections 21 and 22.
-

From the W 1/16 section corner of sections 22 and 27.

N. 0°01.5' E., along the N-S centerline of the SW 1/4 of section 22.

- 20.030** Point for the SW 1/16 section corner, at the intersection with the E-W centerline of the SW 1/4 of section 22.

THE SUBDIVISION OF SECTION 22,
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

SW 1/16 S22
2010

Set a steel fence post alongside the corner.

A fence intersection extending north, south, and east is 12.1 links northeast of the corner.

40.060 The center W 1/16 section corner of section 22.

From the center S 1/16 section corner of section 22.

N. 89°56.0' W., along the E-W centerline of the SW 1/4 of section 22.

20.020 The SW 1/16 section corner of section 22.

40.040 The S 1/16 section corner of sections 21 and 22.

From the center W 1/16 section corner of section 22.

N. 0°03.2' E., along the N-S centerline of the NW 1/4 of section 22.

40.134 The W 1/16 section corner of sections 15 and 22.

The Subdivision of Section 27,
Township 9 South, Range 19 West, Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 27 and 34.

N. 0°13.3' E., along the N-S centerline of section 27.

40.149 Point for the center 1/4 section corner, at the intersection with the E-W centerline of section 27.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum post marked:

T9S R19W
C 1/4 S27
2010

Set a steel fence post alongside.

The corner is located in a field.

80.022 The 1/4 section corner of sections 22 and 27.

From the 1/4 section corner of sections 26 and 27.

THE SUBDIVISION OF SECTION 27,
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

N. 89°56.6' W., along the E-W centerline of section 27.

40.200 The center 1/4 section corner of section 27.

59.312 Point for the center W 1/16 section corner of section 27.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with the aluminum cap marked:

W 1/16
C———C
S27
2010

Set a steel fence post alongside the corner.

A barbed wire fence extending north and south is approximately 60.6 links west.

78.424 The 1/4 section corner of sections 27 and 28.

From the W 1/16 section corner of sections 27 and 34.

N. 1°23.0' E., along the N-S centerline of the SW 1/4 of section 27.

40.138 The center W 1/16 section corner of section 27.

N. 1°05.9' W., along the N-S centerline of the NW 1/4 of section 27.

39.869 The W 1/16 section corner of sections 22 and 27.

The Subdivision of Section 28,
Township 9 South, Range 19 West, Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 28 and 33.

N. 0°02.5' E., along the N-S centerline of section 28.

40.063 Point for the center 1/4 section corner, at the intersection with the E-W centerline of section 28.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with the aluminum cap marked:

T9S R19W
C 1/4 S28
2011

Set a steel fence post on the north side of the corner.

79.983 The point for the 1/4 section corner of sections 21 and 28.

THE SUBDIVISION OF SECTION 28,
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

From the 1/4 section corner of sections 27 and 28.

N. 89°58.6' W., along the E-W centerline of section 28.

20.891 Point for the center E 1/16 section corner of section 28.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W
E 1/16
C———C
S28
2011

Corner is located on flat ground. A fence extending north and south is approximately 1.05 chains west of the corner.

41.782 The center 1/4 section corner of section 28.

81.807 The 1/4 section corner of section 28 and 29.

From the center E 1/16 section corner of section 28.

N. 1°11.3' W., along the N-S centerline of the NE 1/4 of section 28.

39.894 The E 1/16 section corner of sections 21 and 28.

From the E 1/16 section corner of sections 28 and 33.

N. 1°17.6' E., along the N-S centerline of the SE 1/4 of section 28.

40.093 The center E 1/16 section corner of section 28.

The Subdivision of Section 33,
Township 9 South, Range 19 West, Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 4 and 33 on the south boundary of the township, hereinbefore described.

N. 0°00.4' E., along the N-S centerline of section 33.

19.965 Point for the center S 1/16 section corner of section 33.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

THE SUBDIVISION OF SECTION 33,
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T9S R19W
C
S1/16 | S33
C
2011

- 39.930 Point for the center 1/4 section corner, at the intersection with the E-W centerline of section 33.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with the aluminum cap marked:

T9S R19W
C 1/4 S33
2011

- 59.923 Point for the center N 1/16 section corner of section 33.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W
C
N1/16 | S33
C
2011

- 79.916 The 1/4 section corner of sections 28 and 33.

From the 1/4 section corner of sections 33 and 34.

N. 89°57.0' W., along the E-W centerline of section 33.

- 20.012 Point for the center E 1/16 section corner of section 33.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W
E 1/16
C ——— C
S33
2011

- 40.024 The center 1/4 section corner of section 33.

- 60.074 Point for the center W 1/16 section corner of section 33.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 27 inches in the ground, with the aluminum cap marked:

THE SUBDIVISION OF SECTION 33,
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T9S R19W
W1/16
C ————— C
S33
2011

80.124 The 1/4 section corner of section 32 and 33.

From the center E 1/16 section corner of section 33.

N. 0°01.0' E., along the N-S centerline of the NE 1/4 of section 33.

19.988 Point for the NE 1/16 section corner, at the intersection with the E-W centerline of the NE 1/4 of section 33.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W
NE 1/16 S33
2011

39.976 The E 1/16 section corner of sections 28 and 33.

From the N 1/16 section corner of sections 33 and 34.

N. 89°56.1' W., along the E-W centerline of the NE 1/4 of section 33.

20.015 The NE 1/16 section corner of section 33.

40.030 The center N 1/16 section corner of section 33.

From the W 1/16 section corner of sections 4 and 33, on the south boundary of the township, hereinbefore described.

N. 0°01.1' E., along the N-S centerline of the SW 1/4 of section 33.

19.963 Point for the SW 1/16 section corner, at the intersection with the E-W centerline of the SW 1/4 of section 33.

Set an aluminum drive rod, 36 inches long, 3/4 inch diameter, 32 inches in the ground, with aluminum cap marked:

T9S R19W
SW 1/16 S33
2011

39.928 The center W 1/16 section corner of section 33.

THE SUBDIVISION OF SECTION 33,
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

From the center S 1/16 section corner of section 33.

N. 89°57.1' W., along the E-W centerline of the SW 1/4 of section 33.

20.055 The SW 1/16 section corner of section 33.

40.109 The point for the S 1/16 section corner of sections 32 and 33.

From the center W 1/16 section corner of section 33.

N. 0°03.0' E., along the N-S centerline of the NW 1/4 of section 33.

19.998 Point for the NW 1/16 section corner, at the intersection with the E-W centerline of the NW 1/4 of section 33.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W
NW 1/16 S33
2011

39.996 The point for the W 1/16 section corner of sections 28 and 33.

From the center N 1/16 section corner of section 33.

N. 89°56.1' W., along the E-W centerline of the NW 1/4 of section 33.

20.034 The NW 1/16 section corner of section 33.

40.068 The point for the N 1/16 section corner of sections 32 and 33.

The Subdivision of Section 34,
Township 9 South, Range 19 West, Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 3 and 34 on the south boundary of the township, hereinbefore described.

N. 0°13.8' W., along the N-S centerline of section 34.

19.991 Point for the center S 1/16 section corner of sections 34.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

C
S 1/16 | S34
C
2011

THE SUBDIVISION OF SECTION 34,
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Set a steel fence post alongside the corner, next to a rebar in concrete.

- 39.982** Point for the center 1/4 section corner, at the intersection with the E-W centerline of section 34.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W
C 1/4 S34
2011

- 79.827** Set a steel fence post alongside the corner.
The 1/4 section corner of sections 27 and 34.
-

From the 1/4 section corner of sections 34 and 35.

S. 89°56.9' W., along the E-W centerline of section 34.

- 40.262** The center 1/4 section corner of section 34.

- 60.281** Point for the center W 1/16 section corner of section 34.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

W 1/16
C ————— C
S34
2010

Set a steel fence post alongside the corner.

Corner is located in a barbed wire fence extending north and south.

- 80.300** The 1/4 section corner of sections 33 and 34.
-

From the W 1/16 section corner of sections 3 and 34 on the south boundary of the township, hereinbefore described.

N. 0°11.8' W., along the N-S centerline of the SW 1/4 of section 34.

- 19.961** Point for the SW 1/16 section corner, at the intersection with the E-W centerline of the SW 1/4 of section 34.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T9S R19W
SW 1/16 S34
2011

- 39.939** The center W 1/16 section corner of section 34.
-

THE SUBDIVISION OF SECTION 34,
TOWNSHIP 9 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

From the center S 1/16 section corner of section 34.

S. 89°59.1' W., along the E-W centerline of the SW 1/4 of section 34.

20.032 The SW 1/16 section corner of section 34.

40.079 The point for the S 1/16 section corner of sections 33 and 34.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Ronald K. Baugh	Supervisory Cadastral Surveyor
Richard B. West	Surveying Technician
Christopher May	Surveying Technician
Daniel T. Gillins	Cadastral Surveyor

CERTIFICATE OF SURVEY

I, **Ronald K. Batty, Cadastral Surveyor**, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing the date of **September 10, 2010**, I have **dependently resurveyed a portion of the south boundary, and a portion of the subdivisional lines, and surveyed the subdivisions of sections 15, 21, 22, 27, 28, 33, and 34, in Township 9 South, Range 19 West**, of the **Salt Lake Meridian**, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

JUNE 23, 2011

Date



Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the **dependent resurvey of a portion of the south boundary, and a portion of the subdivisional lines, and the subdivision of sections 15, 21, 22, 27, 28, 33, and 34, in Township 9 South, Range 19 West, Salt Lake Meridian, Utah**, executed by **Ronald K. Batty, Cadastral Surveyor**, having been critically examined and found correct, are hereby approved.

June 30, 2011

Date



Chief Cadastral Surveyor for Utah