

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE EAST AND NORTH BOUNDARIES,

AND

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 4, 5, 9, 10, 13, 14, AND 15,

IN

TOWNSHIP 2 SOUTH, RANGE 7 WEST,

OF THE UINTAH SPECIAL MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Ronald K. Batty
Cadastral Surveyor

Under Special Instructions dated **June 14, 2010**, approved **June 14, 2010**, which provided for the surveys included under Group Number **1139**, and Assignment Instructions dated **June 14, 2010**.

Survey Commenced, **June 14, 2010**
Survey Completed, **March 19, 2011**

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE EAST AND NORTH BOUNDARIES,

AND

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 4, 5, 9, 10, 13, 14, AND 15,

IN

TOWNSHIP 2 SOUTH, RANGE 7 WEST,

OF THE UINTAH SPECIAL MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Ronald K. Batty
Cadastral Surveyor

Under Special Instructions dated **June 14, 2010**, approved **June 14, 2010**, which provided for the surveys included under Group Number **1139**, and Assignment Instructions dated **June 14, 2010**.

Survey Commenced, **June 14, 2010**
Survey Completed, **March 19, 2011**

INDEX DIAGRAM

Township 2 South, Range 7 West.

		9	9	7	6
6	31 5	29 4	25 3	19 2	15 1 5
	30	28	24	19	14
7	8	27 9	22 10	17 11	13 12 4
	30	26	22	17	12
18	17	26 16	21 15	16 14	11 13 3
		25	21	15	10
19	20	21	20 22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

The Subdivision of Section 4.....	32
The Subdivision of Section 5.....	35
The Subdivision of Section 9.....	37
The Subdivision of Section 10.....	39
The Subdivision of Section 13.....	43
The Subdivision of Section 14.....	44
The Subdivision of Section 15.....	45

TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH.

The following field notes are those of the dependent resurvey of a portion of the east and north boundaries, and a portion of the subdivisional lines, and the subdivision of sections 4, 5, 9, 10, 13, 14, and 15, in T. 2 S., R. 7 W., Uintah Special Meridian, Utah.

HISTORY OF SURVEYS

	Surveyed by		Retr. or Resurveyed by	
SOUTH BOUNDARY				
All	A.J. Stewart & A.L. Booth	1903		
EAST BOUNDARY				
All	A.J. Stewart & A.L. Booth	1903		
Portion			R.L. Houston	1998
WEST BOUNDARY				
All	A.J. Stewart & A.L. Booth	1903		
NORTH BOUNDARY				
All	A.J. Stewart & A.L. Booth	1903		
Portion			J.F. Carroll	2004-05
SUBDIVISION				
All	A.J. Stewart & A.L. Booth	1903		

TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 1139, dated June 14, 2010.

The directions of the lines were determined by references to true meridian, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards for the Positional Accuracy of Cadastral Surveys when using Global Navigation Satellite Systems (GNSS)*, dated February 23, 2009. Trimble model 5800 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

The interior subdivision of sections 13 and 14, were surveyed because of Federal subsurface ownership, but not monumented because of present cultivation and river movement.

Geodetic control was derived from GPS static observations, post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS); RED BUTTE CORS, CARBON COUNTY COUT CORS, MYTON 2 CORS.

The geographic position of the corner of sections 13, 14, 23, and 24, as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: 40°17'57.059" N.,
 Longitude: 110°38'01.984" W., N.A.D. 83,
 Network Accuracy = 0.200 meter at 95% confidence

The geographic position of the corner of sections 5, 6, 7, and 8, as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: 40°19'40.825" N.,
 Longitude: 110°42'31.686" W., N.A.D. 83,
 Network Accuracy = 0.200 meter at 95% confidence

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the East Boundary,
Township 2 South, Range 7 West, Uintah Special Meridian, Utah

Reestablishment of the Survey Executed by J.R. Stewart and A.L. Booth in 1903, and the Resurvey executed by R.L. Houston in 1998.

Beginning at the corner of sections 13, 18, 19, and 24, on the east boundary of the township, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, in a mound of stone, 3 foot base, 6 inches high, with aluminum cap marked as described in the official record of the 1998 resurvey.

The left bank of the Duchesne river is approximately 40 feet south of the corner.

N. 0°12.2' E., between sections 13 and 18 on the east boundary of the township.

19.700 Point for the S 1/16 section corner of sections 13 and 18, on the east boundary of the township, not monumented.

39.400 The 1/4 section corner of sections 13 and 18, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 7 inches above the ground, in a mound of stone, 2 foot base to top of cap, marked as described in the official record of the 1998 resurvey.

N. 0°02.3' E., beginning new measurement.

39.680 Point for the corner of sections 7, 12, 13, and 18 on the east boundary of the township, determined at record bearing and distance from the northeast, southeast, and southwest 1903 bearing trees. No evidence remains of the corner reestablished in the 1998 resurvey.

From which

A pinon pine, 10 inches diameter, bears N. 49° E., 41 links distance, marked T2S R6W S7 BT.

A pinon pine, 20 inches diameter, bears S. 35° E., 36 links distance, marked T2S R6W S18 BT.

A pinon pine, 20 inches diameter, bears S. 56° W., 49 links distance, marked T2S R7W S13 BT.

At the corner point,

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 8 inches in the ground, in a mound of stone, 4 foot base, 20 inches high, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

T2S
R7W R6W
S12 | S7
S13 | S18
2010

Reestablishment of the Survey Executed by
J.R. Stewart and A.L. Booth in 1903.

N. 0°31.7' E, between sections 7 and 12 on the east boundary of the township.

- 38.873** The 1/4 section corner of sections 7 and 12, monumented with a sandstone, 15x8x5, (record: 16x10x5), loosely set and dimly marked 1/4 on west face.

From which

A pinon, 16 inches diameter, bears N. 62° E., 26 links distance, blazed and scribed as recorded in the official record of the 1903 survey.

A pinon, 16 inches diameter, bears N. 86° W., 60 links distance, blazed and scribed as recorded in the official record of the 1903 survey.

At the corner point,

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 12 inches in the ground, in a mound of stone, 4 foot base, 14 inches high, with aluminum cap marked:

T2S
R7W R6W
1/4
S12 | S7
2010

Deposit the marked stone alongside the corner.

N. 0°12.3' E., beginning a new measurement.

- 39.400** The corner of sections 1, 6, 7, and 12, determined at record bearing and distances from the bearing trees, which are:

A pinon, bears N. 62° E., 65 links distant, blazed and scribed as recorded in the official record of the 1903 survey.

A pinon, bears S. 28° E., 20 links distant, blazed and scribed as recorded in the official record of the 1903 survey.

A pinon, bears S. 50° W, 47 links distant, blazed and scribed as recorded in the official record of the 1903 survey.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

A dead, hollowed out stump, bears N. 45° W., 42 links distant, markings illegible.

At the corner point,

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with a magnet at base, 12 inches in the ground, in a mound of stone, 2 1/2 foot base, 16 inches high, with aluminum cap marked:

T2S	
R7W	R6W
S1	S6
S12	S7
2010	

Corner is located in an old fence line extending to the east and west.

N. 0°02.9' E., between sections 1 and 6 on the east boundary of the township.

39.770 The 1/4 section corner of sections 1 and 6, monumented with a sandstone, 18x10x4, loosely set, marked 1/4 on the west face.

From which

A pinon, 6 inches diameter, bears N. 30°30' E., 34.5 links distant, blaze partially healed over.

A juniper, 6 inches diameter, bears S. 80°W, 95 links distant, blaze partially healed over.

At the corner point,

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with aluminum cap marked:

T2S	
R7W	R6W
1/4	
S1	S6
2010	

Deposit the marked stone alongside the corner.

N. 0°13.0' E., beginning new measurement.

42.291 The corner of Townships 1 and 2 South, Ranges 6 and 7 West, monumented with a sandstone, 24x14x12 (record: 30x14x12), firmly set, projecting 8 inches above the ground, marked 1S on the northeast side, other marks too dim to read.

From which

A pinon, dead and down, to the northwest.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

A pinon, 10 inches diameter, bears S. 33° E., 46 links distant.

A pinon, 10 inches diameter, bears S. 58° W., 35 links distant.

A pinon, 14 inches diameter, bears N. 17° W., 25 links distant.

At the corner point,

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, in a mound of stone, 2 1/2 foot base to top, with aluminum cap marked:

T1S	
R7W	R6W
S36	S31
S1	S6
T2S	
2010	

Deposit the marked stone at the base of the stone mound, alongside the corner.

Dependent Resurvey of a Portion of the North Boundary,
Township 2 South, Range 7 West, Uintah Special Meridian, Utah

Reestablishment of the Survey Executed by
J.R. Stewart and A.L. Booth in 1903.

From the corner of Townships 1 and 2 South, Ranges 6 and 7 West.

S. 89°06.2' W., between sections 1 and 36 on the north boundary of the township.

39.274 The 1/4 section corner of sections 1 and 36 on the north boundary of the township, monumented with a sandstone 16x14x6, firmly set, decayed and dimly marked, projecting 6 inches above the ground.

From which

A juniper, 8 inches diameter, bears N. 39° E., 91 links distant, blaze healed over. (Record; N. 20° E., 94 links distance)

A pinon, dead and down, bears S. 23° E, 43 links distant, blazed and scribed as recorded in the official record of the 1903 survey. (Record; S. 10° E., 43 links distance)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 25 inches in the ground, with aluminum cap

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

marked:

T1S R7W
S36
1/4 —————
S1
T2S
2010

Deposit the marked stone alongside the corner.

N. 89°48.2' W., beginning new measurement.

- 39.585** The corner of sections 1, 2, 35, and 36, on the north boundary of the township, monumented with a sandstone, 18x12x7 (record: 17x8x6), firmly set, marked with 5 notches on the west and 1 notch on the east.

From which

A pinon pine, 8 inches diameter, bears N. 15° E., 91 links distance, with the blaze healed over. (Record; 87 links distance)

A juniper, 6 inches diameter, bears S. 85° E, 54 links distance, blazed and scribed as recorded in the official record of the 1903 survey. (Record; 521 links distance)

A pinon, 12 inches diameter, bears S. 40° W., 46 links distance, blazed and scribed as recorded in the official record of the 1903 survey.

A pinon, 12 inches diameter, bears N. 30° W., 57 links distance, blazed and scribed as recorded in the official record of the 1903 survey.

At the corner point,

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, with aluminum cap marked:

T1S R7W
S35 | S36
S2 | S1
T2S
2010

Deposit the marked stone alongside the corner.

S. 89°19.5' W., between sections 2 and 35 on the north boundary of the township.

- 39.620** The 1/4 section corner of sections 2 and 35 on the north boundary of the township, monumented with a sandstone 15x8x7, (record: 16x10x10), firmly set, dimly marked 1/4 on the north side.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UTAH SPECIAL MERIDIAN, UTAH

CHAINS

From which

A pinon, dead and down, to the north.

A juniper, 12 inches diameter, bears S. 58° W., 21 links distance, blazed and scribed as recorded in the official record of the 1903 survey. (Record; S. 35° W.)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 27 inches in the ground, with aluminum cap marked:

T1S R7W
S35
1/4 —————
S2
T2S R7W
2010

Deposit the marked stone alongside the corner.

N. 89°39.1' W., beginning new measurement.

40.114 The corner of sections 2, 3, 34, and 35, on the north boundary of the township, monumented with a sandstone, 19x8x6 (record: 16x8x6), loosely set, and dimly marked 1/4 on N. face.

From which

A pinon, 14 inches diameter, bears N. 55° E., 47 links distance, blazed and scribed as recorded in the official record of the 1903 survey. (Record; N. 60° E., 48 links distance)

A juniper, 13 inches diameter, bears S. 56° E, 87 links distance, blazed with scribing illegible. (Record; S. 70° E., 54 links distance)

A pinon, gone. (SW BT)

A pinon, 20 inches diameter, bears N. 47° E., 27 links distance, blazed and scribed as recorded in the official record of the 1903 survey. (Record; N. 51° W., 36 links distance)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 27 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

T1S R7W
S34 | S35
S3 | S2
T2S R7W
2010

Deposit the marked stone alongside the corner.

S. 89°21.0' W., between sections 3 and 34 on the north boundary of the township.

- 39.441** The 1/4 section corner of section 3 and 34, monumented with a sandstone, 19x10x7 (record: 20x10x8), firmly set, projecting 13 inches above the ground, marked 1/4 on east face.

From which

A juniper, 15 inches diameter, bears S. 58° E., 5 links distance, blazed and scribed as recorded in the official record of the 1903 survey. (Record; S. 30° E., 19 links distance)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 22 inches in the ground, with aluminum cap marked:

T1S R7W
S34
1/4 ———
S3
T2S R7W
2010

Deposit the marked stone alongside the corner.

A barbed wire fence, extending east and west, is approximately 4 feet north of the corner.

N. 89°47.0' W., beginning new measurement,

- 39.702** The corner of sections 3, 4, 33, and 34, monumented with an aluminum post, 2 1/2 inches diameter, set, marked and witnessed as described in the official record of the 2004 resurvey.
-

Reestablishment of the Survey Executed by J.R. Stewart and A.L. Booth in 1903, and the Dependent Resurvey Executed by J.F. Carroll in 2004.

N. 89°45.0' W., between sections 4 and 33 on the north boundary of the township.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

- 19.969** Point for E 1/16 section corner of sections 4 and 33, on the north boundary of the township, not monumented.
- 39.938** The 1/4 section corner of sections 4 and 33, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, in a collar of stone, marked as described in the official record of the 2004 resurvey.

S. 89°38.0' W., beginning new measurement.

- 19.969** Point for the W 1/16 section corner of sections 4 and 33, on the north boundary of the township.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 4 inches below ground level, with aluminum cap marked:

T1S R7W
W 1/16 S33
S4
T2S
2010

Corner falls in the center of a 6 ft. wide dirt road, at the extension of fences from the east, west, and north.

- 39.938** The corner of sections 4, 5, 32, and 33, monumented with an aluminum drive rod, 3/4 inch diameter, projecting 5 inches above ground, firmly set, marked as described in the official record of the 2004 resurvey.

Dependent Resurvey of a Portion of the Subdivisional Lines,
Township 2 South, Range 7 West, Uintah Special Meridian, Utah

Reestablishment of the Survey Executed by
J.R. Stewart and A.L. Booth in 1903.

From the corner of sections 13, 18, 19, and 24, on the east boundary of the township, hereinbefore described.

S. 89°24.5' W., between sections 13 and 24.

- 19.907** Point for the E 1/16 section corner of sections 13 and 24, not monumented.
- 39.814** The 1/4 section corner of sections 13 and 24, monumented with a sandstone 14x10x4 (record: 16x10x5), laying loose and above ground, dimly marked.

From which

A pinon, 17 inches diameter, bears N. 15° E., 49 links
distance, blazed and scribed as recorded in the official

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH
CHAINS

record of the 1903 survey. (Record; N. 52° E.)

A pinon, 16 inches diameter, bears S. 10° W., 29 links distance, blazed and scribed as recorded in the official record of the 1903 survey. (Record; S. 43° W.)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

T2S R7W
S13
1/4 —————
S24
2010

Deposit the marked stone alongside the corner.

N. 89°41.1' W., beginning new measurement.

40.441 The corner of sections 13, 14, 23, and 24, monumented with a 1/2 inch rebar, projecting 3 inches above the ground, set in solid stone ledge.

From which

A pinion, 20 inches diameter, bears N. 50° E., 30 links distance, blazed and scribed as recorded in the official record of the 1903 survey. (Record; 40 links distance)

A pinion, 16 inches diameter, bears S. 20° E., 25 links distance, blazed and scribed as recorded in the official record of the 1903 survey. (Same as record)

No remaining evidence of the other two trees. Not remonumented.

This position is accepted as a faithful establishment of the corner position.

N. 0°25.2' E., between sections 13 and 14.

39.600 Point for the 1/4 section corner of sections 13 and 14, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

59.400 Point for the N 1/16 section corner of sections 13 and 14, not monumented.

79.200 The corner of sections 11, 12, 13, and 14, monumented with a sandstone, 13x11x4, firmly set, projecting 9 inches above the ground, with 4 notches on the south, in a scattered mound of stone.

From which

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

A pinon, 24 inches diameter, bears N. 8° E., 41 links distance, blazed and scribed as recorded in the official record of the 1903 survey. (Record; N. 10° E., 43 links distance)

A juniper, 14 inches diameter, bears S. 68° E., 88 links distance, blazed and scribed as recorded in the official record of the 1903 survey. (Same as record)

A pinon, 25 inches diameter, bears S. 44° W., 110 links distance, blazed and scribed as recorded in the official record of the 1903 survey. (Record; 130 links distance)

A pinon, 23 inches diameter, bears N. 70° W., 110 links distance, blazed and scribed as recorded in the official record of the 1903 survey. (Record; 109 links distance)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 27 inches in the ground, with aluminum cap marked:

T2S R7W	
S11	S12
S14	S13
2010	

Deposit the marked stone alongside the corner.

From the corner of sections 7, 12, 13, and 18, on the east boundary of the township, hereinbefore described.

N. 89°47.3' W., between sections 12 and 13.

40.139 The 1/4 section corner of sections 12 and 13, monumented with a decayed sandstone, 14x11x4, (record: 16x10x45) loosely set.

From which

A juniper, 12 inches diameter, bears N. 45° E., 73 links distance, clearly blazed, scribing faded.

A pinion, 22 inches diameter, bears S. 30° E., 35 links distance, blazed and scribed as recorded in the official record of the 1903 survey.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 10 inches in the ground, to bedrock, in a mound of stone, 3 foot base, 1 1/2 feet high, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH
CHAINS

T2S R7W
S12
1/4 —————
S13
2010

Deposit the marked stone at the base of the mound.

Corner is located near the east edge of a shelf on the west side of Wagstaff Canyon.

S. 89°41.0' W., beginning a new measurement.

- 19.843 Point for the W 1/16 section corner of sections 12 and 13, not monumented.
- 39.686 The corner of sections 11, 12, 13, and 14.

N. 0°56.8' E., between sections 11 and 12.

- 39.352 The 1/4 section corner of sections 11 and 12, monumented with a sandstone, 22x8x6 (record: 16x11x4), firmly set, projecting 10 inches above the ground, marked 1/4 on west face.

From which

A pinon, 21 inches diameter, bears N. 60° E., 21 links distance, blazed and scribed as recorded in the official record of the 1903 survey. (Record; N. 40° E., 20 links distance)

A pinon, 22 inches diameter, bears S. 50° W., 78 links distance, blazed and scribed as recorded in the official record of the 1903 survey. (Record; 90 links distance)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with aluminum cap marked:

T2S R7W
1/4
S11 | S12
2010

Deposit the marked stone alongside the corner.

N. 1°06.7' E., beginning new measurement.

- 39.433 Point for the section corner of sections 1, 2, 11, and 12, determined at a bearing-bearing intersect from the northeast and southeast bearing trees.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

From which

A pinon, 21 inches diameter, bears N. 75° E., 111 links distance, blazed and scribed as recorded in the official record of the 1903 survey. (Record; 150 links distance)

A pinon, 24 inches diameter, bears S. 74° E., 106 links distance, blazed and scribed as recorded in the official record of the 1903 survey. (Record; 145 links distance)

A juniper, 20 inches diameter, bears S. 46° W., 46 links distance, blazed and scribed as recorded in the official record of the 1903 survey. (Record; S. 60° W., 75 links distance)

A pinon, 18 inches diameter, bears N. 38° W., 63 links distance, blazed and scribed as recorded in the official record of the 1903 survey. (Record; N. 40° W., 35 links distance)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 18 inches in the ground, in a mound of stone, 2 1/2 foot base, 12 inches high, with aluminum cap marked:

T2S R7W	
S2	S1
S11	S12
2010	

Corner is located in an old fence extending east and west.

From the corner of sections 1, 6, 7, and 12, on the east boundary of the township, hereinbefore described.

N. 89°20.4' W., between sections 1 and 12.

37.599 The 1/4 section corner of sections 1 and 12, monumented with a sandstone, 15x8x5, firmly set, projecting 4 inches above the ground, dimly marked

From which

A pinon, 12 inches diameter, bears S. 20° E., 25 links distance, blazed and scribed as recorded in the official record of the 1903 survey.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 8 inches in the ground to bedrock, in a mound of stone, 3 foot base, 1 1/2 feet high, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH
CHAINS

T2S R7W
S1
1/4 —————
S12
2010

Deposit the marked stone alongside the corner at the base of the mound.

Corner is located in a fence extending east and west.

—————
S. 89°59.8' W., beginning new measurement.

41.297 The corner of sections 1, 2, 11, and 12.

—————
N. 0°07.3' W., between sections 1 and 2.

40.097 The 1/4 section corner of sections 1 and 2, monumented with a sandstone, 18x15x8, loosely set, dimly marked, no evidence of bearing trees remains.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 10 inches in the ground to bedrock, in a mound of stone, 2 1/2 foot base, 1 1/2 feet high, with aluminum cap marked:

T2S R7W
1/4
S2 | S1
2010

Deposit the marked stone alongside the corner at the base of the mound.

—————
N. 0°24.5' E., beginning new measurement.

41.049 The corner of sections 1, 2, 35, and 36 on the north boundary of the township, hereinbefore described.

—————
From the corner of sections 13, 14, 23, and 24.

N. 89°32.8' W., between sections 14 and 23.

39.031 The 1/4 section corner of sections 14 and 23, monumented with a sandstone, 14x11x4 (record: 18x11x4), loosely set, marked 1/4 on the north face.

From which

A pinon, 24 inches diameter, bears S. 35° W., 45 links
distance, blazed and scribed as described in the official

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

record of the 1903 survey. (Record; S. 45° W.)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, with aluminum cap marked:

T2S R7W
S14
1/4 —————
S23
2010

Deposit the marked stone alongside the corner.

N. 89°45.4' W., beginning new measurement.

39.867 The corner of sections 14, 15, 22, and 23, monumented with a pinion pine, 12 inches diameter (record 9 inches), marked T2S S14 on northeast, R7W S23 on the southeast, S22 on the southwest, and S15 on the northwest, 2 notches on the east, notches on the south appear to have healed over.

From which

A pinon, 14 inches diameter, bears N. 45° E., 52 links distance, marked as described in the 1903 survey. (Record; 45 links distance)

A juniper, 13 inches diameter, bears S. 46° E., 43 links distance, partially over grown and scribed as described in the 1903 survey. (Record; 40 links distance)

A pinon, 14 inches diameter, bears S. 17° W., 62 links distance, blazed and scribed as described in the official record of the 1903 survey. (Record; 60 links distance)

A pinon, 15 inches diameter, bears N. 25° W., 61 links distance, blazed and scribed as described in the official record of the 1903 survey. (Record; 55 links distance)

An aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, set 25 inches in the ground, for a reference monument, bears S. 82°09.2' E., 19.5 links distance, with an aluminum cap marked, RM T2S R7W S22 12.86 FT 2010, and an arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, set 26 inches in the ground, for a reference monument, bears S. 3°50.0' W., 17.0 links distance, with an aluminum cap marked, RM T2S R7W S22 11.20 FT 2010, and an arrow pointing to the corner.

N. 0°12.2' E., between sections 14 and 15.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH
CHAINS

39.429 Point for the 1/4 section corner of section 14 and 15, determined at record bearing and distance from the northwest bearing tree:

A juniper, 14 inches diameter, bears N. 80° W., 70 links distance, blazed and scribed as described in the 1903 survey.

The bearing tree to the northeast is dead and down.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 14 inches in the ground, in a mound of stone, 3 foot base, 1 1/2 feet high, with aluminum cap marked:

T2S R7W
1/4
S15 | S14
2010

N. 0°24.0' W., beginning new measurement.

19.849 Point for the N 1/16 section corner of sections 14 and 15, not monumented.

39.698 The corner of sections 10, 11, 14, and 15, monumented with an iron rebar, 3/8 inch diameter, with an aluminum cap marked: "LS148951".

This position is harmoniously related to identified original corners, and is accepted as the best available evidence of the original corner position, not remonumented.

A steel fence post is set alongside.

The corner is located in a flat pasture.

From the corner of sections 11, 12, 13, and 14.

N. 89°42.5' W., between sections 11 and 14.

19.899 Point for the E 1/16 section corner of sections 11 and 14, not monumented.

39.798 Point for the 1/4 section corner of sections 11 and 14, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

59.697 Point for the W 1/16 section corner of sections 11 and 14, not monumented.

79.596 The corner of sections 10, 11, 14, and 15.

N. 0°13.3' E., between sections 10 and 11.

39.708 The 1/4 section corner of sections 10 and 11, monumented with a

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

sandstone, 14x9x4 (record: 18x11x4), firmly set, projecting 7 inches above the ground, marked 1/4 on the west face, in a mound of stone, 3 foot base, 6 inches high.

From which

A pinon, 24 inches diameter, bears S. 11 E., 36 links distance, blazed and scribed as described in the 1903 survey. (Record; S. 5° E., 35 links distance)

At the corner point

Set an aluminum post, 30 inches long 2 1/2 inches diameter, with magnet at base, 4 inches in the ground, in a mound of stone, 4 foot base, 2 feet high, with aluminum cap marked:

T2S R7W	
1/4	
S10	S11
2010	

Deposit the marked stone alongside the corner at the base of the mound.

N. 1°13.0' E., beginning new measurement.

39.076 Point for the corner of sections 2, 3, 10, and 11, determined at record bearing and distance from the southwest bearing tree and record bearing from the southeast and northwest bearing trees,

From which

A pinon, 9 inches diameter, bears S. 16° E., 56 links distance, blazed and scribed as described in the official record of the 1903 survey. (Record; 60 links)

A pinon, 13 inches diameter, bears S. 35° W., 30 links distance, blazed and scribed as described in the official record of the 1903 survey.

A pinon, 14 inches diameter, bears N. 28° W, 42 links distance, blazed and scribed as described in the official record of the 1903 survey. (Record; 50 links)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 4 inches in the ground, in a mound of stone, 5 foot base, 3 feet high, with aluminum cap marked:

T2S R7W	
S3	S2
S10	S11
2010	

Corner is located in a small drainage descending south, on a

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

south facing steep slope.

From the corner of sections 1, 2, 11, and 12.

N. 89°41.6' W., between sections 2 and 11.

39.648 The 1/4 section corner of sections 2 and 10, monumented with a sandstone, 18x6x4 (record: 18x6x6), firmly set, projecting 5 inches above the ground, with 1/4 on the north face, no evidence remains of the original bearing trees.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 25 inches in the ground, with aluminum cap marked:

T2S R7W
S2
1/4 —————
S11
2010

Deposit the marked stone alongside the corner.

The corner is located in a large meadow in a fence line extending to east and west.

N. 89°43.2' W., beginning new measurement.

40.364 The section corner of sections 2, 3, 10, and 11.

N. 0°24.4' E., between sections 2 and 3.

40.559 The 1/4 section corner of sections 2 and 3, monumented with a sandstone, 16x8x5, firmly set, projecting 7 inches above the ground, faintly marked 1/4 on the west face.

From which

A juniper, 12 inches diameter, bears S. 78 W., 95 links distance, blazed and scribed as described in the official record of the 1903 survey.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to bedrock, in a mound of stone, 3 foot base, 1 1/2 feet high, with aluminum cap marked:

T2S R7W
1/4
S3 | S2
2010

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

Deposit the marked stone alongside the corner at the base of the mound.

N. 0°15.8' E., beginning new measurement.

- 39.956 The corner of sections 2, 3, 34, and 35, on the north boundary of the township, hereinbefore described.

From the corner of sections 21, 22, 27, and 28, monumented with a sandstone 16x8x6, firmly set, projecting 8 inches above the ground, dimly marked with notches on east and south sides.

From which

A pinon, 23 inches diameter, bears N. 49° E., 86 links distance, blazed and scribed as described in the official record of the 1903 survey. (Record; 68 links)

A pinon, 20 inches diameter, bears S. 37° E., 45 links distance, blazed and scribed as described in the official record of the 1903 survey. (Record; 29 links)

A pinon, 16 inches diameter, bears S. 30° W., 45 links distance, blazed and scribed as described in the official record of the 1903 survey. (Record; 32 links)

A pinon, 22 inches diameter, bears N. 70° W., 52 links distance, blazed and scribed as described in the official record of the 1903 survey. (Record; 40 links)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, with aluminum cap marked:

T2S R7W	
S21	S22
S28	S27
2010	

Deposit the marked stone alongside the corner.

N. 0°04.4' W., between sections 21 and 22.

- 39.837 Point for the 1/4 section corner of sections 21 and 22, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

- 79.674 Point for the corner of sections 15, 16, 21, and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 22 inches in the ground, in a mound of stone, 2

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH
CHAINS

foot base, 6 inches high, with aluminum cap marked:

T2S R7W	
S16	S15
S21	S22
2010	

From the corner of sections 14, 15, 22, and 23.

S. 88°57.9' W., between sections 15 and 22.

- 39.098** Point for the 1/4 section corner of sections 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with aluminum cap marked:

T2S R7W	
S15	
1/4	—————
S22	
2010	

Raise a mound of stone, 3 foot base, 1 1/2 feet high, 3 feet west of the corner.

- 78.196** The corner of sections 15, 16, 21, and 22.

N. 0°32.6' W., between sections 15 and 16.

- 39.838** Point for the 1/4 section corner of sections 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with aluminum cap marked:

T2S R7W	
1/4	
S16	S15
2010	

The corner is located on an east facing slope, approximately 10 feet east of a 10 feet tall rock face.

- 59.757** Point for the N 1/16 section corner of sections 15 and 16, not monumented.

- 79.676** The corner of sections 9, 10, 15, and 16, monumented with a Duchesne County monument, a 2 1/2 inches diameter aluminum pipe, firmly set, projecting 4 inches above the ground, in a collar of stone, 2 foot base, with the 2 1/2 inches diameter aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH
CHAINS

T2S R7W	
S9	S10
S16	S15
2002	

This position is harmoniously related to identified original corners, and is accepted as the best available evidence of the original corner position. Not remonumented.

From the corner of sections 10, 11, 14, and 15.

S. 89°22.3' W., between sections 10 and 15.

- 39.394 Point for the 1/4 section corner of sections 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 27 inches in the ground, with aluminum cap marked:

T2S R7W	
S10	
1/4	—————
S15	
2010	

Set a steel fence post alongside the north side of the corner.

The corner is located on a steep northeast facing slope.

- 59.091 Point for the W 1/16 section corner of sections 10 and 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 27 inches in the ground, with aluminum cap marked:

S10	
W1/16	—————
S15	
2010	

Set a steel fence post on the north side of the corner.

- 78.788 The corner of sections 9, 10, 15, and 16.
-

N. 0°50.3' E., between sections 9 and 10.

- 19.815 Point for the S 1/16 section corner of sections 9 and 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 27 inches in the ground, with aluminum cap marked:

S 1/16	
S9	S10
2010	

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

Set a steel fence post on the north side of the corner.

A two track road, extending north and south, is approximately 20 feet east of the corner.

- 39.630 The 1/4 section corner of sections 9 and 10, monumented with a sandstone, 16x10x6, loosely set, dimly marked 1/4 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, with aluminum cap marked:

T2S R7W
1/4
S9 | S10
2010

Deposit the marked stone alongside the corner.

N. 0°12.0' W., beginning new measurement.

- 19.924 Point for the N 1/16 section corner of sections 9 and 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

N 1/16
S9 | S10
2010

The corner is located in a grassy field in the Duchesne River bottoms.

- 29.886 Point for the N-N 1/64 section corner of sections 9 and 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, with aluminum cap marked:

N-N
1/64
S9 | S10
2010

Corner is located in a grassy pasture, 9 feet west of a barbed wire fence, extending north and south.

- 34.867 Point for the N-N-N 1/256 section corner of sections 9 and 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with the aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

N-N-N
1/256
S9 | S10
2010

Corner is located in a field. A barbed wire fence extending north and south is 15 links west of the corner. The centerline of a road extending north and south is 62 links west of the corner.

- 39.848** The corner of sections 3, 4, 9, and 10, monumented with a Duchesne County monument, a 5/8 inch rebar, projecting 4 inches above the ground, with a 2 1/2 inch diameter aluminum cap marked:

T2S R7W
S3 | S4
S9 | S10
2002

This position is harmoniously related to identified original corners, and is accepted as the best available evidence of the original corner position. Not monumented.

From the corner of sections 2, 3, 10, and 11.

S. 89°44.5' W., between sections 3 and 10.

- 39.095** The 1/4 section corner of sections 3 and 10, monumented with a sandstone 18x6x6, dimly marked, firmly set, projecting 8 inches above the ground, in a scattered mound of stone, 3 foot base. A 5/8 inch rebar with an aluminum cap, 1 1/2 inched diameter, marked LS158961 is set alongside.

From which

A pinon, 18 inches diameter, bears S. 60° E., 56 links distance, blazed and scribed as described in the official record of the 1903 survey. (Record; S. 20° E., 65 links distance)

A pinon, 9 inches diameter, bears N. 80° W., 58 links distance, blazed and scribed as described in the official record of the 1903 survey. (Record; 60 links distance)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with aluminum cap marked:

T2S R7W
S3
1/4 —————
S10
2010

Deposit the marked stone and rebar alongside the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

N. 89°58.7' W., beginning new measurement.

- 20.108 True point for the W 1/16 section corner of sections 3 and 10, falls in the center of an irrigation ditch where it is impracticable to set a permanent monument.
- 30.162 Point for the W-W 1/64 section corner of sections 3 and 10, not monumented.
- 40.216 The section corner of sections 3, 4, 9, and 10.

N. 0°49.9' E., between sections 3 and 4.

- 20.026 Point for the S 1/16 section corner of sections 3 and 4, not monumented.
- 40.052 Point for the 1/4 section corner of sections 3 and 4, determined from an original bearing tree:

A pinon, 8 inches diameter, bears N. 80° W., 60 links distance, marked as described in the official record of the 1903 survey. (The original 1903 notes were reversed)

There is no remaining evidence of the other bearing tree.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, with aluminum cap marked:

T2S R7W
1/4
S4 | S3
2010

N. 0°03.7' E., beginning new measurement.

- 20.165 Point for the N 1/16 section corner of sections 3 and 4, not monumented.
- 40.330 The corner of sections 3, 4, 33, and 34, on the north boundary of the township, hereinbefore described.

From the corner of sections 15, 16, 21, and 22.

N. 87°55.4' W., between sections 16 and 21.

- 39.373 The 1/4 section corner of sections 16 and 21, determined from an original bearing tree:

A pinon, 12 inches diameter, bears N. 20° W., 149 links distance, marked as described in the official record of the

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

1903 survey.

There is no remaining evidence of the other bearing tree.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 25 inches in the ground, with aluminum cap marked:

	T2S R7W
	S16
1/4	-----
	S21
	2010

From the 1/4 section corner of sections 16 and 17, monumented with a fragmented sandstone, 18x12x6, loosely set, no markings visible. The stone is the only stone of its type and size within the area, and is accepted as the original stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with aluminum cap marked:

	T2S R7W
	1/4
S17	S16
	2010

Deposit the fragmented stone alongside the corner.

N. 0°02.5' E., between sections 16 and 17.

39.363 The corner of sections 8, 9, 16, and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 20 inches in the ground, in a mound of stone, 2 1/2 foot base, 8 inches high, with aluminum cap marked:

	T2S R7W
S8	S9
S17	S16
	2010

From the corner of sections 9, 10, 15, and 16.

S. 89°56.8' W., between sections 9 and 16.

19.844 Point for the E 1/16 section corner of sections 9 and 16, not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH
CHAINS

- 39.688** Point for the 1/4 section corner of sections 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with aluminum cap marked:

T2S R7W
S9
1/4 —————
S16
2010

- 79.376** The corner of sections 8, 9, 16, and 17.
-

N. 1°26.3' W., between sections 8 and 9.

- 39.375** The 1/4 section corner of sections 8 and 9, determined from an original bearing tree:

A pinion, 12 inches diameter, bears N. 10° W., 25 links distance, blaze partially healed over, marked as described in the official record of the 1903 survey.

There is no remaining evidence of the other bearing tree.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with aluminum cap marked:

T2S R7W
1/4
S8 | S9
2010

Corner is located on an east facing slope. The centerline of State Road 208 is approximately 240 feet north of the corner.

N. 1°39.6' E., beginning new measurement.

- 40.212** True point for the corner of sections 4, 5, 8, and 9, at proportionate distance; there is no remaining evidence of the original corner, falls in cultivated field.

From which

Point selected for an offline witness corner to the corner of sections 4, 5, 8, and 9, bears S. 31°21.4' W., 2.184 chains distance.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, with aluminum cap

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

marked:

WC
T2S R7W
S5 | ↗ S4
S8 | S9
2010

Set a steel fence post alongside the corner.

The corner is located on the south edge of a field.

From the corner of sections 3, 4, 9, and 10.

N. 89°59.8' W., between sections 4 and 9.

19.905 Point for the E 1/16 section corner of sections 4 and 9.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with aluminum cap marked:

T2S R7W
S4
E1/16 —————
S9
2010

Corner is located in an open field. A barbed wire fence extending east and west is approximately 309 feet north of the corner.

39.810 True point for the 1/4 section corner of sections 4 and 9, at proportionate distance; there is no remaining evidence of the original corner. Corner falls in the Duchesne River where it is impracticable to set a permanent monument.

40.422 Point selected for a witness corner to the 1/4 section corner of sections 4 and 9.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with aluminum cap marked:

WC
T2S R7W
S4
1/4 —————>
S9
2010

59.715 Point for the W 1/16 section corner of sections 4 and 9.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 30 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

S4
W1/16 —————
S9
2010

Set a steel fence post alongside the corner.

Corner is located in an open pasture. A barbed wire fence extending east and west is 4 feet north of the corner. A barbed wire fence extending north and south is approximately 30 feet west of the corner.

79.620 The true point for the corner of sections 4, 5, 8, and 9.

N. 0°15.2' E., between sections 4 and 5.

40.196 Point for the 1/4 section corner of sections 4 and 5, at proportionate distance; there is no remaining evidence of the original corner. Corner falls in the Duchesne River where it is impracticable to set a permanent monument.

From which

The point selected for an offline witness corner to the 1/4
section corner of sections 4 and 5, bears N. 2°33.6' W.,
2.274 chains distance.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with aluminum cap marked:

WC
T2S R7W
1/4
S5 ↓ S4
2010

Corner is located near the left bank of the Duchesne River.

60.294 Point for the N 1/16 section corner of sections 4 and 5.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 20 inches in the ground, with aluminum cap marked:

N 1/16
S5 | S4
2010

Corner is located in a swampy, grassy field surrounded by cottonwood trees.

80.291 The corner of sections 4, 5, 32, and 33, on the north boundary of the township, hereinbefore described.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

From the corner of sections 8, 9, 16, and 17.

N. 89°36.6' W., between sections 8 and 17.

39.827 The 1/4 section corner of sections 8 and 17, determined at record distance and bearing from the original bearing trees:

A pinon, 11 inches diameter, bears N. 30° E., 58 links distance, blazed and scribed as described in the official record of the 1903 survey.

A pinon, 21 inches diameter, bears S. 60° W., 39 links distance, blazed and scribed as described in the official record of the 1903 survey.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 23 inches in the ground, in a mound of stone, 2 foot base, 6 inches high, with aluminum cap marked:

T2S R7W
S8
1/4 —————
S17
2010

The centerline of State Road 208 is approximately 5 chains west of the corner.

From the true point for the corner of sections 4, 5, 8, and 9.

N. 88°11.4' W., between sections 5 and 8.

39.920 The 1/4 section corner of sections 5 and 8, determined from an original bearing tree:

A pinon, 18 inches diameter, bears S. 20° E., 61 links distance, blaze partially healed over, scribed as described in the official record of the 1903 survey.

There is no remaining evidence of the other bearing tree.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 27 inches in the ground, with aluminum cap marked:

T2S R7W
S5
1/4 —————
S8
2010

S. 89°31.4' W., beginning new measurement.

39.744 The corner of sections 5, 6, 7, and 8, determined from the

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

remains of the original bearing trees:

A pinon, 20 inches diameter, bears N. 76° E., 41 links distance, blazed and scribed as described in the official record of the 1903 survey.

A dead pinon, 7 inches diameter, bears N. 61°31' W., 24 links distance, blazed and scribed as described in the official record of the 1903 survey. (Record; N. 36° W.)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 25 inches in the ground, with aluminum cap marked:

T2S R7W	
S6	S5
S7	S8
2010	

N. 0°11.9' E., between sections 5 and 6.

- 39.613 The 1/4 section corner of sections 5 and 6, monumented with a quartzite 17x16x8 (record: 16x14x8), firmly set, projecting 4 inches above the ground, marked 1/4 on the west face, with a 5/8 inch rebar with a Duchesne County Survey aluminum cap set alongside the corner.

From which

A pinon, 7 inches diameter, bears S. 57° W., 46 links distance, blazed and scribed as described in the official record of the 1903 survey. (Record; 60 links distance)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with aluminum cap marked:

T2S R7W	
1/4	
S6	S5
2010	

Bury the rebar and marked stone alongside the corner. The southwest corner of a hunting lodge is approximately 350 feet east of the corner.

N. 0°02.8' W., beginning new measurement.

- 39.667 The corner of sections 5, 6, 31, and 32, on the north boundary of the township, monumented with an aluminum post, set, marked and witnessed as described in the official record of the 2004 resurvey.

THE SUBDIVISION OF SECTION 4,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

The Subdivision of Section 4,
Township 2 South, Range 7 West, Uintah Special Meridian, Utah

From the true point for the 1/4 section corner of sections 4 and 9.

N. 0°20.8' E., on the N-S centerline of section 4.

20.061 Point for the center S 1/16 section corner of section 4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{C} \\ \text{S1/16} \mid \text{S4} \\ \text{C} \\ 2010 \end{array}$$

A barbed wire fence, extending north, east, and west is approximately 25 feet north of the corner.

40.122 Point for the center 1/4 section corner, at intersection the E-W centerline of section 4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{T2S R7W} \\ \text{C1/4 S4} \\ 2010 \end{array}$$

Corner is located in a flat, open field. A barbed wire fence is approximately 10 feet north of the corner.

60.361 True point for the center N 1/16 section corner of section 4. Point falls in the center of an irrigation ditch where it is impracticable to set a permanent monument.


From which

Point selected for an offline witness corner to the center N 1/16 section corner, bears S. 47°26.1' E., 0.099 chains distance.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 27 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 4,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UTAH SPECIAL MERIDIAN, UTAH

CHAINS



Corner is located in a field. A fence extending north and south is 1 foot east of the corner. The intersection of fences extending north, south, east, and west is approximately 11 feet north of the corner.


- 80.549 The 1/4 section corner of sections 4 and 33, on the north boundary of the township, hereinbefore described.
-

From the 1/4 section corner of sections 3 and 4.

N. 89°53.4' W., along the E-W centerline of section 4.

- 20.072 Point for the center E 1/16 section corner of section 4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 25 inches in the ground, with aluminum cap marked:




A fence extending north and south is 10 feet east of the corner.

- 40.144 The center 1/4 section corner of section 4.

- 60.080 The center W 1/16 section corner of section 4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 25 inches in the ground, with aluminum cap marked:



A fence extending north and south is approximately 1 foot west of the corner.

- 80.016 The true point for the 1/4 section corner of sections 4 and 5.
-

From the center E 1/16 section corner of section 4.

N. 0°12.3' E., on the N-S centerline of the NE 1/4 of section 4.

- 20.202 Point for the NE 1/16 section corner, at intersection with the

THE SUBDIVISION OF SECTION 4,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

E-W centerline of the NE 1/4 of section 4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 25 inches in the ground, with aluminum cap marked:

NE 1/16 S4
2010

Corner is located on the east bank of a ditch. A barbed wire fence corner is 1 foot southeast of the corner.

- 40.378 The point for the E 1/16 section corner of sections 4 and 33, on the north boundary of the township, hereinbefore described.
-

From the point for the N 1/16 section corner of sections 3 and 4.

N. 89°47.0' W., on the E-W centerline of the NE 1/4 of section 4.

- 20.021 The NE 1/16 section corner of section 4.

- 40.042 The true point for the center N 1/16 section corner of section 4.
-

From the E 1/16 section corner of sections 4 and 9.

N. 0°35.4' E., on the N-S centerline of the SE 1/4 of section 4.

- 20.043 Point for the SE 1/16 section corner, at intersection with the E-W centerline of the SE 1/4 of section 4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter with magnet at base, 27 inches in the ground, with aluminum cap marked:

SE 1/16 S4
2010

Corner is located in a flat, open field. A barbed wire fence extending east and west is 20 feet north of the corner. A barbed wire fence extending north and south is 27 feet east of the corner.

- 40.086 The center E 1/16 section corner of section 4.
-

From the point for the S 1/16 section corner of sections 3 and 4.

N. 89°56.6' W., on the E-W centerline of the SE 1/4 of section 4.

- 19.989 The SE 1/16 section corner of section 4.

- 39.978 The center S 1/16 section corner of section 4.
-

From the W 1/16 section corner of sections 4 and 9.

THE SUBDIVISION OF SECTION 4,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

N. 0°18.0' E., on the N-S centerline of the SW 1/4 of section 4.

40.159 The center W 1/16 section corner of section 4.

From the center W 1/16 section corner of section 4.

N. 0°18.0' E., on the N-S centerline of the NW 1/4 of section 4.

20.168 Point for the NW 1/16 section corner, at intersection with the E-W centerline of the NW 1/4 of section 4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, with aluminum cap marked:

NW 1/16 S4
2010

Corner is located alongside a dirt road extending north and south. A fence corner bears N. 14°02' E., 18.5 links distance.

40.261 The W 1/16 section corner of sections 4 and 33, on the north boundary of the township, hereinbefore described.

From the true point for the center N 1/16 section corner of section 4.

S. 89°54.4' W., on the E-W centerline of the NW 1/4 of section 4.

19.952 The NW 1/16 section corner of section 4.

39.904 The N 1/16 section corner of sections 4 and 5.

The Subdivision of Section 5,
Township 2 South, Range 7 West, Uintah Special Meridian, Utah

From the 1/4 section corner of section 5 and 8.

N. 0°13.5' E., on the N-S centerline of section 5.

39.109 Point for the center 1/4 section corner, at intersection with the E-W centerline of section 5, not monumented.

59.120 Point for the center N 1/16 section corner of section 5.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 25 inches in the ground, in a collar of stone, 2 feet base, with aluminum cap marked:

C
N1/16 | S5
C
2010

THE SUBDIVISION OF SECTION 5,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH
CHAINS

The corner is located on the east edge of a dirt road extending north and south. An 8 foot tall wire fence extending north and south is approximately 20 feet west of the corner.

- 78.991 The 1/4 section corner of sections 5 and 32, on the north boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, projecting 3 inches above ground, in a mound of stone, to top of brass cap marked as described in the official record of the 2004 resurvey.

From the true point for the 1/4 section corner of sections 4 and 5.

N. 89°45.0' W., on the E-W centerline of section 5.

- 19.960 Point for the center E 1/16 section corner of section 5.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, with aluminum cap marked:

E 1/16
C ——— C
S5
2010

An 8 foot tall fence extending north and south is approximately 8 feet west of the corner. A dirt road extending north and south is approximately 8 feet east of the corner.

- 39.920 The point for the center 1/4 section corner of section 5.

- 79.674 The 1/4 section corner of sections 5 and 6.

From the center E 1/16 section corner of section 5.

N. 0°14.3' E., on the N-S centerline of the NE 1/4 of section 5.

- 20.054 Point for the NE 1/16 section corner, at intersection with the E-W centerline of the NE 1/4 of section 5, monumented with a 3/8 inch rebar and a plastic cap marked PLS 148951. This position is accepted as a faithful establishment of the corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with aluminum cap marked:

NE 1/16 S5
2010

Deposit rebar and cap inside the aluminum post.

A railroad tie fence post is located approximately 3 feet south of the aluminum post, and a north and south barbed wire fence is

THE SUBDIVISION OF SECTION 5,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

approximately 7 feet west of this same post, among cottonwood trees.

- 39.988 The E 1/16 section corner of section 5 and 32, on the north boundary of the township, monumented with a PK-nail flush with surface of a paved road, bears NW and SE, as described in the official record of the 2004 resurvey.

From the N 1/16 section corner of sections 4 and 5.

N. 89°52.6' W., on the E-W centerline of section 5.

- 19.964 The NE 1/16 section corner of section 5.

- 39.928 The center N 1/16 section corner of section 5.

The Subdivision of Section 9,
Township 2 South, Range 7 West, Uintah Special Meridian, Utah

From the 1/4 section corner of sections 9 and 16.

N. 0°13.3' E., on the N-S centerline of section 9.

- 19.748 Point for the center S 1/16 section corner of section 9, not monumented.

- 39.496 Point for the center 1/4 section corner, at intersection with the E-W centerline of section 9.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 20 inches in the ground, in a mound of stone, 3 foot base, 8 inches high, with aluminum cap marked:

T2S R7W
C1/4 S9
2010

The corner is located on the east edge of a wash draining northwest.

- 59.507 Point for the center N 1/16 section corner of section 9.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with aluminum cap marked:

C
N1/16 | S9
C
2010

- 79.518 The true point for the 1/4 section corner of sections 4 and 9.

From the 1/4 section corner of section 9 and 10.

THE SUBDIVISION OF SECTION 9,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

S. 89°45.6' W., on the E-W centerline of section 9.

20.055 Point for the center E 1/16 section corner of section 9.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 23 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S9} \\ \text{2010} \end{array}$$

Raise a mound of stone, 3 foot base, 1 foot high, on the downhill side of the corner.

Corner is located on a rocky northwest facing slope.

40.110 The center 1/4 section corner of section 9.

80.935 The 1/4 section corner of section 8 and 9.

From the center E 1/16 section corner of section 9.

N. 0°00.7' E., on the N-S centerline of the NE 1/4 of section 9.

19.968 Point for the NE 1/16 section corner, at the intersection with the E-W centerline of the NE 1/4 of section 9.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{NE } 1/16 \quad \text{S9} \\ \text{2010} \end{array}$$

Corner is located among scattered willows.

39.937 The E 1/16 section corner of sections 4 and 9.

From the N 1/16 section corner of sections 9 and 10.

S. 89°52.9' W., on the E-W centerline of the NE 1/4 of section 9.

19.980 The NE 1/16 section corner of section 9.

39.960 The center N 1/16 section corner of section 9.

From the point for the E 1/16 section corner of sections 9 and 16.

N. 0°31.8' E., on the N-S centerline of the SE 1/4 of section 9.

19.782 The SE 1/16 section corner, at intersection with the E-W

THE SUBDIVISION OF SECTION 9,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

centerline of the SE 1/4 of section 9.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with aluminum cap marked:

SE 1/16 S9
2010

Set a steel fence post on the north side of the corner.

39.564 The center E 1/16 section corner of section 9.

From the S 1/16 section corner of sections 9 and 10.

S. 89°51.2' W., on the E-W centerline of the SE 1/4 of section 9.

19.949 The SE 1/16 section corner of section 9.

39.898 The point for the center S 1/16 section corner of section 9.

The Subdivision of Section 10,
Township 2 South, Range 7 West, Uintah Special Meridian, Utah

From the 1/4 section corner of sections 10 and 15.

N. 0°55.4' E., on the N-S centerline of section 10.

19.838 Point for the center S 1/16 section corner of section 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 27 inches in the ground, with aluminum cap marked:

C
S1/16 | S10
C
2010

Corner is located in the middle of a swamp in the Duchesne River flood plain. An 8 feet tall fence, extending northwest and southeast is approximately 100 feet south of the corner.

39.676 Point for the center 1/4 section corner, at the intersection with the E-W centerline of section 10, falls in the middle of the field in an elk ranch, where it is impracticable to set a permanent monument.

59.359 Point for the center N 1/16 section corner of section 10, falls in the middle of a hay field where it is impracticable to set a permanent monument.

79.042 The 1/4 section corner of sections 3 and 10.

THE SUBDIVISION OF SECTION 10,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 10 and 11.

S. 89°18.5' W., on the E-W centerline of section 10.

38.905 The point for the center 1/4 section corner of section 10.

58.629 Point for the center W 1/16 section corner of section 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter with magnet at base, 28 inches in the ground, with aluminum cap marked:

W 1/16
C-----C
S10
2010

Corner is located approximately 15 feet north of the left bank of the Duchesne River.

68.491 Point for the center W-W 1/64 section corner of section 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with aluminum cap marked:

S10
C-W-W
1/64
2010

Corner is located on a north facing slope. The right bank of the Duchesne River is approximately 70 feet north of the corner.

78.353 The 1/4 section corner of sections 9 and 10.

From the W 1/16 section corner of sections 10 and 15.

N. 0°52.9' E., on the N-S centerline of the SW 1/4 of section 10.

19.827 Point for the SW 1/16 section corner, at the intersection with the E-W centerline of the SW 1/4 of section 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with aluminum cap marked:

SW 1/16 S10
2010

Set a steel fence post on the north side of the corner.

The corner is located on a northeast facing slope.

39.654 The center W 1/16 section corner of sections 10.

From the center S 1/16 section corner of section 10.

THE SUBDIVISION OF SECTION 10,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

S. 89°20.4' W., on the E-W centerline of the SW 1/4 of section 10.

19.711 The SE 1/16 section corner of section 10.

39.422 The S 1/16 section corner of sections 9 and 10.

From the center W 1/16 section corner of section 10.

N. 0°21.5' E., on the N-S centerline of the NW 1/4 of section 10.

19.802 Point for the NW 1/16 section corner, at the intersection with the E-W centerline of the NW 1/4 of section 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, with aluminum cap marked:


NW1/16 S10
2010

Corner is located in a swamp. A fence extending north and south is 20 feet east of the corner.

29.704 Point for the center N-NW 1/64, not monumented.

38.990 Point selected for the witness corner to the W 1/16 section corner of sections 3 and 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with aluminum cap marked:



39.606 The true point for the W 1/16 section corner of sections 3 and 10.

From the point for the center N 1/16 section corner of section 10.

S. 89°40.1' W., on the E-W centerline of the NW 1/4 of section 10.

19.916 The NW 1/16 section corner of section 10.

29.874 Point for the center W-NW 1/64 section corner of section 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 27 inches in the ground, with aluminum cap

THE SUBDIVISION OF SECTION 10,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH
CHAINS

marked:

S10
C-W-NW
1/64
2010

The corner is located in a grassy pasture.

39.832 The N 1/16 section corner of sections 9 and 10.

From the center W-W 1/64 section corner of section 10.

N. 0°04.7' E., on the N-S centerline of the SW 1/4 of the NW 1/4 of section 10.

19.864 The center W-NW 1/64 section corner of section 10.

N. 0°04.7' E., on the N-S centerline of the NW 1/4 of the NW 1/4 of section 10.

9.932 Point for the NW-NW 1/64 section corner, at intersection with the E-W centerline of the NW 1/4 of the NW 1/4 of section 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 29 inches in the ground, with aluminum cap marked:

S10
NW-NW
1/64
2010

Corner is located in a grassy pasture.

14.898 Point for the center N-NW-NW 1/256 section corner of section 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with aluminum cap marked:

S10
C-N-NW-NW
1/256
2010

The corner is located in a grassy pasture.

19.864 The point for the W-W 1/64 section corner of sections 3 and 10.

From the point for the center N-NW 1/64 section corner of section 10.

S. 89°50.7' W., on the E-W centerline of the NW 1/4 of the NW 1/4 of section 10.

THE SUBDIVISION OF SECTION 10,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

- 10.006 The NW-NW 1/64 section corner of section 10.
20.012 The N-N 1/64 section corner of sections 9 and 10.

From the center N-NW-NW 1/256 section corner of section 10.

S. 89°56.0' W., on the E-W centerline of the NW 1/4 of the NW 1/4 of the NW 1/4 of section 10.

- 10.030 The N-N-N 1/256 section corner of sections 9 and 10.

The Subdivision of Section 13,
Township 2 South, Range 7 West, Uintah Special Meridian, Utah

From the 1/4 section corner of sections 13 and 24.

N. 0°07.2' W., on the N-S centerline of section 13.

- 19.908 Point for the center S 1/16 section corner of section 13, not monumented.
39.816 Point for the center 1/4 section corner, at intersection with the E-W centerline of section 13. Not monumented.
59.728 Point for the center N 1/16 section corner of section 13, not monumented.
79.640 The 1/4 section corner of sections 12 and 13.

From the 1/4 section corner of sections 13 and 18, on the east boundary of the township, hereinbefore described.

N. 89°59.6' W., on the E-W centerline of section 13.

- 20.016 Point for the center E 1/16 section corner of section 13, not monumented.
40.032 The point for the center 1/4 section corner of section 13.
60.063 Point for the center W 1/16 section corner of section 13, not monumented.
80.094 The point for the 1/4 section corner of sections 13 and 14.

From the point for the E 1/16 section corner of sections 13 and 24.

N. 0°02.5' E., on the N-S centerline of the SE 1/4 of section 13.

- 19.804 Point for the SE 1/16 section corner, at intersection with the E-W centerline of the SE 1/4 of section 13, not monumented.
39.608 The point for the center E 1/16 section corner of section 13.

THE SUBDIVISION OF SECTION 13,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

From the S 1/16 section corner of sections 13 and 18 on the east boundary of the township, hereinbefore described.

S. 89°42.5' W., on the E-W centerline of the SE 1/4 of section 13.

19.961 The SE 1/16 section corner of section 13.

39.922 The point for the center S 1/16 section corner of section 13.

From the point for the center W 1/16 section corner of section 13.

N. 0°08.9' E., on the N-S centerline of the NW 1/4 of section 13.

19.856 Point for the NW 1/16 section corner, at intersection with the E-W centerline of the NW 1/4 of section 13, not monumented.

39.712 The point for the W 1/16 section corner of sections 12 and 13.

From the point for the center N 1/16 section corner of section 13.

S. 89°50.8' W., on the E-W centerline of the NW 1/4 of section 13.

19.937 The point for the NW 1/16 section corner of section 13.

39.874 The point for the N 1/16 section corner of sections 13 and 14.

The Subdivision of Section 14,
Township 2 South, Range 7 West, Uintah Special Meridian, Utah

From the 1/4 section corner of sections 14 and 23.

N. 0°08.5' W., on the N-S centerline of section 14.

39.444 Point for the center 1/4 section corner, at intersection with the E-W centerline of section 14, not monumented.

59.268 Point for the center N 1/16 section corner of section 14, not monumented.

79.092 The point for the 1/4 section corner of sections 11 and 14.

From the point for the 1/4 section corner of sections 13 and 14.

N. 89°46.6' W., on the E-W centerline of section 14.

19.707 Point for the center E 1/16 section corner of section 14, not

THE SUBDIVISION OF SECTION 14,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

- monumented.
- 39.414 The point for the center 1/4 section corner of section 14.
- 59.226 Point for the center W 1/16 section corner of section 14, not monumented.
- 79.038 The 1/4 section corner of sections 14 and 15.

From the point for the center E 1/16 section corner of section 14.

N. 0°08.3' E., on the N-S centerline of the NE 1/4 of section 14.

- 19.812 Point for the NE 1/16 section corner, at intersection with the E-W centerline of the NE 1/4 of section 14, not monumented.
- 39.624 The point for the E 1/16 section corner of sections 11 and 14.

From the point for the N 1/16 section corner of sections 13 and 14.

N. 89°44.6' W., on the E-W centerline of the NE 1/4 of section 14.

- 19.803 The point for the NE 1/16 section corner of section 14.
- 39.606 The point for the center N 1/16 section corner of section 14.

From the point for the center W 1/16 section corner of section 14.

N. 0°16.2' W., on the N-S centerline of the NW 1/4 of section 14.

- 19.837 Point for the NW 1/16 section corner, at intersection with the E-W centerline of the NW 1/4 of section 14, not monumented.
- 39.674 The point for the W 1/16 section corner of sections 11 and 14.

From the point for the center N 1/16 section corner of section 14.

N. 89°44.6' W., on the E-W centerline of the NW 1/4 of section 14.

- 19.856 The point for the NW 1/16 section corner of section 14.
- 39.712 The point for the N 1/16 section corner of sections 14 and 15.

The Subdivision of Section 15,
Township 2 South, Range 7 West, Uintah Special Meridian, Utah

From the 1/4 section corner of sections 15 and 22.

THE SUBDIVISION OF SECTION 15,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

N. 0°19.4' W., on the N-S centerline of section 15.

39.632 Point for the center 1/4 section corner, at intersection with the E-W centerline of section 15, not monumented.

59.516 Point for the center N 1/16 section corner of section 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{C} \\ \text{N1/16} \mid \text{S15} \\ \text{C} \\ 2010 \end{array}$$

Set a steel fence post alongside the north side of the corner.

79.400 The 1/4 section corner of sections 10 and 15.

From the 1/4 section corner of sections 14 and 15.

S. 89°16.1' W., on the E-W centerline of section 15.

39.453 The point for the center 1/4 section corner of section 15.

59.075 Point for the center W 1/16 section corner of section 15, not monumented.

78.697 The 1/4 section corner of sections 15 and 16.

From the point for the center W 1/16 section corner of section 15.

N. 0°26.0' W., on the N-S centerline of the NW 1/4 of section 15.

19.902 Point for the NW 1/16 section corner, at intersection with the E-W centerline of section 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{NW1/16 S15} \\ 2010 \end{array}$$

Set a steel fence post on the north side of the corner.

39.804 The W 1/16 section corner of sections 10 and 15.

From the center N 1/16 section corner of section 15.

S. 89°19.2' W., on the E-W centerline of the NW 1/4 of section 15.

THE SUBDIVISION OF SECTION 15,
TOWNSHIP 2 SOUTH, RANGE 7 WEST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

19.660 The NW 1/16 section corner of section 15.

39.320 The point for the N 1/16 section corner of sections 15 and 16.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Daniel T. Gillins	Cadastral Surveyor
Richard B. West	Survey Technician
Christopher May	Survey Technician
David Gillins	Survey Technician

CERTIFICATE OF SURVEY

I, **Ronald K. Batty, Cadastral Surveyor**, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing the date of the **14th day of June 2010**, I have **dependently resurveyed a portion of the east and north boundaries, and a portion of the subdivisional lines, and subdivided sections 4, 5, 9, 10, 13, 14, and 15, in Township 2 South, Range 7 West, of the Uintah Special Meridian, in the State of Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

June 29, 2011

Date



Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the **dependent resurvey of a portion of the east and north boundaries, and a portion of the subdivisional lines, and the subdivision of sections 4, 5, 9, 10, 13, 14, and 15 in Township 2 South, Range 7 West, Uintah Special Meridian, Utah**, executed by **Ronald K. Batty, Cadastral Surveyor**, having been critically examined and found correct, are hereby approved.

June 30, 2011

Date



Chief Cadastral Surveyor for Utah