

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE EAST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 26, 33, 34, 35, AND 36,

IN

TOWNSHIP 38 SOUTH, RANGE 23 EAST,

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Scott A. Burkhardt*  
*Cadastral Surveyor*

Under Special Instructions dated and approved *June 4, 2010*, which provided for the surveys included under Group Number *1140*, and Assignment Instructions dated *June 4, 2010*.

Survey Commenced, *June 8, 2010*  
Survey Completed, *August 3, 2010*

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE EAST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 26, 33, 34, 35, AND 36,

IN

TOWNSHIP 38 SOUTH, RANGE 23 EAST,

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Scott A. Burkhardt*  
*Cadastral Surveyor*

Under Special Instructions dated and approved *June 4, 2010*, which provided for the surveys included under Group Number *1140*, and Assignment Instructions dated *June 4, 2010*.

Survey Commenced, *June 8, 2010*  
Survey Completed, *August 3, 2010*

## INDEX DIAGRAM

Township 38 South, Range 23 East.

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	12 29	28	27	6 26	5 25
12	12	10	9	6	4
31	11 32	9 33	8 34	5 35	4 36 3

The Subdivision of Section 26.....13  
 The Subdivision of Section 33.....14  
 The Subdivision of Section 34.....15  
 The Subdivision of Section 35.....15  
 The Subdivision of Section 36.....16

## TOWNSHIP 38 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of a portion of the east boundary, a portion of the subdivisional lines, and the subdivision of sections 26, 33, 34, 35, and 36, in T. 38 S., R. 23 E., Salt Lake Meridian, Utah.

## HISTORY OF SURVEYS

Surveyed by		Retr. or Resurveyed by	
<b>SOUTH BOUNDARY</b>			
All	D.B. Miller & J.C. Thoma	1912	
Portion			R.A. Zaninovich 1984
All			S.A. Burkhardt 2007
<b>EAST BOUNDARY</b>			
All	D.B. Miller & J.C. Thoma	1912	
<b>WEST BOUNDARY (Colorado Guide Meridian)</b>			
All	F. Dickert	1878	
All			A.P. Hansen 1907
All			D.B. Miller & J.C. Thoma 1912
Portion			R.A. Zaninovich 1984
<b>NORTH BOUNDARY</b>			
All	D.B. Miller & J.C. Thoma	1912	
<b>SUBDIVISION</b>			
All	D.B. Miller & J.C. Thoma	1912	
Portion	R.A. Zaninovich	1984	

## TOWNSHIP 38 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 1140, dated June 4, 2010.

The direction of the lines was determined by references to true meridian, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards for the Positional Accuracy of Cadastral Surveys When Using Global Navigation Satellite Systems (GNSS)*, dated February 23, 2009. Trimble model 5800 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from GPS static observations, post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS): DI3419 P012 MONTICELLOUT2006 CORS ARP, DW6916 MC04 MESA CNTY 04 COOP CORS ARP, and DL3642 MC09 NUCLA CORS ARP.

The corner of sections 29, 30, 31, and 32, T. 38 S., R. 23 E., as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: 37°26'49.150" N.,  
Longitude: 109°25'19.126" W., N.A.D. 83,  
Network Accuracy = 0.200 meter at 95% confidence

The corner of sections 23, 24, 25, and 26, T. 38 S., R. 23 E., as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: 37°27'41.601" N.,  
Longitude: 109°20'57.061" W., N.A.D. 83,  
Network Accuracy = 0.200 meter at 95% confidence

All stainless steel monuments set in this survey bear the Navajo seal, unless otherwise noted.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
TOWNSHIP 38 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the East Boundary,  
T. 38 S., R. 23 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by D.B. Miller  
and J.C. Thoma in 1912

Beginning at the corner of sections 1, 6, 31, and 36, Tps. 38 and 39 S., Rs. 23 and 24 E., monumented with an iron post, 3 inches diameter, firmly set, projecting 17 inches above the ground, with brass cap (GLO) marked as described in the official record of the 2007 dependent resurvey of T. 39 S., R. 23 E.

A steel fence post is west of corner.

N. 0°02.3' E., between sections 31 and 36.

- 40.039 Point for the 1/4 section corner of sections 31 and 36, at proportionate distance.

Found the original iron post, 1 inch diameter, bent and laying loose on the ground, with brass cap (GLO) marked as described in the official record of the 1912 survey. There is no remaining evidence of the location of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

T38S	
R23E	R24E
1/4	
S36	S31
2010	

Remove original monument from location.

Set a steel fence post north of corner.

Corner is located in a gently rolling field with sagebrush.

- 80.078 The corner of sections 25, 30, 31, and 36, monumented with an iron post, 3 inches diameter, firmly set, projecting 17 inches above the ground, with brass cap (GLO) marked as described in the official record of the 1912 survey.

Corner is located in a barbed-wire fence, extending east and west.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 38 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 38 S., R. 23 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by D.B. Miller  
and J.C. Thoma in 1912

From the corner of sections 1, 2, 35, and 36, on the south boundary of the township, monumented with an iron post, 3 inches in diameter, firmly set, projecting 11 inches above the ground, with brass cap (GLO) marked as described in the official record of the 2007 dependent resurvey of T. 39 S., R. 23 E.

A steel fence post is north of the iron post.

N. 0°03.7' E., between sections 35 and 36.

- 40.043 Point for the 1/4 section corner of sections 35 and 36, at proportionate distance. There is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T38S R24E

1/4

S35 | S36

2010

Set a steel fence post north of corner.

Corner is located in gently rolling, open terrain, with grasses.

- 80.086 The corner of sections 25, 26, 35, and 36, monumented with an iron post, 2 inches diameter, firmly set in cement, projecting 26 inches above the ground, with brass cap (GLO) marked as described in the official record of the 1912 survey.

Corner is located northeast of the intersection of barbed-wire fences, extending north and east.

From the corner of sections 25, 30, 31, and 36, on the east boundary of the township, hereinbefore described.

S. 89°57.6' W., between sections 25 and 36.

- 11.574 The centerline of San Juan County Road No. 408, a gravel road, 24 feet wide, bears N. 30° W. and S. 30° E.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 38 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 39.957 The 1/4 section corner of sections 25 and 36, monumented with an iron post, 1 inch diameter, firmly set, projecting 17 inches above the ground, with brass cap (GLO) marked as described in the official record of the 1912 survey.

Corner is located in a barbed-wire fence, extending east and west.

Set a steel fence post south of corner.

---

S. 89°58.1' W., beginning new measurement.

- 40.014 The corner of sections 25, 26, 35, and 36.

---

N. 0°03.4' E., between sections 25 and 26.

- 40.037 The 1/4 section corner of sections 25 and 26, monumented with an iron post, 1 inch diameter, firmly set, projecting 13 inches above the ground, with brass cap (GLO) marked as described in the official record of the 1912 survey.

Corner is located in a barbed-wire fence, extending north and south.

Set a steel fence post east of corner.

---

N. 0°03.0' E., beginning new measurement.

- 40.004 The corner of sections 23, 24, 25, and 26, monumented with an iron post, 2 inches diameter, firmly set in cement, projecting 19 inches above the ground, with brass cap (GLO) marked as described in the official record of the 1912 survey.

Corner is located immediately southwest of the intersection of barbed-wire fences, extending south and west.

---

From the corner of sections 2, 3, 34, and 35, on the south boundary of the township, monumented with an iron post, 3 inches diameter, firmly set, projecting 15 inches above the ground, with brass cap (GLO) marked as described in the official record of the 1912 survey.

A steel fence post is north of the iron post.

N. 0°01.7' E., between sections 34 and 35.

- 40.035 Point for the 1/4 section corner of sections 34 and 35, at proportionate distance. There is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches in diameter, 29 inches in the ground, magnet at base, with brass

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 38 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

cap marked:

T38S R23E

1/4

S34 | S35

2010

Set a steel fence post north of corner.

Corner is located on level, open, grassy terrain, with houses to the west.

From this corner point, the southwest corner of a cemetery, bears N. 59°00.7' E., 13.178 chains distance.

- 80.070 The corner of sections 26, 27, 34, and 35, monumented with an iron post, 2 inches diameter, firmly set in cement, projecting 24 inches above the ground, with brass cap (GLO) marked as described in the official record of the 1912 survey.

An embedded mound of stone is west of the iron post.

Corner is located immediately northwest of a barbed-wire fence, extending north and west.

From the corner of sections 25, 26, 35, and 36.

S. 89°59.3' W., between sections 26 and 35.

- 40.043 The 1/4 section corner of sections 26 and 35, monumented with an iron post, 1 inch diameter, firmly set, projecting 19 inches above the ground, with brass cap (GLO) marked as described in the official record of the 1912 survey.

A mound of stone, 3 feet base, 1 foot high, is north of corner.

Set a steel fence post northwest of corner.

S. 89°56.2' W., beginning new measurement.

- 40.059 The corner of sections 26, 27, 34, and 35.

N. 0°03.6' E., between sections 26 and 27.

- 19.967 Point for the S 1/16 section corner of sections 26 and 27.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 38 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T38S R23E

S 1/16

S27 | S26

2010

Set a steel fence post east of corner.

Corner is located in a barbed-wire fence, extending north and south.

- 39.934 The 1/4 section corner of sections 26 and 27, monumented with an iron post, 1 inch diameter, firmly set, projecting 18 inches above the ground, with brass cap (GLO) marked as described in the official record of the 1912 survey.

Corner is located in a barbed-wire fence, extending north and south.

---

N. 0°01.3' E., beginning new measurement.

- 40.132 The corner of sections 22, 23, 26, and 27, monumented with an iron post, 2 inches diameter, firmly set, projecting 18 inches above the ground, with brass cap (GLO) marked as described in the official record of the 1912 survey.

Corner is located immediately southeast of the intersection of barbed-wire fences, extending east and south.

---

From the corner of sections 23, 24, 25, and 26.

S. 89°58.9' W., between sections 23 and 26.

- 40.052 Point for the 1/4 section corner of sections 23 and 26, at proportionate distance.

The original iron post, 1 inch diameter, 36 inches long, projecting 34 inches above a small circle of cement, with brass cap (GLO) marked as described in the official record of the 1912 survey, and was found above ground in a nearby fence line. Instability of monument renders it unacceptable as proof of the original corner position.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, in a collar of stone, 2 feet diameter, magnet at base, with brass cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 38 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH  
CHAINS

T38S R23E  
S23  
1/4 ———  
S26  
2010

Bury original iron post south of corner.

Set a steel fence post north of corner.

Corner is located in a barbed-wire fence, extending east and west.

- 80.104 The corner of sections 22, 23, 26, and 27.

---

From the corner of sections 3, 4, 33, and 34, on the south boundary of the township, monumented with an iron post, 3 inches diameter, firmly set, flush in a mound of stone, 2 feet base, 1 foot high, with brass cap (GLO) marked as described in the official record of the 1912 survey.

A steel fence post is north of the iron post.

N. 0°01.6' W., between sections 33 and 34.

- 19.611 The centerline of Utah State Highway No. 262, a 25 foot paved road, bears N. 83° W. and S. 83° E.

- 40.067 The 1/4 section corner of sections 33 and 34, monumented with an iron post, 1 inch diameter, firmly set, projecting 20 inches above the ground, with brass cap (GLO) marked as described in the official record of the 1912 survey. Cap oriented N. 60° W.

Rehabilitate original mound of stone, 3 feet base to top of brass cap.

Set a steel fence post southeast of corner.

---

N. 0°03.8' W., beginning new measurement.

- 40.078 The corner of sections 27, 28, 33, and 34, monumented with an iron post, 2 inches diameter, loosely set, and rusted at base, 20 inches long, set in a mound of stone, 2 feet base, 1 foot high, with brass cap (GLO) marked as described in the official record of the 1912 survey.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 8 inches in the ground, magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 38 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH  
CHAINS

T38S R23E

S28	S27
S33	S34

2010

Bury original iron post west of corner.

Set a steel fence post east of corner.

Corner is located on gently-rolling terrain, in a barbed-wire fence, extending east and west.

From the corner of sections 26, 27, 34, and 35.

N. 89°59.6' W., between sections 27 and 34.

- 40.061 The 1/4 section corner of sections 27 and 34, monumented with an iron post, 1 inch diameter, firmly set, projecting 13 inches above the ground, with brass cap (GLO) marked as described in the official record of the 1912 survey.

Set a steel fence post south of corner.

Corner is located in a barbed-wire fence, extending east and west.

S. 89°58.0' W., beginning new measurement.

- 40.000 The corner of sections 27, 28, 33, and 34.

From the corner of sections 4, 5, 32, and 33, on the south boundary of the township, monumented with a PK nail set flush in pavement of Utah State Highway No. 262, with a brass washer, 1 1/2 inches diameter, marked BLM Cadastral Survey, as described in the official record of the 2007 dependent resurvey of T. 39 S., R. 23 E.

From which:

A stainless steel post, functioning as a reference monument, 2 1/2 inches diameter, firmly set, projecting 1 inch above the ground, in a collar of stone, 1 1/2 feet diameter, bears S. 71°16' E., 0.722 chains distance, with brass cap marked as described in the official record of the 2007 resurvey.

A steel fence post is north of reference monument.

A stainless steel post, functioning as a reference monument,

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 38 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

2 1/2 inches diameter, firmly set, projecting 1 inch above the ground, in a collar of stone, 1 1/2 feet diameter, bears S. 20°07' W., 1.460 chains distance, with brass cap marked as described in the official record of the 2007 resurvey.

A steel fence post is north of reference monument.

N. 0°00.5' E., between sections 32 and 33.

- 0.146 The centerline of Utah State Highway No. 262, a paved road, 25 feet wide, extending N. 47° E. and S. 47° W.
- 40.037 Point for the 1/4 section corner of sections 32 and 33, at proportionate distance.

Found the original iron post, 1 inch diameter, 36 inches long, wired to a steel fencepost in a barbed-wire fence, with brass cap (GLO) marked as described in the official record of the 1912 survey. There is no other remaining evidence of the location of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 9 inches in the ground to bedrock, magnet at base, in a mound of stone, 4 feet base to top of brass cap marked:

T38S R23E

1/4  
S32 | S33

2010

Bury original iron post at base of mound of stone.

Set a steel fence post northeast of corner.

Corner is located in a barbed-wire fence, extending north and south.

- 80.074 The corner of sections 28, 29, 32, and 33, monumented with an iron post, 2 inches diameter, firmly set, flush with the ground, with brass cap (GLO) marked as described in the official record of the 1912 survey.

Corner is located immediately southeast of the intersection of barbed-wire fences, extending east and south.

From the corner of sections 27, 28, 33, and 34.

S. 89°53.5' W., between sections 28 and 33.

- 39.903 The 1/4 section corner of sections 28 and 33, monumented with an

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 38 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

iron post, 1 inch diameter, firmly set, projecting 18 inches above the ground, with brass cap (GLO) marked as described in the official record of the 1912 survey.

Corner is located in a barbed-wire fence, extending east and west.

Set a steel fence post north of corner.

---

S.  $89^{\circ}56.3'$  W., beginning new measurement.

39.996 The corner of sections 28, 29, 32, and 33.

---

From the corner of sections 5, 6, 31, and 32, on the south boundary of the township, monumented with an iron post, 3 inches diameter, firmly set, flush in a mound of stone, 3 feet base, 2 feet high, with brass cap (GLO) marked as described in the official record of the 1912 survey.

A steel fence post is north of the iron post.

Corner is located on a moderately-steep, south-facing slope, approximately midway in elevation between valley bottom and mesa top.

N.  $0^{\circ}05.8'$  W., between sections 31 and 32.

39.979 The  $1/4$  section corner of sections 31 and 32, monumented with an iron post, 1 inch diameter, firmly set, projecting 14 inches above the ground, with brass cap (GLO) marked as described in the official record of the 1912 survey.

A mound of stone, 2 feet base, 2 feet high, is west of corner.

Add a mound of stone around iron post, 2 feet base to top of brass cap.

Set a steel fence post north of corner.

Corner is located on an east-facing slope, in a large drainage.

---

N.  $0^{\circ}13.2'$  W., beginning new measurement.

40.007 The corner of sections 29, 30, 31, and 32, monumented with an iron post, 2 inches diameter, firmly set, projecting 16 inches above the ground, with brass cap (GLO) marked as described in the official record of the 1912 survey.

Set a steel fence post north of corner.

---

From the corner of sections 28, 29, 32, and 33.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 38 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH  
CHAINS

S. 89°49.5' W., between sections 29 and 32.

- 40.309 The 1/4 section corner of sections 29 and 32, determined at the center of a mound of stone, 2 feet base, 1 foot high, with a mound of stone to the north. There is no remaining evidence of the iron post. This mound of stone is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches in diameter, 4 inches in the ground to bedrock, magnet at base, in a mound of stone, 3 feet base to top of brass cap marked:

T38S R24E

S29  
1/4 ———  
S32

2010

Set a steel fence post north of corner.

Corner is located on a gentle south-sloping mesa top.

---

S. 89°55.8' W., beginning new measurement.

- 39.841 The corner of sections 29, 30, 31, and 32.

---

S. 89°59.1' W., between sections 30 and 31.

- 40.242 The 1/4 section corner of sections 30 and 31, monumented with an iron post, 1 inch diameter, firmly set, projecting 18 inches above the ground, with brass cap (GLO) marked as described in the official record of the 1912 survey.

From the corner, barbed-wire fences extend south and west.

---

From the corner of sections 29, 30, 31, and 32.

N. 0°06.4' E., between sections 29 and 30.

- 39.953 The 1/4 section corner of sections 29 and 30, monumented with an iron post, 1 inch diameter, firmly set, projecting 16 inches above the ground, with brass cap (GLO) marked as described in the official record of the 1912 survey.

Set a steel fence post south of corner.

---

N. 0°01.9' E., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 38 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.055 The corner of sections 19, 20, 29, and 30, monumented with an iron post, 2 inches diameter, firmly set, projecting 18 inches above the ground, with brass cap (GLO) marked as described in the official record of the 1912 survey.

From which:

- A juniper, 13 inches diameter, bears N. 57°08.6' E., 78.1 links distance, with a partially-healed blaze with undecipherable markings (Record: N. 57° E., 78 links distance, marked T38S R23E S20 BT).
- A juniper, 12 inches diameter, bears S. 49°53.7' E., 73.2 links distance, with a partially-healed blaze with undecipherable markings (Record: S. 51°15'E., 72 links distance, marked T38S R23E S29 BT).
- A juniper snag, bears N. 65°31.2' W., 62.0 links distance, with a partially-healed blaze with undecipherable markings (Record: N. 64°W., 61 links distance, marked T38S R23E S19 BT).

Set a steel fence post south of corner.

---

The Subdivision of Section 26,  
T. 38 S., R. 23 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 26 and 35.

N. 0°02.5' E., on the N-S centerline of section 26.

- 39.968 Point for the center 1/4 section corner, at intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T38S R23E

C1/4 S26

2010

Set a steel fence post northeast of corner.

Corner is located on a gentle southwest-slope in scattered juniper trees.

- 80.036 The 1/4 section corner of sections 23 and 26.

---

From the 1/4 section corner of sections 25 and 26.

THE SUBDIVISION OF SECTION 26,  
TOWNSHIP 38 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

- S. 89°53.4' W., on the E-W centerline of section 26.
- 40.050 The center 1/4 section corner of section 26.
- 80.092 The 1/4 section corner of sections 26 and 27.
- 

The Subdivision of Section 33,  
T. 38 S., R. 23 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 4 and 33, on the south boundary of the township, monumented with an iron post, 1 inch diameter, firmly set, projecting 17 inches above the ground, with brass cap (GLO) marked as described in the official record of the 2007 dependent resurvey of T. 39 S., R. 23 E.

A mound of stone, 2 feet base, 1 1/2 feet high, is north of corner, and a steel fence post east of corner.

N. 0°01.2' E., on the N-S centerline of section 33.

- 9.695 The centerline of Utah State Highway No. 262, a paved road, 25 feet wide, bears N. 65° E. and S. 75° W.
- 40.027 Point for the center 1/4 section corner, at intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, flush in a collar of stone, 2 feet diameter, magnet at base, with brass cap marked:

T38S R23E

C1/4 S33

2010

Set a steel fence post, in a mound of stone, 2 feet base, 1 foot high, north of corner.

Corner is located in an open valley with desert brush.

- 80.069 The 1/4 section corner of sections 28 and 33.
- 

From the 1/4 section corner of sections 33 and 34.

S. 89°56.7' W., on the E-W centerline of section 33.

- 39.965 The center 1/4 section corner of section 33.
- 79.957 The 1/4 section corner of sections 32 and 33.

THE SUBDIVISION OF SECTION 34,  
TOWNSHIP 38 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 34,  
T. 38 S., R. 23 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 3 and 34, on the south boundary of the township, monumented with an iron post, 1 inch diameter, firmly set, projecting 16 inches above the ground, with brass cap (GLO) marked as described in the official record of the 2007 dependent resurvey of T. 39 S., R. 23 E.

A steel fence post is north of corner.

N. 0°00.8' E., on the N-S centerline of section 34.

11.391 The centerline of Utah State Highway No. 262, a paved road, 25 feet wide, extending N. 75° W. and S. 75° E.

40.021 Point for the center 1/4 section corner, at intersection with E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T38S R23E

C1/4 S34

2010

Set a steel fence post north of corner.

Corner is located in rolling hills, with scattered juniper trees.

80.092 The 1/4 section corner of sections 27 and 34.

From the 1/4 section corner of sections 34 and 35.

S. 89°57.3' W., on the E-W centerline of section 34.

40.054 The center 1/4 section corner of section 34.

80.004 The 1/4 section corner of sections 33 and 34.

The Subdivision of Section 35,  
T. 38 S., R. 23 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 2 and 35, on the south boundary of the township, monumented with an iron post, 1 inch diameter, firmly set, projecting 18 inches above the ground, in a mound of stone, 2 1/2 feet base to top of brass cap (GLO) marked as described in the official record of the 2007 dependent resurvey of T. 39 S., R. 23 E.

THE SUBDIVISION OF SECTION 35,  
TOWNSHIP 38 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

A steel fence post is north of corner.

N. 0°03.4' E., on the N-S centerline of section 35.

- 40.039 Point for the center 1/4 section corner, at intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with brass cap marked:

T38S R23E

C1/4 S35

2010

Corner is located in gently-rolling terrain, with scattered sage brush.

- 80.096 The 1/4 section corner of sections 26 and 35.

From the 1/4 section corner of sections 35 and 36.

S. 89°58.1' W., on the E-W centerline of section 35.

- 40.043 The center 1/4 section corner of section 35.

- 80.086 The 1/4 section corner of sections 34 and 35.

The Subdivision of Section 36,  
T. 38 S., R. 23 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 1 and 36, on the south boundary of the township, monumented with an iron post, 1 inch diameter, firmly set, projecting 16 inches above the ground, with brass cap (GLO) marked as described in the official record of the 2007 dependent resurvey of T. 39 S., R. 23 E.

A steel fence post is north of corner.

N. 0°03.7' E., on the N-S centerline of section 36.

- 40.041 Point for the center 1/4 section corner, at intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with brass cap marked:

THE SUBDIVISION OF SECTION 36,  
TOWNSHIP 38 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T38S R23E

C1/4 S36

2010

Corner is located in gently-rolling, open terrain, with desert grasses.

80.080 The 1/4 section corner of sections 25 and 36.

---

From the 1/4 section corner of sections 31 and 36.

S. 89°57.7' W., on the E-W centerline of section 36.

2.382 The centerline of San Juan County No. 408, a gravel road, 24 feet wide, bears N. 2° E. and S. 2° W.

39.976 The center 1/4 section corner of section 36.

79.994 The 1/4 section corner of sections 35 and 36.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Phil Freiberg	Survey Technician

---

## CERTIFICATE OF SURVEY

I, *Scott A. Burkhardt, Cadastral Surveyor*, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing the date of the *4<sup>th</sup> day of June, 2010*, I have *dependently resurveyed a portion of the east boundary, a portion of the subdivisional lines, and subdivided sections 26, 33, 34, 35, and 36, in Township 38 South, Range 23 East, of the Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions of the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

11/16/2011

Date

Scott A. Burkhardt

Cadastral Surveyor

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the east boundary, a portion of the subdivisional lines, and the subdivision of sections 26, 33, 34, 35, and 36, in Township 38 South, Range 23 East, Salt Lake Meridian, Utah*, executed by *Scott A. Burkhardt, Cadastral Surveyor*, having been critically examined and found correct, are hereby approved.

December 2, 2011

Date

Daniel W. Webb

Chief Cadastral Surveyor for Utah