

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF
A PORTION OF THE EAST BOUNDARY
(PANGUITCH AND KANAB GUIDE MERIDIAN),
A PORTION OF THE SUBDIVISIONAL LINES,
THE SUBDIVISION OF SECTION 13,

AND

THE SUBDIVISION OF SECTIONS 14 AND 23,

IN

TOWNSHIP 39 SOUTH, RANGE 6 WEST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Jeremy D. Davis
Cadastral Surveyor

Under Special Instructions dated *July 2, 2010*, approved *July 2, 2010*,
which provided for the surveys included under Group Number *1147*, and
Assignment Instructions dated *July 2, 2010*.

Survey Commenced, *July 14, 2010*
Survey Completed, *July 29, 2010*

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF
A PORTION OF THE EAST BOUNDARY
(PANGUITCH AND KANAB GUIDE MERIDIAN),
A PORTION OF THE SUBDIVISIONAL LINES,
THE SUBDIVISION OF SECTION 13,

AND

THE SUBDIVISION OF SECTIONS 14 AND 23,

IN

TOWNSHIP 39 SOUTH, RANGE 6 WEST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Jeremy D. Davis
Cadastral Surveyor

Under Special Instructions dated *July 2, 2010*, approved *July 2, 2010*,
which provided for the surveys included under Group Number *1147*, and
Assignment Instructions dated *July 2, 2010*.

Survey Commenced, *July 14, 2010*
Survey Completed, *July 29, 2010*

INDEX DIAGRAM

Township 39 South, Range 6 West.

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	6 14	4 13 3
				5	
19	20	21	22	5 23	24
30	29	28	27	26	25
31	32	33	34	35	36

The Dependent Resurvey of Section 13.....7
 The Subdivision of Section 14.....9
 The Subdivision of Section 23.....11

TOWNSHIP 39 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of a portion of the east boundary(Panguitch and Kanab Guide Meridian), a portion of the subdivisional lines, the subdivision of section 13, and the subdivision of sections 14 and 23, in T. 39 S., R. 6 W., Salt Lake Meridian, Utah.

HISTORY OF SURVEYS

	Surveyed by		Retr. or Resurveyed by	
SOUTH BOUNDARY				
Portion	J.G. Burrill	1876		
All	A.J. Stewart Jr.	1883	A.J. Stewart Jr.	1883
Portion			E. Bird	1927-30
Portion			C.P. Sylvester	1974
EAST BOUNDARY (Panguitch and Kanab Guide Meridian)				
All	J.G. Burrill	1876		
Portion			A.J. Stewart Jr.	1883
			S.M. Richardson	1884
			E. Bird	1946
			C.P. Sylvester	1974
			L.V. Judd	2004
WEST BOUNDARY				
All	A.J. Stewart Jr.	1883		
All			R.C. Yundt	1948-49
NORTH BOUNDARY				
All	S.M. Richardson	1884		
All			A. Nelson & E. Bird	1945
SUBDIVISION				
Portion	J.G. Burrill	1876		
All	S.M. Richardson	1884	S.M. Richardson	1884
Portion			E. Bird	1946
Portion			C.P. Sylvester	1974
Portion			L.V. Judd	2004

TOWNSHIP 39 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 1147, dated July 2, 2010.

The directions of the lines were determined by references to true meridian, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards for the Positional Accuracy of Cadastral Surveys When Using Global Navigation Satellite Systems (GNSS), February 23, 2009*. Trimble model 5800 GPS receivers were used for field collection. Cadastral Measurement Management (CMM) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from GPS static observations of, post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS): NVSV SPRING VALLEY CORS ARP, P009 MARYSVALE_UT2006 CORS ARP, AZPG CITY OF PAGE CORS ARP.

The geographic position of the corner of sections 10, 11, 14, and 15, T. 39 S., R. 6 W., as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: 37°25'36.678" N.,
Longitude: 112°30'15.357" W., N.A.D. 83,
Network Accuracy = 0.200 meter at 95% confidence level.

The geographic position of the 1/4 section corner of sections 23 and 24, T. 39 S., R. 6 W., as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: 37°24'18.824" N.,
Longitude: 112°29'11.243" W., N.A.D. 83,
Network Accuracy = 0.200 meter at 95% confidence level.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY
(PANGUITCH AND KANAB GUIDE MERIDIAN),
TOWNSHIP 39 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the East Boundary
(Panguitch and Kanab Guide Meridian),
T. 39 S., R. 6 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by J.G. Burrill in 1876,
and the Resurveys Executed by S.M. Richardson in 1884,
and E. Bird in 1946

From the corner of sections 13, 18, 19, and 24, monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone, 3 feet base to top of brass cap marked as described in the official record of the 1946 resurvey.

Corner falls at the intersection of fences extending east, S. 59° E., and west on level ground.

N. 0°00.8' W., between sections 13 and 18.

- 20.021 The S 1/16 section corner of sections 13 and 18, monumented with an iron post, 1 inch diameter, firmly set, projecting 10 inches above the ground, with brass cap marked as described in the official record of the 1946 resurvey.

Corner falls online of a fence extending north and south.

N. 0°02.9' W., beginning new measurement.

- 20.017 Point for the 1/4 section corner of sections 13 and 18, falls at the centerline of Johnson Valley Road, determined by record bearing and distance from the remaining 1946 bearing tree

A juniper, 18 inches diameter, bears N. 47°30' E., 66 links distance, with a healed blaze.

There is no remaining evidence of the northwest bearing tree.

At the corner point

Set a Railroad spike flush with the road surface.

from which

An aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, for a reference monument, bears S. 34°28.5' E., 163.3 links distance, with aluminum cap marked RM T30S R5W 1/4 S18 107.8 FT TO COR 2010, and an arrow pointing to the corner point.

An aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, for a reference monument, bears S. 60°00.6' W., 75.6 links distance, with aluminum cap marked RM T30S R6W 1/4 S13 49.9 FT TO COR 2010, and an arrow pointing to the corner point.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 39 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 39 S., R. 6 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by J.G. Burrill in 1876,
and the Resurveys Executed by S.M. Richardson in 1884,
and E. Bird in 1946

From the corner of sections 13, 14, 23, and 24, monumented with an iron post, 2 inches diameter, firmly set, projecting 14 inches above the ground, with brass cap marked as described in the official record of the 1974 resurvey; with a mound of stone, 3 feet diameter, west of the corner.

from which the 1946 bearing tree

A pinon, 12 inches diameter, dead and standing, 5 feet above the ground, bears N. 70° E., 15 links distance, marked T39S R6W S13 BT on an open blaze.

There is no remaining evidence of the northwest bearing tree.

Corner falls on flat open ground.

N. 0°04.5' W., between sections 13 and 14.

20.040 Point for the S 1/16 section corner of sections 13 and 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, in a mound of stone, 3 feet base to top of aluminum cap marked

S 1/16
S14|S13
2010

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls online of a fence extending north and south on level ground.

40.080 The 1/4 section corner of sections 13 and 14, monumented with an iron post, 1 inch diameter, firmly set, projecting 10 inches above the ground, with brass cap marked as described in the official record of the 1946 resurvey.

from which the 1946 bearing tree

A juniper, 12 inches diameter, bears N. 68°30' E., 23 links distance, with visible scribed marks on an open blaze.

There is no remaining evidence of the northwest bearing tree.

A mound of stone 2 feet base, 1 foot high, is located east of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 39 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Corner falls 2 feet southwest of the intersection of fences extending north and east on a gentle northeast-facing slope.

Reestablishment of the Survey Executed by J.G. Burrill in 1876,
and the Resurvey Executed by S.M. Richardson in 1884,
and C.P. Sylvester in 1974

From the 1/4 section corner of sections 22 and 23, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 4 inches above the ground, with brass cap marked as described in the official record of the 1974 resurvey.

from which the 1974 bearing tree

A juniper, 14 inches diameter, bears S. 50° E., 9 links distance, marked BT with a chainsaw, on a partially healed blaze.

Corner falls on level ground with heavy piñon, juniper, and oak brush.

N. 0°56.1' E., between sections 22 and 23.

19.832 Point for the N 1/16 section corner of sections 22 and 23.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a mound of stone, 2 feet base to top of aluminum cap marked

N 1/16
S22|S23
2010

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls on a gradual west-facing slope with piñon and juniper growth.

39.664 The corner of sections 14, 15, 22, and 23, monumented with an iron post, 2 1/2 inches diameter, firmly set, in a small mound of stone to top of brass cap marked as described in the official record of the 1974 resurvey.

Corner falls on level ground with heavy piñon, juniper, and oak brush.

From the corner of sections 13, 14, 23, and 24.

S. 88°51.0' W., between sections 14 and 23.

39.179 The 1/4 section corner of sections 14 and 23, monumented with an iron post, 2 1/2 inches diameter, firmly set, in a mound of stone, 3 feet base to top of brass cap marked as described in the official record of the 1974 resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 39 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH
CHAINS

There is no remaining evidence of the southeast bearing tree.

Corner falls on a gradual southeast-facing slope.

S. 88°49.0' W., beginning new measurement.

39.176 The corner of sections 14, 15, 22, and 23.

N. 0°05.7' E., between sections 14 and 15.

40.081 The 1/4 section corner of sections 14 and 15, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 3 inches above the ground, with brass cap marked as described in the official record of the 1974 resurvey.

Corner falls on a gradual southeast-facing slope with heavy piñon, juniper, and oak brush.

N. 0°19.4' E., beginning new measurement.

20.401 Point for the N 1/16 section corner of sections 14 and 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

N 1/16
S15|S14
2010

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls on a gradual northeast-facing slope with dense oak brush, and scattering piñon and juniper growth.

40.802 The corner of sections 10, 11, 14, and 15, monumented with an iron post, 2 1/2 inches diameter, firmly set, in a small mound of stone to top of brass cap marked as described in the official record of the 1974 resurvey.

from which the 1884 bearing trees

A ponderosa pine, 30 inches diameter, bears N. 44° E., 145 links distance, with a healed blaze.

A ponderosa pine, 28 inches diameter, bears S. 2° E., 73 links distance, with a healed blaze.

A ponderosa pine, 24 inches diameter, bears S. 70° W., 185 links distance, with a healed blaze.

A ponderosa pine stump, in a state of decay, 20 inches diameter, bears N. 67° W., 216 links distance, scribed T39S R6W S10 BT, on a partially healed blaze.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 39 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Corner falls on a gradual southwest-facing slope at the edge of a dense ponderosa pine stand.

Dependent Resurvey of the Subdivision of Section 13,
T. 39 S., R. 6 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by E. Bird in 1946

From the 1/4 section corner of sections 13 and 24, monumented with an iron post, 1 inch diameter, firmly set, projecting 9 inches above a mound of stone, 3 feet base to top of brass cap marked as described in the official record of the 1946 resurvey.

from which the 1946 bearing trees

A juniper, 12 inches diameter, bears N. 43°15' E., 62 links distance, scribed 1/4 S13 BT, on a partially healed blaze.

A juniper, dead and standing, 16 inches diameter, bears S. 77°30' E., 40 links distance, scribed 1/4 S24 BT, on an open blaze.

Corner falls 3 feet south of a fence extending east and west on level ground with piñon and juniper growth.

N. 0°03.1' W., on the N-S centerline of section 13.

- 20.031 The center S 1/16 section corner of section 13, monumented with an iron post, 1 inch diameter, firmly set, projecting 10 inches above a mound of stone, 3 feet base to top of brass cap marked as described in the official record of the 1946 survey.

from which the 1946 bearing trees

A juniper, 8 inches diameter, bears S. 33°45' E., 67 links distance, scribed CS 1/16 S 13 BT, on a partially healed blaze.

A juniper, 10 inches diameter, bears N. 9°30' W., 10 links distance, scribed CS 1/16 S 13 BT, on a partially healed blaze.

Corner falls on a gradual southwest-facing slope with piñon and juniper growth.

N. 0°01.3' W., beginning new measurement.

- 20.034 The center 1/4 section corner of section 13, monumented with an iron post, 1 inch diameter, firmly set, projecting 16 inches above the ground, with brass cap marked as described in the official record of the 1946 survey.

from which the 1946 bearing tree

DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 13,
TOWNSHIP 39 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

A piñon, 12 inches diameter, bears S. 22° W., 22 links distance, scribed C 1/4 S13 BT, on a partially healed blaze.

There is no remaining evidence of the northeast bearing tree.

Corner falls online of a fence extending east and west.

N. 0°02.9' W., beginning new measurement.

- 40.106 The 1/4 section corner of sections 12 and 13, monumented with an iron post, 1 inch diameter, firmly set, projecting 6 inches above the ground, with brass cap marked as described in the official record of the resurvey executed in 1946.

There is no remaining evidence of the 1946 bearing trees.

Corner falls on level open ground.

From the point for the 1/4 section corner of sections 13 and 18, on the east boundary of the township, hereinbefore described.

N. 89°59.3' W., on the E-W centerline of section 13.

- 20.064 The center E 1/16 section corner of section 13, monumented with an iron post, 1 inch diameter, firmly set, projecting 12 inches above the ground, with brass cap marked as described in the official record of the 1946 survey.

from which the 1946 bearing tree

A juniper, 20 inches diameter, bears S. 81°30' W., 102 links distance, scribed CE 1/16 S13 BT, on an open blaze.

There is no remaining evidence of the northwest bearing tree.

Corner falls at the intersection of fences extending north, east, and west.

N. 89°58.2' W., beginning new measurement.

- 20.046 The center 1/4 section corner of section 13.
-

N. 89°59.5' W., beginning new measurement.

- 40.147 The 1/4 section corner of sections 13 and 14.
-

From the E 1/16 section corner of sections 13 and 24, monumented with an iron post, 1 inch diameter, projecting 8 inches above the ground, with brass cap marked as described in the official record of the 1946 survey.

from which the 1946 bearing trees

DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 13,
TOWNSHIP 39 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

A juniper, 20 inches diameter, bears S. 37°45' W., 23 links distance, scribed E 1/16 S 24 BT, on a partially healed blaze.

A piñon, 14 inches diameter, bears N. 46°30' W., 40 links distance, scribed E 1/16 S13 BT, on a partially healed blaze.

Corner falls online of an old fence extending east and west, on a gradual east-facing slope with piñon and juniper growth.

N. 0°03.8' W., on the N-S centerline of the SE 1/4 of section 13.

20.041 The SE 1/16 section corner, at the intersection of the E-W centerline of the SE 1/4, monumented with an iron post, 1 inch diameter, firmly set, projecting 10 inches above a mound of stone, 3 feet base to top of brass cap marked as described in the official record of the 1946 survey.

from which the 1946 bearing trees

A piñon, 10 inches diameter, bears S. 70° E., 14 links distance, scribed SE 1/16 S13 BT, on a partially healed blaze.

A piñon, down and dead, scribed SE 1/16 S13 BT, on an open blaze, not remeasured.

Corner falls on a gradual northwest-facing slope with piñon and juniper growth.

N. 0°02.3' W., beginning new measurement.

19.998 The center E 1/16 section corner of section 13.

From the S 1/16 section corner of sections 13 and 18, on the east boundary of the township, hereinbefore described.

N. 89°56.0' W., on the E-W centerline of the SE 1/4 of section 13.

20.068 The SE 1/16 section corner of section 13.

N. 89°55.5' W., beginning new measurement.

20.053 The center S 1/16 section corner of section 13.

The Subdivision of Section 14,
T. 39 S., R 6 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 14 and 23.

N. 0°03.6' W., on the N-S centerline of section 14.

THE SUBDIVISION OF SECTION 14,
TOWNSHIP 39 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

20.037 Point for the center S 1/16 section corner of section 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked

C
S 1/16 | S14
C
2010

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls on level ground with piñon, juniper, and oak brush.

40.074 Point for the center 1/4 section corner, at intersection with the E-W centerline of section 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked

T39SR6W
C 1/4
S14
2010

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls on level ground with oak brush.

60.087 Point for the center N 1/16 section corner of section 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

C
N 1/16 | S14
C
2010

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the corner.

Corner falls 4 feet east of an old fence extending north and south with heavy piñon and juniper growth.

80.100 The 1/4 section corner of sections 11 and 14, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 10 inches above the ground, with brass cap marked as described in the 1974 resurvey.

Corner falls in old fence extending south and east.

THE SUBDIVISION OF SECTION 14,
TOWNSHIP 39 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 13 and 14.

S. 88°49.4' W., on the E-W centerline of section 14.

39.165 The center 1/4 section corner of section 14.

78.229 The 1/4 section corner of sections 14 and 15.

From the S 1/16 section corner of sections 13 and 14.

S. 88°49.7' W., on the E-W centerline of the SE 1/4 of section 14.

39.172 The center S 1/16 section corner of section 14.

From the center N 1/16 section corner of section 14.

S. 89°23.4' W., on the E-W centerline of the NW 1/4 of section 14.

38.919 The point for the N 1/16 section corner of sections 14 and 15.

The Subdivision of Section 23,
T. 39 S., R. 6 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 23 and 26, monumented with an iron post, 2 1/2 inches diameter, firmly set, in a mound of stone, 2 feet base to top of brass cap marked as described in the 1974 resurvey.

Corner falls 6 feet north of a fence extending east and west on level ground.

N. 0°21.7' W., on the N-S centerline of section 23.

20.129 Point for the center S 1/16 section corner of section 23.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a mound of stone, 2 feet base to top of aluminum cap marked

C
S 1/16 | S23
C
2010

Corner falls on level ground with piñon, juniper, and oak brush.

40.258 Point for the center 1/4 section corner, at intersection with the E-W centerline of section 23.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with aluminum cap marked

THE SUBDIVISION OF SECTION 23,
TOWNSHIP 39 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T39SR6W
C 1/4
S23
2010

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the corner.

Corner falls on level ground with dense piñon, juniper, and oak brush.

60.192 Point for the center N 1/16 section corner of section 23.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

C
N 1/16 | S23
C
2010

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the corner.

Corner falls on level ground with piñon and juniper growth.

80.126 The 1/4 section corner of sections 14 and 23.

From the 1/4 section corner of sections 23 and 24, monumented with an iron post, 2 1/2 inches diameter, firmly set, in a mound of stone, 3 feet base to top of brass cap marked as described in the official record of the 1974 resurvey.

Corner falls on level ground with piñon, juniper and oakbrush.

S. 89°08.5' W., on the E-W centerline of section 23.

39.287 The center 1/4 section corner of section 23.

79.361 The 1/4 section corner of sections 22 and 23.

From the S 1/16 section corner of sections 23 and 24, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 2 inches above the ground, with aluminum cap marked as described in the official record of the 2004 resurvey.

A mound of stone, 3 feet base, 2 feet high, is located west of the corner.

Corner falls on level ground with piñon and juniper growth.

S. 89°13.9' W., on the E-W centerline of the SE 1/4 of section

THE SUBDIVISION OF SECTION 23,
TOWNSHIP 39 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

23.

39.325 The center S 1/16 section corner of section 23.

From the center N 1/16 section corner of section 23.

S. $88^{\circ}58.9'$ W., on the E-W centerline of the NW 1/4 of section
23.

39.625 The N 1/16 section corner of sections 22 and 23.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS


Name	Capacity
Vincent Porter	Survey Aide

CERTIFICATE OF SURVEY

I, *Jeremy D. Davis*, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing the date of the *July 2, 2010*, I have *dependently resurveyed a portion of the east boundary (Panguitch and Kanab Guide Meridian), a portion of the subdivisional lines, the subdivision of section 13, and subdivided sections 14 and 23, in Township 39 South, Range 6 West, of the Salt Lake Meridian, in the State of Utah,* which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

February 13, 2012

Date



Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the east boundary (Panguitch and Kanab Guide Meridian), a portion of the subdivisional lines, the subdivision of section 13, and the subdivision of sections 14 and 23, in Township 39 South, Range 6 West, Salt Lake Meridian, Utah,* executed by *Jeremy D. Davis, Cadastral Surveyor,* having been critically examined and found correct, are hereby approved.

March 30, 2012

Date



Chief Cadastral Surveyor for Utah