

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE EAST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

A PORTION OF THE OPHIR CITY TOWNSITE,

AND MINERAL SURVEYS LOCATED IN SECTION 24,

IN

TOWNSHIP 5 SOUTH, RANGE 4 WEST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Ronald K. Batty
Cadastral Surveyor

Under Special Instructions dated **July 12, 2010**, approved **July 12, 2010**, which provided for the surveys included under Group Number **1151**, and Assignment Instructions dated **July 12, 2010**, and **Reassignment Instructions** dated **April 25, 2011**.

Survey Commenced, **July 13, 2010**
Survey Completed, **November 3, 2012**

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE EAST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

A PORTION OF THE OPHIR CITY TOWNSITE,

AND MINERAL SURVEYS LOCATED IN SECTION 24,

IN

TOWNSHIP 5 SOUTH, RANGE 4 WEST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Ronald K. Batty
Cadastral Surveyor

Under Special Instructions dated **July 12, 2010**, approved **July 12, 2010**, which provided for the surveys included under Group Number **1151**, and Assignment Instructions dated **July 12, 2010**, and **Reassignment Instructions** dated **April 25, 2011**.

Survey Commenced, **July 13, 2010**
Survey Completed, **November 3, 2012**

INDEX DIAGRAM

TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	7 24 4
30	29	28	27	26	5 25
31	32	33	34	35	36

Ophir City Townsite.....Page 7
 Trace Lode, Lot No. 139.....Page 13
 Trace No. 2 Lode, Lot No. 140.....Page 15
 Baltic Millsite, Lot No. 151B.....Page 17
 Mineral Survey 4580.....Page 19
 Ophir Queen No. 2 Lode, M.S. 5096.....Page 23
 Golden Eagle Mine Lode, M.S. 5841.....Page 24

TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of a portion of the east boundary, a portion of the subdivisional lines, a portion of the Ophir City Townsite, and mineral surveys located in Section 24, in T. 5 S., R. 4 W., Salt Lake Meridian, Utah.

HISTORY OF SURVEYS

		Surveyed by	Retr. or Resurveyed by	
SOUTH BOUNDARY				
Portion	C.L. Craig	1856		
Portion			E.W. Koeber	1886
All	R. Gentry	1926-31	R. Gentry	1926-31
EAST BOUNDARY				
All	R. Gentry	1926		
WEST BOUNDARY				
All	C.L. Craig	1856		
Portion			G.V.M. Boutelle	1872
All			E.W. Koeber	1886
All			R. Gentry	1926-31
NORTH BOUNDARY				
Portion	C.L. Craig	1856		
Portion	A.J. Stewart Jr.	1896		
All			R. Gentry	1926-31
SUBDIVISION				
Portion	C.L. Craig	1856		
Portion			G.V.M. Boutelle	1872
Portion	W. Brederneyer	1875	W. Brederneyer	1875
All	R. Gentry	1926-31	R. Gentry	1926-31
OPHIR CITY TOWNSITE				
Boundary	J.F. Smith	1871		
Townsite	C.A. Herman	1873		
Boundary			R. Gentry	1926-31
MINING SURVEYS-Mineral District No. 9				
1	A.D. Ferron	1872		
98	W. Bredemeyer	1879		
101	C.P. Brooks	1880		
103	F. Dickert	1880		
104	F. Dickert	1880		
115 A&B	R.H. Browne	1883		
126	L.E. Holden & J.H. Wolcott	1887		
127	B.B. Van Deusen	1887		
4580	R.E.L. Collier	1901		
5096	J.T. Breckon	1903		
5841	L.G. Burton	1907		

TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

PRIVATE

Mineral Survey 115B was resurveyed by Victor R. Campbell, LS 8460, dated Dec 22, 1992.

Section and quarter corner record ties, recorded by Donald Grosenberg, Tooele County Surveyor, dated Dec 2, 1994.

Road remonumentation was performed for the City of Ophir dated November 12, 1996.

Lots 1, 2, 3, 4, and 5, Block 9, Ophir City Townsite were resurveyed Donald J. Rosenberg, RLS 18-2201, dated July 7, 1999.

Lot 151B, MS 115B, was resurveyed by Francis D. Eickbush, LS 317443, dated November 27, 2000

Nile No. 3 Load, Nile No. 4 Load, Nyle, Fernex, Lone Pine, Golden Eagle Mine, MS 5623, portions of the subdivisional lines, and east boundary of T. 5 S., R. 4 W., were resurveyed by Francis D. Eickbush, LS 317443, dated November 27, 2000.

Retracement of a portion of the Ophir City Townsite Boundary and Topography, performed by Douglas Kinsman, LS 334575, dated January 31, 2003.

Retracement of a portion of the Ophir City Townsite Boundary, performed by Nolan C. Hathcock, LS 166346, dated July 19, 2003.

Retracement of portions of Ophir Queen Lode, MS 5096, performed by Nolan C. Hathcock, LS 166346, dated September 21, 2004.

A portion of the Ophir City Townsite Boundary was resurveyed by Matt Clark, LS 323716, Deputy Tooele County Surveyor, executed sometime after 2008.

TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 1151, dated July 12, 2010.

The direction of each line is with reference to the true meridian, determined by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards for the Positional Accuracy of Cadastral Surveys when using Global Navigation Satellite Systems (GNSS)*, dated February 23, 2009. Trimble model 5800 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from GPS static observations, post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS); DH7098 P086 KENNECOTT1UT2005, AJ6822 SLCU SALT LAKE CITY, CQ6018 MIDV MIDVALE.

The geographic position of the corner of sections 24 and 25, on the east boundary of the township, as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: **40°21'49.391" N.**,
Longitude: **112°13'51.441" W.**, N.A.D. 83 (CORS96), EPOCH: 2002.00,
Network Accuracy = 0.200 meter at 95% confidence.

The geographic position of the corner of sections 13, 14, 23, and 24, T. 5 S., R. 4 W., as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: **40°22'41.625" N.**,
Longitude: **112°14'59.643" W.**, N.A.D. 83 (CORS96), EPOCH: 2002.00,
Network Accuracy = 0.200 meter at 95% confidence.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH
CHAINS

Dependent Resurvey of a Portion of the East Boundary,
T. 5 S., R. 4 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by R. Gentry in 1926-31

Beginning at the corner of sections 24 and 25 only, monumented with an iron post, 2 inches diameter, in a mound of stone, with brass cap marked as described in the official record of the 1926-31 survey.

Rebuild the mound of stone around the corner.

N. 0°03.3' E., along the east boundary of section 24.

- 33.814 The 1/4 section corner of section 19 only, T. 5 S., R. 3 W., monumented with an iron post, 1 inch diameter, firmly set flush with the ground, with brass cap marked as described in the official record of the 1926-31 survey.

N. 0°27.3' E., beginning new measurement.

- 6.289 The 1/4 section corner of section 24 only, monumented with an iron post, 1 inch diameter, firmly set flush with the ground, with brass cap marked as described in the official record of the 1926-31 survey.

N. 0°05.0' W., beginning new measurement.

- 33.649 The corner of sections 18 and 19 only, T. 5 S., R. 3 W., monumented with an aluminum pipe, 2 inch diameter, projecting 14 inches above the ground, with a 3 inch diameter aluminum cap marked:

EIKBUSH & ASSOCIATES

T5S	
R4W	S18
S24	S19
	T5S
	R3W
2000	
LS317443	

This monument is accepted as a careful and faithful perpetuation of the original corner position.

N. 0°05.3' E., beginning new measurement.

- 6.239 The corner of sections 13 and 24 only, monumented with an iron post, 2 inches diameter, projecting 12 inches above a mound of stone, 3 ft. base, 18 inches high, with brass cap marked as

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

described in the official record of the 1926-31 survey.

The corner is located on a southwest facing slope surrounded by scrub oak.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 4 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by R. Gentry in 1926-31

From the corner of sections 24 and 25 only, on the east boundary of the township, hereinbefore described.

N. 89°59.5' W., between sections 24 and 25.

- 39.990 The 1/4 section corner of sections 24 and 25, monumented with an iron post, 1 inch diameter, projecting 5 inches above the ground, with brass cap marked as described in the official record of the 1926-31 survey.

A mound of stone 2 1/2 ft. base, 2 ft. high is to the north of the corner.

N. 89°59.0' W., beginning new measurement.

- 34.318 Intersect line 1-2 of Trace No. 2 Lode, Lot No. 140, not monumented.
- 37.440 Intersect line 3-4 of Trace No. 2 Lode, Lot No. 140, not monumented.
- 37.995 Intersect line 4-1 of Trace Lode, Lot No. 139, not monumented.
- 40.044 The corner of sections 23, 24, 25, and 26, monumented with an iron post, 2 inches diameter, projecting 9 inches above the ground, with brass cap marked as described in the official record of the 1926-31 survey.

NORTH, between sections 23 and 24.

- 4.375 Intersect line 2-3 of Trace Lode, Lot No. 139, not monumented.
- 6.918 Intersect line 5-1 of Fraction Lode, MS 4580, not monumented.
- 11.227 Intersect line 1-2 of Fraction Lode, MS 4580, identical with line 3-4 of Kickapoo Lode, MS 4580, not monumented.
- 40.084 The 1/4 section corner of sections 23 and 24, monumented with an iron post, 1 inch diameter, firmly set, projecting 6 inches above a mound of stone, 3 ft. base, 1 ft. high, with brass cap marked as described in the official record of the 1926-31

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

survey.

The corner is located northwest of a fire pit, on a north facing slope.

N. 0°01.1' E., beginning new measurement.

20.960 Intersect line 2-3, Ophir Queen No. 2 Lode, MS 5096, point falls on a sloping face of a limestone rock out crop.

Chisel an 'X' on point and add marks "WP" on face of the rock.

40.017 The corner of sections 13, 14, 23, and 24, monumented with an iron post, 2 inches diameter, firmly set, with the top of cap 30 inches below the ground surface, with brass cap marked as described in the official record of the 1926-31 survey.

A steel fence post is along the south side of the corner.

From which

An axed pinion stump, 18 inches diameter, bears S. 26°52.6' E., 34.6 links distant, with illegible scribing on an open blaze. (Record: S. 37° E., 36 links distance)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with base of aluminum post on top of the brass cap, with aluminum cap marked

T5S R4W	
S14	S13
S23	S24
2010	

The corner is on a steep south facing slope in thick mahogany and oak scrub. The center line of a dirt road, extending east and west, is 30 links north of the corner.

From the corner

US Mineral Monument #1, bears S. 37°27.9' E., 14.646 chains distance (1926-31 Record, S. 37°33' E., 14.64 chains distance), monumented with an iron post, 3 inches diameter, firmly set, projecting 18 inches above a mound of stone, 3 ft. base, 18 inches high, with brass cap marked as described in the official record of the 1926-31 survey.

Raise mound of stone to top.

A nail spike is set in a rock ledge 26.5 links west of the mineral monument.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH


CHAINS

From the corner of sections 13 and 24 only, on the east boundary of the township, hereinbefore described.

N. 89°59.5' W., between sections 13 and 24.

34.751 Intersect line 2-3, Golden Eagle Mine Lode, MS 5841.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 10 inches in the ground to bedrock, in a mound of stone, 4 ft. base, 20 inches high, with aluminum cap marked




The corner is located on a very steep northwest facing slope.

40.022 Point for the 1/4 section corner of sections 13 and 24, at proportionate distance, there is no remaining evidence of the original corner, not monumented.

44.420 Intersect line 1-4, Golden Eagle Mine Lode, MS 5841.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, in a mound of stone, 3 ft. base, 6 inches high, with aluminum cap marked



The corner is located 1 chains north of the centerline of a dirt road running along the bottom of Ophir Canyon, bears northeast and southwest.

80.044 The corner of sections 13, 14, 23, and 24.

Dependent Resurvey of a Portion of the Ophir City Townsite,
T. 5 S., R. 4 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by J.F. Smith in 1871,
and Resurvey Executed by R. Gentry in 1926-31

NOTE: Corner Nos. 19, 27, and 33, of Ophir City Townsite were established from original evidence. The positions of the other corners were established base on the Grant Boundary Adjustment.

DEPENDENT RESURVEY OF A PORTION OF THE OPHIR CITY TOWNSITE,
TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

From corner No. 19, monumented with a rebar, 5/8 inches diameter, projecting 5 inches above the ground, with yellow plastic cap, with illegible marks.

This monument is accepted as a careful and faithful perpetuation of the original corner position.

N. 48°05.9' E., on line 19-20 of the Ophir City Townsite Boundary.

3.636 Point for corner No. 20, not monumented.

S. 78°32.1' E., on line 20-21 of the Ophir City Townsite Boundary.

1.481 Point for corner No. 21.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, in a mound of stone, 3 ft. base, 6 inches high, with aluminum cap marked

T5S R4W
S23
21
OCTS
2010

Set a steel fence post alongside the corner.

The corner is behind a tan stucco house on lot 94 of the Ophir City Townsite.

N. 81°01.9' E., on line 21-22 of the Ophir City Townsite Boundary.

5.110 Point for corner No. 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, in a mound of stone, 2 1/2 ft. base, 4 inches high, with aluminum cap marked

T5S R4W
S23
22
OCTS
2010

Set a steel fence post alongside the corner.

The corner is located at the base of a tall ledge. The base is 5 links north of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE OPHIR CITY TOWNSITE,
TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH
CHAINS

N. 60°01.9' E., on line 22-23 of the Ophir City Townsite Boundary.

18.536 Point for corner No. 23.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, in a mound of stone, 3 ft. base, 4 inches high, with aluminum cap marked

T5SR4W
S24
/ 23
OCTS
2010

Set a steel fence post alongside the corner.

N. 83°06.9' E., on line 23-24 of the Ophir City Townsite Boundary.

7.059 Point for corner No. 24. The corner falls on a concrete pad for a picnic table under an aluminum canopy.

Set a brass tablet, 3 1/4 inches in diameter, with a 3 1/2 inch stem, in cement bond, into a drill hole on a concrete pad, marked

T5S
R4W |
S24 |
— 24
OCTS
2010

N. 0°01.9' E., on line 24-25 of the Ophir City Townsite Boundary.

4.661 Point for corner No. 25.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, in a mound of stone 3 ft. base, 4 inches high, with aluminum cap marked

T5S R4W
S24 /
| 25
| OCTS
2010

Set a steel fence post alongside the corner.

N. 56°54.9' E., on line 25-26 of the Ophir City Townsite Boundary.

DEPENDENT RESURVEY OF A PORTION OF THE OPHIR CITY TOWNSITE,
TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

10.901 Point for corner No. 26.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, in a collar of stone, 3 ft. base, with aluminum cap marked

T5S
R4W
S24 / 26
OCTS
2010

Set a steel fence post alongside the corner.

N. 15°03.9' E., on line 26-27 of the Ophir City Townsite Boundary.

- 4.552** Corner No. 27, monumented with a limestone, 17 X 16 X 8 inches, loosely set and plainly marked with a cross on top and "OCS27US" on the west face. The 1931 iron post, 2 inches diameter, is set 1.1 links north of the stone, with brass cap marked as described in the official record of the 1926-31 survey.

In 2003, Nolan C. Hathcock, a registered land surveyor, license No. 166346, rehabilitated this corner and used the cross on top of the stone for his position to control his survey. The cross on top of the stone is also used for this resurvey of Ophir Townsite.

From which accessories, established by Mr. Hathcock in 2003

A rebar, 5/8 inches diameter, bears N. 66°17.2' E., 31.6 links distance. (Record from the Tooele County tie sheet: N. 66°13'19" E., 20.89 FT.)

A rebar, 5/8 inches diameter, bears S. 46°28.2' E., 28.3 links distance. (Record from the Tooele County tie sheet: S. 46°30'18" E., 18.67 FT.)

A bearing object, "27 X" chiseled into rock face, bears N. 14°10.1' W., 10.5 links distance. (Record from the Tooele County tie sheet: N. 14°04'51" W., 6.90 FT.)


S. 54°33.2' E., on line 27-28 of the Ophir City Townsite Boundary.

- 4.762** Point for corner No. 28.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, in a mound of stone, 3 ft. base, 6 inches high, with aluminum cap marked

DEPENDENT RESURVEY OF A PORTION OF THE OPHIR CITY TOWNSITE,
TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS




Set a steel fence post alongside the corner.

S. 29°59.8' W., on line 28-29 of the Ophir City Townsite Boundary.

11.954 Point for corner No. 29.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, in a mound of stone, 2 1/2 ft. base, 4 inches high, with aluminum cap marked



Set a steel fence post alongside the corner.

The corner is in thick scrub oak.


S. 55°05.8' W., on line 29-30 of the Ophir City Townsite Boundary.

12.418 True point for corner No. 30. Point falls on a sloping limestone ledge where it is impracticable to set permanent monumentation.

S. 69°38.8' W., on line 30-31 of the Ophir City Townsite Boundary.

0.428 Point selected for the witness corner of corner No. 30.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at bases, 26 inches in the ground, in a collar of stone, with aluminum cap marked



~~Set a steel fence post alongside the witness corner.~~

DEPENDENT RESURVEY OF A PORTION OF THE OPHIR CITY TOWNSITE,
TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH
CHAINS

The witness corner is at the base of a tall limestone ledge.

9.586 Point for corner No. 31.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
with magnet at base, 24 inches in the ground, in a mound of
stone, 3 ft. base, 6 inches high, with aluminum cap marked

OCTS
31
T5S
R4W
S24
2010

Set a steel fence post alongside the corner.

The southwest corner of an old log cabin bears N. 63°02.3' E.,
41.3 links distant.

S. 19°36.8' W., on line 31-32 of the Ophir City Townsite
Boundary.

1.782 Point for corner No. 32.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
with magnet at base, 28 inches in the ground, in a collar of
stone, 2 1/2 ft. base, with aluminum cap marked

T5S
32 R4W
S24
2010

Set a steel fence post alongside the corner.

S. 66°07.8' W., on line 32-33 of the Ophir City Townsite
Boundary.

6.366 Intersect line 2-3 of the New York Lode, MS 4580.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
with magnet at base, 22 inches in the ground, in a mound of
stone, 3 ft. base, 8 inches high, with aluminum cap marked

OCTS
MS 4580
T5S
R4W
S24
2010

Set a steel fence post alongside the corner.

DEPENDENT RESURVEY OF A PORTION OF THE OPHIR CITY TOWNSITE,
TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH
CHAINS

The corner is surrounded by thick willow and scrub oak.

- 8.386 Point for corner No. 33, determined using the 1926-31 record ties made to corner No. 33 from the intersection of the line between sections 23 and 24, and intersection of line 33-34 of the Ophir Townsite. Corner falls on private land, not monumented.

From which

The 1/4 section corner of sections 23 and 24, bears N. 18°53.8' W., 1.622 chains distance, hereinbefore described.

Dependent Resurvey of Trace Lode, Lot No. 139,
T. 5 S., R. 4 W., Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by F. Dickert in 1880

Trace Lode Lot No. 139

From corner No. 1, of Trace Lode, Lot No. 139, determined using the 1880 record ties made from the Ore house located on the lode line.

Set an aluminum post, 30 inches long, 2 1/2 inches, with magnet at base, 24 inches in the ground, with aluminum cap marked

LOT
139 /
1 S25
T5SR4W
2012

A 12 ft. deep cut bears east, approx. 60 links east of the corner.

From which

The corner of sections 23, 24, 25, and 26, bears N. 23°08.4' W., 3.315 chains distant.

NOTE: No other monuments for Trace Lode, Lot No. 139, were recovered during the course of this resurvey. Subsequently corner Nos. 2, 3, and 4, were reestablished at record bearings and distances, beginning at corner No. 1.

N. 81°30.0' W., along line 1-2 of the Trace Lode, Lot No. 139.


- 3.042 Point for corner No. 2, of Trace Lode, Lot No. 139.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,

DEPENDENT RESURVEY OF TRACE LODE, LOT No. 139,
TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

with a steel can and broken pottery at the base, 24 inches in the ground, with aluminum cap marked




The corner is located on a very steep northwest facing slope.

N. 13°45.0' E., along line 2-3 of the Trace Lode, Lot No. 139.

- 7.179** Intersect the section line of sections 23 and 24, not monumented.
- 9.105** Intersect line 4-5 of the Fraction Lode, MS 4580, not monumented.
- 18.635** Intersect line 1-2 of the Fraction Lode, MS 4580, identical with line 3-4 of Kickapoo Lode, MS 4580, not monumented.
- 20.546** Point for corner No. 3, of Trace Lode, Lot No. 139.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 10 inches in the ground, in a mound of stone, 3 ft. base, 1 1/2 ft. high, with aluminum cap marked



The corner is located on a very steep northwest facing slope.

S. 81°30.0' E., along line 3-4 of the Trace Lode, Lot No. 139.

- 0.670** Intersect line 1-2 of the Fraction Lode, MS 4580, identical with line 3-4 of the Kickapoo Lode, MS 4580, not monumented.
- 3.042** Point for corner No. 4, of Trace Lode, Lot No. 139. Point falls on a steep cliff where permanent monumentation is impracticable.

From the corner

The point selected for the witness corner for corner No. 4, chisel an "X" and "WC" onto a slanted grey rock, bears S. 41°19.7' W., 15.7 links distant.

The corner is located on a very steep northwest facing slope.

DEPENDENT RESURVEY OF TRACE LODE, LOT No. 139,
TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

- S. 13°45.0' W., along line 4-1 of the Trace Lode, Lot No. 139.
- 3.064 Intersect line 4-5 of the Fraction Lode, MS 4580, not monumented.
- 17.408 Intersect the section line of sections 24 and 25, not monumented.
- 20.546 Corner No. 1, of Trace Lode, Lot No. 139.

Dependent Resurvey of Trace No. 2 Lode, Lot No. 140,
T. 5 S., R. 4 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by F. Dickert in 1880


Trace No. 2 Lode, Lot No. 140

From corner No. 1, of Trace No. 2 Lode, Lot No. 140, determined at record bearing and distance from an original bearing tree.

A juniper, 20 inches diameter, bears S. 39° E., 10.6 links distance, with scribing "140 P1 BT" visible on open blaze.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, in a collar of stone, 3 ft. base, with aluminum cap marked



NOTE: No other corner monuments for Trace No. 2 Lode, Lot No. 140, were recovered during the course of this resurvey. Subsequently corner Nos. 2, 3, and 4, were reestablished at record bearings and distances, beginning at corner No. 1.

- S. 13°45.0' W., along line 1-2 of Trace No. 2 Lode, Lot No. 140.
- 2.404 Intersect line 5-1 of the Dr. Woodruff Lode, MS 4580, not monumented.
- 9.612 Intersect the section line of sections 24 and 25, not monumented.
- 21.000 Point for corner No. 2, of Trace No. 2 Lode, Lot No. 140.
- ~~Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 21 inches in the ground, in a mound of~~

DEPENDENT RESURVEY OF TRACE NO. 2 LODGE, LOT NO. 140,
TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

stone, 2 ft. base, 6 inches high, with aluminum cap marked

LOT
140 / T5S
2 / R4W
S25
2012

The corner is located on a gentle northwest facing slope,
approximately 5 chains northwest of the top of the peak.

N. 81°30.0' W., along line 2-3 of Trace No. 2 Lode, Lot No. 140.

3.046 Point for corner No. 3, of Trace No. 2 Lode, Lot No. 140.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
with magnet at base, 20 inches in the ground, in a mound of
stone, 2 ft. base, 10 inches high, with aluminum cap marked

T5S LOT
R4W / 140
S25 / 3
2012

The corner is located in a small hollow with pines to the west
and a small clearing to the east.

N. 13°45.0' E., along line 3-4 of Trace No. 2 Lode, Lot No. 140.

10.926 Intersect the section line of sections 24 and 25, not
monumented.

21.000 Point for corner No. 4, of Trace No. 2 Lode, Lot 140.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
with magnet at base, 4 inches in the ground, in a mound of
stone, 3 ft. base, 2.5 ft. high, with aluminum cap marked

T5SR4W
S24
/ 4
/ LOT 140
2012

The corner is located on a very steep northwest facing slope.

S. 81°30.0' E., along line 4-1 of Trace No. 2 Lode, Lot No. 140.

2.361 Intersect line 1-5 of Dr. Woodruff Lode, MS 4580, not
monumented.

3.046 Corner No. 1, of Trace No. 2 Lode, Lot No. 140.

DEPENDENT RESURVEY OF BALTIC MILLSITE, LOT NO. 151B,
TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of Baltic Millsite, Lot No. 151B,
T. 5 S., R. 4 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by R.H. Browne in 1883

Baltic Millsite, Lot No. 151B

From corner No. 1, of the Baltic Millsite, Lot No. 151B, monumented with a rebar, 5/8 inch diameter, firmly set, projecting 2 inches above the ground, with a 2 inch aluminum cap marked

EIKBUSH & ASSOCIATES

C1
151B

LS 317443

A steel fence post is on the SE side of the corner. A barbed wire fence extends east-southeast and south-southwest from the corner. The corner is surrounded by thick oak brush.

This monument is accepted as a careful and faithful perpetuation of the original corner position.

NOTE: No other monuments for Baltic Millsite, Lot No. 151B, were recovered during the course of this resurvey. Subsequently corner Nos. 2, 3, and 4, were established at record bearing and distances, beginning at corner No. 1.

S. 73°20.0' E., along line 1-2 of Baltic Millsite, Lot No. 151B.

1.409 Intersect line 1-4, of Golden Eagle Mine Lode, MS 5841.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, in a mound of stone, 3 ft. base, 6 inches high, with aluminum cap marked

T5S
R4W
S24
LOT MS 5841
MS 151B
2010

The corner is located along the west side of a road, bearing northeast and southwest. A mesh fence extending northwest and southeast is 2 links south of the corner.

3.530 Point for corner No. 2, Baltic Millsite, Lot No. 151B. The corner falls on the lawn of private property. Not monumented.

DEPENDENT RESURVEY OF BALTIC MILLSITE, LOT NO. 151B,
TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

S. 16°40.0' W., along line 2-3 of Baltic Millsite, Lot No. 151B.

3.070 Intersect line 1-2, of Golden Eagle Mine Lode, MS 5841, not monumented.

8.333 Point for corner No. 3, Baltic Millsite, Lot No. 151B. The corner falls in the center of a gravel road at the bottom of the canyon.

Set a rail road spike.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, set 24 inches in the ground, in a collar of stone, for a reference monument, bears N. 46°43.2' W., 57.5 links distant, with aluminum cap marked "LOT 151B TO COR3 37.9 FT RM1 2010" with arrow pointing to corner. The reference corner is located between large rocks placed along the south edge of the creek.

An aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, set 24 inches in the ground, in a mound of stone, 3 ft. base, 6 inches high, for a reference monument, bears S. 73°08.0' E., 55.3 links distance, with aluminum cap marked "RM LOT 151B TO COR3 36.5 FT S24 2010" with arrow pointing to corner. The reference corner is located on a small hill to the south of the road.

N. 73°20.0' W., along line 3-4 of Baltic Millsite, Lot No. 151B.

3.530 Point for corner No. 4, Baltic Millsite, Lot No. 151B.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 22 inches in the ground to limestone ledge rock, in a mound of stone, 3 ft. base, 8 inches high, with aluminum cap marked

T5S
R4W / 151B
4
S24
2010

Set a steel fence post alongside the corner.

The corner is on a ledge between limestone rocks.

N. 16°40.0' E., along line 4-1 of Baltic Millsite, Lot No. 151B.

8.333 Corner No. 1, Baltic Millsite, Lot No. 151B.

DEPENDENT RESURVEY OF A PORTION OF MS 4580,
TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of MS 4580,
T. 5 S., R. 4 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by R.E.L. Collier in 1901

From corner No. 2, New York Lode, MS No. 4580, determined using the 1926-31 record tie made to corner No. 2 from the intersection of the line between sections 23 and 24, and the intersection of line 1-2 of the New York Lode. Corner falls on private land, not monumented.

From which

The 1/4 section corner of sections 23 and 24, bears S. 6°40.3' W., 1.760 chains distance, hereinbefore described.

S. 41°18.7' E., along line 2-3 of the New York Lode.

3.283 Intersect line 32-33 of the Ophir City Townsite Boundary.

8.271 Corner No. 3, New York Lode, MS 4580, identical with corner No. 2, Kickapoo Lode, MS 4580, determined at record bearing and distance from an original bearing tree:

A pinion, 12 inches diameter, bears S. 60°31' E., 62.1 links distance.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, in a mound of stone, 3 ft. base, 4 inches high, with aluminum cap marked

T5S
R4W
S24
NY 3/2
KI
MS4580
2010

S. 40°47.6' E., along line 2-3 of the Kickapoo Lode.

8.691 Corner No. 3, Kickapoo Lode, MS 4580, identical with corner No. 2, Fraction Lode, MS 4580, monumented with a decayed pine post, 3 1/2 inches square, 4 inches long, in the center of an embedded mound of stone, 2 ft. base, 6 inches high.

From which an original BT

A pine tree, 18 inches diameter, bears S. 50° E., 55.6 links

DEPENDENT RESURVEY OF A PORTION OF MS 4580,
TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH


CHAINS

distant, with illegible scribe marks.

Remaining bearing trees are dead and down.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 24 inches in the ground, in a mound of stone, 3 ft. base, 6 inches high, with aluminum cap marked




S. 7°40.3' E., along line 2-3 of the Fraction lode.

- 4.721 Corner No. 3, Fraction Lode, MS 4580, identical with corner No. 2, Dr. Woodruff Lode, MS 4580, determined at record bearing and distance from an original bearing tree.

A balsam tree, 12 inches diameter, bears S. 72°39' E., 69.7 links distance, with scribing "80" on open blaze.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to solid rock, and in a mound of stone, 4 ft. base to top of aluminum cap marked



S. 31°41.0' W., along line 3-4 of the Fraction lode, identical with line 2-1 of Dr. Woodruff Lode.

- 9.412 Corner No. 4, Fraction Lode, MS 4580, identical with corner No. 1, Dr. Woodruff Lode, MS 4580, determined at record bearing and distance from an original bearing tree.

A pine, 12 inches diameter, bears S. 61°15' E., 23.3 links distant, with scribing "80" on an open blaze.


At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28

DEPENDENT RESURVEY OF A PORTION OF MS 4580,
TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

inches in the ground, with aluminum cap marked



Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, 2 links east of the corner.


S. 2°29.4' E., along line 1-5 of the Dr. Woodruff Lode.

- 6.922 Intersect line 1-4, Trace No. 2 Lode, Lot No. 140, not monumented.
- 9.361 Intersect line 1-2, Trace No. 2 Lode, Lot No. 140, not monumented.
- 14.048 Corner No. 5, Dr. Woodruff Lode, MS 4580, determined at record bearing and distance from an original bearing tree.

A balsam stump, bears S. 10°25' E., 57.6 links distant, with scribing "4580 BT" legible on an open blaze.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 18 inches in the ground, in a mound of stone, 3 ft. base, 1 ft. high, with aluminum cap marked



The corner is located on the west edge of a gulch draining northwest.

N. 32°31.8' E., along line 5-4 of the Dr. Woodruff Lode.

- 0.076 Corner No. 4, Dr. Woodruff Lode, MS 4580, determined at record bearing and distance from an original bearing tree.

A balsam stump, (identical to the bearing tree for corner No. 5), bears S. 5°53' E., 63.5 links distant.


At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,

DEPENDENT RESURVEY OF A PORTION OF MS 4580,
TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

with magnet at base, 26 inches in the ground, in a mound of stone, 3 ft. base, 4 inches high, with aluminum cap marked



The corner is located on the west edge of a gulch draining northwest.

From corner No. 2, Fraction Lode, MS 4580, identical with corner No. 3 of Kickapoo Lode, hereinbefore described.


S. 32°29.4' W., along line 2-1, Fraction Lode, identical with line 3-4, Kickapoo Lode.

- 13.968 Intersect line 3-4, Trace Lode, Lot No. 139, not monumented.
- 16.050 Intersect line 2-3, Trace Lode, Lot No. 139, not monumented.
- 21.119 Intersect the section line of sections 23 and 24, not monumented.
- 22.023 Corner No. 1, Fraction Lode, MS 4580, identical with corner No. 4, Kickapoo Lode, MS 4580, determined at record bearing and distance from an original bearing tree.

A balsam, 24 inches diameter, bears S. 18°20' E., 26.4 links distant. I find a decayed pine post lying alongside, 3 inches square, 2 ft. long, with scribing "80" legible.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, in a mound of stone, 3 ft. base, 4 inches high, with aluminum cap marked



S. 7°47.9' E., along line 1-5, Fraction Lode.

- 3.580 Intersection the section line of sections 23 and 24, not monumented.
- 4.727 Corner No. 5, Fraction Lode, MS 4580, monumented with a mound of stone, 2 1/2 ft. base, 6 inches high, with a hewn cedar post, 3 inches square, 4 ft. long, with dim scribing lying alongside.


DEPENDENT RESURVEY OF A PORTION OF MS 4580,
TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Both bearing trees of record are down and dead.

At the corner point (center of mound)

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 26 inches in the ground, in a mound of stone, 3 ft. base, 4 inches high, with aluminum cap marked



NOTE: This corner now falls west of Lot No. 139.

N. 33°02.6' E., along line 5-4, Fraction Lode.

- 0.554 Intersect line 2-3, Trace Lode, Lot No. 139, not monumented.
- 9.723 Intersect line 1-4, Trace Lode, Lot No. 139, not monumented.
- 12.610 Corner No. 4, Fraction Lode, identical with Corner No. 1, Dr. Woodruff Lode, hereinbefore described.

Dependent Resurvey of a Portion of
Ophir Queen No. 2 Lode, MS 5096,
T. 5 S., R. 4 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by J.T. Breckon in 1903

Ophir Queen No. 2 Lode

From corner No. 2, Ophir Queen No. 2 Lode, MS 5096, identical with corner No. 3, Ophir Queen Lode, same survey, determined at record bearing and distance from an original bearing tree.


A cedar stump, 12 inches diameter, projecting 3 ft. above the ground, bears S. 75° W., 5.3 links distance, with scribing "5096" legible on an opened blaze.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground, in a mound of stone, 3 ft. base, 1.5 ft. high, with aluminum cap marked

DEPENDENT RESURVEY OF A PORTION OF
OPHIR QUEEN No. 2 LODE, MS 5096,
TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS



N. 80°57.1' E., along line 2-3, Ophir Queen No. 2 Lode.


- 11.510 Intersect the section line of sections 23 and 24, hereinbefore described.
- 23.059 Corner No. 3, Ophir Queen No. 2, Lode, MS 5096, monumented with the remnants of a decayed cedar post.

From which the original bearing tree

A pinion, 14 inches diameter, bears S. 3°25' E., 66.7' links distant, with hack marks on a mostly healed blaze.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, with magnet at base, 28 inches in the ground, in a mound of stone, 3 ft. base, 2 inches high, with aluminum cap marked




Dependent Resurvey of Golden Eagle Mine Lode, MS 5841,
T. 5 S., R. 4 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by L.G. Burton in 1907

Golden Eagle Mine Lode

From corner No. 1, Golden Eagle Mine Lode, MS 5841, monumented with a rebar, 5/8 inch diameter, in a scattered mound of stone, with brass cap marked

EIKBUSH & ASSOC LLC



The corner is surrounded by thick brush, located just above a cut slope around a trailer pad inside of the Varios Memorial

DEPENDENT RESURVEY OF GOLDEN EAGLE MINE LODE, MS 5841,
TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Park.

This monument is accepted as a careful and faithful perpetuation of the original corner position.

S. 72°49.9' E., along line 1-2, Golden Eagle Mine Lode.

2.305 Intersect line 2-3, Baltic Millsite, Lot No. 151B, not monumented.

9.099 Corner No. 2, Golden Eagle Mine Lode, MS 5841, monumented with a rebar, 5/8 inch diameter, firmly set, with a red plastic cap marked "LS317443".

This monument is accepted as a careful and faithful perpetuation of the original corner position.

N. 20°06.3' E., along line 2-3, Golden Eagle Mine Lode.


9.958 Intersect the section line of sections 13 and 24, hereinbefore described.

22.734 Corner No. 3, Golden Eagle Mine Lode, MS 5841, monumented with a rebar, 5/8 inch diameter, firmly set, with a red plastic cap marked "LS 317443".

This monument is accepted as a careful and faithful perpetuation of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, in a collar of stone, 2 1/2 ft. base, with aluminum cap marked



Deposit rebar inside the aluminum post.

The corner is located at the toe of a north facing slope.

N. 72°51.7' W., along line 3-4, Golden Eagle Mine Lode.

9.098 Corner No. 4, Golden Eagle Mine Lode, MS 5841, monumented with a rebar, 5/8 inch diameter, with aluminum cap marked "OAK HILLS SURVEYING RLS 317443", in a mound of stone, 3 feet base, 8 inches high.


This monument is accepted as a careful and faithful perpetuation of the original corner position.

DEPENDENT RESURVEY OF GOLDEN EAGLE MINE LODE, MS 5841,
TOWNSHIP 5 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, in a mound of stone, 3 ft. base, 10 inches high, with aluminum cap marked



Deposit rebar inside the aluminum post.

S. 20°06.4' W., along line 4-1, Golden Eagle Mine Lode.

- 15.612 Intersect the section line of sections 13 and 24, hereinbefore described.
- 19.672 Intersect line 1-2, Baltic Millsite, Lot No. 151B, not monumented.
- 22.728 Corner No. 1, Golden Eagle Mine Lode, MS 5841.
-

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Daniel T. Gillins	Cadastral Surveyor
Christopher May	Survey Technician
Matthew N. Gillins	Survey Technician
Richard B. West	Survey Technician
David A. Gillins	Survey Aid

CERTIFICATE OF SURVEY

I, **Ronald K. Batty, Cadastral Surveyor**, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing the date of the **July 12, 2010**, I have **dependently resurveyed a portion of the east boundary, a portion of the subdivisional lines, a portion of the Ophir City Townsite, and mineral surveys within section 24, in Township 5 South, Range 4 West, of the Salt Lake Meridian, in the State of Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

SEPT 25 2013

Date

Ronald K. Batty

Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the **dependent resurvey of a portion of the east boundary, a portion of the subdivisional lines, a portion of the Ophir City Townsite, and mineral surveys within section 24, in Township 5 South, Range 4 West, Salt Lake Meridian, Utah**, executed by **Ronald K. Batty, Cadastral Surveyor**, having been critically examined and found correct, are hereby approved.

November 21, 2013

Date

Daniel W. Webb

Chief Cadastral Surveyor for Utah