

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF THE WEST (COLORADO GUIDE MERIDIAN),

EAST, AND NORTH BOUNDARIES,

AND

THE SURVEY OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 12, 13, 14, 22, 23,

24, 26, 27, 28, 33, 34, AND 35,

IN

TOWNSHIP 42 SOUTH, RANGE 23 EAST,

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Scott A. Burkhardt*  
*Cadastral Surveyor*

Under Special Instructions dated and approved *September 1, 2010*, which provided for the surveys included under Group Number *1152*, and Assignment Instructions dated *September 1, 2010*.

Survey Commenced, *September 1, 2010*  
Survey Completed, *November 18, 2010*

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF THE WEST (COLORADO GUIDE MERIDIAN),

EAST, AND NORTH BOUNDARIES,

AND

THE SURVEY OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 12, 13, 14, 22, 23,

24, 26, 27, 28, 33, 34, AND 35,

IN

TOWNSHIP 42 SOUTH, RANGE 23 EAST,

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Scott A. Burkhardt*  
*Cadastral Surveyor*

Under Special Instructions dated and approved *September 1, 2010*, which provided for the surveys included under Group Number *1152*, and Assignment Instructions dated *September 1, 2010*.

Survey Commenced, *September 1, 2010*  
Survey Completed, *November 18, 2010*

## INDEX DIAGRAM

Township 42 South, Range 23 East.

12	11	11	10	10	9
5 6	49 5	39 4	32 3	25 2	19 1 9
48	48	38	32	25	18
5 7	47 8	38 9	31 10	24 11	17 12 8
46	46	37	31	24	17
4 18	45 17	37 16	30 15	23 14	16 13 8
45	44	36	29	22	16
4 19	43 20	35 21	29 22	22 23	15 24 7
43	42	35	28	21	14
4 30	41 29	34 28	27 27	20 26	14 25 7
41	40	34	27	20	13
3 31	39 32	33 33	26 34	19 35	12 36 6

The Subdivision of Section 12.....	49
The Subdivision of Section 13.....	50
The Subdivision of Section 14.....	51
The Subdivision of Section 22.....	51
The Subdivision of Section 23.....	52
The Subdivision of Section 24.....	53
The Subdivision of Section 26.....	53
The Subdivision of Section 27.....	54
The Subdivision of Section 28.....	55
The Subdivision of Section 33.....	56
The Subdivision of Section 34.....	56
The Subdivision of Section 35.....	57

## TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN

The following field notes are those of the dependent resurvey of the west (Colorado Guide Meridian), east, and north boundaries, and the survey of the subdivisional lines, and the subdivision of sections 12, 13, 14, 22, 23, 24, 26, 27, 28, 33, 34, and 35, in T. 42 S., R. 23 E., Salt Lake Meridian, Utah.

## HISTORY OF SURVEYS

Surveyed by		Retr. or Resurveyed by	
<b>SOUTH BOUNDARY</b>			
All	A. Nelson & R.C. Yundt	1953	
All		D.W. Webb & T. Trujillo	2005
<b>EAST BOUNDARY</b>			
All	A. Nelson & R.C. Yundt	1953	
<b>WEST BOUNDARY (Colorado Guide Meridian)</b>			
All	F. Dickert	1878	
All		A. Nelson & R.C. Yundt	1953
<b>NORTH BOUNDARY</b>			
All	A. Nelson & R.C. Yundt	1953	
<b>SUBDIVISION</b>			
All	Unsurveyed		

## TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 1153, dated September 1, 2010.

The direction of the lines was determined by references to true meridian, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards For the Positional Accuracy of Cadastral Surveys When Using Global Navigation Satellite Systems (GNSS)*, February 23, 2009. Trimble model R8 GNSS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from GPS static observations, post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS): DI2245 P011 SPIDERROCKAZ2005 CORS ARP, DL3642 MC09 NUCLA CORS ARP, AI0265 AZCN AZTEC CORS ARP.

The geographic position for the corner of Tps. 41 and 42 S., Rs. 23 and 24 E., as determined by direct RTK methods from the National Geodetic Survey OPUS solutions, is as follows:

Latitude: 37°10'23.813" N.,  
Longitude: 109°19'56.271" W., N.A.D. 1983 (CORS96),  
Network Accuracy = 0.200 meter at 95% confidence.

The geographic position for the corner of Tps. 41 and 42 S., Rs. 22 and 23 E., as determined by direct RTK methods from the National Geodetic Survey OPUS solutions, is as follows:

Latitude: 37°10'23.466" N.,  
Longitude: 109°26'27.022" W., N.A.D. 1983 (CORS96),  
Network Accuracy = 0.200 meter at 95% confidence.

All stainless steel posts and brass tablets set in this survey bear the Navajo Nation Seal, unless otherwise noted.

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
(COLORADO GUIDE MERIDIAN),  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of the West Boundary  
(Colorado Guide Meridian),  
T. 42 S., R. 23 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by F. Dickert in 1878, and  
the Resurvey Executed by A. Nelson and R.C. Yundt in 1953

Beginning at the corner of Tps. 42 and 43 S., Rs. 22 and 23 E., monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 5 inches above ground, in a collar of stone, 1 1/2 ft. diameter, with brass cap marked as described in the official record of the 2005 resurvey.

A steel fence post is located north of the corner.

Corner is located near the east edge of a seasonal lake bed.

N. 0°00.4' W., between sections 31 and 36.

- 40.028 The 1/4 section corner of sections 31 and 36, monumented with broken glass, from surface to 12 inches below the ground (1953 record: broken glass at the base of the iron post). There is no remaining evidence of the 1953 iron post.

At the corner point (center of broken glass)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S  
R22E R23E  
1/4  
S36 | S31  
2010

Set a steel fence post north of the corner.

Corner is located in clay on a seasonal lake bed.

N. 0°00.8' E., beginning new measurement.

- 40.007 The corner of sections 25, 30, 31, and 36, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 10 inches above a mound of stone, 4 ft. base, 1 ft. high, with brass cap marked as described in the official record of the 1953 resurvey.

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
(COLORADO GUIDE MERIDIAN),  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post north of the corner.

Corner is located on rolling, sandy hills with desert vegetation.

---

N. 0°00.1' E., between sections 25 and 30.

- 39.994 The 1/4 section corner of sections 25 and 30, monumented with an iron post, 2 1/2 inches diameter, firmly set, 6 inches below the ground, in a collar of stone, with brass cap marked as described in the official record of the 1953 resurvey.

Set a steel fence post north of the corner.

Corner is located on rolling, sandy hills.

---

N. 0°00.8' E., beginning new measurement.

- 40.005 The corner of sections 19, 24, 25, and 30, monumented with an iron post, 2 1/2 inches diameter, firmly set, flush in a mound of stone, 5 ft. base, 1 1/2 ft. high, with brass cap marked as described in the official record of the 1953 resurvey.
- 

N. 0°00.7' E., between sections 19 and 24.

- 40.005 The 1/4 section corner of sections 19 and 24, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 11 inches above the ground, in an embedded collar of stone, 3 ft. diameter, with brass cap marked as described in the official record of the 1953 resurvey.

Set a steel fence post north of the corner.

---

N. 0°00.7' W., beginning new measurement.

- 40.023 The corner of sections 13, 18, 19, and 24, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 9 inches above an embedded mound of stone, 2 ft. base, 2 ft. high, with brass cap marked as described in the official record of the 1953 resurvey.

Set a steel fence post north of the corner.

Corner is located on rolling, sandy hills with desert vegetation.

---

N. 0°00.1' E., between sections 13 and 18.

- 40.020 The 1/4 section corner of sections 13 and 18, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 10 inches above an embedded collar of stone, 2 ft. diameter, with brass cap marked as described in the official record of the 1953

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
(COLORADO GUIDE MERIDIAN),  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH  
CHAINS

resurvey.

Set a steel fence post north of the corner.

Corner is located on rolling, sandy hills.

---

N. 0°00.1' W., beginning new measurement.

- 40.011 The corner of sections 7, 12, 13, and 18, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 1 inch above the ground, in a collar of stone, 2 ft. diameter, with brass cap marked as described in the official record of the 1953 resurvey.

A steel fence post is located north of the corner.

---

N. 0°00.3' W., between sections 7 and 12.

- 18.232 Point for the 1953 reference monument, at proportionate distance. There is no remaining evidence of the original corner. Not monumented.

- 18.477 Intersect the centerline of San Juan County Road No. 439, a gravel road, 20 ft. wide, bears N. 77° W. and S. 77° E.

- 40.005 The 1/4 section corner of sections 7 and 12, monumented with an iron post, 2 1/2 inches diameter, firmly set, flush in a mound of stone, 4 ft. base, 2 ft. high, with brass cap marked as described in the official record of the 1953 resurvey.

Set a steel fence post north of the corner.

Corner is located on rolling hills with sandstone ledges.

---

N. 0°00.6' W., beginning new measurement.

- 40.006 The corner of sections 1, 6, 7, and 12, monumented with an iron post, 2 1/2 inches diameter, firmly set, 12 inches below the ground, with brass cap marked as described in the official record of the 1953 resurvey.

Set a steel fence post west of the corner.

Corner is located in drainage, 30 ft. wide, course N. 15° E.

---

N. 0°00.1' E., between sections 1 and 6.

- 39.999 The 1/4 section corner of sections 1 and 6, monumented with an iron post, 2 1/2 inches diameter, 30 inches long, loosely set, projecting 20 inches above a mound of stone, with brass cap marked as described in the official record of the 1953 resurvey. Reset iron post, 20 inches in the ground, magnet at base, in a

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
(COLORADO GUIDE MERIDIAN),  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

mound of stone, 3 ft. base, 1 ft. high, to top of brass cap.

Set a steel fence post north of the corner.

Corner is located on a sandy ridge, south of drainage, course N. 40° E.

---

N. 0°00.1' W., beginning new measurement.

- 40.022 The corner of Tps. 41 and 42 S., Rs. 22 and 23 E., monumented with an iron post, 2 1/2 inches diameter, firmly set, flush in the ground, with brass cap marked as described in the official record of the 1953 resurvey.

Raise a mound of stone, 2 ft. base, 1 ft. high, west of the corner.

---

Dependent Resurvey of the East Boundary,  
T. 42 S., R. 23 E., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
A. Nelson & R.C. Yundt in 1953

From the corner of Tps. 42 and 43 S., Rs. 23 and 24 E., monumented with an iron post, 2 1/2 inches diameter, firmly set, flush with a mound of stone, 4 ft. diameter, 2 ft. high, with brass cap marked as described in the official record of the 2005 resurvey.

Corner is located at the base of steep cliffs in a deep and narrow drainage.

N. 0°01.1' E., between sections 31 and 36.

- 40.068 The 1/4 section corner of sections 31 and 36, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 2 inches above the ground, with brass cap marked as described in the official record of the 1953 survey.

Set a steel fence post north of the corner.

Corner is located on a mesa top in rolling, sandy hills.

---

N. 0°00.1' E., beginning new measurement.

- 40.008 Point for the corner of sections 25, 30, 31, and 36, at proportionate distance. There is no remaining evidence of the 1953 iron post. Broken glass broadly scattered on the ground.

Set a stainless steel post, 30 inches long, 2 1/2 inches

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

diameter, 28 inches in the ground, magnet at base, with brass cap marked:

T42S	
R23E	R24E
S25	S30
S36	S31
2010	

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy hills.

---

N. 0°00.1' E., between sections 25 and 30.

- 40.008 Point for the 1/4 section corner of sections 25 and 30, at proportionate distance. There is no remaining original evidence of the 1953 iron post.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground, to bedrock, magnet at base, in a mound of stone, 2 ft. base to top of brass cap marked:

T42S	
R23E	R24E
1/4	
S25	S30
2010	

Set a steel fence post north of the corner.

Corner is located on a level mesa top.

- 80.016 The corner of sections 19, 24, 25, and 30, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 5 inches above the ground, with brass cap marked as described in the official record of the 1953 survey.

Corner is located on a steep, west-facing hillside.

---

N. 0°01.6' E., between sections 19 and 24.

- 39.936 The 1/4 section corner of sections 19 and 24, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 7 inches above the ground, with brass cap marked as described in the official record of the 1953 survey.

Raise a mound of stone, 3 ft. base, 2 ft. high, northwest of the corner.

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located northwest of White Mesa, in an open valley.

---

N. 0°00.6' E., beginning new measurement.

- 40.013 Point for the corner of sections 13, 18, 19, and 24, at proportionate distance. Found the 1953 iron post, 2 1/2 inches diameter, 30 inches long, lying loose on the ground.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S	
R23E	R24E
S13	S18
S24	S19
2010	

Set a steel fence post north of the corner.

Bury original iron post alongside the corner.

Corner is located on a small sandy hill.

---

N. 0°00.6' E., between sections 13 and 18.

- 40.013 The 1/4 section corner of sections 13 and 18, monumented with an iron post, 2 1/2 inches diameter, firmly set, flush with the ground, with brass cap marked as described in the official record of the 1953 survey.

Set a steel fence post north of the corner.

---

N. 0°00.1' E., beginning new measurement.

- 40.036 The corner of sections 7, 12, 13, and 18, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 1 inch above the ground, with brass cap marked as described in the official record of the 1953 survey.

Corner is located on top of a spur, bears S. 50° W.

---

N. 0°00.6' E., between sections 7 and 12.

- 40.020 The 1/4 section corner of sections 7 and 12, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 1 inch above the ground, with brass cap marked as described in the official record of the 1953 survey.

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post north of the corner.

---

N. 0°00.3' E., beginning new measurement.

15.584 Intersect the centerline of San Juan County Road No. 406, a paved road, 25 ft. wide, bears N. 15° E. and S. 15° W.

40.000 The corner of sections 1, 6, 7, and 12, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 3 inches above a mound of stone, 3 ft. diameter, 1 ft. high, with brass cap marked as described in the official record of the 1953 survey.

---

N. 0°00.1' E., between sections 1 and 6.

39.968 The 1/4 section corner of sections 1 and 6, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 5 inches above the ground, with brass cap marked as described in the official record of the 1953 survey.

---

N. 0°00.2' E., beginning new measurement.

40.004 The corner of Tps. 41 and 42 S., Rs. 23 and 24 E., monumented with an iron post, 2 1/2 inches diameter, firmly set, flush with the ground, with brass cap marked as described in the official record of the 1953 survey.

Set a steel fence post north of the corner.

---

Dependent Resurvey of the North Boundary,  
T. 42 S., R. 23 E., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
A. Nelson & R.C. Yundt in 1953

---

From the corner of Tps. 41 and 42 S., Rs. 23 and 24 E., hereinbefore described.

S. 89°55.9' W., between sections 1 and 36.

40.016 The 1/4 section corner of sections 1 and 36, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 2 inches above the ground, with brass cap marked as described in the official record of the 1953 survey.

---

S. 89°55.0' W., beginning new measurement.

40.014 The corner of sections 1, 2, 35, and 36, monumented with an iron post, 2 1/2 inches diameter, firmly set, flush with a mound of

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,  
TOWNSHIP 43 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

stone, 4 ft. base, 1 ft. high, with brass cap marked as described in the official record of the 1953 survey.

---

S. 89°57.5' W., between sections 2 and 35.

- 20.028 Intersect the centerline of San Juan County Road No. 490, a gravel road, 25 ft. wide, bears N. 64° E. and S. 64° W.
- 40.005 The 1/4 section corner of sections 2 and 35, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 12 inches above a mound of stone, 4 ft. base, 2 ft. high, with brass cap marked as described in the official record of the 1953 survey.

Corner is located in drainage, course southerly.

---

S. 89°55.5' W., beginning new measurement.

- 40.004 The corner of sections 2, 3, 34, and 35, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 14 inches above a mound of stone, 4 ft. base, 1 1/2 ft. high, with brass cap marked as described in the official record of the 1953 survey.

Corner is located on exposed sandstone bedrock.

---

S. 89°56.8' W., between sections 3 and 34.

- 39.987 The 1/4 section corner of sections 3 and 34, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 12 inches above a mound of stone, 5 ft. base, 3 ft. high, with brass cap marked as described in the official record of the 1953 survey.

Corner is located on exposed sandstone bedrock west of Desert Creek.

---

S. 89°55.6' W., beginning new measurement.

- 40.012 Point for the corner of sections 3, 4, 33, and 34, at proportionate distance. Found the 1953 iron post, 2 1/2 inches diameter, 30 inches long, lying loose on the ground.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,  
TOWNSHIP 43 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T41S R23E	
S33	S34
S4	S3
T42S	
2010	

Set a steel fence post north of the corner.

Bury original iron post alongside the corner.

Corner is located on the east bank of drainage, course N. 20° W.

---

S. 89°55.6' W., between sections 4 and 33.

- 40.012 The 1/4 section corner of sections 4 and 33, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 12 inches above the ground, with brass cap marked as described in the official record of the 1953 survey.

Set a steel fence post north of the corner.

---

S. 89°56.5' W., beginning new measurement.

- 40.030 The corner of sections 4, 5, 32, and 33, monumented with an iron post, 2 1/2 inches diameter, firmly set, flush in a mound of stone, 4 ft. base, 1 ft. high, with brass cap marked as described in the official record of the 1953 survey.

Corner is located on top of Standing Rock, 600 ft. above the valley floor.

---

S. 89°56.2' W., between sections 5 and 32.

- 39.998 True point for the 1/4 section corner of sections 5 and 32.

Corner is located in a drainage, susceptible to erosion.

- 40.698 The witness corner for the 1/4 section corner of sections 5 and 32, monumented with an iron post, 2 1/2 inches diameter, firmly set, flush in a mound of stone, 4 ft. base, 2 ft. high, with brass cap marked as described in the official record of the 1953 survey.

Set a steel fence post north of the corner.

Corner is located west of drainage, course northerly.

---

S. 89°56.6' W., beginning new measurement.

- 39.325 Point for the corner of sections 5, 6, 31, and 32, at proportionate distance. There is no remaining evidence of the

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,  
TOWNSHIP 43 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

1953 iron post, or broken glass memorial.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T41S R23E	
S31	S32
S6	S5
T42S	
2010	

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy hills.

---

S. 89°56.6' W., between sections 6 and 31.

- 40.026 The 1/4 section corner of sections 6 and 31, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 13 inches above the ground, with brass cap marked as described in the official record of the 1953 survey.

Set a steel fence post north of the corner.

---

S. 89°56.3' W., beginning new measurement.

- 39.165 The corner of Tps. 41 and 42 S., Rs. 22 and 23 E., hereinbefore described.
- 

The Survey of the Subdivisional Lines,  
T. 42 S., R. 23 E., Salt Lake Meridian, Utah

---

From the corner of sections 1, 2, 35, and 36, on the south boundary of the township, monumented with a brass tablet, 3 1/4 inches diameter, cemented in sandstone bedrock, with brass cap marked as described in the official record of the 2005 resurvey of the north boundary of T. 43 S., R. 23 E.

A mound of stone, 3 ft. base, 2 ft. high, is located west of the corner.

Corner is located on top of a bedrock ledge, 30 ft. high.

N. 0°00.2' W., between sections 35 and 36.

- 40.000 Point for the 1/4 section corner of sections 35 and 36.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T42S R23E

1/4

S35 | S36

2010

Set a steel fence post east of the corner.

Corner is located on the east edge of an open valley at the base of White Mesa.

80.000 Point for the corner of sections 25, 26, 35, and 36.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, in a mound of stone, 4 ft. base on a slope, with brass cap marked:

T42S R23E

S26 | S25

S35 | S36

2010

Set a steel fence post north of the corner.

Corner is located on a steep, west-facing slope of White Mesa, 150 ft. above the valley floor.

From the corner of sections 25, 30, 31, and 36, on the east boundary of the township, hereinbefore described.

S. 89°52.3' W., between sections 25 and 36.

40.022 Point for the 1/4 section corner of sections 25 and 36.

Set a brass tablet, 3 1/4 inch diameter, with 3 1/2 inch stem, in cement bond, into a hole drilled in solid rock, six inches below the ground marked:

T42S R23E

S25

1/4 ———

S36

2010

From which:

A BLM Cadastral Survey brass washer, 1 1/2 inches diameter, attached to a juniper tree with a magnetic nail, bears S. 13°05' W., 29.0 links distance.

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a steel fence post southeast of the corner.

Corner is located on a gentle rolling mesa top with scattered juniper trees.

80.044 The corner of sections 25, 26, 35, and 36.

N. 0°00.2' W., between sections 25 and 26.

40.000 Point for the 1/4 section corner of sections 25 and 26.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

1/4

S26	S25
-----	-----

2010

Set a steel fence post east of the corner.

Corner is located on a steep, west-facing slope of White Mesa.

80.000 Point for the corner of sections 23, 24, 25, and 26.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 6 inches in the ground, to bedrock, magnet at base, in a mound of stone, 4 ft. base to of brass cap marked:

T42S R23E

S23	S24
S26	S25

2010

Set a steel fence post north of the corner.

Corner is located in broken ledges of sandstone bedrock on a gentle, west-facing slope.

From the corner of sections 19, 24, 25, and 30, on the east boundary of the township, hereinbefore described.

S. 89°51.5' W., between sections 24 and 25.

40.018 Point for the 1/4 section corner of sections 24 and 25.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, in a collar of stone, 3 ft. base, with brass cap marked:

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T42S R23E  
S24  
1/4           
S25  
2010

Set a steel fence post east of the corner.

Corner is located on a gentle, northwest-facing slope in a boulder field.

80.036 The corner of sections 23, 24, 25, and 26.

---

N. 0°00.2' W., between sections 23 and 24.

40.000 Point for the 1/4 section corner of sections 23 and 24.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E  
1/4  
S23 | S24  
2010

Set a steel fence post north of the corner.

Corner is located on rolling, sandy hills with desert vegetation.

67.723 Intersect the centerline of San Juan County Road No. 406, a paved road, 25 ft. wide, bears N. 35° E. and S. 35° W.

76.157 Intersect the centerline of San Juan County Road No. 490, a gravel road, 25 ft. wide, bears N. 89° W. and S. 89° E.

80.000 Point for the corner of sections 13, 14, 23, and 24.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E  
S14 | S13  
          
S23 | S24  
2010

Set a steel fence post north of the corner.

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

Corner is located on rolling, sandy hills.

---

From the corner of sections 13, 18, 19, and 24, on the east boundary of the township, hereinbefore described.

S. 89°53.8' W., between sections 13 and 24.

40.025 Point for the 1/4 section corner of sections 13 and 24.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

T42S R23E  
S13  
1/4 ———  
S24  
2010

Set a steel fence post north of the corner.

Corner is located on rolling, sandy hills.

71.528 Intersect the centerline of San Juan County Road No. 406, a paved road, 25 ft. wide, bears N. 35° E. and S. 35° W.

80.050 The corner of sections 13, 14, 23, and 24.

---

N. 0°00.2' W., between sections 13 and 14.

40.000 Point for the 1/4 section corner of sections 13 and 14.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

T42S R23E  
1/4  
S14 | S13  
2010

Set a steel fence post north of the corner.

Corner is located on rolling, sandy hills.

80.000 Point for the corner of sections 11, 12, 13, and 14.

Set a brass tablet, 3 1/4 inch diameter, with 3 1/2 inch stem, in cement bond, into a hole drilled in solid rock, magnet at base, marked:

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T42S R23E

S11	S12
S14	S13

2010

Set a steel fence post west of the corner.

Corner is located on gentle south-sloping sandstone bedrock.

---

From the corner of sections 7, 12, 13, and 18, on the east boundary of the township, hereinbefore described.

S. 89°51.7' W., between sections 12 and 13.

16.052 Intersect the centerline of San Juan County Road No. 406, a paved road, 25 ft. wide, bears N. 31° E. and S. 34° W.

40.024 Point for the 1/4 section corner of sections 12 and 13.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

1/4	S12
	S13

2010

Set a steel fence post north of the corner.

Corner is located on gentle southwest-sloping, sandy terrain.

80.048 The corner of sections 11, 12, 13, and 14.

---

N. 0°00.2' W., between sections 11 and 12.

40.000 Point for the 1/4 section corner of sections 11 and 12.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T42S R23E

1/4

S11	S12
-----	-----

2010

Set a steel fence post north of the corner.

Corner is located on rolling, sandy hills.

80.000 Point for the corner of sections 1, 2, 11, and 12.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, magnet at base, in a mound of stone, 2 ft. base to top of brass cap marked:

T42S R23E

S2	S1
S11	S12

2010

Set a steel fence post north of the corner.

Corner is located on a moderately-steep northwest-facing slope, 15 ft. below a ridge top.

From the corner of sections 1, 6, 7, and 12, on the east boundary of the township, hereinbefore described.

S. 89°50.8' W., between sections 1 and 12.

40.024 Point for the 1/4 section corner of sections 1 and 12.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 6 inches in the ground, to bedrock, magnet at base, in a mound of stone, 3 ft. base to top of brass cap marked:

T42S R23E

S1

1/4	S12
-----	-----

2010

Set a steel fence post west of the corner

Corner is located on rough, rocky ground.

80.048 The corner of sections 1, 2, 11, and 12.

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH  
CHAINS

N. 0°00.3' E., between sections 1 and 2.

40.000 Point for the 1/4 section corner of sections 1 and 2.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground, magnet at base, in a mound of stone, 3 ft. base to top of brass cap marked:

T42S R23E

1/4  
S2 | S1

2010

Corner is located at the base of a steep mesa to the east on rocky ground.

80.080 The corner of sections 1, 2, 35, and 36, on the north boundary of the township, hereinbefore described.

From the corner of sections 2, 3, 34, and 35, on the south boundary of the township, monumented with an iron post, 1 1/2 inches diameter, firmly set, projecting 6 inches above a mound of stone, 3 ft. base, 1 ft. high, marked as described in the official record of the 2005 resurvey of the north boundary of T. 43 S., R. 23 E.

Set a steel fence post north of the corner.

N. 0°00.9' W., between sections 34 and 35.

40.000 Point for the 1/4 section corner of sections 34 and 35.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with magnet at base, with brass cap marked:

T42S R23E

1/4  
S34 | S35

2010

Set a steel fence post west of the corner.

Corner is located on level desert terrain.

80.000 Point for the corner of sections 26, 27, 34, and 35.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T42S R23E

S27	S26
S34	S35

2010

Set a steel fence post north of the corner.

Corner is located on rolling, sandy hills with desert vegetation.

---

From the corner of sections 25, 26, 35, and 36.

S. 89°56.2' W., between sections 26 and 35.

40.015 Point for the 1/4 section corner of sections 26 and 35.

Set a brass tablet, 3 1/4 inch diameter, with 3 1/2 inch stem, in cement bond, in a hole drilled in solid sandstone bedrock, magnet at base, marked:

T42S R23E

	S26
1/4	———
	S35

2010

Raise a mound of stone, 2 ft. base, 2 ft. high, east of the corner.

Corner is located on rolling, sandy hills.

80.030 The corner of sections 26, 27, 34, and 35.

---

N. 0°00.9' W., between sections 26 and 27.

40.000 Point for the 1/4 section corner of sections 26 and 27.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

	1/4
S27	S26

2010

Set a steel fence post east of the corner.

From the corner, a galvanized iron pipe, 1 1/4 inches diameter,

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

firmly set, flush with the ground, bears S. 77°02' W., 4.4 links distance, with side of pipe marked 1/4 S27/S26.

This monument is not recorded and was not utilized in this survey.

Corner is located on gentle rolling, sandy hills with desert vegetation.

52.449 Intersect the centerline of San Juan County Road No. 406, a paved road, 25 ft. wide, bears N. 42° E. and S. 42° W.

62.273 Intersect the centerline of San Juan County Road No. 456, a gravel road, 12 ft. wide, bears N. 73° E. and S. 73° W.

80.000 Point for the corner of sections 22, 23, 26, and 27.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet and broken glass at base, with brass cap marked:

T42S R23E

S22	S23
S27	S26

2010

Set a steel fence post north of the corner.

Corner is located on rolling, sandy hills, south of an improved gravel road.

From the corner of sections 23, 24, 25, and 26.

S. 89°56.2' W., between sections 23 and 26.

40.015 Point for the 1/4 section corner of sections 23 and 26.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet and broken glass at base, with brass cap marked:

T42S R23E

1/4	S23
	S26

2010

Set a steel fence post north of the corner.

Corner is located on a gentle west-sloping hill, east of a buried gas pipeline.

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

- 55.575 Intersect the centerline of San Juan County Road No. 406, a paved road, 25 ft. wide, bears N. 42° E. and S. 42° W.
- 64.127 Intersect the centerline of San Juan County Road No. 454 (Navajo No. 5062), a gravel road, 25 ft. wide, bears N. 83° W. and S. 81° E.
- 80.030 The corner of sections 22, 23, 26, and 27.

N. 0°00.9' W., between sections 22 and 23.

- 0.344 Intersect the centerline of San Juan County Road No. 454 (Navajo No. 5062), a gravel road, 25 ft. wide, bears east and west.
- 40.000 Point for the 1/4 section corner of sections 22 and 23.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

1/4

S22	S23
-----	-----

2010

Set a steel fence post east of the corner.

Corner is located on rolling, sandy hills.

- 80.000 Point for the corner of sections 14, 15, 22, and 23.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

S15	S14
S22	S23

2010

Set a steel fence post north of the corner.

Corner is located on rolling, sandy hills with desert vegetation.

From the corner of sections 13, 14, 23, and 24.

S. 89°56.2' W., between sections 14 and 23.

- 12.419 Intersect the centerline of San Juan County Road No. 490, a gravel road, 25 ft. wide, bears N. 8° E. and S. 5° W.

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

40.015 Point for the 1/4 section corner of sections 14 and 23.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, flush with the ground, magnet at base, with brass cap marked:

T42S R23E  
S14  
1/4 —————  
S23  
2010

Set a steel fence post approximately 7 ft. south of the corner.

Corner is located at the center of a 2-track trail.

80.030 The corner of sections 14, 15, 22, and 23.

N. 0°00.9' W., between sections 14 and 15.

40.000 Point for the 1/4 section corner of sections 14 and 15.

Set a brass tablet, 3 1/4 inch diameter, with 3 1/2 inch stem, in cement bond, into a hole drilled in solid sandstone bedrock, marked:

T42S R23E  
1/4  
S15 | S14  
2010

Set a steel fence post north of the corner.

Corner is located on fairly level terrain, 10 inches beneath a wind-blown layer of sand.

80.000 Point for the corner of sections 10, 11, 14, and 15.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, in a collar of stone, 3 ft. diameter, with brass cap marked:

T41S R23E  
S10 | S11  
S15 | S14  
2010

Set a steel fence post east of the corner.

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

From the corner, a rebar, 1/2 inch diameter, firmly set, bears N. 21°11' W., 6.9 links distance, with brass cap, 1 1/4 inches diameter, marked T42SR23E S14/S15/S22/S23 1955 LS1448.

This monument is not recorded and was not utilized in this survey.

Corner is located on rolling, sandy hills.

---

From the corner of sections 11, 12, 13, and 14.

S. 89°56.2' W., between sections 11 and 14.

40.016 Point for the 1/4 section corner of sections 11 and 14.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E  
S11  
1/4 ———  
S14  
2010

Set a steel fence post east of the corner.

Corner is located on rolling, sandy hills.

62.492 Intersect the centerline of San Juan County Road No. 490, a gravel road, 25 ft. wide, bears N. 24° W. and S. 25° E.

80.032 The corner of sections 10, 11, 14, and 15.

---

N. 0°00.9' W., between sections 10 and 11.

40.000 Point for the 1/4 section corner of sections 10 and 11.

Set a brass tablet, 3 1/4 inch diameter, with 3 1/2 inch stem, in cement bond, into a hole drilled in solid sandstone bedrock, magnet at base, marked:

T42S R23E  
1/4  
S10 | S11  
2010

Raise a mound of stone, 2 ft. base, 1 ft. high, west of the corner.

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

Corner is located on rolling sandstone bedrock.

80.000 Point for the corner of sections 2, 3, 10, and 11.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at base, with brass cap marked:

T42S R23E  

S3	S2
S10	S11

  
2010

Set a steel fence post north of the corner.

Corner is located on rolling, sandy hills.

---

From the corner of sections 1, 2, 11, and 12.

S. 89°56.2' W., between sections 2 and 11.

40.016 Point for the 1/4 section corner of sections 2 and 11.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E  

S2
1/4
S11

  
2010

Set a steel fence post north of the corner.

Corner is located on gentle, rolling sand dunes.

63.490 Intersect the centerline of San Juan County Road No. 490, a gravel road, 25 ft. wide, bears N. 4° E. and S. 4° W.

80.032 The corner of sections 2, 3, 10, and 11.

---

N. 0°00.6' E., between sections 2 and 3.

40.000 Point for the 1/4 section corner of sections 2 and 3.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T42S R23E  
1/4  
S3 | S2  
2010

Set a steel fence post north of the corner.

Corner is located on a gentle west-sloping, sandy hill.

- 80.087** The corner of sections 2, 3, 34, and 35, on the north boundary of the township, hereinbefore described.

From the corner of sections 3, 4, 33, and 34, on the south boundary of the township, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 4 inches above an embedded mound of stone, 2 ft. base, 1/2 ft. high, with brass cap marked as described in the official record of the 2005 resurvey of the north boundary of T. 43 S., R. 23 E.

Set a steel fence post north of the corner.

N. 0°01.5' W., between sections 33 and 34.

- 40.000** Point for the 1/4 section corner of sections 33 and 34.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E  
1/4  
S33 | S34  
2010

Set a steel fence post east of the corner.

Corner is located on sandy, gentle rolling hills.

- 74.427** Intersect the centerline of San Juan County Road No. 455, a gravel road, 20 ft. wide, bears N. 21° W. and S. 25° E.

- 80.000** Point for the corner of sections 27, 28, 33, and 34.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T42S R23E

S28	S27
S33	S34

2010

Set a steel fence post north of the corner.

Corner is located on level terrain with sparse vegetation.

---

From the corner of sections 26, 27, 34, and 35.

S. 89°55.3' W., between sections 27 and 34.

13.729 Intersect the centerline of San Juan County Road No. 406, a paved road, 25 ft. wide, bears north and south.

40.041 Point for the 1/4 section corner of sections 27 and 34.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

	S27
1/4	
	S34

2010

Set a steel fence post north of the corner.

Corner is located on fairly level terrain with desert vegetation.

73.744 Intersect the centerline of San Juan County Road No. 456, a gravel road, 12 ft. wide, bears N. 30° E. and S. 30° W.

80.082 The corner of sections 27, 28, 33, and 34.

---

N. 0°01.5' W., between sections 27 and 28.

40.000 Point for the 1/4 section corner of sections 27 and 28.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T42S R23E

$$\begin{array}{c} 1/4 \\ S28 \left| S27 \end{array}$$

2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy hills with desert vegetation.

78.448 Intersect the centerline of San Juan County Road No. 454, a gravel road, 25 ft. wide, bears east and west.

80.000 Point for the corner of sections 21, 22, 27, and 28.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet and broken glass at base, with brass cap marked:

T42S R23E

$$\begin{array}{c} S21 \left| S22 \\ \hline S28 \left| S27 \end{array}$$

2010

Set a steel fence post north of the corner.

Corner is located on rolling, sandy hills.

From the corner of sections 22, 23, 26, and 27.

S. 89°55.3' W., between sections 22 and 27.

40.041 Point for the 1/4 section corner of sections 22 and 27.

Set a brass tablet, 3 1/4 inch diameter, with 3 1/2 inch stem, in cement bond, into a hole drilled in solid sandstone bedrock, magnet at base, marked:

T42S R23E

$$\begin{array}{c} S22 \\ 1/4 \text{ —————} \\ S27 \end{array}$$

2010

Raise a mound of stone, 3 ft. base, 4 ft. high, southwest of the corner.

Corner is located on a gentle west-sloping sandstone outcrop.

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

- 43.874 Intersect the centerline of San Juan County Road No. 454, a gravel road, 25 ft. wide, bears N. 40° E. and S. 51° W.
- 80.082 The corner of sections 21, 22, 27, and 28.

N. 0°01.5' W., between sections 21 and 22.

- 40.000 Point for the 1/4 section corner of sections 21 and 22.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

1/4	
S21	S22

2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling hills with desert vegetation.

- 80.000 Point for the corner of sections 15, 16, 21, and 22.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

S16	S15
S21	S22

2010

Set a steel fence post north of the corner.

Corner is located on rolling, sandy hills.

From the corner of sections 14, 15, 22, and 23.

S. 89°55.3' W., between sections 15 and 22.

- 40.041 Point for the 1/4 section corner of sections 15 and 22.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T42S R23E

S15

1/4 ———

S22

2010

Set a steel fence post north of the corner.

Corner is located on rolling, sandy hills.

80.082 The corner of sections 15, 16, 21, and 22.

N. 0°01.5' W., between sections 15 and 16.

40.000 Point for the 1/4 section corner of sections 15 and 16.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

1/4

S16 | S15

2010

Set a steel fence post south of the corner.

Corner is located on sandy, rolling hills with desert vegetation.

80.000 Point for the corner of sections 9, 10, 15, and 16.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

S9	S10
S16	S15

2010

Set a steel fence post north of the corner.

From the corner, an iron pipe, 2 3/8 inches diameter, firmly set, projecting 16 inches above the ground, bears N. 38°18' E., 22.1 links distance, with the side of pipe marked T42S R23E S9/S10/S15/S16.

This monument is not recorded and was not utilized in this

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

survey.

Corner is located on gentle rolling hills with desert vegetation.

---

From the corner of sections 10, 11, 14, and 15.

S. 89°55.3' W., between sections 10 and 15.

40.041 Point for the 1/4 section corner of sections 10 and 15.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

T42S R23E  
S10  
1/4 ———  
S15  
2010

Set a steel fence post north of the corner.

Corner is located on sandy, rolling hills, west of Desert Creek.

80.082 The corner of sections 9, 10, 15, and 16.

---

N. 0°01.5' W., between sections 9 and 10.

40.000 Point for the 1/4 section corner of sections 9 and 10.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E  
1/4  
S9 | S10  
2010

Set a steel fence post north of the corner.

Corner is located on rolling, sandy hills.

80.000 Point for the corner of sections 3, 4, 9, and 10.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T42S R23E

S4	S3
S9	S10

2010

Set a steel fence post northwest of the corner.

Corner is located on rolling, sandy hills.

---

From the corner of sections 2, 3, 10, and 11.

S. 89°55.3' W., between sections 3 and 10.

40.041 Point for the 1/4 section corner of sections 3 and 10.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

S3
1/4 ———
S10

2010

Set a steel fence post north of the corner.

Corner is located on sand dunes.

80.082 The corner of sections 3, 4, 9, and 10.

---

N. 0°03.5' E., between sections 3 and 4.

40.000 Point for the 1/4 section corner of sections 3 and 4.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

1/4
S4   S3

2010

Set a steel fence post north of the corner.

Corner is located on open desert terrain.

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

- 80.109 The corner of sections 3, 4, 33, and 34, on the north boundary of the township, hereinbefore described.
- 

From the corner of sections 4, 5, 32, and 33, on the south boundary of the township, monumented with an iron post, 2 1/2 inches diameter, firmly set but leaning, projecting 20 inches above the ground, with brass cap marked as described in the official record of the 2005 resurvey of the north boundary of T. 43 S., R. 23 E.

Reset iron post to 29 inches in the ground with magnet at the base.

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy hills.

N. 0°02.2' W., between sections 32 and 33.

- 40.000 Point for the 1/4 section corner of sections 32 and 33.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

T42S R23E  
1/4  
S32 | S33  
2010

Set a steel fence post north of the corner.

From the corner, a galvanized iron pipe, 1 1/2 inches diameter, firmly set, projecting 3 inches above the ground, bears S. 44°33' W., 1.2 links distance, with 2x2 inch iron plate cap marked 1/4 S32/S33.

This monument is not recorded and was not utilized in this survey.

Corner is located on gentle rolling, sandy hills.

- 80.000 Point for the corner of sections 28, 29, 32, and 33.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T42S R23E

S29	S28
S32	S33

2010

Set a steel fence post north of the corner.

Corner is located on rolling, sandy hills.

---

From the corner of sections 27, 28, 33, and 34.

S. 89°55.8' W., between sections 28 and 33.

1.897 Intersect the centerline of San Juan County Road No. 455, a gravel road, 20 ft. wide, bears N. 9° W. and S. 16° E.

40.034 Point for the 1/4 section corner of sections 28 and 33.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

S28
1/4
S33

2010

Set a steel fence post north of the corner.

Corner is located on rolling, sandy hills.

80.068 The corner of sections 28, 29, 32, and 33.

---

N. 0°02.2' W., between sections 28 and 29.

40.000 Point for the 1/4 section corner of sections 28 and 29.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

1/4
S29
S28

2010

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a steel fence post north of the corner.

Corner is located on rolling, sandy hills with desert vegetation.

78.503 Intersect the centerline of San Juan County Road No. 454, a gravel road, 25 ft. wide, bears east and west.

80.000 Point for the corner of sections 20, 21, 28, and 29.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet and broken glass at base, with brass cap marked:

T42S R23E

S20	S21
S29	S28

2010

Set a steel fence post north of the corner.

Corner is located on rolling, sandy hills.

---

From the corner of sections 21, 22, 27, and 28.

S. 89°55.8' W., between sections 21 and 28.

40.034 Point for the 1/4 section corner of sections 21 and 28.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet and broken glass at base, with brass cap marked:

T42S R23E

S21
1/4 ———
S28

2010

Set a steel fence post north of the corner.

Corner is located on rolling, sandy hills.

80.068 The corner of sections 20, 21, 28, and 29.

---

N. 0°02.2' W., between sections 20 and 21.

40.000 Point for the 1/4 section corner of sections 20 and 21.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

cap marked:

T42S R23E

1/4

S20	S21
-----	-----

2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy hills with desert vegetation.

**80.000** Point for the corner of sections 16, 17, 20, and 21.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

S17	S16
S20	S21

2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy hills, southwest of an unimproved dirt road.

From the corner of sections 15, 16, 21, and 22.

S. 89°55.8' W., between sections 16 and 21.

**40.034** Point for the 1/4 section corner of sections 16 and 21.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

S16

1/4	S21
-----	-----

2010

Set a steel fence post north of the corner.

Corner is located on fairly level desert terrain.

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

80.068 The corner of sections 16, 17, 20, and 21.

---

N. 0°02.2' W., between sections 16 and 17.

40.000 Point for the 1/4 section corner of sections 16 and 17.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

1/4	
S17	S16

2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy hills.

80.000 Point for the corner of sections 8, 9, 16, and 17.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

S8	S9
S17	S16

2010

Set a steel fence post north of the corner.

From the corner, a copper weld survey rod, 1/2 inch diameter, firmly set, projecting 13 inches above the ground, bears N.14°52' E., 9.6 links distance, marked T42SR23E 8/9/16/17 LS1446 1955.

Corner is located on rolling, sandy hills.

---

From the corner of sections 9, 10, 15, and 16.

S. 89°55.8' W., between sections 9 and 16.

40.034 Point for the 1/4 section corner of sections 9 and 16.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T42S R23E

	S9	
1/4	—	
	S16	

2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy hills.

80.068 The corner of sections 8, 9, 16, and 17.

N. 0°02.2' W., between sections 8 and 9.

40.000 Point for the 1/4 section corner of sections 8 and 9.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

	1/4	
S8		S9

2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy hills.

80.000 Point for the corner of sections 4, 5, 8, and 9.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

	S5	S4
S8		S9

2010

Set a steel fence post east of the corner.

Corner is located on fairly level desert terrain, with sparse vegetation.

From the corner of sections 3, 4, 9, and 10.

S. 89°55.8' W., between sections 4 and 9.

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

40.034 Point for the 1/4 section corner of sections 4 and 9.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E  
S4  
1/4 —————  
S9  
2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy hills, with sparse vegetation.

80.068 The corner of sections 4, 5, 8, and 9.

---

N. 0°04.0' E., between sections 4 and 5.

40.000 Point for the 1/4 section corner of sections 4 and 5.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E  
1/4  
S5 | S4  
2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling hills, south of Standing Rock.

80.116 Point for the corner of sections 4, 5, 32, and 33, on the north boundary of the township, hereinbefore described.

---

From the corner of sections 5, 6, 31, and 32, on the south boundary of the township, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above a mound of stone, 2 1/2 ft. base, 1/2 ft. high, with brass cap marked as described in the official record of the 2005 resurvey of the north boundary of T. 43 S., R. 23 E.

A steel fence post is located north of the corner.

Corner is located east of a seasonal lake bed, on gentle rolling, sandy ground.

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

N.  $0^{\circ}02.8'$  W., between sections 31 and 32.

40.000 Point for the 1/4 section corner of sections 31 and 32.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

1/4

S31	S32
-----	-----

2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy dunes.

80.000 Point for the corner of sections 29, 30, 31, and 32.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

S30	S29
S31	S32

2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy hills with desert vegetation.

From the corner of sections 28, 29, 32, and 33.

S.  $89^{\circ}56.3'$  W., between sections 29 and 32.

40.025 Point for the 1/4 section corner of sections 29 and 32.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

T42S R23E

S29

1/4 ———

S32

2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy hills with desert vegetation.

80.050 The corner of sections 29, 30, 31, and 32.

---

S. 89°57.8' W., between sections 30 and 31.

40.000 Point for the 1/4 section corner of sections 30 and 31.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

S30

1/4 ———

S31

2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling hills with desert vegetation.

47.039 Intersect the centerline of San Juan County Road No. 439, a gravel road, 20 ft. wide, bears N. 2° W. and S. 2° E.

79.425 The corner of sections 25, 30, 31, and 36, on the west boundary of the township, hereinbefore described.

---

From the corner of sections 29, 30, 31, and 32.

N. 0°02.8' W., between sections 29 and 30.

40.000 Point for the 1/4 section corner of sections 29 and 30.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T42S R23E

1/4  
S30 | S29

2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy hills.

78.359 Intersect the centerline of San Juan County Road No. 454, a gravel road, 25 ft. wide, bears east and west.

80.000 Point for the corner of sections 19, 20, 29, and 30.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

S19 | S20  
-----  
S30 | S29

2010

Set a steel fence post north of the corner.

From the corner, an iron pipe, 1 1/2 inch diameter, with square plate, 2 x 2 inches, welded on top, firmly set, projecting 4 inches above the ground, bears N. 72°32' W., 5.5 links distance, with the plate marked T42S R23E S19/S20/S29/S30.

This monument is not recorded and was not utilized in this survey.

Corner is located on gentle rolling, sandy hills with desert vegetation.

---

From the corner of sections 20, 21, 28, and 29.

S. 89°56.3' W., between sections 20 and 29.

40.025 Point for the 1/4 section corner of sections 20 and 29.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T42S R23E

S20  
1/4 ———  
S29

2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy hills with desert vegetation.

80.050 The corner of sections 19, 20, 29, and 30.

---

S. 89°57.7' W., between sections 19 and 30.

21.766 Intersect the centerline of San Juan County Road No. 454, a gravel road, 25 ft. wide, bears N. 75° W. and S. 80° E.

27.862 Intersect the centerline of San Juan County Road No. 454, a gravel road, 20 ft. wide, bears N. 89° E. and S. 87° W.

40.000 Point for the 1/4 section corner of sections 19 and 30.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

S19  
1/4 ———  
S30

2010

Set a steel fence post north of the corner.

Corner is located on a gentle, east-facing slope, in sandy ground with desert vegetation.

49.299 Intersect the centerline of San Juan County Road No. 439, a gravel road, 20 ft. wide, bears N. 11° E. and S. 8° W.

79.334 The corner of sections 19, 24, 25, and 30, on the west boundary of the township, hereinbefore described.

---

From the corner of sections 19, 20, 29, and 30.

N. 0°02.8' W., between sections 19 and 20.

40.000 Point for the 1/4 section corner of sections 19 and 20.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

cap marked:

T42S R23E  
1/4  
S19 | S20  
2010

Set a steel fence post north of the corner.

Corner is located in an open valley, on fairly level desert terrain.

80.000 Point for the corner of sections 17, 18, 19, and 20.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E  
S18 | S17  
S19 | S20  
2010

Set a steel fence post north of the corner.

Corner is located on a moderately-steep, northwest-facing slope, above a bedrock drainage, course N. 80° E.

From the corner of sections 16, 17, 20, and 21.

S. 89°56.3' W., between sections 17 and 20.

40.025 Point for the 1/4 section corner of sections 17 and 20.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

T42S R23E  
S17  
1/4 ———  
S20  
2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy hills with desert vegetation.

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

80.050 The corner of sections 17, 18, 19, and 20.

---

S. 89°58.9' W., between sections 18 and 19.

37.396 Intersect the centerline of San Juan County Road No. 439, a gravel road, 20 ft. wide, bears N. 25° E. and S. 34° W.

40.000 Point for the 1/4 section corner of sections 18 and 19.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

S18

1/4 —————

S19

2010

Set a steel fence post north of the corner.

Corner is located on a gentle, northwest-sloping sand dune.

79.254 The corner of sections 13, 18, 19, and 24, on the west boundary of the township, hereinbefore described.

---

From the corner of sections 17, 18, 19, and 20.

N. 0°02.8' W., between sections 17 and 18.

40.000 Point for the 1/4 section corner of sections 17 and 18.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, on bedrock, magnet at base, in a mound of stone, 5 ft. base, 2 1/2 ft. high, with brass cap marked:

T42S R23E

1/4

S18 | S17

2010

Set a steel fence post north of the corner.

Corner is located at a level bench, on a steep, southeast-facing, rocky hillside, approximately 100 ft. above the valley floor.

80.000 Point for the corner of sections 7, 8, 17, and 18.

Set a stainless steel post, 30 inches long, 2 1/2 inches

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

diameter, 18 inches in the ground, to bedrock, magnet at base, in a mound of stone, 4 ft. base to top of brass cap marked:

T42S R23E  

S7	S8
S18	S17

  
2010

Set a steel fence post east of the corner.

From the corner, a rusty iron pipe, 2 3/8 inches diameter, firmly set, projecting 20 inches above a collar of stone, 3 ft. diameter, bears N. 36°25' E., 17.2 links distance, with the side of pipe marked T42SR23E S7/S8/S17/S18.

This monument is not recorded and was not utilized in this survey.

Corner is located on a rocky spur, bears S. 60° E.

---

From the corner of sections 8, 9, 16, and 17.

S. 89°56.3' W., between sections 8 and 17.

40.025 Point for the 1/4 section corner of sections 8 and 17.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

T42S R23E  

S8
1/4 ———
S17

  
2010

Set a steel fence post north of the corner.

Corner is located on a gentle, south-sloping hill, above a drainage, course east.

80.050 The corner of sections 7, 8, 17, and 18.

---

N. 89°59.7' W., between sections 7 and 18.

40.000 Point for the 1/4 section corner of sections 7 and 18.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground, to bedrock, magnet at base, in a mound of stone, 2 ft. base to top of brass cap marked:

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T42S R23E  
 $\frac{1}{4}$   $\frac{S7}{S18}$   
 2010

Set a steel fence post north of the corner.

Corner is located on a fairly level mesa top with desert vegetation.

- 49.778 Intersect the centerline of San Juan County Road No. 439, a gravel road, 20 ft. wide, bears N. 46° W. and S. 43° E.
- 79.172 The corner of sections 7, 12, 13, and 18, on the west boundary of the township, hereinbefore described.
- 

From the corner of sections 7, 8, 17, and 18.

N. 0°02.8' W., between sections 7 and 8.

- 40.000 Point for the 1/4 section corner of sections 7 and 8.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E  
 $\frac{1}{4}$   
 $S7 \left| S8 \right.$   
 2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy hills with desert vegetation.

- 80.000 Point for the corner of sections 5, 6, 7, and 8.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T42S R23E

S6	S5
S7	S8

2010

Corner is located on gentle rolling, sandy hills with desert vegetation.

---

From the corner of sections 4, 5, 8, and 9.

S. 89°56.3' W., between sections 5 and 8.

40.025 Point for the 1/4 section corner of sections 5 and 8.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

S5
1/4 ———
S8

2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy hills with desert vegetation.

80.050 The corner of sections 5, 6, 7, and 8.

---

N. 89°59.3' W., between sections 6 and 7.

40.000 Point for the 1/4 section corner of sections 6 and 7.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

S6
1/4 ———
S7

2010

Set a steel fence post north of the corner.

Corner is located on a sandy hill, east of the base of a high mesa with desert vegetation.

THE SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

- 79.101 The corner of sections 1, 6, 7, and 12, on the west boundary of the township, hereinbefore described.
- 

From the corner of sections 5, 6, 7, and 8.

N. 0°04.5' E., between sections 5 and 6.

- 40.000 Point for the 1/4 section corner of sections 5 and 6.  
Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, flush in the ground, magnet at base, with brass cap marked:

T42S R23E

1/4

S6 | S5

2010

Set a steel fence post approximately 12 ft. north of the corner.

Corner is located on gentle rolling, sandy hills, at the northeast shoulder of an unimproved dirt road, bears N. 40° W. and S. 40° E.

- 80.119 The corner of sections 5, 6, 31, and 32, on the north boundary of the township, hereinbefore described.
- 

The Subdivision of Section 12,  
T. 42 S., R. 23 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 12 and 13.

N. 0°00.1' E., along the N-S centerline of section 12.

- 40.010 Point for the center 1/4 section corner of section 12, at the intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, to bedrock, magnet at base, in a mound of stone, 3 ft. base to top of brass cap marked:

T42S R23E

C 1/4 S12

2010

Set a steel fence post north of the corner.

Corner is located on broken ground, southeast of a large juniper tree.

- 80.010 The 1/4 section corner of sections 1 and 12.
-

THE SUBDIVISION OF SECTION 12,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

From the 1/4 section corner of sections 7 and 12, on the east boundary of the township.

S. 89°50.8' W., along the E-W centerline of section 12.

- 3.949 Intersect the centerline of San Juan County Road No. 406, a paved road, 25 ft. wide, bears N. 15° E. and S. 10° W.
- 40.026 The center 1/4 section corner of section 12.
- 80.050 The 1/4 section corner of sections 11 and 12.

The Subdivision of Section 13,  
T. 42 S., R. 23 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 13 and 24.

N. 0°00.1' E., along the N-S centerline of section 13.

- 40.006 Point for the center 1/4 section corner of section 13, at the intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E  
C 1/4 S13  
2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy hills.

- 45.428 Intersect the centerline of San Juan County Road No. 406, a paved road, 25 ft. wide, bears N. 35° E. and S. 35° W.
- 80.024 The 1/4 section corner of sections 12 and 13.

From the 1/4 section corner of sections 13 and 18, on the east boundary of the township.

S. 89°53.2' W., along the E-W centerline of section 13.

- 40.028 The center 1/4 section corner of section 13.
- 43.790 Intersect the centerline of San Juan County Road No. 406, a paved road, 25 ft. wide, bears N. 35° E. and S. 35° W.
- 80.053 The 1/4 section corner of sections 13 and 14.

THE SUBDIVISION OF SECTION 14,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

---

The Subdivision of Section 14,  
T. 42 S., R. 23 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 14 and 23.

N. 0°00.5' W., along the N-S centerline of section 14.

- 40.000 Point for the center 1/4 section corner of section 14, at the intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

C 1/4 S14

2010

Set a steel fence post west of the corner.

Corner is located on gentle rolling, sandy hills.

- 68.380 Intersect the centerline of San Juan County Road No. 490, a gravel road, 25 ft. wide, bears N.76°W. and S.76°E.

- 80.000 The 1/4 section corner of sections 11 and 14.

---

From the 1/4 section corner of sections 13 and 14.

S. 89°56.2' W., along the E-W centerline of section 14.

- 6.811 Intersect the centerline of San Juan County Road No. 490, a gravel road, 25 ft. wide, bears N.12°W. and S.12°E.

- 40.015 The center 1/4 section corner of section 14.

- 80.030 The 1/4 section corner of sections 14 and 15.

---

The Subdivision of Section 22,  
T. 42 S., R. 23 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 22 and 27.

N. 0°01.2' W., along the N-S centerline of section 22.

- 6.119 Intersect the centerline of San Juan County Road No. 454, a gravel road, 25 ft. wide, bears N.34°E. and S.31°W.

- 40.000 Point for the center 1/4 section corner of section 22, at the intersection with the E-W centerline.

THE SUBDIVISION OF SECTION 22,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E  
C 1/4 S22  
2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy hills with desert vegetation.

80.000 The 1/4 section corner of sections 15 and 22.

---

From the 1/4 section corner of sections 22 and 23.

S. 89°55.3' W., along the E-W centerline of section 22.

40.041 The center 1/4 section corner of section 22.

80.082 The 1/4 section corner of sections 21 and 22.

---

The Subdivision of Section 23,  
T. 42 S., R. 23 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 23 and 26.

N. 0°00.5' W., along the N-S centerline of section 23.

17.540 Intersect the centerline of San Juan County Road No. 406, a paved road, 25 ft. wide, bears N. 42° E. and S. 42° W.

40.000 Point for the center 1/4 section corner of section 23, at the intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E  
C 1/4 S23  
2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy hills.

80.000 The 1/4 section corner of sections 14 and 23.

---

From the 1/4 section corner of sections 23 and 24.

S. 89°56.2' W., along the E-W centerline of section 23.

THE SUBDIVISION OF SECTION 23,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

- 20.081 Intersect the centerline of San Juan County Road No. 406, a paved road, 25 ft. wide, bears N. 42° E. and S. 42° W.
- 40.015 The center 1/4 section corner of section 23.
- 80.030 The 1/4 section corner of sections 22 and 23.

The Subdivision of Section 24,  
T. 42 S., R. 23 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 24 and 25.

N. 0°00.4' E., along the N-S centerline of section 24.

- 39.968 Point for the center 1/4 section corner of section 24, at the intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

C 1/4 S24

2010

Set a steel fence post south of the corner.

Corner is located on gentle rolling, sandy hills.

- 79.974 The 1/4 section corner of sections 13 and 24.

From the 1/4 section corner of sections 19 and 24, on the east boundary of the township.

S. 89°54.3' W., along the E-W centerline of section 24.

- 40.027 The center 1/4 section corner of section 24.
- 80.049 The 1/4 section corner of sections 23 and 24.

The Subdivision of Section 26,  
T. 42 S., R. 23 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 26 and 35.

N. 0°00.5' W., along the N-S centerline of section 26.

- 40.000 Point for the center 1/4 section corner of section 26, at the intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches

THE SUBDIVISION OF SECTION 26,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E  
C 1/4 S26  
2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy hills, at the base of White Mesa to the east.

80.000 The 1/4 section corner of sections 23 and 26.

---

From the 1/4 section corner of sections 25 and 26.

S. 89°56.2' W., along the E-W centerline of section 26.

40.015 The center 1/4 section corner of section 26.

80.030 The 1/4 section corner of sections 26 and 27.

---

The Subdivision of Section 27,  
T. 42 S., R. 23 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 27 and 34.

N. 0°01.2' W., along the N-S centerline of section 27.

31.058 Intersect the centerline of San Juan County Road No. 456, a gravel road, 12 ft. wide, bears N. 49° E. and S. 49° W.

40.000 Point for the center 1/4 section corner of section 27, at the intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E  
C 1/4 S27  
2010

Set a steel fence post northeast of the corner.

Corner is located on gentle rolling, sandy hills with desert vegetation.

80.000 The 1/4 section corner of sections 22 and 27.

---

From the 1/4 section corner of sections 26 and 27.

S. 89°55.3' W., along the E-W centerline of section 27.

THE SUBDIVISION OF SECTION 27,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

- 8.914 Intersect the centerline of San Juan County Road No. 406, a paved road, 25 ft. wide, bears N. 26° E. and S. 26° W.
- 32.795 Intersect the centerline of San Juan County Road No. 456, a gravel road, 12 ft. wide, bears N. 25° E. and S. 30° W.
- 40.041 The center 1/4 section corner of section 27.
- 80.082 The 1/4 section corner of sections 27 and 28.

The Subdivision of Section 28,  
T. 42 S., R. 23 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 28 and 33.

N. 0°01.8' W., along the N-S centerline of section 28.

- 40.000 Point for the center 1/4 section corner of section 28, at the intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

C 1/4 S28

2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy hills with desert vegetation.

- 78.503 Intersect the centerline of San Juan County Road No. 454, a gravel road, 25 ft. wide, bears east and west.
- 80.000 The 1/4 section corner of sections 21 and 28.

From the 1/4 section corner of sections 27 and 28.

S. 89°55.8' W., along the E-W centerline of section 28.

- 11.255 Intersect the centerline of San Juan County Road No. 455, a gravel road, 20 ft. wide, bears N. 35° W. and S. 38° E.
- 40.034 The center 1/4 section corner of section 28.
- 80.068 The 1/4 section corner of sections 28 and 29.

THE SUBDIVISION OF SECTION 33,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

---

The Subdivision of Section 33,  
T. 42 S., R. 23 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 4 and 33, on the south boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 15 inches above the ground, with brass cap marked as described in the official record of the 2005 resurvey; with a steel fence post alongside.

Reset stainless steel post, 29 inches in the ground.

Corner is located in rolling sandy hills.

N. 0°02.1' W., along the N-S centerline of section 33.

40.000 Point for the center 1/4 section corner of section 33, at the intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at base, with brass cap marked:

T42S R23E

C 1/4 S33

2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling, sandy hills

80.000 The 1/4 section corner of sections 28 and 33.

---

From the 1/4 section corner of sections 33 and 34.

S. 89°55.8' W., along the E-W centerline of section 33.

40.032 The center 1/4 section corner of section 33.

80.069 The 1/4 section corner of sections 32 and 33.

---

The Subdivision of Section 34,  
T. 42 S., R. 23 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 3 and 34, on the south boundary of the township, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 12 inches above an embedded mound of stone, 2 ft. base, 6 inches high, with brass cap marked as described in the official record of the 1953 survey; with a steel fence post alongside.

N. 0°01.3' W., along the N-S centerline of section 34.

37.821 Intersect the centerline of San Juan County Road No. 455, a

THE SUBDIVISION OF SECTION 34,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH  
CHAINS

gravel road, 20 ft. wide, bears N. 60° W. and S. 62° E.

- 40.004 Point for the center 1/4 section corner of section 34, at the intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T42S R23E

C 1/4 S34

2010

Set a steel fence post northwest of the corner.

Corner is located on fairly level desert terrain.

- 80.004 The 1/4 section corner of sections 27 and 34.
- 

From the 1/4 section corner of sections 34 and 35.

S. 89°55.3' W., along the E-W centerline of section 34.

- 14.416 Intersect the centerline of San Juan County Road No. 406, a paved road, 25 ft. wide, bears north and south.

- 40.040 The center 1/4 section corner of section 34.

- 43.729 Intersect the centerline of San Juan County Road No. 455, a gravel road, 20 ft. wide, bears N. 60° W. and S. 62° E.

- 80.082 The 1/4 section corner of sections 33 and 34.
- 

The Subdivision of Section 35,  
T. 42 S., R. 23 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 2 and 35, on the south boundary of the township, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 13 inches above the ground, with brass cap marked as described in the official record of the 1953 survey; with a steel fence post alongside.

Corner is located on gentle south-facing sandy slope.

N. 0°00.1' W., along the N-S centerline of section 35.

- 40.013 Point for the center 1/4 section corner of section 35, at the intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked:

THE SUBDIVISION OF SECTION 35,  
TOWNSHIP 42 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T42S R23E

C 1/4 S35

2010

Set a steel fence post north of the corner.

Corner is located on gentle rolling desert terrain.

80.013 The 1/4 section corner of sections 26 and 35.

---

From the 1/4 section corner of sections 35 and 36.

S. 89°56.2' W., along the E-W centerline of section 35.

40.021 The center 1/4 section corner of section 35.

80.031 The 1/4 section corner of sections 34 and 35.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Phil Freiberg	Survey Technician

---

## CERTIFICATE OF SURVEY

I, *Scott A. Burkhardt, Cadastral Surveyor*, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing the date of *September 1, 2010*, I have *dependently resurveyed the west (Colorado Guide Meridian), east, and north boundaries, and surveyed the subdivisional lines, and subdivided sections 12, 13, 14, 22, 23, 24, 26, 27, 28, 33, 34, and 35, in Township 42 South, Range 23 East, of the Salt Lake Meridian, in the state of Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

*2/13/12*

Date

*Scott A. Burkhardt*

Cadastral Surveyor

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of the west (Colorado Guide Meridian), east, and north boundaries, the survey of the subdivisional lines, and the subdivision of sections 12, 13, 14, 22, 23, 24, 26, 27, 28, 33, 34, and 35, in Township 42 South, Range 23 East, Salt Lake Meridian, Utah*, executed by *Scott A. Burkhardt, Cadastral Surveyor*, having been critically examined and found correct, are hereby approved.

*February 24, 2012*

Date

*Daniel W. Webb*

Chief Cadastral Surveyor for Utah