

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE EAST BOUNDARY, IN TOWNSHIP 17 SOUTH, RANGE 21 EAST,

A PORTION OF THE SOUTH BOUNDARY, IN TOWNSHIP 16 SOUTH, RANGE 22 EAST,

AND

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,

AND

A METES-AND-BOUNDS SURVEY IN SECTIONS 3, 4, 8, 9, 17, 18, 19, AND 30,

IN

TOWNSHIP 17 SOUTH, RANGE 22 EAST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Scott A. Burkhardt
Cadastral Surveyor

Under Special Instructions dated and approved *July 12, 2010*, which provided for the surveys included under Group No. *1153*, and Assignment Instructions dated *July 12, 2010*.

Survey Commenced, *July 12, 2010*
Survey Completed, *August 23, 2010*

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE EAST BOUNDARY, IN TOWNSHIP 17 SOUTH, RANGE 21 EAST,

A PORTION OF THE SOUTH BOUNDARY, IN TOWNSHIP 16 SOUTH, RANGE 22 EAST,

AND

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,

AND

A METES-AND-BOUNDS SURVEY IN SECTIONS 3, 4, 8, 9, 17, 18, 19, AND 30,

IN

TOWNSHIP 17 SOUTH, RANGE 22 EAST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Scott A. Burkhardt
Cadastral Surveyor

Under Special Instructions dated and approved *July 12, 2010*, which provided for the surveys included under Group No. *1153*, and Assignment Instructions dated *July 12, 2010*.

Survey Commenced, *July 12, 2010*
Survey Completed, *August 23, 2010*

INDEX DIAGRAM

Township 17 South, Range 22 East.

	5	6	7	8	
6	5	13 4	10 3	8 2	1
	19	13	10		
7	18 8	12 9	9 10	11	12
18	18	12			
5 18	17 17	12 16	9 15	14	13
16	16	11			
4 19	15 20	21	22	23	24
15					
3 30	14 29	28	27	26	25
14					
31	32	33	34	35	36

Metes-and-Bounds Survey
 in Sections 3, 4, 8, 9, 17, 18, 19, and 30.....19

TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

The following field notes are those of the dependent resurvey of a portion of the east boundary of T. 17 S., R. 21 E., a portion of the south boundary of T. 16 S., R. 22 E., and the dependent resurvey of a portion of the subdivisional lines, and a metes-and-bounds survey in sections 3, 4, 8, 9, 17, 18, 19, and 30, in T. 17 S., R. 22 E., Salt Lake Meridian, Utah.

HISTORY OF SURVEYS

	Surveyed by	Retr. or Resurveyed by
SOUTH BOUNDARY		
All	G.D. Voorhees, et al.	1960
EAST BOUNDARY		
All	G.D. Voorhees, et al.	1960
WEST BOUNDARY (EAST BOUNDARY of T. 17 S., R. 21 E.)		
All	J.C. Clark & W.H. Good	1921
NORTH BOUNDARY (SOUTH BOUNDARY of T. 16 S., R. 22 E.)		
All	J.C. Clark	1922
SUBDIVISION		
Portion	G.D. Voorhees, et al.	1960
Portion	G.B. Hatch	1970

TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 1153, dated July 12, 2010.

The original corners on the west and north boundaries of T. 17 S., R. 22 E., were remarked by A.D. Griffen, under the supervision of G.D. Voorhees, in 1960, and refer to the east boundary of T. 17 S., R. 21 E., and the south boundary of T. 16 S., R. 21 E. only.

The direction of the lines was determined by references to true meridian, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards for the Positional Accuracy of Cadastral Surveys When Using Global Navigation Satellite Systems (GNSS)*, dated April 1, 2010. Trimble model 5800 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from GPS static observations, post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS); DH6916 MC04 MESA CNTY 04 COOP CORS ARP, DL3522 MC06 MACK CORS ARP, and DH6914 MC03 MESA CNTY 03 COOP CORS ARP.

The geographic position of the corner of sections 2 and 3 only, T. 17 S., R. 22 E., determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: 39°21'54.260" N.,
 Longitude: 109°27'45.457" W., N.A.D. 1983,
 Network Accuracy = 0.200 meter at 95% confidence

The geographic position of the 1/4 section corner of section 25 only, T. 17 S., R. 21 E., determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: 39°18'03.554" N.,
 Longitude: 109°32'12.144" W., N.A.D. 1983,
 Network Accuracy = 0.200 meter at 95% confidence

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 17 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Dependent Resurvey of a Portion of the East Boundary,
T. 17 S., R. 21 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
J.C. Clark and W.H. Good in 1921

Beginning at the corner of sections 25 and 36 only, on the east boundary of the township, monumented with an iron post, 2 inches diameter, firmly set, projecting 12 inches above the ground, with brass cap marked as described in the official record of the 1970 survey.

There is no remaining evidence of the original 1921 bearing trees.

Corner is located on a steep, west-facing slope with oak brush.

From this point, the closing corner of sections 30 and 31 only, T. 17 S., R. 22 E., bears S. 0°00.1' E., 9.930 chains distance, monumented with an iron post, 2 1/2 inches diameter, firmly set, flush with a mound of stone, 3 feet base, 2 feet high, with brass cap marked as described in the official record of the 1970 survey; located on a steep, west-facing slope.

N. 0°01.6' W., between sections 25 and 30.

- 30.037 The 1/4 section corner of section 30 only, T. 17 S., R. 22 E., monumented with an iron post, 2 inches diameter, firmly set, projecting 10 inches above the ground, with brass cap marked as described in the official record of the 1970 survey.
- 39.989 The 1/4 section corner of section 25 only, monumented with an iron post, 1 inch diameter, firmly set, projecting 12 inches above a mound of stone, 3 feet base, 1 foot high, with brass cap marked as described in the official record of the 1970 survey.

There is no remaining evidence of the original 1921 bearing tree.

This corner also functions as a reference monument for Angle Point No. 89 of a metes-and-bounds survey in section 30, hereinafter described.

N. 0°03.6' W., beginning new measurement.

- 1.357 Point for Angle Point No. 89, hereinafter described.
- 30.167 The closing corner of sections 19 and 30 only, T. 17 S., R. 22 E., monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 5 inches above the ground, with brass cap marked as described in the official record of the 1970 survey.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 17 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

There is no remaining evidence of the original 1970 bearing tree.

- 40.089 The corner of sections 24 and 25 only, monumented with an iron post, 2 inches diameter, firmly set, projecting 6 inches above an embedded mound of stone, 3 feet diameter, with brass cap marked as described in the official record of the 1970 survey.

There is no remaining evidence of the original 1921 bearing trees.

N. 0°01.3' W., between sections 19 and 24.

- 30.206 The 1/4 section corner of section 19 only, T. 17 S., R. 22 E., monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 4 inches above the ground, with brass cap marked as described in the official record of the 1970 survey.

There is no remaining evidence of the original 1970 bearing tree.

- 40.019 The 1/4 section corner of section 24 only, monumented with an iron post, 1 inch diameter, firmly set, projecting 6 inches above a mound of stone, 3 feet base, 2 feet high, with brass cap marked incorrectly:

$$\begin{array}{c} 1/4 \\ S24 \mid S19 \\ 1921 \end{array}$$

Remove marking "S19" from cap, and rehabilitate mound of stone.

N. 0°03.7' W., beginning new measurement.

- 29.577 True point for the closing corner of sections 18 and 19 only, T. 17 S., R. 22 E. Not monumented.

From this true point, the closing corner, bears S. 89°59.7' W., 0.018 chain distance, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 2 inches above a collar of stone, 2 feet diameter, with brass cap marked as described in the official record of the 1970 survey.

There is no remaining evidence of the original 1970 witness mound of stone to east of corner.

- 39.920 The corner of sections 13 and 24 only, monumented with an iron post, 2 inches diameter, firmly set, projecting 7 inches above the ground, witnessed by a mound of stone, 3 feet base, 1 foot high, west of corner, with brass cap marked as described in the official record of the 1970 survey.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 17 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

N. 0°01.3' W., between sections 13 and 18.

29.772 The 1/4 section corner of section 18 only, T. 17 S., R. 22 E., monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 8 inches above a mound of stone, 4 feet base, 2 feet high, with brass cap marked as described in the official record of the 1970 survey.

40.021 The 1/4 section corner of section 13 only, monumented with an iron post, 1 inch diameter, firmly set, projecting 5 inches above a mound of stone, 3 feet base, 2 feet high, with brass cap marked as described in the official record of the 1970 survey.

N. 0°00.2' W., beginning new measurement.

29.708 True point for the closing corner of sections 7 and 18 only, T. 17 S., R. 22 E. Not monumented.

From this true point, the closing corner, bears N. 89°56.6' W., 0.017 chains distance, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 5 inches above the ground, witnessed by a mound of stone, 3 feet base, 1 foot high, east of corner, with brass cap marked as described in the official record of the 1970 survey.

39.958 The corner of sections 12 and 13 only, monumented with an iron post, 2 inches diameter, firmly set, projecting 14 inches above a mound of stone, 3 feet base, 1 foot high, with brass cap marked as described in the official record of the 1970 survey.

Rehabilitate mound of stone, 3 feet base to top of brass cap.

Dependent Resurvey of a Portion of the South Boundary,
T. 16 S., R. 22 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by J.C. Clark in 1922

From the corner of sections 32 and 33 only, monumented with an iron post, 2 inches diameter, firmly set, projecting 4 inches above the ground, with brass cap marked as described in the official record of the 1922 survey.

Corner is located on a steep, northeast-facing hillside with thick brush.

S. 89°59.8' E., between sections 5 and 33.

25.683 The closing corner of sections 4 and 5 only, T. 17 S., R. 22 E., monumented with an iron post, 2 1/2 inches diameter, loosely set and leaning, in a mound of stone, 3 feet base, 1 foot high, with brass cap marked as described in the official record of the 1970

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
TOWNSHIP 16 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.
CHAINS

survey.

Reset iron post, and rehabilitate mound of stone.

Corner lies on a moderately steep, northeast-facing slope in thick brush.

- 39.927 The 1/4 section corner of section 33 only, monumented with an iron post, 1 inch diameter, firmly set but slightly bent, projecting 10 inches above the ground, with brass cap marked as described in the official record of the 1970 survey.

Straighten iron post, build a collar of stone, 2 feet diameter, around post.

S. 89°57.9' E., beginning new measurement.

- 25.533 True point for the 1/4 section corner of section 4 only, T. 17 S., R. 22 E. Not monumented.

From this true point, the 1970 1/4 section corner of section 4 only, T. 17 S., R. 22 E., bears North, 0.013 chain distance, monumented with an iron post, 2 1/2 inches diameter, loosely set, projecting 20 inches above a mound of stone, 2 feet base, 1 foot high, with brass cap marked as described in the official record of the 1970 survey.

Reset iron post, 10 inches in the ground to bedrock, magnet at base, in a mound of stone, 2 feet base to top of brass cap.

Corner is located on a gentle, west-facing slope with sagebrush and oak.

- 39.952 The corner of sections 33 and 34 only, monumented with an iron post, 2 inches diameter, firmly set, projecting 3 inches above the ground, witnessed by an embedded mound of stone, 4 feet diameter, to west of corner, with brass cap marked as described in the official record of the 1970 survey.

Corner is located on a northeast-facing slope, in a brushy drainage extending northwest and southeast.

Reestablishment of the Survey Executed by J.C. Clark in 1922,

N. 89°57.0' E., between sections 4 and 34.

- 25.330 The closing corner of sections 3 and 4 only, T. 17 S., R. 22 E., monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 15 inches above a collar of stone, 2 feet diameter, with brass cap marked as described in the official record of the 1960 survey.

- 39.971 The 1/4 section corner of section 34 only, monumented with an

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
TOWNSHIP 16 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

iron post, 1 inch diameter, firmly set, projecting 7 inches above the ground, witnessed by a mound of stone, 2 feet base, 1/2 foot high, north of corner, with brass cap marked incorrectly:

1/4	S34
	S3

1922

Remove marking "S3" from cap. Add markings "T16S R22E" and "2010" to cap.

S. 89°59.1' E., beginning new measurement.

- 25.271 Point for the 1/4 section corner of section 3 only, T. 17 S., R. 22 E., at proportionate distance. There is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with aluminum cap marked:

T16S	R22E
1/4	S3
T17S	
2010	

Corner is located on a moderately steep, east-facing slope with thick sagebrush.

- 39.940 The corner of sections 34 and 35 only, monumented with an iron post, 2 inches diameter, firmly set, projecting 16 inches above the ground, with brass cap incorrectly marked:

T16S	R22E
S34	S35
T17S	
1922	

There is no "1960" marked on cap.

S. 89°58.4' E., between sections 3 and 35.

- 25.243 The corner of sections 2 and 3 only, T. 17 S., R. 22 E., monumented with an iron post, 2 1/2 inches diameter, 30 inches long, lying loose on an embedded collar of stone, 2 feet diameter, with brass cap marked as described in the official record of the 1960 survey.

At the corner point (center of collar of stone)

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
TOWNSHIP 16 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Reset the iron post, 25 inches in the ground, magnet at base.

Corner lies in rolling terrain with sagebrush and oakbrush.

N. 89°57.5' E., beginning new measurement.

- 14.747 The 1/4 section corner of section 35 only, monumented with an iron post, 1 inch diameter, firmly set but bent over, projecting 24 inches above the ground, with brass cap marked as described in the official record of the 1960 resurvey.

At the corner point (base of iron post)

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 3 inches below the surface, magnet at base, with aluminum cap marked:

T16S	R22E
<hr style="width: 50%; margin: 0 auto;"/>	
1/4 S35	
2010	

Bury original iron post north of corner.

Corner is located on a gentle north slope with sagebrush, in the middle of an unimproved dirt road, 8 feet wide, bears north and south.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 17 S., R. 22 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
G.D. Voorhees, Et al. in 1960

From the corner of sections 2, 3, 10, and 11, determined from a mound of stone, 2 feet diameter, 1 foot high, with an iron post, 2 1/2 inches in diameter, 30 inches long, lying loose, with brass cap marked as described in the official record of the 1960 survey.

At the corner (center of mound of stone)

Reset the iron post, flush with the rehabilitated mound of stone, 4 feet base, 2 feet high.

Corner is located on a moderately steep, west-facing slope.

N. 0°08.0' E., between sections 2 and 3.

- 39.561 The 1/4 section corner of sections 2 and 3, monumented with an iron post, 2 1/2 inches in diameter, firmly set, projecting 13

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.
CHAINS

inches above the ground, with brass cap marked as described in the official record of the 1960 survey.

Corner is located on gently rolling ground, with sagebrush and scattered oak brush.

N. 0°01.8' W., beginning new measurement.

28.147 Point for Angle Point No. 1, hereinafter described.

44.680 The closing corner of sections 2 and 3, on the north boundary of the township, hereinbefore described.

From the corner of sections 15, 16, 21, and 22, monumented with an iron post, 2 1/2 inches in diameter, firmly set, projecting 8 inches above a mound of stone, 3 feet base, 2 feet high, with brass cap marked as described in the official record of the 1960 survey.

N. 0°00.7' W., between sections 15 and 16.

40.079 Point for the 1/4 section corner of sections 15 and 16, at proportionate distance. There is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 29 inches in the ground, magnet at base, with brass cap marked:

T17S R22E

1/4

S16 | S15

2010

Corner is located on a very steep, north-facing slope in thick oak brush. Difficult access.

80.158 The corner of sections 9, 10, 15, and 16, monumented with an iron post, 2 1/2 inches in diameter, firmly set, projecting 14 inches above a mound of stone, 3 feet base, 2 feet high, with brass cap marked as described in the official record of the 1960 survey.

Corner is located on a steep southwest-facing slope on the northeast side of Pipeline Canyon with pinon and juniper trees. Difficult access.

N. 0°23.7' W., between sections 9 and 10.

40.187 The 1/4 section corner of sections 9 and 10, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 8 inches above the ground, in a collar of stone, 2 feet diameter, with a

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.
CHAINS

brass cap marked as described in the official record of the 1960 survey.

Corner is located on a very steep, northeast-facing slope near the bottom of a deep drainage.

N. $0^{\circ}17.1'$ E., beginning new measurement.

- 39.835 The corner of sections 3, 4, 9, and 10, monumented with an iron post, 2 1/2 inches in diameter, firmly set, projecting 13 inches above a mound of stone, 2 feet diameter base, 1/2 foot high, with brass cap marked as described in the official record of the 1960 survey.

Corner is located on a gentle, east-facing slope in a brushy area.

Reestablishment of the Survey Executed by G.B. Hatch in 1970

From the corner of sections 2, 3, 10, and 11.

N. $89^{\circ}42.8'$ W., between sections 3 and 10.

- 39.523 The 1/4 section corner of sections 3 and 10, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 8 inches above the ground, witnessed by a mound of stone, 2 feet base, 1 foot high, north of corner, with a brass cap marked as described in the official record of the 1970 survey.

From which the 1970 bearing trees

A pine, 11 inches diameter, bears N. $7^{\circ}00'$ E., 24.0 links distance, marked 1/4 S3 BT (Record: 10 inches diameter, N. $7^{\circ}30'$ W.).

A pine, 7 inches diameter, bears S. $55^{\circ}00'$ E., 4.0 links distance, with undecipherable markings (Record: 6 inches diameter, S. 63° E., marked 1/4 S BT).

Corner is located on a very steep, northeast-facing slope in dense timber.

S. $89^{\circ}52.5'$ W., beginning new measurement.

- 40.132 The corner of sections 3, 4, 9, and 10.

Reestablishment of the Survey Executed by
G.D. Voorhees, et al. in 1960

N. $0^{\circ}04.8'$ W., between sections 3 and 4.

- 18.322 Point for Angle Point No. 18, hereinafter described.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.
CHAINS

- 39.756 Point for the 1/4 section corner of sections 3 and 4, at proportionate distance.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, magnet at base, in a collar of stone, 1 foot diameter, with brass cap marked:

T17S R22E
 1/4
 |
 S4 | S3
 |
 2010

Corner is located next to a fencepost, 6 inches diameter, 4 feet high, with a fence, 4-strand barbed wire, extending N. 20° W. and S. 10° E.

- 40.073 Point for the 1960 witness corner to the 1/4 section corner of sections 3 and 4, at proportionate distance. There is no remaining evidence of the witness corner. Not monumented.
- 84.142 The closing corner of sections 3 and 4, on the north boundary of the township, hereinbefore described.

From the corner of sections 15, 16, 21, and 22.

N. 89°57.4' W., between sections 16 and 21.

- 39.836 The 1/4 section corner of sections 16 and 21, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 12 inches above a collar of stone, 2 feet diameter, with a brass cap incorrectly marked:

T17S R22E
 S16

 S21
 1960

Add mark "1/4" to cap, and rehabilitate mound of stone, 2 feet base to top of brass cap.

Corner is located in an open drainage of Westwater Canyon with sagebrush.

N. 89°49.0' W., beginning new measurement.

- 39.914 The corner of sections 16, 17, 20, and 21, monumented with an iron post, 2 1/2 inches in diameter, firmly set, projecting 6 inches above a mound of stone, 5 feet base, 2 feet high, with brass cap marked as described in the official record of the 1960

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.
CHAINS

survey.

Corner is located near the bottom of a south-facing slope in Westwater Canyon.

N. 0°03.4' W., between sections 16 and 17.

- 39.512 The 1/4 section corner of sections 16 and 17, monumented with an iron post, 2 1/2 inches in diameter, firmly set, projecting 5 inches above a mound of stone, 4 feet base, 3 feet high, with brass cap marked as described in the official record of the 1960 survey.

Corner is located on a very steep, rocky, east-facing slope, with oak brush.

N. 0°08.9' E., beginning new measurement.

- 40.002 The corner of sections 8, 9, 16, and 17, monumented with an iron post, 2 1/2 inches in diameter, firmly set, projecting 10 inches above the ground, witnessed by an embedded mound of stone, 2 feet diameter, east of corner, with brass cap marked as described in the official record of the 1960 survey.
-

From the corner of sections 9, 10, 15, and 16.

S. 89°02.6' W., between sections 9 and 16.

- 39.800 The 1/4 section corner of sections 9 and 16, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 10 inches above the ground, with a brass cap marked as described in the official record of the 1960 survey.

Corner is located on a very steep, north-facing slope. Area has been burned.

N. 89°44.6' W., beginning new measurement.

- 39.859 The corner of sections 8, 9, 16, and 17.
-

Reestablishment of the Survey Executed by G.B. Hatch in 1970

N. 0°02.2' W., between sections 8 and 9.

- 19.527 Point for Angle Point No. 39, hereinafter described.

- 40.061 The 1/4 section corner of sections 8 and 9, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 5 inches above the ground, witnessed by a mound of stone, 2 feet base, 1 foot high, west of corner, with a brass cap marked as described

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.
CHAINS

in the official record of the 1970 survey.

From which the 1970 bearing tree

A pine, 18 inches diameter, bears N. 7°30' W., 67.0 links distance, with healed blaze (Record: 10 inches diameter, marked 1/4 S8 BT).

Corner is located on a moderately steep, west-facing slope in brush and scattered pine trees.

N. 0°01.7' W., beginning new measurement.

- 40.044 The corner of sections 4, 5, 8, and 9, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 10 inches above the ground, witnessed by a mound of stone, 2 feet base, 1 foot high, west of corner, with a brass cap marked as described in the official record of the 1970 survey.

Corner is located on a brushy, moderately steep, west-facing slope.

From the corner of sections 3, 4, 9, and 10.

S. 89°42.7' W., between sections 4 and 9.

- 22.335 Point for Angle Point No. 24, hereinafter described.

- 39.766 The 1/4 section corner of sections 4 and 9, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 5 inches above a mound of stone, 3 feet base, 1 foot high, with a brass cap marked as described in the official record of the 1970 survey.

From which the 1970 bearing tree

A pine, 15 inches diameter, bears S. 42°15' W., 32.0 links distance, with healed blaze (Record: 6 inches diameter, marked 1/4 S9 BT).

Corner is located on a gentle, northeast-facing slope with brush and scattered pine trees.

S. 89°42.5' W., beginning new measurement.

- 39.840 The corner of sections 4, 5, 8, and 9.

N. 0°02.2' W., between sections 4 and 5.

- 39.934 The 1/4 section corner of sections 4 and 5, monumented with an iron post, 2 1/2 inches diameter, firmly set, flush with a mound of stone, 3 feet base, 2 feet high, with a brass cap marked as described in the official record of the 1970 survey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.
CHAINS

N. 0°02.5' W., beginning new measurement.

- 44.607 The closing corner of sections 4 and 5, on the north boundary of the township, hereinbefore described.
-

From the corner of sections 29, 30, 31, and 32, monumented with an iron post, 2 1/2 inches in diameter, loosely set, projecting 15 inches above a mound of stone, 4 feet base, 2 feet high, with a brass cap marked as described in the official record of the 1960 survey.

Reset iron post, 30 inches long, 26 inches in the mound of stone, 4 feet base, 2 feet high.

Corner is located on the bench of a steep, west-facing slope with ledges.

N. 89°59.8' W., between sections 30 and 31.

- 40.129 The 1/4 section corner of sections 30 and 31, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 5 inches above a mound of stone, 4 feet base, 2 feet high, with a brass cap marked as described in the official record of the 1970 survey.

There is no remaining evidence of the original 1970 bearing trees.

Corner is located on a very steep, east-facing slope.

S. 89°56.0' W., beginning new measurement.

- 37.665 The closing corner of sections 30 and 31 only, on the west boundary of the township, hereinbefore described.
-

From the corner of sections 29, 30, 31, and 32.

N. 0°05.1' W., between sections 29 and 30.

- 39.995 The 1/4 section corner of sections 29 and 30, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above a mound of stone, 2 feet base, 2 feet high, with a brass cap marked as described in the official record of the 1970 survey.

Corner is located on a steep, southwest-facing slope in oak brush.

N. 0°03.1' W., beginning new measurement.

- 40.054 The corner of sections 19, 20, 29, and 30, monumented with an

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.
CHAINS

iron post, 2 1/2 inches diameter, firmly set, projecting 9 inches above the ground, with a brass cap marked as described in the official record of the 1970 survey.

Corner is located in deep drainage.

S. 89°59.7' W., between sections 19 and 30.

- 39.985 Point for the 1/4 section corner of sections 19 and 30. There is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, in a collar of stone, 2 feet diameter, magnet at base, with aluminum cap marked:

T17S R22E

S19

1/4 —————

S30

2010

Corner is located southeast of an improved gravel road (Grand County Road 209) in sagebrush.

This corner also functions as a reference monument for Angle Point No. 81 of a metes-and-bounds survey of sections 19 and 30, hereinafter described.

- 40.813 Point for Angle Point No. 81, hereinafter described.
- 77.730 The closing corner of sections 19 and 30 only, on the west boundary of the township, hereinbefore described.

From the corner of sections 19, 20, 29, and 30

N. 0°02.3' W., between sections 19 and 20.

- 39.976 The 1/4 section corner of sections 19 and 20, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 8 inches above the ground, with a brass cap marked as described in the official record of the 1970 survey.

From which the 1970 bearing trees

A pine, 18 inches diameter, bears S. 78°00.0' E., 22.0 links distance, with healed blaze (Record: 12 inches diameter, marked 1/4 S20 BT).

A pine, 13 inches diameter, bears N. 70°00.0' W., 10.0 links distance, with healed blaze (Record: 10 inches diameter, marked 1/4 S19 BT).

Corner is located on a very steep, north-facing slope with dense

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

pine trees.

N. 0°06.7' W., beginning new measurement.

- 39.542 The closing corner of sections 19 and 20 only, monumented with an iron post, 2 1/2 inches diameter, firmly set, flush with the ground, with a brass cap marked as described in the official record of the 1970 survey.

From which the 1970 bearing tree

A pine snag, 18 inches diameter, bears S. 80°54.0' E., 177.6 links distance, marked T17S R22E S20 CC BT (Record: S. 80°45' E., 179 links distance).

From the corner of sections 16, 17, 20, and 21.

S. 89°59.0' W., between sections 17 and 20.

- 40.028 The 1/4 section corner of section 17 only, monumented with an iron post, 2 1/2 inches diameter, firmly set, flush with ground, supported by a mound of stone, 4 feet diameter base, with a brass cap marked as described in the official record of the 1970 survey.

There is no remaining evidence of the original 1970 bearing tree.

Corner is located on a very steep, north-facing slope. Large fire in area, difficult access.

N. 89°56.9' W., beginning new measurement.

- 39.982 The corner of sections 17 and 18 only, monumented with an iron post, 2 1/2 inches in diameter, firmly set, projecting 4 inches above the ground, with brass cap marked as described in the official record of the 1970 survey.

From which the 1970 bearing trees

A pinon, 10 inches diameter, bears N. 39°09.7' E., 117.0 links distance, marked T17S R22E S17 BT (Record: 8 inches diameter, N. 37°45' E., 115 links distance).

A burnt pinon snag, 10 inches diameter, bears N. 37°42.2' W., 116.6 links distance, marked T17S R22E S18 BT (Record: 8 inches diameter, N. 39°00' W., 120 links distance).

S. 89°59.8' W., on the south boundary of section 18.

- 0.680 The closing corner of sections 19 and 20 only.

- 6.406 Point for Angle Point No. 68, of a metes-and-bounds survey in

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.
CHAINS

sections 18 and 19, hereinafter described.

- 39.911 The 1/4 section corner of section 18 only, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 4 inches above the ground, with a brass cap marked as described in the official record of the 1970 survey.

Corner is located on a moderately steep, northeast-facing slope with brush and scattered pine trees.

S. 89°59.7' W., beginning new measurement.

- 0.677 The 1/4 section corner of section 19 only, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above an embedded mound of stone, 2 feet diameter, with a brass cap marked as described in the official record of the 1970 survey.

Corner is located on a moderately steep, northeast-facing slope with brush and scattered pine trees.

- 38.440 The true point for the closing corner of sections 18 and 19 only, on the west boundary of the township, hereinbefore described.

From the corner of sections 17 and 18 only.

N. 0°00.2' W., between sections 17 and 18.

- 12.024 Point for Angle Point No. 64, of the metes and bounds survey in sections 17 and 18, hereinafter described.

- 39.900 The 1/4 section corner of sections 17 and 18, monumented with an iron post, 2 1/2 inches in diameter, firmly set, projecting 9 inches above a collar of stone, 3 feet diameter base, with brass cap marked as described in the official record of the 1970 survey.

From which the remaining 1970 bearing tree

A spruce, 8 inches diameter, bears S. 59°00.0' E., 60.0 links distance, with healed blaze (Record: 4 inches diameter, marked 1/4 S17 BT).

Second tree dead and down.

N. 0°02.7' W., beginning new measurement.

- 40.104 The corner of sections 7, 8, 17, and 18, monumented with an iron post, 2 1/2 inches in diameter, firmly set, projecting 3 inches above the ground, witnessed by an embedded mound of stone, 2 feet diameter, west of corner, with brass cap marked as described in the official record of the 1970 survey.
-

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

From the corner of sections 8, 9, 16, and 17.

N. 89°38.6' W., between sections 8 and 17.

- 40.100 The 1/4 section corner of sections 8 and 17, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above an embedded mound of stone, 3 feet diameter, with a brass cap marked as described in the official record of the 1970 survey.

Corner is located on a moderately-steep, east-facing slope, with dense oak brush.

N. 89°37.3' W., beginning new measurement.

- 19.573 Point for Angle Point No. 51, hereinafter described.

- 39.994 The corner of sections 7, 8, 17, and 18.

N. 89°58.1' W., between sections 7 and 18.

- 39.979 The 1/4 section corner of sections 7 and 18, monumented with an iron post, 2 1/2 inches in diameter, firmly set, projecting 10 inches above a mound of stone, 4 feet diameter base, 2 feet high, with brass cap marked as described in the official record of the 1970 survey.

Rehabilitate mound of stone, 4 feet base, to top of brass cap.

There is no remaining evidence of the original 1970 bearing tree.

N. 89°56.6' W., beginning new measurement.

- 38.349 The true point for the closing corner of sections 7 and 18, on the west boundary of the township, hereinbefore described.

From the corner of sections 7, 8, 17, and 18.

N. 0°01.6' W., between sections 7 and 8.

- 39.959 The 1/4 section corner of sections 7 and 8, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above the ground, with a brass cap marked as described in the official record of the 1970 survey.

N. 0°04.4' W., beginning new measurement.

- 39.955 The corner of sections 5, 6, 7, and 8, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 7 inches above the ground, witnessed by a mound of stone, 2 feet base, 1 foot high, west of corner, with a brass cap marked as described

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.
CHAINS

in the official record of the 1970 survey.

From the corner of sections 4, 5, 8, and 9.

N. 89°46.6' W., between sections 5 and 8.

- 40.069 The 1/4 section corner of sections 5 and 8, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 4 inches above the ground, witnessed by a mound of stone, 2 feet base, 1 foot high, north of corner, with a brass cap marked as described in the official record of the 1970 survey.

Corner is located on a moderately steep, north-facing slope with dense pine trees.

N. 89°45.6' W., beginning new measurement.

- 40.033 The corner of sections 5, 6, 7, and 8.
-

Metes-and-Bounds Survey
in Sections 3, 4, 8, 9, 17, 18, 19, and 30,
T. 17 S., R. 22 E., Salt Lake Meridian, Utah.

This metes-and-bounds survey follows the centerline of Grand County Road 209, also known as Divide Ridge Road, an improved gravel road, 20 feet wide, in sections 3, 4, 8, 9, 17, 18, 19, and 30, in T. 17 S., R. 22 E. Angle points were determined by visual inspection and aerial photography, and all angle points are monumented with steel spikes, 8 inches long, 3/8 inch diameter, set 6 inches or greater below the surface of the road.

Angle points at the intersection of section lines were perpetuated by reference monuments, one on each side of the roadway. Additionally, intermediate angle points were perpetuated by reference monuments to provide a spacing of approximately 1/2 mile between referenced angle points.

From the point for Angle Point No. 1, at intersection with the section line of sections 2 and 3, Township 17 South, Range 22 East.

At the corner point

Set a steel spike, 3/8 inch diameter, 8 inches long, 7 inches below the road surface.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, for a reference monument, bears N. 71°34.2' E., 105.5 links distance, with aluminum cap marked RM T17S R22E S2 2010, with an arrow

METES-AND-BOUNDS SURVEY IN
 SECTIONS 3, 4, 8, 9, 17, 18, 19, AND 30,
 TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

pointing toward the corner with 69.6 FT. TO COR. marked along it.

An aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, for a reference monument, bears S. 12°51.1' E., 98.1 links distance, with aluminum cap marked RM T17S R22E S2 2010, with an arrow pointing toward the corner with 64.7 FT. TO COR. marked along it.

N. 68°47.6' W., on line 1-2, in section 3.

6.230 Point selected for Angle Point No. 2.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 72°22.8' W., on line 2-3, beginning new measurement.

6.226 Point selected for Angle Point No. 3.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 66°15.7' W., on line 3-4, beginning new measurement.

12.910 Point selected for Angle Point No. 4.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 78°47.4' W., on line 4-5, beginning new measurement.

4.357 Point selected for Angle Point No. 5.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 60°22.1' W., on line 5-6, beginning new measurement.

5.967 Point selected for Angle Point No. 6.

Set a steel spike, 3/8 inch diameter, 8 inches long, 9 inches below the road surface.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, for a reference monument, bears N. 37°25.1' E., 96.6 links distance, with aluminum cap marked RM T17S R22E S3 2010, with an arrow

METES-AND-BOUNDS SURVEY IN
 SECTIONS 3, 4, 8, 9, 17, 18, 19, AND 30,
 TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

pointing toward the corner with 63.8 FT. TO COR. marked along it.

An aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, for a reference monument, bears S. 60°18.9' E., 79.6 links distance, with aluminum cap marked RM T17S R22E S3 2010, with an arrow pointing toward the corner with 52.5 FT. TO COR. marked along it.

S. 89°36.8' W., on line 6-7, beginning new measurement.

4.897 Point selected for Angle Point No. 7.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

N. 79°12.1' W., on line 7-8, beginning new measurement.

5.871 Point selected for Angle Point No. 8.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 70°01.6' W., on line 8-9, beginning new measurement.

3.192 Point selected for Angle Point No. 9.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 27°31.6' W., on line 9-10, beginning new measurement.

9.930 Point selected for Angle Point No. 10.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 48°04.5' W., on line 10-11, beginning new measurement.

3.246 Point selected for Angle Point No. 11.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 30°32.4' W., on line 11-12, beginning new measurement.

4.821 Point selected for Angle Point No. 12.

METES-AND-BOUNDS SURVEY IN
 SECTIONS 3, 4, 8, 9, 17, 18, 19, AND 30,
 TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Set a steel spike, 3/8 inch diameter, 8 inches long, 10 inches below the road surface.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, for a reference monument, bears S. 20°34.1' E., 61.2 links distance, with aluminum cap marked RM T17S R22E S3 2010, with an arrow pointing toward the corner with 40.4 FT. TO COR. marked along it.

An aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, for a reference monument, bears S. 70°57.5' W., 67.3 links distance, with aluminum cap marked RM T17S R22E S3 2010, with an arrow pointing toward the corner with 44.4 FT. TO COR. marked along it.

S. 35°10.7' W., on line 12-13, beginning new measurement.

6.584 Point selected for Angle Point No. 13.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 45°40.8' W., on line 13-14, beginning new measurement.

8.507 Point selected for Angle Point No. 14.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 24°42.2' W., on line 14-15, beginning new measurement.

5.031 Point selected for Angle Point No. 15.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 30°48.8' W., on line 15-16, beginning new measurement.

7.817 Point selected for Angle Point No. 16.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 58°17.8' W., on line 16-17, beginning new measurement.

4.063 Point selected for Angle Point No. 17.

METES-AND-BOUNDS SURVEY IN
 SECTIONS 3, 4, 8, 9, 17, 18, 19, AND 30,
 TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 79°44.2' W., on line 17-18, beginning new measurement.

- 4.232 The point for Angle Point No. 18, at intersection with the section line between sections 3 and 4.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, for a reference monument, bears S. 44°17.1' W., 80.6 links distance, with aluminum cap marked RM T17S R22E S4 2010, with an arrow pointing toward the corner with 53.2 FT. TO COR. marked along it.

An aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, for a reference monument, bears N. 49°36.3' W., 78.1 links distance, with aluminum cap marked RM T17S R22E S4 2010, with an arrow pointing toward the corner with 51.6 FT. TO COR. marked along it.

S. 77°26.3' W., on line 18-19, in section 4.

- 2.055 Point selected for Angle Point No. 19.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 50°21.7' W., on line 19-20, beginning new measurement.

- 6.400 Point selected for Angle Point No. 20.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 33°50.9' W., on line 20-21, beginning new measurement.

- 5.667 Point selected for Angle Point No. 21.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 64°49.0' W., on line 21-22, beginning new measurement.

- 3.653 Point selected for Angle Point No. 22.

METES-AND-BOUNDS SURVEY IN
 SECTIONS 3, 4, 8, 9, 17, 18, 19, AND 30,
 TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 54°37.9' W., on line 22-23, beginning new measurement.

9.175 Point selected for Angle Point No. 23.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 31°29.4' W., on line 23-24, beginning new measurement.

2.734 The point for Angle Point No. 24, at intersection with the line between sections 4 and 9.

Set a steel spike, 3/8 inch diameter, 8 inches long, 9 inches below the road surface.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, for a reference monument, bears N. 72°00.8' E., 64.6 links distance, with aluminum cap marked RM T17S R22E S4 2010, with an arrow pointing toward the corner with 42.7 FT. TO COR. marked along it.

An aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, for a reference monument, bears N. 12°02.0' W., 44.2 links distance, with aluminum cap marked RM T17S R22E S4 2010, with an arrow pointing toward the corner with 29.2 FT. TO COR. marked along it.

S. 45°13.9' W., on line 24-25, in section 9.

12.338 Point selected for Angle Point No. 25.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 73°40.4' W., on line 25-26, beginning new measurement.

2.695 Point selected for Angle Point No. 26.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

N. 88°30.1' W., on line 26-27, beginning new measurement.

METES-AND-BOUNDS SURVEY IN
 SECTIONS 3, 4, 8, 9, 17, 18, 19, AND 30,
 TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

5.169 Point selected for Angle Point No. 27.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

N. 75°00.5' W., on line 27-28, beginning new measurement.

4.271 Point selected for Angle Point No. 28.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

N. 81°41.6' W., on line 28-29, beginning new measurement.

3.138 Point selected for Angle Point No. 29.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 78°24.1' W., on line 29-30, beginning new measurement.

2.067 Point selected for Angle Point No. 30.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 54°04.9' W., on line 30-31, beginning new measurement.

2.075 Point selected for Angle Point No. 31.

Set a steel spike, 3/8 inch diameter, 8 inches long, 9 inches below the road surface.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, for a reference monument, bears S. 17°59.7' E., 76.1 links distance, with aluminum cap marked RM T17S R22E S9 2010, with an arrow pointing toward the corner with 50.2 FT. TO COR. marked along it.

An aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, for a reference monument, bears S. 81°29.1' W., 111.5 links distance, with aluminum cap marked RM T17S R22E S9 2010, with an arrow pointing toward the corner with 73.6 FT. TO COR. marked along it.

S. 28°06.6' W., on line 31-32, beginning new measurement.

METES-AND-BOUNDS SURVEY IN
 SECTIONS 3, 4, 8, 9, 17, 18, 19, AND 30,
 TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

7.688 Point selected for Angle Point No. 32.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. $10^{\circ}43.2'$ W., on line 32-33, beginning new measurement.

2.994 Point selected for Angle Point No. 33.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. $43^{\circ}19.9'$ W., on line 33-34, beginning new measurement.

4.510 Point selected for Angle Point No. 34.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. $30^{\circ}32.4'$ W., on line 34-35, beginning new measurement.

5.140 Point selected for Angle Point No. 35.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. $43^{\circ}04.7'$ W., on line 35-36, beginning new measurement.

11.799 Point selected for Angle Point No. 36.

Set a steel spike, 3/8 inch diameter, 8 inches long, 8 inches below the road surface.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, for a reference monument, bears S. $5^{\circ}47.1'$ E., 109.9 links distance, with aluminum cap marked RM T17S R22E S9 2010, with an arrow pointing toward the corner with 72.5 FT. TO COR. marked along it.

An aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, for a reference monument, bears N. $84^{\circ}11.9'$ W., 88.2 links distance, with aluminum cap marked RM T17S R22E S9 2010, with an arrow pointing toward the corner with 58.2 FT. TO COR. marked along it.

METES-AND-BOUNDS SURVEY IN
 SECTIONS 3, 4, 8, 9, 17, 18, 19, AND 30,
 TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

S. 28°20.1' W., on line 36-37, beginning new measurement.

10.609 Point selected for Angle Point No. 37.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 20°09.6' W., on line 37-38, beginning new measurement.

11.369 Point selected for Angle Point No. 38.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 28°03.3' W., on line 38-39, beginning new measurement.

6.147 The point for Angle Point No. 39, at intersection with the section line between sections 8 and 9.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, magnet at base, for a reference monument, bears S. 14°37.7' E., 53.2 links distance, with aluminum cap marked RM T17S R22E S9 2010, with an arrow pointing toward the corner with 35.1 FT. TO COR. marked along it.

An aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, for a reference monument, bears S. 77°41.4' W., 46.4 links distance, with aluminum cap marked RM T17S R22E S8 2010, with an arrow pointing toward the corner with 30.6 FT. TO COR. marked along it.

S. 39°00.5' W., on line 39-40, in section 8.

2.183 Point selected for Angle Point No. 40.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 68°00.5' W., on line 40-41, beginning new measurement.

7.167 Point selected for Angle Point No. 41.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

METES-AND-BOUNDS SURVEY IN
SECTIONS 3, 4, 8, 9, 17, 18, 19, AND 30,
TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

S. 89°19.5' W., on line 41-42, beginning new measurement.

3.306 Point selected for Angle Point No. 42.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 83°03.4' W., on line 42-43, beginning new measurement.

5.871 Point selected for Angle Point No. 43.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

N. 87°07.0' W., on line 43-44, beginning new measurement.

7.133 Point selected for Angle Point No. 44.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

N. 54°21.7' W., on line 44-45, beginning new measurement.

11.236 Point selected for Angle Point No. 45.

Set a steel spike, 3/8 inch diameter, 8 inches long, 9 inches below the road surface.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, in a collar of stone, 2 feet diameter, magnet at base, for a reference monument, bears S. 57°26.1' W., 94.7 links distance, with aluminum cap marked RM T17S R22E S8 2010, with an arrow pointing toward the corner with 62.5 FT. TO COR. marked along it.

An aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, for a reference monument, bears N. 17°57.6' W., 71.3 links distance, with aluminum cap marked RM T17S R22E S8 2010, with an arrow pointing toward the corner with 47.1 FT. TO COR. marked along it.

N. 71°28.0' W., on line 45-46, beginning new measurement.

4.048 Point selected for Angle Point No. 46.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

METES-AND-BOUNDS SURVEY IN
SECTIONS 3, 4, 8, 9, 17, 18, 19, AND 30,
TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

S. 67°23.4' W., on line 46-47, beginning new measurement.

4.004 Point selected for Angle Point No. 47.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 38°36.8' W., on line 47-48, beginning new measurement.

9.017 Point selected for Angle Point No. 48.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 59°11.4' W., on line 48-49, beginning new measurement.

7.643 Point selected for Angle Point No. 49.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 48°28.0' W., on line 49-50, beginning new measurement.

6.872 Point selected for Angle Point No. 50.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 14°59.1' W., on line 50-51, beginning new measurement.

5.337 The point for Angle Point No. 51, at intersection with the section line between sections 8 and 17.

Set a steel spike, 3/8 inch diameter, 8 inches long, 7 inches below the road surface.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, for a reference monument, bears N. 59°06.7' E., 71.2 links distance, with aluminum cap marked RM T17S R22E S8 2010, with an arrow pointing toward the corner with 47.0 FT. TO COR. marked along it.

An aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, for a reference monument, bears N. 40°35.6' W., 94.1 links distance, with aluminum cap marked RM T17S R22E S8 2010, with an arrow

METES-AND-BOUNDS SURVEY IN
 SECTIONS 3, 4, 8, 9, 17, 18, 19, AND 30,
 TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

pointing toward the corner with 62.1 FT. TO COR. marked
 along it.

S. $17^{\circ}14.9'$ W., on line 51-52, in section 17.

14.847 Point selected for Angle Point No. 52.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches
 below the road surface.

S. $47^{\circ}49.3'$ W., on line 52-53, beginning new measurement.

1.305 Point selected for Angle Point No. 53.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches
 below the road surface.

S. $66^{\circ}31.2'$ W., on line 53-54, beginning new measurement.

3.978 Point selected for Angle Point No. 54.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches
 below the road surface.

S. $24^{\circ}18.7'$ W., on line 54-55, beginning new measurement.

1.256 Point selected for Angle Point No. 55.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches
 below the road surface.

S. $25^{\circ}27.2'$ E., on line 55-56, beginning new measurement.

4.924 Point selected for Angle Point No. 56.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches
 below the road surface.

S. $0^{\circ}21.2'$ E., on line 56-57, beginning new measurement.

13.062 Point selected for Angle Point No. 57.

Set a steel spike, 3/8 inch diameter, 8 inches long, 9 inches
 below the road surface.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, 29
 inches in the ground, magnet at base, for a reference

METES-AND-BOUNDS SURVEY IN
 SECTIONS 3, 4, 8, 9, 17, 18, 19, AND 30,
 TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

monument, bears S. 66°30.6' E., 53.3 links distance, with aluminum cap marked RM T17S R22E S17 2010, with an arrow pointing toward the corner with 35.2 FT. TO COR. marked along it.

An aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, for a reference monument, bears S. 53°03.4' W., 64.0 links distance, with aluminum cap marked RM T17S R22E S17 2010, with an arrow pointing toward the corner with 42.2 FT. TO COR. marked along it.

S. 16°38.6' E., on line 57-58, beginning new measurement.

8.307 Point selected for Angle Point No. 58.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 7°31.4' W., on line 58-59, beginning new measurement.

6.194 Point selected for Angle Point No. 59.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 28°31.7' W., on line 59-60, beginning new measurement.

4.545 Point selected for Angle Point No. 60.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 23°09.4' W., on line 60-61, beginning new measurement.

8.001 Point selected for Angle Point No. 61.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 42°32.5' W., on line 61-62, beginning new measurement.

3.991 Point selected for Angle Point No. 62.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 70°47.9' W., on line 62-63, beginning new measurement.

METES-AND-BOUNDS SURVEY IN
 SECTIONS 3, 4, 8, 9, 17, 18, 19, AND 30,
 TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

4.642 Point selected for Angle Point No. 63.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 40°09.9' W., on line 63-64, beginning new measurement.

3.448 Point for Angle Point No. 64, at intersection with the section line between sections 17 and 18.

At the corner point

Set a steel spike, 3/8 inch diameter, 8 inches long, 8 inches below the road surface.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, for a reference monument, bears S. 79°23.2' E., 70.3 links distance, with aluminum cap marked RM T17S R22E S17 2010, with an arrow pointing toward the corner with 46.4 FT. TO COR. marked along it.

An aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, for a reference monument, bears N. 9°50.2' W., 54.0 links distance, with aluminum cap marked RM T17S R22E S18 2010, with an arrow pointing toward the corner with 35.7 FT. TO COR. marked along it.

S. 33°56.9' W., on line 64-65, in section 18.

5.257 Point selected for Angle Point No. 65.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 3°55.4' E., on line 65-66, beginning new measurement.

2.472 Point selected for Angle Point No. 66.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 27°13.7' W., on line 66-67, beginning new measurement.

3.854 Point selected for Angle Point No. 67.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

METES-AND-BOUNDS SURVEY IN
 SECTIONS 3, 4, 8, 9, 17, 18, 19, AND 30,
 TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

S. $46^{\circ}33.1'$ W., on line 67-68, beginning new measurement.

- 2.579 The point for Angle Point No. 68, at intersection with the section line between sections 18 and 19.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, to bedrock, in a mound of stone, 2 feet diameter, to cap, magnet at base, for a reference monument, bears N. $88^{\circ}21.6'$ E., 62.5 links distance, with aluminum cap marked RM T17S R22E S18 2010, with an arrow pointing toward the corner with 41.3 FT. TO COR. marked along it.

An aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, magnet at base, for a reference monument, bears N. $9^{\circ}06.0'$ W., 64.9 links distance, with aluminum cap marked RM T17S R22E S18 2010, with an arrow pointing toward the corner with 42.8 FT. TO COR. marked along it.

S. $21^{\circ}00.8'$ W., on line 68-69, in section 19.

- 2.480 Point selected for Angle Point No. 69.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. $1^{\circ}43.8'$ E., on line 69-70, beginning new measurement.

- 6.568 Point selected for Angle Point No. 70.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. $2^{\circ}34.4'$ W., on line 70-71, beginning new measurement.

- 12.521 Point selected for Angle Point No. 71.

Set a steel spike, 3/8 inch diameter, 8 inches long, 8 inches below the road surface.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, in a collar of stone, 2 feet

METES-AND-BOUNDS SURVEY IN
 SECTIONS 3, 4, 8, 9, 17, 18, 19, AND 30,
 TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

diameter, magnet at base, for a reference monument, bears S. $54^{\circ}33.9'$ E., 92.4 links distance, with aluminum cap marked RM T17S R22E S19 2010, with an arrow pointing toward the corner with 61.0 FT. TO COR. marked along it.

An aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, for a reference monument, bears S. $41^{\circ}13.9'$ W., 80.1 links distance, with aluminum cap marked RM T17S R22E S19 2010, with an arrow pointing toward the corner with 52.8 FT. TO COR. marked along it.

S. $6^{\circ}20.3'$ W., on line 71-72, beginning new measurement.

14.148 Point selected for Angle Point No. 72.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. $10^{\circ}54.2'$ E., on line 72-73, beginning new measurement.

7.483 Point selected for Angle Point No. 73.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. $4^{\circ}11.8'$ W., on line 73-74, beginning new measurement.

2.070 Point selected for Angle Point No. 74.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. $18^{\circ}14.8'$ W., on line 74-75, beginning new measurement.

8.545 Point selected for Angle Point No. 75.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. $31^{\circ}57.8'$ W., on line 75-76, beginning new measurement.

3.427 Point selected for Angle Point No. 76.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. $19^{\circ}20.2'$ W., on line 76-77, beginning new measurement.

4.793 Point selected for Angle Point No. 77.

METES-AND-BOUNDS SURVEY IN
 SECTIONS 3, 4, 8, 9, 17, 18, 19, AND 30,
 TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Set a steel spike, 3/8 inch diameter, 8 inches long, 10 inches below the road surface.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, for a reference monument, bears N. 80°26.9' E., 64.6 links distance, with aluminum cap marked RM T17S R22E S19 2010, with an arrow pointing toward the corner with 42.6 FT. TO COR. marked along it.

An aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, for a reference monument, bears N. 23°03.9' W., 49.2 links distance, with aluminum cap marked RM T17S R22E S19 2010, with an arrow pointing toward the corner with 32.4 FT. TO COR. marked along it.

S. 42°44.2' W., on line 77-78, beginning new measurement.

12.637 Point selected for Angle Point No. 78.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 67°31.5' W., on line 78-79, beginning new measurement.

5.324 Point selected for Angle Point No. 79.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 76°56.7' W., on line 79-80, beginning new measurement.

4.683 Point selected for Angle Point No. 80.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 54°04.2' W., on line 80-81, beginning new measurement.

11.479 The point for Angle Point No. 81, at intersection with the section line between sections 19 and 30.

Set a steel spike, 3/8 inch diameter, 8 inches long, 8 inches below the road surface.

From which

The 1/4 section corner of sections 19 and 30, also functions as a reference monument, bears N. 89°59.7' E., 82.8 links

METES-AND-BOUNDS SURVEY IN
SECTIONS 3, 4, 8, 9, 17, 18, 19, AND 30,
TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

distance, hereinbefore described.

An aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, for a reference monument, bears N. 11°23.4' W., 79.6 links distance, with aluminum cap marked RM T17S R22E S19 2010, with an arrow pointing toward the corner with 52.5 FT. TO COR. marked along it.

S. 55°12.3' W., on line 81-82, in section 30.

3.417 Point selected for Angle Point No. 82.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 69°43.0' W., on line 82-83, beginning new measurement.

5.550 Point selected for Angle Point No. 83.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 79°43.5' W., on line 83-84, beginning new measurement.

9.573 Point selected for Angle Point No. 84.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 66°38.6' W., on line 84-85, beginning new measurement.

3.518 Point selected for Angle Point No. 85.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 74°36.7' W., on line 85-86, beginning new measurement.

5.140 Point selected for Angle Point No. 86.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, in a collar of stone, 2 feet diameter, magnet at base, for a reference monument, bears S. 6°11.3' W., 78.4 links distance, with aluminum cap marked RM T17S R22E S30 2010, with an arrow pointing toward

METES-AND-BOUNDS SURVEY IN
 SECTIONS 3, 4, 8, 9, 17, 18, 19, AND 30,
 TOWNSHIP 17 SOUTH, RANGE 22 EAST, SALT LAKE MERIDIAN, UTAH.

CHAINS

the corner with 51.7 FT. TO COR. marked along it.

An aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, for a reference monument, bears N. 73°00.3' W., 49.3 links distance, with aluminum cap marked RM T17S R22E S30 2010, with an arrow pointing toward the corner with 32.5 FT. TO COR. marked along it.

S. 37°19.0' W., on line 86-87, beginning new measurement.

13.072 Point selected for Angle Point No. 87.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 7°24.0' W., on line 87-88, beginning new measurement.

3.229 Point selected for Angle Point No. 88.

Set a steel spike, 3/8 inch diameter, 8 inches long, 6 inches below the road surface.

S. 23°05.6' W., on line 88-89, beginning new measurement.

7.475 The point for Angle Point No. 89, at intersection with the section line between sections 25 and 30, on the west boundary of T. 17 S., R. 22 E.

Set a steel spike, 3/8 inch diameter, 8 inches long, 8 inches below the road surface.

From which

The 1/4 section corner of section 25 only, T. 17 S., R. 21 E., also functions as a reference monument, hereinbefore described, bears S. 0°03.6' E., 135.7 links distance.

An aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, for a reference monument, bears N. 81°51.8' W., 52.7 links distance, with aluminum cap marked RM T17S R21E S25 2010, with an arrow pointing toward the corner with 34.8 FT. TO COR. marked along it.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Phil Freiberg	Survey Technician

CERTIFICATE OF SURVEY

I, *Scott A. Burkhardt*, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing the date of *July 12, 2010*, I have dependently resurveyed a portion of the east boundary of *T. 17 S., R. 21 E.*, a portion of the south boundary of *T. 16 S., R. 22 E.*, and a portion of the subdivisional lines, and a metes-and-bounds survey in sections *3, 4, 8, 9, 17, 18, 19, and 30*, in *T. 17 S., R. 22 E., Salt Lake Meridian, Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions of the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

11/2/2011

Date

Scott A. Burkhardt

Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The following field notes of the *dependent resurvey of a portion of the east boundary of T. 17 S., R. 21 E., a portion of the south boundary of T. 16 S., R. 22 E., and a portion of the subdivisional lines, and a metes-and-bounds survey in sections 3, 4, 8, 9, 17, 18, 19, and 30, in T. 17 S., R. 22 E., Salt Lake Meridian, Utah, executed by Scott A. Burkhardt, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.*

December 21, 2011

Date

Daniel W. Webb

Chief Cadastral Surveyor for Utah