

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH, EAST, AND NORTH BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 2, 13, 24, 26, AND 35,

IN

TOWNSHIP 25 SOUTH, RANGE 11 WEST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Jeremy D. Davis
Cadastral Surveyor

Under Special Instructions dated and approved ***July 23, 2012***, which provided for the surveys included under Group Number ***1197***, and Assignment Instructions dated ***July 23, 2012***.

Survey Commenced, ***July 30, 2012***
Survey Completed, ***August 23, 2012***

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH, EAST, AND NORTH BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 2, 13, 24, 26, AND 35,

IN

TOWNSHIP 25 SOUTH, RANGE 11 WEST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Jeremy D. Davis
Cadastral Surveyor

Under Special Instructions dated and approved ***July 23, 2012***, which provided for the surveys included under Group Number ***1197***, and Assignment Instructions dated ***July 23, 2012***.

Survey Commenced, ***July 30, 2012***
Survey Completed, ***August 23, 2012***

TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of a portion of the south, east, and north boundaries, a portion of the subdivisional lines, and the subdivision of sections 2, 13, 24, 26, and 35, in T. 25 S., R. 11 W., Salt Lake Meridian, Utah.

HISTORY OF SURVEYS

Surveyed by		Retr. or Resurveyed by	
SOUTH BOUNDARY (FIFTH STANDARD PARALLEL SOUTH)			
All	A.J. Stewart Jr.	1875	
All		J.W. Dougall	1911
EAST BOUNDARY			
All	J. Bausman	1870	
Portion		L.V. Judd	2001
Portion		S.A. Burkhardt	2012
WEST BOUNDARY			
All	J. Gorlinski	1880	
All		A.J. Stewart Jr.	1882
All		C.P. Sylvester	1959
NORTH BOUNDARY			
Portion	J. Gorlinski	1880	
All	A.J. Stewart Jr.	1882	A.J. Stewart Jr. 1882
All		C.P. Sylvester	1959
SUBDIVISION			
Portion	J. Gorlinski	1880	

PRIVATE SURVEY

Millard County monumented certain corners within the township. There were no corner filing records found in the Millard County Records Office.

A survey was executed by Neil L. Rhodes R.L.S. 4100, Bulloch Brothers Engineering, with a plat dated March 8, 2002.

TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 1197, dated July 23, 2012.

The directions of the lines were determined by references to true meridians, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards for the positional Accuracy of Cadastral surveys when using Global Navigation Satellite Systems (GNSS)* dated, February 23, 2009. Trimble model 5800 GPS receivers were used for field collection. Cadastral Measurement Management (CMM) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from GPS static observations; post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS); MARYSVALE_UT2006 CORS, DELTAMUNI_UT2004 CORS, SPRING VALLEY CORS.

The geographic position of the corner of sections 1, 6, 31, and 36, Tps. 25 and 26 S., Rs. 10 and 11 W., is as follows:

Latitude: **38°35'14.280" N.**,
Longitude: **113°01'41.329" W.**, N.A.D. 83 (2011), EPOCH: 2010.00,
Network Accuracy = 0.200 meter at 95% confidence.

The geographic position of the corner of sections 2 and 3 only, is as follows:

Latitude: **38°40'28.517" N.**,
Longitude: **113°03'53.583" W.**, N.A.D. 83 (2011), EPOCH: 2010.00,
Network Accuracy = 0.200 meter at 95% confidence.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
(FIFTH STANDARD PARALLEL SOUTH),
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the South Boundary
(Fifth Standard Parallel South),
T. 25 South, Range 11 West, Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by A.J. Stewart in 1875
and Resurvey Executed by J.W. Dougall in 1911

Beginning at the standard corner of Tps. 25 and 26 S., Rs. 10 and 11 W., monumented with an iron post, 3 inches diameter, firmly set, in a 1 ft. concrete base, 3 inches above the ground, with brass cap marked as described in the official record of the 2011-2012 resurvey of the north boundary of T. 26 S., R. 10 W., executed by M.J. Kurchinski.

A steel fence post is 1 ft. west of the corner.

The corner is located on flat ground.

N. 89°24.3' W., between sections 1 and 36.

20.072 Point for the standard E 1/16 section corner of sections 1 and 36.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W
S36
E 1/16 ———
S1
2012

Set a steel fence post alongside and bury a magnet at the base of aluminum post.

The corner is located on flat ground surrounded by weeds.

40.144 Point for the standard 1/4 section corner of sections 1 and 36, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in ground, with aluminum cap marked

T25S R11W
S36
1/4 ———
S1
2012

Set a steel fence post alongside and bury a magnet at the base of

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
(FIFTH STANDARD PARALLEL SOUTH),
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

aluminum post.

The corner is located on flat ground surrounded by low sage and greasewood.

- 80.288** The standard corner of sections 1, 2, 35 and 36, monumented with an iron post, 3 inches diameter, firmly set, projecting 9 inches above the ground, with brass cap marked

SC
T25S R11W
S35 | S36

1911

Remark brass cap

SC
T25S R11W
S35 | S36
S2 | S1

T26S
2012
1911

The corner is located on flat ground, beneath the eastern power line extending north and south.

S. 89°49.7' W., between sections 2 and 35.

- 40.255** The standard 1/4 section corner of sections 2 and 35, monumented with an iron post, 1 inch diameter, firmly set, projecting 10 inches above a mound of stone, with brass cap marked as described in the official record of the 1911 resurvey.

Set a steel fence post alongside the corner.

The corner is located on flat open ground.

S. 89°51.7' W., beginning new measurement.

- 39.854** Point for the closing corner of sections 2 and 3, T. 26 S., R. 11 W., at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
(FIFTH STANDARD PARALLEL SOUTH),
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T25S	
S35	
C	C
S3	S2
T26S	R11W
2012	

Set a cedar post, 6 ft. long, 2 ft. in the ground alongside and bury a magnet at the base of aluminum post.

The corner is located on the top of barren land.

- 40.194** The standard corner of sections 34 and 35, monumented with an iron post, 3 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap marked as described in the official record of the 1911 resurvey.

A steel fence post is alongside the corner.

The corner is located on flat ground, at the corner of fences extending north, south, and west.

Dependent Resurvey of a Portion of the East Boundary,
T. 25 S., R. 11 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 13 and 18, on the east boundary of the township, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 3 inches above the ground, with aluminum cap marked as described in the official record of the 2012 resurvey of the west boundary of T. 25 S., R. 10 W.

A steel fence post is set alongside.

The corner is located on flat barren ground.

N. 0°03.0' E., between sections 13 and 18.

- 20.130** Point for the N 1/16 section corner of sections 13 and 18, not monumented.

- 40.260** The corner of sections 7, 12, 13, and 18, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 2 inches above a collar of stone, with aluminum cap marked as described in the official record of the 2012 resurvey of the west boundary of T. 25 S., R. 10 W.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the North Boundary,
T. 25 S., R. 11 W., Salt Lake Meridian, Utah

From the corner of sections 1, 2, 35, and 36, on the north boundary of the township, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 10 inches above the ground, with brass cap marked as described in the official record of the 1959 resurvey of the south boundary of T. 24 S., R. 11 W.

The marked stone, clearly marked, is set alongside the corner.

Set a steel fence post alongside the corner.

S. 89°06.5' W., along the north boundary of section 2.

- 40.153** The 1/4 section corner of section 35 only, T. 24 S., R. 11 W., monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 10 inches above the ground, with brass cap marked as described in the official record of the 1959 resurvey of the south boundary of T. 24 S., R. 11 W.

Set a steel fence post alongside the corner.

- 40.455** The 1/4 section corner of section 2 only, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap marked as described in the official record of the 1959 resurvey of the south boundary of T. 24 S., R. 11 W. The marked stone, clearly marked, is located alongside.

Set a steel fence post 1 foot north of the corner.

Corner falls on flat ground.

S. 89°03.1' W., beginning new measurement.

- 39.720** The corner of sections 34 and 35 only, T. 24 S., R. 11 W., monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 10 inches above the ground, with brass cap marked as described in the official record of the 1959 resurvey of the south boundary T. 24 S., R. 11 W.

Set a steel fence post 1 foot north of the corner.

- 40.340** The corner of sections 2 and 3 only, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 12 inches above the ground, with brass cap marked as described in the official record of the 1959 resurvey of the south boundary of T. 24 S., R. 11 W.

Set a steel fence post 1 foot north of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 11 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by J. Gorlinski in 1880

From the standard corner of sections 1, 2, 35, and 36, on the south boundary of the township, hereinbefore described.

N. 1°51.7' W., between sections 35 and 36.

40.562 The 1/4 corner of sections 35 and 36, monumented with a granite stone, 11x7x4 inches, firmly set, marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S	1/4	R11W
S35		S36
2012		

Deposit the marked stone alongside and bury a magnet at the base of aluminum post.

The corner is located on flat ground in the middle of power lines.

N. 1°16.9' E., beginning new measurement.

39.477 The corner of sections 25, 26, 35, and 36, monumented with a red granite stone, 13x10x9, firmly set, marked 1 notch on south and east edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked

T25S	R11W	
S26		S25
S35		S36
2012		

Deposit the marked stone alongside and bury a magnet at the base of aluminum post.

Set a steel fence post alongside the corner.

The corner is located on flat ground under the eastern power

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

line.

From the corner of sections 25, 30, 31, and 36, on the east boundary of the township, monumented with a Millard County survey monument, an aluminum drive rod, 1 inch diameter, firmly set, projecting 4 inches above the ground, with an aluminum cap 3 1/4 inches diameter attached marked, MILLARD COUNTY T25S R10W 25 30 36 31 R11W 2008 LS162522.

The remnants of an old wooden post and steel fence post are set to the north of the corner.

This position is accepted as a careful and faithful perpetuation of the original corner position.

The corner is located on flat ground surrounded by grease wood.

N. 89°36.3' W., between sections 25 and 36.

- 41.116** The 1/4 section corner of sections 25 and 36, monumented with a limestone, 11x7x5 inches, firmly set, below an anthill marked 1/4 on the north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked

T25S R11W
S25
1/4 —————
S36
2012

Deposit the marked stone and steel fence post alongside and bury a magnet at the base of aluminum post.

The corner is located on flat ground in an old ruined anthill.

From the corner, an unrecorded Millard County drive rod, 1 inch diameter, firmly set, projecting 4 inches above the ground, with an aluminum cap 3 1/4 inches diameter attached marked, MILLARD COUNTY T25S R11W 1/4 25 36 2008 LS162522, bears S. 83°41.5' E., 32.1 links distance.

N. 89°50.8' W., beginning new measurement.

- 39.964** The corner of sections 25, 26, 35, and 36.

N. 1°08.4' W., between sections 25 and 26.

- 41.317** The 1/4 section corner of sections 25 and 26, monumented with a

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

granite stone, 12x7x3 inches, firmly set, marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked

T25S	1/4	R11W
S26		S25
2012		

Deposit the marked stone alongside and bury a magnet at the base of aluminum post.

The corner is located on flat ground in the middle of power lines.

N. 0°22.9' W., beginning new measurement.

- 39.637** The corner of sections 23, 24, 25, and 26, monumented with a granite stone, 11x8x5 inches, firmly set, marked 2 notches on the south and 1 notch on the east edges. With a rebar, 1/2 inch rebar, with 1 1/2 inches diameter aluminum cap marked WESTWOOD 2011 T25SR11W S23 S24 S26 S25 LS6763499 alongside the corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S	R11W	
S23		S24
S26		S25
2012		

Deposit the marked stone, rebar and cap alongside, set a steel fence post, and bury a magnet at the base of aluminum post.

Raise a mound of stone, 2 ft. base, 1 ft. high, west of the corner.

Corner falls in flat ground.

From the corner of sections 19, 24, 25, and 30, on the east boundary of the township, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 3 inches above the ground, with aluminum cap marked as described in the official record of the 2012 resurvey of the west boundary of T. 25 S., R. 10 W.

A steel fence post is set 1 ft. north of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The corner is located on flat ground surrounded by low grease wood.

N. 89°55.7' W., between sections 24 and 25.

- 41.244** The 1/4 section corner of sections 24 and 25, monumented with a fragmented red sandstone, 11x5x5 inches, firmly set, marked 1/4 on north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked

T25S R11W
S24
1/4 —————
S25
2012

Deposit the marked stone, set a steel fence post alongside and bury a magnet at the base of aluminum post.

The corner is located on flat ground.

N. 89°24.8' W., beginning new measurement.

- 41.479** The corner of sections 23, 24, 25, and 26.

N. 0°41.7' W., between sections 23 and 24.

- 40.280** The 1/4 section corner of sections 23 and 24, monumented with a red granite stone, 11x7x5 inches, firmly set, marked 1/4 on the west face. With a 1 1/2 inches iron pipe, firmly set, projecting 25 1/2 inches above the ground.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W
1/4
S23 | S24
2012

Deposit the marked stone, set a steel fence post alongside and bury a magnet at the base of aluminum post.

The corner is located on flat open ground between two power lines.

From the corner, a rebar, 1/2 inch diameter, firmly set, projecting 2 inches above the ground, with an aluminum cap 3 1/4

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

inches diameter attached marked, LA DWP Survey Point No. L642
R803 LS3322 POWER SYSTEM, bears N. 80°04.3' W., 46.6 links
distant.

N. 0°41.0' W., beginning new measurement.

- 40.497** The corner of sections 13, 14, 23, and 24, monumented with an iron pipe, 2 inches diameter, firmly set, marked with 3 grooves on south, and 1 groove on east faces.

This position is accepted as a careful and faithful perpetuation of the original corner position.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 30 inches in the ground, with aluminum cap marked

T25S R11W	
S14	S13
S23	S24
2012	

Deposit the iron post inside aluminum post and bury a magnet at the base of aluminum post.

The corner is located among large sand drifts.

From the corner of section 13, 18, 19, and 24, on the east boundary of the township, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 4 inches above the ground, with aluminum cap marked as described in the official record of the 2001 resurvey, of the west boundary of T. 25 S., R. 10 W.

A steel fence post is set alongside.

The corner is located on flat ground surrounded by low greasewood.

N. 89°44.0' W., between sections 13 and 24.

- 42.124** Point for the 1/4 section corner of sections 13 and 24, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W	
S13	
1/4	
S24	
2012	

A steel fence post is set alongside.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

While reestablishing the corner, I find a rebar, 1/2 inch diameter, with an aluminum cap attached, with illegible marks. I bury the rebar and a magnet at the base of aluminum post.

The corner is located on flat sandy ground surrounded by dunes.

84.248 The corner of sections 13, 14, 23, and 24.

N. 0°14.3' W., between sections 13 and 14.

42.618 Point for the 1/4 section corner of sections 13 and 14, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W
1/4
S14 | S13
2012

Set a steel fence post alongside and bury a magnet at the base of aluminum post.

The corner is located on flat ground. A road bearing north south is 23 links east of the corner.

85.236 The corner of sections 11, 12, 13, and 14, monumented with a flint stone, 11x8x7 inches, firmly set, marked with 4 notches on south and 1 notch on east edges. A small mound of stone is to the west of the corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W
S11 | S12
S14 | S13
2012

Deposit the marked stone, set a steel fence post alongside and bury a magnet at the base of aluminum post.

The corner is located on flat ground with power lines to the west.

From the corner of sections 7, 12, 13, and 18, on the east boundary of the township, hereinbefore described.

N. 82°58.2' W., between sections 12 and 13.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 22.329** Point for the E 1/16 section corner of sections 12 and 13, not monumented.
- 44.658** The 1/4 corner of sections 12 and 13, monumented with a red flint stone, 10x7x7 inches, firmly set, marked 1/4 on north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked

T25S R11W
S12
1/4 —————
S13
2012

Deposit the marked stone, set a steel fence post alongside and bury a magnet at the base of aluminum post.

The corner is located on flat barren land.

S. 89°29.6' W., beginning new measurement.

- 40.331** The corner of sections 11, 12, 13, and 14.

N. 2°56.3' E., between sections 11 and 12.

- 37.962** Point for the 1/4 section corner of sections 11 and 12, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W
1/4
S11 | S12
2012

Set a steel fence post alongside and bury a magnet at the base of aluminum post.

The corner is located on flat barren land.

- 75.924** The corner of sections 1, 2, 11, and 12, monumented with a Bulloch Brothers survey monument, an aluminum pipe, 2 1/2 inches diameter, firmly set, projecting 8 inches above the ground, with aluminum cap marked, T25S R11W S1 S2 S11 S12 2002 LS 4100 BB.

This position is accepted as a careful and faithful perpetuation of the original corner position.

The corner is located on flat barren ground.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 1, 6, 7, and 12, on the east boundary of the township, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above the ground, with aluminum cap marked as described in the official record of the 2001 resurvey of the west boundary of T. 25 S., R. 10 W.

A steel fence post is set alongside the corner.

The corner is located on flat ground. A fence extending east and west is 56 links north of the corner.

N. 89°42.6' W., between sections 1 and 12.

- 40.409** Point for the 1/4 section corner of sections 1 and 12, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W
S1
1/4 ———
S12
2012

Set a steel fence post alongside and bury a magnet at the base of aluminum post.

The corner is located on flat ground surrounded in low greasewood.

- 80.818** The corner of sections 1, 2, 11, and 12.

N. 0°41.9' E., between sections 1 and 2.

- 40.278** Point for the 1/4 section corner of sections 1 and 2, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum posts, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W
1/4
S2 | S1
2012

Set a steel fence post alongside and bury a magnet at the base of aluminum post.

- 79.469** The corner of sections 1, 2, 35 and 36, on the north boundary of the township, hereinbefore described.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS


From the corner of sections 2, 3, 34, and 35, on the south boundary of the township, hereinbefore described.

N. 0°29.1' W., between sections 34 and 35.

42.351 The 1/4 corner of sections 34 and 35, monumented with a red flint stone, 12x8x7 inches, firmly set, marked 1/4 on west face in a small mound of stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked



Deposit the marked stone alongside, set a steel fence post, and bury a magnet at the base of aluminum post.

The corner is located in a fence line extending north and south on flat ground.

From the corner, a 1/2 inch rebar, firmly set, projecting 3 inches above the ground, with a 2 inch aluminum cap marked WESTWOOD 2011 1/4 S34 S35 LS6763499 bears S. 1°38.6' W., 2.166 chains distance.


N. 0°29.8' W., beginning new measurement.

38.019 The corner of sections 26, 27, 34, and 35, monumented with a flint stone, 15x10x8, firmly set, in a mound of stone, 3 ft. base, marked 1 notch on south and 2 notches on east edges.

A rebar, 1/2 inch diameter, with an aluminum cap 2 inches diameter attached marked, WESTWOOD 2011 T25SR11W S27 S26 S35 S36 LS6763499, is set alongside the corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked



Deposit the marked stone, rebar and cap alongside and bury a magnet at the base of aluminum post.

The corner is located on flat ground, in a fence line extending north and south.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 25, 26, 35, and 36.

S. 85°35.6' W., between sections 26 and 35.

- 42.636 The 1/4 section corner of sections 26 and 35, monumented with a granite stone, 13x8x5, firmly set, marked 1/4 on the north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked

T25S R11W
S26
1/4 —————
S35
2012

Deposit the marked stone alongside and bury a magnet at the base of aluminum post.

The corner is located on flat ground.

N. 84°53.0' W., beginning new measurement.

- 38.329 The corner of sections 26, 27, 34, and 35.

N. 0°02.7' W., between sections 26 and 27.

- 44.758 The 1/4 section corner of sections 26 and 27, monumented with a flint stone, 9x8x7 inches, firmly set, marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S 1/4 R11W
S27 | S26
2012

Deposit the marked stone alongside, set a steel fence post, and bury a magnet at the base of aluminum post.

The corner is located on flat ground. A fence line extending north and south is 39.4 links west of the corner.

From the corner, an unrecorded Millard County survey monument, an aluminum drive rod, 1 inch diameter, firmly set, projecting 8 inches above the ground, with an aluminum cap, 3 inches diameter, attached marked Millard County 1/4 26 27 2008 LS 162522, bears

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

S. 4°04.7' W., 4.972 chains distance, and is located in a fence line extending north and south.

N. 0°08.7' E., beginning new measurement.

- 34.828** The corner of sections 22, 23, 26, and 27, monumented with a flint stone, 12x8x4 inches, firmly set, marked 2 notches on south and east edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W	
S22	S23
S27	S26
2012	

Deposit the marked stone alongside, set a steel fence post, and bury a magnet at the base of aluminum post.

The corner is located on flat ground. A fence line extending north and south is 83.3 links west of the corner.

From the corner, an unrecorded Millard County survey monument, an aluminum drive rod, 1 inch diameter, firmly set, projecting 6 inches above the ground, with an aluminum cap, 3 inches diameter, attached marked Millard County 22 23 26 27 2008 LS 162522, bears N. 89°23.3' W., 0.832 chains distance.

From the corner of sections 23, 24, 25, and 26.

S. 89°08.6' W., between sections 23 and 26.

- 40.185** The 1/4 section corner of sections 23 and 26, monumented with an unrecorded Millard County survey monument, an aluminum drive rod, 1 inch diameter, firmly set, projecting 4 inches above the ground, with an aluminum cap 3 1/4 inches diameter attached marked, MILLARD COUNTY T25SR11W 23 1/4 26 2008 LS102522.

A granite stone, 12x6x7 inches is set alongside the drive rod, marked 1/4 on the north face.

Set a steel fence post and bury the marked stone alongside the drive rod.

This position is accepted as a careful and faithful perpetuation of the original corner position.

The corner is located on flat ground.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

S. 89°06.1' W., beginning new measurement.

39.355 The corner of sections 22, 23, 26, and 27.

N. 1°45.8' W., between sections 22 and 23.

39.828 The 1/4 section corner of sections 22 and 23, monumented with a flint stone 13x7x4, firmly set, marked 1/4 on the west face.

An iron pipe, 2 inches diameter, firmly set alongside the corner, projecting 2 ft. above the ground, marked 1/4 on the east side of the post.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S	S22		S23	R11W
		1/4		
		20		

Deposit the marked stone, iron pipe alongside, set a steel fence post, and bury a magnet at the base of aluminum post.

The corner is located on flat ground in a fence line extending north and south.

N. 0°34.6' W., beginning new measurement.

40.198 The corner of sections 14, 15, 22, and 23, monumented with an iron pipe, 2 inches diameter, firmly set, projecting 2 ft. above the ground, marked 3 grooves on south and 2 grooves on east sides.

The marked stone was found at corner of fences extending south, east, and west, which is a granite stone, 10x8x4, firmly set, marked 3 notches on south and 2 notches on east edges. It was determined that the marked stone was moved, due to other corners in the area having an iron pipe set alongside.

At the corner point (2 inch iron pipe)

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S	R11W	
S15		S14
S22		S23
2012		

Deposit the marked stone, iron pipe alongside, set a steel fence

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

post, and bury a magnet at the base of aluminum post.

Corner is located in a fence extending north and south.

From the corner of sections 13, 14, 23, and 24.

S. 88°34.9' W., between sections 14 and 23.

- 40.099** Point for the 1/4 section corner of sections 14 and 23, at proportionate distance, there is no remaining evidence of the original corner. I find a rebar, 1/2 inch diameter, with a 1 inch diameter aluminum cap, set below the ground on point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W
S14
1/4 ———
S23
2012

Deposit the rebar alongside and bury a magnet at the base of aluminum post.

- 80.198** The corner of sections 14, 15, 22, and 23.
-

N. 0°38.0' W., between sections 14 and 15.

- 39.814** The 1/4 section corner of sections 14 and 15, monumented with a flint stone, 14x10x4, firmly set, marked 1/4 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W
1/4
S15 | S14
2012

Deposit the marked stone alongside, set a steel fence post, and bury a magnet at the base of aluminum post.

The corner is located on flat ground.

N. 0°18.7' W., beginning new measurement.

- 40.200** Point for the corner of sections 10, 11, 14, and 15, at proportionate distance, there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W
S10 | S11
S15 | S14
2012

Bury a magnet at the base of aluminum post.

The corner is located on flat ground surrounded by low sage.

From the corner of sections 11, 12, 13, and 14.

S. 84°52.8' W., between sections 11 and 14.

- 40.392** Point for the 1/4 section corner of sections 11 and 14, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W
S11
1/4 ———
S14
2012

Bury a magnet at the base of aluminum post.

The corner is located on flat ground.

- 80.784** The corner of sections 10, 11, 14, and 15.
-

N. 2°41.6' W., between sections 10 and 11.

- 40.244** The 1/4 section corner of sections 10 and 11, monumented with a flint stone, 14x10x4 inches, firmly set, marked 1/4 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W
1/4
S10 | S11
2012

Bury a magnet at the base of aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The corner is located on flat ground.

N. 7°50.9' E., beginning new measurement.

- 41.830** The corner of sections 2, 3, 10, and 11, monumented with a quartz stone, 12x8x4, firmly set, marked 5 notches on south and 2 notches on east edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W	
S3	S2
S10	S11
2012	

Deposit the marked stone, set a steel fence post alongside and bury a magnet at the base of aluminum post.

The corner is located on flat ground.

From the corner of sections 1, 2, 11, and 12.

S. 89°00.5' W., between sections 2 and 11.

- 40.265** Point for the 1/4 section corner of sections 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W	
S2	
1/4	—————
S11	
2012	

Set a steel fence post, and bury a magnet at the base of aluminum post.

The corner is located on flat ground.

- 80.530** The corner of sections 2, 3, 10, and 11.

N. 2°45.8' W., between sections 2 and 3.

- 44.491** The 1/4 section corner of sections 2 and 3, monumented with a lime stone, 16x8x7, firmly set, marked 1/4 on west face.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W
1/4
S3 | S2
2012

Deposit the marked stone alongside, set a steel fence post, and bury a magnet at the base of aluminum post.

The corner is located on flat ground surrounded by scattered low sage.

N. 4°36.3' E., beginning new measurement.

- 35.234 The corner of sections 2 and 3 only, on the north boundary of the township, hereinbefore described.

From the corner of sections 10, 11, 14, and 15.

N. 81°52.7' W., between sections 10 and 15.

- 40.801 The 1/4 section corner of sections 10 and 15, monumented with a red flint stone, 13x9x5 inches, firmly set, marked 1/4 on north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W
S10
1/4 ———
S15
2012

Deposit the marked stone alongside, set a steel fence post, and bury a magnet at the base of aluminum post.

The corner is located on open flat ground.

S. 89°26.3' W., beginning new measurement.

- 41.581 The corner of sections 9, 10, 15, and 16, monumented with a quartzite stone, 8x8x4 inches, firmly set, marked 4 notches on south and 3 notches on east edges.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25SR11W
S9|S10
S16|S15
2014

Deposit the marked stone, set a steel fence post alongside, and buried a magnet at the base of the aluminum post.

Corner falls on flat ground in grass.

N. 0°42.0' W., between sections 9 and 10.

- 40.124** The 1/4 section corner of sections 9 and 10, monumented with a rebar, 5/8 inch diameter, firmly set, projecting 4 inches above the ground, with yellow cap attached marked PLS 5152671.

This is accepted as a careful and faithful reestablishment of the original corner position.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25SR11W
1/4
S9|S10
2014

Set a steel fence post alongside, buried the rebar and cap along with a magnet at the base of the aluminum post.

Corner falls 2 ft. southwest of a 4 inch diameter wood post, on flat ground in grass.

N. 0°42.0' W., beginning new measurement.

- 40.157** The corner of sections 3, 4, 9, and 10, monumented with a quartzite stone, 8x8x6 inches, firmly set, marked 5 notches on south and 3 notches on east edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25SR11W
S4|S3
S9|S10
2014

Deposit the marked stone alongside, set a steel fence post 1.5

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

ft. north, and buried a magnet at the base of the aluminum post.
Corner falls on flat ground in grass.

From the corner of sections 2, 3, 10, and 11.

N. 84°33.8' W., between sections 3 and 10.

- 46.848** The 1/4 section corner of sections 3 and 10, monumented with a quartzite stone, 12x8x5 inches, firmly set, marked 1/4 on north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25SR11W
S3
1/4 ———
S10
2014

Deposit the marked stone alongside, set a steel fence post 1 ft. north, and buried a magnet at the base of the aluminum post.

Corner falls on flat ground in grass.

S. 89°21.8' W., beginning new measurement.

- 40.120** The corner of sections 3, 4, 9, and 10.
-

The Subdivision of Section 2,
T. 25 S., R. 11 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 2 and 11.

N. 0°33.2' E., on the N-S centerline of section 2.

- 42.319** Point for the center 1/4 section corner, at intersection with the E-W centerline of section 2.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top of aluminum cap marked

T25SR11W
C 1/4
S2
2012

THE SUBDIVISION OF SECTION 2,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside and buried a magnet at the base of the aluminum post.

Corner falls on a gradual west slope.

From this corner point, a rebar, 5/8 inch diameter, firmly set, projecting 6 inches above the ground, with yellow cap attached, with illegible marks, bears S. 0°26.1' W., 2.054 chains distance. A steel fence post is located alongside. Corner falls on top of small rocky knoll.

From this corner point, a rebar, 5/8 inch diameter, firmly set, projecting 6 inches above the ground, with an aluminum cap, 1 1/2 inches diameter attached marked LAPS L64D E 264P RLS 3322, bears S. 3°33.8' W., 1.585 chains distance. Corner falls on top of small rocky knoll.

- 79.535** The 1/4 section corner of section 2 only, on the north boundary of the township, hereinbefore described.

From the 1/4 section corner of sections 1 and 2.

N. 88°05.5' W., on the E-W centerline of section 2.

- 40.359** The center 1/4 section corner of section 2.

- 83.191** The 1/4 section corner of sections 2 and 3.

The Subdivision of Section 13,
T. 25 S., R. 11 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 13 and 24.

N. 1°25.7' W., on the N-S centerline of section 13.

- 41.482** Point for the center 1/4 section corner, at intersection with the E-W centerline of section 13.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W
C1/4
S13
2012

Set a steel fence post alongside and bury a magnet at the base of aluminum post.

The corner is located on flat barren ground.

- 63.648** Point for the center N 1/16 section corner of section 13.

THE SUBDIVISION OF SECTION 13,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W
C
N1/16 | S13
C
20

Set a steel fence post alongside and bury a magnet at the base of aluminum post.

The corner is located on flat barren ground.

85.814 The 1/4 section corner of sections 12 and 13.

From the 1/4 section corner of sections 13 and 18, on the east boundary of the township, hereinbefore described.

N. 88°08.0' W., on the E-W centerline of section 13.

21.605 Point for the center E 1/16 section corner of section 13.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W
E 1/16
C ——— C
S13
2012

Set a steel fence post alongside and bury a magnet at the base of aluminum post.

The corner is located on flat ground, surrounded by tall greasewood.

43.210 The center 1/4 section corner of section 13.

84.494 The 1/4 section corner of sections 13 and 14.

From the center E 1/16 section corner of section 13.

N. 0°43.5' W., on the N-S centerline of the NE 1/4 of section 13.

21.146 Point for the NE 1/16 section corner, at intersection with the E-W centerline of the NE 1/4 of section 13.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

THE SUBDIVISION OF SECTION 13,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T25S R11W
NE 1/16
S13
2012

Set a steel fence post alongside and bury a magnet at the base of aluminum post.

The corner is located on flat ground, surrounded by low sage and greasewood.

- 42.292** The point for the E 1/16 section corner of sections 12 and 13.

From the point for the N 1/16 section corner of sections 13 and 18, on the east boundary of the township, hereinbefore described.

N. 85°30.5' W., on the E-W centerline of the NE 1/4 of section 13.

- 21.945** The NE 1/16 section corner of section 13.

- 43.890** The center N 1/16 section corner of section 13.

The Subdivision of Section 24,
T. 25 S., R. 11 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 24 and 25.

N. 0°13.4' W., on the N-S centerline of section 24.

- 40.539** Point for the center 1/4 section, at intersection with the E-W centerline of section 24.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W
C1/4
S24
2012

Set a steel fence post alongside and bury a magnet at the base of aluminum post.

The corner is located on flat ground.

- 81.001** The 1/4 section corner of sections 13 and 24.

From the 1/4 section corner of sections 19 and 24, on the east boundary of the township, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 3 inches above the ground, marked as described in the official record of the 2012

THE SUBDIVISION OF SECTION 24,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

resurvey of the west boundary of T. 25 S., R. 10 W.

N. 89°46.5' W., on the E-W centerline of section 24.

41.684 The center 1/4 section corner of section 24.

83.488 The 1/4 section corner of sections 23 and 24.

The Subdivision of Section 26,
T. 25 S., R. 11 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 26 and 35.

N. 0°50.7' E., on the N-S centerline of section 26.

46.432 Point for the center 1/4 section corner, at intersection with the E-W centerline of section 26.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W
C1/4
S26
2012

Set a steel fence post alongside and bury a magnet at the base of aluminum post.

The corner is located on flat ground surrounded by weeds.

83.629 The 1/4 section corner of sections 23 and 26.

From the 1/4 section corner of sections 25 and 26.

N. 87°25.6' W., on the E-W centerline of section 26.

41.039 The center 1/4 section corner of section 26.

79.971 The 1/4 section corner of sections 26 and 27.

The Subdivision of Section 35,
T. 25 S., R. 11 W., Salt Lake Meridian, Utah

From the 1/4 section corner of section 2 and 35, on the south boundary of the township, hereinbefore described.

N. 2°00.6' W., on the N-S centerline of section 35.

41.495 Point for the center 1/4 section corner, at intersection with the

THE SUBDIVISION OF SECTION 35,
TOWNSHIP 25 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

E-W centerline of section 35.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked

T25S R11W
C1/4
S35
2012

Set a steel fence post alongside and bury a magnet at the base of aluminum post.

The corner is located on flat ground, surrounded by low sage and grass.

76.899 The 1/4 section corner of section 26 and 35.

From the 1/4 section corner of sections 35 and 36.

N. 88°51.2' W., on the E-W centerline of section 35.

40.397 The center 1/4 section corner of section 35.

79.498 The 1/4 section corner of sections 34 and 35.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Jacob Murdoch	Survey Technician, SCEP
Luke Stoddard	Survey Technician

CERTIFICATE OF SURVEY

I, *Jeremy D. Davis*, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing the date of the *July 23, 2012*, I have *dependently resurveyed a portion of the south, east, and north boundaries, a portion of the subdivisional lines, and subdivided sections 2, 13, 24, 26, and 35, in Township 25 South, Range 11 West, of the Salt Lake Meridian, in the State of Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 17, 2014

Date


Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the south, east, and north boundaries, a portion of the subdivisional lines, and the subdivision of sections 2, 13, 24, 26, and 35 in Township 25 South, Range 11 West, Salt Lake Meridian, Utah*, executed by *Jeremy D. Davis, Cadastral Surveyor*, having been critically examined and found correct, are hereby approved.

September 26, 2014

Date



Chief Cadastral Surveyor for Utah