

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE WEST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 7, 8, AND 19,

IN

TOWNSHIP 22 SOUTH, RANGE 4 WEST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Christopher J. May, Survey Technician
Under the Supervision of
Ronald K. Batty, Cadastral Surveyor

Under Special Instructions dated **May 05, 2014**, approved **May 05, 2014**, which provided for the surveys included under Group Number **1204**, and assignment instructions dated **May 05, 2014**.

Survey Commenced, **May 05, 2014**
Survey Completed, **July 18, 2014**

INDEX DIAGRAM

TOWNSHIP 22 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

6	5	4	3	2	1
7 10	8 4	9	10	11	12
9	9				
4 18 8	17	16	15	14	13
7					
3 19 6	20	21	22	23	24
5					
30	29	28	27	26	25
31	32	33	34	35	36

The Subdivision of Section 7.....11
 The Subdivision of Section 8.....13
 The Subdivision of Section 19.....14

TOWNSHIP 22 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of a portion of the west boundary, a portion of the subdivisional lines, and the subdivision of sections 7, 8, and 19, in T. 22 S., R. 4 W., Salt Lake Meridian, Utah.

HISTORY OF SURVEYS

		Surveyed by	Retr. or Resurveyed by	
SOUTH BOUNDARY				
All	H.D. Page & G.C. Swan	1898		
Portion			S.P. Stewart & E.N. Thompson	1915
Portion			A. Nelson	1916
EAST BOUNDARY				
Portion	A.J. Stewart Jr.	1874		
All	J.T. Breckon	1896	H.D. Page & G.C. Swan	1898
Portion			A. Nelson	1916
WEST BOUNDARY				
All	A. Jessen	1879		
Portion			H.D. Page & G.C. Swan	1898
Portion			F.R. Chappell	1969
NORTH BOUNDARY				
Portion	A.J. Stewart Jr.	1874		
Portion	A. Jessen	1879		
Portion	S.M. Richardson	1884	S.M. Richardson	1884
Portion			H.D. Page & G.C. Swan	1898
SUBDIVISION				
Portion	A. Jessen	1879		
Portion	H.D. Page & G.C. Swan	1989	H.D. Page & G.C. Swan	1898
Remonumentation of corners			F.D. Reynolds	1969

PRIVATE SURVEYS

Millard County Recorders Office has reestablished and/or perpetuated corners established by the General Land Office in this township.

REPORT

Overview/Field Report of Findings Involving GP. No. 1204 Township 22 South, Range 4 West, Salt Lake Meridian, Utah. Bureau of Land Management, Utah State Office, September 30, 2014, AND UPDATED January 15, 2016.
Written by: Keith Batty and Christopher J. May.

TOWNSHIP 22 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 1204, dated May 05, 2014.

The direction of each line is with reference to the true meridian, determined by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards for the Positional Accuracy of Cadastral Surveys when using Global Navigation Satellite Systems (GNSS)*, dated February 23, 2009. Trimble model 5700 and Trimble model R8 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from GPS static observations, post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS); PUC1 CARBON COUNTY COU CORS, NVSV SPRING VALLEY CORS, and P086 KENNECOTT1UT2005 CORS.

The geographic position of the corner of sections 24 and 25 on the west boundary of the Township as determined by direct RTK methods from the geodetic control, is as follows:

Latitude: **38°52'34.690" N.**,
Longitude: **112°21'20.914" W.**, N.A.D. 83 (2011), EPOCH: 2010.00,
Network Accuracy = 0.200 meter at 95% confidence

The geographic position of the corner of sections 4, 5, 8 and 9, as determined by direct RTK methods from the geodetic control, is as follows:

Latitude: **38°55'11.724" N.**,
Longitude: **112°19'05.384" W.**, N.A.D. 83 (2011), EPOCH: 2010.00,
Network Accuracy = 0.200 meter at 95% confidence

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
TOWNSHIP 22 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the West Boundary,
Township 22 South, Range 4 West, Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by A. Jessen in 1879, the
Resurvey Executed by H.D. Page & G.C. Swan in 1898, and the
Resurvey Executed by F.R. Chappell in 1969

Beginning at the corner of sections 24 and 25 only of Township
22 South, Range 5 West, monumented with an iron post, 2 1/2
inches diameter, firmly set, projecting 4 inches above a mound
of stone, 3 1/2 feet base, 12 inches high, with brass cap marked
as described in the official record of the 1969 resurvey.

There is no remaining evidence of the bearing trees.

Rehabilitate mound of stone, 3 1/2 feet base, and 14 inches
high.

N. 0°02.8' E., along the west boundary of the township.

0.474 Point for the closing corner of sections 19 and 30, hereinafter
described.

40.582 The 1/4 section corner of section 24 only, monumented with an
iron post, 2 1/2 inches diameter, firmly set, projecting 5
inches above the ground, with brass cap marked as described in
the official record of the 1969 resurvey; with mound of stone, 3
1/2 feet base, 33 inches high, west of corner.

North, beginning a new measurement.

0.513 Point for the 1/4 section corner of section 19 only, at
proportionate distance.

Set aluminum post, 30 inches long, 2 1/2 inches diameter, 25
inches in the ground, in a mound of stone, 2 1/2 feet base, 5
inches high, with magnet at base and aluminum cap marked

T22S
R5W R4W
1/4
| S19
2014

Corner is located near the top of a northwest facing slope.

40.605 The corner of sections 13, 18, 19, and 24, monumented with an
iron post, 2 1/2 inches diameter, firmly set, projecting 6
inches above the ground, with brass cap marked as described in
the official record of the 1969 resurvey; with a mound of stone,
3 1/2 feet base, 1 1/2 feet high, west of corner.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
TOWNSHIP 22 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located on a west facing slope.

N. 0°06.7' W., along the west boundary of the township.

- 40.591 The 1/4 section corner of sections 13 and 18, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 8 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey; with a scattered mound of stone, north of corner.

Rebuild scattered mound of stone, 3 feet base, 12 inches high, north of corner.

N. 0°05.9' W., beginning a new measurement.

- 40.655 The corner of sections 7, 12, 13, and 18, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 10 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey; with a mound of stone, 2 feet base, 6 inches high, west of corner.

Corner falls in a fence line, extending east and west.

Dependent Resurvey of a Portion of the Subdivisional lines,
Township 22 South, Range 4 West, Salt Lake Meridian, Utah

Reestablishment of the Survey Executed in 1879 by A. Jessen, the
Survey Executed in 1898 by H.D. Page & G.C. Swan, and the
Resurvey Executed in 1898 by H.D. Page & G.C. Swan

From the corner of sections 8 and 9 only, monumented with a sandstone, 27X14X5 inches, loosely set, dimly marked. This stone is harmoniously related to the topographic calls made during the execution of the 1879 survey as well as the 1898 resurvey and is accepted as best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a mound of stone, 2 1/2 feet base, 6 inches high, magnet at base, with aluminum cap marked

T22S R4W
S8 | S9

2014

Deposit dimly marked stone alongside.

DEPENDENT RESURVEY OF A PORTION OF SUBDIVISIONAL LINES,
TOWNSHIP 22 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Top of ridge, extending northwesterly, bears East, 5.10 chains distance.

Corner is located in a fence line, extending east and west.

N. 0°15.2' E., between sections 8 and 9.

32.300 Deep gulch drains westerly.

39.788 Point for the 1/4 section corner of sections 8 and 9, at proportionate distance. There is no evidence remaining of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 4 inches in the ground to limestone ledge rock, in a mound of stone, 5 feet base, 26 inches high, with magnet at base with aluminum cap marked

T22S R4W
1/4
S8 | S9
2014

Corner is located on a rocky westerly slope.

48.900 Foot of lone mountain, bears irregularly easterly and westerly.

79.576 The corner of sections 4, 5, 8, and 9, monumented with a brass tablet, firmly set, in a 6X6 inches concrete block, projecting 2 inches above the ground with brass cap marked T22S R4W S4 S5 S8 S9 1981 GENERAL LAND OFFICE REESTABLISHED BY MILLARD COUNTY SURVEY MARKER, and is accepted as a careful and faithful reestablishment of the original corner position.

Corner is located in a fence corner, extending east, west, and north.

From the corner of sections 19, 20, 29, and 30, monumented with a sandstone, 14X11X8 inches, (Record: 24X12X4 inches), loosely set, dimly marked, with an embedded mound of stone to the west.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T22S R4W
S19 | S20
S30 | S29
2014

Set a steel fence post alongside.

Raise mound of stone, 3 feet base, 12 inches high, west of corner.

DEPENDENT RESURVEY OF A PORTION OF SUBDIVISIONAL LINES,
TOWNSHIP 22 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH
CHAINS

S. 89°52.7' W., between sections 19 and 30.

- 40.056** Point for the 1/4 section corner of sections 19 and 30, at proportionate distance. There is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 19 inches in the ground, in a mound of stone, 3 feet base, and 11 inches high, magnet at base, with aluminum cap marked

T22S R4W
S19
1/4 —————
S30
2014

Set a cedar post alongside.

Corner falls in dense oak brush growth on the east side of the bottom of a wash, drains northwest.

- 86.972** The closing corner of sections 19 and 30, established in the survey of 1898, at record bearing and distance from the original bearing trees on the western edge of an embedded mound of stone, 3 1/2 feet base.

A dead cedar stump, 12 inches diameter, no visible marks, bears N. 60° E., 32 links distance.

A cedar branch, 12 inches diameter, no visible marks, S. 10° E., 70 links distance.

A sandstone, 23X16X5 inches (Record: 24X16X6 inches), clearly marked 2 notches on south edge, 4 notches on north edge, marked CC and 6 grooves on east face, was found at the base of the mound of stone at the corner of sections 24 and 25 only, clearly disturbed.

Chisel AM on marked stone and bury it 6 inches below the ground at the original point.

- 86.998** Point for the corner of sections 19 and 30 only, on the west boundary of the township.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a mound of stone, 2 1/2 inches base, 6 inches high, magnet at base, with aluminum cap marked

T22S
R5W R4W
S24 | C S19
 | C S30
2014

DEPENDENT RESURVEY OF A PORTION OF SUBDIVISIONAL LINES,
TOWNSHIP 22 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 19, 20, 29, and 30.

N. 0°13.3' W., between sections 19 and 20.

- 39.780** Point for the 1/4 section corner of sections 19 and 20, at proportionate distance. Monumented with a fragmented sandstone, 14X12X5 inches (Record: 30X9X5 inches), clearly marked 1/4, lying loose and face down, and clearly disturbed by the creation of an earthen berm. There is no remaining evidence of the record mound of stone or remaining fragments of the marked stone.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T22S R4W
1/4
S19 | S20
2014

Deposit fragmented marked stone alongside.

Raise mound of stone, 3 feet base, 2 feet high, north of corner.

- 79.560** The closing corner of sections 19 and 20, monumented with an embedded mound of stone, 3 1/2 feet base. Accepted the center of embedded mound of stone as best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, in a mound of stone, 3 1/2 inches base, 10 inches high, magnet at base, with aluminum cap marked

T22S R4W
S 17
S19 | S20
C C
2014

From the southeast corner of section 18 only, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 8 inches above a mound of stone, 5 feet base, 12 inches high, with brass cap marked as described in the official record in the 1969 remonumentation; with a steel fence post 2 feet SE of corner.

Corner is located on the top of a spur, projecting northeast.

N. 89°11.2' W., between sections 18 and 19.

- 32.652** Point for the 1/4 section corner of section 19 only, at proportionate distance.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 16

DEPENDENT RESURVEY OF A PORTION OF SUBDIVISIONAL LINES,
TOWNSHIP 22 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

inches in the ground, in a mound of stone, 4 feet base, 14 inches high, magnet at base, with aluminum cap marked

T22S R4W
1/4
S19
2014

- 39.554** Point for the 1/4 section corner of section 18 only, at proportionate distance.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 23 inches in the ground, in a mound of stone, 2 1/2 feet base, 7 inches high, magnet at base, with aluminum cap marked

T22S R4W
S18
1/4
2014

- 79.108** The corner of sections 13, 18, 19, and 24 on the west boundary of the township, hereinbefore described.

From the SE corner of section 18.

N. 1°38.7' E., between sections 17 and 18.

- 0.489** The closing corner of sections 17 and 19 only, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 4 inches above a mound of stone, 3 1/2 feet base, 1 1/2 feet high, bears West, 0.044 chains distance, with brass cap marked as described in the official record of the 1969 remonumentation.

From which

A cedar, 20 inches diameter, bears N. 53° W., 8 links distance, marked CC 18 on an open blaze and a United States Forest Service bearing tree tag.

A cedar, 15 inches diameter, bears N. 12° E., 47 links distance, marked with a healed blaze and a United States Forest Service bearing tree tag.

- 42.101** Point for the 1/4 section corner of section 18 only, at proportionate distance. There is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground, in a mound of stone, 3 feet base, 12 inches high, magnet at base, with aluminum cap marked

DEPENDENT RESURVEY OF A PORTION OF SUBDIVISIONAL LINES,
TOWNSHIP 22 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T22S R4W
1/4
S18 |
2014

- 84.202** The corner of sections 7, 8, 17, and 18, monumented with a limestone, 17X6X5 inches, loosely set, dimly marked with 2 notches on south edge, other marks illegible; with a scattered mound of stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T22S R4W
S7 | S8
S18 | S17
2014

Deposit marked stone alongside.

Raise mound of stone, 3 feet base, 12 inches high, west of corner.

From this corner a barbed wire fence corner extending south and east, bears S.47°02'W., 4.10 chains distance.

From the corner of sections 8 and 9 only.

N. 87°50.9' W., between sections 8 and 17.

- 4.010** Ravine, course northwest.
- 20.480** Spring, course northwest, bears North, approximately 2 chains distance.
- 40.272** Point for the 1/4 section corner of sections 8 and 17, at proportionate distance. There is no evidence remaining of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T22S R4W
S8
1/4 ———
S17
2014

From this point the southeast corner of a house approximately bears N. 87°51' E., 2.60 chains distance.

DEPENDENT RESURVEY OF A PORTION OF SUBDIVISIONAL LINES,
TOWNSHIP 22 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

From this same point a barbed wire fence, extending easterly and westerly, bears South, 1.43 chains distance.

50.000 A steep wash, drains northwest.

56.300 A deep ravine, course north.

60.408 Point for the W 1/16 section corner of sections 8 and 17.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with aluminum cap marked

S8
W 1/16 ———
S17
2014

From this point, a barbed wire fence corner, extending east, west, and northwesterly, bears S.67°34' E., 5.66 chains distance.

Corner is located on a westerly slope.

64.362

A deep ravine, course northeast.

80.544 The corner of sections 7, 8, 17, and 18.

S. 87°11.6' W., between sections 7 and 18.

41.646 The 1/4 section corner of sections 7 and 18, monumented with a sandstone, 14X12X8 inches, firmly set, projecting 8 inches above the ground, clearly marked 1/4 on W. face.

At the corner point

Set aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T22S R4W
S7
1/4 ———
S18
2014

Deposit marked stone alongside.

Raise mound of stone, 3 1/2 feet base, 12 inches high, north of corner.

Center of dirt track road running east and west, bears North, approximately 38 links distance.

N. 89°39.2' W., beginning a new measurement.

DEPENDENT RESURVEY OF A PORTION OF SUBDIVISIONAL LINES,
TOWNSHIP 22 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 19.928** Point for the W 1/16 section corner of sections 7 and 18.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base and aluminum cap marked

S7
W 1/16 ———
S18
2014

- 40.055** The corner of sections 7, 12, 13, and 18, on the west boundary of the township, hereinbefore described.

From the corner of sections 7, 8, 17, and 18.

N. 0°20.3' E., between sections 7 and 8.

- 8.600** Base of slope, bears westerly and easterly.

- 20.990** Top of ridge, slopes easterly.

- 39.221** Point for the 1/4 section corner of sections 7 and 8, at proportionate distance. There is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T22S R4W
1/4
S7 | S8
2014

Raise mound of stone, 3 feet base, 1 1/2 feet high, north of corner.

- 78.442** The corner of sections 5, 6, 7, and 8, monumented with an aluminum cap, 3 1/2 inches diameter, firmly set, projecting 3 inches above the ground with cap marked MILLARD COUNTY 2011 T22S S5 S6 S7 S8 R4W LS 189369, and is accepted as a careful and faithful perpetuation of the original corner position.

A fence corner, extending east, west, and north, bears North, 1 link distance.

Subdivision of Section 7,
Township 22 South, Range 4 West, Salt Lake Meridian, Utah

From the 1/4 section corner of sections 7 and 18.

N. 1°15.3' E., along the N-S centerline of section 7.

SUBDIVISION OF SECTION 7,
TOWNSHIP 22 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 41.381** Point for the center 1/4 section corner of section 7, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a mound of stone, 1 1/2 feet base, 6 inches high, magnet at base, with aluminum cap marked

T22S R4W
C1/4 · S7
2014

Corner is located on a northerly slope.

- 81.621** The 1/4 section corner of sections 6 and 7, monumented with an aluminum pipe, 1 inch diameter, firmly set, projecting 4 inches above the ground, with cap marked MILLARD COUNTY 2011 1/4 S6 S7 LS 189369 SURVEY MARKER, and is accepted as a careful and faithful perpetuation of the original corner position.

Corner falls in a barbed wire fence line, extending east and west.

From the 1/4 section corner of sections 7 and 8.

N. 89°50.6' W., along the E-W centerline of section 7.

- 40.916** The center 1/4 section corner of section 7.

- 60.900** Point for the center W 1/16 section corner of section 7.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground, in a mound of stone, 4 feet base, 20 inches high, with magnet at base and aluminum cap marked

W 1/16
C———C
S7
2014

Corner is located on a westerly slope.

A fence, extending east and west, bears South, 73 links distance.

- 80.784** The 1/4 section corner of sections 12 and 7, on the west boundary of the township, monumented with brass tablet, firmly set, in a 6 X 6 inches concrete block, with brass cap marked, T22S R5W S12 S7 R4W 1/4 1981, and is accepted as a careful and faithful perpetuation of the original corner position.

From the W 1/16 section corner of sections 7 and 18.

SUBDIVISION OF SECTION 7,
TOWNSHIP 22 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

N. 1°10.6' E., along the N-S centerline of the SW 1/4 of section 7.

41.313 The center W 1/16 section corner of section 7.

Subdivision of Section 8,
Township 22 South, Range 4 West, Salt Lake Meridian, Utah

From the 1/4 section corner of section 8 and 17.

N. 0°17.8' E., along the N-S centerline of section 8.

19.752 Point for the center S 1/16 section corner of section 8, not monumented.

39.504 Point for the center 1/4 section corner of section 8, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at base and aluminum cap marked

T22S R4W
C1/4 · S8
2014

79.010 The 1/4 section corner of sections 5 and 8, monumented with an aluminum pipe, 1/2 inch diameter, firmly set, projecting 4 inches above the ground, with 3 1/2 inch aluminum cap marked MILLARD COUNTY 2011 1/4 S5 S8 LS 189369 SURVEY MARKER, and is accepted as a careful and faithful perpetuation of the original corner position.

A fence, extends east and west, bears South, 11 links distance.

From the 1/4 section corner of sections 8 and 9.

N. 88°15.0' W., along the E-W centerline of section 8.

40.229 The center 1/4 section corner of section 8.

60.345 Point for the center W 1/16 section corner of section 8.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground, in a mound of stone, 3 1/2 feet base, 14 inches high, magnet at base, with aluminum cap marked

T22S R4W
W 1/16
C ——— C
S8
2014

SUBDIVISION OF SECTION 8,
TOWNSHIP 22 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

A barbed wire fence corner, extending easterly, westerly and southeasterly, bears S.15°32'E., 1.45 chains distance.

80.461 The 1/4 section corner of sections 7 and 8.

From the W 1/16 section corner of section 8 and 17.

N. 0°19.0' E., along the N-S centerline of the SW 1/4 of section 8.

39.363 The center W 1/16 section corner of section 8.

Subdivision of Section 19,
Township 22 South, Range 4 West, Salt Lake Meridian, Utah

From the 1/4 section corner of sections 19 and 30.

N. 0°19.1' W., along the N-S centerline of section 19.

40.169 Point for the center 1/4 section corner of section 19, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground, in a mound of stone, 3 feet base, 12 inches high, magnet at base, with aluminum cap marked

T22S R4W
C1/4 · S19
2014

79.957 The 1/4 section corner of section 19 only.

From the 1/4 section corner of sections 19 and 20.

N. 89°34.0' W., along the E-W centerline of section 19.

40.123 The center 1/4 section corner of section 19.

86.804 The 1/4 of section 19 only, on the west boundary of the township, hereinbefore described.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT


FIELD ASSISTANTS

Name	Capacity
Ronald K. Baugh	Sup. Cadastral Surveyor
Matthew N. Gillins	Survey Technician
Kevin R. Muncey	Survey Aid

CERTIFICATE OF SURVEY

We, **Christopher J. May, Survey Technician, and R. Keith Batty, Cadastral Surveyor**, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing the date of the **May 05, 2014**, we have **dependently resurveyed a portion of the west boundary, a portion of the subdivisional lines and subdivided sections 7, 8, and 19, in Township 22 South, Range 4 West**, of the **Salt Lake Meridian**, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 14, 2016
Date


Survey Technician

January 14, 2016
Date


Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the **dependent resurvey of a portion of the west boundary, a portion of the subdivisional lines and the subdivision of sections 7, 8, and 19 in Township 22 South, Range 4 West, Salt Lake Meridian, Utah**, executed by **Christopher J. May, Survey Technician, under the supervision of Ronald K. Batty, Cadastral Surveyor**, having been critically examined and found correct, are hereby approved.

January 20, 2016
Date


Chief Cadastral Surveyor for Utah