

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH BOUNDARY (THIRD STANDARD PARALLEL SOUTH),

**TOWNSHIP 15 SOUTH, RANGE 10 EAST,**

AND A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 3, 4, 5, 8, 9, AND 10,

IN

**TOWNSHIP 16 SOUTH, RANGE 10 EAST,**

OF THE SALT LAKE MERIDIAN,  
IN THE STATE OF UTAH

EXECUTED BY

***Scott A. Burkhardt***  
***Cadastral Surveyor***

Under Special Instructions dated and approved ***July 22, 2013***, which provided for the surveys included under Group No. ***1206***, and Assignment Instructions dated ***July 22, 2013***.

Survey Commenced, ***August 6, 2013***  
Survey Completed, ***September 17, 2013***

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH BOUNDARY (THIRD STANDARD PARALLEL SOUTH),

**TOWNSHIP 15 SOUTH, RANGE 10 EAST,**

AND A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 3, 4, 5, 8, 9, AND 10,

IN

**TOWNSHIP 16 SOUTH, RANGE 10 EAST,**

OF THE SALT LAKE MERIDIAN,  
IN THE STATE OF UTAH

EXECUTED BY

***Scott A. Burkhardt***  
***Cadastral Surveyor***

Under Special Instructions dated and approved ***July 22, 2013***, which provided for the surveys included under Group No. ***1206***, and Assignment Instructions dated ***July 22, 2013***.

Survey Commenced, ***August 6, 2013***  
Survey Completed, ***September 17, 2013***

# INDEX DIAGRAM

TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH

	5	4	3		
6	18 5	13 4	10 3	2	1
	17	13	9		
7	16 8	12 9	8 10	6 11	12
	14	11	7		
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

The Subdivision of Section 3.....Page 18  
 The Subdivision of Section 4.....Page 20  
 The Subdivision of Section 5.....Page 23  
 The Subdivision of Section 8.....Page 24  
 The Subdivision of Section 9.....Page 28  
 The Subdivision of Section 10.....Page 29

## TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH

The following field notes describe the dependent resurvey of a portion of the south boundary (Third Standard Parallel South), T. 15 S., R. 10 E., and a portion of the subdivisional lines, and the subdivision of sections 3, 4, 5, 8, 9, and 10, in T. 16 S., R. 10 E., Salt Lake Meridian, Utah.

## HISTORY OF SURVEYS

Surveyed by		Retr. or Resurveyed by	
<b>SOUTH BOUNDARY</b>			
Portion	A.D. Ferron	1880	
All	A.D. Ferron	1883	A.D. Ferron 1883
All			J.T. Breckon 1895
Portion			C.P. Sylvester 1969
<b>EAST BOUNDARY</b>			
All	A.D. Ferron	1883	
All			J.T. Breckon 1895
All			C.P. Sylvester 1969
<b>WEST BOUNDARY (Castle Valley Guide Meridian)</b>			
All	A.D. Ferron	1873	
All			A.D. Ferron 1881
All			J.C. Clark 1940
Portion			J.L. Thomas 1986
Portion			J.L. Thomas 1987
<b>NORTH BOUNDARY (Third Standard Parallel South)</b>			
Portion	A.D. Ferron	1873	
All	A.D. Ferron	1880	A.D. Ferron 1880
All			C.P. Sylvester 1969
<b>SUBDIVISION</b>			
All	J.T. Breckon	1895	
Portion			C.P. Sylvester 1969
Portion			J.L. Thomas 1987
<b>COUNTY SURVEYS</b>			

The Emery County Surveyor's Office has identified Public Land Survey System corner monuments, and in some cases has perpetuated the locations by setting rebar as accessories to the monument, details of which are maintained on Section Corner Tie Sheets on file at their office.

## TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 1206, dated July 22, 2013.

The direction of the lines was determined by references to true meridian, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards for the Positional Accuracy of Cadastral Surveys When Using Global Navigation Satellite Systems (GNSS)*, dated February 23, 2009. Trimble model R8 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from GPS static observations, post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS): AF9633 RBUT RED BUTTE CORS ARP, AJ2124 PUC1 CARBON COUNTY COU CORS ARP, and DI2242 P009 MARYSVILLE\_UT2006 CORS ARP.

The geographic position of the corner of sections 10, 11, 14, and 15, T. 16 S., R. 10 E., as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: **39°26'26.644" N.**,  
Longitude: **110°46'38.625" W.**, N.A.D. 83 (2011), EPOCH: 2010.00,  
Network Accuracy = 0.200 meter at 95% confidence.

The geographic position of the 1/4 section corner of sections 7 and 8, T. 16 S., R. 10 E., as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: **39°26'52.442" N.**,  
Longitude: **110°50'02.650" W.**, N.A.D. 83 (2011), EPOCH 2010.00,  
Network Accuracy = 0.200 meter at 95% confidence.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY  
(THIRD STANDARD PARALLEL SOUTH),  
TOWNSHIP 15 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the South Boundary  
(Third Standard Parallel South),  
T. 15 S., R. 10 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by A.D. Ferron in 1880,  
And the Dependent Resurvey Executed by C.P. Sylvester in 1969

Beginning at the standard 1/4 section corner of section 34, T. 15 S., R. 10 E., monumented with an iron post, 2 1/2 inches diameter, firmly set, flush with the ground, with brass cap, oriented to the south, marked as described in the official record of the 1969 resurvey, with a steel fence post east of the corner.

Corner is located west of a paved road bearing north and south, in flat, level ground, with grasses.

**S. 89°25.5'W.**, between sections 3 and 34.

- 0.338** The 1/4 section corner of section 3 only, T. 16 S., R. 10 E., monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey, with a steel fence post south of the corner.

Corner is located near the base of a small cottonwood tree, west of a paved road bearing north and south, in flat, level ground, with sparse vegetation.

**N. 89°54.0'W.**, beginning new measurement.

- 20.187** The W 1/16 section corner of section 3 only, T. 16 S., R. 10 E., monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 9 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey, with a steel fence post east of the corner.

From which

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears S.79°44.9'E., 36.8 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears S.4°28.0'W., 41.3 links distance.

Corner is located in flat, nearly level ground, with scattered rabbitbrush.

- 40.040** The standard corner of sections 33 and 34 only, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 9 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey, with a steel fence post

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY  
(THIRD STANDARD PARALLEL SOUTH),  
TOWNSHIP 15 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

east of the corner.

Corner is located in flat, level ground, with scattered tamarisk brush.

---

Reestablishment of the Survey Executed by A.D. Ferron in 1873,  
and the Dependent Resurveys Executed by A.D. Ferron in 1880,  
and C.P. Sylvester in 1969

---

**N. 89°25.2' W.**, between sections 3 and 33.

- 0.352** The closing corner of sections 3 and 4, T. 16 S., R. 10 E., monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 9 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey, with a steel fence post east of the corner.

Corner is located on flat, level ground, with scattered tamarisk brush.

---

**N. 89°54.0' W.**, between sections 4 and 33.

- 40.028** The standard 1/4 section corner of section 33 only, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 11 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey, with a steel fence post east of the corner.

Corner is located on flat, level ground, with sparse vegetation and scattered tamarisk brush.

---

**S. 89°40.5' W.**, beginning new measurement.

- 0.318** The 1/4 section corner of section 4 only, T. 16 S., R. 10 E., monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 12 inches above the ground, with brass cap marked as described in the official record of the 1969 survey, with a steel fence post east of the corner.

From which

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears N.24°09.4'E., 42.8 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears S.27°30.7'E., 34.4 links distance.

Corner is located on flat, level ground, with sparse vegetation and scattered tamarisk brush.

---

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY  
(THIRD STANDARD PARALLEL SOUTH),  
TOWNSHIP 15 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

**N. 89°54.2' W.**, beginning new measurement.

- 40.075** The standard corner of sections 32 and 33, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 7 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey, with a steel fence post north of the corner.

Corner is located on flat, level ground, with shadscale brush.

---

**N. 89°12.2' W.**, between sections 4 and 32.

- 0.288** The closing corner of sections 4 and 5, T. 16 S., R. 10 E., monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 13 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey, with a steel fence post north of the corner.

From the corner, a fence corner, with fence lines, wood posts with enclosure wire and barbed-wire, extending south and east, bears N.45°23.7'W., 21.3 links distance.

Corner is located on flat, level ground, with shadscale brush.

---

**N. 89°54.9' W.**, between sections 5 and 32.

- 40.092** The standard 1/4 section corner of section 32, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 11 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey.

Corner is located on flat, level ground, with grasses.

---

**N. 89°44.4' W.**, beginning new measurement.

- 0.323** The 1/4 section corner of section 5 only, T. 16 S., R. 10 E., monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 12 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey, with a steel fence post east of the corner.

Corner is located on flat, level ground, with grasses.

---

**N. 89°54.5' W.**, beginning new measurement.

- 40.073** The standard corner of sections 31 and 32, monumented with an iron post, 2 1/2 inches diameter, firmly set, flush with the ground, with brass cap marked as described in the official record of the 1969 resurvey.

Set a steel fence post north of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY  
(THIRD STANDARD PARALLEL SOUTH),  
TOWNSHIP 15 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located east of an unimproved dirt road bearing north and south.

---

N. 89°49.0' W., between sections 5 and 31.

- 0.350 The closing corner of sections 5 and 6, T. 16 S., R. 10 E., monumented with an iron post, 2 1/2 inches diameter, firmly set, flush with the ground, with brass cap marked as described in the official record of the 1969 resurvey.

Corner is located on the west edge of an unimproved dirt road bearing north and south.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 10 E., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by J.T. Breckon in 1895,  
and the Dependent Resurvey Executed by C.P. Sylvester in 1969

---

From the corner of sections 10, 11, 14, and 15, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 7 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey.

From which

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears N.63°46.3'E., 27.2 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears S.89°46.1'E., 42.4 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears S.18°36.7'E., 31.3 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears S.64°41.3'W., 39.4 links distance.

Corner is located in a fence line, steel posts with 4-strand barbed-wire, extending east and west; on flat, level ground with shadscale.

N. 0°19.6' W., between sections 10 and 11.

- 40.116 The 1/4 section corner of sections 10 and 11, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 7 inches above a mound of stone, 3 feet diameter, 1 foot high, with brass cap marked as described in the official record of the 1969 resurvey.

From which

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH  
CHAINS

A rebar 1/2 inch diameter, firmly set, projecting 3 inches  
above the ground, bears S.12°00.6'E., 47.3 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches  
above the ground, bears N.89°24.3'W., 45.1 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches  
above the ground, bears N.12°36.6'W., 49.1 links distance.

Corner is located on a southeast-facing slope, with sparse  
vegetation.

---

N. 0°19.7'W., beginning new measurement.

- 20.058 The N 1/16 section corner of sections 10 and 11, monumented with  
an iron post, 2 1/2 inches diameter, firmly set, projecting 6  
inches above a mound of stone, 2 1/2 feet diameter, 1 1/2 feet  
high, with brass cap marked as described in the official record  
of the 1969 resurvey.

From which

A rebar 1/2 inch diameter, firmly set, projecting 3 inches  
above the ground, bears N.80°42.5'E., 41.6 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches  
above the ground, bears S.0°25.7'E., 39.1 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches  
above the ground, bears S.77°21.7'W., 35.6 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches  
above the ground, bears N.0°37.0'W., 39.1 links distance.

Corner is located on flat, level ground, with sparse vegetation.

---

N. 0°20.7'W., beginning new measurement.

- 20.058 The corner of sections 2, 3, 10, and 11, monumented with an iron  
post, 2 1/2 inches diameter, firmly set, projecting 7 inches  
above the ground, with brass cap marked as described in the  
official record of the 1969 resurvey, with a steel fence post  
north of the corner.

Corner is located north of an irrigation ditch, on flat, level  
ground, with sparse vegetation.

---

From the corner of sections 10, 11, 14, and 15.

S. 89°02.5' W., between sections 10 and 15.

- 20.252 The E 1/16 section corner of sections 10 and 11, monumented with

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH  
CHAINS

an iron post, 2 1/2 inches diameter, firmly set, projecting 3 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey, with a steel fence post southwest of the corner.

From which

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears N.73°01.2'E., 32.5 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears S.17°05.9'E., 28.3 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears S.72°31.5'W., 36.7 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears N.17°37.4'W., 46.0 links distance.

Corner is located on flat, level ground, with scattered rabbitbrush.

---

S. 89°02.6' W., beginning new measurement.

- 20.257 The 1/4 section corner of sections 10 and 15, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 14 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey.

Corner is located in a cultivated field, north of a small drainage.

---

S. 89°02.0' W., beginning new measurement.

- 40.491 The corner of sections 9, 10, 15, and 16, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 4 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey.

From the corner, fence lines, wood and steel post with 4-strand barbed-wire, extend north, south, and west.

Corner is located on the west edge of a cultivated field.

---

N. 0°06.4' W., between sections 9 and 10.

- 20.167 The S 1/16 section corner of sections 9 and 10, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 8 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey.

From the corner, a fence line, 4-strand barbed-wire, extending north and south, bears West, 3 links distance.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH  
CHAINS

Corner is located in fairly level mud flats.

---

**N. 0°08.5'W.**, beginning new measurement.

- 20.188** The 1/4 section corner of sections 9 and 10, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 5 inches above a mound of stone, 3 feet diameter, 1 1/2 feet high, with brass cap marked as described in the official record of the 1969 resurvey.

From which

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears N.86°10.1'E., 33.8 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears S.2°05.4'W., 25.3 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears S.89°38.1'W., 32.8 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears N.1°11.9'W., 33.5 links distance.

From the corner, fence lines, wood post with 4-strand barbed-wire, extend west and south.

Corner is located on a moderately steep, south-facing slope, with sparse vegetation.

---

**N. 0°00.1'E.**, beginning new measurement.

- 40.498** The corner of sections 3, 4, 9, and 10, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 5 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey, with a steel fence post east of the corner.

Corner is located on flat, level ground, with sparse vegetation.

---

From the corner of sections 2, 3, 10, and 11.

**S. 89°27.4' W.**, between sections 3 and 10.

- 20.152** True point for the E 1/16 section corner of sections 3 and 10, falls in an irrigation ditch.

From the true point, the witness corner bears S. 0°15.9' E., 59.6 links distance, hereinafter described.

- 40.304** The 1/4 section corner of sections 3 and 10, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 3 inches

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

above the ground, with brass cap marked as described in the official record of the 1969 resurvey, with a steel fence post northwest of the corner.

From the corner, a fence corner, with a fence line, wood and steel posts and 4-strand barbed-wire, extending north and south, and a fence line, steel posts and 4-strand barbed-wire, extending west, bears S.89°48'W., 12.2 links distance.

Corner is located west of a paved road extending north and south, on flat, level ground.

---

S. 89°29.7' W., beginning new measurement.

- 20.145 The W 1/16 section corner of sections 3 and 10, monumented with an unrecorded rebar, 5/8 inch diameter, firmly set, projecting 6 inches above the ground, with yellow plastic cap, 1 1/4 inches diameter, marked with partially legible markings PLS & PE \_\_\_56, and is accepted as a careful and faithful determination of the position of the corner.

From the corner, fence lines, steel posts with 4-strand barbed-wire, extend north and east.

Corner is located in flat, level ground, with sparse vegetation.

---

S. 89°29.6' W., beginning new measurement.

- 20.147 The corner of sections 3, 4, 9, and 10.

---

N. 0°51.4' W., between sections 3 and 4.

- 20.212 The S 1/16 section corner of sections 3 and 4, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 10 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey.

From which

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears N.72°41.9'E., 33.5 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears S.9°25.9'E., 33.8 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears S.72°59.4'W., 32.5 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears N.7°55.0'W., 30.2 links distance.

Set a steel fence post west of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH  
CHAINS

Corner is located on flat, level ground, with sparse vegetation.

---

**N. 0°49.3'W.**, beginning new measurement.

**10.116** Point for the N-S 1/64 section corner of sections 3 and 4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked

T16S R10E

N-S 1/64

S4 | S3

2013

Set a steel fence post north of the corner.

Corner is located in rolling ground, with brush.

**20.232** The 1/4 section corner of sections 3 and 4, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey.

From which

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears N.74°12.3'E., 38.5 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears S.20°32.6'E., 50.2 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears S.73°57.5'W., 41.7 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears N.10°52.8'W., 42.0 links distance.

Corner is located on flat, level ground, with scattered sagebrush.

---

**N. 0°50.0'W.**, beginning new measurement.

**38.475** The closing corner of sections 3 and 4, on the northern boundary of the township, hereinbefore described.

---

From the corner of sections 9, 10 15, and 16.

**N. 89°52.9' W.**, between sections 9 and 16.

**40.457** The 1/4 section corner of sections 9 and 16, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

above the ground, with brass cap marked as described in the official record of the 1969 resurvey.

Corner is located in flat, level ground, at the southeast corner of a small wooden corral, immediately south of a fence corner, with fence lines, enclosure wire and barbed-wire, extending north, east, and west.

---

S. 89°56.8' W., beginning new measurement.

- 40.187 The corner of sections 8, 9, 16, and 17, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 4 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey.

From the corner, a rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, on file with the Emery County Recorder, C.R. No. 1610300500, as an accessory to the corner, bears S. 1°11.2' W., 30.1 links distance (Record: S. 0°02.2' E., 30.8 links distance).

Corner is located in flat, level ground, immediately south of a fence corner, with fence lines, steel and wood posts with enclosure wire and barbed-wire, extending north, south, east, and west.

---

N. 0°05.6' W., between sections 8 and 9.

- 20.217 Point for the S 1/16 section corner of sections 8 and 9. Not monumented.
- 40.265 The witness corner to the 1/4 section corner of sections 8 and 9, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 4 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey, with a steel fence post east of the corner.

From which

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears S.23°30.4'W., 49.2 links distance.

Corner is located on a gentle south-facing slope, south of an unimproved dirt road.

---

N. 0°06.2' W., beginning new measurement.

- 0.170 True point for the 1/4 section corner of sections 8 and 9.
- 40.572 The corner of sections 4, 5, 8, and 9, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 11 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH  
CHAINS

From the corner, a fence line, steel posts with enclosure wire and barbed-wire, extends east and west.

Corner is located on flat, level ground, with sparse vegetation.

---

From the corner of sections 3, 4, 9, and 10.

**N. 89°59.2' W.**, between sections 4 and 9.

**20.174** Point for the E 1/16 section corner of sections 4 and 9. Not monumented.

**40.348** The 1/4 section corner of sections 4 and 9, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey.

From the corner, a fence line, wood posts and fallen barbed-wire, extending east and west, bears North, 1.339 chains distance.

Corner is located on flat, level ground, with sparse vegetation.

---

**N. 89°58.3' W.**, beginning new measurement.

**20.167** Point for the W 1/16 section corner of sections 4 and 9. Not monumented.

**40.334** The corner of sections 4, 5, 8, and 9.

---

**N. 0°51.9' W.**, between sections 4 and 5.

**20.213** The S 1/16 section corner of sections 4 and 5, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 7 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey.

From which

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears N.88°21.6'E., 43.3 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears S.0°53.5'E., 44.5 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears S.89°7.4'W., 38.0 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears N.0°58.8'W., 42.0 links distance.

The corner falls in a fence line, steel posts with enclosure wire and barbed-wire, extends east and west.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH  
CHAINS

Corner is located on flat, level ground, with sparse vegetation.

---

**N. 0°52.9'W.**, beginning new measurement.

- 20.217** The 1/4 section corner of sections 4 and 5, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 5 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey.

From which

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears S.87°18.1'E., 31.7 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears S.33°43.3'W., 41.4 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears N.87°20.7'W., 22.6 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears N.25°31.3'W., 51.9 links distance.

From the corner, a fence line, wood and steel posts with 4-strand barbed-wire, extending north and south, bears West, 23.2 links distance. A fence line, wood posts with 4-strand barbed-wire, extending east, and steel posts with 4-strand barbed-wire extending west, bears South, 71.4 links distance.

Corner is located on a low berm, approximately 15 links distance north of an abandoned and dry irrigation ditch extending east and west.

---

**N. 0°51.6'W.**, beginning new measurement.

- 38.599** The closing corner of sections 4 and 5, on the north boundary of the township, hereinbefore described.
- 

From the corner of sections 8, 9, 16, and 17.

**N. 88°45.0' W.**, between sections 8 and 17.

- 20.205** Point for the E 1/16 section corner of sections 8 and 17. Not monumented.
- 40.410** The 1/4 section corner of sections 8 and 17, monumented with an iron post, 2 1/2 inches diameter, firmly set, flush with the ground, with brass cap marked as described in the official record of the 1969 resurvey.

Build a mound of stone, 2 feet diameter, 1 foot high, north of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH  
CHAINS

From the corner, a rebar 1/2 inch diameter, firmly set, projecting 4 inches above the ground, bears N.18°36.4'W., 4.0 links distance. This unrecorded rebar is of unknown origin and was set using unknown procedures, and is not utilized during the course of this survey.

From the corner, a rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, on file with the Emery County Recorder, C.R. No. 1610240500, as an accessory to the corner, bears N.88°23.5'E., 31.0 links distance.

From the corner, a rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, on file with the Emery County Recorder, C.R. No. 1610240500, as an accessory to the corner, bears N.89°8.2'E., 74.3 links distance.

From the corner, a rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, on file with the Emery County Recorder, C.R. No. 1610240500, as an accessory to the corner, bears N.89°51.4'W., 85.6 links distance.

From the corner, a rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, on file with the Emery County Recorder, C.R. No. 1610240500, as an accessory to the corner, bears N.89°21.6'W., 38.6 links distance.

Corner is located in an abandoned fence line, wood and steel posts with wire removed, on the north edge of a cultivated field.

---

S. 89°44.9'W., beginning new measurement.

- 20.219 The W 1/16 section corner of sections 8 and 17, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 5 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey.

Corner is located on flat, level ground, in a newly built fence, wood and steel posts with 4-strand barbed-wire, extending east and west.

---

S. 89°45.9'W., beginning new measurement.

- 20.213 The corner of sections 7, 8, 17, and 18, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 5 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey.

From the corner, a rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, on file with the Emery County Recorder, C.R. No. 1610200500, as an accessory to the corner, bears N.89°27.8'E., 25.4 links distance.

From the corner, a rebar 1/2 inch diameter, firmly set,

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH  
CHAINS

projecting 3 inches above the ground, on file with the Emery County Recorder, C.R. No. 1610200500, as an accessory to the corner, bears N.89°50.5'E., 64.2 links distance.

From the corner, a rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, on file with the Emery County Recorder, C.R. No. 1610200500, as an accessory to the corner, bears N.89°17.1'W., 26.8 links distance.

From the corner, a rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, on file with the Emery County Recorder, C.R. No. 1610200500, as an accessory to the corner, bears N.89°3.0'W., 58.5 links distance.

Corner is located immediately south of a fence corner, newly built fence, wood and steel posts and 4-strand barbed-wire extending north and east, an older fence, wood and steel posts and 4-strand barbed-wire extending west. Fences extending east and west have remnants of old wood posts projecting from the ground.

N. 0°10.7' W., between sections 7 and 8.

20.082 Point for the S 1/16 section corner of sections 7 and 8. Not monumented.

40.164 The 1/4 section corner of sections 7 and 8, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 11 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey.

From the corner, a rebar 1/2 inch diameter, firmly set, projecting 6 inches above the ground, in a collar of stone, 2 feet diameter, on file with Emery County Recorder, C.R. No. 1610200540, as an accessory to the corner, bears S.84°23.6'E., 46.3 links distance.

Corner is located north of a fence line, wood and steel posts with enclosure wire and barbed-wire.

N. 0°10.2' W., beginning new measurement.

40.275 The corner of sections 5, 6, 7, and 8, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 4 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey, with a steel fence post north of the corner.

From the corner, a rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, on file with Emery County Recorder, C.R. No. 1610200600, as an accessory to the corner, bears S.74°55.5'E., 41.1 links distance.

Corner is located in gently-rolling ground, with scattered

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

sagebrush.

---

From the corner of sections 4, 5, 8, and 9.

**N. 89°44.7' W.**, between sections 5 and 8.

- 20.245** The E 1/16 section corner of sections 5 and 8, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 8 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey.

From which

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears S.89°24.9'E., 37.9 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears S.0°52.4'W., 40.8 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears N.89°42.0'W., 39.1 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears N.2°49.5'W., 38.8 links distance.

Corner is located in a fence corner, with fence lines, wood and steel posts with enclosure wire and 4-strand barbed-wire, extending north, south, and east.

---

**N. 89°49.5' W.**, beginning new measurement.

- 20.223** The 1/4 section corner of sections 5 and 8, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 2 inches above a mound of stone, 2 feet diameter, 1 foot high, with brass cap marked as described in the official record of the 1969 resurvey, with a mound of stone, 3 feet diameter, 2 feet high, north of the corner.

From which

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears N.73°12.1'E., 31.4 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears S.12°22.8'E., 29.2 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears S.73°49.5'W., 27.4 links distance.

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears N.12°24.2'W., 28.9 links distance.

Corner is located on a south-facing slope, with sparse vegetation.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH  
CHAINS

---

N. 89°46.4' W., beginning new measurement.

40.453 The corner of sections 5, 6, 7, and 8.

---

N. 0°49.3' W., between sections 5 and 6.

40.279 The 1/4 section corner of sections 5 and 6, monumented with an aluminum pipe, 2 1/2 inches diameter, firmly set, flush with the ground, with aluminum cap marked EMERY COUNTY SURVEY T16S R10E 1/4 S6/S5 2005, with a steel fence post west of the corner.

This unrecorded aluminum pipe is harmoniously related to existing corners and is accepted as the best available evidence of the original corner position.

Corner is located in a drainage ditch, on the west edge of an unimproved dirt road bearing north and south.

---

N. 0°49.2' W., beginning new measurement.

38.563 The closing corner of sections 5 and 6, on the north boundary of the township, hereinbefore described.

---

The Subdivision of Section 3,  
T. 16 S., R. 10 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 3 and 10.

N. 0°45.7' W., on the north-south centerline of section 3.

20.150 Point for the center S 1/16 section corner of section 3. Not monumented.

40.300 Point for the center 1/4 section corner of section 3, at intersection with the east-west centerline, falls in a cultivated field. Not monumented.

78.487 The 1/4 section corner of section 3 only, on the north boundary of the township, hereinbefore described.

---

From the 1/4 section corner of sections 2 and 3, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 12 inches above the ground, with brass cap marked as described in the official record of the 1969 resurvey.

From which

A rebar 1/2 inch diameter, firmly set, projecting 3 inches above the ground, bears N.15°57.0'E., 33.0 links distance.

THE SUBDIVISION OF SECTION 3,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner, a fence corner, with fences, steel and wood posts with barbed-wire, extending north, south, and west, bears S.8°14.2'E., 105.0 links distance.

Corner is located in flat, level ground, with sparse vegetation.

**S. 89°41.8' W.**, on the east-west centerline of section 3.

**40.360** The point for the center 1/4 section corner of section 3.

**60.532** Point for the center W 1/16 section corner of section 3.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T16S R10E

W 1/16  
C  $\frac{\quad}{S3}$  C  
2013

Corner is located on flat, level ground, with scattered brush, in a proposed fence line.

**80.704** The 1/4 section corner of sections 3 and 4.

---

From the W 1/16 section corner of sections 3 and 10.

**N. 0°48.1' W.**, on the north-south centerline of the SW 1/4 of section 3.

**20.181** Point for the SW 1/16 section corner of section 3, at intersection with the east-west centerline of the SW 1/4 of section 3. Not monumented.

**30.277** Point for the C-N-SW 1/64 section corner of section 3.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with aluminum cap marked

T16S R10E  
C-N-SW 1/64  
S3  
2013

Corner is located on flat, level ground, with scattered brush, in a proposed fence line.

**40.373** The center W 1/16 section corner of section 3.

---

From the point for the center S 1/16 section corner of section 3.

THE SUBDIVISION OF SECTION 3,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

**S. 89°34.9' W.**, on the east-west centerline of the SW 1/4 of section 3.

**20.158** The point for the SW 1/16 section corner of section 3.

**40.324** The S 1/16 section corner of sections 3 and 4.

---

From the C-N-SW 1/64 section corner of section 3.

**S. 89°38.3' W.**, on the east-west centerline of the NW 1/4 of the SW 1/4 of section 3.

**20.169** The N-S 1/64 section corner of sections 3 and 4.

---

From the center W 1/16 section corner of section 3.

**N. 0°47.0' W.**, on the north-south centerline of the NW 1/4 of section 3.

**38.330** The W 1/16 section corner of section 3 only, on the north boundary of the township, hereinbefore described.

---

The Subdivision of Section 4,  
T. 16 S., R. 10 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 4 and 9.

**N. 0°50.4' W.**, on the north-south centerline of section 4.

**20.221** Point for the center S 1/16 section corner of section 4. Not monumented.

**40.442** Point for the center 1/4 section corner of section 4, at intersection with the east-west centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with aluminum cap marked

T16S R10E

C 1/4 S4

2013

Set a steel fence post north of the corner.

From the corner, a fence line, enclosure wire and 1-strand barbed-wire, extending east and west, bears North, 98.3 links distance.

Corner is located in gently rolling, open ground.

**78.977** The 1/4 section corner of section 4 only, on the north boundary

THE SUBDIVISION OF SECTION 4,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

of the township, hereinbefore described.

---

From the 1/4 section corner of sections 3 and 4.

**N. 89°59.3' W.**, on the east-west centerline of section 4.

**20.172** Point for the center E 1/16 section corner of section 4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with aluminum cap marked

T16S R10E  
  

$$C \frac{E \ 1/16}{S4} C$$
  
 2013

Set a steel fence post north of the corner.

From the corner, a fence line, enclosure wire and 1-strand barbed-wire, extending north and south, bears West, 109.4 links distance.

Corner is located in rolling, open ground with low brush.

**40.344** The center 1/4 section corner of section 4.

**60.520** Point for the center W 1/16 section corner of section 4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked

T16S R10E  
  

$$C \frac{W \ 1/16}{S4} C$$
  
 2013

Set a steel fence post southwest of the corner.

From the corner, a fence line, enclosure wire and 1-strand barbed-wire, extending east and west, bears North, 26.8 links distance.

Corner is located in gently rolling, open ground with sparse vegetation.

**80.696** The 1/4 section corner of sections 4 and 5.

---

From the point for the E 1/16 section corner of sections 4 and 9.

**N. 0°50.4' W.**, on the north-south centerline of the SE 1/4 of section 4.

THE SUBDIVISION OF SECTION 4,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

**20.216** Point for the SE 1/16 section corner of section 4, at intersection with the east-west centerline of the SE 1/4 of section 4. Not monumented.

**30.329** Point for the C-N-SE 1/64 section corner of section 4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked

T16S R10E  
C-N-SE 1/64  
S4  
2013

Set a steel fence post west of the corner.

From the corner, a fence line, enclosure wire and 1-strand barbed-wire, extending north and south, bears West, 94.5 links distance.

Corner is located on gently rolling, open ground.

**40.442** The center E 1/16 section corner of section 4.

From the S 1/16 section corner of sections 3 and 4.

**N. 89°58.4' W.**, on the east-west centerline of the SE 1/4 of section 4.

**20.167** The point for the SE 1/16 section corner of section 4.

**40.340** The point for the center S 1/16 section corner of section 4.

From the N-S 1/64 section corner of sections 3 and 4.

**N. 89°58.9' W.**, on the east-west centerline of the NE 1/4 of the SE 1/4 of section 4.

**20.169** The C-N-SE 1/64 section corner of section 4.

From the point for the W 1/16 section corner of sections 4 and 9.

**N. 0°51.4' W.**, on the north-south centerline of the SW 1/4 of section 4.

**20.217** The SW 1/16 section corner of sections 4, at intersection with the east-west centerline of the SW 1/4 of section 4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with aluminum cap marked

THE SUBDIVISION OF SECTION 4,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T16S R10E  
SW 1/16 S4  
2013

Set a steel fence post northeast of the corner.

Corner is located in gently rolling, open ground.

**40.436** The center W 1/16 section corner of section 4.

---

From the point for the center S 1/16 section corner of section 4.

**N. 89°59.0' W.**, on the east-west centerline of the SW 1/4 of section 4.

**20.171** The SW 1/16 section corner of section 4.

**40.340** The S 1/16 section corner of sections 4 and 5.

---

The Subdivision of Section 5,  
T. 16 S., R. 10 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 5 and 8.

**N. 0°50.1' W.**, on the north-south centerline of section 5.

**20.179** Point for the center S 1/16 section corner of section 5. Not monumented.

**40.358** Point for the center 1/4 section corner of section 5, at intersection with the east-west centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with aluminum cap marked

T16S R10E  
C 1/4 S5  
2013

Set a steel fence post north of the corner.

From the corner, a fence corner, with fence lines extending east and south, wood and steel post with enclosure wire and 2-strand barbed-wire, bears S. 22°41' E., 104.2 links distance.

Corner is located in the north shoulder of an unimproved dirt road, 12 feet wide, extending N. 80° E. and S. 80° W.

**78.937** The 1/4 section corner of section 5 only, on the north boundary of the township, hereinbefore described.

---

THE SUBDIVISION OF SECTION 5,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 4 and 5.

**N. 89°53.1' W.**, on the east-west centerline of section 5.

- 20.218** Point for the center E 1/16 section corner of section 5. Not monumented.
- 40.436** The center 1/4 section corner of section 5.
- 80.873** The 1/4 section corner of sections 5 and 6.

From the E 1/16 section corner of sections 5 and 8.

**N. 0°50.3' W.**, on the north-south centerline of the SE 1/4 of section 5.

- 20.182** Point for the SE 1/16 section corner of section 5, at intersection with the east-west centerline of the SE 1/4 of section 5.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, magnet at base, in a collar of stone, 2 feet diameter, with aluminum cap marked

T16S R10E  
SE 1/16 S5  
2013

Set a steel fence post east of the corner.

From the corner, a fence corner, with fence lines extending east and south, enclosure wire and 1-strand barbed-wire, bears S. 13°25' E., 80.0 links distance.

Corner is located on a rocky hill top.

- 40.380** The point for the center E 1/16 section corner of section 5.

From the S 1/16 section corner of sections 4 and 5.

**N. 89°50.0' W.**, on the east-west centerline of the SE 1/4 of section 5.

- 20.234** The SE 1/16 section corner of section 5.
- 40.455** The point for the center S 1/16 section corner of section 5.

The Subdivision of Section 8,  
T. 16 S., R. 10 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 8 and 17.

THE SUBDIVISION OF SECTION 8,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

N. 0°09.3 W., on the north-south centerline of section 8.

**9.943** Point for the C-S-S 1/64 section corner of section 8.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T16S R10E  
C-S-S 1/64  
S8  
2013

Set a steel fence post north of the corner.

Corner is located in open ground, east of a meandering drainage.

**19.886** Point for the center S 1/16 section corner of section 8. Not monumented.

**39.773** Point for the center 1/4 section corner of section 8, at intersection with the east-west centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with aluminum cap marked

T16S R10E  
C 1/4 S8  
2013

Corner is located on a moderately steep slope, on the north side of a small hill.

**80.107** The 1/4 section corner of sections 5 and 8.

From the true point for the 1/4 section corner of sections 8 and 9.

N. 89°41.3' W., on the east-west centerline of section 8.

**20.219** Point for the center E 1/16 section corner of section 8.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T16S R10E  
E 1/16  
C ——— C  
S8  
2013

Set a steel fence post west of the corner.

THE SUBDIVISION OF SECTION 8,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

From the corner, a fence line, enclosure wire and 2-strand barbed-wire, extending north and south, bears East, 4.2 links distance.

**40.438** The center 1/4 section corner of section 8.

**60.661** Point for the center W 1/16 section corner of section 8.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, in a collar of stone, 2 feet diameter, with aluminum cap marked

T16S R10E  
C  $\frac{W\ 1/16}{S8}$  C  
2013

Set a steel fence post north of the corner.

Corner is located on a gentle south slope.

**80.884** The 1/4 section corner of sections 7 and 8.

From the point for the E 1/16 section corner of sections 8 and 17.

N. 0°07.4' W., on the north-south centerline of the SE 1/4 of section 8.

**10.026** Point for the C-S-SE 1/64 section corner of section 8. Corner falls in the east shoulder of a paved road.

Set a magnetic nail, 1 1/2 inches long, flush with the surface of the road.

From which

An aluminum post, 2 1/2 inches diameter, set 27 inches in the ground, with magnet at base, for a reference monument, bears N. 47°39.6' E., 49.5 links distance, with an aluminum cap marked RM T16S R10E S8 2013, with an arrow pointing toward the corner with 32.7 FT. TO COR. marked along it, with a steel fence post north of the corner.

An aluminum post, 2 1/2 inches diameter, set 27 inches in the ground, with magnet at base, for a reference monument, bears S. 49°27.9' E., 48.5 links distance, with an aluminum cap marked RM T16S R10E S8 2013, with an arrow pointing toward the corner with 32.0 FT. TO COR. marked along it, with a steel fence post west of the corner.

**20.052** Point for the SE 1/16 section corner of section 8, at intersection with the east-west centerline of the SE 1/4 of section 8. Not monumented.

THE SUBDIVISION OF SECTION 8,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

**40.104** The center E 1/16 section corner of section 8.

---

From the point for the S 1/16 section corner of sections 8 and 9.

**N. 89°13.2' W.**, on the east-west centerline of the SE 1/4 of section 8.

**20.211** The point for the SE 1/16 section corner of section 8.

**40.422** The point for the center S 1/16 section corner of section 8.

---

From the C-S-SE 1/64 section corner of section 8.

**N. 88°59.1' W.**, on the east-west centerline of the SW 1/4 of the SE 1/4 of section 8.

**20.208** The C-S-S 1/64 section corner of section 8.

---

From the W 1/16 section corner of sections 8 and 17.

**N. 0°09.7' W.**, on the north-south centerline of the SW 1/4 of section 8.

**9.994** Point for the C-S-SW 1/64 section corner of section 8.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with aluminum cap marked

T16S R10E  
C-S-SW 1/64  
S8  
2013

Set a steel fence post north of the corner.

From the corner, a fence line, extending north and south, 4-strand barbed-wire, bears East, 133.3 links distance.

Corner is located in open ground.

**19.988** Point for the SW 1/16 section corner of section 8, at intersection with the east-west centerline of the SW 1/4 of section 8. Not monumented.

From the corner point, a fence line, extending north and south, 4-strand barbed-wire, bears East, 135.1 links distance.

**39.972** The center W 1/16 section corner of section 8.

---

From the point for the center S 1/16 section corner of section 8.

THE SUBDIVISION OF SECTION 8,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

**N. 89°58.0' W.**, on the east-west centerline of the SW 1/4 of section 8.

- 20.221** The point for the SW 1/16 section corner of section 8.  
**40.439** The point for the S 1/16 section corner of sections 7 and 8.

---

From the C-S-S 1/64 section corner of section 8.

**S. 89°53.5' W.**, on the east-west centerline of the SE 1/4 of the SW 1/4 of section 8.

- 20.220** The C-S-SW 1/64 section corner of section 8.

---

The Subdivision of Section 9,  
T. 16 S., R. 10 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 9 and 16.

**N. 0°00.7 E.**, on the north-south centerline of section 9.

- 40.335** Point for the center 1/4 section corner of section 9, at intersection with the east-west centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, in a collar of stone, 2 feet diameter, with aluminum cap marked

T16S R10E

C 1/4 S9

2013

Set a steel fence post north of the corner.

From the corner, a fence line, extending east and west, enclosure wire and 2-strand barbed-wire, bears South, 33.3 links distance.

Corner is located on a south-facing slope, at the edge of an old cement-lined ditch.

- 80.780** The 1/4 section corner of sections 4 and 9.

---

From the 1/4 section corner of sections 9 and 10.

**N. 89°54.7' W.**, on the east-west centerline of section 9.

- 40.358** The center 1/4 section corner of section 9.  
**80.615** The true point for the 1/4 section corner of sections 8 and 9.
-

THE SUBDIVISION OF SECTION 10,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 10,  
T. 16 S., R. 10 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 10 and 15.

**N. 0°11.6 W.**, on the north-south centerline of section 10.

**20.116** Point for the center S 1/16 section corner of section 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 23 inches in the ground, magnet at base, in a collar of stone, 3 feet diameter, with aluminum cap marked .

T16S R10E  
C  
S 1/16 | S10  
C  
2013

From the corner, a fence corner, with fence lines, 4-strand barbed-wire, extending north and west, bears S.7°30'E., 5.9 links distance.

Corner is located in a fence line, 4-strand barbed-wire, extending north and south.

**40.232** The center 1/4 section corner of section 10, at intersection with the east-west centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with aluminum cap marked

T16S R10E  
C 1/4 S10  
2013

Set a steel fence post northeast of the corner.

From the corner, the centerline of a paved road, 24 feet wide, bearing S.10°W., and N.5°E., bears East, 45.8 links distance.

**80.525** The 1/4 section corner of sections 3 and 10.

---

From the 1/4 section corner of sections 10 and 11.

**S. 89°12.3' W.**, on the east-west centerline of section 10.

**20.204** Point for the center E 1/16 section corner of section 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with aluminum cap marked

THE SUBDIVISION OF SECTION 10,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T16S R10E

E 1/16  
C  $\frac{\quad}{S 10}$  C

2013

Set a steel fence post north of the corner.

Corner is located on a gentle west slope, in open ground.

**40.408** The center 1/4 section corner of section 10.

**80.844** The 1/4 section corner of sections 9 and 10.

From the center E 1/16 section corner of section 10.

**N. 0°15.9' W.**, on the north-south centerline of the NE 1/4 of section 10.

**39.608** The point for the witness corner to the E 1/16 section corner of sections 3 and 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with a magnet at base, with aluminum cap, marked

WC  
T16S R10E

↑ E 1/16  $\frac{S3}{S10}$

2013

Set a steel fence post north of the corner.

Corner is located on a fairly level mud flat.

**40.204** The true point for the E 1/16 section corner of sections 3 and 10.

From the E 1/16 section corner of sections 10 and 15.

**N. 0°15.8' W.**, on the north-south centerline of the SE 1/4 of section 10.

**40.175** The center E 1/16 section corner of section 10.

From the center S 1/16 section corner of section 10.

**S. 89°06.3' W.**, on the east-west centerline of the SW 1/4 of section 10.

THE SUBDIVISION OF SECTION 10,  
TOWNSHIP 16 SOUTH, RANGE 10 EAST, SALT LAKE MERIDIAN, UTAH

*CHAINS*

**40.457** The S 1/16 section corner of sections 9 and 10.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Phil Freiberg	Survey Technician

---

## CERTIFICATE OF SURVEY

I, *Scott A. Burkhardt, Cadastral Surveyor*, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing the date of *July 22, 2013*, I have *dependently resurveyed a portion of the south boundary (Third Standard Parallel South), Township 15 South, Range 10 East, a portion of the subdivisional lines, and subdivided sections 3, 4, 5, 8, 9, and 10, in Township 16 South, Range 10 East, of the Salt Lake Meridian, in the State of Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

11/20/2015

Date

Scott A. Burkhardt

Cadastral Surveyor

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the south boundary (Third Standard Parallel South), Township 15 South, Range 10 East, a portion of the subdivisional lines, and the subdivision of sections 3, 4, 5, 8, 9, and 10, in Township 16 South, Range 10 East, Salt Lake Meridian, Utah*, executed by *Scott A. Burkhardt, Cadastral Surveyor*, having been critically examined and found correct, are hereby approved.

January 21, 2015

Date

Daniel W. Webb

Chief Cadastral Surveyor for Utah