

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE EAST AND NORTH BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES,

THE SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,

THE SUBDIVISION OF SECTIONS 10, 13, 14, 15, AND 24,

AND THE SURVEY OF THE MEANDERS OF THE LEFT BANK OF THE GREEN RIVER,

IN

TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Scott A. Burkhardt
Cadastral Surveyor

Under Special Instructions dated and approved **May 13, 2013**, which provided for the surveys included under Group Number **1219**, and Assignment Instructions dated **May 13, 2013**.

Survey Commenced, **May 21, 2013**
Survey Completed, **October 22, 2013**

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE EAST AND NORTH BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES,

THE SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,

THE SUBDIVISION OF SECTIONS 10, 13, 14, 15, AND 24,

AND THE SURVEY OF THE MEANDERS OF THE LEFT BANK OF THE GREEN RIVER,

IN

TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Scott A. Burkhardt
Cadastral Surveyor

Under Special Instructions dated and approved **May 13, 2013**, which provided for the surveys included under Group Number **1219**, and Assignment Instructions dated **May 13, 2013**.

Survey Commenced, **May 21, 2013**
Survey Completed, **October 22, 2013**

INDEX DIAGRAM

TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

			6		5		
6	5	24	4	20	3	8	2
			23		19		
7	8		9	19	10	7	11
			18		17		
18	17		16	17	15	13	14
			16		14		11
19	20	22	21	15	22	12	23
			21				
							10
							24
							3
							9
30	29	22	28		27		26
							25
							3
							6
31	32		33		34		35
							36

The Subdivision of Section 10.....Page 25
 The Subdivision of Section 13.....Page 26
 The Subdivision of Section 14.....Page 28
 The Subdivision of Section 15.....Page 29
 The Subdivision of Section 24.....Page 31
 The Meanders of the Left Bank of the Green River.....Page 33

TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of a portion of the east and north boundaries, a portion of the subdivisional lines, the survey of a portion of the subdivisional lines, the subdivision of sections 10, 13, 14, 15, and 24, and the survey of the meanders of the left bank of the Green River, in T. 25 S., R. 17 1/2 E., Salt Lake Meridian, Utah.

HISTORY OF SURVEYS

	Surveyed by		Retr. or Resurveyed by	
SOUTH BOUNDARY (Fifth Standard Parallel South)				
All	C.F. Moore	1928		
EAST BOUNDARY				
All	L.P. Lewis & C.A. Swiatek	1954		
Portion			S.A. Burkhardt	2012
WEST BOUNDARY				
Portion	C.F. Moore	1934		
NORTH BOUNDARY				
All	H.W. Miller	1911		
Portion			S.A. Burkhardt	2012
SUBDIVISION				
Portion	L.P. Lewis & A. Nelson	1954		
Portion	S.A. Burkhardt	2012	S.A. Burkhardt	2012
MEANDERS OF THE LEFT BANK OF THE GREEN RIVER				
Portion	L.P. Lewis & A. Nelson	1954		

TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 1219, dated May 13, 2013.

The direction of each line is with reference to the true meridian, determined by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards for the Positional Accuracy of Cadastral Surveys when using Global Navigation Satellite Systems (GNSS)*, dated February 23, 2009. Trimble model R8 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

NOTE: Photo interpretation of aerial photography flown in 2011, 1 meter resolution, Natural Color Aerial Photography obtained from the National Agriculture Imagery Program (NAIP), was used to meander the Green River for the survey record of the left bank. The aerial photography was photo controlled with ground observation points, using the real-time kinematic global positioning system. Meander corner positions were calculated but not monumented. Distances along the surveyed lines to the meander corners are incorporated within the field notes.

Geodetic control was derived from GPS static observations, post processed by the National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS): DH6914 MC03 MESA CNTY 03 COOP CORS ARP, DH6916 MC04 MESA CNTY 04 COOP CORS ARP, and DL3522 MC06 MACK CORS ARP.

The geographic position of the corner of sections 2, 3, 34, and 35, Tps. 24 and 25 S., Rs. 17 and 17 1/2 E., as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: **38°40'21.820" N.**,
 Longitude: **110°01'21.488" W.**, N.A.D. 83 (2011), EPOCH: 2010.00,
 Network Accuracy = 0.200 meter at 95% confidence.

The geographic position of the corner of sections 25, 30, 31, and 36, T. 25 S., Rs. 17 1/2 and 18 E., as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: **38°35'37.748" N.**,
 Longitude: **109°59'08.229" W.**, N.A.D. 83 (2011), EPOCH: 2010.00,
 Network Accuracy = 0.200 meter at 95% confidence.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

Dependent Resurvey of a Portion of the East Boundary,
T. 25 S., R. 17 1/2 E., Salt Lake Meridian, Utah

The Reestablishment of the Survey Executed by L.P. Lewis
and C.A. Swiatek in 1954

Beginning at the corner of sections 25, 30, 31, and 36, on the east boundary of T. 25 S., R. 17 1/2 E., monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 3 inches above a mound of stone, 5 feet diameter, 1 foot high, with brass cap marked as described in the official record of the 1954 survey.

From which the remaining 1954 bearing trees

A juniper, 9 inches diameter, bears S. 64°15'W., 79 links distance, marked S36 BT.

A juniper, 9 inches diameter, bears N. 77°15'W., 30 links distance, marked BT.

Set a steel fence post southwest of the corner.

Corner is located on a mesa top, in an area of exposed sandstone bedrock and juniper trees.

N. 0°01.4'W., between sections 25 and 30, on the east boundary of the township.

40.020 The 1/4 section corner of sections 25 and 30, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above a mound of stone, 4 feet diameter, 1 1/2 feet high, with brass cap marked as described in the official record of the 1954 survey.

Set a steel fence post south of the corner.

Corner is located on the edge of a mesa top, south of a steep drop-off.

N. 0°01.9'W., beginning new measurement.

40.027 The corner of sections 19, 24, 25, and 30, monumented with an iron post, 1 inch diameter, firmly set, flush in a mound of stone, 4 feet diameter, 2 feet high, with brass cap marked as described in the official record of the 1954 survey.

Corner is located on top of a sandstone mesa, approximately 700 feet above and to the east of the Green River.

N. 0°01.7'W., between sections 19 and 24, on the east boundary of the township.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 39.980** The 1/4 section corner of sections 19 and 24, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above an embedded mound of stone, 3 feet diameter, with brass cap marked as described in the official record of the 1954 survey.

Set a steel fence post east of the corner.

Corner is located in an area of sandstone ledges, with juniper trees and blackbrush.

N. 0°01.4 'W., beginning new measurement.

- 20.023** Point for the N 1/16 section corner of sections 19 and 24.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inch stem, flush with sandstone, in epoxy bond, with magnet at base of stem, into a drill hole on solid rock, marked

T25S
R17 1/2E R18E
N 1/16
S24 | S19
2013

Raise a mound of stone south of the corner.

Corner is located in an area of gently-rolling sandstone bedrock.

- 40.046** The corner of sections 13, 18, 19, and 24, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 9 inches above an embedded mound of stone, 3 feet diameter, with brass cap marked as described in the official record of the 1954 survey.

Rehabilitate mound of stone to 2 1/2 feet diameter, to cap.

Corner is located next to a two-track road.

N. 0°01.4 'W., between sections 13 and 18, on the east boundary of the township.

- 20.022** Point for the S 1/16 section corner of sections 13 and 18. Not monumented.

- 40.044** The 1/4 section corner of sections 13 and 18, monumented with an iron post, 1 inch diameter, firmly set, projecting 9 inches above a mound of stone, 4 feet diameter, 1 foot high, with brass cap marked as described in the official record of the 1954 survey.

Set a steel fence post alongside the corner.

Corner is located in an area of sandstone ledges.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

N. 0°01.3'W., beginning new measurement.

- 39.025** The witness corner to the corner of sections 7, 12, 13, and 18, monumented with an iron post, 1 inch diameter, firmly set, in a hole drilled in sandstone bedrock, projecting 1 inch above a mound of stone, 3 feet diameter, 1 1/2 feet high, with brass cap marked as described in the official record of the 2012 resurvey.

Corner is located on a small sandstone ledge, on a sandstone bedrock point bearing East-West, on the easterly rim of Spring Canyon.

N. 0°01.6'W., beginning new measurement.

- 1.000** True point for the corner of sections 7, 12, 13, and 18, at record distance, falls on a steep NW slope of cliffs.

Dependent Resurvey of a Portion of the North Boundary,
T. 25 S., R. 17 1/2 E., Salt Lake Meridian, Utah

The Reestablishment of the Survey Executed by H.W. Miller in 1911

From the corner of sections 2, 3, 34, and 35, on the north boundary of T. 25 S., R. 17 1/2 E., monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above a mound of stone, 4 feet diameter, 2 1/2 feet high, with brass cap marked as described in the official record of the 1954 survey of the subdivisional lines by L.P. Lewis and A. Nelson in 1954.

Corner is located on sloping sandstone bedrock.

N. 89°59.3'W., between sections 3 and 34, on the north boundary of the township.

- 40.026** The 1/4 section corner of sections 3 and 34, monumented with an iron post, 1 inch diameter, firmly set, projecting 11 inches above the ground, with brass cap marked as described in the official record of the 1911 survey.

Corner is located in gently-rolling ground, with exposed sandstone bedrock and sandy soil.

S. 89°56.3'W., beginning new measurement.

- 40.016** The corner of sections 3, 4, 33, and 34, monumented with an iron post, 3 inches diameter, firmly set, projecting 8 inches above a mound of stone, 3 1/2 feet diameter, 3 feet high, with brass cap marked as described in the official record of the 1954 survey of the subdivisional lines by L.P. Lewis and A. Nelson in 1954.

There is no remaining evidence of the 1911 witness mound of

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

stone.

Corner is located on level, gently-rolling ground, with exposed sandstone bedrock and sandy soil.

S. 89°58.8'W., between sections 4 and 33, on the north boundary of the township.

- 40.019** The 1/4 section corner of sections 4 and 33, monumented with an iron post, 1 inch diameter, firmly set, projecting 6 inches above a mound of stone, 3 feet diameter, 1 1/2 feet high, with brass cap marked as described in the official record of the 1911 survey.

With a mound of stone, 3 feet diameter, 2 feet high, north of the corner.

Corner is located on sandstone bedrock, east of a canyon extending north and south.

N. 89°44.9'W., beginning new measurement.

- 39.676** The corner of sections 4, 5, 32, and 33, monumented with an iron post, 3 inches diameter, firmly set, projecting 16 inches above a mound of stone, 3 feet diameter, 3 feet high, with brass cap marked as described in the official record of the 1911 survey.

Add marks "R17 1/2 E", and "2013" to cap.

Corner is located on the east side of Ten Mile Canyon, above a creek, in sagebrush.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 17 1/2 E., Salt Lake Meridian, Utah

The Reestablishment of the Survey Executed by
L.P. Lewis and A. Nelson in 1954

From the corner of sections 25, 30, 31, and 36, on the east boundary of the township, hereinbefore described.

N. 89°58.7'W., between sections 25 and 36.

- 39.899** The 1/4 section corner of sections 25 and 36, monumented with an iron post, 2 1/2 inches diameter, firmly set, buried 2 feet below the ground, with brass cap marked as described in the official record of the 1954 survey.

This corner now also functions as the witness corner to the meander corner of sections 25 and 36 on the left bank of the Green River.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

Corner is located on the floodplain of the Green River, with dense Tamarisk brush.

- 42.260** Point for the 1954 meander corner of sections 25 and 36, on the left bank of the Green River, at record distance. There is no remaining evidence of the iron post.
- 42.645** True point for the meander corner of sections 25 and 36, on the left bank of the Green River.

The Reestablishment of the Survey Executed by
S.A. Burkhardt in 2012

From the corner of sections 10, 11, 14, and 15, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 2 inches above the ground, in a collar of stone, 2 feet diameter, with aluminum cap marked as described in the official record of the 2012 survey.

With a steel fence post north of the corner.

Corner is located in broken terrain with sandstone ledges, south of a narrow wash, course N. 35° W.

N. 0°02.8' W., between sections 10 and 11.

- 40.038** The 1/4 section corner of sections 10 and 11, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, flush in a mound of stone, 4 feet diameter, 2 feet high, to cap, with an aluminum cap marked as described in the official record of the 2012 survey.

With a steel fence post north of the corner.

Corner is located on a south-facing rocky slope, at the base of a vertical sandstone cliff to the north.

N. 0°02.8' W., beginning new measurement.

- 20.019** Point for the N 1/16 section corner of sections 10 and 11.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inch stem, flush with sandstone, in epoxy bond, with magnet at base of stem, into a drill hole on solid rock, marked

T25S R171/2E
N 1/16
S10 | S11
2013

Raise a mound of stone north of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

Corner is located in sandstone ledges.

- 40.038** The corner of sections 2, 3, 10, and 11, monumented with an iron post, 1 inch diameter, firmly set, in a hole drilled in sandstone bedrock, projecting 20 inches above the surface, with brass cap marked as described in the official record of the 2012 resurvey.

The Reestablishment of the Survey Executed by
L.P. Lewis and A. Nelson in 1954

N. 0°00.1'E., between sections 2 and 3.

- 40.048** The 1/4 section corner of sections 2 and 3, monumented with an iron post, 1 inch diameter, firmly set, projecting 10 inches above sandstone bedrock, with brass cap marked as described in the official record of the 1954 survey.

Corner is located in an area of sandstone bedrock outcrops with juniper trees and brush.

N. 0°00.7'E., beginning new measurement.

- 40.043** The 80 1/16 section corner of sections 2 and 3, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 9 inches above a mound of stone, 4 feet diameter, 1 1/2 feet high, with brass cap marked as described in the official record of the 1954 survey.

From which the 1954 bearing trees

A juniper, 7 inches diameter, bears S.11°E., 140 links distance, marked 1/16 S2 80 BT.

A juniper, 5 inches diameter, bears S.74°15'W., 73 links distance, marked BT.

Set a steel fence post north of the corner.

Corner is located in an area of exposed sandstone bedrock, with blackbrush and Mormon tea.

N. 0°00.2'E., beginning new measurement.

- 35.226** The corner of sections 2, 3, 34, and 35, on the north boundary of the township, hereinbefore described.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Survey of a Portion of the Subdivisional Lines,
T. 25 S., R. 17 1/2 E., Salt Lake Meridian, Utah

From the corner of sections 19, 24, 25, and 30, on the east boundary of the township, hereinbefore described.

N. 89°55.9'W., between sections 24 and 25.

40.030 Point for the 1/4 section corner of sections 24 and 25.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at base, with aluminum cap marked

T25S R171/2E
S24
1/4 —————
S25
2013

Set a steel fence post north of the corner.

This corner also functions as the witness corner to the meander corner of sections 24 and 25 on the left bank of the Green River.

Corner is located on fairly level bench, southwest of a jeep trail and east of a patch of tamarisk brush.

42.672 True point for the meander corner of sections 24 and 25 on the left bank of the Green River.

From the corner of sections 13, 18, 19, and 24, on the east boundary of the township, hereinbefore described.

N. 89°57.0'W., between sections 13 and 24.

20.015 True point for the E 1/16 section corner of sections 13 and 24. Point falls on a location that is inaccessible due to vertical cliffs.


Point selected for the witness corner for the E 1/16 section corner of sections 13 and 24, bears S.0°01.7'E., 5.010 chains distance, hereinafter described.

39.849 Point selected for the witness corner to the 1/4 section corner of sections 13 and 24.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground, with magnet at base, in a mound of stone, 4 feet diameter, to cap, with aluminum cap marked

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS




Set a steel fence post northwest of the corner.

Corner is located in an area of large boulders, above a steep west-facing slope.

40.030 True point for the 1/4 section corner of sections 13 and 24. Point falls on an unstable slope where it is impracticable to set a permanent monument.

80.060 Point for the corner of sections 13, 14, 23, and 24.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, on sandstone bedrock, with magnet at base, in a mound of stone, 4 feet diameter, to cap, with aluminum cap marked



Set a steel fence post southwest of the corner.

This corner also functions as the witness corner to the meander corner of sections 23 and 24 on the left bank of the Green River, and as the witness corner to the meander corner of sections 14 and 23 on the left bank of the Green River.

Corner is located on a steep southwest-facing talus slope, above and northeast of the Green River.

S. 0°02.2'E., between sections 23 and 24.

6.110 True point for the meander corner of sections 23 and 24 on the left bank of the Green River.

From the corner of sections 13, 14, 23, and 24.

N. 0°02.2'W., between sections 13 and 14.

40.000 Point for the 1/4 section corner of sections 13 and 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, to bedrock, with magnet at base, in a

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

collar of stone, 2 feet diameter, with aluminum cap marked

T25S R171/2E
1/4
S14 | S13
2013

Set a steel fence post east of the corner.

Corner is located in gently-rolling ground, with blackbrush.

60.000 Point for the N 1/16 section corner of sections 13 and 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, to bedrock, with magnet at base, in a mound of stone, 3 feet diameter, to cap, with aluminum cap marked

T25S R171/2E
N 1/16
S14 | S13
2013

Set a steel fence post northwest of the corner.

Corner is located in exposed sandstone bedrock, with blackbrush.

80.000 The corner of sections 11, 12, 13, and 14, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 3 inches above the ground, with aluminum cap marked as described in the official record of the 2012 survey.

With a steel fence post north of the corner.

Corner is located on a gentle northwest-facing slope, with blackbrush and Mormon tea.

From the corner of sections 13, 14, 23, and 24.

WEST, between sections 14 and 23.

9.101 True point for the meander corner of sections 14 and 23, on the left bank of the Green River.

From the point for the corner of sections 14, 15, 22, and 23.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, to bedrock, with magnet at base, in a mound of stone, 2 1/2 feet diameter, to cap, with aluminum cap marked

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T25S R171/2E

S15	S14
S22	S23

2013

Set a steel fence post east of the corner.

Corner is located on a rocky mesa top.

EAST, between sections 14 and 23.

- 15.767** Point selected for the witness corner to the meander corner of sections 14 and 23 on the left bank of the Green River.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with magnet at base, with aluminum cap marked

WC				
T25S R171/2E				
<table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">S14</td> <td style="border-left: 1px solid black; padding: 0 5px;">MC</td> </tr> <tr> <td style="border-bottom: 1px solid black; padding: 0 5px;">→</td> <td style="border-left: 1px solid black; padding: 0 5px;">S23</td> </tr> </table>	S14	MC	→	S23
S14	MC			
→	S23			

2013

Set a steel fence post northeast of the corner.

Corner is located east of a jeep trail, in shadscale brush.

- 22.862** True point for the meander corner of sections 14 and 23 on the left bank of the Green River.

From the corner of sections 14, 15, 22, and 23.

S. 0°02.9'E., between sections 22 and 23.

- 40.000** Point for the 1/4 section corner of sections 22 and 23.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with magnet at base, in a collar of stone, 3 feet diameter, with aluminum cap marked

T25S R171/2E

1/4		
<table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S22</td> <td style="padding: 0 5px;">S23</td> </tr> </table>	S22	S23
S22	S23	

2013

Set a steel fence post east of the corner.

Corner is located at the top of a south-facing talus slope, at


SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

the base of a vertical cliff.

- 56.426** Point selected for the witness corner to the meander corner of sections 22 and 23 on the left bank of the Green River.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with magnet at base, with aluminum cap marked



Set a steel fence post east of the corner.

Corner is located southeast of, and at the base of, a steep talus slope.


- 68.466** True point for the meander corner of sections 22 and 23 on the left bank of the Green River.

From the corner of sections 14, 15, 22, and 23.

N. 0°02.9'W., between sections 14 and 15.

- 40.000** Point for the 1/4 section corner of sections 14 and 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground, to bedrock, with magnet at base, in a mound of stone, 3 feet diameter, to cap, with aluminum cap marked



Set a steel fence post northeast of the corner.

Corner is located in rolling, rocky ground, with blackbrush.

- 60.000** Point for the N 1/16 section corner of sections 14 and 15.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inch stem, flush with sandstone, in epoxy bond, with magnet at base of stem, into a drill hole on solid rock, marked

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T25S R171/2E

N 1/16

S15 | S14

2013

Raise a mound of stone, 1 1/2 feet diameter, 1 1/2 feet high,
north of the corner.

Corner is located in sandstone ledges.

80.000 The corner of sections 10, 11, 14, and 15.

From the corner of sections 14, 15, 22, and 23.

N. 89°56.7'W., between sections 15 and 22.

20.010 Point for the E 1/16 section corner of sections 15 and 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29
inches in the ground, with magnet at base, with aluminum cap
marked

T25S R171/2E

S15

E 1/16 ———

S22

2013

Set a steel fence post north of the corner.

Corner is located on a mesa top, with blackbrush.

40.020 Point for the 1/4 section corner of sections 15 and 22.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inch stem,
flush with sandstone, in epoxy bond, with magnet at base of stem,
into a drill hole on solid rock, marked

T25S R171/2E

S15

1/4 ———

S22

2013

Raise a mound of stone, 2 feet diameter, 2 feet high, north of
the corner.

Corner is located in sandstone ledges.

80.040 True point for the corner of sections 15, 16, 21, and 22, falls


SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

on a rock face where it is impracticable to set a permanent monument.

Point selected for an offline witness corner of sections 15, 16, 21, and 22, bears N. 47°05.0'W., 0.098 chains distance.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, on sandstone bedrock, with magnet at base, in a mound of stone, 3 feet diameter, to cap, with aluminum cap marked



Set a steel fence post northwest of the corner.

This corner also functions an offline witness corner to the meander corner of sections 16 and 21 on the left bank of the Green River, and as an offline witness corner to the meander corner of sections 21 and 22 on the left bank of the Green River.

Corner is located in a bedrock fracture.

S. 0°03.7'E., between sections 21 and 22.

- 8.059** True point for the meander corner of sections 21 and 22 on the left bank of the Green River.

From this true point, the offline witness corner for the meander corner of sections 21 and 22, on the left bank of the Green River, bears N. 0°34.1'W., 8.126 chains distance.

From this same true point, the true point for the meander corner of sections 21 and 22 on the left bank of the Green River bears S. 0°03.7'E., 18.877 chains distance.

From the true point for the meander corner of sections 21 and 22 on the left bank of the Green River.

S. 0°03.7'E., between sections 21 and 22.


- 1.929** Point selected for the witness corner to the meander corner of sections 21 and 22 on the left bank of the Green River.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground, with magnet at base, in a mound of stone, 3 feet diameter, to cap, with aluminum cap marked

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

WC
T25S R171/2E




Corner is located on a small hill, east of a jeep trail.

- 13.064** Point for the 1/4 section corner of sections 21 and 22, falls on inaccessible ledge, where it is impracticable to set a permanent monument.

- 44.260** Point selected for the witness corner to the meander corner of sections 21 and 22 on the left bank of the Green River.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with magnet at base, with aluminum cap marked

WC
T25S R171/2E



Set a steel fence post south of the corner.

Corner is located at the base of a talus slope, north of a jeep trail.

- 47.762** True point for the meander corner of sections 21 and 22 on the left bank of the Green River.

From this true point, the true point for the meander corner of sections 21 and 28 on the left bank of the Green River bears S. 68°45.1'W., 14.630 chains distance.

From the true point for the corner of sections 15, 16, 21, and 21.

WEST, between sections 16 and 21.

- 3.298** True point for the meander corner of sections 16 and 21 on the left bank of the Green River.

From this true point, the offline witness corner for the meander corner of sections 16 and 21, on the left bank of the Green River, bears N. 88°48.8'E., 3.227 chains distance.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the true point for the corner of sections 15, 16, 21, and 22.

N. 0°03.7'W., between sections 15 and 16.

40.000 Point for the 1/4 section corner of sections 15 and 16.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inch stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, marked

T25S R171/2E
1/4
S16 | S15
2013

Corner is located on a mesa top, on exposed sandstone bedrock.

80.000 True point for the corner of sections 9, 10, 15, and 16, falls on a vertical rock face where it is impracticable to set a permanent monument.

Point selected for an offline witness corner of sections 9, 10, 15, and 16, bears N. 64°27.5'E., 0.296 chains distance.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 6 inches in the ground, to bedrock, with magnet at base, in a mound of stone, 4 feet diameter, to cap, with aluminum cap marked

WC
T25S R171/2E
S9 | S10
S16 | S15
↙ 2013

Corner is located on the edge of a mesa top, with a vertical drop-off to the southwest.

From the corner of sections 10, 11, 14, and 15.

N. 89°56.7'W., between sections 10 and 15.

20.010 Point for the E 1/16 section corner of sections 10 and 15. Not monumented.

40.020 Point for the 1/4 section corner of sections 10 and 15.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inch stem, flush with the surface of a 12x8x4 feet, sandstone boulder, in epoxy bond, into a drill hole on solid rock, marked

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T25S R171/2E
S10
1/4 —————
S15
2013

Set a steel fence post in a mound of stone southwest of the corner.

Corner is located in sandstone ledges.

60.030 Point for the W 1/16 section corner of sections 10 and 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in a bedrock fracture, with magnet at base, in a mound of stone, 3 feet diameter, to cap, with aluminum cap marked

T25S R171/2E
S10
W 1/16 —————
S15
2013

Corner is located in an area of fractured sandstone bedrock.

80.040 The true point for the corner of sections 9, 10, 15, and 16.

WEST, between sections 9 and 16.

25.820 Point selected for the witness corner to the meander corner of sections 9 and 16 on the left bank of the Green River.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with magnet at base, with aluminum cap marked

WC
T25S R171/2E
S9
MC ← —————
S16
2013

Set a steel fence post north of the corner.

Corner is located above the floodplain of the Green River, 10 feet distance west of the centerline of a jeep trail, 6 feet wide, course N. 25° E.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 28.716** True point for the meander corner of sections 9 and 16 on the left bank of the Green River.

From the true point for the corner of sections 9, 10, 15, and 16.

N. 0°03.5'W., between sections 9 and 10.

- 36.390** Point selected for the witness corner to the 1/4 section corner of sections 9 and 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with magnet at base, in a collar of stone, with aluminum cap marked

WC
T25S R171/2E

1/4
S9 ↑ S10

2013

Set a steel fence post north of the corner.

This corner also functions as the witness corner to the meander corner of sections 9 and 10 on the left bank of the Green River.

Corner is located above the floodplain of the Green River.

- 40.000** True point for the 1/4 section corner of sections 9 and 10, falls in an area subject to flooding, where it is impracticable to set a permanent monument.
- 40.895** True point for the meander corner of sections 9 and 10 on the left bank of the Green River.

From the corner of sections 2, 3, 10 and 11.

WEST, between sections 3 and 10.

- 20.010** Point for the E 1/16 section corner of sections 3 and 10. Not monumented.
- 40.020** Point for the 1/4 section corner of sections 3 and 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground, with magnet at base, in a mound of stone, 3 feet diameter, to cap, with aluminum cap marked

T25S R171/2E
S3
1/4 ———
S10

2013

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located on a fairly level bench, west of a sandstone hill.

- 56.190** Point for the meander corner of sections 3 and 10 on the left bank of the Green River. Not monumented.

From this point, the true point for the meander corner of sections 4 and 9 on the left bank of the Green River bears WEST, 52.258 chains distance.

From the corner of sections 3, 4, 33, and 34, on the north boundary of the township, hereinbefore described.

S. 0°00.4'E., between sections 3 and 4.

- 35.281** Point for the 80 1/16 section corner of sections 3 and 4.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inch stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, marked

T25S R171/2E
1/16
S4 | S3
80
2013

Raise a mound of stone, 2 feet diameter, 2 feet high, south of the corner.

Corner is located on a mesa top, with rolling sandstone bedrock, near a primitive road.

- 60.910** Point selected for the witness corner to the meander corner of sections 3 and 4 on the left bank of the Green River.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, in a fracture in the sandstone bedrock, with magnet at base, in a mound of stone, 3 feet diameter, to cap, with aluminum cap marked

WC
T25S R171/2E
S4 | S3
↓
MC
2013

Corner is located on a cliff edge, immediately north of a tributary canyon to the Green River.

- 71.669** True point for the meander corner of sections 3 and 4 on the left

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS


bank of the Green River.

From the true point for the meander corner of sections 21 and 28 on the left bank of the Green River.

WEST, between sections 21 and 28.

- 9.650** Point selected for the witness corner to the meander corner of sections 21 and 28 on the left bank of the Green River.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with magnet at base, in a collar of stone, 2 1/2 feet diameter, with aluminum cap marked




Set a steel fence post north of the corner.

Corner is located at the base of a rocky slope, north of a jeep trail.

- 26.359** Point for the 1/4 section corner of sections 21 and 28.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground, to bedrock, with magnet at base, in a mound of stone, 4 feet diameter, to cap, with aluminum cap marked



Set a steel fence post west of the corner.

Corner is located on an east-facing slope, in rocky ledges.


- 66.359** True point for the corner of sections 20, 21, 28, and 29, falls on a fractured rock face where it is impracticable to set a permanent monument.

Point selected for an offline witness corner of sections 20, 21, 28, and 29, bears S. 13°30.5'W., 0.013 chains distance.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 6 inches in the ground, with magnet at base, in a mound of stone, 2 feet diameter, to cap, with aluminum cap marked

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS



Set a steel fence post east of the corner.

Corner is located in broken, rocky ledges.

S. 0°04.4'E., between sections 28 and 29.

- 10.915** Point for the meander corner of sections 28 and 29 on the left bank of the Green River. Not monumented.

From the true point for the corner of sections 20, 21, 28, and 29.

WEST, between sections 20 and 29.

- 17.880** Point for the meander corner of sections 20 and 29 on the left bank of the Green River. Not monumented.

From the true point for the corner of sections 20, 21, 28, and 29.


N. 0°04.4'W., between sections 20 and 21.

- 40.000** Point for the 1/4 section corner of sections 20 and 21, falls on north slope where it is impracticable to set a permanent monument.

- 50.755** Point selected for the witness corner to the meander corner of sections 20 and 21 on the left bank of the Green River.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with magnet at base, in a collar of stone, 2 feet diameter, with aluminum cap marked

WC
T25S R171/2E



Set a steel fence post northwest of the corner.

Corner is located on a small hill, south of a jeep trail.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 51.994** True point for the meander corner of sections 20 and 21 on the left bank of the Green River.


From the true point for the meander corner of sections 4 and 9 on the left bank of the Green River. Not monumented.

WEST, between sections 4 and 9.

- 11.439** True point for the 1/4 section corner of sections 4 and 9, falls on inaccessible sandstone bedrock.

- 17.376** Point selected for the witness corner to the 1/4 section corner of sections 4 and 9.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inch stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, marked




2013

Raise a mound of stone north of the corner.

Corner is located on sandstone bluffs, above the Green River.

- 32.756** Point selected for the witness corner to the meander corner of sections 4 and 9 on the left bank of the Green River.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inch stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, marked



2013

Raise a mound of stone, 2 feet diameter, 2 feet high, south of the corner.

Corner is located on a sandstone mesa top, above the Green River.

- 44.002** True point for the second meander corner of sections 4 and 9 on the left bank of the Green River.

From the corner of sections 4, 5, 32, and 33, on the north

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS


boundary of the township, hereinbefore described.

S. 0°01.1'E., between sections 4 and 5.

35.441 True point for the 80 1/16 section corner of sections 4 and 5, falls on an unstable slope where it is impracticable to set a permanent monument.

38.679 Point selected for the witness corner to the 80 1/16 section corner of sections 4 and 5.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inch stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, marked




Raise a mound of stone, 1 1/2 feet diameter, 1 1/2 feet high, north of the corner.

Corner is located on a sandstone bench, at the top of a cliff band, above and to the south of Tenmile Wash.

54.693 Point selected for the witness corner to the meander corner of sections 4 and 5 on the left bank of the Green River.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inch stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, marked



Raise a mound of stone, 2 feet diameter, 2 feet high, south of the corner.

Corner is located on a sandstone bedrock cliff edge, immediately north of the Green River.

55.567 True point for the meander corner of sections 4 and 5 on the left bank of the Green River.

CHAINS

THE SUBDIVISION OF SECTION 10,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

The Subdivision of Section 10,
T. 25 S., R. 17 1/2 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 10 and 15.

N. 0°03.2'W., on the N-S centerline of section 10.

- 40.019** Point for the center 1/4 section corner of section 10, at the intersection with the E-W centerline.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inch stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, marked

T25S R17 1/2E
C 1/4 S10
2013

Raise a mound of stone north of the corner.

Corner is located on a sandstone bedrock bench, north of Hey Joe Canyon.

- 60.029** Point for the center N 1/16 section corner of section 10. Not monumented.

- 80.039** The 1/4 section corner of sections 3 and 10.
-

From the 1/4 section corner of sections 10 and 11.

N. 89°58.4'W., on the E-W centerline of section 10.

- 20.010** Point for the center E 1/16 section corner of section 10, falls in inaccessible canyon. Not monumented.

- 40.020** The center 1/4 section corner of section 10.

- 80.040** The true point for the 1/4 section corner of sections 9 and 10.
-

From the point for the center E 1/16 section corner of section 10.

N. 0°03.0'W., on the N-S centerline of the NE 1/4 of section 10.

- 20.014** Point for the NE 1/16 section corner of section 10, at the intersection with the E-W centerline of the NE 1/4 of section 10.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inch stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, marked

THE SUBDIVISION OF SECTION 10,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

T25S R17 1/2E
NE 1/16 S10
2013

Raise a mound of stone northwest of the corner.

Corner is located on a fairly level sandstone bedrock bench.

40.028 The point for the E 1/16 of sections 3 and 10.

From the N 1/16 section corner of sections 10 and 11.

N. 89°59.2'W., on the E-W centerline of the NE 1/4 of section 10.

20.010 The NE 1/16 section corner of section 10.

40.020 The point for the center N 1/16 section corner of section 10.

The Subdivision of Section 13,
T. 25 S., R. 17 1/2 E., Salt Lake Meridian, Utah

From the true point for the 1/4 section corner of sections 13 and 24.

N. 0°01.8'W., on the N-S centerline of section 13.

20.011 Point for the center S 1/16 section corner of section 13.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with magnet at base, with aluminum cap marked

T25S R17 1/2E
C
S1/16 | S13
C
2013

Set a steel fence post northwest of the corner.

Corner is located in sandy soil, in a valley bottom.

40.022 Point for the center 1/4 section corner of section 13, at the intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, to bedrock, with magnet at base, in a collar of stone, 3 feet diameter, with aluminum cap marked

THE SUBDIVISION OF SECTION 13,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T25S R171/2E

C 1/4 S13

2013

Set a steel fence post southwest of the corner.

Corner is located on a very steep, east-facing rocky slope, at the base of a vertical cliff to the west.

- 80.036** The 1/4 section corner of sections 12 and 13, monumented with a brass tablet, 3 1/4 inches diameter, firmly set, flush with sandstone, marked as described in the official record of the 2012 survey.

From the 1/4 section corner of sections 13 and 18, on the east boundary of the township, hereinbefore described.

N. 89°58.9'W., on the E-W centerline of section 13.

- 20.015** Point for the center E 1/16 section corner of section 13. Not monumented.
- 40.030** The center 1/4 section corner of section 13.
- 80.060** The 1/4 section corner of sections 13 and 14.

From the true point for the E 1/16 section corner of sections 13 and 24.

N. 0°01.6'W., on the N-S centerline of the SE 1/4 of section 13.

- 20.016** Point for the SE 1/16 section corner of section 13, at the intersection with the E-W centerline of the SE 1/4 of section 13.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, on sandstone bedrock, with magnet at base, in a mound of stone, 3 feet diameter, to cap, with aluminum cap marked

T25S R171/2E

SE 1/16 S13

2013

Set a steel fence post north of the corner.

Corner is located in a rocky drainage, at the base of a vertical cliff to the north.

- 40.032** The point for the center E 1/16 section corner of section 13.

From the point for the S 1/16 section corner of sections 13 and 18, on the east boundary of the township.

THE SUBDIVISION OF SECTION 13,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

N. 89°58.0'W., on the E-W centerline of the SE 1/4 of section 13.

20.015 The SE 1/16 section corner of section 13.

40.030 The center S 1/16 section corner of section 13.

The Subdivision of Section 14,
T. 25 S., R. 17 1/2 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 11 and 14, monumented with a brass tablet, 3 1/4 inches diameter, firmly set, flush with sandstone, marked as described in the official record of the 2012 survey.

With a mound of stone, 2 feet diameter, 2 feet high, north of the corner.

Corner is located on a fairly level sandstone bedrock bench.

S. 0°02.6'E., on the N-S centerline of section 14.

20.000 Point for the center N 1/16 section corner of section 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with magnet at base, with aluminum cap marked

T25S R17 1/2E

C

N1/16 | S14

C

2013

Set a steel fence post east of the corner.

Corner is located on a mesa top, with blackbrush.

40.000 Point for the center 1/4 section corner of section 14, at the intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with magnet at base, with aluminum cap marked

T25S R17 1/2E

C 1/4 S14

2013

Set a steel fence post north of the corner.

Corner is located on a mesa top, with blackbrush.

THE SUBDIVISION OF SECTION 14,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 71.139** Point for the special meander corner of the left bank of the Green River. Not monumented.
-

From the 1/4 section corner of sections 13 and 14.

WEST, on the E-W centerline of section 14.

- 40.011** The center 1/4 section corner of section 14.

- 80.022** The 1/4 section corner of sections 14 and 15.
-

From the N 1/16 section corner of sections 13 and 14.

WEST, on the E-W centerline of the NE 1/4 of section 14.

- 40.012** The center N 1/16 section corner of section 14.
-

From the center N 1/16 section corner of section 14.

WEST, on the E-W centerline of the NW 1/4 of section 14.

- 40.010** The N 1/16 section corner of sections 14 and 15.
-

The Subdivision of Section 15,
T. 25 S., R. 17 1/2 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 15 and 22.

N. 0°03.3'W., on the N-S centerline of section 15.

- 40.000** Point for the center 1/4 section corner of section 15, at the intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with magnet at base, with aluminum cap marked

T25S R17 1/2E

C 1/4 S15

2013

Set a steel fence post northwest of the corner.

Corner is located in rolling, sandy hills, with blackbrush.

- 60.000** Point for the center N 1/16 section corner of section 15. Not monumented.

- 80.000** The 1/4 section corner of sections 10 and 15.
-

THE SUBDIVISION OF SECTION 15,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 14 and 15.

N. 89°56.7'W., on the E-W centerline of section 15.

20.010 Point for the center E 1/16 section corner of section 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, to bedrock, with magnet at base, in a mound of stone, 3 feet diameter, to cap, with aluminum cap marked

T25S R171/2E
E 1/16
C—————C
S15
2013

Set a steel fence post west of the corner.

Corner is located in sandstone ledges.

40.020 The center 1/4 section corner of section 15.

60.030 Point for the center W 1/16 section corner of section 15.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inch stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, marked

T25S R171/2E
W 1/16
C—————C
S15
2013

Raise a mound of stone, 2 feet diameter, 2 feet high, north of the corner.

Corner is located on sandstone mesa top, with juniper trees.

80.040 The 1/4 section corner of sections 15 and 16.

From the center E 1/16 section corner of section 15.

N. 0°03.1'W., on the N-S centerline of the NE 1/4 of section 15.

20.000 Point for the NE 1/16 section corner of section 15, at the intersection with the E-W centerline of the NE 1/4 of section 15.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inch stem, flush with sandstone, in epoxy bond, with magnet at base of stem, into a drill hole on solid rock, marked

THE SUBDIVISION OF SECTION 15,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

T25S R171/2E
NE 1/16 S15
2013

Raise a mound of stone north of the corner.

40.000 The point for the E 1/16 section corner of sections 10 and 15.

From the N 1/16 section corner of sections 14 and 15.

N. 89°56.7'W., on the E-W centerline of the NE 1/4 of section 15.

20.010 The NE 1/16 section corner of section 15.

40.020 The point for the center N 1/16 section corner of section 15.

From the E 1/16 section corner of sections 15 and 22.

N. 0°03.1'W., on the N-S centerline of the SE 1/4 of section 15.

40.000 The center E 1/16 section corner of section 15.

From the center W 1/16 section corner of section 15.

N. 0°03.5'W., on the N-S centerline of the NW 1/4 of section 15.

40.000 The W 1/16 section corner of sections 10 and 15.

The Subdivision of Section 24,
T. 25 S., R. 17 1/2 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 24 and 25.

N. 0°01.9'W., on the N-S centerline of section 24.

39.990 Point for the center 1/4 section corner of section 24, at the intersection with the E-W centerline.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inch stem, flush with sandstone, in epoxy bond, with magnet at base of stem, into a drill hole on solid rock, marked

T25S R171/2E
C 1/4 S24
2013

Corner is located on a gentle south-sloping point of sandstone bedrock, approximately 300 feet above, and to the east of the Green River.

THE SUBDIVISION OF SECTION 24,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 60.002** Point for the center N 1/16 section corner of section 24. Not monumented.
- 80.014** The true point for the 1/4 section corner of sections 13 and 24.

From the 1/4 section corner of sections 19 and 24, on the east boundary of the township, hereinbefore described.

N. 89°55.1'W., on the E-W centerline of section 24.

- 20.014** Point for the center E 1/16 section corner of section 24. Not monumented.
- 40.028** The center 1/4 section corner of section 24.
- 52.886** Point for the special meander corner on the left bank of the Green River. Not monumented.

From the point for the center E 1/16 section corner of section 24.

N. 0°01.7'W., on the N-S centerline of the NE 1/4 of section 24.

- 20.017** Point for the NE 1/16 section corner of section 24, at the intersection with the E-W centerline of the NE 1/4 of section 24.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inch stem, flush with sandstone, in epoxy bond, with magnet at base of stem, into a drill hole on solid rock, marked

T25S R17 1/2E

NE 1/16 S24

2013

Raise a mound of stone, 2 feet diameter, 2 feet high, northwest of the corner.


Corner is located on a mesa top, near the north edge of a jeep trail.

- 35.024** Point selected for the witness corner to the E 1/16 section corner of sections 13 and 24.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground, to bedrock, with magnet at base, in a mound of stone, 4 feet diameter, to cap, with aluminum cap marked

THE SUBDIVISION OF SECTION 24,
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS



Corner is located on the northwesterly edge of a vertical cliff.

- 40.034** The true point for the E 1/16 section corner of sections 13 and 24.

From the N 1/16 section corner of sections 19 and 24, on the east boundary of the township, hereinbefore described.

N. 89°56.0'W., on the E-W centerline of the NE 1/4 of section 24.

- 20.014** The NE 1/16 section corner of section 24.

- 40.028** The point for the center N 1/16 section corner of section 24.

The Survey of the Meanders of the Left Bank of the Green River,
Downstream through
T. 25 S., R. 17 1/2 E., Salt Lake Meridian, Utah

The following is a survey of the meanders of the left bank of the Green River through a portion of T. 25 S., R. 17 1/2 E. Aerial photography (2011 NAIP) was used to establish some portions of the meanders in this survey.

From the true point for the meander corner of sections 4 and 5 on the left bank of the Green River.

Thence, downstream with the meanders of the left bank of the Green River through section 4.

N. 68°27.6' E.,	0.900 chains	
S. 82°36.3' E.,	3.263 chains	
S. 65°30.7' E.,	3.157 chains	
S. 72°22.4' E.,	3.491 chains	
S. 50°13.6' E.,	5.116 chains	
S. 37°10.6' E.,	4.172 chains	
S. 33°55.2' E.,	7.161 chains	
S. 0°00.8' E.,	1.998 chains	
S. 9°17.4' E.,	2.501 chains	
S. 11°23.6' W.,	4.842 chains	
S. 7°38.9' W.,	9.454 chains	
S. 18°54.1' W.,	7.307 chains	
S. 35°07.6' W.,	8.932 chains	
S. 3°33.8' W.,	1.615 chains	
S. 20°56.2' W.,	11.207 chains	The true point for the meander

THE SURVEY OF THE MEANDERS OF THE LEFT BANK OF THE GREEN RIVER,
DOWNSTREAM THROUGH
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH
corner of sections 4 and 9.

Thence, downstream with the meanders of the left bank of the Green River, through section 9.

S.20°23.5' W., 1.727 chains
S.12°18.6' W., 8.818 chains
S.16°33.1' W., 1.274 chains
S. 2°30.3' E., 3.040 chains
S.40°29.1' E., 1.323 chains
S.11°28.2' E., 2.661 chains
S.31°21.6' E., 5.334 chains
S.42°55.3' E., 4.754 chains
S.58°01.4' E., 7.165 chains
S.78°01.4' E., 5.402 chains
N.83°40.7' E., 11.712 chains
N.55°40.0' E., 6.698 chains
N.41°13.1' E., 7.066 chains
N.27°33.7' E., 6.423 chains
N.16°24.3' E., 6.779 chains
N. 8°18.7' E., 8.568 chains

The point for the meander corner of sections 4 and 9.

Thence, downstream with the meanders of the left bank of the Green River, through section 4.

N. 1°22.1' E., 11.883 chains
N. 4°45.0' W., 12.581 chains
N. 0°40.9' E., 11.273 chains
N.43°19.7' E., 8.262 chains
N.69°36.8' E., 9.212 chains
N.81°52.2' E., 3.836 chains
S.48°29.6' E., 2.113 chains
N.88°19.7' E., 4.659 chains
S.83°00.3' E., 4.718 chains

The true point for the meander corner of sections 3 and 4.

Thence, downstream with the meanders of the left bank of the Green River, through section 3.

S.83°24.0' E., 0.394 chains
S.70°03.0' E., 4.483 chains
S.47°13.3' E., 5.831 chains
S.57°45.4' E., 5.736 chains
S.47°17.4' E., 7.517 chains
S.18°30.0' E., 7.238 chains
S.28°25.8' E., 3.703 chains
S.11°51.7' E., 6.750 chains
S.33°42.4' E., 1.605 chains
S. 8°25.9' W., 3.036 chains
S. 1°58.6' E., 3.229 chains
S.11°13.7' W., 4.764 chains

THE SURVEY OF THE MEANDERS OF THE LEFT BANK OF THE GREEN RIVER,
DOWNSTREAM THROUGH
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS S.26°52.5' W., 1.071 chains The point for the meander corner of sections 3 and 10.

Thence, downstream with the meanders of the left bank of the Green River, through section 10.

S.24°47.7' W., 2.385 chains
S.13°47.3' W., 4.047 chains
S.30°54.7' W., 6.789 chains
S.23°41.6' W., 4.617 chains
S.35°47.3' W., 8.121 chains
S.29°28.2' W., 4.600 chains
S.36°35.7' W., 8.402 chains
S.32°05.2' W., 3.283 chains
S.43°58.7' W., 3.945 chains The true point for the meander corner of sections 9 and 10.

Thence, downstream with the meanders of the left bank of the Green River, through section 9.

S.30°14.2' W., 3.767 chains
S.36°56.7' W., 4.281 chains
S.44°19.3' W., 6.206 chains
S.31°18.2' W., 2.103 chains
S.40°19.6' W., 5.049 chains
S.56°51.1' W., 3.158 chains
S.33°24.8' W., 9.794 chains
S.38°11.5' W., 8.495 chains
S.16°21.0' W., 7.873 chains The true point for the meander corner of sections 9 and 16.

Thence, downstream with the meanders of the left bank of the Green River, through section 16.

S.15°47.3' W., 6.174 chains
S. 4°40.0' W., 11.070 chains
S. 6°42.1' E., 9.193 chains
S.16°21.1' E., 12.425 chains
S.25°06.3' E., 5.850 chains
S.18°45.9' E., 4.034 chains
S.29°53.2' E., 10.075 chains
S.36°31.8' E., 8.907 chains
S.25°52.8' E., 4.135 chains
S.37°42.2' E., 8.761 chains
S.16°32.4' E., 5.350 chains
S.31°37.7' E., 1.391 chains The true point for the meander corner of sections 16 and 21.

Thence, downstream with the meanders of the left bank of the Green River, through section 21.

THE SURVEY OF THE MEANDERS OF THE LEFT BANK OF THE GREEN RIVER,
DOWNSTREAM THROUGH
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

S.30°43.0' E., 3.164 chains
S.17°34.3' E., 5.601 chains The true point for the meander
corner of sections 21 and 22.

Thence, downstream with the meanders of the left bank of the Green River, through section 22.

S.17°34.3' E., 0.245 chains
S.19°46.2' E., 5.457 chains
S. 0°09.9' W., 6.710 chains
S.15°27.8' W., 7.053 chains The true point for the meander
corner of sections 21 and 22.

Thence, downstream with the meanders of the left bank of the Green River, through section 21.

S.15°27.8' W., 0.918 chains
S.29°16.8' W., 6.398 chains
S.47°04.9' W., 5.439 chains
S.66°05.0' W., 3.134 chains
S.62°31.1' W., 6.422 chains
S.78°41.4' W., 7.322 chains
S.86°31.0' W., 8.400 chains
N.72°59.9' W., 2.374 chains
N.88°58.1' W., 2.548 chains
N.80°17.9' W., 6.137 chains
N.20°51.1' W., 0.495 chains
N.75°11.3' W., 11.513 chains
N.65°52.8' W., 2.355 chains
N.76°18.8' W., 6.254 chains
N.59°03.9' W., 4.320 chains
N.75°11.0' W., 8.968 chains
N.61°18.3' W., 6.549 chains The true point for the meander
corner of sections 20 and 21.

Thence, downstream with the meanders of the left bank of the Green River, through section 20.

N.63°57.6' W., 5.740 chains
N.79°12.9' W., 12.790 chains
S.83°27.3' W., 9.542 chains
S.60°09.5' W., 8.952 chains
S.17°33.5' W., 11.912 chains
S. 3°40.2' E., 10.769 chains
S.19°37.3' E., 11.066 chains
S.34°14.2' E., 11.984 chains
S.47°04.6' E., 13.114 chains The point for the meander corner of
sections 20 and 29.

Thence, downstream with the meanders of the left bank of the Green River, through section 29.

THE SURVEY OF THE MEANDERS OF THE LEFT BANK OF THE GREEN RIVER,
DOWNSTREAM THROUGH
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

S.57°24.7' E., 13.891 chains
S.60°59.0' E., 7.079 chains The point for the meander corner of
sections 28 and 29.

Thence, downstream with the meanders of the left bank of the Green River, through section 28.

S.62°38.4' E., 9.200 chains
S.85°19.6' E., 12.574 chains
N.79°54.6' E., 10.438 chains
N.70°42.3' E., 26.440 chains
N.61°42.9' E., 11.824 chains The true point for the meander
corner of sections 21 and 28.

Thence, downstream with the meanders of the left bank of the Green River, through section 21.

N.49°52.9' E., 2.808 chains
N.67°16.0' E., 8.770 chains
N.88°15.5' E., 3.401 chains The true point for the meander
corner of sections 21 and 22.

Thence, downstream with the meanders of the left bank of the Green River, through section 22.

N.82°21.2' E., 18.708 chains
N.88°24.8' E., 14.431 chains
S.78°08.5' E., 6.944 chains
N.87°32.8' E., 26.617 chains
N.75°26.5' E., 14.133 chains The true point for the meander
corner of sections 22 and 23.

Thence, downstream with the meanders of the left bank of the Green River, through section 23.

N.42°01.2' E., 13.936 chains
N.14°42.9' E., 20.471 chains
N. 4°12.2' E., 3.124 chains
N.12°52.8' E., 36.108 chains The true point for the meander
corner of sections 14 and 23.

Thence, downstream with the meanders of the left bank of the Green River, through section 14.

N.29°38.1' E., 5.715 chains
N.45°02.8' E., 5.443 chains
N.89°07.1' E., 4.600 chains
N.63°27.7' E., 1.607 chains
S.80°29.6' E., 4.489 chains The point for the special meander

THE SURVEY OF THE MEANDERS OF THE LEFT BANK OF THE GREEN RIVER,
DOWNSTREAM THROUGH
TOWNSHIP 25 SOUTH, RANGE 17 1/2 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

corner of section 14.

S.80°29.6' E., 6.158 chains
S.87°18.2' E., 4.557 chains
S.66°53.0' E., 6.341 chains
S.75°13.7' E., 10.886 chains
S.58°59.3' E., 4.588 chains

The true point for the meander
corner of sections 14 and 23.

Thence, downstream with the meanders of the left bank of the
Green River, through section 23.

S.56°08.2' E., 10.965 chains

The true point for the meander
corner of sections 23 and 24.

Thence, downstream with the meanders of the left bank of the
Green River, through section 24.

S.60°19.2' E., 6.751 chains
S.51°43.7' E., 8.879 chains
S.42°40.3' E., 12.990 chains
S.20°21.9' E., 14.802 chains
S.13°34.2' E., 1.706 chains

The point for the special meander
corner of section 24.

S.13°34.2' E., 5.532 chains
S.19°23.4' E., 17.113 chains
S. 2°16.3' E., 5.307 chains
S.13°50.9' E., 11.973 chains
S. 6°42.0' E., 1.569 chains

The true point for the meander
corner of sections 24 and 25.

Thence, downstream with the meanders of the left bank of the
Green River, through section 25.

S. 6°56.0' E., 5.055 chains
S. 0°37.3' W., 6.132 chains
S. 2°03.5' E., 12.008 chains
S. 4°53.7' W., 2.571 chains
S.15°17.3' W., 3.317 chains
S. 1°05.3' E., 14.985 chains
S. 5°09.8' E., 11.267 chains
S. 4°21.6' W., 7.702 chains
S. 0°40.4' E., 11.928 chains
S. 7°01.3' W., 5.400 chains

The true point for the meander
corner of sections 25 and 36.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Phil Freiberg	Survey Technician

CERTIFICATE OF SURVEY

I, *Scott A. Burkhardt, Cadastral Surveyor*, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing the date of *May 13, 2013*, I have *dependently resurveyed a portion of the east and north boundaries, a portion of the subdivisional lines, surveyed a portion of the subdivisional lines, subdivided sections 10, 13, 14, 15, and 24, and surveyed the meanders of the left bank of the Green River, in Township 25 South, Range 17 1/2 East, of the Salt Lake Meridian, in the State of Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions of the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

11/12/2014

Date

Scott A. Burkhardt

Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the east and north boundaries, a portion of the subdivisional lines, the survey of a portion of the subdivisional lines, the subdivision of sections 10, 13, 14, 15, and 24, and the survey of the meanders of the left bank of the Green River, in Township 25 South, Range 17 1/2 East, Salt Lake Meridian, Utah*, executed by *Scott A. Burkhardt, Cadastral Surveyor*, having been critically examined and found correct, are hereby approved.

November 13, 2014

Date

Daniel W. Webb

Chief Cadastral Surveyor for Utah