

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY

OF

A PORTION OF THE SOUTH

(SIXTH STANDARD PARALLEL SOUTH) BOUNDARY,

A PORTION OF THE WEST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 30 AND 31,

IN

TOWNSHIP 30 SOUTH, RANGE 26 EAST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Scott A. Burkhardt
Cadastral Surveyor

Under Special Instructions dated **March 28, 2014**, approved **March 28, 2014**,
which provided for the surveys included under Group Number **1253**, and
Assignment Instructions dated **March 28, 2014**.

Survey Commenced, **October 29, 2014**
Survey Completed, **November 13, 2014**

INDEX DIAGRAM

TOWNSHIP 30 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
10					
5 30	9 29	28	27	26	25
7					
4 31	6 32	33	34	35	36
3					

Subdivision of section 30.....11
 Subdivision of section 31.....13

TOWNSHIP 30 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of a portion of the south (Sixth Standard Parallel South) boundary, a portion of the west boundary, a portion of the subdivisional lines, and the subdivision of section 30 and 31, in T. 30 S., R. 26 E., Salt Lake Meridian, Utah.

HISTORY OF SURVEYS

	Surveyed by		Retr. or Resurveyed by	
SOUTH BOUNDARY (Sixth Standard Parallel South)				
All	T.C. Rathbone & H.G. Mason	1916		
EAST BOUNDARY (Utah-Colorado State Boundary Line)				
All	R.J. Reeves	1878		
All			A.D. Wilson	1885
All			T.C. Rathbone & H.G. Mason	1916
Portion			R. Gentry	1917
WEST BOUNDARY				
All	T.C. Rathbone & H.G. Mason	1916		
NORTH BOUNDARY				
All	T.C. Rathbone & H.G. Mason	1916		
SUBDIVISION				
All	T.C. Rathbone & H.G. Mason	1916		

TOWNSHIP 30 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 1253, dated March 28, 2014.

The direction of each line is with reference to the true meridian, determined by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards for the Positional Accuracy of Cadastral Surveys when using Global Navigation Satellite Systems (GNSS)*, dated February 23, 2009. Trimble model R8 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from GPS static observations, post processed by the National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS): DL3585 MC10 MONTROSE CORS ARP, DI3419 P012 MONTICELLOUT2006 CORS ARP, and DL3642 MC09 NUCLA CORS ARP.

The geographic position of the corner of sections 19, 20, 29, and 30, T. 30 S., R. 26 E., as determined by direct RTK methods from the geodetic control, is as follows:

Latitude: **38°09'22.241" N.**,
Longitude: **109°06'03.868" W.**, N.A.D. 83 (2011), (EPOCH: 2010.00),
Network Accuracy = 0.200 meter at 95% confidence.

The geographic position of the standard corner of sections 31 and 36, T. 30 S., Rs. 25 and 26 E., as determined by direct RTK methods from the geodetic control, is as follows:

Latitude: **38°07'37.787" N.**,
Longitude: **109°07'09.865" W.**, N.A.D. 83 (2011), (EPOCH: 2010.00),
Network Accuracy = 0.200 meter at 95% confidence.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
 (SIXTH STANDARD PARALLEL SOUTH),
 T. 30 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the South Boundary
 (Sixth Standard Parallel South),
 T. 30 S., R. 26 E., Salt Lake Meridian, Utah

The Reestablishment of the Survey Executed by
 T.C. Rathbone and H.G. Mason in 1916

Beginning at the standard corner of sections 31 and 32 only, Township 30 South, Range 26 East, monumented with an iron post, 3 inches diameter, firmly set, projecting 12 inches above the ground, with brass cap marked as described in the official record of the 1916 survey.

Corner is located in a north-south fenceline, 4-strand barbed-wire, on fairly level ground, with sagebrush.

S. 89°55.3' W., between sections 6 and 31.

19.991 Point for the E 1/16 section corner of section 31 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 2 1/2 feet base, to aluminum cap marked

T30S R26E
E 1/16 S31

2014

Set a steel fence post north of the corner.

Corner is located 26 1/2 links distance south of an east-west fenceline, 4-strand barbed-wire; in fairly level ground, with sagebrush.

39.982 The standard 1/4 section corner of section 31 only, monumented with an iron post, 1 inch diameter, firmly set, projecting 7 inches above the ground, in a collar of stone, 2 1/2 feet diameter, with brass cap marked as described in the official record of the 1916 survey.

With a steel fence post (San Juan County survey marker) south of the corner.

Corner is west of a paved road.

N. 89°58.6' W., beginning new measurement.

19.991 Point for the W 1/16 section corner of section 31 only.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
 (SIXTH STANDARD PARALLEL SOUTH),
 T. 30 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 23 inches in the ground, with a magnet at base, in a collar of stone, 2 feet diameter, with aluminum cap marked

T30S R26E
W 1/16 S31

2014

Set a steel fence post north of the corner.

Corner is located 5 links distance south of an east-west fenceline, 4-strand barbed-wire; on a gentle south slope.

- 33.374** The closing corner of sections 1 and 6, T. 31 S., Rs. 25 and 26 E., bears NORTH, 0.024 chains distance, monumented with an iron post, 3 inches diameter, firmly set, flush with the ground, with brass cap marked as described in the official record of the 1916 survey.

Add marks AM and 2014 to cap.

Set a steel fence post north of the corner.

Corner is located in an east-west fenceline, 4-strand barbed-wire.

- 39.982** The standard corner of sections 31 and 36, T. 30 S., Rs. 25 and 26 E., monumented with an iron post, 3 inches diameter, firmly set, flush with the ground, with brass cap marked as described in the official record of the 1916 survey, with a scattered mound of stone north of the corner.

Set a steel fence post south of the corner.

Rehabilitate mound of stone to 2 feet base, 2 feet high, north of the corner.

Corner is located in an east-west fenceline, 4-strand barbed-wire; in fairly level ground, with sagebrush.

Dependent Resurvey of a Portion of the West Boundary
 T. 30 S., R. 26 E., Salt Lake Meridian, Utah

The Reestablishment of the Survey Executed by
 T.C. Rathbone and H.G. Mason in 1916

From the standard corner of sections 31 and 36, T. 30 S., Rs. 25 and 26 E., hereinbefore described.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY
T. 30 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0°02.5' W., between sections 31 and 36.

19.970 Point for the S 1/16 section corner of sections 31 and 36.

Set a brass tablet, 3 1/4 inch diameter, with 3 1/2 inch stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, marked

T30S
R25E R26E
S 1/16
S36 | S31
2014

Set a steel fence post northeast of the corner.

Raise a mound of stone, 2 feet base, 1 1/2 feet high, north of the corner.

Corner is located on the southeast-sloping face of exposed sandstone rock, in pinon and juniper trees.

39.940 The 1/4 section corner of sections 31 and 36, monumented with an iron post, 1 inch diameter, firmly set, projecting 6 inches above a mound of stone, 3 feet base, 1 1/2 feet high, with brass cap marked as described in the official record of the 1916 survey.

From which the 1916 bearing trees

A juniper, 8 inches diameter, bears N. 69 1/2° E., 16 links distance, marked 1/4 S31 BT (Record: bears N. 73°15' E.).

A juniper, 8 inches diameter, bears S. 61° W., 45 links distance, marked 1/4 S36 BT (Record: bears S. 57°45' W.).

Set a steel fence post northeast of the corner.

N. 0°00.3' E., beginning new measurement.

39.961 The corner of sections 25, 30, 31, and 36, monumented with an iron post, 3 inches diameter, firmly set, projecting 16 inches above the ground, with brass cap marked as described in the official record of the 1916 survey.

Three of the 1916 bearing trees are dead and down, there is no remaining evidence of the fourth bearing tree.

Set a steel fence post south of the corner.

N. 0°00.2' E., between sections 25 and 30.

19.974 Point for the S 1/16 section corner of sections 25 and 30.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY
T. 30 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

inches in the ground, with a magnet at base, with aluminum cap marked

T30S
R25E R26E
S 1/16
S25 | S30
2014

Set a steel fence post north of the corner.

Corner is located in a valley, 3 links distance East of a north-south fenceline.

- 39.948** The 1/4 section corner of sections 25 and 30, monumented with an iron post, 1 inch diameter, firmly set, projecting 16 inches above the ground, with brass cap marked as described in the official record of the 1916 survey.

One of the 1916 bearing trees is dead and down, there is no remaining evidence of the other bearing tree.

Set a steel fence post east of the corner.

N. 0°03.0' E., beginning new measurement.

- 39.894** The corner of sections 19, 24, 25, and 30, monumented with an iron post, 2 inches diameter, firmly set, projecting 12 inches above a mound of stone, 3 feet base, 1 foot high, with brass cap marked as described in the official record of the 1916 survey.

From which the remaining 1916 bearing trees

A juniper, 11 inches diameter, bears S. 27° W., 6 links distance, marked T30S R25E S25 BT.

A pinon snag, 10 inches diameter, bears N. 31° W., 40 links distance, marked T30S R25E S24 BT.

A third tree is dead and down, there is no remaining evidence of the other bearing tree.

The corner is located in dense pinon and juniper trees.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 26 E., Salt Lake Meridian, Utah

The Reestablishment of the Survey Executed by
T.C. Rathbone and H.G. Mason in 1916

From the standard corner of sections 31 and 32 only, on the south boundary of the township, hereinbefore described.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0°01.3' W., between sections 31 and 32.

19.994 Point for the S 1/16 section corner of sections 31 and 32. Not monumented.

39.988 The 1/4 section corner of sections 31 and 32, monumented with an iron post, 1 inch diameter, firmly set, projecting 13 inches above the ground, with brass cap marked as described in the official record of the 1916 survey, with a mound of stone, 2 feet base, 2 feet high, west of the corner.

From which the 1916 bearing tree

A pinon snag, 12 inches diameter, bears S. 87°05' W., 235 links distance, marked 1/4 S31 BT (Record: bears S. 88°30' W.).

Set a steel fence post north of the corner.

The corner is located 4 1/2 links distance East of a fenceline, 4-strand barbed-wire, extending north-south.

N. 0°00.2' W., beginning new measurement.

40.013 The corner of sections 29, 30, 31, and 32, monumented with an iron post, 2 inches diameter, firmly set, projecting 6 inches above a mound of stone, 3 feet base, 2 feet high, with brass cap marked as described in the official record of the 1916 survey.

From which the 1916 bearing trees

A juniper, 7 inches diameter, bears N. 82°02' E., 14 links distance, marked T30S R26E S29 BT (Record: bears N. 89° E., 16 links distance).

A juniper, 5 inches diameter, bears S. 34°29' E., 47 links distance, marked T30S R26E S32 BT (Record: bears S. 36° E., 48 links distance).

A juniper, 6 inches diameter, bears S. 40°32' W., 44 links distance, marked T30S R26E S31 BT (Record: bears S. 38°45' W., 45 links distance).

A juniper, 10 inches diameter, bears N. 25°22' W., 61 links distance, marked T30S R26E S30 BT (Record: bears N. 22° W., 59 links distance).

Set a steel fencepost north of the corner.

Corner falls on a gentle southwest slope with scattered boulders, with pinon and juniper trees.

N. 89°59.7' W., between sections 30 and 31.

10.70 Leave timber, edge bears NE and SE.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- 16.40 Wash, drains south.
17.60 Old road, bears north and south.
19.985 Point for the E 1/16 section corner of sections 30 and 31.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with a magnet at base, with aluminum cap marked

T30S R26E
 S30
E 1/16
 S31
2014

Set a steel fencepost west of the corner.

Corner is located in rolling terrain, with grass and sagebrush.

- 25.20 Enter timber, edge bears north and south.
30.00 Leave timber, edge bears NW and SE.
39.970 The 1/4 section corner of sections 30 and 31, determined at the center of a mound of stone, 2 feet base, 1 foot high. There is no remaining evidence of the 1916 iron post. However, a report submitted to this office, dated January 13, 2009, by the San Juan County Surveyor (a copy of which will be kept in the Cadastral Group File for this survey), contained photos clearly showing the iron post, 1 inch diameter, loosely set and slightly bent, projecting 20 inches above the mound of stone, with brass cap marked as described in the official record of the 1916 survey.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, in a collar of stone, 2 1/2 feet diameter, with aluminum cap marked

T30S R26E
 S30
1/4
 S31
2014

From which the 1916 bearing trees

A juniper snag, 16 inches diameter, bears S. 79° W., 242.0 links distance, marks BT visible on a partially healed blaze (Record: S. 38 1/2° W., 145 links distance, marked 1/4 S31 BT).

A juniper, 17 inches diameter, bears N. 48° W., 131 links distance, marks BT visible on a partially healed blaze (Record: N. 5° E., 89 links distance, marked 1/4 S30 BT).

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fencepost north of the corner.

Note: The blazes on the 1916 bearing trees face a point approximately one chain westerly of the mound of stone, and a point utilizing the 1916 record distances from the bearing trees also falls approximately one chain westerly of the mound of stone. However, it is the opinion of this office that in the course of the 1916 survey that, 1) the corner was erroneously set one chain to the west and the bearing trees marked before the measurement error was discovered and the corner moved to the midpoint, one chain to the east; and 2) the bearing trees were not corrected following this corner move, explaining the inaccurate orientations of their blazes and record ties. This opinion is supported by the evidence of the record distances to the topography calls along the line between sections 30 and 31, described herein, which consistently match the observed distances measured from the mound of stone, which lies N. 7° W., 7 links distance from the calculated midpoint of the section line. Therefore, it was determined that the mound of stone occupies the original location of the corner.

Corner falls in an area of flat, level ground, with sagebrush and grasses, surrounded by a circular, unimproved dirt road, southwest of an old wooden corral.

S. 89°47.8' W., beginning new measurement.

19.992 Point for the W 1/16 section corner of sections 30 and 31.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked

T30S R26E
 S30
W 1/16
 S31
2014

Set a steel fencepost north of the corner.

Corner is located in gently-rolling, open terrain, with grass and sagebrush.

39.984 The corner of sections 25, 30, 31, and 36, on the west boundary of the township, hereinbefore described.

From the corner of sections 29, 30, 31, and 32.

N. 0°00.8' W., between sections 29 and 30.

20.026 Point for the S 1/16 section corner of sections 29 and 30. Not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.052** Point for the 1/4 section corner of sections 29 and 30, at proportionate distance. There is no remaining evidence of the 1916 iron post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked

T30S R26E
1/4
S30 | S29
2014

Set a steel fencepost north of the corner.

Corner is located in fairly level terrain, with grass and sagebrush.

- 80.104** The corner of sections 19, 20, 29, and 30, monumented with an iron post, 2 inches diameter, firmly set, projecting 16 inches above the ground, with brass cap marked as described in the official record of the 1916 survey.

From which the remaining 1916 bearing trees

A pinon, 15 inches diameter, bears N. 18° E., 280 links distance, marked T30S R26E S20 BT. (Record: bears N. 19° E.)

A pinon, 10 inches diameter, bears N. 76° W., 280 links distance, marked T30S R26E S19 BT. (Record: bears N. 74° W.).

A third tree is dead and down, there is no remaining evidence of the other bearing tree.

Set a steel fencepost northwest of the corner.

S. 89°53.6' W., between sections 19 and 30.

- 39.931** The 1/4 section corner of sections 19 and 30, monumented with an iron post, 1 inch diameter, firmly set, projecting 8 inches above a mound of stone, 4 feet base, 2 feet high, with brass cap marked as described in the official record of the 1916 survey.

From which the 1916 bearing trees

A pinon, 11 inches diameter, bears N. 63° W., 30 links distance, marked 1/4 S19 BT. (Record: 26 links distance)

A juniper, 7 inches diameter, bears S. 36°20' W., 35 links distance, with partially healed blaze (Record: bears S. 40° W., 34 links distance, marked 1/4 S30 BT).

Set a steel fencepost east of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 89°31.9' W., beginning new measurement.

- 39.954 The corner of sections 19, 24, 25, and 30, on the west boundary of the township, hereinbefore described.

The Subdivision of Section 30,
T. 30 S., R. 26 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 30 and 31.

N. 0°00.6 E., on the north-south centerline of section 30.

- 19.964 Point for the center S 1/16 section corner of section 30.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 13 inches in the ground to bedrock, magnet at base, in a mound of stone, 3 feet base, to aluminum cap marked

T30S R26E
C
S 1/16 | S30
C
2014

Set a steel fencepost north of the corner.

Corner is located in pinon and juniper trees.

- 39.928 Point for the center 1/4 section corner of section 30, at intersection with the east-west centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T30S R26E
C 1/4 S30
2014

Set a steel fencepost southeast of the corner.

Corner is located on an east-sloping mesa top, with juniper trees and sagebrush.

- 80.027 The 1/4 section corner of sections 19 and 30.

From the 1/4 section corner of sections 29 and 30.

S. 89°49.6' W., on the E-W centerline of section 30.

THE SUBDIVISION OF SECTION 30,
T. 30 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- 19.976 Point for the center E 1/16 of section 30. Not monumented.
39.952 The center 1/4 section corner of section 30.
59.944 Point for the center W 1/16 of section 30. Not monumented.
79.936 The 1/4 section corner of sections 25 and 30, on the west boundary of the township, hereinbefore described.

From the E 1/16 section corner of sections 30 and 31.

N. 0°00.1' W., on the north-south centerline of the SE 1/4 of section 30.

- 19.995 Point for the SE 1/16 section corner of section 30, at the intersection with the east-west centerline of the SE 1/4 of section 30.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T30S R26E
SE 1/16 S30
2014

Set a steel fencepost northwest of the corner.

Corner is located on a gentle east slope, with grass and sagebrush.

- 39.990 The point for the center E 1/16 section corner of section 30.

From the point for the S 1/16 section corner of sections 29 and 30.

S. 89°54.9' W., on the east-west centerline of the SE 1/4 of section 30.

- 19.981 The SE 1/16 section corner of section 30.

- 39.962 The center S 1/16 section corner of section 30.

From the W 1/16 section corner of sections 30 and 31.

N. 0°00.4' E., on the north-south centerline of the SW 1/4 of section 30.

- 19.969 Point for the SW 1/16 section corner of section 30, at the intersection with the east-west centerline of the SW 1/4 of section 30.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 16

THE SUBDIVISION OF SECTION 30,
T. 30 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

inches in the ground to bedrock, magnet at base, in a mound of stone, 2 1/2 feet base, to aluminum cap marked

T30S R26E
SW 1/16 S30
2014

Set a steel fencepost west of the corner.

Corner is located on a fairly level mesa top.

- 39.938** The point for the center W 1/16 section corner of section 30.
-

From the center S 1/16 section corner of section 30.

S. 89°48.7' W., on the east-west centerline of the SW 1/4 of section 30.

- 19.992** The SW 1/16 section corner of section 30.

- 39.984** The S 1/16 section corner of sections 25 and 30, on the west boundary of the township, hereinbefore described.
-

The Subdivision of Section 31,
T. 30 S., R. 26 E., Salt Lake Meridian, Utah

From the standard 1/4 section corner of section 31 only, on the south boundary of the township, hereinbefore described.

N. 0°00.6 W., on the north-south centerline of section 31.

- 19.999** Point for the center S 1/16 section corner of section 31.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, magnet at base, in a mound of stone, 3 feet base, to aluminum cap marked

T30S R26E
C
S 1/16 | S31
C
2014

Set a steel fencepost north of the corner.

Corner is located in gently-rolling terrain, with sagebrush.

- 39.998** Point for the center 1/4 section corner of section 31, at intersection with the east-west centerline.

THE SUBDIVISION OF SECTION 31,
T. 30 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T30S R26E

C 1/4 S31

2014

Set a steel fencepost north of the corner.

Corner is located on a gentle southeast slope, with sagebrush.

80.058 The 1/4 section corner of sections 30 and 31.

From the 1/4 section corner of sections 31 and 32.

S. 89°56.3' W., on the E-W centerline of section 31.

19.985 Point for the center E 1/16 of section 31. Not monumented.

39.970 The center 1/4 section corner of section 31.

59.970 Point for the center W 1/16 of section 31. Not monumented.

79.970 The 1/4 section corner of sections 31 and 36, on the west boundary of the township, hereinbefore described.

From the E 1/16 section corner of section 31 only, on the south boundary of the township, hereinbefore described.

N. 0°01.0' W., on the north-south centerline of the SE 1/4 of section 31.

19.996 Point for the SE 1/16 section corner of section 31, at the intersection with the east-west centerline of the SE 1/4 of section 31.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T30S R26E

SE 1/16 S31

2014

Set a steel fencepost north of the corner.

Corner is located on a gentle east slope, with sagebrush.

39.992 The point for the center E 1/16 section corner of section 31.

From the point for the S 1/16 section corner of sections 31 and 32.

THE SUBDIVISION OF SECTION 31,
T. 30 S., R. 26 E., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 89°55.8' W., on the east-west centerline of the SE 1/4 of section 31.

19.988 The SE 1/16 section corner of section 31.

39.976 The center S 1/16 section corner of section 31.

From the W 1/16 section corner of section 31 only, on the south boundary of the township, hereinbefore described.

N. 0°01.6' W., on the north-south centerline of the SW 1/4 of section 31.

19.984 Point for the SW 1/16 section corner of section 31, at the intersection with the east-west centerline of the SW 1/4 of section 31.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T30S R26E
SW 1/16 S31
2014

Set a steel fencepost north of the corner.

Corner is located on a gentle southeast slope, with sagebrush.

39.968 The point for the center W 1/16 section corner of section 31.

From the center S 1/16 section corner of section 31.

S. 89°58.8' W., on the east-west centerline of the SW 1/4 of section 31.

19.995 The SW 1/16 section corner of section 31.

39.990 The S 1/16 section corner of sections 31 and 36, on the west boundary of the township, hereinbefore described.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Phil Freiberg	Survey Technician

CERTIFICATE OF SURVEY

I, *Scott A. Burkhardt, Cadastral Surveyor*, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing the date of *March 28, 2014*, I have *dependently resurveyed a portion of the south (Sixth Standard Parallel South) boundary, a portion of the west boundary, a portion of the subdivisional lines*, and have *subdivided sections 30 and 31, in Township 30 South, Range 26 East*, of the *Salt Lake* Meridian, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 21, 2015
Date

Scott A. Burkhardt
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the south (Sixth Standard Parallel South) boundary, a portion of the west boundary, a portion of the subdivisional lines, and the subdivision of sections 30 and 31, in Township 30 South, Range 26 East, Salt Lake Meridian; Utah*, executed by *Scott A. Burkhardt, Cadastral Surveyor*, having been critically examined and found correct, are hereby approved.

September 24, 2015
Date

Daniel W. Wehler
Chief Cadastral Surveyor for Utah