

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE RETRACEMENT AND DEPENDENT RESURVEY OF
A PORTION OF THE UTAH-COLORADO STATE BOUNDARY
FROM MILE POST 5 1/2 TO MILE POST 12,

THE DEPENDENT RESURVEY OF

A PORTION OF THE NORTH BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

THE MEANDERS OF THE RIGHT BANK OF THE SAN JUAN RIVER,

AND

THE SURVEY OF

A PORTION OF THE SUBDIVISIONAL LINES,

THE SUBDIVISION OF SECTIONS 3, 4, 5, 7, 9, 10, 18, 20, 22, 29, AND 32,

AND THE MEANDERS OF THE LEFT BANK OF THE SAN JUAN RIVER,

IN

TOWNSHIP 42 SOUTH, RANGE 26 EAST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Scott A. Burkhardt
Cadastral Surveyor

Under Special Instructions dated and approved **April 24, 2014**, which provided for the surveys included under Group No. **1262**, and Assignment Instructions dated **April 24, 2014**.

Survey Commenced, **April 29, 2014**
Survey Completed, **July 10, 2014**

INDEX DIAGRAM

TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

			12				
6	48	5	28	4	20	3	11
48		47		27		19	
7	46	8	26	9	18	10	9
45		44		26		17	
18	43	17	25	16	17	15	7
42		41		25		16	
19	37	20	24	21	15	22	6
36		35		23		15	
30	34	29	23	28	14	27	5
32		31		22		13	
31	29	32	21	33	12	34	3

The Subdivision of Section 3.....	Page 49
The Subdivision of Section 4.....	Page 50
The Subdivision of Section 5.....	Page 51
The Subdivision of Section 7.....	Page 52
The Subdivision of Section 9.....	Page 53
The Subdivision of Section 10.....	Page 54
The Subdivision of Section 18.....	Page 54
The Subdivision of Section 20.....	Page 56
The Subdivision of Section 22.....	Page 56
The Subdivision of Section 29.....	Page 57
The Subdivision of Section 32.....	Page 58
Meanders of the Right Bank of the San Juan River.....	Page 59
Meanders of the Left Bank of the San Juan River.....	Page 63
Meanders of an island in the San Juan River in Secs. 19 & 20.....	Page 66
Meanders of an island in the San Juan River in Sec. 32.....	Page 67

TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

The following field notes describe the retracement and dependent resurvey of a portion of the Utah-Colorado state boundary line from Mile Post 5 1/2 to Mile Post 12, the dependent resurvey of a portion of the north boundary, a portion of the subdivisional lines, and the meanders of the right bank of the San Juan River, and the survey of a portion of the subdivisional lines, the subdivision of sections 3, 4, 5, 7, 9, 10, 18, 20, 22, 29, and 32, and the meanders of the left bank of the San Juan River, in T. 42 S., R. 26 E., Salt Lake Meridian, Utah.

HISTORY OF SURVEYS

Surveyed by	Retr. or Resurveyed by
SOUTH BOUNDARY	
Portion H.D. Page & J.M. Lentz	1899
Portion A. Nelson & R.C. Yundt	1953 A. Nelson & R.C. Yundt
All	S.A. Burkhardt 2012-13
EAST BOUNDARY (Utah-Colorado State Boundary Line)	
All R.J. Reeves	1878
All	A.D. Wilson 1885
All	C.R. Burt 1915
Portion	J.A. Eaves & L.G. Edmonds 1957
Portion	D.A. Cody 1989-90
Portion	R.K. Baugh 2005
Portion	S.A. Burkhardt 2012-13
WEST BOUNDARY	
Portion H.D. Page & J.M. Lentz	1899
Portion A. Nelson & R.C. Yundt	1953 A. Nelson & R.C. Yundt
Portion	J.F. Carroll 2004-05
Portion	M.D. Boeckman 2012-13
NORTH BOUNDARY	
All H.D. Page & J.M. Lentz	1899
All	R.K. Baugh 2005
Portion	J.F. Carroll 2004-05
SUBDIVISION	
Portion H.D. Page & J.M. Lentz	1899
MEANDERS OF THE RIGHT BANK OF THE SAN JUAN RIVER	
All H.D. Page & J.M. Lentz	1899

TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 1262, dated April 24, 2014.

The direction of each line is with reference to true the meridian, determined by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards for the Positional Accuracy of Cadastral Surveys When Using Global Navigation Satellite Systems (GNSS)*, dated February 23, 2009. Trimble model R8 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from GPS static observations, post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS): DL3642 MC09 NUCLA CORS ARP, DI3419 P012 MONTICELLOUT2006 CORS ARP, DH6916 MC04 MESA CNTY 04 COOP CORS ARP.

The geographic position of the corner of sections 6 and 31 only, Tps. 42 and 43 S., R. 26 E., as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: **37°05'04.427" N.**,
Longitude: **109°06'56.686" W.**, N.A.D. 83 (2011), EPOCH: 2010.00,
Network Accuracy = 0.200 meter at 95% confidence.

The geographic position of Mile Post 12 on the Utah-Colorado State Boundary Line, as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: **37°10'22.124" N.**,
Longitude: **109°02'44.395" W.**, N.A.D. 83 (2011), EPOCH: 2010.00,
Network Accuracy = 0.200 meter at 95% confidence.

All stainless steel monuments and brass tablets set in this survey bear the Navajo Nation seal, unless otherwise noted.

RETRACEMENT AND DEPENDENT RESURVEY OF A PORTION OF THE UTAH-COLORADO
STATE BOUNDARY LINE, FROM MILE POST 5 1/2 TO MILE POST 12

CHAINS

Retracement and Dependent Resurvey of a Portion of the Utah-Colorado
State
Boundary Line, From Mile Post 5 1/2 to Mile Post 12

Reestablishment of the Survey Executed by R.J. Reeves in 1878, and
the Retracement and/or Resurveys by A.D. Wilson in 1885, and C.R.
Burt in 1915, D.A. Cody (Colorado) in 1989-90,
and S.A. Burkhardt in 2012-13

Beginning at Mile Post 5 1/2 on the Utah-Colorado State boundary
line, monumented with an aluminum post, 2 1/2 inches diameter,
firmly set, projecting 4 inches above the ground, with aluminum
cap marked as described in the official record of the 1989-90
retracement and resurvey; with a mound of stone, 3 feet base, 2
feet high, north of the corner; with a carsonite post marked
"RESERVATION BOUNDARY" alongside the corner.

From the corner, a fence, 4-strand barbed wire, extending north
and south, bears East, 7.0 links distance.

N. 0°15.8' E., on the 6th mile.

33.759 The closing corner of sections 3 and 34, Tps. 42 and 43 S., R. 26
E., on the south boundary of the township, monumented with a
stainless steel post, 2 1/2 inches diameter, firmly set,
projecting 2 inches above the ground, in a collar of stone, 2
feet base, with brass cap marked as described in the 2012-13
resurvey; with a steel fence post northwest of the corner.

From the corner, a fence, 4-strand barbed wire, extends north
and south.

Corner is located in rolling hills, in barren ground.

40.105 Mile Post 6, on the Utah-Colorado State boundary line,
monumented with an iron post, 3 inches diameter, firmly set,
projecting 7 inches above the ground, with brass cap marked as
described in the official record of the 2012-13 resurvey; with a
carsonite post marked "RESERVATION BOUNDARY" alongside the
corner.

From the corner, a fence, 5-strand barbed wire, extends north
and south.

Corner is located at the foot of a small bench, bears east and
west.

Reestablishment of the Survey Executed by R.J. Reeves in 1878,
and the Retracement and/or Resurveys by A.D. Wilson in 1885, C.R.
Burt in 1915 and D.A. Cody (Colorado) in 1989-90.

N. 0°09.0' E., on the 7th mile.

RETRACEMENT AND DEPENDENT RESURVEY OF A PORTION OF THE UTAH-COLORADO
STATE BOUNDARY LINE, FROM MILE POST 5 1/2 TO MILE POST 12

CHAINS

- 33.672** Point for the 1/4 section corner of section 34 only.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground, magnet at base, in a collar of stone, 1 1/2 feet base, with brass cap marked

T42S	
R26E	
1/4 S34	
2014	

Set a steel fencepost northeast of the corner.

Corner is located in a fence, 4-strand barbed-wire, extending north and south.

- 40.136** Mile Post 6 1/2, on the Utah-Colorado State Boundary Line, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 4 inches above a mound of stone, 3 feet base, 1/2 foot high, with aluminum cap marked as described in the official record of the 1989-90 resurvey; with a carsonite post marked "RESERVATION BOUNDARY" alongside the corner.

From the corner, a fence, 4-strand barbed wire, extends north and south.

Corner is located on a ridge top, in barren ground.

N. 0°09.4' E., beginning new measurement.

- 33.554** Point for the closing corner of sections 27 and 34, at proportionate distance (1899 record distance to Mile Post 7, proportioned between Mile Post 6 and Mile Post 7), there is no remaining evidence of the 1899 marked stone or mound of stone.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 25 inches in the ground, magnet at base, with brass cap marked

T42S	
R26E	
S27 C	
S34 C	
2014	

Set a steel fencepost east of the corner.

From the corner, a fence, 4-strand barbed wire, extends north and south.

- 40.125** Mile Post 7, on the Utah-Colorado State Boundary Line, monumented with an iron post, 3 inches diameter, firmly set, projecting 10 inches above the ground, with brass cap marked as

RETRACEMENT AND DEPENDENT RESURVEY OF A PORTION OF THE UTAH-COLORADO
STATE BOUNDARY LINE, FROM MILE POST 5 1/2 TO MILE POST 12

CHAINS

described in the official record of the 1915 resurvey; with a carsonite post marked "RESERVATION BOUNDARY" alongside the corner.

From the corner, a fence, 4-strand barbed wire, extends north and south.

Corner is located in rolling, barren ground with cobblestones.

N. 0°14.3' E., on the 8th mile.

33.285 Point for the 1/4 section corner of section 27 only.

Set a brass tablet, 3 1/4 inch diameter, with 3 1/2 inch stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, marked

T42S	
R26E	
1/4 S27	
2014	

Raise a mound of stone, 2 feet base, 1 foot high, west of the corner.

From the corner, a fence, 4-strand barbed-wire, extending north and south, bears West, 4.2 links distance.

Corner is located on the south rim of a canyon.

40.078 Mile Post 7 1/2, on the Utah-Colorado State Boundary Line, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, flush in a mound of stone, 2 1/2 feet base, 1/2 foot high, with aluminum cap marked as described in the official record of the 1989-90 resurvey.

From the corner, a fence, 4-strand barbed-wire, extending north and south, bears West, 4.8 links distance.

Corner is located on a gentle south slope on the west edge of a mesa top.

N. 0°14.2' E., beginning new measurement.

33.063 Point for the closing corner of sections 22 and 27, at proportionate distance (1899 record distance to Mile Post 8, proportioned between Mile Post 7 and Mile Post 8), there is no remaining evidence of the 1899 marked stone or mound of stone.

Set a brass tablet, 3 1/4 inch diameter, with 3 1/2 inch stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, marked

RETRACEMENT AND DEPENDENT RESURVEY OF A PORTION OF THE UTAH-COLORADO
STATE BOUNDARY LINE, FROM MILE POST 5 1/2 TO MILE POST 12

CHAINS

T42S
R26E
S22 C
S27 C
2014

Raise a mound of stone, 2 feet base, 2 feet high, west of the corner.

From the corner, a fence, 4-strand barbed-wire, extending north and south, bears West, 9.1 links distance.

- 40.077** Mile Post 8, on the Utah-Colorado State Boundary Line, monumented with an iron post, 3 inches diameter, firmly set, projecting 10 inches above the ground, with brass cap marked as described in the official record of the 1915 resurvey; with a carsonite post marked "RESERVATION BOUNDARY" alongside the corner.

From which the 1915 bearing object

An "B+O", marked on a sandstone boulder and partially hidden by another boulder, bears S. 27° W., 64.5 links distance (Record: bears S. 29°35' W., 67 links distance).

From the corner, a fence, 4-strand barbed-wire, extending north and south, bears East, 1.8 links distance.

Corner is located in broken, barren ground, south of a large boulder.

N. 0°30.8' W., on the 9th mile.

- 33.069** Point for the 1/4 section corner of section 22 only.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 22 inches in the ground, magnet at base, in a mound of stone, 4 feet base, with aluminum cap marked

T42S
R26E
1/4 S22
2014

From the corner, a fence, 4-strand barbed-wire, extends north and south.

- 39.999** Mile Post 8 1/2, on the Utah-Colorado State Boundary Line, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above a collar of stone, 3 feet base, with aluminum cap marked as described in the official record of

RETRACEMENT AND DEPENDENT RESURVEY OF A PORTION OF THE UTAH-COLORADO
STATE BOUNDARY LINE, FROM MILE POST 5 1/2 TO MILE POST 12

CHAINS

the 1989-90 resurvey; with a carsonite post marked "RESERVATION BOUNDARY" alongside the corner.

From the corner, a fence, 4-strand barbed-wire, extends north and south.

N. 0°30.7' W., beginning new measurement.

- 33.152** Point for the closing corner of sections 15 and 22, at proportionate distance (1899 record distance to Mile Post 9, proportioned between Mile Post 8 and Mile Post 9), there is no remaining evidence of the 1899 marked stone or mound of stone.

Set a brass tablet, 3 1/4 inch diameter, with 3 1/2 inch stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, marked

T42S	
S15	C
S22	C
R26E	

2014

Raise a mound of stone, 2 feet base, 1 foot high, southwest of the corner.

From the corner, a fence, 4-strand barbed-wire, extends north and south.

- 40.002** Mile Post 9, on the Utah-Colorado State Boundary Line, monumented with an iron post, 3 inches diameter, firmly set, flush with the ground, with brass cap marked as described in the official record of the 1915 resurvey; with a carsonite post marked "RESERVATION BOUNDARY" alongside the corner.

From the corner, a fence, 4-strand barbed-wire, extends north and south.

N. 0°30.4' W., on the 10th mile.

- 33.148** Point for the 1/4 section corner of section 15 only.

Set a brass tablet, 3 1/4 inch diameter, with 3 1/2 inch stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, marked

T42S	
R26E	
1/4 S15	

2014

From the corner, a fence, 4-strand barbed-wire, extends north and south.

RETRACEMENT AND DEPENDENT RESURVEY OF A PORTION OF THE UTAH-COLORADO
STATE BOUNDARY LINE, FROM MILE POST 5 1/2 TO MILE POST 12

CHAINS

- 40.070** Mile Post 9 1/2, on the Utah-Colorado State Boundary Line, monumented with an iron post, 1 inch diameter, firmly set, flush with a mound of stone, 3 feet base, 1 foot high, with brass cap marked as described in the official record of the 1957 resurvey of a portion of the north boundary of the old Southern Ute Indian Reservation and the survey of the south boundary and the subdivisional lines of fractional Township 33 1/2 North, Range 20 West of the New Mexico Principal Meridian, State of Colorado, by Eaves and Edmonds; with a carsonite post marked "RESERVATION BOUNDARY" alongside the corner.

From the corner, a fence, 4-strand barbed-wire, extends north and south.

Corner is located on a mesa top.

Reestablishment of the Survey Executed by R.J. Reeves in 1879 and the Retracement and/or Resurveys by A.D. Wilson in 1885, and C.R. Burt in 1915 and J.A. Eaves and L.G. Edmonds (Colorado) in 1957

N. 0°29.0' W., beginning new measurement.

- 33.076** Point for the closing corner of sections 10 and 15, determined by an unrecorded iron pipe, 1 inch diameter, firmly set, projecting 24 inches above a mound of stone, 2 feet base, 1/2 foot high, capped with a steel plate, 2 x 2 inches square, marked T42S R S10/S15 R26E, bears N. 89°57.8' W., 2.6 links distance. The position of this monument is harmoniously related to existing corners and is accepted as the best available evidence of the original closing corner, Add marks "AM" to cap and bury in place.

At the corner point (at intersection with the Utah-Colorado State Boundary Line)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 5 inches in the ground to bedrock, magnet at base, in a mound of stone, 3 feet base, to brass cap marked

T42S

R26E

S10 C

S15 C

2014

From the corner, a fence, 4-strand barbed-wire, extending north and south, bears West, 2.3 links distance from the corner.

- 40.212** Point for Mile Post 10, on the Utah-Colorado State Boundary Line, at proportionate distance (Irregular Boundary Adjustment), there is no remaining evidence of the 1915 iron post or mound of stone.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 5

RETRACEMENT AND DEPENDENT RESURVEY OF A PORTION OF THE UTAH-COLORADO
STATE BOUNDARY LINE, FROM MILE POST 5 1/2 TO MILE POST 12

CHAINS

inches in the ground to bedrock, magnet at base, in a mound of
stone, 3 feet base, to aluminum cap marked

10 MP
UTAH | COLO
2014

Set a steel fencepost north of the corner.

From the corner, a fence, 4-strand barbed-wire, extending north
and south, bears West, 2.7 links distance.

Corner is located in eroded terrain, on a rocky bench,
approximately midway up the slope of the mesa.

N. 0°29.0' W., on the 11th mile.

- 30.898** A Right-of-Way monument, a cement pier, 6 inches diameter,
firmly set, projecting 1 1/2 feet above the ground, with brass
cap, 3 1/4 inches diameter, set flush in top of pier, marked
Colorado Dept. of Highways ROW Marker Sta. Elev., bears West,
2.4 links distance.

- 32.847** Point for the 1/4 section corner of section 10 only.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches
long, 25 inches in the ground, magnet at base, in a collar of
stone, 2 feet base, with brass cap marked

T42S |
R26E |
1/4 S10 |
2014

Set a steel fencepost west of the corner.

Corner is located in the southwest shoulder of Utah State
Highway 262.

- 33.709** Centerline of Utah State Highway 262, paved, 25 feet wide, bears
N. 43° W., S. 43° E.

- 36.433** A Right-of-Way monument, a cement pier, 6 inches diameter,
firmly set, projecting 6 inches above the ground, with brass
cap, 3 1/4 inches diameter, set flush in top of pier, marked
Colorado Dept. of Highways ROW Marker Sta. Elev., bears West,
1.8 links distance.

- 40.212** Point for Mile Post 10 1/2, on the Utah-Colorado State Boundary
Line, at proportionate distance (Irregular Boundary Adjustment),
not monumented during the 1915 resurvey.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 6

RETRACEMENT AND DEPENDENT RESURVEY OF A PORTION OF THE UTAH-COLORADO
STATE BOUNDARY LINE, FROM MILE POST 5 1/2 TO MILE POST 12

CHAINS

inches in the ground to bedrock, magnet at base, in a mound of
stone, 3 feet base, to aluminum cap marked

10 1/2 MP
UTAH | COLO
2014

From the corner, a fence, 4-strand barbed-wire, extending north
and south, bears West, 2.3 links distance.

N. 0°30.0' W., beginning new measurement.

- 32.618** Point for the closing corner of sections 3 and 10, at
proportionate distance (1899 record distance to Mile Post 11,
proportioned between Mile Post 10 and Mile Post 11), there is no
remaining evidence of the 1899 marked stone or mound of stone.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches
long, 25 inches in the ground, magnet at base, in a mound of
stone, 3 feet base, to brass cap marked

T42S
R26E
S3 C |
S10 C |
2014

Set a steel fencepost northeast of the corner.

From the corner, a fence, 4-strand barbed-wire, extends north and
south.

Reestablishment of the Survey Executed by R.J. Reeves in 1878,
and the Retracement and/or Resurveys by A.D. Wilson in 1885,
C.R. Burt in 1915, J.A. Eaves and L.G. Edmonds
(Colorado) in 1957, and R.K. Baugh in 2005

- 39.402** Witness corner to Mile Post 11, on the Utah-Colorado State
Boundary Line, monumented with an iron post, 3 inches diameter,
firmly set, projecting 13 inches above the ground, with brass
cap marked as described in the official record of the 2005
resurvey; with a mound of stone, 4 feet base, 2 feet high, west
of the corner.

From the corner, a fence, 4-strand barbed-wire, extends north
and south.

N. 0°35.8' W., beginning new measurement.

- 0.200** True point for Mile Post 11, on the Utah-Colorado State Boundary
Line. Point falls in a wash where it is impractical to establish

RETRACEMENT AND DEPENDENT RESURVEY OF A PORTION OF THE UTAH-COLORADO
STATE BOUNDARY LINE, FROM MILE POST 5 1/2 TO MILE POST 12

CHAINS

a permanent monument.

Continue measurement, on the 12th mile.

33.189 Point for the 1/4 section corner of section 3 only.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 23 inches in the ground, magnet at base, in a mound of stone, 2 1/2 feet base, to brass cap marked

T42S	
R26E	
1/4 S3	
2014	

Set a steel fencepost west of the corner.

From the corner, a fence, 4-strand barbed-wire, extending north and south, bears East, 6.7 links distance.

40.253 Point for Mile Post 11 1/2, on the Utah-Colorado State Boundary Line, at proportionate distance. Not monumented.

73.163 The closing corner of sections 3 and 34, Tps. 41 and 42 S., R. 26 E., on the north boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 5 inches above the ground, in a mound of stone, 3 feet diameter, 1 foot high, with brass cap marked as described in the 2005 resurvey.

From the corner, a fence, 4-strand barbed wire, extends north and south.

Corner is located on an east facing slope.

80.306 Mile Post 12, on the Utah-Colorado State Boundary Line, monumented with an iron post, 3 inches diameter, firmly set, projecting 3 inches above a mound of stone, 3 1/2 feet base, 2 feet high, with brass cap marked as described in the official record of the 1915 survey.

From the corner, a fence, 4-strand barbed-wire, extends north and south.

Corner is located on an east-facing slope.

Dependent Resurvey of a Portion of the North Boundary
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by H.D. Page and J.M. Lentz
in 1899, and the Resurvey Executed by R.K. Baugh in 2005

From the corner of sections 3, 4, 33, and 34, on the north

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

boundary of the township, hereinafter described.

S. 89°59.0' W., between sections 4 and 33.

- 40.027** Point for the 1/4 section corner of sections 4 and 33. There is no remaining evidence of the 2005 stainless steel post.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 29 inches in the ground, magnet at base, with brass cap marked

T41S R26E

S33

1/4

S4

T42S

2014

Set a steel fencepost north of the corner.

Corner is located on the east edge of a wash, 50 feet wide, 3 feet deep, course S.15°W.

- 80.054** The corner of sections 4, 5, 32, and 33, hereinafter described.

Resurvey and Survey of a Portion of the Subdivisional Lines,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
H.D. Page and J.M. Lentz in 1899

From the corner of sections 3, 4, 33, and 34, on the south boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, flush with a mound of stone, 4 feet base, 1 foot high, with brass cap marked as described in the official record of the 2012-13 resurvey; with a steel fencepost alongside the corner.

Corner is located in rocky, rolling hills on a northeast-facing slope.

N. 0°07.8' E., between sections 33 and 34.

- 40.057** The 1/4 section corner of sections 33 and 34, monumented with a cobblestone, 14 x 8 x 5 inches, firmly set, projecting 8 inches above the ground, marked 1/4 on west face. There is no remaining evidence of the 1899 mound of stone west of the corner.

At the corner (marked stone)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T42S R26E

1/4

S33	S34
-----	-----

2014

Bury original marked stone alongside the corner.

Corner is located on a moderately-steep east-facing slope with cobblestones and sparse vegetation.

N. 0°02.5' W., beginning new measurement.

- 39.975** The corner of sections 27, 28, 33, and 34, monumented with a sandstone, 30 x 12 x 5 inches, firmly set but tilted, projecting 20 inches above the ground, marked with 3 notches on one edge, 1 notch on other edge (record: 24 x 10 x 3 inches); with an embedded mound of stone north of the corner.

At the corner (marked sandstone)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 22 inches in the ground, magnet at base, in a mound of stone, 3 feet base, to brass cap marked

T42S R26E

S28	S27
S33	S34

2014

Bury original marked stone in mound of stone.

Set a steel fencepost north of the corner.

Corner is located in a broad drainage, in rocky soil.

N. 89°59.5' E., between sections 27 and 34.

- 39.985** Point for the 1/4 section corner of sections 27 and 34, at proportionate distance. There is no remaining evidence of the 1899 marked stone or mound of stone.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 20 inches in the ground to bedrock, magnet at base, in a mound of stone, 3 feet base, to brass cap marked

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

T42S R26E
 S27
 1/4 ———
 S34
 2014

Set a steel fencepost north of the corner.

Corner is located in an area of sandstone outcrops and sandy benches.

- 72.424** The closing corner of sections 27 and 34, on the Utah-Colorado State boundary line, hereinbefore described.

From the corner of sections 27, 28, 33, and 34.

N. 0°03.0' E., between sections 27 and 28.

- 40.021** Point for the 1/4 section corner of sections 27 and 28, at proportionate distance. There is no remaining evidence of the 1899 marked stone or mound of stone.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

T42S R26E
 1/4
 S28 | S27
 2014

Set a steel fencepost north of the corner.

Corner is located in a valley bottom, course westerly.

- 80.042** The corner of sections 21, 22, 27, and 28, monumented with a sandstone, 18 x 13 x 5 inches, firmly set, projecting 5 inches above the ground, with no discernible marks (record: 26 x 10 x 5 inches, marked with 3 notches on east edge, 2 notches on south edge), in an embedded mound of stone, 3 feet base (record: 2 feet base, 1 1/2 feet high, west of the corner).

At the corner (sandstone)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 26 inches in the ground, magnet at base, in a mound of stone, 3 feet base to brass cap marked

T42S R26E
 S21 | S22
 S28 | S27
 2014

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

Set a steel fencepost northeast of the corner.

Corner is located in rolling, rocky terrain.

N. 89°49.1' E., between sections 22 and 27.

- 40.012** The 1/4 section corner of sections 22 and 27, monumented with a sandstone, 14 x 11 x 9 inches, lying loose on ground, immediately south of an embedded mound of stone, 2 feet base, marked 1/4 on one face, (record: 14 x 12 x 4 inches, marked 1/4 S on north face, with a mound of stone, 2 feet base, 1 1/2 feet high, north of the corner).

At the corner (immediately south of embedded mound of stone)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 26 inches in the ground, magnet at base, in a collar of stone, 2 feet base, with brass cap marked

T42S R26E
 S22
1/4 ———
 S27
2014

Bury original marked stone alongside the corner.

Set a steel fencepost north of the corner.

Corner is located on a fairly level mesa top, surrounded by higher mesas.

S. 89°13.0' E., beginning new measurement.

- 32.652** The closing corner of sections 22 and 27, on the Utah-Colorado State boundary line, hereinbefore described.

From the corner of sections 21, 22, 27, and 28.

N. 0°10.0' W., between sections 21 and 22.

- 39.970** Point for the 1/4 section corner of sections 21 and 22, at proportionate distance. There is no remaining evidence of the 1899 marked stone or mound of stone.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, magnet at base, with brass cap marked

T42S R26E
 1/4
S21 | S22
2014

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

Set a steel fencepost north of the corner.

Corner is located on a fairly level mesa top.

- 79.940** Point for the corner of sections 15, 16, 21, and 22, at proportionate distance. There is no remaining evidence of the 1899 marked stone or mound of stone.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 20 inches in the ground to bedrock, magnet at base, in a mound of stone, 3 feet base, to brass cap marked

T42S	R26E
S16	S15
S21	S22
2014	

Set a steel fencepost east of the corner.

Corner is located on a fairly level, rocky bench.

S. 89°55.4' E., between sections 15 and 22.

- 39.838** Point for the 1/4 section corner of sections 15 and 22, at proportionate distance. There is no remaining evidence of the 1899 marked stone and mound of stone.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 23 inches in the ground, magnet at base, in a mound of stone, 3 feet base to brass cap marked

T42S	R26E
1/4	S15
	S22
2014	

Set a steel fencepost west of the corner.

Corner is located in open terrain, with sparse vegetation.

- 72.256** The closing corner of sections 15 and 22, on the Utah-Colorado State boundary line, hereinbefore described.
-

From the corner of sections 15, 16, 21, and 22.

N. 0°13.6' E., between sections 15 and 16.

- 39.970** Point for the 1/4 section corner of sections 15 and 16, at proportionate distance. There is no remaining evidence of the 1899 marked stone or mound of stone.

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, magnet at base, with brass cap marked

T42S R26E
1/4
S16 | S15
2014

Set a steel fencepost north of the corner.

Corner is located in rolling, sandy hills.

- 79.940** The corner of sections 9, 10, 15, and 16, determined immediately west of 3 grooves on a sandstone boulder, 5 x 4 x 2 feet, with a mound of stone, 2 feet base, 2 feet high, on the hillside immediately adjacent to the boulder (record: an "+" chiseled into the boulder with 4 notches south and east edges; with a mound of stone, 2 feet base, 1 1/2 feet high, west of the corner).

At the corner (immediately west of 3 grooves)

Set a brass tablet, 3 1/4 inch diameter, with 3 1/2 inch stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at bottom, marked

T42S R26E
S9 | S10
S16 | S15
2014

Rehab mound of stone west of corner.

Set a steel fencepost northeast of the corner.

S. 89°57.8' E., between sections 10 and 15.

- 39.285** Point for the 1/4 section corner of sections 10 and 15, at proportionate distance. There is no remaining evidence of the 1899 marked stone or mound of stone.

Set a brass tablet, 3 1/4 inch diameter, with 3 1/2 inch stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, marked

T42S R26E
S10
1/4 ———
S15
2014

Raise a mound of stone, 2 feet base, 2 feet high, north of the corner.

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located on a fairly level mesa top.

- 71.204** The amended closing corner of sections 10 and 15, hereinbefore described.
- 71.230** The true point for the closing corner of sections 10 and 15, on the Utah-Colorado State boundary line, hereinbefore described.

From the corner of sections 9, 10, 15, and 16.

N. 0°02.8' W., between sections 9 and 10.

- 40.062** The 1/4 section corner of sections 9 and 10, determined immediately west of a sandstone boulder, 3 x 3 x 2 feet, with no discernible marks (record: 1/4 S chiseled into the west face); with a mound of stone, 2 feet base, 2 feet high, west of the corner.

At the corner (immediately west of sandstone boulder and east of the mound of stone)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, on bedrock, magnet at base, in a mound of stone, 3 feet base, to brass cap marked

T42S R26E
1/4
S9 | S10
2014

Raise a mound of stone, 2 feet base, 2 feet high, east of the corner.

Set a steel fencepost northeast of the corner.

Corner is located northeast of a ravine, course southeasterly.

N. 0°09.7' E., beginning new measurement.

- 39.749** The corner of sections 3, 4, 9, and 10, monumented with a sandstone, 17 x 6 x 5 inches, loosely set, projecting 14 inches above an embedded mound of stone 2 feet base, with 3 notches on east edge (record: 16 x 8 x 5 inches, marked with 3 notches on east edge, 5 notches on south edge, with a mound of stone, 2 feet base, 1 1/2 feet high, west of the corner).

At the corner (marked sandstone)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 22 inches in the ground, magnet at base, in a mound of stone, 2 feet base, to brass cap marked

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T42S R26E

S4	S3
S9	S10

2014

Set a steel fencepost northwest of the corner.

From this point, a Right-of-Way monument, an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, marked PT 52+5.0, bears N.17°43.9'W., 13.146 chains distance.

From this same point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 1/4 inches diameter, set flush in top of pier, no markings, bears N.27°35.8'W., 10.929 chains distance; with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, marked PT 52+1, west of the pier.

Corner is located in gently rolling terrain, no vegetation.

S. 89°38.6' E., between sections 3 and 10.

15.878 Centerline of Utah State Highway 262, paved, 25 feet wide, bears N. 55°W., S. 52°E.

39.776 The 1/4 section corner of sections 3 and 10, monumented with a sandstone, 18 x 9 x 6 inches, buried 2 inches below ground, marked 1/4 on north face, no remaining evidence of mound of stone. (record: 16 x 8 x 6 inches, with a mound of stone, 2 feet base, 1 1/2 feet high, north of the corner).

At the corner (marked sandstone)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground, magnet at base, in a collar of stone, 2 feet base, with brass cap marked

T42S R26E

1/4	S3
	S10

2014

Set a steel fencepost north of the corner.

From this point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 1/4 inches diameter, set flush in top of pier, marked PC 14+13.32, bears S.33°33.5'E., 14.790 chains distance; with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, west of the pier.

From this same point, a Right-of-Way monument, a cement pier, 6

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 1/4 inches diameter, set flush in top of pier, marked PC 23+38.15, bears S.30°5.3'W., 10.862 chains distance; with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, west of the pier.

From this same point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 1/4 inches diameter, set flush in top of pier, marked PC 23+38.15, bears S.40°23.1'W., 8.359 chains distance; with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, west of the pier.

Corner is located in gently rolling, open terrain.

N. 89°20.3' E., beginning new measurement.

- 30.680 The closing corner of sections 3 and 10, on the Utah-Colorado State Boundary Line, hereinbefore described.

From the corner of sections 3, 4, 9, and 10.

N. 0°04.4' E., between sections 3 and 4.

- 9.240 Centerline of Utah State Highway 262, paved, 25 feet wide, bears N. 67° W., S. 65° E.

- 40.243 The 1/4 section corner of sections 3 and 4, monumented with a sandstone, 18 x 15 x 4 inches, firmly set, projecting 14 inches above the ground, marked 1/4 on west face, (record: 16 x 12 x 2 inches); with a mound of stone, 2 feet base, 2 feet high, west of the corner.

At the corner (marked sandstone)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 12 inches in the ground to bedrock, magnet at base, in a mound of stone, 3 feet base, to brass cap marked

T42S R26E
1/4
S4 | S3
2014

Set a steel fencepost north of the corner.

Bury original marked stone in mound of stone.

Corner is located at the base of sandstone cliffs to the east.

N. 0°07.2' E., beginning new measurement.

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

39.983 The corner of sections 3, 4, 33, and 34, Tps. 41 and 42 S., R. 26 E., on the north boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 4 inches above an embedded mound of stone, 2 feet base, with brass cap marked as described in the official record of the 2005 resurvey; with a mound of stone, 2 1/2 feet base, 2 feet high, west of the corner.

From the true point for the corner of sections 4, 5, 32, and 33, on the south boundary of the township.

From the true point, the 1953 witness corner to sections 4, 5, 32, and 33, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above a mound of stone, 2 feet base, 1 foot high, with brass cap (BLM) marked as described in the official record of the 1953 resurvey, bears N. 89°58.7' E., 1.799 chains distance; with a mound of stone, 2 feet base, 2 feet high, west of the corner.

N. 0°11.3' E., between sections 32 and 33.

40.082 The 1/4 section corner of sections 32 and 33, monumented with an unrecorded iron pipe, 1 inch diameter, firmly set, projecting 11 1/2 inches above a mound of stone, 2 feet base, 1 1/2 foot high, capped with a steel plate, 2 x 2 inches square, marked 1/4 32/33, with the 1899 marked stone, 24 x 13 x 6 inches, marked 1/4 on one face (record: 20 x 12 x 8 inches, marked 1/4 S on west face with a mound of stone, 2 feet base, 1 1/2 feet high, west of the corner), lying loose alongside the corner. This position is accepted as a careful and faithful perpetuation of the original corner.

At the corner (iron pipe)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 8 inches in the ground to bedrock, magnet at base, in a mound of stone, 4 feet base, to brass cap marked

T42S R26E
1/4
S32 | S33
2014

Bury original marked stone and unrecorded iron pipe in mound of stone.

Set a steel fencepost west of the corner.

Corner is located on a moderately-steep, west-facing clay slope.

N. 0°04.0' E., beginning new measurement.

39.949 The corner of sections 28, 29, 32, and 33, monumented with a

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

cobblestone, 13 x 9 x 5 inches, loosely set, projecting 11 inches above the ground, marked with 4 notches on east edge, no other discernible marks (record: 12 x 8 x 6 inches, marked with 4 notches on east edge, 1 notch on south edge), there is no remaining evidence of the 1899 mound of stone (record: 2 feet base, 1 1/2 feet high, west of the corner).

At the corner (marked cobblestone)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 17 inches in the ground, magnet at base, in a mound of stone, 2 feet base, to brass cap marked

T42S	R26E
S29	S28
S32	S33
2014	

Bury original marked stone in mound of stone.

Set a steel fencepost west of the corner.

Corner is located on a cobblestone-covered east-facing slope, just off the edge of a mesa top.

From the corner of sections 27, 28, 33, and 34.

N. 89°59.7' W., between sections 28 and 33.

- 39.934** Point for the 1/4 section corner of sections 28 and 33, at proportionate distance. There is no remaining evidence of the 1899 marked stone or mound of stone.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 9 inches in the ground to bedrock, magnet at base, in a mound of stone, 2 1/2 feet base, to brass cap marked

T42S	R26E
1/4	S28
	S33
2014	

Set a steel fencepost northwest of the corner.

Corner is located on a fairly level bench, in barren, rocky terrain.

- 79.868** The corner of sections 28, 29, 32, and 33.

N. 0°05.1' W., between sections 28 and 29.

- 39.951** The 1/4 section corner of sections 28 and 29, monumented with a sandstone, 19 x 13 x 5 inches, marked 1/4 on one face (record: 12 x

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

12 x 6 inches, marked 1/4 S on west face), lying loose on an embedded mound of stone, 2 feet base (record: 2 feet base, 1 1/2 feet high, west of the corner).

At the corner (immediately east of the mound of stone)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, in a collar of stone, 2 feet base, with brass cap marked

T42S R26E
1/4
S29 | S28
2014

Set a steel fencepost north of the corner.

Corner is located near the bottom of a valley, above a wash to the north.

N. 0°22.9' E., beginning new measurement.

- 39.770 The corner of sections 20, 21, 28, and 29, monumented with an unrecorded iron pipe, 1 inch diameter, firmly set, projecting 12 inches above an embedded mound of stone, 2 feet base, capped with a steel plate, 1 1/2 x 1 1/2 inches square, marked T42S 20/21/28/29 R26E; with a sandstone boulder, 12 x 6 x 4 feet, with no discernible marks (record: 14 x 6 x 4 feet, with an "+" chiseled into the boulder, with 4 notches on the east edge and 2 notches on the south edge, southeast of the corner, with a mound of stone, 2 feet base, 1 1/2 feet high, west of the corner). This position is accepted as a careful and faithful perpetuation of the original corner.

Rehabilitate mound of stone to 2 feet base, 2 feet high.

From the corner of sections 21, 22, 27, and 28.

S. 89°46.4' W., between sections 21 and 28.

- 39.858 Point for the 1/4 section corner of sections 21 and 28, at proportionate distance. There is no remaining evidence of the 1899 marked stone or mound of stone.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 20 inches in the ground, magnet at base, in a mound of stone, 3 feet base, to brass cap marked

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T42S R26E

$$\frac{1/4 \text{ } \overline{\text{S21}}}{\text{S28}}$$

2014

Set a steel fencepost north of the corner.

Corner is located on a steep, west-facing, rocky slope.

79.716 The corner of sections 20, 21, 28, and 29.

N. 0°16.9' W., between sections 20 and 21.

40.125 The 1/4 section corner of sections 20 and 21, monumented with a sandstone, 22 x 6 x 6 inches, marked 1/4 on one face (record: 18 x 8 x 6 inches, marked 1/4 S on west face), lying loose on the ground; with an embedded mound of stone, 2 feet base, west of the corner (record: 2 feet base, 1 1/2 feet high, west of the corner).

At the corner (loose marked stone, immediately east of the embedded mound of stone)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 12 inches in the ground to bedrock, magnet at base, in a mound of stone, 2 1/2 feet base, with brass cap marked

T42S R26E

1/4

$$\text{S20} \left| \text{S21} \right.$$

2014

Bury original marked stone in mound of stone.

Set a steel fencepost north of the corner.

Corner is located in rocky, eroded terrain.

N. 0°01.0' W., beginning new measurement.

39.889 The corner of sections 16, 17, 20, and 21, monumented with an unrecorded iron bar, 5/8 x 5/8 inch square, firmly set, projecting 3 inches above exposed sandstone bedrock, with aluminum cap, 1 1/4 inches diameter, marked 16/17/20/21; with 16/17/20/21 chiseled into bedrock around the corner. There is no remaining evidence of the 1899 sandstone or mound of stone. The position of this monument is harmoniously related to existing corners and is accepted as the best available evidence of the original corner.

Raise a mound of stone, 2 feet base, 2 feet high, southeast of the corner.

Corner is located on top of a narrow sandstone ridge extending

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

east and west.

From the corner of sections 15, 16, 21, and 22.

S. 89°49.6' W., between sections 16 and 21.

- 39.838** Point for the 1/4 section corner of sections 16 and 21, at proportionate distance. There is no remaining evidence of the 1899 marked stone or mound of stone.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 3 inches in the ground to bedrock, magnet at base, in a mound of stone, 3 feet base to, brass cap marked

T42S R26E
1/4 $\frac{S16}{S21}$
2014

Set a steel fencepost west of the corner.

Corner is located in rocky, eroded ground, on a south-facing slope.

- 79.676** The corner of sections 16, 17, 20, and 21.
-

N. 0°00.9' W., between sections 16 and 17.

- 40.199** The 1/4 section corner of sections 16 and 17, monumented with a sandstone, 18 x 8 x 7 inches, firmly set, projecting 11 inches above a mound of stone, 4 feet base, 1 foot high, marked 1/4 on west face. (record: 18 x 18 x 6 inches). There is no remaining evidence of the 1899 mound of stone.

At the corner (marked stone)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 5 inches in the ground, magnet at base, in a mound of stone, 4 feet base, to brass cap marked

T42S R26E
1/4
S17 | S16
2014

Bury original marked stone in mound of stone.

Set a steel fencepost northeast of the corner.

N. 0°08.2' E., beginning new measurement.

- 39.738** The corner of sections 8, 9, 16, and 17, monumented with an

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

unrecorded iron pipe, 1 inch diameter, firmly set, projecting 12 inches above an embedded mound of stone, 2 feet base, capped with a steel plate, 1 1/2 x 1 1/2 inches square, marked T42S R26E 8/9/16/17. There is no remaining evidence of the 1899 marked stone or mound of stone. The position of this monument is harmoniously related to existing corners and is accepted as the best available evidence of the original corner.

At the corner (iron pipe)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 6 inches in the ground, magnet at base, in a mound of stone, 4 feet base, to brass cap marked

T42S R26E	
S8	S9
S17	S16
2014	

Bury iron pipe inside stainless steel post.

Corner is located on a moderately-steep, rocky, southeast-facing hillside.

From the corner of sections 9, 10, 15, 16.

S. 89°49.5' W., between sections 9 and 16.

- 39.947** Point for the 1/4 section corner of sections 9 and 16, at proportionate distance. There is no remaining evidence of the 1899 marked stone or mound of stone.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, magnet at base, with brass cap marked

T42S R26E	
S9	
1/4	S16
2014	

Set a steel fencepost north of the corner.

From the corner, an old water well in a cement enclosure called "Aneth", bears N. 4°21' E., 4.17 chains distance.

- 79.894** The corner of sections 8, 9, 16, and 17.

N. 0°01.8' E., between sections 8 and 9.

- 40.208** The 1/4 section corner of sections 8 and 9, monumented with a sandstone, 15 x 13 x 2 inches, marked 1/4 on one face (record: 14 x 10 x 3 inches), loosely set, projecting 13 inches above the

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

ground; with a mound of stone, 2 feet base, 2 feet high, west of the corner.

At the corner (marked stone)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 8 inches in the ground to bedrock, magnet at base, in a mound of stone, 3 feet base, to brass cap marked

T42S R26E
1/4
S8 | S9
2014

Bury original marked stone in mound of stone.

Set a steel fencepost northeast of the corner.

Corner is located on a rocky, west-facing slope.

N. 0°01.5' W., beginning new measurement.

- 40.004** The corner of sections 4, 5, 8, and 9, monumented with a sandstone, 17 x 10 x 9 inches (record: 16 x 10 x 8 inches), firmly set, projecting 10 inches above the ground, with 5 notches on south edge, 4 notches on east edge; in an embedded mound of stone, 2 feet base (record: 2 feet base, 1 1/2 feet high, west of the corner).

At the corner (marked stone)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 10 inches in the ground to bedrock, magnet at base, in a mound of stone, 3 feet base, to brass cap marked

T42S R26E
S5 | S4
S8 | S9
2014

Bury original marked stone in mound of stone.

Set a steel fencepost northeast of the corner.

Corner is located in rocky ground, on an east-facing slope.

From the corner of sections 3, 4, 9, and 10.

N. 89°47.9' W., between sections 4 and 9.

- 39.896** The 1/4 section corner of sections 4 and 9, monumented with a

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

sandstone, 16 x 8 x 5 inches, marked 1/4 on one face (record: 14 x 10 x 8 inches, marked 1/4 S on north face), lying loose on an embedded mound of stone, 2 feet base (record: a mound of stone 2 feet base, 1 1/2 feet high, north of the corner).

At the corner (immediately south of the embedded mound of stone)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 15 inches in the ground, magnet at base, in a mound of stone, 3 feet base, to brass cap marked

T42S R26E
S4
1/4
S9
2014

Set a steel fencepost north of the corner.

Corner is located in rolling, rocky soil.

N. 89°58.6' W., beginning new measurement.

40.058 The corner of sections 4, 5, 8, and 9.

N. 0°00.1' E., between sections 4 and 5.

40.029 The 1/4 section corner of sections 4 and 5, monumented with a sandstone, 17 x 11 x 5 inches, marked 1/4 on one face (record: 16 x 10 x 4 inches, marked 1/4 S on west face), lying loose on an embedded mound of stone, 2 feet diameter (record: a mound of stone 2 feet base, 1 1/2 feet high, west of the corner).

At the corner (immediately east of the embedded mound of stone)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 22 inches in the ground, magnet at base, in a collar of stone, 3 feet base, with brass cap marked

T42S R26E
1/4
S5 | S4
2014

Set a steel fencepost north of the corner.

From this point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 1/4 inches diameter, set flush in top of pier, marked PT 108+60, bears N.11°40.4'E., 12.959 chains distance; with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, west of the pier.

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

From this same point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 1/4 inches diameter, set flush in top of pier, marked PT 103+60, bears N.42°37.1'E., 13.738 chains distance; with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, west of the pier.

From this same point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 1/4 inches diameter, set flush in top of pier, marked PT 103+60, bears N.50°9.5'E., 11.185 chains distance; with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, west of the pier.

Corner is located on a rolling mesa top, with grasses.

N. 0°01.8' E., beginning new measurement.

12.439 Centerline of Utah State Highway 262, paved, 25 feet wide, bears N. 61°W., S. 63°E.

40.016 The corner of sections 4, 5, 32, and 33, on the north boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 4 inches above a collar of stone, 3 feet base, with brass cap marked as described in the official record of the 2004-05 resurvey.

Corner is located near the top of a knoll, in barren, rocky ground.

From the corner of sections 5, 6, 31, and 32, on the south boundary of the township, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 9 inches above the ground, with brass cap marked as described in the official record of the 2012-13 resurvey; with an embedded mound of stone, 3 feet base, 2 feet high, east of the corner, and a steel fence post north of the corner.

Corner lies in gently-rolling open terrain, with sparse vegetation, 44 links distance east of the centerline of San Juan County Road 475, an improved gravel road, 20 feet wide, bearing N.22°W., S.22°E.

Survey of a Portion of the Subdivisional Lines,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

N. 0° 15.6' E., between sections 31 and 32.

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 36.708** Point for the 1899 meander corner of sections 31 and 32, and the right bank of the San Juan River, at record distance, from the corner of sections 29, 30, 31, and 32. There is no remaining evidence of the 1899 cottonwood post or bearing trees.

Resurvey of a Portion of the Subdivisional Lines,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
H.D. Page and J.M. Lentz in 1899

Continue measurement.

- 39.979** Point for the 1/4 section corner of sections 31 and 32, determined at midpoint between section corners. There is no remaining evidence of the 1899 marked stone or mound of stone.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

T42S R26E
1/4
S31 | S32
2014

Set a steel fencepost northwest of the corner.

Corner is located on the floodplain of the San Juan River, in tamarisk, Russian olive, and cottonwood trees.

- 66.195** Point selected for the witness corner to the meander corner of sections 31 and 32, and the present left bank of the San Juan River.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 29 inches in the ground, magnet at base, with brass cap, marked

WC
T42S R26E
MC
S31 | S32
2014

Set a steel fencepost north of the corner.

Corner is located on the floodplain of the San Juan River.


- 67.670** True point for the meander corner of sections 31 and 32, on the present left bank of the San Juan River.

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 70.782** True point for the meander corner of sections 31 and 32, on the present right bank of the San Juan River.
- 72.668** Point selected for the witness corner to the meander corner of sections 31 and 32, and the present right bank of the San Juan River.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 16 inches in the ground to bedrock, magnet at base, in a mound of stone, 3 feet base, to brass cap marked




Set a steel fencepost north of the corner.

Corner is located on the edge of a fairly level bench, approximately 80 feet elevation above the San Juan River to the southwest.

- 79.958** The corner of sections 29, 30, 31, and 32, monumented with a sandstone, 17 x 8 x 3 inches, broken and lying loose on an embedded mound of stone, 3 feet base, faint and indiscernible marks on one edge (record: 16 x 6 x 3 inches, marked with 5 notches on the east edge, 1 notch on the south edge; with a mound of stone, 2 feet base, 1 1/2 feet high, west of the corner).

At the corner (immediately east of mound of stone).

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground, magnet at base, in a mound of stone, 3 feet base, to brass cap marked



Set a steel fencepost north of the corner.

Corner is located on the fairly level floodplain of the San Juan River.

From the corner of sections 28, 29, 32, and 33.

S. 89°59.2' W., between sections 29 and 32.

- 39.928** The 1/4 section corner of sections 29 and 32, monumented with an

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

unrecorded iron pipe, 1 inch diameter, firmly set, projecting 14 inches above an embedded collar of stone, 2 feet base, capped with a steel plate, 1 1/2 x 1 1/2 inches square, marked 1/4 29/32. There is no remaining evidence of the 1899 marked stone or mound of stone. The position of this monument is harmoniously related to existing corners and is accepted as the best available evidence of the original corner.

At the corner (iron pipe)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 25 inches in the ground, magnet at base, in a collar of stone, 2 feet base, with brass cap marked

T42S R26E
 S29
1/4 ———
 S32
2014

Bury iron pipe next to the corner.

Set a steel fencepost northeast of the corner.

Corner is located on a fairly level bench above the floodplain of the San Juan River.

S. 89°54.1' W., beginning new measurement.

39.996 The corner of sections 29, 30, 31, and 32.

S. 89°48.6' W., between sections 30 and 31.

14.228 The 1899 meander corner of sections 30 and 31, and the right bank of the San Juan River, monumented with a cobblestone, 13 x 9 x 5 inches, firmly set, in an embedded mound of stone, 2 feet base, marked MC on west face (record: 14 x 10 x 5 inches, marked MC on west face, 1 groove on south face; with a mound of stone 2 feet base, 1 1/2 feet high, west of the corner)

This corner now functions as a witness corner to the meander corner of sections 30 and 31, and the present right bank of the San Juan River.

At the corner (marked stone)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 15 inches in the ground, magnet at base, in a mound of stone, 3 feet base, to brass cap marked

WC
T42S R26E
 S30
←——
MC S31
 2014

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fencepost east of the corner, remove original marked stone.

Corner is located near the top edge of a steep, cobblestone-covered slope.

Survey of a Portion of the Subdivisional Lines,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

S. 89°59.2' W., beginning new measurement.

- 6.204** True point for the meander corner of sections 30 and 31, and the present right bank of the San Juan River.
- 9.838** True point for the meander corner of sections 30 and 31, and the present left bank of the San Juan River.
- 11.273** Point selected for the witness corner to the meander corner of sections 30 and 31, and the present left bank of the San Juan River.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

WC
T42S R26E

$$\begin{array}{c} \text{S30} \\ \hline \text{S31} \end{array} \rightarrow \text{MC}$$

2014

Set a steel fencepost west of the corner.

Corner is located on the floodplain of the San Juan River.

- 25.772** Point for the 1/4 section corner of sections 30 and 31, calculated at a distance of 40 chains westerly from the corner of sections 29, 30, 31, and 32, on the line controlled by the witness meander corner of sections 30 and 31, on the present left bank and the corner of sections 25, 30, 31, and 36, on the west boundary of the township.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

T42S R26E

$$\begin{array}{c} \text{S30} \\ \hline \text{S31} \end{array}$$

1/4

2014

Set a steel fencepost north of the corner.

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located in the floodplain of the San Juan River.

29.820 Centerline of San Juan County Road 475, an improved gravel road, 20 feet wide, bears N.18°W., S.18°E.

65.899 The corner of sections 25 and 36, on the west boundary of the township, monumented with an iron post, 2 1/2 inches diameter, firmly set, flush in a mound of stone, 6 feet base, 3 feet high, with brass cap marked as described in the official record of the 2012-13 resurvey. This corner now functions as the corner of sections 25, 30, 31, and 36.

Add marks S30/S31 R26E 2014 to cap.

Corner is located on a south-facing slope, in rough, rocky terrain.

Resurvey of a portion of the subdivisional lines,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
H.D. Page and J.M. Lentz in 1899

From the corner of sections 29, 30, 31, and 32.

NORTH, between sections 29 and 30.

40.000 Point for the 1/4 section corner of sections 29 and 30, at midpoint between section corners. The 1899 marked cobblestone, 15 x 10 x 7 inches, marked 1/4 on one face (record: 16 x 8 x 6 inches, marked with 1/4 on west face; with a mound of stone, 2 feet base, 1 1/2 feet high, west of the corner), buried nearby, and determined to have been disturbed by road construction activities.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 22 inches in the ground, magnet at base, in a collar of stone, 2 feet base, with brass cap marked

T42S R26E
1/4
S30 | S29
2014

Bury original marked stone alongside the corner.

Set a steel fencepost north of the corner.

Corner is located on the fairly level floodplain above the San Juan River.

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 62.450** Point for the 1899 meander corner of sections 29 and 30, and the right bank of the San Juan River, at record distance, there is no remaining evidence of the 1899 marked stone or mound of stone.

Survey of a portion of the subdivisional lines,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

- 80.000** Point for the corner of sections 19, 20, 29, and 30, calculated at 80 chains north from corner of sections 29, 30, 31, and 32.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, magnet at base, with brass cap marked

T42S R26E

S19	S20
S30	S29

2014

Set a steel fence post north of the corner.

Corner is located on the floodplain of the San Juan River, in dense tamarisk trees.

Resurvey of a portion of the subdivisional lines,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
H.D. Page and J.M. Lentz in 1899

From the corner of sections 20, 21, 28, and 29

N. 89°42.6' W., between sections 20 and 29.

- 40.138** The 1/4 section corner of sections 20 and 29, monumented with an unrecorded iron pipe, 1 inch diameter, base rusted out, capped with a steel plate, 1 1/2 x 1 1/2 inches square, marked 1/4 20/29, with a sandstone, 12 x 11 x 4 inches, marked 1/4 S on one face, buried to the west (record: a cobblestone, 15 x 8 x 6 inches, marked with 1/4 on north face; with a mound of stone, 2 feet base, 1 1/2 feet high, north of the corner), in mound of stone. This position is accepted as a careful and faithful perpetuation of the original corner.

At the corner (iron pipe)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 22 inches in the ground, magnet at base, in a mound of stone, 2 feet base, to brass cap marked

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T42S R26E
 S20
 1/4 ———
 S29
 2014

Bury original marked stone and iron pipe alongside the corner.

Set a steel fencepost north of the corner.

Corner is located south of an unimproved dirt road.

Survey of a Portion of the Subdivisional Lines,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

WEST, beginning new measurement.

- 10.350** Point for the 1899 meander corner of sections 20 and 29, and the right bank of the San Juan River, at record bearing and distance. There is no remaining evidence of the 1899 corner or mound of stone (record: an "+" chiseled into bedrock, with an MC on the west face and 2 grooves on the south face; with a mound of stone, 2 feet base 1 1/2 high east of the corner).
- 39.978** The corner of sections 19, 20, 29, and 30.

S. 89°57.9' W., between sections 19 and 30.

- 4.190** Point selected for the witness corner to the meander corner of sections 19 and 30, and the present right bank of the San Juan River.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 29 inches in the ground, magnet at base, with brass cap marked

WC
 T42S R26E
 S19
 ←———
 S30
 MC
 2014

Set a steel fencepost north of the corner.

Corner is located in dense tamarisk trees, near the right bank of the San Juan River.

- 5.975** True point for the meander corner of sections 19 and 30, on the present right bank of the San Juan River.
- 8.876** True point for the meander corner of sections 19 and 30, on the present left bank of the San Juan River.

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH


CHAINS

- 13.697** Point selected for the witness corner to the meander corner of sections 19 and 30, and the present left bank of the San Juan River.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, magnet at base, with brass cap marked

WC
T42S R26E

S19
S30
2014



Corner is located on a rocky bluff above the San Juan River to the southeast.

- 29.542** Centerline of San Juan County Road 475, an improved gravel road, 20 feet wide, bears N. 44° E., S. 38° W.
- 40.000** Point for the 1/4 section corner of sections 19 and 30.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground, magnet at base, in a mound of stone, 3 feet base, to brass cap marked

T42S R26E
1/4 $\frac{S19}{S30}$
2014

Set a steel fencepost north of the corner.

Corner is located in rolling, rocky ground, with brush.

- 80.118** The corner of sections 24 and 25, on the west boundary of the township, monumented with an iron post, 2 1/2 inches diameter, firmly set, with brass cap marked as described in the official record of the 2012-13 resurvey. This corner now functions as the corner of section 19, 24, 25, and 30.

Add marks S19/S30 R26E 2014 to cap.

From the corner of sections 19, 20, 29, and 30.

N. 0°03.1' W., between sections 19 and 20.


- 3.307** Point selected for the witness corner to the meander corner of sections 19 and 20, and the present right bank of the San Juan River.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

long, 29 inches in the ground, magnet at base, with brass cap marked




Set a steel fencepost north of the corner.

Corner is located on the right bank of the San Juan River, in dense tamarisk and Russian olive trees.

- 6.716** True point for the meander corner of sections 19 and 20, on the present right bank of the San Juan River.
- 10.373** True point for the meander corner of sections 19 and 20, on the present left bank of the San Juan River.
- 16.660** Point selected for the witness corner to the meander corner of sections 19 and 20, and the present left bank of the San Juan River.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 22 inches in the ground, magnet at base, in a collar of stone, 2 feet base, with brass cap marked




Set a steel fencepost north of the corner.

Corner is located on the south edge of the top of a gravel bench, above the San Juan River to the southeast.

- 39.970** Point for the 1/4 section corner of sections 19 and 20, at midpoint between section corners.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 15 inches in the ground, magnet at base, in a mound of stone, 2 feet base, to brass cap marked



RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH


CHAINS

Set a steel fencepost north of the corner.

Corner is located on a fairly level bench, with cobblestones and no vegetation.

- 51.804** Point selected for the witness corner to the meander corner of sections 19 and 20, and the present left bank of the San Juan River.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, magnet at base, with brass cap marked




Set a steel fencepost north of the corner.

Corner is located on the left bank of the San Juan River, near the base of a gravel terrace, above the dense floodplain vegetation.

- 53.845** True point for the meander corner of sections 19 and 20, on the present left bank of the San Juan River.
- 55.750** True point for the meander corner of sections 19 and 20, on the present southerly bank of an island in the San Juan River.
- 56.829** Point selected for the witness corner to the meander corner of sections 19 and 20, and the present southerly bank of an island in the San Juan River.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 26 inches in the ground, magnet at base, with brass cap marked



Set a steel fencepost north of the corner.

Corner is located in tamarisk and Russian olive trees, on an island in the San Juan River.


- 62.740** Point selected for the witness corner to the meander corner of sections 19 and 20, and the present northerly bank of an island

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

in the San Juan River.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap, marked



Set a steel fencepost north of the corner.

Corner is located in tamarisk and Russian olive trees, on an island in the San Juan River.

- 63.818** True point for the meander corner of sections 19 and 20, on the present northerly bank of an island in the San Juan River.
- 67.033** True point for the meander corner of sections 19 and 20, on the present right bank of the San Juan River.


Resurvey of a Portion of the Subdivisional Lines, T. 42 S.,
R. 26 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
H.D. Page and J.M. Lentz in 1899

Continue measurement.

- 67.407** Point for the 1899 meander corner of sections 19 and 20, and the right bank of the San Juan River, at record distance, from the corner of sections 17, 18, 19, and 20. There is no remaining evidence of the 1899 marked boulder or mound of stone.
- 68.094** Point selected for the witness corner to the meander corner of sections 19 and 20, and the present right bank of the San Juan River.

Set a stainless steel post 2 1/2 inches diameter, 30 inches long, 14 inches in the ground, magnet at base, in a mound of stone, 3 feet base, to brass cap marked



RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

79.940 The corner of sections 17, 18, 19, and 20, monumented with a sandstone, 13 x 7 x 6 inches, lying loose next to an embedded mound of stone, 2 feet base, marked with 5 notches on one edge, 3 notches on other edge (record: 12 x 8 x 6 inches, marked with 5 notches on the east edge, 3 notches on the south edge; with a mound of stone, 2 feet base, 1 1/2 feet high, west of the corner).

At the corner (immediately east of embedded mound of stone)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, magnet at base, in a collar of stone, 2 feet base, with brass cap marked

T42S R26E	
S18	S17
S19	S20
2014	

Bury original marked stone alongside of the corner.

Set a steel fencepost east of the corner.

Corner is located on the fairly level bench above the floodplain of the San Juan River.

From the corner of sections 16, 17, 20, and 21.

N. 89°46.0' W., between sections 17 and 20.

39.941 The 1/4 section corner of sections 17 and 20, determined immediately south of an embedded mound of stone, 2 feet base, 1 foot high; with a sandstone, 16 x 9 x 6 inches, lying loose approximately 50 links away, marked 1/4 S on one face (record: cobblestone, 14 x 8 x 7 inches, marked 1/4 S on north face; with a mound of stone, 2 feet base, 1 1/2 feet high, north of the corner).

At the corner (immediately south of mound of stone)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 22 inches in the ground, magnet at base, in a mound of stone, 3 feet base, to brass cap marked

T42S R26E	
	S17
1/4	-----
	S20
2014	

Bury original marked stone in mound of stone.

Set a steel fencepost northeast of the corner.

Corner is located on rocky, barren ground, on a gentle north

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

slope.


S. 89°57.0' W., beginning new measurement.

40.023 The corner of sections 17, 18, 19, and 20.

N. 89°58.4' W., between sections 18 and 19.

19.634 Point selected for the witness corner to the meander corner of sections 18 and 19, and the present right bank of the San Juan River.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked



Set a steel fencepost west of the corner.

Corner is located at the base of a rocky slope to the northwest.

24.000 Point for the 1899 meander corner of sections 18 and 19, and the right bank of the San Juan River, at record distance. There is no remaining evidence of the 1899 marked stone or mound of stone.


Survey of a Portion of the Subdivisional Lines,
T.42 S., R. 26 E., Salt Lake Meridian, Utah

24.748 True point for the meander corner of sections 18 and 19, on the present right bank of the San Juan River.

27.869 True point for the meander corner of sections 18 and 19, on the present left bank of the San Juan River.

28.937 Point selected for the witness corner to the meander corner of sections 18 and 19, and the present left bank of the San Juan River.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked



RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

Set a steel fencepost south of the corner.

Corner is located on the left bank of the San Juan River, in tamarisk and Russian olive trees.

40.000 Point for the 1/4 section corner of sections 18 and 19.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, magnet at base, with brass cap marked

T42S R26E
S18
1/4 ———
S19
2014

Set a steel fencepost south of the corner.

Corner is located in sandy ground on the floodplain of the San Juan River.

60.868 Centerline of San Juan County Road 475, an improved gravel road, 20 feet wide, bears N. 31° W., S. 35° E.

65.726 Centerline of San Juan County Road 475, an improved gravel road, 20 feet wide, bears N. 10° W., S. 10° E.

80.027 The corner of sections 13 and 24, on the west boundary of the township, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 15 inches above an embedded collar of stone, 3 feet base, with brass cap marked as described in the official record of the 2012-13 resurvey. This corner now functions as the corner of sections 13, 18, 19, and 24.

Add marks S18/S19 R26E 2014 to cap.

Resurvey of a Portion of the Subdivisional Lines,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
H.D. Page and J.M. Lentz in 1899

From the corner of sections 17, 18, 19, and 20.

N. 0°02.4' E., between sections 17 and 18.

39.971 The 1/4 section corner of sections 17 and 18, monumented with a sandstone, 16 x 8 x 5 inches, firmly set, projecting 6 inches above the ground, marked 1/4 on west face (record: 18 x 8 x 6 inches; with a mound of stone, 2 feet base, 1 1/2 feet high, west of the corner).

At the corner (marked stone)

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, magnet at base, with brass cap marked

T42S R26E
1/4
S18 | S17
2014

Bury original marked stone alongside the corner.

Set a steel fencepost north of the corner.

Corner is located on a gentle northeast slope, in dirt hills with shadscale.

N. 0°00.8' E., beginning new measurement.

- 40.011** The corner of sections 7, 8, 17, and 18, monumented with a sandstone, 21 x 11 x 6 inches, lying loose on an embedded mound of stone, 2 feet base, marked with 5 notches on one edge, 4 notches on other edge (record: 18 x 10 x 8 inches, marked with 5 notches on the east edge, 4 notches on the south edge; with a mound of stone, 2 feet base, 1 1/2 feet high, west of the corner).

At the corner (immediately east of mound of stone)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 26 inches in the ground, magnet at base, in a collar of stone, 3 feet base, with brass cap marked

T42S R26E
S7 | S8
S18 | S17
2014

Bury original marked stone in collar of stone.

Set a steel fencepost north of the corner.

Corner is located in rocky, rolling ground.

From the corner of sections 8, 9, 16, and 17.

N. 89°50.3' W., between sections 8 and 17.

- 39.916** The 1/4 section corner of sections 8 and 17, monumented with a sandstone, 18 x 12 x 5 inches, loosely set, projecting 13 inches above the ground, marked 1/4 on north face (record: 16 x 10 x 5 inches; with a mound of stone, 2 feet base, 1 1/2 feet high, north of the corner).

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner (marked stone)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 22 inches in the ground, magnet at base, in a mound of stone, 3 feet base, to brass cap marked

T42S R26E
S8
1/4
S17
2014

Set a steel fencepost north of the corner.

Corner is located on a rocky, southeast-facing slope.

N. 89°54.7' W., beginning new measurement.

40.078 The corner of sections 7, 8, 17, and 18.

N. 89°56.5' W., between sections 7 and 18.

38.850 Point for the 1899 meander corner of sections 7 and 18, and the right bank of the San Juan River, at record distance. There is no remaining evidence of the 1899 marked stone or mound of stone.

40.000 Point for the 1/4 section corner of sections 7 and 18, at record distance. There is no remaining evidence of the 1899 marked stone or mound of stone.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, magnet at base, with brass cap marked

T42S R26E
S7
1/4
S18
2014

Set a steel fencepost north of the corner.

Corner is located on the flood plain of the San Juan River, in a formerly cultivated field.

73.700 Point for the 1899 meander corner of sections 7 and 18, and the right bank of the San Juan River, at record distance. There is no remaining evidence of the 1899 marked stone or mound of stone.


Survey of a Portion of the Subdivisional Lines,
T. 42 S., R. 26 E., Salt Lake Meridian. Utah

75.084 Point selected for the witness corner to the meander corner of sections 7 and 18, and the present right bank of the San Juan

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

River.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 29 inches in the ground, magnet at base, with brass cap marked



Set a steel fencepost north of the corner.

Corner is located in dense tamarisk and Russian Olive trees, on the right bank of the San Juan River.

77.470 True point for the meander corner of sections 7 and 18, on the present right bank of the San Juan River.

80.051 The true point for the corner of sections 12 and 13, on the west boundary of the township. Point falls in San Juan River. This now functions as the corner of sections 7, 12, 13, and 18.

From the true point, the 1953 witness corner to the corner of sections 12 and 13, now functioning as the witness corner to the corner of sections 7, 12, 13, and 18, monumented with an iron post, 2 1/2 inches diameter, firmly set, flush with the ground, with brass cap (BLM) marked as described in the official record of the 2012-13 resurvey, bears S. 0°00.2' W., 3.651 chains distance; with a mound of stone, 3 feet base, 2 feet high, 4 links, west of the corner.

Add S7, S18, R26E, and 2014 to cap. Corner also functions as witness corner to meander corner of sections 13 and 18, and the present left bank of the San Juan River.

Corner is located on the left bank of the San Juan River.

Resurvey of a Portion of the Subdivisional Lines,
T.42 S., R. 26 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
H.D. Page and J.M. Lentz in 1899

From the corner of sections 7, 8, 17, and 18.

N. 0°00.7' W., between sections 7 and 8.

40.051 Point for the 1/4 section corner of sections 7 and 8, at proportionate distance. There is no remaining evidence of the 1899 marked stone or mound of stone.

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 16 inches in the ground to bedrock, magnet at base, in a mound of stone, 3 feet base, to brass cap marked

T42S R26E
1/4
S7 | S8
2014

Corner is located on a spur above the San Juan River flood plain to the south.

- 80.102** The corner of sections 5, 6, 7, and 8, monumented with a sandstone, 21 x 14 x 5 inches, lying loose on an embedded mound of stone, 2 feet base, 5 notches on one corner, 5 notches on other corner, (record: 18 x 12 x 6 inches, marked with 5 notches on south edge, 5 notches on east edge, with a mound of stone, 2 feet base, 1 1/2 feet high, west of the corner).

At the corner (immediately east of mound of stone)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 12 inches in the ground to bedrock, magnet at base, in a mound of stone, 3 feet base, to brass cap marked

T42S R26E
S6 | S5
S7 | S8
2014

Bury original marked stone in mound of stone.

Set a steel fencepost north of the corner.

Corner is located on a rocky, southwest-facing slope.

From the corner of sections 4, 5, 8, and 9.

N. 89°59.7' W., between sections 5 and 8.

- 40.005** The 1/4 section corner of sections 5 and 8, monumented with a sandstone, 18 x 7 x 7 inches, firmly set, buried in the ground, marked 1/4 on one face; with an embedded mound of stone, 2 feet base, north of the corner (record: 18 x 8 x 8 inches, marked 1/4 S on the north face; with a mound of stone, 2 feet base, 1 1/2 feet high, north of the corner).

At the corner (marked stone)

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 20 inches in the ground, magnet at base, in a collar of stone, 2 feet base, with brass cap marked

T42S R26E
S5
1/4 ———
S8
2014

Set a steel fencepost north of the corner.

Corner is located on gently-rolling, barren clay hills.

N. 89°54.7' W., beginning new measurement.

39.995 The corner of sections 5, 6, 7, and 8.

N. 88°59.0' W., between sections 6 and 7.

40.004 The 1/4 section corner of sections 6 and 7, monumented with a sandstone, 15 x 11 x 7 inches, loosely set, projecting 12 inches above the ground, marked 1/4 on north face; with an embedded collar of stone, 2 feet base, north of the corner (record: 16 x 10 x 8 inches; with a mound of stone, 2 feet base, 1 1/2 feet high, north of the corner).

At the corner (marked stone)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 16 inches in the ground, magnet at base, in a mound of stone, 2 1/2 feet base, to brass cap marked

T42S R26E
S6
1/4 ———
S7
2014

Bury original marked stone in mound of stone.

Set a steel fencepost north of the corner.

Corner is located in rocky, rolling terrain, with no vegetation.

S. 88°59.7' W., beginning new measurement.

40.026 The corner of sections 1, 6, 7, and 12, on the west boundary of the township, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 1 inch above the ground, with brass cap (BLM) marked as described in the official record of the 2012-13 resurvey.

Set a steel fencepost north of the corner.

RESURVEY AND SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

Corner is located in sandy ground on the floodplain of the San Juan River.

From the corner of sections 5, 6, 7, and 8.

N. 0°05.8' E., between sections 5 and 6.

- 40.005** Point for the 1/4 section corner of sections 5 and 6, at proportionate distance. There is no remaining evidence of the 1899 marked stone or mound of stone.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 12 inches in the ground, magnet at base, in a mound of stone, 3 feet base, to brass cap marked

T42S R26E
1/4
S6 | S5
2014

Set a steel fencepost north of the corner.

Corner is located on a rocky hillside.

- 80.010** The corner of sections 5, 6, 31, and 32, on the north boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, flush in an embedded mound of stone, 3 feet base, with brass cap marked as described in the official record of the 2005 resurvey.

Set a steel fencepost south of the corner.

Corner is located in an area of ground disturbance due to pipeline construction.

The Subdivision of Section 3,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 3 and 10.

N. 0°18.4 E., on the north-south centerline of section 3.

- 40.397** Point for the center 1/4 section corner of section 3, at intersection with the east-west centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 19 inches in the ground, magnet at base, in a mound of stone, 4 feet base, to brass cap marked

THE SUBDIVISION OF SECTION 3,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T42S R26E

C 1/4 S3

2014

Set a steel fencepost west of the corner.

Corner is located on a moderately-steep, west-facing slope of shale.

- 80.525** The 1/4 section corner of sections 3 and 34, on the north boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 3 inches above the ground, with brass cap marked as described in the official record of the 2005 resurvey; with a mound of stone, 1 foot base, 1 foot high, north of the corner

Corner is located in open rolling terrain.

From the 1/4 section corner of section 3 only, on the Utah-Colorado state boundary line, hereinbefore described.

N. 89°51.9' W., on the east-west centerline of section 3.

- 30.054** The center 1/4 section corner of section 3.

- 69.990** The 1/4 section corner of sections 3 and 4.

The Subdivision of Section 4,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 4 and 9.

N. 0°00.1 W., on the north-south centerline of section 4.

- 30.209** Centerline of Utah State Highway 262, paved, 25 feet wide, bears N. 48° W., S. 51° E.

- 40.074** Point for the center 1/4 section corner of section 4, at intersection with the east-west centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, magnet at base, in a collar of stone, 2 1/2 feet base, with brass cap marked

T42S R26E

C 1/4 S4

2014

Set a steel fencepost east of the corner.

From this point, a Right-of-Way monument, a cement pier, 6 inches

THE SUBDIVISION OF SECTION 4,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 1/4 inches diameter, set flush in top of pier, marked PC 89+55.07, bears S.88°52.6'W., 12.422 chains distance; with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, west of the pier.

From this same point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 1/4 inches diameter, set flush in top of pier, marked PC 89+55.07, bears N.79°17.3'W., 10.522 chains distance; with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, west of the pier.

Corner is located in rocky, barren ground, northeast of paved highway Utah 262, 25 feet wide, bears N.46°W., S.46°E.

- 80.074** The 1/4 section corner of sections 4 and 33, on the north boundary of the township, hereinbefore described.

From the 1/4 section corner of sections 3 and 4.

S. 89°57.5' W., on the east-west centerline of section 4.

- 25.900** Centerline of improved gravel road, 20 feet wide, bears N.49°W., S.49°E.
- 39.945** The center 1/4 section corner of section 4.
- 50.327** Centerline of Utah State Highway 262, paved, 25 feet wide, bears N.48°W., S.46°E.
- 79.997** The 1/4 section corner of sections 4 and 5.

The Subdivision of Section 5,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 5 and 8.

N. 0°03.6 E., on the north-south centerline of section 5.

- 40.046** Point for the center 1/4 section corner of section 5, at intersection with the east-west centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 3 inches in the ground to bedrock, magnet at base, in a mound of stone, 4 feet base, to brass cap marked

THE SUBDIVISION OF SECTION 5,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T42S R26E

C 1/4 S5

2014

Set a steel fencepost southeast of the corner.

Corner is located in rocky, barren ground, northwest of an improved gravel road.

74.162 Centerline of Utah State Highway 262, paved, 25 feet wide, bears N. 61°W., S. 61°E.

80.055 The 1/4 section corner of sections 5 and 32, on the north boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 4 inches above the ground, with brass cap marked as described in the official record of the 2005 resurvey; with a mound of stone, 2 feet base, 1 foot high, north of the corner, and a steel fencepost southeast of the corner.

From this point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 1/4 inches diameter, set flush in top of pier, marked PC 143+75, bears S.51°24.6'W., 7.244 chains distance.

From this same point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 1/4 inches diameter, set flush in top of pier, marked PC 143+75, bears S.66°28.6'W., 4.623 chains distance; with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, west of the pier.

Corner is located in open, fairly level rocky ground, and no vegetation.

From the 1/4 section corner of sections 4 and 5.

N. 89°58.3' W., on the east-west centerline of section 5.

39.960 The center 1/4 section corner of section 5.

79.926 The 1/4 section corner of sections 5 and 6.

The Subdivision of Section 7,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 7 and 18.

N. 0°01.0 W., on the north-south centerline of section 7.

40.029 Point for the center 1/4 section corner of section 7, at intersection with the east-west centerline.

THE SUBDIVISION OF SECTION 7,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked

T42S R26E

C 1/4 S7

2014

Set a steel fencepost southeast of the corner.

Corner is located in a previously cultivated field.

80.773 The 1/4 section corner of sections 6 and 7.

From the 1/4 section corner of sections 7 and 8.

N. 89°58.5' W., on the east-west centerline of section 7.

39.999 The center 1/4 section corner of section 7.

80.034 True point for the 1/4 section corner of section 12 only, on the west boundary of the township, falls in the floodplain of the San Juan River where it is impracticable to establish a permanent monument. Not monumented. This true point now functions as the 1/4 section corner of sections 7 and 12.

The Subdivision of Section 9,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 9 and 16.

N. 0°05.3 E., on the north-south centerline of section 9.

40.135 Point for the center 1/4 section corner of section 9, at intersection with the east-west centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with brass cap marked

T42S R26E

C 1/4 S9

2014

Set a steel fencepost north of the corner.

Corner is located in fairly level ground, with typical desert brush.

80.073 The 1/4 section corner of sections 4 and 9.

THE SUBDIVISION OF SECTION 9,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 9 and 10.

S. 89°55.8' W., on the east-west centerline of section 9.

39.849 The center 1/4 section corner of section 9.

79.832 The 1/4 section corner of sections 8 and 9.

The Subdivision of Section 10,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 10 and 15.

N. 0°24.9 E., on the north-south centerline of section 10.

40.018 Point for the center 1/4 section corner of section 10, at intersection with the east-west centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, magnet at base, in a mound of stone, 4 feet base, to brass cap marked

T42S R26E

C 1/4 S10

2014

Set a steel fencepost northeast of the corner.

Corner is located in rocky, barren ground.

70.927 Centerline of Utah State Highway 262, paved, 25 feet wide, bears N. 78° W., S. 64° E.

79.591 The 1/4 section corner of sections 3 and 10.

From the 1/4 section corner of section 10 only, on the Utah-Colorado state boundary line, hereinbefore described.

N. 89°53.9' W., on the east-west centerline of section 10.

31.314 The center 1/4 section corner of section 10.

70.918 The 1/4 section corner of sections 9 and 10.

The Subdivision of Section 18,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 18 and 19.

N. 0°01.3 E., on the north-south centerline of section 18.

THE SUBDIVISION OF SECTION 18,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 9.781** Point for the special meander corner on the present left bank of the San Juan River. Not monumented.
- 12.742** Point for the special meander corner on the present right bank of the San Juan River. Not monumented.
- 39.994** Point for the center 1/4 section corner of section 18, at intersection with the east-west centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 23 inches in the ground, magnet at base, in a collar of stone, 2 feet base, with brass cap marked

T42S R26E

C 1/4 S18

2014

Set a steel fencepost north of the corner.

Corner is located on the floodplain of the San Juan River.

- 80.004** The 1/4 section corner of sections 7 and 18.

From the 1/4 section corner of sections 17 and 18.

N. 89°56.4' W., on the east-west centerline of section 18.

- 40.009** The center 1/4 section corner of section 18.
- 65.270** Point for the special meander corner on the present right bank of the San Juan River. Not monumented.
- 67.987** Point for the special meander corner on the present left bank of the San Juan River. Not monumented.
- 80.047** True point for the 1/4 section corner of section 13 only, on the west boundary of the township, falls in the San Juan River. This true point now functions as the 1/4 section corner of sections 13 and 18.

From the true point, the witness 1/4 section corner of section 13, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 3 inches above the ground, with brass cap marked as described in the official record of the 2012-13 resurvey, bears N. 0°00.1' W., 26.0 links distance; with a mound of stone, 4 feet base, 2 feet high, southwest of the corner.

This corner now functions as the witness 1/4 section corner of sections 13 and 18.

Add marks T42S R25E R26E S18 2014 to cap.

Corner is located on steep east facing slope above the San Juan River to the east.

THE SUBDIVISION OF SECTION 20,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 20,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 20 and 29.

N. 0°00.9 W., on the north-south centerline of section 20.

- 39.945** Point for the center 1/4 section corner of section 20, at intersection with the east-west centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with brass cap marked

T42S R26E

C 1/4 S20

2014

Set a steel fencepost north of the corner.

Corner is located on the floodplain of the San Juan River, in shadscale brush.

- 79.973** The 1/4 section corner of sections 17 and 20.
-

From the 1/4 section corner of sections 20 and 21.

N. 89°58.0' W., on the east-west centerline of section 20.

- 39.946** The center 1/4 section corner of section 20.
- 65.551** Point for the special meander corner on the present right bank of the San Juan River. Not monumented.
- 68.710** Point for the special meander corner on the present left bank of the San Juan River. Not monumented.
- 79.947** The 1/4 section corner of sections 19 and 20.
-

The Subdivision of Section 22,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 22 and 27.

N. 0°17.2 W., on the north-south centerline of section 22.

- 39.729** Point for the center 1/4 section corner of section 22, at intersection with the east-west centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches

THE SUBDIVISION OF SECTION 22,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

diameter, 21 inches in the ground to bedrock, magnet at base, in a mound of stone, 3 feet base, to brass cap marked

T42S R26E

C 1/4 S22

2014

Corner is located southeast of a house, near animal corrals.

79.761 The 1/4 section corner of sections 15 and 22.

From the 1/4 section corner of section 22 only, on the Utah-Colorado state boundary line, hereinbefore described.

N. 89°50.1' W., on the east-west centerline of section 22.

32.578 The center 1/4 section corner of section 22.

72.504 The 1/4 section corner of sections 21 and 22.

The Subdivision of Section 29,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 29 and 32.

N. 0°00.4 W., on the north-south centerline of section 29.

39.945 Point for the center 1/4 section corner of section 29, at intersection with the east-west centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with brass cap marked

T42S R26E

C 1/4 S29

2014

Set a steel fencepost north of the corner.

Corner is located on a rocky bench.

79.931 The 1/4 section corner of sections 20 and 29.

From the 1/4 section corner of sections 28 and 29.

S. 89°58.8' W., on the east-west centerline of section 29.

39.870 The center 1/4 section corner of section 29.

79.857 The 1/4 section corner of sections 29 and 30.

THE SUBDIVISION OF SECTION 32,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 32,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 5 and 32, on the south boundary of the township, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 10 inches above a collar of stone, 2 1/2 feet base, with brass cap marked as described in the official record of the 2012-2013 resurvey.

N. 0°11.1 E., on the north-south centerline of section 32.

- 18.562** Point for the special meander corner on the present left bank of the San Juan River. Not monumented.
- 25.520** Point for the special meander corner on the present right bank of the San Juan River. Not monumented.
- 40.028** Point for the center 1/4 section corner of section 32, at intersection with the east-west centerline, falls in a drainage, 10 feet wide, course S. 55° W., where it is impracticable to establish a permanent monument.

From the corner, the point selected for an off-line witness corner bears S. 73°42.9' E., 0.192 chains distance.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, on bedrock, magnet at base, in a mound of stone, 3 feet base, to brass cap marked

WC
T42S R26E
C 1/4 S32
↙ 2014

Set a steel fencepost west of the corner.

Corner is located on the southeast side of the drainage, in rocky terrain.

- 80.021** The 1/4 section corner of sections 29 and 32.

From the 1/4 section corner of sections 32 and 33.

S. 89°55.4' W., on the east-west centerline of section 32.

- 40.015** The true point for the center 1/4 section corner of section 32.
- 55.815** Point for the special meander corner on the present right bank of the San Juan River. Not monumented.
- 59.416** Point for the special meander corner on the present easterly bank of an island in the San Juan River. Not monumented.
- 62.949** True point for the special meander corner on the present westerly


THE SUBDIVISION OF SECTION 32,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

bank of an island in the San Juan River. Point falls in an area subject to inundation, where it is impracticable to establish a permanent monument.

From the corner, the point selected for an off-line witness special meander corner bears N. 2°05.1' E., 0.877 chains distance.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 29 inches in the ground, with brass cap marked



Corner is located in sand, with willow and Russian olive trees.

- 66.261** Point for the special meander corner on the present left bank of the San Juan River. Not monumented.
- 80.067** The 1/4 section corner of sections 31 and 32.

Dependent Resurvey of
the Meanders of the Right Bank of the San Juan River,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

NOTE: The meander corners of the San Juan River are not monumented, unless otherwise noted.

From true point for the meander corner on the present right bank of the San Juan River, and the south boundary of the township.

From the true point, the 1953 witness corner to the meander corner of sections 5 and 32, and the right bank of the San Juan River, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above a mound of stone, 3 feet base, 2 feet high, with brass cap marked as described in the official record of the 2012-13 resurvey, bears S. 89°59.3' E., 1.903 chains distance; with a mound of stone, 4 feet base, 2 feet high, northwest of the corner.

From which,

The 1953 bearing object, an "+", chiseled into the face of a boulder, 3x1x1 feet, bears N. 64°17' W., 2.7 links distance (record: 1953 bears West, 5 links distance).

Corner is located approximately 50 feet above the San Juan River.

RESURVEY OF THE MEANDERS OF THE RIGHT BANK OF THE SAN JUAN RIVER,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Thence downstream with the meanders of the right bank of the San Juan River, through section 32.

N.34°21.3' W., 1.032 chains
N.10°39.1' W., 0.988 chains
N.27°13.9' W., 5.441 chains
N.49°02.7' W., 7.454 chains
N.51°39.3' W., 12.312 chains
N.42°58.1' W., 4.574 chains
N.18°48.5' W., 3.161 chains

The true point for the special meander corner on the north-south centerline of section 32, hereinbefore described.

N.18°48.5' W., 2.199 chains
N.14°22.8' W., 3.550 chains
N.33°46.1' W., 3.552 chains
N.58°35.9' W., 5.423 chains
N.89°37.4' W., 1.635 chains
N.61°47.5' W., 6.723 chains

The true point for the special meander corner on the east-west centerline of section 32, hereinbefore described.

N.61°47.5' W., 2.183 chains
N.48°30.4' W., 1.886 chains
N.38°16.6' W., 4.243 chains
N.44°55.4' W., 1.905 chains
N.28°06.2' W., 7.861 chains
N.17°28.0' W., 2.967 chains
N.27°15.5' W., 6.170 chains
N.44°09.4' W., 7.587 chains
N.52°45.1' W., 5.146 chains

The true point for the meander corner of sections 31 and 32, hereinbefore described.

Thence downstream with the meanders of the right bank of the San Juan River, through section 31.

N.56°49.5' W., 2.792 chains
N.65°03.4' W., 3.973 chains
N.72°31.7' W., 3.860 chains
N.67°43.8' W., 8.846 chains
N.61°19.4' W., 2.945 chains

The true point for the meander corner of sections 30 and 31, hereinbefore described.

Thence downstream with the meanders of the right bank of the San Juan River, through section 30.

N.53°20.2' W., 1.114 chains

RESURVEY OF THE MEANDERS OF THE RIGHT BANK OF THE SAN JUAN RIVER,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

N. 42°24.8' W., 4.367 chains
 N. 14°50.6' W., 1.631 chains
 N. 10°25.3' E., 2.582 chains
 N. 17°12.6' E., 2.303 chains
 N. 7°38.1' W., 4.399 chains
 N. 6°03.9' E., 2.705 chains
 N. 11°59.0' E., 2.966 chains
 N. 4°44.5' E., 3.313 chains
 N. 18°14.0' E., 2.929 chains
 N. 31°12.0' E., 4.376 chains
 N. 10°56.2' E., 4.336 chains
 N. 13°09.9' E., 5.048 chains
 N. 19°56.4' E., 1.766 chains
 N. 24°09.5' E., 1.549 chains
 N. 18°38.6' E., 5.253 chains
 N. 24°38.2' E., 4.998 chains
 N. 15°44.1' E., 6.179 chains
 N. 0°58.8' W., 4.770 chains
 N. 4°19.4' E., 2.245 chains
 N. 5°03.9' W., 1.614 chains
 N. 11°10.8' E., 4.641 chains
 N. 15°54.8' E., 5.511 chains
 N. 32°55.5' E., 3.297 chains
 N. 41°46.7' E., 1.492 chains

The true point for the meander corner of sections 19 and 30,
hereinbefore described.

Thence downstream with the meanders of the right bank of the
San Juan River, through section 19.

N. 41°46.7' E., 2.300 chains
 N. 40°55.2' E., 5.325 chains
 N. 44°02.7' E., 1.363 chains

The true point for the meander corner of sections 19 and 20,
hereinbefore described.

Thence downstream with the meanders of the right bank of the
San Juan River, through section 20.

N. 44°02.7' E., 4.087 chains
 N. 40°14.8' E., 9.377 chains
 N. 47°05.9' E., 5.620 chains
 N. 37°25.6' E., 6.293 chains
 N. 28°00.2' E., 2.061 chains
 N. 8°47.2' W., 2.600 chains
 N. 4°31.3' E., 1.865 chains
 N. 28°26.4' W., 2.081 chains
 N. 41°24.3' W., 1.198 chains
 N. 14°44.5' W., 5.532 chains

The true point for the special meander corner on the east-
west centerline of section 20, hereinbefore described.

RESURVEY OF THE MEANDERS OF THE RIGHT BANK OF THE SAN JUAN RIVER,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

N.14°44.5' W., 0.294 chains
 N.28°09.3' W., 4.677 chains
 N. 4°55.8' W., 2.236 chains
 N.11°29.5' E., 3.383 chains
 N. 3°03.4' W., 3.256 chains
 N.33°16.8' W., 3.956 chains
 N.57°47.2' W., 1.981 chains
 N.21°45.6' W., 2.941 chains
 N.50°04.2' W., 2.688 chains
 N.38°32.4' W., 2.302 chains
 N.44°15.1' W., 2.524 chains
 N.45°25.6' W., 1.388 chains
 N.69°44.7' W., 1.347 chains

The true point for the meander corner of sections 19 and 20,
hereinbefore described.

Thence downstream with the meanders of the right bank of the
San Juan River, through section 19.

N.76°30.4' W., 2.823 chains
 N.66°33.4' W., 1.571 chains
 N.77°03.7' W., 12.600 chains
 N.55°18.0' W., 4.894 chains
 N.40°18.1' W., 3.800 chains
 N.49°49.4' W., 1.519 chains
 N.26°25.5' W., 1.694 chains
 N. 9°09.1' E., 0.641 chains

The true point for the meander corner of sections 18 and 19,
hereinbefore described.

Thence downstream with the meanders of the right bank of the
San Juan River, through section 18.

N.15°25.7' E., 0.149 chains
 N.14°49.1' E., 0.383 chains
 N.28°56.1' W., 1.863 chains
 N.45°01.6' W., 1.340 chains
 N.32°52.2' W., 6.070 chains
 N.72°23.1' W., 5.585 chains
 N.59°43.2' W., 5.694 chains

The true point for the special meander corner on the north-
south centerline of section 18, hereinbefore described.

N.60°37.4' W., 4.395 chains
 N.43°38.0' W., 3.222 chains
 N.53°06.2' W., 3.348 chains
 N.40°06.2' W., 1.447 chains
 N.51°21.5' W., 8.921 chains
 N.38°28.4' W., 3.226 chains
 N.30°18.6' W., 11.150 chains

RESURVEY OF THE MEANDERS OF THE RIGHT BANK OF THE SAN JUAN RIVER,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

N.26°50.0' W., 2.184 chains

The True point for the special meander corner on the east-west centerline of section 18, hereinbefore described.

N.26°50.0' W., 3.425 chains
N.14°44.7' W., 5.278 chains
N.24°39.5' W., 3.113 chains
N.18°41.7' W., 5.110 chains
N.26°59.9' W., 5.196 chains
N. 0°50.5' E., 5.001 chains
N.13°04.5' W., 5.787 chains
N.18°53.2' W., 6.177 chains
N.13°34.6' W., 2.910 chains
N.20°23.9' W., 0.269 chains

The true point for the meander corner of sections 7 and 18, hereinbefore described.

Thence downstream with the meanders of the right bank of the San Juan River, through section 7.

N.20°37.7' W., 2.099 chains
N.28°22.2' W., 3.877 chains

The true point for the meander corner of sections 7 and 12, on the west boundary of the township.

From the true point, the 1953 witness corner to the meander corner of sections 7 and 12, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 4 inches above the ground, with brass cap marked as described in the official record of the 2012-13 resurvey, bears N.0°00.2'E., 71.440 chains distance.

From this same true point, the point for the 1/4 section corner of sections 7 and 12 bears N.0°00.2'E., 34.633 chains distance, not monumented.

Survey of the Meanders of the Left Bank of the San Juan River,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

From the true point for the meander corner of sections 13 and 18, on the present left bank of the San Juan River, and the west boundary of the township.

From the true point, the 1953 witness corner to the corner of sections 7, 12, 13, and 18, hereinbefore described, bears S. 0°00.2'W., 0.949 chains distance.

Thence upstream with the meanders of the left bank of the San Juan River, through section 32.

SURVEY OF THE MEANDERS OF THE LEFT BANK OF THE SAN JUAN RIVER,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

S.45°05.9' E., 1.252 chains
 S.18°53.4' E., 3.351 chains
 S.10°16.6' E., 5.513 chains
 S.18°43.4' E., 4.317 chains
 S. 6°07.2' E., 2.627 chains
 S. 5°38.2' W., 4.855 chains
 S. 2°22.1' W., 3.065 chains
 S.53°43.2' E., 2.217 chains
 S.85°37.8' E., 2.042 chains
 S.25°05.2' E., 6.215 chains
 S. 6°33.4' E., 2.456 chains
 S.19°23.0' E., 3.932 chains

The true point for the special meander corner on the east-west centerline of section 18, hereinbefore described.

S.19°23.0' E., 3.598 chains
 S.26°24.8' E., 8.860 chains
 S.45°37.4' E., 8.372 chains
 S.53°34.9' E., 7.828 chains
 S.46°20.6' E., 8.182 chains
 S.59°10.6' E., 5.390 chains

The true point for the special meander corner on the north-south centerline of section 18, hereinbefore described.

S.59°10.6' E., 1.988 chains
 S.76°54.3' E., 4.295 chains
 S.50°42.9' E., 6.402 chains
 S.19°19.6' E., 3.463 chains
 S.15°59.3' E., 0.493 chains

The true point for the meander corner of sections 18 and 19, hereinbefore described.

Thence upstream with the meanders of the left bank of the San Juan River, through section 19.

S.16°05.1' E., 1.266 chains
 S.40°11.8' E., 8.477 chains
 S.19°09.1' E., 4.006 chains
 S.41°44.6' E., 9.158 chains
 S.66°00.2' E., 8.512 chains
 S.59°37.8' E., 6.801 chains
 S.48°30.5' E., 1.356 chains

The true point for the meander corner of sections 19 and 20, hereinbefore described.

Thence upstream with the meanders of the left bank of the San Juan River, through section 20.

S.50°39.0' E., 4.760 chains
 S.41°10.1' E., 5.862 chains

SURVEY OF THE MEANDERS OF THE LEFT BANK OF THE SAN JUAN RIVER,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

S.34°53.4' E., 4.271 chains
S.14°43.1' E., 1.419 chains
S.29°55.4' E., 1.817 chains

The true point for the special meander corner on the east-west centerline of section 20, hereinbefore described.

S.29°55.4' E., 2.344 chains
S.17°19.4' E., 4.627 chains
S. 1°17.7' W., 4.831 chains
S.25°23.1' W., 5.581 chains
S.43°55.3' W., 13.960 chains
S.26°04.6' W., 3.578 chains

The true point for the meander corner of sections 19 and 20, hereinbefore described.

Thence upstream with the meanders of the left bank of the San Juan River, through section 19.

S.38°44.8' W., 1.307 chains
S.44°28.9' W., 8.373 chains
S.32°48.1' W., 4.027 chains

The true point for the meander corner of sections 19 and 30, hereinbefore described.

Thence upstream with the meanders of the left bank of the San Juan River, through section 30.

S.44°29.4' W., 4.051 chains
S.12°47.3' W., 8.704 chains
S. 2°42.7' E., 3.551 chains
S. 7°04.3' W., 9.652 chains
S.14°52.9' W., 6.866 chains
S.48°32.0' W., 1.663 chains
S.18°06.2' W., 10.028 chains
S.20°25.8' W., 8.741 chains
S. 9°42.3' W., 6.385 chains
S. 7°58.4' W., 8.173 chains
S.22°06.9' W., 6.554 chains
S. 9°16.2' E., 5.840 chains
S.42°20.2' E., 5.216 chains

The true point for the meander corner of sections 30 and 31, hereinbefore described.

Thence upstream with the meanders of the left bank of the San Juan River, through section 31.

S.49°14.6' E., 2.042 chains
S.57°05.4' E., 4.492 chains
S.68°04.5' E., 7.528 chains

SURVEY OF THE MEANDERS OF THE LEFT BANK OF THE SAN JUAN RIVER,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

S.73°28.6' E., 6.003 chains
S.58°25.0' E., 5.142 chains
S.51°27.4' E., 2.011 chains

The true point for the meander corner of sections 31 and 32,
hereinbefore described.

Thence upstream with the meanders of the left bank of the San
Juan River, through section 32.

S.51°07.4' E., 1.025 chains
S.50°09.1' E., 3.447 chains
S.43°30.1' E., 6.411 chains
S.20°22.6' E., 5.696 chains
S. 7°11.3' W., 4.459 chains
S. 7°11.4' E., 5.624 chains
S.34°31.0' E., 5.506 chains
S.63°15.0' E., 0.643 chains

The true point for the special meander corner on the east-
west centerline of section 32, hereinbefore described.

S.63°15.0' E., 3.558 chains
S.72°31.8' E., 16.341 chains
S.53°27.7' E., 3.453 chains
S.12°35.5' E., 9.594 chains
S.35°59.6' E., 4.332 chains

The true point for the special meander corner on the north-
south centerline of section 32. Not monumented.

S.35°59.6' E., 2.582 chains
S.55°14.0' E., 12.973 chains
S.44°18.5' E., 11.423 chains
S.35°01.9' E., 1.104 chains

The true point for the meander corner of sections 5 and 32,
on the south boundary of the township.

From the true point, the 2012-13 witness corner to the meander
corner of sections 5 and 32, monumented with a stainless steel
post, 2 1/2 inches diameter, firmly set, projecting 2 inches above
the ground, with brass cap marked as described in the official
record of the 2012-13 resurvey; with a steel fencepost east of the
corner; bears N. 89°59.3' W., 2.043 chains distance.

Survey of the Meanders of an Island in the San Juan River,
in Sections 19 and 20,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

From the true point for the meander corner of sections 19 and 20,
on the present northerly bank of an island in the San Juan River,
hereinbefore described.

SURVEY OF THE MEANDERS OF AN ISLAND IN THE SAN JUAN RIVER,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the true point, the witness corner to the meander corner bears S. 0°03.1' E., 1.078 chains distance, hereinbefore described.

Thence the following meanders of the island in the San Juan River, through section 19, in a counter clockwise direction.

N. 61°22.9' W., 4.756 chains
 N. 79°37.8' W., 5.755 chains
 N. 77°07.5' W., 5.501 chains
 S. 0°41.5' W., 2.656 chains
 S. 22°52.0' E., 2.328 chains
 S. 53°00.3' E., 2.932 chains
 S. 65°51.0' E., 5.850 chains
 S. 64°26.1' E., 4.667 chains
 S. 56°12.9' E., 2.964 chains

The true point for the meander corner of sections 19 and 20, on the present southerly bank of an island in the San Juan River, hereinbefore described.

Thence the following the meanders of the island in the San Juan River, through section 20.

S. 49°50.7' E., 8.104 chains
 S. 58°26.0' E., 4.729 chains
 N. 14°11.0' E., 3.478 chains
 N. 53°27.9' W., 1.800 chains
 N. 31°24.4' W., 7.431 chains
 N. 64°34.2' W., 1.086 chains
 N. 44°16.6' W., 4.927 chains
 N. 53°39.1' W., 1.691 chains

The true point for the meander corner of sections 19 and 20, on the present northerly bank of an island in the San Juan River, and the point of beginning.

Survey of the Meanders of an Island in the San Juan River,
in Section 32,
T. 42 S., R. 26 E., Salt Lake Meridian, Utah

From the true point for the special meander corner of the east-west centerline of section 32, and the present westerly bank of an island in the San Juan River, hereinbefore described.

From the true point, the off-line witness corner to the special meander corner, bears N. 2°05.1' E., 0.877 chains distance, hereinbefore described.

Thence the following meanders of the island in the San Juan River, within section 32, in a counter clockwise direction.

SURVEY OF THE MEANDERS OF AN ISLAND IN THE SAN JUAN RIVER,
TOWNSHIP 42 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

S.56°28.0' E., 0.390 chains
S.81°39.3' E., 3.705 chains
N.31°06.8' W., 0.885 chains

The true point for the special meander corner on the east-west centerline of section 32, hereinbefore described.

N.31°06.8' W., 2.765 chains
N.39°29.2' W., 3.179 chains
N.40°36.6' W., 3.533 chains
N.16°26.6' W., 2.563 chains
N.42°55.5' W., 1.939 chains
S.24°29.2' W., 3.228 chains
S. 3°53.3' E., 2.607 chains
S.28°32.9' E., 2.547 chains
S.42°58.1' E., 2.932 chains
S.56°28.0' E., 2.649 chains

The true point for the special meander corner of the east-west centerline of section 32, and the present westerly bank of an island in the San Juan River, and the point of beginning.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Phil Freiberg	Survey Technician
Brandt Hart	Boatman

CERTIFICATE OF SURVEY

I, *Scott A. Burkhardt, Cadastral Surveyor*, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing the date of the *24th day of April, 2014*, I have *retraced and dependently resurveyed a portion of the Utah-Colorado state boundary line, from Mile Post 5 1/2 to Mile Post 12, dependently resurveyed a portion of the north boundary, a portion of the subdivisional lines, and the meanders of the right bank of the San Juan River, and surveyed a portion of the subdivisional lines, the subdivision of sections 3, 4, 5, 7, 9, 10, 18, 20, 22, 29, and 32, and the meanders of the left bank of the San Juan River, in Township 42 South, Range 26 East, of the Salt Lake Meridian, in the State of Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 29, 2015
Date

Scott A. Burkhardt
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *retracement and dependent resurvey of a portion of the Utah-Colorado state boundary line, from Mile Post 5 1/2 to Mile Post 12, the dependent resurvey of a portion of the north boundary, a portion of the subdivisional lines, and the meanders of the right bank of the San Juan River; and the survey of a portion of the subdivisional lines, the subdivision of sections 3, 4, 5, 7, 9, 10, 18, 20, 22, 29, and 32, and the meanders of the left bank of the San Juan River; in Township 42 South, Range 26 East, Salt Lake Meridian, Utah, executed by Scott A. Burkhardt, Cadastral Surveyor*, having been critically examined and found correct, are hereby approved.

September 30, 2015
Date

Daniel W. Webb
Chief Cadastral Surveyor for Utah