

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE RETRACEMENT OF

A PORTION OF THE UTAH-ARIZONA STATE BOUNDARY
FROM MILE POST 243 TO MILE POST 250 (SOUTH BOUNDARY),

THE DEPENDENT RESURVEY OF

THE EAST, WEST, AND NORTH BOUNDARIES,

AND

THE SURVEY OF

THE SUBDIVISIONAL LINES, AND

THE SUBDIVISION OF SECTIONS 1, 12, 13, 14, 22, 23, 27, 28, AND 33,

IN

TOWNSHIP 43 SOUTH, RANGE 21 EAST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Scott A. Burkhardt
Cadastral Surveyor

Under Special Instructions dated and approved **May 23, 2014**, which provided for the surveys included under Group No. **1267**, and Assignment Instructions dated **May 23, 2014**.

Survey Commenced, **May 23, 2014**
Survey Completed, **June 26, 2014**

INDEX DIAGRAM

TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

17	16	16	15	15	14
14 6	50 5	42 4	36 3	30 2	23 1 10
50	50	42	36	29	23
13 7	49 8	41 9	35 10	29 11	22 12 9
49	48	41	35	28	22
13 18	47 17	40 16	34 15	28 14	21 13 9
47	47	40	34	27	20
12 19	46 20	39 21	33 22	26 23	20 24 8
45	45	39	32	26	19
12 30	44 29	38 28	31 27	25 26	18 25 8
44	43	37	31	25	18
11 31	43 32	37 33	30 34	24 35	17 36 7
3	3	4	5	6	6
3	3	3	4	5	6
3	3	3	4	5	6

The Subdivision of Section 1.....	Page 51
The Subdivision of Section 12.....	Page 52
The Subdivision of Section 13.....	Page 53
The Subdivision of Section 14.....	Page 53
The Subdivision of Section 22.....	Page 54
The Subdivision of Section 23.....	Page 55
The Subdivision of Section 27.....	Page 56
The Subdivision of Section 28.....	Page 57
The Subdivision of Section 33.....	Page 58

TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

The following field notes describe the retracement of a portion of the Utah-Colorado state boundary line from Mile Post 243 to Mile Post 250 (south boundary); the dependent resurvey of the east, west, and north boundaries; and the survey of the subdivisional lines and the subdivision of sections 1, 12, 13, 14, 22, 23, 27, 28, and 33; in T. 43 S., R. 21 E., Salt Lake Meridian, Utah.

HISTORY OF SURVEYS

Surveyed by		Retr. or Resurveyed by	
SOUTH BOUNDARY (Utah-Arizona State Boundary Line)			
All	H.B. Carpenter	1901	
All		A. Nelson & R.C. Yundt	1953
All		J. Curtiss	2000-02
EAST BOUNDARY			
All	A. Nelson & R.C. Yundt	1953	
WEST BOUNDARY			
All	A. Nelson & R.C. Yundt	1953	
NORTH BOUNDARY			
All	A. Nelson & R.C. Yundt	1953	
SUBDIVISION			
All	Unsurveyed		

TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 1267, dated May 23, 2014.

The direction of the lines was determined by references to true meridian, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards for the Positional Accuracy of Cadastral Surveys When Using Global Navigation Satellite Systems (GNSS)*, dated February 23, 2009. Trimble model R8 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from GPS static observations, post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS): DL3642 MC09 NUCLA CORS ARP, DO2634 CTI4 COMPASSTOOLS4CRNR CORS ARP, and DH5816 P028 CHACOCNHP_NM2005 CORS ARP.

The geographic position of the corner of sections 1, 6, 31, and 36, Tps. 42 and 43 S., Rs. 21 and 22 E., as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: **37°05'10.349" N.**,
Longitude: **109°32'57.663" W.**, N.A.D. 83 (2011), EPOCH: 2010.00,
Network Accuracy = 0.200 meter at 95% confidence.

The geographic position of Mile Post 243 on the Utah-Arizona state boundary line, as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: **36°59'53.743" N.**,
Longitude: **109°39'37.728" W.**, N.A.D. 83, (2011), EPOCH: 2010.00,
Network Accuracy = 0.200 meter at 95% confidence.

All stainless steel monuments and brass tablets set in this survey bear the Navajo Nation seal, unless otherwise noted.

RETRACEMENT OF A PORTION OF THE UTAH - ARIZONA STATE BOUNDARY LINE,
FROM MILE POST 243 TO MILE POST 250

CHAINS

Retracement of a Portion of the Utah-Arizona State Boundary Line,
From Mile Post 243 to Mile Post 250,
T. 43 S., R. 21 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by H.B. Carpenter in 1901,
and the Resurveys by A. Nelson and R.C. Yundt in 1953,
and J. Curtiss in 2000-02

Beginning at Mile Post 243 on the Utah-Arizona state boundary line, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, flush in the ground, with brass cap with Navajo seal marked as described in the official record of the 2000-02 retracement and resurvey.

Corner is located south of a group of houses.

S. 89°58.3' E., on the 244th mile.

11.795 The corner of T. 43 S., Rs. 20 and 21 E., monumented with an iron post, 2 1/2 inches diameter, firmly set, flush with a mound of stone, 4 feet base, 2 1/2 feet high, with brass cap marked as described in the 1953 resurvey.

51.803 The point for the 1/4 section corner of section 31 only.

From which the 1953 amended 1/4 section corner, monumented with an iron post, 2 1/2 inches diameter, firmly set, flush with a mound of stone, 4 feet base, 2 1/2 feet high, with brass cap marked as described in the official record of the 1953 resurvey, bears N.0°01.6'W., 1.3 links distance.

Add marks AM and 2014 to cap.

80.012 Mile Post 244 on the Utah-Arizona state boundary line, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 7 inches above the ground, with brass cap with Navajo seal marked as described in the official record of the 2000-02 retracement and resurvey.

Set a steel fence post north of the corner.

Corner is located in rolling, sandy hills, with Mormon tea and blackbrush.

S. 89°58.3' E., on the 245th mile.

11.821 The corner of sections 31 and 32 only, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 3 inches above a mound of stone, 4 feet base, 3 feet high, with brass cap marked as described in the 1953 resurvey.

51.850 The 1/4 section corner of section 32 only, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches

RETRACEMENT OF A PORTION OF THE UTAH - ARIZONA STATE BOUNDARY LINE,
FROM MILE POST 243 TO MILE POST 250

CHAINS

above the ground, with brass cap marked as described in the official record of the 1953 resurvey.

Set a steel fence post north of the corner.

Corner is located in rolling, sandy hills, with Mormon tea and blackbrush.

- 80.012** Mile Post 245 on the Utah-Arizona state boundary line, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 5 inches above the ground, with brass cap marked as described in the official record of the 2000-02 retracement and resurvey; with a mound of stone, 4 feet base, 2 1/2 feet high, east of the corner.

Corner is located in rolling, sandy hills, with Mormon tea and blackbrush.

N. 89°15.4' E., on the 246th mile.

- 11.836** The corner of sections 32 and 33 only, at proportionate distance. There is no remaining evidence of the 1953 iron post.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 23 inches in the ground, with a magnet at base, in a collar of stone, 2 1/2 feet diameter, with brass cap marked

T43S	R21E
S32	S33
2014	

Set a steel fence post north of the corner.

Corner is located on a mesa top, in an area previously disturbed by earth-moving equipment.

- 51.828** The 1/4 section corner of section 33 only, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 5 inches above the ground, with brass cap marked as described in the official record of the 1953 resurvey.

Corner is located in gently-rolling, rocky, open ground.

- 67.438** Centerline of U.S. Highway 191, a paved road, 33 feet wide, bears N.11°W., S.11°E.

- 80.005** Mile Post 246 on the Utah-Arizona state boundary line, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, flush with the ground, with brass cap with Navajo seal marked as described in the official record of the 2000-02 retracement and resurvey.

Set a steel fence post north of the corner.

RETRACEMENT OF A PORTION OF THE UTAH - ARIZONA STATE BOUNDARY LINE,
FROM MILE POST 243 TO MILE POST 250

CHAINS

From the corner, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 inches diameter, set flush in top of pier, bears S.89°18.3'W., 14.494 chains distance, marked EL 4974.26 1980, with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, north of the pier.

Also from the corner, a Right-of-Way monument, an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, bears S.89°27.5'W., 10.651 chains distance, with marked 0+00

Corner is located in rolling, sandy hills, with Mormon tea and blackbrush.

N. 89°15.4' E., on the 247th mile.

- 11.830** The corner of sections 33 and 34 only, monumented with an iron post, 2 1/2 inches diameter, firmly set, flush with a mound of stone, 4 feet base, 1 1/2 feet high, with brass cap marked as described in the 1953 resurvey.

Corner is located on a fairly level, rocky plain, with sparse vegetation.

- 51.838** The 1/4 section corner of section 34 only, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 2 inches above a mound of stone, 2 feet base, 1 foot high, with brass cap marked as described in the official record of the 1953 resurvey.

Set a steel fence post north of the corner.

- 66.309** Centerline of an improved gravel road, 20 feet wide, bears S. 64°W., N. 61°E.

- 80.007** Mile Post 247 on the Utah-Arizona state boundary line, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 1 inch above the ground, with brass cap with Navajo seal marked as described in the official record of the 2000-02 retracement and resurvey.

Set a steel fence post north of the corner.

Corner is located in rolling, sandy hills, with Mormon tea and blackbrush.

N. 89°15.4' E., on the 248th mile.

- 11.821** Point for the corner of sections 34 and 35 only.

From which the 1953 amended corner, monumented with an iron post, 2 1/2 inches diameter, firmly set, flush with a mound of stone, 4 feet base, 1 foot high, with brass cap marked as described in the official record of the 1953 resurvey, bears N. 0°00.9'W., 3.0 links distance.

RETRACEMENT OF A PORTION OF THE UTAH - ARIZONA STATE BOUNDARY LINE,
FROM MILE POST 243 TO MILE POST 250

CHAINS

Add marks AM and 2014 to cap.

Set a steel fence post north of the corner.

Corner is located in rolling hills, with barren ground.

- 51.824** Point for the 1/4 section corner of section 35 only.

From which the 1953 amended 1/4 section corner, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 4 inches above a mound of stone, 3 feet base, 1 1/2 feet high, with brass cap marked as described in the official record of the 1953 resurvey, bears N.0°00.5'W., 2.4 links distance.

Add marks AM and 2014 to cap.

Set a steel fence post north of the corner.

Corner is located on west-facing slope.

- 80.007** Mile Post 248 on the Utah-Arizona state boundary line, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 3 inches above the ground, with brass cap with Navajo seal marked as described in the official record of the 2000-02 retracement and resurvey.

Set a steel fence post north of the corner.

N. 89°15.5' E., on the 249th mile.

- 11.833** Point for the corner of sections 35 and 36 only.

From which the 1953 amended corner, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 4 inches above the ground, with brass cap marked as described in the official record of the 1953 resurvey, bears N.0°00.7'W., 1.8 links distance.

Add marks AM and 2014 to cap.

Set a steel fence post north of the corner.

Corner is located in rolling, sandy hills.

- 15.342** Centerline of an improved gravel road, 20 feet wide, bears N. 63°W., S. 63°E.

- 51.837** Point for the 1/4 section corner of section 36 only.

From which the 1953 amended 1/4 section corner, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap marked as described in the official record of the 1953 resurvey, bears N.0°00.4'W., 1.4 links distance, with a mound of stone, 2 feet base, 2 feet high, south of corner.

RETRACEMENT OF A PORTION OF THE UTAH - ARIZONA STATE BOUNDARY LINE,
FROM MILE POST 243 TO MILE POST 250

CHAINS

Add marks AM and 2014 to cap.

Set a steel fence post north of the corner.

Corner is located in rolling, sandy hills, with blackbrush.

- 80.007** Mile Post 249 on the Utah-Arizona state boundary line, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 3 inches above the ground, with brass cap with Navajo seal marked as described in the official record of the 2000-02 retracement and resurvey.

Set a steel fence post north of the corner.

Corner is located in rolling, sandy hills, with Mormon tea and blackbrush.

N. 89°15.4' E., on the 250th mile.

- 11.828** The corner of T. 43 S., Rs. 21 and 22 E., monumented with an iron post, 2 1/2 inches diameter, firmly set, flush with the ground, with brass cap marked as described in the 1953 resurvey; with a mound of stone, 3 feet base, 1 1/2 feet high, north of the corner.

Set a steel fence post west of the corner.

Corner is located in rolling, sandy hills, with blackbrush.

- 80.005** Mile Post 250 on the Utah-Arizona state boundary line, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap marked as described in the official record of the 2000-02 retracement and resurvey; with a mound of stone, 4 feet base, 2 feet high, east of the corner; with original marked sandstone buried to the south.

Corner is located in rolling, sandy hills.

Dependent Resurvey of a Portion of the East Boundary,
T. 43 S., R. 21 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
A. Nelson and R.C. Yundt in 1953

From the corner of T. 43 S., Rs. 21 and 22 E., on the Utah-Arizona state boundary line, hereinbefore described.

N. 0°00.3' E., between sections 31 and 36.

- 40.884** The 1/4 section corner of sections 31 and 36, monumented with an

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

iron post, 2 1/2 inches diameter, firmly set, projecting 4 inches above the ground, in an embedded mound of stone, 4 feet base, with brass cap marked as described in the official record of the 1953 survey.

Set a steel fence post north of the corner.

Corner is located in rolling terrain of sand and exposed sandstone bedrock, with blackbrush.

NORTH, beginning new measurement.

- 40.008** The corner of sections 25, 30, 31, and 36, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 15 inches above the ground, with brass cap marked as described in the official record of the 1953 survey.

Set a steel fence post north of the corner.

Corner is located in rolling, sandy hills, with Mormon tea and blackbrush.

N. 0°00.3' E., between sections 25 and 30.

- 40.023** The 1/4 section corner of sections 25 and 30, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 9 inches above the ground, in an embedded mound of stone, 3 feet base, with brass cap marked as described in the official record of the 1953 survey.

Set a steel fence post north of the corner.

Corner is located east of Boundary Butte, in rolling, sandy hills, with Mormon tea and blackbrush.

N. 0°00.2' W., beginning new measurement.

- 40.025** The corner of sections 19, 24, 25, and 30, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 8 inches above the ground, in an embedded mound of stone, 4 feet base, with brass cap marked as described in the official record of the 1953 survey.

Corner is located in rolling, barren ground.

N. 0°00.2' W., between sections 19 and 24.

- 40.014** The 1/4 section corner of sections 19 and 24, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 5 inches above an embedded mound of stone, 3 feet diameter, with brass cap marked as described in the official record of the 1953 survey.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

Set a steel fence post north of the corner.

Corner is located in rolling terrain with desert vegetation.

NORTH, beginning new measurement.

- 40.013** The corner of sections 13, 18, 19, and 24, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap marked as described in the official record of the 1953 survey.

Set a steel fence post north of the corner.

Corner is located in rolling, sandy hills, with Mormon tea and blackbrush.

N. 0°00.3' E., between sections 13 and 18.

- 40.019** The 1/4 section corner of sections 13 and 18, determined at the center of a mound of stone, on exposed sandstone bedrock. There is no remaining evidence of the 1953 iron post.

At the corner (center of mound of stone)

Mark a "+" on the sandstone bedrock.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, magnet at base, in a mound of stone, 2 feet base, to brass cap marked

T43S
R21E R22E

1/4
S13 | S18

2014

Corner is located in gentle hills of sand and exposed sandstone bedrock.

N. 0°00.1' E., beginning new measurement.

- 40.026** The corner of sections 7, 12, 13, and 18, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 8 inches above the ground, with brass cap marked as described in the official record of the 1953 survey; with pieces of broken glass scattered around the corner.

Set a steel fence post north of the corner.

N. 0°00.4' W., between sections 7 and 12.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

- 40.004** The 1/4 section corner of sections 7 and 12, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 8 inches above the ground, with brass cap marked as described in the official record of the 1953 survey.

Set a steel fence post north of the corner.

Corner is located in rolling, sandy hills, with blackbrush.

NORTH, beginning new measurement.

- 40.012** The corner of sections 1, 6, 7, and 12, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 14 inches above the ground, with brass cap marked as described in the official record of the 1953 survey.

Add a collar of stone, 2 feet diameter, around the corner.

Set a steel fence post north of the corner.

From this point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 inches diameter, set flush in top of pier, bears S.57°48.6'W., 19.960 chains distance, cap marked BIA ROADS 19—, with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, west of the pier.

From this same point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 inches diameter, set flush in top of pier, bears S.46°56.5'W., 19.207 chains distance, cap marked BIA ROADS 19—, with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, west of the pier.

Corner is located in rolling, sandy hills.

N. 0°0.7' W., between sections 1 and 6.

- 13.828** Centerline of U.S. Highway 191, a paved road, 33 feet wide, bears S.22°W., N.19°E.

- 40.029** The 1/4 section corner of sections 1 and 6, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 3 inches above the ground, with brass cap marked as described in the official record of the 1953 survey.

Set a steel fence post north of the corner.

Corner is located in rolling sand dunes.

N. 0°00.1' E., beginning new measurement.

- 40.010** The corner of Tps. 42 and 43 S., Rs. 21 and 22 E., monumented

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

with an iron post, 2 1/2 inches diameter, firmly set, projecting 12 inches above the ground, with brass cap marked as described in the official record of the 1953 survey; with a collar of stone and pieces of broken glass around the corner.

Set a steel fence post north of the corner.

Corner is located in rolling, sandy hills.

Dependent Resurvey of a Portion of the West Boundary,
T. 43 S., R. 21 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
A. Nelson and R.C. Yundt in 1953.

From the corner of T. 43 S., Rs. 20 and 21 E., on the Utah-Arizona state boundary line, hereinbefore described.

N. 0°00.6' E., on the west boundary of section 31.

- 45.080** Point for the 1/4 section corner of sections 31, at proportionate distance. There is no remaining evidence of the 1953 iron post or mound of stone.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

T43S
R20E R21E

| 1/4
| S31

2014

Set a steel fence post north of the corner.

Corner is located southeast of a power line, in an area of sand and exposed sandstone bedrock.

- 85.089** Point for the corner of sections 30 and 31 only, at proportionate distance, falls in a gravel road, 12 feet wide, extending north and south. There is no remaining evidence of the 1953 iron post or mound of stone.

Set a 60d nail, 2 inches below the road surface.

From which

A stainless steel post, 2 1/2 inches diameter, set 25 inches in the ground, with magnet at base, for a reference monument, bears S.42°25.1'W., 41.5 links distance, with a

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

brass cap marked RM T43S R20E S36 2014, 27.4 FT. TO COR.
with an arrow pointing toward the corner, in a collar of
stone, 2 feet diameter. Set a steel fence post to the
northwest. Monument is located west of the gravel road.

A stainless steel post, 2 1/2 inches diameter, set 25 inches
in the ground, with magnet at base, for a reference
monument, bears N.46°20.4'W., 40.1 links distance, with a
brass cap marked RM T43S R20E S25 2014, 26.5 FT. TO COR.
with an arrow pointing toward the corner, in a collar of
stone, 2 feet diameter. Set a steel fence post to the east.
Monument is located west of the gravel road.

N. 00°0.6' E., on the west boundary of section 30.

15.670 Centerline of San Juan County Road 449, an improved gravel road,
20 feet wide, bears N. 88° E., S. 88° W.

40.009 The 1/4 section corner of section 30 only, monumented with an
iron post, 2 1/2 inches diameter, firmly set, projecting 15
inches above the ground, with brass cap marked as described in
the official record of the 1953 survey.

Set a steel fence post northwest of the corner.

Corner is located east of a power line extending north and south,
in rolling, sandy hills.

N. 0°00.7' E., beginning new measurement.

40.025 The corner of sections 19 and 30 only, monumented with an iron
post, 2 1/2 inches diameter, firmly set, projecting 5 inches
above the ground, with brass cap marked as described in the
official record of the 1953 survey.

Set a steel fence post north of the corner.

Corner is located east of a power line extending north and
south, in rolling, sandy hills.

N. 0°00.6' E., on the west boundary of section 19.

40.009 The 1/4 section corner of section 19 only, monumented with an
iron post, 2 1/2 inches diameter, firmly set, projecting 7 inches
above the ground, with brass cap marked as described in the
official record of the 1953 survey.

Set a steel fence post north of the corner.

Corner is located in rolling, sandy hills, with desert brush.

N. 0°00.2' E., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

23.020 Centerline of San Juan County Road 415, an improved gravel road, 20 feet wide, bears N. 37° W., S. 40° E.

39.993 The corner of sections 18 and 19 only, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 14 inches above a scattered mound of stone, with brass cap marked as described in the official record of the 1953 survey.

Rehabilitate mound of stone, to cap.

Set a steel fence post north of the corner.

Corner is located on a moderately-steep, northwest-facing, rocky slope.

N. 0°00.2' W., on the west boundary of section 18.

39.963 The 1/4 section corner of section 18 only, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 10 inches above an embedded mound of stone, 3 feet base, with brass cap marked as described in the official record of the 1953 survey.

Set a steel fence post north of the corner.

Corner is located on a southwest-facing slope, at the base of a small sandstone hill.

N. 0°00.1' E., beginning new measurement.

40.015 The corner of sections 7 and 18 only, monumented with an iron rod, 5/8 inch diameter, firmly set, projecting 6 inches above exposed sandstone bedrock, with 4 grooves to the south and 2 grooves to the north.

Raise a mound of stone, 2 feet base, 1 foot high, south of the corner.

N. 0°00.3' W., along the west boundary of section 7.

40.001 The 1/4 section corner of section 7 only, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 15 inches above a mound of stone, 3 feet base, 1 foot high, with brass cap marked as described in the official record of the 1953 survey.

Rehabilitate mound of stone, to cap.

Corner is located in exposed sandstone bedrock.

N. 0°00.4' E., beginning new measurement.

40.000 The corner of sections 6 and 7 only, determined at a mound of

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

stone, 2 feet base, 2 feet high, with the 1953 iron post lying loose on top, with brass cap marked as described in the official record of the 1953 survey.

At the corner (center of mound of stone)

Reset the 1953 iron post, 2 1/2 inches diameter, 36 inches long, on bedrock, in a mound of stone, 3 feet base, to cap.

Corner is located in an area of sand and exposed sandstone bedrock.

NORTH, on the west boundary of section 6.

- 40.003** The 1/4 section corner of section 6 only, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 3 inches above an embedded mound of stone, with brass cap marked as described in the official record of the 1953 survey.

Set a steel fence post north of the corner.

Corner is located in gently-rolling terrain, with blackbrush.

N. 0°00.1' E., beginning new measurement.

- 40.000** The corner of Tps. 42 and 43 S., R.21 E., monumented with an iron rod, 5/8 inch diameter, firmly set, projecting 6 inches above exposed sandstone bedrock, marked with 6 grooves and T43S to the south, 6 grooves and R21E to the east, and 6 grooves and T42S to the north; with a mound of stone, 1 foot base, 1 foot high, west of the corner.

Corner is located in an area of exposed sandstone bedrock.

Dependent Resurvey of a Portion of the North Boundary,
T. 43 S., R. 21 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
A. Nelson and R.C. Yundt in 1953

From the corner of Tps. 42 and 43 S., Rs. 21 and 22 E.

N. 89°57.1' W., between sections 1 and 36.

- 40.017** The 1/4 section corner of sections 1 and 36, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap marked as described in the official record of the 1953 survey.

Set a steel fence post north of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

S. 89°54.8' W., beginning new measurement.

- 39.954 The corner of sections 1, 2, 35, and 36, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 14 inches above a mound of stone, 2 feet base, 1 foot high, with brass cap marked as described in the official record of the 1953 survey.

Corner is located in a small area of sand surrounded by exposed sandstone bedrock.

S. 89°58.5' W., between sections 2 and 35.

- 39.978 The 1/4 section corner of sections 2 and 35, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 7 inches above a mound of stone, 3 feet base, 1 foot high, with brass cap marked as described in the official record of the 1953 survey.

Corner is located in an area of sand and exposed sandstone bedrock.

S. 89°58.2' W., beginning new measurement.

- 39.952 The corner of sections 2, 3, 34, and 35, monumented with an iron rod, 5/8 inch diameter, firmly set, projecting 4 inches above exposed sandstone bedrock, with no visible marks in sandstone (record: marked with 2 grooves to the east, and 4 grooves to the west); with a mound of stone, 2 feet base, 1 foot high, west of the corner.
-

S. 89°59.1' W., between sections 3 and 34.

- 39.975 The 1/4 section corner of sections 3 and 34, monumented with an iron post, 2 1/2 inches diameter, firmly set, flush with a mound of stone, 3 feet base, 1 1/2 feet high, with brass cap marked as described in the official record of the 1953 survey.

Set a steel fence post north of the corner.

Corner is located in a small area of sand surrounded by exposed sandstone bedrock.

S. 89°58.8' W., beginning new measurement.

- 40.003 The corner of sections 3, 4, 33, and 34, monumented with an iron post, 2 1/2 inches diameter, firmly set, buried 2 feet below ground, with brass cap marked as described in the official record of the 1953 survey.

At the corner (on top of 1953 iron post)

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 22 inches in the ground, with brass cap marked

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T42S R21E

S33	S34
S4	S3

T43S

2014

Original iron post buried beneath new iron post; set a steel fence post north of the corner.

Corner is located in sandy hills.

S. 89°58.3' W., between sections 4 and 33.

- 39.987** The 1/4 section corner of sections 4 and 33, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 7 inches above a scattered mound of stone, with brass cap marked as described in the official record of the 1953 survey.

Rehabilitate mound of stone, 3 feet base, to cap.

Set a steel fence post north of the corner.

Corner is located in sand dunes, with blackbrush.

S. 89°57.8' W., beginning new measurement.

- 39.959** The corner of sections 4, 5, 32, and 33, determined immediately east of an embedded mound of stone, 2 feet diameter, with the 1953 iron post lying loose alongside, with brass cap marked as described in the official record of the 1953 survey.

At the corner (immediately east of mound of stone)

Reset the 1953 iron post, 2 1/2 inches diameter, 36 inches long, 27 inches in the ground, in a collar of stone, 3 feet diameter.

Set a steel fence post north of the corner.

Corner is located in sandy hills.

S. 89°59.4' W., between sections 5 and 32.

- 40.017** The 1/4 section corner of sections 5 and 32, determined at a mound of stone 2 feet base, 1 foot high, with the 1953 iron post, lying loose on top, with brass cap marked as described in the official record of the 1953 survey; with a "+" on the sandstone bedrock beneath the mound of stone.

At the corner ("+" on sandstone bedrock)

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Reset the original 1953 iron post, 2 1/2 inches diameter, 36 inches long, on sandstone bedrock, in a mound of stone, 3 feet diameter, to cap.

Set a steel fence post north of the corner.

Corner is located in exposed sandstone bedrock.

S. 89°58.9' W., beginning new measurement.

- 39.981** The corner of sections 5, 6, 31, and 32, monumented with an iron post, 2 1/2 inches diameter, firmly set, flush with a mound of stone, 3 feet base, to brass cap marked as described in the official record of the 1953 survey.

Corner is located on exposed sandstone bedrock.

S. 89°58.7' W., between sections 6 and 31.

- 39.963** The 1/4 section corner of sections 6 and 31, monumented with an iron post, 2 1/2 inches diameter, firmly set, in a mound of stone, 3 feet base, 2 feet high, with brass cap marked as described in the official record of the 1953 survey.

Corner is located in rolling sandstone bedrock.

S. 89°58.4' W., beginning new measurement.

- 39.672** The corner of Tps. 42 and 43 S., R. 21 E., hereinbefore described.
-

The Survey of the Subdivisional Lines,
T. 43 S., R. 21 E., Salt Lake Meridian, Utah

From the point for the corner of sections 25, 26, 35, and 36.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, marked

T43S	R21E
S26	S25
S35	S36
2014	

Raise a mound of stone north of the corner.

Corner is located east of a drainage, in an area of sandstone ledges.

S. 0°00.7' E., between sections 35 and 36.

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

40.000 Point for the 1/4 section corner of sections 35 and 36.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

T43S R21E
1/4
S35 | S36
2014

Set a steel fence post north of the corner.

Corner is located in rolling, sandy hills, with Mormon tea and blackbrush.

80.109 Centerline of an improved gravel road, 20 feet wide, bears N. 63° W., S. 63° E.

81.905 The amended corner of sections 35 and 36 only.

81.923 The true point for the corner of sections 35 and 36 only, on the Utah-Arizona state boundary line, hereinbefore described.

From the corner of sections 25, 30, 31, and 36, on the east boundary of the township, hereinbefore described.

S. 89°59.8' W., between sections 25 and 36.

40.000 Point for the 1/4 section corner of sections 25 and 36.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 23 inches in the ground to bedrock, magnet at base, with brass cap marked

T43S R21E
S25
1/4 ———
S36
2014

Set a steel fence post east of the corner.

Corner is located south of Boundary Butte, in rolling terrain, with Mormon tea and blackbrush.

80.000 The corner of sections 25, 26, 35, and 36.

N. 0°00.7' W., between sections 25 and 26.


40.000 True point for the 1/4 section corner of sections 25 and 26, falls in a drainage, 5 feet wide, course N. 10° W., where it is impracticable to establish a permanent monument.

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Point selected for an off-line witness corner, bears
S.70°24.0'E., 21.1 links distance.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches
long, 27 inches in the ground, magnet at base, with brass cap
marked




With an arrow pointing toward the true point.

Set a steel fence post east of the corner.

Corner is located on the east side of a drainage, in broken,
eroded terrain.

80.000 Point for the corner of sections 23, 24, 25, and 26.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches
long, 20 inches in the ground to bedrock, magnet at base, in a
mound of stone, 3 feet base, to brass cap marked



Set a steel fence post west of the corner.

Corner is located in a fairly level valley.

From the corner of sections 19, 24, 25, and 30, on the east
boundary of the township, hereinbefore described.

S. 89°57.7' W., between sections 24 and 25.

40.001 Point for the 1/4 section corner of sections 24 and 25.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches
long, 22 inches in the ground, magnet at base, in a mound of
stone, 3 feet base, to brass cap marked

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T43S R21E
 $\frac{1}{4}$ $\frac{S24}{S25}$
 2014

Set a steel fence post north of the corner.

Corner is located on a small ridge, in eroded terrain.

80.002 The corner of sections 23, 24, 25, and 26.

N. 0°00.7' W., between sections 23 and 24.

40.000 Point for the 1/4 section corner of sections 23 and 24.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, magnet at base, with brass cap marked

T43S R21E
 $\frac{1}{4}$
 $\frac{S23}{S24}$
 2014

Set a steel fence post north of the corner.

Corner is located in sand dunes, with Mormon tea and blackbrush.

80.000 Point for the corner of sections 13, 14, 23, and 24.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 22 inches in the ground to bedrock, magnet at base, in a mound of stone, 2 feet base, to brass cap marked

T43S R21E
 $\frac{S14}{S23}$ $\frac{S13}{S24}$
 2014

Set a steel fence post north of the corner.

Corner is located in an area of shallow sand overlying sandstone bedrock, with blackbrush.

From the corner of sections 13, 18, 19, and 24, on the east boundary of the township, hereinbefore described.

S. 89°56.6' W., between sections 13 and 24.

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

40.000 Point for the 1/4 section corner of sections 13 and 24.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 26 inches in the ground, magnet at base, in a mound of stone, 3 feet base, to brass cap marked

T43S R21E
 S13
1/4 ———
 S24
2014

Set a steel fence post north of the corner.

Corner is located in rolling, sandy terrain, with Mormon tea and blackbrush.

80.000 The corner of sections 13, 14, 23, and 24.

N. 0°00.7' W., between sections 13 and 14.

40.000 Point for the 1/4 section corner of sections 13 and 14.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

T43S R21E
 1/4
S14 | S13
2014

Set a steel fence post north of the corner.

Corner is located in an area of sandy hills and exposed sandstone bedrock.

73.136 Centerline of U.S. Highway 191, a paved road, 33 feet wide, bears N. 40° E., S. 37° W.

80.000 Point for the corner of sections 11, 12, 13, and 14.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

T43S R21E
S11 | S12
S14 | S13
2014

Set a steel fence post north of the corner.

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

From this point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 inches diameter, set flush in top of pier, bears S.24°20.7'W., 10.042 chains distance, cap marked BIA ROADS 19—, with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, south of the pier.

From this same point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 inches diameter, set flush in top of pier, bears S.5°39.2'W., 11.505 chains distance, cap marked BIA ROADS 19—, with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, west of the pier.

Corner is located in rolling, sandy terrain, with blackbrush.

From the corner of sections 7, 12, 13, and 18, on the east boundary of the township, hereinbefore described.

S. 89°54.6' W., between sections 12 and 13.

40.002 Point for the 1/4 section corner of sections 12 and 13.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, magnet at base, with brass cap marked

T43S R21E
S12
1/4 ———
S13
2014

Set a steel fence post north of the corner.

Corner is located at the base of a steep hill to the west, with Mormon tea and blackbrush.

74.521 Centerline of U.S. Highway 191, a paved road, 33 feet wide, bears S.39°W., N.40°E.

80.004 The corner of sections 11, 12, 13, and 14.

N. 0°00.7' W., between sections 11 and 12.

40.000 Point for the 1/4 section corner of sections 11 and 12.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, marked

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T43S R21E
1/4
S11 | S12
2014

Raise a mound of stone, 2 feet base, 2 feet high, north of the corner.

Corner is located in gently-rolling, exposed sandstone bedrock.

80.000 Point for the corner of sections 1, 2, 11, and 12.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, marked

T43S R21E
S2 | S1
S11 | S12
2014

Corner is located in exposed sandstone bedrock, with blackbrush.

From the corner of sections 1, 6, 7, and 12, on the east boundary of the township, hereinbefore described.

S. 89°53.9' W., between sections 1 and 12.

6.819 Centerline of U.S. Highway 191, a paved road, 33 feet wide, bears S. 34°W., N. 29°E.

40.000 Point for the 1/4 section corner of sections 1 and 12.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

T43S R21E
S1
1/4 ———
S12
2014

Set a steel fence post east of the corner.

Corner is located in sand dunes, with Mormon tea and blackbrush.

80.000 The corner of sections 1, 2, 11, and 12.

N. 0°00.2' E., between sections 1 and 2.

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

40.000 Point for the 1/4 section corner of sections 1 and 2.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, marked

T43S R21E
1/4
S2 | S1
2014

Corner is located in an area of sandy hills and exposed sandstone bedrock.

80.153 The corner of sections 1, 2, 35, and 36, on the north boundary of the township, hereinbefore described.

From the point for the corner of sections 26, 27, 34, and 35.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

T43S R21E
S27 | S26
S34 | S35
2014

Set a steel fence post southeast of the corner.

Corner is located in rolling hills, with desert vegetation.

S. 0°00.9' E., between sections 34 and 35.

40.000 Point for the 1/4 section corner of sections 34 and 35.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 23 inches in the ground, magnet at base, in a collar of stone, 1 1/2 feet base, with brass cap marked

T43S R21E
1/4
S34 | S35
2014

Set a steel fence post north of the corner.

Corner is located on a gentle south-facing slope, with blackbrush.

66.502 Centerline of an improved gravel road, 20 feet wide, bears

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

N. 55° E., S. 58° W.

- 82.925** The amended corner of sections 34 and 35 only.
- 82.955** The true point for the corner of sections 34 and 35 only, on the Utah-Arizona state boundary line, hereinbefore described.

From the corner of sections 25, 26, 35, and 36.

S. 89°59.8' W., between sections 26 and 35.

- 40.000** Point for the 1/4 section corner of sections 26 and 35.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 26 inches in the ground, magnet at base, with brass cap marked

T43S R21E
 S26
1/4
 S35
2014

Set a steel fence post east of the corner.

Corner is located on a gentle northeast-facing slope, with Mormon tea.

- 80.000** The corner of sections 26, 27, 34, and 35.

N. 0°01.3' W., between sections 26 and 27.

- 40.000** Point for the 1/4 section corner of sections 26 and 27.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

T43S R21E
 1/4
 S27 | S26
2014

Set a steel fence post north of the corner.

Corner is located in gently-rolling hills, with blackbrush.

- 80.000** Point for the corner of sections 22, 23, 26, and 27.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, magnet at base, with brass cap marked

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T43S R21E

S22	S23
S27	S26

2014

Set a steel fence post north of the corner.

Corner is located in gently-rolling terrain, with blackbrush.

From the corner of sections 23, 24, 25, and 26.

S. 89°59.8' W., between sections 23 and 26.

40.000 Point for the 1/4 section corner of sections 23 and 26.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

T43S R21E

1/4	S23
	S26

2014

Set a steel fence post northeast of the corner.

Corner is located at the base of a ridge to the west.

80.000 The corner of sections 22, 23, 26, and 27.

N. 0°01.3' W., between sections 22 and 23.

40.000 Point for the 1/4 section corner of sections 22 and 23.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, magnet at base, with brass cap marked

T43S R21E

1/4	
S22	S23

2014

Set a steel fence post north of the corner.

Corner is located in sand dunes, with Mormon tea and blackbrush.

51.716 Centerline of U.S. Highway 191, a paved road, 33 feet wide, bears S. 48° W., N. 46° E.

80.000 Point for the corner of sections 14, 15, 22, and 23.

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 23 inches in the ground, magnet at base, in a mound of stone, 2 1/2 feet base to brass cap marked

T43S	R21E
S15	S14
S22	S23

2014

Set a steel fence post north of the corner.

Corner is located northeast of a group of houses.

From the corner of sections 13, 14, 23, and 24.

S. 89°59.8' W., between sections 14 and 23.

40.000 Point for the 1/4 section corner of sections 14 and 23.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 22 inches in the ground to bedrock, magnet at base, in a mound of stone, 3 feet base, to brass cap marked

T43S	R21E
	S14
1/4	S23

2014

Set a steel fence post north of the corner.

From this point, a Right-of-Way monument, an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, bears N.31°57.8'W., 15.064 chains distance, cap marked POT 208+79.4.

From this same point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 inches diameter, set flush in top of pier, bears N.25°15.1'W., 11.677 chains distance, cap marked BIA ROADS BM 47 5062.61 1974.

From this same point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 inches diameter, set flush in top of pier, bears N.25°5.8'W., 11.627 chains distance, cap marked BIA ROADS EL 5061.98 1980.

Corner is located in an area of exposed sandstone bedrock and sandy hills.

55.243 Centerline of U.S. Highway 191, a paved road, 33 feet wide, bears S. 37°W., N. 37°E.

80.000 The corner of sections 14, 15, 22, and 23.

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0°01.3' W., between sections 14 and 15.

40.000 Point for the 1/4 section corner of sections 14 and 15.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

T43S R21E
1/4
S15 | S14
2014

Set a steel fence post north of the corner.

Corner is located in sandy hills with Mormon tea.

80.000 Point for the corner of sections 10, 11, 14, and 15.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, on sandstone bedrock, magnet at base, in a mound of stone, 3 feet base, to brass cap marked

T43S R21E
S10 | S11
S15 | S14
2014

Raise a mound of stone, 3 feet base, 2 feet high, north of the corner.

Corner is located in rolling, exposed sandstone bedrock.

From the corner of sections 11, 12, 13, and 14.

S. 89°59.8' W., between sections 11 and 14.

40.000 Point for the 1/4 section corner of sections 11 and 14.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

T43S R21E
S11
1/4 ———
S14
2014

Set a steel fence post northeast of the corner.

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located in sandy hills, with Mormon tea.

80.000 The corner of sections 10, 11, 14, and 15.

N. 0°01.3' W., between sections 10 and 11.

40.000 Point for the 1/4 section corner of sections 10 and 11.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, marked

T43S R21E
1/4
S10 | S11
2014

Raise a mound of stone, 2 feet base, 2 feet high, north of the corner.

Corner is located in gently-rolling, exposed sandstone bedrock.

80.000 Point for the corner of sections 2, 3, 10, and 11.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, marked

T43S R21E
S3 | S2
S10 | S11
2014

Raise a mound of stone, 2 feet base, 2 feet high, north of the corner.

Corner is located in exposed sandstone bedrock and sandy hills.

From the corner of sections 1, 2, 11, and 12.

S. 89°59.8' W., between sections 2 and 11.

40.000 Point for the 1/4 section corner of sections 2 and 11.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, marked

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T43S R21E
 $\frac{1}{4} \frac{S2}{S11}$
 2014

Set a steel fence post southeast of the corner.

Corner is located in exposed sandstone bedrock and sand dunes.

80.000 The corner of sections 2, 3, 10, and 11.

N. 0°02.5' E., between sections 2 and 3.

40.000 Point for the 1/4 section corner of sections 2 and 3.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 26 inches in the ground to bedrock, magnet at base, with brass cap marked

T43S R21E
 $\frac{1}{4}$
 $\frac{S3}{S2}$
 2014

Corner is located in an area of sandy hills, with Mormon tea and blackbrush.

80.119 The corner of sections 2, 3, 34, and 35, on the north boundary of the township, hereinbefore described.

From the point for the corner of sections 27, 28, 33, and 34.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 25 inches in the ground, magnet at base, with brass cap marked

T43S R21E
 $\frac{S28}{S33} \frac{S27}{S34}$
 2014

Set a steel fence post north of the corner.

Corner is located in fairly level terrain, with blackbrush.

S. 0°01.9' E., between sections 33 and 34.

40.000 Point for the 1/4 section corner of sections 33 and 34.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 22 inches in the ground to bedrock, magnet at base, in a

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

mound of stone, 3 feet base, to brass cap marked

T43S R21E
1/4
S33 | S34
2014

Set a steel fence post north of the corner.

Corner is located approximately 7 feet east of a narrow drainage, course southerly.

83.988 The corner of sections 33 and 34 only, on the Utah-Arizona state boundary line, hereinbefore described.

From the corner of sections 26, 27, 34, and 35.

S. 89°59.8' W., between sections 27 and 34.

40.000 Point for the 1/4 section corner of sections 27 and 34.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

T43S R21E
1/4 $\frac{S27}{S34}$
2014

Set a steel fence post north of the corner.

Corner is located in rolling, sandy hills.

80.000 The corner of sections 27, 28, 33, and 34.

N. 0°02.0' W., between sections 27 and 28.

40.000 Point for the 1/4 section corner of sections 27 and 28.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 29 inches in the ground, magnet at base, with brass cap marked

T43S R21E
1/4
S28 | S27
2014

Set a steel fence post north of the corner.

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

Corner is located southwest of Mexican Water Chapter House, east of paved U.S. Highway 191.

From this point, the southwesterly corner of the Mexican Water Chapter House parcel, monumented with a rebar, 5/8 inch diameter, with yellow plastic cap, bears S.10°10.5'W., 5.993 chains distance, cap marked FRANCOM LS4861.

From this same point, the southerly corner of the Mexican Water Chapter House parcel, monumented with a rebar, 5/8 inch diameter, with yellow plastic cap, bears S.32°33.5'E., 20.410 chains distance, cap marked FRANCOM LS4861.

54.193 Centerline of U.S. Highway 191, a paved road, 33 feet wide, bears S.38°W., N.38°E.

80.000 Point for the corner of sections 21, 22, 27, and 28.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

T43S	R21E
S21	S22
S28	S27

2014

Set a steel fence post north of the corner.

From this point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 inches diameter, set flush in top of pier, bears S.36°32.4'E., 14.518 chains distance, cap marked BIA ROADS EL 5099.72 1980, with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, southwest of the pier.

From this same point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 inches diameter, set flush in top of pier, bears S.39°42.5'E., 18.174 chains distance, cap marked BM 39 5107.15 1974.

Corner is located in gently-rolling hills.

From the corner of sections 22, 23, 26, and 27.

S. 89°59.8' W., between sections 22 and 27.

40.000 Point for the 1/4 section corner of sections 22 and 27.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T43S R21E
 S22
1/4 $\frac{\quad}{\quad}$
 S27
2014

Set a steel fence post north of the corner.

From this point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 inches diameter, set flush in top of pier, bears N.85°18.1'W., 14.232 chains distance, cap marked BM 40 5092.01 1974, with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, south of the pier.

Corner is located in fairly level terrain.

- 58.187** Centerline of U.S. Highway 191, a paved road, 33 feet wide, bears S. 46° W., N. 48° E.
- 80.000** The corner of sections 21, 22, 27, and 28.

N. 0°02.0' W., between sections 21 and 22.

- 40.000** Point for the 1/4 section corner of sections 21 and 22.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, magnet at base, with brass cap marked

T43S R21E
 1/4
 S21 | S22
2014

Set a steel fence post north of the corner.

- 80.000** Point for the corner of sections 15, 16, 21, and 22.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, marked

T43S R21E
 S16 | S15
 S21 | S22
2014

Corner is located in rolling, exposed sandstone bedrock.

From the corner of sections 14, 15, 22, and 23.

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

S. 89°59.8' W., between sections 15 and 22.

40.000 Point for the 1/4 section corner of sections 15 and 22.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, magnet at base, with brass cap marked

T43S R21E
 S15
1/4 ———
 S22
2014

Set a steel fence post north of the corner.

Corner is located in an area of exposed sandstone bedrock and sandy hills, with Mormon tea and blackbrush.

80.000 The corner of sections 15, 16, 21, and 22.

N. 0°02.0' W., between sections 15 and 16.

40.000 Point for the 1/4 section corner of sections 15 and 16.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, marked

T43S R21E
 1/4
 S16 | S15
2014

Raise a mound of stone, 2 feet base, 2 feet high, north of the corner.

Corner is located in an area of rolling, exposed sandstone bedrock.

80.000 Point for the corner of sections 9, 10, 15, and 16.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, marked

T43S R21E
 S9 | S10
 S16 | S15
2014

Raise a mound of stone, 3 feet base, 2 feet high, north of the

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

corner.

Corner is located in an area of rolling, exposed sandstone bedrock and sandy hills.

From the corner of sections 10, 11, 14, and 15.

S. 89°59.8' W., between sections 10 and 15.

40.001 Point for the 1/4 section corner of sections 10 and 15.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, magnet at base, with brass cap marked

T43S R21E
 S10
1/4 ———
 S15
2014

Set a steel fence post west of the corner.

Corner is located in sandy hills.

80.002 The corner of sections 9, 10, 15, and 16.

N. 0°02.0' W., between sections 9 and 10.

40.000 Point for the 1/4 section corner of sections 9 and 10.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, 4 inches below the local ground surface, marked

T43S R21E
 1/4
 S9 | S10
2014

Raise a mound of stone, 2 feet base, 2 feet high, north of the corner.

Set a steel fence post east of the corner.

Corner is located in an area of exposed sandstone bedrock and sand.

80.000 Point for the corner of sections 3, 4, 9, and 10.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, over an "+" chiseled into sandstone bedrock, magnet at

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

base, in a mound of stone, 4 feet base, to brass cap marked

T43S	R21E
S4	S3
S9	S10

2014

Corner is located in an area of rolling, exposed sandstone bedrock and sand.

From the corner of sections 2, 3, 10, and 11.

S. 89°59.8' W., between sections 3 and 10.

40.001 Point for the 1/4 section corner of sections 3 and 10.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, marked

T43S	R21E
	S3
1/4	S10

2014

Raise a mound of stone, 2 feet base, 2 feet high, north of the corner.

Corner is located in an area of rolling, exposed sandstone bedrock and sand.

80.002 The corner of sections 3, 4, 9, and 10.

N. 0°02.9' E., between sections 3 and 4.

40.000 Point for the 1/4 section corner of sections 3 and 4.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

T43S	R21E
	1/4
S4	S3

2014

Set a steel fence post north of the corner.

Corner is located in an area of sandy hills, with Mormon tea and blackbrush.

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 80.099** The corner of sections 3, 4, 33, and 34, on the north boundary of the township, hereinbefore described.

From the point for the corner of sections 28, 29, 32, and 33.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

T43S	R21E
S29	S28
S32	S33

2014

Set a steel fence post northeast of the corner.

Corner is located in gently-rolling hills, with blackbrush.

S. 0°02.9' E., between sections 32 and 33.

- 40.000** Point for the 1/4 section corner of sections 32 and 33.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 25 inches in the ground, magnet at base, in a collar of stone, 2 feet base, with brass cap marked

T43S	R21E
1/4	
S32	S33

2014

Set a steel fence post north of the corner.

Corner is located on open, fairly level ground, with blackbrush.

- 85.021** The corner of sections 32 and 33 only, on the Utah-Arizona state boundary line, hereinbefore described.

From the corner of sections 27, 28, 33, and 34.

S. 89°59.8' W., between sections 28 and 33.

- 38.135** Centerline of U.S. Highway 191, a paved road, 33 feet wide, bears N.16° E., S.10° W.

- 40.000** Point for the 1/4 section corner of sections 28 and 33.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T43S R21E
 S28
 1/4 ———
 S33
 2014

Set a steel fence post south of the corner.

From this point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 inches diameter, set flush in top of pier, bears S.0°42.5'W., 14.857 chains distance, cap marked BIA ROADS EL 5056.00, with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, south of the pier.

From this same point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 inches diameter, set flush in top of pier, bears S.13°54.9'E., 14.545 chains distance, cap marked BM 32 EL 5047.29 1974.

Corner is located between paved U.S. Highway 191 and the westerly Right-Of-Way fence.

80.000 The corner of sections 28, 29, 32, and 33.

N. 0°02.6' W., between sections 28 and 29.

20.631 Centerline of San Juan County Road 449, an improved gravel road, 20 feet wide, bears N.83°W., S.83°E.

40.000 Point for the 1/4 section corner of sections 28 and 29.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 26 inches in the ground, magnet at base, with brass cap marked

T43S R21E
 1/4
 S29 | S28
 2014

Set a steel fence post north of the corner.

Corner is located in gently-rolling hills, with blackbrush.

80.000 Point for the corner of sections 20, 21, 28, and 29.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, magnet at base, in a collar of stone, 3 feet base, with brass cap marked

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T43S R21E

S20	S21
S29	S28

2014

Set a steel fence post north of the corner.

Corner is located in gently-rolling, sandy terrain, with Mormon tea and blackbrush.

From the corner of sections 21, 22, 27, and 28.

S. 89°59.8' W., between sections 21 and 28.

40.000 Point for the 1/4 section corner of sections 21 and 28.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

T43S R21E

1/4	S21
	S28

2014

Set a steel fence post north of the corner.

Corner is located in rolling, sandy hills.

80.000 The corner of sections 20, 21, 28, and 29.

N. 0°02.6' W., between sections 20 and 21.

40.000 Point for the 1/4 section corner of sections 20 and 21.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, magnet at base, with brass cap marked

T43S R21E

1/4	
S20	S21

2014

Set a steel fence post north of the corner.

Corner is located in sandy hills.

80.000 Point for the corner of sections 16, 17, 20, and 21.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

long, 22 inches in the ground to bedrock, magnet at base, in a mound of stone, 3 feet base to brass cap marked

T43S	R21E
S17	S16
S20	S21

2014

Set a steel fence post north of the corner.

Corner is located in sandy hills overlying sandstone bedrock.

From the corner of sections 15, 16, 21, and 22.

S. 89°59.8' W., between sections 16 and 21.

40.000 Point for the 1/4 section corner of sections 16 and 21.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, marked

T43S	R21E
	S16
1/4	S21

2014

Corner is located in an area of rolling, exposed sandstone bedrock.

80.000 The corner of sections 16, 17, 20, and 21.

N. 0°02.6' W., between sections 16 and 17.

40.000 Point for the 1/4 section corner of sections 16 and 17.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, magnet at base, with brass cap marked

T43S	R21E
	1/4
S17	S16

2014

Set a steel fence post north of the corner.

Corner is located in rolling terrain.

80.000 Point for the corner of sections 8, 9, 16, and 17.

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, marked

T43S	R21E
S8	S9
S17	S16

2014

Raise a mound of stone, 2 feet base, 2 feet high, north of the corner.

From the corner of sections 9, 10, 15, and 16.

S. 89°59.8' W., between sections 9 and 16.

40.000 Point for the 1/4 section corner of sections 9 and 16.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

T43S	R21E
	S9
1/4	S16

2014

Set a steel fence post north of the corner.

Corner is located on a fairly level mesa top, with Mormon tea and blackbrush.

80.000 The corner of sections 8, 9, 16, and 17.

N. 0°02.6' W., between sections 8 and 9.

40.000 Point for the 1/4 section corner of sections 8 and 9.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 25 inches in the ground, magnet at base, with brass cap marked

T43S	R21E
	1/4
S8	S9

2014

Set a steel fence post north of the corner.

Corner is located on a small, sandy hill, surrounded by exposed sandstone bedrock.

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

80.000 Point for the corner of sections 4, 5, 8, and 9.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, marked

T43S	R21E
S5	S4
S8	S9

2014

Set a steel fence post north of the corner.

Corner is located in an area of exposed sandstone bedrock and sand.

From the corner of sections 3, 4, 9, and 10.

S. 89°59.8' W., between sections 4 and 9.

40.000 Point for the 1/4 section corner of sections 4 and 9.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, marked

T43S	R21E
	S4
1/4	S9

2014

Set a steel fence post southeast of the corner.

Corner is located in exposed sandstone bedrock sloping east.

80.000 The corner of sections 4, 5, 8, and 9.

N. 0°04.5' E., between sections 4 and 5.

40.000 Point for the 1/4 section corner of sections 4 and 5.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 23 inches in the ground, magnet at base, in a mound of stone, 3 feet base, to brass cap marked

T43S	R21E
	1/4
S5	S4

2014

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

Corner is located in an area of exposed sandstone bedrock and sand.

- 80.059** The corner of sections 4, 5, 32, and 33, on the north boundary of the township, hereinbefore described.

From the point for the corner of sections 29, 30, 31, and 32.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

T43S	R21E
S30	S29
S31	S32

2014

Set a steel fence post north of the corner.

Corner is located in sandy hills.

S. 0°02.5' E., between sections 31 and 32.

- 40.000** Point for the 1/4 section corner of sections 31 and 32.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 26 inches in the ground, magnet at base, with brass cap marked

T43S	R21E
1/4	
S31	S32

2014

Set a steel fence post north of the corner.

Corner is located on fairly level ground, with Mormon tea and blackbrush.

- 85.135** The corner of sections 31 and 32 only, on the Utah-Arizona state boundary line, hereinbefore described.

From the corner of sections 28, 29, 32, and 33.

S. 89°59.8' W., between sections 29 and 32.

- 40.000** Point for the 1/4 section corner of sections 29 and 32.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, 6 inches below the local ground surface, marked

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T43S R21E
 $\frac{1}{4}$ $\frac{S29}{S32}$
 2014

Set a steel fence post south of the corner.

Corner is located in an area of exposed sandstone bedrock and sand, with Mormon tea and blackbrush.

80.000 The corner of sections 29, 30, 31, and 32.

S. 89°59.8' W., between sections 30 and 31.

40.000 Point for the 1/4 section corner of sections 30 and 31.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, magnet at base, with brass cap marked

T43S R21E
 $\frac{1}{4}$ $\frac{S30}{S31}$
 2014

Set a steel fence post east of the corner.

Corner is located on a gentle southwest-sloping slope, with blackbrush.

79.947 The corner of sections 30 and 31 only, on the west boundary of the township, hereinbefore described.

From the corner of sections 29, 30, 31, and 32.

N. 0°03.3' W., between sections 29 and 30.

32.071 Centerline of San Juan County Road 449, an improved gravel road, 20 feet wide, bears N. 75° W., S. 75° E.

40.000 Point for the 1/4 section corner of sections 29 and 30.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, 6 inches below the local ground surface, marked

T43S R21E
 $\frac{1}{4}$
 S30 | S29
 2014

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

Set a steel fence post north of the corner in a mound of stone, 1 foot base, 1 foot high.

Corner is located in an area of exposed sandstone bedrock and sand.

80.000 Point for the corner of sections 19, 20, 29, and 30.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 14 inches in the ground to bedrock, magnet at base, in a mound of stone, 2 1/2 feet base, to brass cap marked

T43S	R21E
S19	S20
S30	S29
2014	

Set a steel fence post southwest of the corner.

Corner is located in an area of exposed sandstone bedrock and sand.

From the corner of sections 20, 21, 28, and 29.

S. 89°59.8' W., between sections 20 and 29.

40.000 Point for the 1/4 section corner of sections 20 and 29.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

T43S	R21E
	S20
1/4	S29
2014	

Set a steel fence post north of the corner.

Corner is located in sandy hills.

80.000 The corner of sections 19, 20, 29, and 30.

N. 89°58.8' W., between sections 19 and 30.

40.000 Point for the 1/4 section corner of sections 19 and 30.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, magnet at base, with brass cap marked

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T43S R21E
 S19
 1/4
 S30
 2014

Set a steel fence post north of the corner.

Corner is located in sandy hills, with Mormon tea.

- 79.841** The corner of sections 19 and 30 only, on the west boundary of the township, hereinbefore described.

From the corner of sections 19, 20, 29, and 30.

N. 0°03.3' W., between sections 19 and 20.

- 40.000** Point for the 1/4 section corner of sections 19 and 20.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, marked

T43S R21E
 1/4
 S19 | S20
 2014

Raise a mound of stone, 2 feet base, 2 feet high, north of the corner.

Corner is located in fairly level exposed sandstone bedrock.

- 80.000** Point for the corner of sections 17, 18, 19, and 20.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, marked

T43S R21E
 S18 | S17
 S19 | S20
 2014

Raise a mound of stone, 2 feet base, 2 feet high, south of the corner.

Corner is located in an area of rolling, exposed sandstone bedrock and sand.

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

From the corner of sections 16, 17, 20, and 21.

S. 89°59.8' W., between sections 17 and 20.

40.000 Point for the 1/4 section corner of sections 17 and 20.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, 5 inches below the local ground surface, marked

T43S R21E
S17
1/4
S20
2014

Set a steel fence post in a mound of stone, 2 feet base, 2 feet high, north of the corner.

Corner is located in an area of sandy hills overlying sandstone bedrock.

80.000 The corner of sections 17, 18, 19, and 20.

N. 89°58.7' W., between sections 18 and 19.

40.000 Point for the 1/4 section corner of sections 18 and 19.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, marked

T43S R21E
S18
1/4
S19
2014

Set a steel fence post east of the corner.

Corner is located in an area of exposed sandstone bedrock with sand.

79.741 The corner of sections 18 and 19 only, on the west boundary of the township, hereinbefore described.

From the corner of sections 17, 18, 19, and 20.

N. 0°03.3' W., between sections 17 and 18.

40.000 Point for the 1/4 section corner of sections 17 and 18.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

long, 26 inches in the ground to bedrock, magnet at base, with brass cap marked

T43S R21E
1/4
S18 | S17
2014

Set a steel fence post southeast of the corner.

Corner is located in an area of exposed sandstone bedrock with sand.

80.000 Point for the corner of sections 7, 8, 17, and 18.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, marked

T43S R21E
S7 | S8
S18 | S17
2014

Raise a mound of stone, 2 feet base, 2 feet high, northeast of the corner.

Corner is located in an area of exposed sandstone bedrock with sand.

From the corner of sections 8, 9, 16, and 17.

S. 89°59.8' W., between sections 8 and 17.

40.000 Point for the 1/4 section corner of sections 8 and 17.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, magnet at base, with brass cap marked

T43S R21E
S8
1/4 ———
S17
2014

Set a steel fence post north of the corner.

Corner is located in an area of exposed sandstone bedrock with sand.

80.000 The corner of sections 7, 8, 17, and 18.

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

N. 89°59.7' W., between sections 7 and 18.

40.000 Point for the 1/4 section corner of sections 7 and 18.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, marked

T43S R21E
S7
1/4 ———
S18
2014

Raise a mound of stone, 2 feet base, 2 feet high, north of the corner.

Corner is located on exposed sandstone bedrock sloping east.

79.651 The corner of sections 7 and 18 only, on the west boundary of the township, hereinbefore described.

From the corner of sections 7, 8, 17, and 18.

N. 0°03.3' W., between sections 7 and 8.

40.000 Point for the 1/4 section corner of sections 7 and 8.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, marked

T43S R21E
1/4
S7 | S8
2014

Set a steel fence post, in a mound of stone, southeast of the corner.

Corner is located in gently-rolling, exposed sandstone bedrock.

80.000 Point for the corner of sections 5, 6, 7, and 8.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, marked

T43S R21E
S6 | S5
———
S7 | S8
2014

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

Raise a mound of stone, 2 feet base, 2 feet high, north of the corner.

Corner is located in rolling, exposed sandstone bedrock.

From the corner of sections 4, 5, 8, and 9.

S. 89°59.8' W., between sections 5 and 8.

40.000 Point for the 1/4 section corner of sections 5 and 8.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, marked

T43S R21E
 S5
1/4
 S8
2014

Raise a mound of stone, 2 feet base, 2 feet high, north of the corner.

Corner is located in rolling, exposed sandstone bedrock.

80.000 The corner of sections 5, 6, 7, and 8.

N. 89°59.6' W., between sections 6 and 7.

40.000 Point for the 1/4 section corner of sections 6 and 7.

Set a stainless steel post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, magnet at base, with brass cap marked

T43S R21E
 S6
1/4
 S7
2014

Set a steel fence post north of the corner.

Corner is located in a small area of sand surrounded by exposed sandstone bedrock.

79.559 The corner of sections 6 and 7 only, on the west boundary of the township, hereinbefore described.

From the corner of sections 5, 6, 7, and 8.

N. 0°03.9' E., between sections 5 and 6.

THE SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH
CHAINS

40.000 Point for the 1/4 section corner of sections 5 and 6.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inches stem, flush with sandstone, in epoxy bond, into a drill hole on solid rock, magnet at base, marked

T43S R21E
1/4
S6 | S5
2014

Raise a mound of stone, 2 feet base, 2 feet high, north of the corner.

Corner is located in an area of rolling, exposed sandstone bedrock.

80.044 The corner of sections 5, 6, 31, and 32, on the north boundary of the township, hereinbefore described.

The Subdivision of Section 1,
T. 43 S., R. 21 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 1 and 12.

N. 0°01.4 W., on the north-south centerline of section 1.

40.015 Point for the center 1/4 section corner of section 1, at intersection with the east-west centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked

T43S R21E
C 1/4 S1
2014

Set a steel fence post north of the corner.

Corner is located in sandy hills.

80.144 The 1/4 section corner of sections 1 and 36, on the north boundary of the township, hereinbefore described.

From the 1/4 section corner of sections 1 and 6, on the east boundary of the township, hereinbefore described.

S. 89°52.7' W., on the east-west centerline of section 1.

40.005 The center 1/4 section corner of section 1.

THE SUBDIVISION OF SECTION 1,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

79.982 The 1/4 section corner of sections 1 and 2.

The Subdivision of Section 12,
T. 43 S., R. 21 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 12 and 13.

N. 0°00.4 W., on the north-south centerline of section 12.

40.002 Point for the center 1/4 section corner of section 12, at intersection with the east-west centerline, falls in U.S. Highway 191, a paved road, 33 feet wide, bearing N. 41° E., S. 41° W.

Set a magnetic nail flush with the pavement.

From which

A stainless steel post, 2 1/2 inches diameter, set 28 inches in the ground, with magnet at base, for a reference monument, bears S.85°52.1'E., 235.7 links distance, with a brass cap marked RM T43S R21E S12 2014, 155.6 FT. TO COR. with an arrow pointing toward the corner, in a collar of stone, 2 feet diameter. Set a steel fence post to the northwest. Monument is located in the easterly Right-Of-Way fenceline, a 4-strand barbed-wire fence, extending N. 40° E., S. 40° W.

A stainless steel post, 2 1/2 inches diameter, set 27 inches in the ground, with magnet at base, for a reference monument, bears S.7°00.5'E., 254.9 links distance, with a brass cap marked RM T43S R21E S12 2014, 168.3 FT. TO COR., with an arrow pointing toward the corner, in a collar of stone, 2 feet diameter. Set a steel fence post to the northwest. Monument is located in the easterly Right-Of-Way fenceline, a 4-strand barbed-wire fence, extending N. 40° E., S. 40° W.

From this point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 inches diameter, set flush in top of pier, bears N.29°51.2'E., 9.674 chains distance, cap marked BIA ROADS 19—, with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, west of the pier.

From this same point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 inches diameter, set flush in top of pier, bears N.52°17.6'E., 9.704 chains distance, cap marked BIA ROADS BM 57 4885.65 1974, with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, west of the pier.

80.008 The 1/4 section corner of sections 1 and 12.

THE SUBDIVISION OF SECTION 12,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 7 and 12, on the east boundary of the township, hereinbefore described.

S. 89°54.4' W., on the east-west centerline of section 12.

39.999 The center 1/4 section corner of section 12.

80.000 The 1/4 section corner of sections 11 and 12.

Subdivision of Section 13,
T. 43 S., R. 21 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 13 and 24.

N. 0°00.2 W., on the north-south centerline of section 13.

40.010 Point for the center 1/4 section corner of section 13, at intersection with the east-west centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked

T43S R21E

C 1/4 S13

2014

Set a steel fence post north of the corner.

Corner is located in fairly level terrain, with Mormon tea and blackbrush.

80.023 The 1/4 section corner of sections 12 and 13.

From the 1/4 section corner of sections 13 and 18, on the east boundary of the township, hereinbefore described.

S. 89°55.7' W., on the east-west centerline of section 13.

40.002 The center 1/4 section corner of section 13.

80.003 The 1/4 section corner of sections 13 and 14.

The Subdivision of Section 14,
T. 43 S., R. 21 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 14 and 23.

N. 0°01.0 W., on the north-south centerline of section 14.

20.196 Centerline of U.S. Highway 191, a paved road, 33 feet wide, bears

THE SUBDIVISION OF SECTION 14,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

N. 37° E., S. 37° W.

- 40.000 Point for the center 1/4 section corner of section 14, at intersection with the east-west centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked

T43S R21E

C 1/4 S14

2014

Set a steel fence post north of the corner.

From this point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 inches diameter, set flush in top of pier, bears S.82°20.2'E., 11.516 chains distance, cap marked BIA ROADS EL 5031.95, with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, west of the pier.

From this same point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 inches diameter, set flush in top of pier, bears S.75°11.6'E., 14.929 chains distance, cap marked BIA ROADS EL 5038.16 1980, with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, west of the pier.

Corner is located in rolling terrain.

- 80.000 The 1/4 section corner of sections 11 and 14.
-

From the 1/4 section corner of sections 13 and 14.

S. 89°59.8' W., on the east-west centerline of section 14.

- 25.059 Centerline of U.S. Highway 191, a paved road, 33 feet wide, bears N. 37° E., S. 37° W.

- 40.000 The center 1/4 section corner of section 14.

- 80.000 The 1/4 section corner of sections 14 and 15.
-

The Subdivision of Section 22,
T. 43 S., R. 21 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 22 and 27.

N. 0°01.6 W., on the north-south centerline of section 22.

- 16.208 Centerline of U.S. Highway 191, a paved road, 33 feet wide, bears N. 48° E., S. 48° W.

THE SUBDIVISION OF SECTION 22,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

40.000 Point for the center 1/4 section corner of section 22, at intersection with the east-west centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked

T43S R21E

C 1/4 S22

2014

Set a steel fence post north of the corner.

Corner is located in sandy hills.

80.000 The 1/4 section corner of sections 15 and 22.

From the 1/4 section corner of sections 22 and 23.

S. 89°59.8' W., on the east-west centerline of section 22.

13.137 Centerline of U.S. Highway 191, a paved road, 33 feet wide, bears N. 49° E., S. 49° W.

40.000 The center 1/4 section corner of section 22.

80.000 The 1/4 section corner of sections 21 and 22.

The Subdivision of Section 23,
T. 43 S., R. 21 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 23 and 26.

N. 0°01.0 W., on the north-south centerline of section 23.

40.000 Point for the center 1/4 section corner of section 23, at intersection with the east-west centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with brass cap marked

T43S R21E

C 1/4 S23

2014

Set a steel fence post north of the corner.

Corner is located in sand dunes, with Mormon tea and blackbrush.

80.000 The 1/4 section corner of sections 14 and 23.

THE SUBDIVISION OF SECTION 23,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 23 and 24.

S. 89°59.8' W., on the east-west centerline of section 23.

40.000 The center 1/4 section corner of section 23.

80.000 The 1/4 section corner of sections 22 and 23.

The Subdivision of Section 27,
T. 43 S., R. 21 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 27 and 34.

N. 0°01.6 W., on the north-south centerline of section 27.

40.000 Point for the center 1/4 section corner of section 27, at intersection with the east-west centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with brass cap marked

T43S R21E

C 1/4 S27

2014

Set a steel fence post north of the corner.

Corner is located in gentle, rolling hills, with Mormon tea and blackbrush.

From this point, the northeasterly corner of the Mexican Water Chapter House parcel, monumented with a rebar, 5/8 inch diameter, with yellow plastic cap, bears N.59°26.0'W., 9.616 chains distance, cap marked FRANCOM LS4861.

From this same point, the northerly corner of the Mexican Water Chapter House parcel, monumented with a rebar, 5/8 inch diameter, with yellow plastic cap, bears N.51°26.8'W., 25.983 chains distance, cap marked FRANCOM LS4861.

From this same point, the southerly corner of the Mexican Water Chapter House parcel, monumented with a rebar, 5/8 inch diameter, with yellow plastic cap, bears S.59°20.1'W., 33.734 chains distance, cap marked FRANCOM LS4861.

80.000 The 1/4 section corner of sections 22 and 27.

From the 1/4 section corner of sections 26 and 27.

S. 89°59.8' W., on the east-west centerline of section 27.

40.000 The center 1/4 section corner of section 27.

80.000 The 1/4 section corner of sections 27 and 28.

THE SUBDIVISION OF SECTION 28,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 28,
T. 43 S., R. 21 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 28 and 33.

N. 0°02.3' W., on the north-south line centerline of section 28.

15.655 Centerline of San Juan County Road 449, an improved gravel road, 20 feet wide, bears N.82°W., S.82°E.

40.000 Point for the center 1/4 section corner of section 28, at the intersection with the east-west centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with brass cap marked

T43S R21E

C 1/4 S28

2014

Set a steel fencepost north of the corner.

From this point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 inches diameter, set flush in top of pier, bears S.78°32.5'E., 23.338 chains distance, cap marked EL 5100.37 1980, with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, south of the pier.

From this same point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 inches diameter, set flush in top of pier, bears S.78°32.5'E., 23.338 chains distance, cap marked BM 36 EL 5104.53 1974, with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, south of the pier.

80.000 The 1/4 section corner of sections 21 and 28.

From the 1/4 section corner of sections 27 and 28.

S. 89°59.8' W., on the east-west centerline of section 28.

11.108 Centerline of U.S. Highway 191, a paved road, 33 feet wide, bears N.38°E., S.38°W.

40.000 The center 1/4 section corner of section 28.

80.000 The 1/4 section corner of sections 28 And 29.

THE SUBDIVISION OF SECTION 33,
TOWNSHIP 43 SOUTH, RANGE 21 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 33,
T. 43 S., R. 21 E., Salt Lake Meridian, Utah

From the 1/4 section corner of section 33 only, on the Utah-Arizona state boundary line, hereinbefore described.

N. 0°02.1 W., on the north-south centerline of section 33.

- 44.504** Point for the center 1/4 section corner of section 33, at intersection with the east-west centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 23 inches in the ground, magnet at base, in a mound of stone, 2 1/2 feet base, to brass cap marked

T43S R21E

C 1/4 S33

2014

Set a steel fence post north of the corner.

From this point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 inches diameter, set flush in top of pier, bears S.42°51.8'E., 9.051 chains distance, cap marked BIA ROADS EL 5002.08 1980, with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, south of the pier.

From this same point, a Right-of-Way monument, a cement pier, 6 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 inches diameter, set flush in top of pier, bears S.59°3.9'E., 11.469 chains distance, cap marked BM 30 5003.02 1974, with an angle iron 4x4 inches, firmly set, projecting 24 inches above the ground, south of the pier.

Corner is located on fairly level, barren ground, west of paved U.S. Highway 191.

- 84.504** The 1/4 section corner of sections 28 and 33.

From the 1/4 section corner of sections 33 and 34.

S. 89°59.8' W., on the east-west centerline of section 33.

- 33.247** Centerline of U.S. Highway 191, a paved road, 33 feet wide, bears N.11°W., S.11°E.

- 40.002** The center 1/4 section corner of section 33.

- 79.997** The 1/4 section corner of sections 32 and 33.
-

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Phil Freiberg	Survey Technician

CERTIFICATE OF SURVEY

I, *Scott A. Burkhardt, Cadastral Surveyor*, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing the date of the *23rd day of May, 2014*, I have retraced a portion of the *Utah-Arizona state boundary line, from Mile Post 243 to Mile Post 250 (south boundary)*; dependently resurveyed the *east, west, and north boundaries*; and surveyed the *subdivisional lines, and subdivided sections 1, 12, 13, 14, 22, 23, 27, 28, and 33, in Township 43 South, Range 21 East, of the Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 8, 2015
Date

Scott A. Burkhardt
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *retracement of a portion of the Utah-Arizona state boundary line, from Mile Post 243 to Mile Post 250 (south boundary)*; the dependent resurvey the *east, west, and north boundaries*; and the survey of the *subdivisional lines, and the subdivision of sections 1, 12, 13, 14, 22, 23, 27, 28, and 33; in Township 43 South, Range 21 East, Salt Lake Meridian, Utah*, executed by *Scott A. Burkhardt, Cadastral Surveyor*, having been critically examined and found correct, are hereby approved.

September 24, 2015
Date

Daniel W. Webb
Chief Cadastral Surveyor for Utah